PrefixSpan: Sequential Pattern Mining by Pattern-Growth

PrefixSpan: A Pattern-Growth Approach

SID	Sequence
10	<a(abc)(ac)d(cf)>
20	<(ad)c(bc)(ae)>
30	<(ef)(ab)(df)cb>
40	<eg(af)cbc>

Prefix	Suffix (Projection)
<a>	<(abc)(ac)d(cf)>
<aa>	<(_bc)(ac)d(cf)>
<ab>	<(_c)(ac)d(cf)>

- Prefix and suffix
  - Given <a(abc)(ac)d(cf)>
  - Prefixes: <a>, <aa>, <a(ab)>, <a(abc)>, …
  - Suffix: Prefixes-based projection

- PrefixSpan Mining: Prefix Projections
  - Step 1: Find length-1 sequential patterns
    - <a>, <b>, <c>, <d>, <e>, <f>
  - Step 2: Divide search space and mine each projected DB
    - <a>-projected DB,
    - <b>-projected DB,
    - …
    - <f>-projected DB, …

PrefixSpan (Prefix-projected Sequential pattern mining) Pei, et al. @TKDE'04

PrefixSpan: Mining Prefix-Projected DBs

SID	Sequence
10	<a(abc)(ac)d(cf)>
20	<(ad)c(bc)(ae)>
30	<(ef)(ab)(df)cb>
40	<eg(af)cbc>

只去选<a>后面的内容.

Length-1 sequential patterns
<a>, <b>, <c>, <d>, <e>, <f>

prefix <a>

<a>-projected DB

<(abc)(ac)d(cf)>

<(_d)c(bc)(ae)>

<(_b)(df)cb>

<(_f)cbc>

Length-2 sequential patterns
<aa>, <ab>, <(ab)>,
<ac>, <ad>, <af>

prefix <b>

<b>-projected DB

... ...

prefix <c>, ..., <f>

...

prefix <aa>

<aa>-projected DB

..

prefix <af>

<af>-projected DB

Major strength of PrefixSpan:

- No candidate subseqs. to be generated
- Projected DBs keep shrinking

Implementation Consideration: Pseudo-Projection vs. Physical Projection

- Major cost of PrefixSpan: Constructing projected DBs
  - Suffixes largely repeating in recursive projected DBs
- When DB can be held in main memory, use pseudo projection
  - No physically copying suffixes
  - Pointer to the sequence
  - Offset of the suffix
- But if it does not fit in memory
  - Physical projection
- Suggested approach:
  - Integration of physical and pseudo-projection
  - Swapping to pseudo-projection when the data fits in memory