

# The Sidelnikov-Shestakov's Attack applied to the Chor-Rivest Cryptosystem

Sylvain Colin & Gaspard Férey

March 18, 2014

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Our Work . . . . .	1
<b>2</b>	<b>Preliminaries</b>	<b>2</b>
2.1	A cryptosystem based on Reed-Solomon codes . . . . .	2
2.1.1	Key generation . . . . .	2
2.1.2	Encryption and Decryption . . . . .	2
2.2	Equivalence between Reed-Solomon codes . . . . .	3
<b>3</b>	<b>The Sidelnikov-Shestakov Attack</b>	<b>4</b>
3.1	A first important remark . . . . .	4
3.2	Computation of the $\alpha_i$ . . . . .	4
3.3	Computation of the $z_i$ . . . . .	5
3.4	Some remarks about the attack . . . . .	5
<b>4</b>	<b>Application to the Chor-Rivest Cryptosystem</b>	<b>6</b>
4.1	Notations . . . . .	6
4.2	The Chor-Rivest Cryptosystem . . . . .	6
4.2.1	Link with Reed-Solomon codes . . . . .	7
4.3	A First Attack using Reed-Solomon codes . . . . .	8
4.3.1	Small powers of $g$ . . . . .	8
4.3.2	Wider set of acceptable generators . . . . .	9
<b>5</b>	<b>Vaudenay attack</b>	<b>10</b>
5.1	Generating more rows... . . . .	10
<b>6</b>	<b>Simulations and expected complexity</b>	<b>11</b>
6.1	First examples . . . . .	11
6.2	Number of linearly independent polynomials . . . . .	11
6.3	Postulate . . . . .	12
6.4	Optimum choice for $r$ . . . . .	12
<b>7</b>	<b>Conclusions</b>	<b>13</b>
<b>A</b>	<b>Simulation examples</b>	<b>14</b>
A.1	Example 1 . . . . .	14
A.2	Example 2 . . . . .	15
<b>B</b>	<b>Simulation results</b>	<b>16</b>

## **Abstract**

In this article, we discuss about the Sidelnikov-Shestakov attack on cryptosystems based on Reed-Solomon codes. Then we describe how this algorithm can be used to improve the attack to the Chor-Rivest Cryptosystem proposed by Vaudenay [\[4\]](#).

# 1 Introduction

Niederreiter and McEliece cryptosystem [2] was one of the first to use randomization in the encryption process. Indeed, in such a scheme, the encrypter uses a random error to prevent attacks on the codeword. This codeword is then decrypted using an error-correcting Reed-Solomon code. This algorithm has never gained much acceptance in the cryptographic community, but is a candidate for "post-quantum cryptography".

In 1992, Sidelnikov and Shestakov suggest an attack [3] on the public key of this cryptosystem using equivalences between private keys.

The Chor-Rivest cryptosystem [1] is a public key knapsack system which has been broken. However, it took longer to break than most, and is a very elegant use of finite fields.

The first efficient attack for the proposed parameters (i.e.,  $p \simeq 200$ ,  $h \simeq 24$ ) has been obtained by Vaudenay in 2001, assuming  $h$  has a small factor.

## 1.1 Our Work

In this article, we first describe the Niederreiter and McEliece cryptosystem and present the original Sidelnikov and Shestakov's attack. We use here the echelon form of the public key as suggested by Wieschebrink [5]. This gives an easy algorithm to attack such a scheme.

On a second part, we focus on the Chor-Rivest cryptosystem and show some similarities between the "known  $g_{p^r}$  attack" introduced by Vaudenay and the Sidelnikov-Shestakov attack. This allows us to describe an algorithm for a "known  $g_{p^r}$  attack" which doesn't require  $r$  to be as big as in Vaudenay's article. In particular the term  $p^{\sqrt{h}}$  in Vaudenay's complexity corresponding to an exhaustive research can be reduced to  $p^{\log p}$  assuming we have  $h \simeq \frac{p}{\log p}$  as suggested in Chor and Rivest's article and  $h$  has very small factors (around  $\log p$ ). That last point should be verified since the scheme can only be used efficiently when  $h$  has a lot of divisors in order to be able to compute discrete logarithms for the public key.

## 2 Preliminaries

### 2.1 A cryptosystem based on Reed-Solomon codes

#### 2.1.1 Key generation

We study here the public-key cryptosystem introduced first by Niederreiter and McEliece [2] and based on generalized Reed-Solomon codes.

Let  $\mathbb{F}_q$  be a finite field with  $q = p^h$  elements and  $\mathbb{F} = \mathbb{F}_q \cup \{\infty\}$ , where  $\infty$  has usual properties ( $1/\infty = 0$ , etc). We call  $G$  the following matrix:

$$G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n) := \begin{pmatrix} z_1 \alpha_1^0 & z_2 \alpha_2^0 & \cdots & z_n \alpha_n^0 \\ z_1 \alpha_1^1 & z_2 \alpha_2^1 & \cdots & z_n \alpha_n^1 \\ \vdots & \vdots & \ddots & \vdots \\ z_1 \alpha_1^{k-1} & z_2 \alpha_2^{k-1} & \cdots & z_n \alpha_n^{k-1} \end{pmatrix} \in \mathcal{M}_{\mathbb{F}}(k, n)$$

where  $\alpha_i \in \mathbb{F}$  and  $z_i \in \mathbb{F}_q \setminus \{0\}$  for all  $i \in \{1, \dots, n\}$ . As in the article of Sidelnikov and Shestakov [3], if  $\alpha_i = \infty$ , the  $i$ -th column is defined by the vector  $z_i(0, \dots, 0, 1)^T$  since the coefficient  $\alpha_i^{k-1}$  dominates all the other coefficients  $\alpha_i^j$  for  $j < k-1$ . So, we concretely manipulate finite coefficients. The codes generated by such matrices are called Generalized Reed-Solomon (GRS) codes.

The cryptosystem is also based on a random nonsingular matrix  $H$  of size  $k \times k$  with coefficients in  $\mathbb{F}_q$ . Finally, we call  $M$  the matrix of size  $k \times n$  defined by  $M = H \cdot G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n)$ . It is clear that  $M$  has the following general form :

$$M := \begin{pmatrix} z_1 f_1(\alpha_1) & z_2 f_1(\alpha_2) & \cdots & z_n f_1(\alpha_n) \\ z_1 f_2(\alpha_1) & z_2 f_2(\alpha_2) & \cdots & z_n f_2(\alpha_n) \\ \vdots & \vdots & \ddots & \vdots \\ z_1 f_k(\alpha_1) & z_2 f_k(\alpha_2) & \cdots & z_n f_k(\alpha_n) \end{pmatrix}$$

where  $f_i$  is a polynomial of degree at most  $k-1$ . We can notice that, if  $\alpha_i = \infty$ ,  $f_j(\alpha_i)$  is equal to the dominant coefficient of the polynomial  $f_j$  for all  $1 \leq j \leq k$  because the last coefficient of the  $i$ -th column of  $G$  is equal to  $z_i$  and the others are equal to 0.

In the considered cryptosystem, the secret key consists of the set  $\{\alpha_1, \dots, \alpha_n\}$ , the set  $\{z_1, \dots, z_n\}$  and the random matrix  $H$ .

The public key is given by the representation of the field  $\mathbb{F}_q$  (ie. the polynomial used to define  $\mathbb{F}_q$  over  $\mathbb{F}_p$ ), the matrix  $M$  and the integer  $t = \lfloor \frac{n-k}{2} \rfloor$ .

#### 2.1.2 Encryption and Decryption

The codewords are then the vectors  $c = b \cdot M$  where  $b \in \mathbb{F}_q^k$ . So, the different codewords have necessarily the following form :

$$c = (z_i f_c(\alpha_i))_{1 \leq i \leq n}$$

where  $f_c$  is a polynomial whose degree is at most  $k-1$ . Once again, we can notice that, if  $\alpha_i = \infty$ ,  $f_c(\alpha_i)$  is equal to the dominant coefficient of the polynomial  $f_c$ .

Thus, given a message to send, which is actually a vector  $b$  of  $\mathbb{F}_q^k$ , one will have to transmit the vector  $b \cdot M + e$  where  $e$  is a random vector of  $\mathbb{F}_q^n$  with Hamming weight at most  $t = \lfloor \frac{n-k}{2} \rfloor$ . Since a GRS code correct  $\lfloor \frac{n-k}{2} \rfloor$  errors, this property remains true for  $M$ . Indeed,  $b \cdot M$  remains a codeword of the GRS code, since it is the codeword obtained applying the GRS code to  $b \cdot H$ . So, in order to decrypt the message, we first compute  $b' = b \cdot H$ , finding the closest codeword from the

received message, using for example the Berlekamp-Welch algorithm. Then, we compute  $b' \cdot H^{-1}$  to get the original message.

However, the original message can not be easily recovered when not knowing the GRS code used in the secret key.

## 2.2 Equivalence between Reed-Solomon codes

Sidelnikov and Shestakov show [3] that for all  $a \in \mathbb{F}_q \setminus \{0\}$  and  $b \in \mathbb{F}_q$ , there exists  $H_1, H_2, H_3 \in \mathcal{M}_{\mathbb{F}_q}(k, k)$  nonsingular,  $(c_1, \dots, c_n) \in \mathbb{F}_q \setminus \{0\}^n$  and  $(d_1, \dots, d_n) \in \mathbb{F}_q \setminus \{0\}^n$  such that:

$$H_1 \cdot G(a \cdot \alpha_1 + b, \dots, a \cdot \alpha_n + b, c_1 z_1, \dots, c_n z_n) = G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n) \quad (1) \quad \text{eq1}$$

$$H_2 \cdot G\left(\frac{1}{\alpha_1}, \dots, \frac{1}{\alpha_n}, d_1 z_1, \dots, d_n z_n\right) = G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n) \quad (2) \quad \text{eq2}$$

$$H_3 \cdot G(\alpha_1, \dots, \alpha_n, a \cdot z_1, \dots, a \cdot z_n) = G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n) \quad (3) \quad \text{eq3}$$

This means that for any cryptosystem  $M = H \cdot G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n)$ , for any birational transformation

$$\phi : x \mapsto \frac{ax + b}{cx + d}$$

there exist a nonsingular matrix  $H_\phi$  and a vector  $(z'_1, \dots, z'_n) \in \mathbb{F}_q \setminus \{0\}^n$  such that:

$$M = H_\phi \cdot G(\phi(\alpha_1), \dots, \phi(\alpha_n), z'_1, \dots, z'_n)$$

By using the unique transformation  $\phi$  that maps  $(\alpha_1, \alpha_2, \alpha_3)$  to  $(0, 1, \infty)$ , we get that, for any cryptosystem  $M = H \cdot G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n)$ ,  $M$  can be uniquely written

$$M = H' \cdot G(0, 1, \alpha'_3, \dots, \alpha'_k, \infty, \alpha'_{k+2}, \dots, \alpha'_n, z'_1, \dots, z'_n)$$

with  $H'$  nonsingular,  $z'_i \neq 0$  and  $\alpha_i$  distinct elements of  $\mathbb{F}_q \setminus \{0, 1, \infty\}$ . So, we can assume that  $\alpha_1 = 0$ ,  $\alpha_2 = 1$  and  $\alpha_{k+1} = \infty$ .

So, when  $M$  is given, it is impossible to compute the original matrices  $G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n)$  and  $H$  since many pairs of such matrices lead to the same public matrix  $M$ . However, computing an equivalent pair is sufficient since it will allow to decrypt the messages as well as the original secret pair of matrices.

So, the attack will consist of finding  $H$  and  $G(0, 1, \alpha'_3, \dots, \alpha'_k, \infty, \alpha'_{k+2}, \dots, \alpha'_n, z'_1, \dots, z'_n)$ , equivalent to the original pair. Considering  $a = z'^{-1}_{k+1}$  in equation (3), we can also assume that  $z'_{k+1} = 1$ .

### 3 The Sidelnikov-Shestakov Attack

#### 3.1 A first important remark

As described in the previous section, we assume that we have:

$$M = H \cdot G(0, 1, \alpha_3, \dots, \alpha_k, \infty, \alpha_{k+2}, \dots, \alpha_n, z_1, \dots, z_k, 1, z_{k+2}, \dots, z_n)$$

First, we compute the echelon form of  $M$ :

$$E(M) = \begin{pmatrix} 1 & 0 & \cdots & 0 & b_{1,k+1} & \cdots & b_{1,n} \\ 0 & 1 & \cdots & 0 & b_{2,k+1} & \cdots & b_{2,n} \\ & & \ddots & & \vdots & & \vdots \\ 0 & \cdots & 0 & 1 & b_{k,k+1} & \cdots & b_{k,n} \end{pmatrix}$$

Since the echelon form can be computed only with left multiplication of the matrix  $M$ , the  $k$  lines of  $E(M)$  are codewords. As a consequence, if we call  $f_{b_i}$  the polynomial associated to the  $i$ -th row, we have :

- $\forall 1 \leq i \leq k, f_{b_i}(\alpha_i) = 1$
- $\forall 1 \leq i \neq j \leq k, f_{b_i}(\alpha_j) = 0$
- $\forall 1 \leq i \leq k, \forall k+1 \leq j \leq n, f_{b_i}(\alpha_j) = b_{i,j}$

So, since all the  $\alpha_i$  are different, the polynomial  $f_{b_i}$  has  $k-1$  simple roots. Since its degree is at most  $k-1$ , we know all its roots. As a consequence,  $b_{i,j} \neq 0$  for all  $1 \leq i \leq k$  and  $k+1 \leq j \leq n$ . Moreover, we know the general form of the polynomial  $f_i$  :

$$f_{b_i}(X) = c_{b_i} \cdot \prod_{1 \leq j \leq k, i \neq j} (X - \alpha_j) \quad (4) \quad \boxed{\text{eq4}}$$

where  $c_{b_i} \in \mathbb{F}_q \setminus \{0\}$ .

Since  $\alpha_{k+1} = \infty$ , we have  $z_{k+1} \cdot f_{b_i}(\alpha_{k+1}) = b_{i,k+1} = c_{b_i} \cdot z_{k+1} = c_{b_i}$ . So, we know the coefficients  $c_{b_i}$  for all the rows of the matrix  $E(M)$ .

#### 3.2 Computation of the $\alpha_i$

Consider now the first and second rows. Using the fact that, for all  $k+2 \leq i \leq n$ ,  $b_{1,j} \neq 0$  and  $b_{2,j} \neq 0$ , and the form of the polynomials  $f_{b_i}$  given in equation (4), the following holds:

$$\frac{b_{1,j}}{b_{2,j}} = \frac{z_j \cdot f_{b_1}(\alpha_j)}{z_j \cdot f_{b_2}(\alpha_j)} = \frac{c_{b_1} \cdot (\alpha_j - \alpha_2)}{c_{b_2} \cdot (\alpha_j - \alpha_1)} = \frac{c_{b_1} \cdot (\alpha_j - 1)}{c_{b_2} \cdot \alpha_j} \quad (5) \quad \boxed{\text{eq5}}$$

So, we have that:

$$\forall k+2 \leq j \leq n, \alpha_j = \frac{b_{2,j} \cdot c_{b_1}}{b_{2,j} \cdot c_{b_1} - b_{1,j} \cdot c_{b_2}} \quad (6) \quad \boxed{\text{eq6}}$$

Consider now the same equation as in equation (5), replacing the second row by the  $i$ -th row where  $3 \leq i \leq k$ . We obtain:

$$\frac{b_{1,j}}{b_{i,j}} = \frac{z_j \cdot f_{b_1}(\alpha_j)}{z_j \cdot f_{b_i}(\alpha_j)} = \frac{c_{b_1} \cdot (\alpha_j - \alpha_i)}{c_{b_i} \cdot (\alpha_j - \alpha_1)} = \frac{c_{b_1} \cdot (\alpha_j - 1)}{c_{b_2} \cdot (\alpha_j - \alpha_i)} \quad (7) \quad \boxed{\text{eq7}}$$

Then, we get, considering for instance  $j = k+2$ :

$$\forall 3 \leq i \leq k, \alpha_i = \alpha_j - \frac{b_{i,k+2}}{b_{1,k+2}} \cdot \frac{c_{b_1}}{c_{b_2}} \cdot (\alpha_{k+2} - 1) \quad (8) \quad \boxed{\text{eq8}}$$

So, we now know the set  $\{\alpha_1, \dots, \alpha_n\}$ .

### 3.3 Computation of the $z_i$

First, note that, since we know  $\alpha_1, \dots, \alpha_n$  and  $c_{b_1}, \dots, c_{b_k}$ , we can completely compute the polynomials  $f_{b_1}, \dots, f_{b_k}$ . Consider now, for all  $1 \leq i \leq k$  and  $1 \leq j \leq n$ , that  $b_{i,j} = z_j \cdot f_{b_i}(\alpha_j)$ . Then, considering  $k+2 \leq j \leq n$ , we get that:

$$\forall k+2 \leq i \leq n, z_j = \frac{b_{i,j}}{f_{b_i}(\alpha_j)} \quad (9) \quad \boxed{\text{eq9}}$$

If we now take  $i = j$  and  $1 \leq i \leq k$ , we get that:

$$\forall 1 \leq i \leq k, z_i = \frac{1}{f_{b_i}(\alpha_i)} \quad (10) \quad \boxed{\text{eq10}}$$

So, we can easily compute the set  $\{z_1, \dots, z_n\}$  and then the matrix  $G(\alpha_1, \dots, \alpha_n, z_1, \dots, z_n)$ . Finally, we can also get the nonsingular matrix  $H$  by computing  $H = M' \cdot G'^{-1}$  where  $G'$  is the matrix formed by the  $k$  first columns of  $G$  and  $M'$  the matrix formed by the  $k$  first columns of  $M$ .

### 3.4 Some remarks about the attack



## 4 Application to the Chor-Rivest Cryptosystem

### 4.1 Notations

From now on,  $p$  is a power of a prime and  $q := p^h$  with  $h$  integer. We call  $\mathbb{F}_n := \text{GF}(n)$  the finite field of order  $n$ . We often refer in this article to  $\mathbb{F}_p$  and  $\mathbb{F}_{p^r}$  (with  $r$  a divisor of  $h$ ) both sub-fields of  $\mathbb{F}_q$ . The elements of  $\mathbb{F}_p$  are  $\{\alpha_0, \dots, \alpha_{p-1}\}$ .

When  $n \in \mathbb{N}$ , we define the weight of  $n$  in base  $p$  as follow

$$w_p : u = \sum_{i=0}^d u_i p^i \mapsto \sum_{i=0}^d u_i \quad \text{where } 0 \leq u_i \leq p-1$$

### 4.2 The Chor-Rivest Cryptosystem

The Chor-Rivest cryptosystem is a public key knapsack scheme using the

The description of the field  $\mathbb{F}_q$  is public. The secret key consist of

- an element  $t \in \mathbb{F}_q$  with algebraic degree  $h$ .
- a generator  $g$  of  $\mathbb{F}_q^*$ .
- an integer  $0 \leq d < q$ .
- a permutation  $\pi$  of  $\{0, \dots, p-1\}$ .

Public keys consist of all

$$c_i := d + \log_g(t + \alpha_{\pi(i)}) \mod q-1$$

To be encrypted, a message should first be encoded into a bitstring  $m = [m_0 \dots m_{p-1}]$  of length  $p$  and weight  $h : \sum_i m_i = h$ . The ciphertext is

$$E(M) := \sum_{i=0}^{p-1} m_i c_i \mod q-1$$

To decipher this message, we compute

$$g^{E(M)-hd} = \prod_i (t + \alpha_{\pi(i)})^{m_i}$$

whose factorization leads to the message  $m$ .

To be able to compute efficiently the discrete logarithm,  $h$  should have a lot of small factors. Besides the density  $d := p/\log_2 q$  which characterize subset-sum problems should stay close to 1, otherwise the problem could be attacked using lattice reduction algorithms. This allow us to suppose that

$$h = \Theta\left(\frac{p}{\log_2 p}\right)$$

### 4.2.1 Link with Reed-Solomon codes

Trying to attack this cryptosystem show some relations between this problem and the previous one studied in section [2](#). <sup>sec:Prel</sup>In particular we have the following theorem.

**Theorem 1.** *Let  $2 \leq k \leq p-2$ . Suppose there exists  $(Q_i)_{0 \leq i \leq k-1}$   $k$  polynomials of  $\mathbb{F}_p[X]$  linearly independent with degree smaller than  $k-1$ . Suppose the evaluations  $m_{i,j} := Q_i(\alpha_{\pi(j)})$  is known for all  $i$  and  $j$ . Then the permutation  $\pi$  can be recovered in polynomial time using a Sidelnikov-Shestakov attack on the matrix  $M = (m_{i,j})_{i,j} \in \mathcal{M}_{k,p}(\mathbb{F}_p)$ .*

*Proof.* We suppose here that one of the  $Q_i$  has a degree exactly  $k$ . Then we write the square non singular matrix  $H = (h_{i,j}) \in \mathcal{M}_k(\mathbb{F}_p)$  of the coefficients of the  $Q_i$

$$Q_i(X) = \sum_{j=0}^{k-1} h_{i,j} X^j$$

If we still consider

$$G_k := (\alpha_{\pi(j)}^i)_{0 \leq i < k, 0 \leq j \leq p-1} \in \mathcal{M}_{k,p}(\mathbb{F}_p)$$

We have the equality

$$H \cdot G_k = M$$

with  $H$  non singular and since  $k \leq p-2$ , this is <sup>sec:Prel</sup>exactly the public key of a cryptosystem based on the Reed-Solomon codes described in Section [2](#).

$$H := \begin{pmatrix} - & Q_1 & - \\ & \vdots & \\ - & Q_i & - \\ & \vdots & \\ - & Q_k & - \end{pmatrix} \begin{pmatrix} 1 & \cdots & 1 & \cdots & 1 \\ \alpha_1 & \cdots & \alpha_j & \cdots & \alpha_p \\ \vdots & & \vdots & & \vdots \\ \alpha_1^{k-1} & \cdots & \alpha_j^{k-1} & \cdots & \alpha_p^{k-1} \end{pmatrix} =: G_k$$

$$\begin{pmatrix} Q_1(\alpha_1) & \cdots & Q_1(\alpha_p) \\ \vdots & \vdots & \vdots \\ Q_i(\alpha_1) & m_{i,j} & Q_i(\alpha_p) \\ \vdots & \vdots & \vdots \\ Q_k(\alpha_1) & \cdots & Q_k(\alpha_p) \end{pmatrix} =: M$$

□

So a possible way to attack the Chor-Rivest cryptosystem would be to find the evaluations of enough small degree polynomials in the  $\alpha_{\pi(i)}$ .

### 4.3 A First Attack using Reed-Solomon codes

When we attack this cryptosystem, we can consider a generator  $g_0 = g^u$  with  $u$  unknown and  $\gcd(u, q-1) = 1$  we then have

$$g_0^{c_i} = (g^d (t + \alpha_{\pi(i)}))^u = (A + \alpha_{\pi(i)} \cdot B)^u$$

The unknown quantities, which can then be considered as an equivalent secret key, are

- $A \in \mathbb{F}_q$ .
- $B \in \mathbb{F}_q$  such that  $t = A \cdot B^{-1}$  has algebraic degree  $h$ .
- $0 < u < q-1$  prime with  $q-1$ .
- the permutation  $\pi$  of  $\{0, \dots, p-1\}$ .

and public key consists in all the

$$d_i := (A + \alpha_{\pi(i)} \cdot B)^u \in \mathbb{F}_q$$

The ciphertext becomes

$$E'(M) := \prod_{i=0}^{p-1} d_i^{m_i} = g^{uE(M)} = B^{uh} \left( \prod_i (t + \alpha_{\pi(i)})^{c_i} \right)^u$$

Knowing  $u$ ,  $B$  and  $h$ , it is easy to compute from  $E'(M)$ , the following quantity

$$\prod_i (t + \alpha_{\pi(i)})^{c_i}$$

which allow us to retrieve all the  $c_i$ .

We have for all  $j$

$$g^{c_j} = g^d \cdot (t + \alpha_{\pi(j)}) = A + \alpha_{\pi(j)} \cdot B$$

where  $\alpha_{\pi(j)} \in \mathbb{F}_p$  and  $A$  and  $B$  are elements of  $\mathbb{F}_{p^h}$ .

A naive attack would be then to try to guess at random the generator  $g$  and perform a polynomial "known  $g$ " attack. We will see that although finding the precise  $g$  is very unlikely, there is a family of generators that still allow to retrieve the permutation  $\pi$  and perform then a polynomial "known  $\pi$ " attack.

#### 4.3.1 Small powers of $g$

As an attempt to guess  $g$ , we suppose that a random generator  $g_0$  of  $\mathbb{F}_q^*$  has been chosen. We know that  $g_0 = g^u$  for a  $u$  integer such that  $\gcd(u, p^h-1) = 1$  and

$$g_0^{c_j} = (A + \alpha_{\pi(j)} \cdot B)^u$$

We chose now a base  $(e_i)_{1 \leq i \leq h}$  of  $\mathbb{F}_q$  as a  $\mathbb{F}_p$ -vector space. When written in this base, each coordinate of  $g_0^{c_j}$  is a polynomial  $Q_i$  in the  $\alpha_{\pi(j)}$ .

$$g_0^{c_j} = \sum_{i=1}^h Q_i(\alpha_{\pi(j)}) e_i$$

where  $Q_i$  has its coefficients in  $\mathbb{F}_p$ .  $Q_i$  depends on  $A$ ,  $B$ ,  $u$  and obviously on  $i$ . However,  $Q_i$  does not depend on  $j$ .

Besides, we have

- $\deg Q_i \leq u$
- $\deg Q_i < p$  since  $\alpha_{\pi(j)}^p = \alpha_{\pi(j)}$ .

This means that we have access to the evaluations in the  $\alpha_{\pi(j)}$  of  $h$  polynomials of degree smaller than  $u$ . According to Theorem [4.3.1](#), a sufficient condition for this attack to work is  $u \leq h - 1 \leq p - 3$ . The last inequality is always true for a big enough instance of the cryptosystem since  $h$  is supposed to be chosen close to  $p/\log p$ . However there are only  $h - 1$  different elements of  $\mathbb{F}_{p^h}$  fulfilling the first inequality.

Considering all these acceptable generators only slightly improves the exhaustive research of  $g$  by a factor of  $h$ .

### 4.3.2 Wider set of acceptable generators

We can notice that if  $u = u'p$ ,

$$g_0^{c_j} = (A + \alpha_{\pi(j)} \cdot B)^{u'p} = (A^p + \alpha_{\pi(j)} \cdot B^p)^{u'}$$

and the coordinates of this quantity are polynomials of degree  $u'$  in  $\alpha_{\pi(j)}$ . Actually, if  $u$  is written  $u = \sum_{i=0}^{h-1} u_i p^i$  in base  $p$ , then we have

$$g_0^{c_j} = \prod_{i=0}^{h-1} (A^{p^i} + \alpha_{\pi(j)} \cdot B^{p^i})^{u_i}$$

whose coordinates are polynomials of degree  $w_p(u) := \sum_{i=0}^{h-1} u_i$  in the  $\alpha_{\pi(j)}$ .

This means that all  $u$  such that  $w_p(u) < h$  allow to retrieve the permutation and break the cryptosystem. The number of such  $u$  is

$$\left( \binom{h+1}{h-1} \right) = \binom{2h}{h-1} = \Theta(4^h \sqrt{h})$$

This is a drastic improvement in the exhaustive research of  $g$ . However this remains quite small compared to the number  $\phi(p^h - 1)$  of different generators in  $\mathbb{F}_{p^h}$  which is comparable to  $p^h$ .

## 5 Vaudenay attack

The previous attack requires to find a generator of  $\mathbb{F}_q$  among the elements that can be written  $g^u$  with  $w_p(u) < h$ . Since there are very few of such elements compared to the  $\phi(q-1)$  different generators of  $\mathbb{F}_q$ , Vaudenay suggests [4] to consider a generator  $g_{p^r}$  of the subfield  $\mathbb{F}_{p^r} \subseteq \mathbb{F}_{p^h}$ . He introduces the following theorem

**Theorem 2.** *For any factor  $r$  of  $h$ , there exists a generator  $g_{p^r}$  of the multiplicative group of the subfield  $\mathbb{F}_{p^r}$  of  $\mathbb{F}_q$  and a polynomial  $Q$  with degree  $h/r$  whose coefficients are in  $\mathbb{F}_{p^r}$  and such that  $-t$  is a root and for all  $j$ , we have  $Q(\alpha_{\pi(j)}) = g_{p^r}^{c_j}$ .*

*Proof.* The expression of such a polynomial is given by

$$Q(X) = g_{p^r}^d \prod_{i=0}^{h/r-1} (X + t^{p^{ri}})$$

where  $g_{p^r} = g^{\frac{q-1}{p^r-1}}$ . □

If we chose a base  $(e_i)_{1 \leq i \leq r}$  of  $\mathbb{F}_{p^r}$  (seen as a  $\mathbb{F}_p$ -vector space), we can write the coefficients of  $g_{p^r}^{c_j}$  in this base as polynomials  $Q_i$  in  $\alpha_{\pi(j)}$ . We get

$$g_{p^r}^{c_j} = \sum_{i=1}^r Q_i(\alpha_{\pi(j)}) e_i$$

with  $\deg Q_i \leq h/r$ . We get the evaluation of  $r$  polynomials of degree smaller than  $h/r$ .

This means that instead of searching a generator among the approximately  $p^h$  generators of  $\mathbb{F}_q$ , we could search only within  $\mathbb{F}_{p^r}$  with  $r$  as small as possible. We notice that to be able to apply Theorem 2, we must have  $h/r < r$ . This yields the following theorem.

**Theorem 3.** *When  $r > \sqrt{h}$ , there exists a polynomial "known  $g_{p^r}$ " attack on the Chor-Rivest cryptosystem.*

This theorem is basically the main result from Vaudenay's article [4]. It states that to attack the Chor-Rivest cryptosystem, one can only search for the generator  $g_{p^r}$  among  $\phi(p^r - 1)$  (which is about  $p^r$ ) possible choices instead of the exhaustive research for  $g$  (around  $p^h$  choices).

However the "known  $g_{p^r}$  attack" suggested in Vaudenay's article can be improved in two ways.

- First it is only polynomial when  $r > \sqrt{h}$ . We will see that using a Reed-Solomon attack, we can still retrieve  $\pi$  in polynomial time provided we manage to get enough linearly independent polynomials in the  $\alpha_{\pi(j)}$  which is possible even for small values of  $r$  using  $g_{p^r}^u$  with  $u$  small enough.
- Besides, the Reed-Solomon attack doesn't require the knowledge of all the  $c_j$ . Only  $O(h)$  (or a little more when considering the attack for  $r$  small) of them. So actually only a small proportion of them is enough. This makes this attack strong.

### 5.1 Generating more rows...

We now describe a "known  $g_{p^r}$ " attack which allow the divisor  $r$  of  $h$  to be far smaller. We still consider the expression of elements of  $\mathbb{F}_{p^r}$  in a given base  $(e_i)_{1 \leq i \leq r}$ .

When we find  $g_{p^r}$  such that  $g_{p^r}^{c_j} = Q(\alpha_{\pi(j)})$  with  $\deg Q \leq h/r$ , we only have  $r$  polynomials corresponding to the  $r$  different coordinates of  $g_{p^r}^{c_j}$  in a certain base of  $\mathbb{F}_{p^r}$ . Being able to generate more polynomials would allow to chose a lower  $r$  and improve drastically the attack.

We could consider now the coordinates in the equation  $Q^u(\alpha_{\pi(j)}) = g_{p^r}^{uc_j}$  for  $u \in [1, p^r - 1]$ . This yields again  $r$  polynomials of degree smaller than  $uh/r$ . Actually, since  $P \mapsto P^p$  let the degree invariant we know that the degree of  $Q^u$  is actually at most  $w_p(u)h/r$ .

To generate more polynomials, we could then decide to consider all the equations  $Q^u(\alpha_{\pi(j)}) = g_{p^r}^{uc_j}$  for all  $u \in U_w^{(r)} := \{u \in [1, p^r - 1] | w_p(u) \leq w\}$ . This yields  $r \cdot |U_w^{(r)}|$  polynomials of degree at most  $wh/r$ .

Besides, assuming  $w \gg r$ , the number of such polynomials can be up to

$$|U_w^{(r)}| = \left( \binom{r+1}{w} \right) = \binom{r+w+1}{w} = \binom{r+w+1}{r+1} = \Theta \left( \frac{w^{r+1}}{(r+1)!} \right).$$

This means that we can choose  $r$  far smaller than  $\sqrt{h}$ . Indeed, even if we consider polynomials of higher degree ( $wh/r$ ), the number of such polynomials we can get is far greater than  $r$  and we can hope that if we choose  $w$  high enough, we can get enough different polynomials to use a Sidelnikov-Shestakov attack.

Unfortunately, these polynomials are strongly linearly dependent. For example, the coordinates of  $g_{p^r}^{pc_j}$  are linearly dependent on the coordinates of  $g_{p^r}^{c_j}$ . Indeed, when decomposed in a normal base of  $\mathbb{F}_{p^r}$ , these two sets of vectors of coordinates only differs by a rotation.

## 6 Simulations and expected complexity

Simul

In order to demonstrate the efficiency of the "known  $g_p$ " attack algorithm presented in Section [5](#) sec:Vau with small  $r$ , we run simulations on the number of linearly independent lines that can be obtained from the coordinates of  $g_{p^r}^{uc_j}$ .

### 6.1 First examples

For example, see Example [A.1](#) Ex:1 in appendix, we try  $h = 24$  and  $r = 3 < \sqrt{h}$ . As a result, we manage to obtain  $11 \times 3 = 33$  lines of coordinates linearly independent (the simulation is the verification of this independence). This would allow the attack to retrieve the permutation  $\pi$  using the attack on the cryptosystem based on Reed-Solomon codes.

This proves that it is possible to duplicate the number of lines at the expense of the degree of the polynomials considered. Here, the polynomials considered are of degree 32 instead of 8 but we manage to generate 33 linearly independent lines instead of only 3. Therefore the condition  $r \geq \sqrt{h}$  is not absolutely necessary and we can hope to get a (far) smaller lower bound on  $r$ .

In the Example [A.1](#) Ex:1 (see appendix), we chose  $h = 27$ ,  $p = 53$  and we manage to get 46 linearly independent lines using  $r = 3$  only. An exhaustive research for  $g_{p^3}$  would require circa 149.000 verifications whereas using  $r = 9 > \sqrt{h}$ , we would need at least  $3.3 \cdot 10^{15}$  steps, which is out of most computer range.

### 6.2 Number of linearly independent polynomials

On several simulations for different values for  $p$  and  $h$ , see Results [B](#) Sim:res in appendix, we choose, each time, the smallest value for  $r$  that allow an attack on the system. We present in the appendix the maximum weight  $w$  chosen for the exponents  $u_i$  of  $g_{p^r}$  and the number of linearly independent rows these  $g_{p^r}^{u_i}$  allow to generate (should be  $w \cdot \frac{h}{r} + 1$ ).

Let  $r$  be a divisor of  $h$ , we call  $u_w$  the number of linearly independent rows of coordinates we can get using the coordinates of  $g_{p^r}^{uc_j}$  for all  $u$  such that  $w_p(u) \leq w$ .

We have  $u_0 = 1$  obviously because using  $g_{p^r}^0$ , we only get one row filled with 1.

We also have  $u_1 = r + 1$  because we can only get  $r$  more lines using  $g_{p^r}$  corresponding to the  $r$  different coordinates of  $g_{p^r}^{c_j}$  in  $\mathbb{F}_{p^r}$ . The coordinates given by the generator  $g_{p^r}^{p^i}$  are the same as those given by  $g_{p^r}$  in a normal base. This mean that whatever the base chosen, they are at least linearly dependent from each other and so using  $g_{p^r}$  doesn't allow to generate more useful polynomials.

### 6.3 Postulate

We notice experimentally the following behavior

**Postulate 4.** *We have for  $r > 2$*

$$u_w = \min \left( \binom{w+r}{r}, w \frac{h}{r} + 1, p \right)$$

This behavior has been observed for the following range of parameters

$r$	$w$	$h/r$
2	1-17	1-2
3	1-17	1-17, 30
4	1-17	1-17, 30
5	1-17	1-17, 30

For  $r = 2$  and  $h/r \geq 3$ , we notice a different behavior...

### 6.4 Optimum choice for $r$

We suppose that we have found  $r$  allowing to attack a Chor-Rivest cryptosystem. Being able to perform a Sidelnikov-Sjestakov attack imposes that there exists  $w$  such that

$$\begin{aligned} wh/r + 1 &\leq p - 2 \\ wh/r + 1 &\leq u_w \end{aligned}$$

We choose the biggest  $w$  verifying the first condition to have the weakest condition on  $r$  :  $w = \lfloor r \frac{p-3}{h} \rfloor$ . Besides we know that  $h$  is suppose to be chosen around  $\frac{p}{\log p}$ . This means that we have  $w = \Theta(r \log p) \geq Cr \log p$ .

We suppose that we remain in the domain  $w \leq h/r$  and that the postulate in the Section [6](#) <sup>[sec:Simul](#)</sup> is true. The second condition is then easily equivalent to

$$v(w) = \binom{w+r}{r} \geq w \frac{h}{r} + 1$$

and since

$$\binom{w+r}{r} \geq \frac{w^r}{r!} \quad \text{and} \quad p \geq w \frac{h}{r} + 1$$

a sufficient condition would be

$$\begin{aligned} \frac{w^r}{r!} &\geq p \\ \Leftrightarrow Cr^r (\log p)^r &\geq p \cdot r! \\ \Leftrightarrow (e \log p)^r &\geq \frac{p}{C\sqrt{2\pi r}} \geq C'p \\ \Leftrightarrow r &\geq \frac{\log p + C''}{\log \log p + 1} \sim \frac{\log p}{\log \log p} \end{aligned}$$

This mean that the exhaustive research can be done in time  $O\left(p^{\frac{\log p}{\log \log p}}\right)$ , far faster than  $O\left(p^{\sqrt{\frac{p}{\log p}}}\right)$ .

The condition  $rw \leq h$  yields an upper bound on the  $r$ .

$$C' r^2 \leq \frac{p}{\log^2 p}$$

which is asymptotically always verified given the upper bound on  $r$  found.

## 7 Conclusions

We can notice that this attack on Chor-Rivest cryptosystem is only effective when  $h$  possesses a small factor.

## References

- Riv88 [1] B. Chor and R. L. Rivest. A knapsack-type public key cryptosystem based on arithmetic in finite fields. *IEEE Trans. Inform. Theory*, 34(5):901–909, 1988.
- NerH86 [2] H. Niederreiter. Knapsack-type cryptosystems and algebraic coding theory. *Probl. Control and Inform. Theory*, 15:19–34, 1986.
- Shest92 [3] V. M. Sidelnikov and S. O. Shestakov. On insecurity of cryptosystems based on generalized reed-solomon codes. *Discrete Math. Appl.*, 2(4):439–444, 1992.
- Vau01 [4] S. Vaudenay. Cryptanalysis of the chor–rivest cryptosystem. *Journal of Cryptology*, 14:87–100, 2001.
- Wiesch [5] C. Wieschebrink. Cryptanalysis of the niederreiter public key scheme based on grs subcodes. Federal Office for Information Security (BSI), Godesberger Allee 185-189, 53175 Bonn, Germany.



## A Simulation examples

### A.1 Example 1

**Ex: 1**

We choose the following parameters

- $p = 197$ ,  $h = 24$ ,  $r = 3 < \sqrt{h}$ .
- We define  $\mathbb{F}_q$  as the quotient of  $\mathbb{F}_p[X]$  by the polynomial

$$\begin{aligned} X^{24} &+ 192X^{23} + 152X^{22} + 25X^{21} + 75X^{20} + 67X^{19} + 92X^{18} + 23X^{17} + 45X^{16} + 97X^{15} \\ &+ 2X^{14} + 21X^{13} + 106X^{12} + 130X^{11} + 128X^{10} + 136X^9 + 195X^8 + 95X^7 + 155X^6 \\ &+ 34X^5 + 51X^4 + 180X^3 + 97X^2 + 23X + 87 \end{aligned}$$

- We choose  $g := X + 2$  the private multiplicative generator.
- We compute

$$\begin{aligned} g_{p^r} &= g^{\frac{p^h-1}{p^r-1}} \\ &= 153X^{23} + 168X^{22} + 167X^{21} + 45X^{20} + 128X^{19} + 68X^{18} + 103X^{17} + 11X^{16} \\ &\quad + 139X^{15} + 190X^{14} + 75X^{13} + 73X^{12} + 190X^{11} + 64X^{10} + 173X^9 + 34X^8 \\ &\quad + 88X^7 + 30X^6 + 139X^5 + 146X^4 + 111X^3 + 80X^2 + 136X + 48 \end{aligned}$$

- We choose different values for  $d$ ,  $t$  and  $\pi$ , the results remain the same.
- We choose the base  $(g_{p^r}, g_{p^r}^p, g_{p^r}^{p^2})$  for the  $\mathbb{F}_p$ -vector space  $\mathbb{F}_{p^r}$  (this is however of no influence on the results).
- We choose  $(u_i)_{1 \leq i \leq 11} = (1, 2, p+1, 3, 2p+1, p+2, 4, p+3, 3p+1, 2p+2, 2p^2+p+1)$   
We have  $w_p(u_i) \leq 4$  so the coordinates of  $g_{p^r}^{u_i c_j}$  are polynomials of degree smaller than  $4h/r + 1 = 33$  in the  $\alpha_{\pi(j)}$ .

## A.2 Example 2

Ex: 2

$p$	53
$h$	27
$r$	$3 < \sqrt{h}$
$\mathbb{F}_{p^q}$	$\mathbb{F}_p[X]/(P)$ with $ \begin{aligned} P := & X^{27} + X^{26} + X^{25} + 6X^{24} + 15X^{23} + 13X^{22} \\ & + 40X^{21} + 34X^{20} + 10X^{19} + 3X^{17} + 34X^{16} \\ & + 40X^{15} + 49X^{14} + 42X^{13} + 20X^{12} + 6X^{11} \\ & + X^{10} + 48X^9 + 35X^8 + 41X^7 + 27X^6 \\ & + 12X^5 + 34X^4 + 38X^3 + 47X^2 + 19X + 1 \end{aligned} $
$g$	$X + 2$
$g_{p^r}$	$ \begin{aligned} 2X^{26} & + 20X^{25} + 38X^{24} + 32X^{23} + 15X^{22} + 28^{21} \\ & + 39X^{20} + 26X^{19} + 39X^{18} + 36X^{17} + 21X^{16} \\ & + 40X^{15} + 38X^{14} + 40X^{13} + 51X^{12} + 32X^{11} \\ & + 50X^{10} + 51X^9 + 2X^8 + 48X^7 + 17X^6 \\ & + 24X^5 + 31X^4 + 42X^3 + 6X^2 + 46X + 16 \end{aligned} $
$(u_i)_{1 \leq i \leq 16}$	$\{0, 1, 2, p+1, 3, p+2, 2p+1, 4, p+3, 3p+1, 2p+2, 2p^2+p+1, 5, 4p+1, 3p+2, p^2+p+3\}$
$t, d, \pi$	Several values chosen at random
Rank	46

## B Simulation results

$p$	$h$	$r$	$w_p(u_i)$	Number of linearly independent lines
197	24	2	$w$	$\frac{w(w+3)}{2} < 12w + 1$ Attack impossible.
197	24	3	4	33
197	24	4	2	13
197	24	$r \geq 6$	1	$1 + h/r$
193	36	2	$w$	$\frac{w(w+3)}{2} < 18w + 1$ Attack impossible.
193	36	3	6	73
193	36	4	3	28
193	36	6	2	13
193	36	$r \geq 9$	1	$1 + h/r$
251	60	2	$w$	$\frac{w(w+3)}{2} < 30w + 1$ Attack impossible.
251	60	3	8	161
251	60	4	4	61
251	60	5	3	37
251	60	6	2	21
251	60	$r \geq 10$	1	$1 + h/r$