

Transaction Post Office (TPO)

Web API Technical Specification

Version 2.6.9

Developed by



Contents

INTRODUCTION	5
OVERVIEW.....	5
ONLINE API DOCUMENTATION AND TESTING (SWAGGER)	5
API RETURN STRUCTURE	6
BASIC RESULT	6
SEARCH RESULT.....	8
INSERT RESULT.....	10
 AVAILABLE API TO USE.....	 11
 CLAIM API	 11
AUTHORIZATION API	17
ERX API	23
LAB API	31
RAD API	41
DISPENSE API	51
ATTACHMENT API	54
 APPENDIX A: JSON OBJECT STRUCTURE & FIELDS DESCRIPTIONS.....	 55
 CLAIM OBJECT STRUCTURE & FIELDS DESCRIPTIONS	 55
REQUEST STRUCTURE – CLAIM POSTSUBMISSION	55
RESPONSE STRUCTURE – CLAIM POSTREMITTANCE	65
RESPONSE DATA MODEL – SET DOWNLOADED	69
PARAMETERS	69
AUTHORIZATION OBJECT STRUCTURE & FIELDS DESCRIPTIONS	70
REQUEST STRUCTURE – POST REQUEST.....	70
RESPONSE STRUCTURE - POSTAUTHORIZATION	79
RESPONSE TABLE – SET DOWNLOADED	84
ERX OBJECT STRUCTURE & FIELDS DESCRIPTIONS	84
REQUEST STRUCTURE - ERX POSTREQUEST	84
REQUEST STRUCTURE - ERX EDITREQUEST	95
RESPONSE STRUCTURE - ERX POSTAUTHORIZATION	105
RESPONSE TABLE – SET DOWNLOADED	110
LAB OBJECT STRUCTURE & FIELDS DESCRIPTIONS.....	110
REQUEST STRUCTURE - LAB POSTREQUEST	110
REQUEST STRUCTURE - LAB EDITREQUEST	118
RESPONSE STRUCTURE - LAB POSTAUTHORIZATION	121
REQUEST STRUCTURE (POST RESULT) - LAB RESULT	125
RESPONSE TABLE – SET DOWNLOADED	127
RESPONSE STRUCTURE - LAB RESULT (TPO VALIDATION).....	127
RAD OBJECT STRUCTURE & FIELDS DESCRIPTIONS	128

REQUEST STRUCTURE - RAD POSTREQUEST	128
REQUEST STRUCTURE – RAD EDITREQUEST.....	137
RESPONSE STRUCTURE - RAD POSTAUTHORIZATION.....	146
REQUEST STRUCTURE (POST RESULT) - RAD RESULT.....	150
RESPONSE TABLE – SET DOWNLOADED	154
DISPENSE OBJECT STRUCTURE & FIELDS DESCRIPTIONS	154
REQUEST STRUCTURE – PRESCRIPTION DISPENSE ERX DISPENSE	154
REQUEST STRUCTURE – DISPENSE LABDISPENSE	159
REQUEST STRUCTURE – DISPENSE RADDISPENSE.	164
ATTACHMENT OBJECT STRUCTURE & FIELDS DESCRIPTIONS:.....	168
RESPONSE STRUCTURE – DOWNLOAD ATTACHMENT	171

Document Revision History

Document Version #	Date of Release	Changes	Changes in Section
2.6.2	9-Dec-2020	Gross changes and inclusion in the schema.	Applicable sections
2.6.3	21-Dec-2020	Added new Encounter Types • 45 = Laboratory Hospital Walk-In • 46 = Radiology Hospital Walk-In • 47 = Pharmacy Hospital Walk-In • 48 = Physiotherapy Hospital Walk-In • 49 = Optics Hospital Walk-In	Applicable sections
2.6.4	21-Apr-21	TLS Changes	Overview
2.6.5	06-Jun-21	EditRequest and Response EditRequest Authorization added	LAB/ RAD/ ERX
2.6.6	10-Jun-21	Review comments updated	LAB/ RAD/ ERX
2.6.7	01-Sep-21	DateOrdered added to Claim Submission	Post Submission
2.6.8	22-Mar-2023	DateOfOnset added to the postrequest and editrequest	Claim/ Authorization/ LAB/ RAD/ ERX
2.6.9	25-Jul-2023	Added code 8 = "Operation Room" in Activity.location field	Claim/ Authorization

Introduction

Overview

Transaction Post Office (TPO) facilitates and manages all transactional messages between the different stakeholders, Healthcare Provider, Payer and Regulator. Transactions passing through the TPO are validated instantly to ensure the provision of minimum data sets, correct formats, authorized users and the utilization of standard data sets mandated by EHSI through this project.

Clean, standard and structured data captured in the TPO will enable the thorough analysis of the different trends both on a clinical and financial level to help drive up the market efficiency and healthcare quality simultaneously.

TPO is equipped with an interface to enable monitoring and managing transaction uploads and downloads taking place through the Hakeem eClaim online portals, or through the direct integration through web service APIs.

	TLS version 1.0 and 1.1 are disabled and no longer supported. Integration Vendors/ Clients can use the version – TLS 1.2 or any higher version to connect to IQVIA's applications / APIs.
---	--

Online API Documentation and Testing (Swagger)

Swagger is a powerful web-based tool that facilitates the API documentation and enables the user to test the API functions and without additional coding requirements. Using the generated swagger JSON file, you can generate all models needed to do integration with the API.

TPO technical documentation is available through swagger on the following link, [Click here](#).
(or enter: <https://TPO.ehc.jo/swagger/> in your web browser)

API Return Structure

Basic Result

Below you can find the description for the returned JSON object structure with fields' type and description.

BASIC RESULT		
Entity	Object	The object we are returning
StatusCode	Integer	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	String	Status description message will be returned from the called API method that provide a text description for the status code
Success	Boolean	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	String	End user description message that provide a description for the status code
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal. • Example provided below (JSON Sample: Response with Error)

JSON Sample: login action response

```
{
  "Entity": {
  },
  "StatusCode": 200,
  "Message": null,
  "Success": false,
  "UserMessage": null,
  "Error": []
}
```

JSON Sample: Response with error

```
{
  "StatusCode": 400,
  "Message": "Error while validating entity",
  "Success": false,
  "UserMessage": "Error while validating entity. Please see the list of
errors and fix them",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please fix
ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    },
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "RuleCode": "VR09",
      "ErrorText": "Claim ProviderId must be equal to Header SenderId, Claim
ProviderId must be equal to Header SenderId",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ]
}
```

Search Result

Below you can find the description for the returned JSON object structure with fields' type and description.

BASIC RESULT		
Entity	Object	The object we are returning
StatusCode	Integer	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	String	Status description message will be returned from the called API method that provide a text description for the status code
Success	Boolean	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	String	End user description message that provide description for the status code
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
SEARCH – RESULT ENTITY		
ReceiverID	String	The Unique ID of the Receiver (the user performing the search) as provided by the regulator.
RecordCount	integer	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
SenderID	String	The Unique ID of the Sender (the entity that uploaded the transaction) as provided by the regulator.
TransactionDate	String	Transaction generated date based on upload action. Date/Time Format: DD/MM/YYYY HH:MM
ID	String	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
CreationDate	string	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean	A flag in the post office to indicate of the transaction has been downloaded or not. (Returned results: “True” , “False”)

JSON Sample: Search transaction

```
{
  "Entities": [
    {
      "ReceiverID": "Provider1",
      "RecordCount": 2,
      "SenderID": "Payer1",
      "TransactionDate": "14/06/2018 11:10",
      "ID": "5b224de5df420c39b0bd6b8f",
      "CreationDate": "14/06/2018 11:13:41",
      "Downloaded": false
    },
    {
      "ReceiverID": "Provider1",
      "RecordCount": 1,
      "SenderID": "Payer2",
      "TransactionDate": "14/06/2018 07:58",
      "ID": "5b2220e5df420c39b0bd6908",
      "CreationDate": "14/06/2018 08:01:41",
      "Downloaded": false
    }
  ],
  "StatusCode": 200,
  "Message": "Items Loaded Successfully.",
  "Success": true,
  "UserMessage": "Items Loaded Successfully",
  "Error": []
}
```

Insert Result

Below you can find the description for the returned JSON object structure with fields' type and description.

BASIC RESULT		
StatusCode	Integer	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	String	Status description message will be returned from the called API method that provide a text description for the status code
Success	String	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	String	End user description message that provide description for the status code
EntityID	string	Unique identifier auto-generated by the TPO at the successful upload of a given transaction or a file.
ReferenceNumber	string	A unique identifier auto-generated by the TPO at the successful upload of erxRequest , LabRequest and RadRequest transactions. This number is given to the member, and is then used to search, download, and process the transaction.
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

JSON Sample: Basic result for the general insert API

```
{
  "StatusCode": 201,
  "Message": "Add One Item to Db",
  "Success": true,
  "UserMessage": "Item Added Successfully",
  "EntityID": "5a531a14aa74aa0f68caca84",
  "ReferenceNumber": "873823",
  "Error": []
}
```

Available API to use

This section will present a full list of the APIs available on the TPO to enable the Payer and Provider from managing their transactions.

Claim API

Below is a list of APIs used to manage the Claim cycle transactions including ClaimSubmission, RemittanceAdvice and ClaimResubmission.

API – GetNew (<https://TPO.ehc.jo/api/Claim/GetNew>)

Expected output

- A list of the latest new transactions (**not set as downloaded**) received by the searching user\account.
- The list may contain only up to 500 transactions.
- Returned transactions depend on the user type:
 - **Provider** = returned transactions will be RemittanceAdvice.
 - **Payer** = Returned transactions will be ClaimSubmimssion, ClaimResubmission.

Below are the details received in the response whenever the **GetNew** is submitted:

Element Name	Type	Description
CLAIM – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID	string example: LC01	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
RecordCount	integer(\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM

Element Name	Type	Description
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions
CLAIM – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.

Element Name	Type	Description
		Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	String example: Paid	Entity Status

API – Search (<https://TPO.ehc.jo/api/Claim/Search>)

This search function support direction filtering (new transactions or sent by me). Below is a list of the possible filter parameters that can be utilized in the search criteria:

Parameter	Type	Behavior Description
license	String (query)	This Is the unique identifier given to the transaction payer or provider by the regulator. If value is set, function will return new transactions with exact match of the Sender License. If direction = 0 (received), license will be the SenderID license. If direction = 1 (sent), license will be the ReceiverID license.
direction	Integer (\$int32) (query)	Can use two possible values listed below to indicate the direction of the transaction being searched for: • 0 = Filter received transactions (Default value). • 1 = Filter sent transactions • Default value is 0, unless it is updated by the user.
fromDate	String (query)	If value is set, function will return new transactions with creation date greater than the filter value. If toDate parameter is not set, it would be a minute after the fromDate. • Date time format: DD/MM/YYYY HH:MM • If toDate is not set, the system will return the first 500 transactions from the set fromDate
toDate	String (query)	If value is set, function will return new transactions with creation date less than the filter value. If fromDate parameter is not set, it would be a minute before the toDate. • Date time format: DD/MM/YYYY HH:MM • If fromDate is not set, the system will return the first 500 transactions prior to the set toDate
downloaded	Integer (\$int32)	Can use three possible values listed below to indicate the download status of the transaction being searched for:

	(query)	0 = Filter not downloaded transactions (Default value). 1 = Filter downloaded transactions. 2 = Filter all transactions. Default value is 0 , unless it is updated by the user.
Id	String (query)	If value is set, the function will return new transaction with ClaimID matching the filter value.
username	String (header)	Username is case sensitive
password	string (header)	Password is case sensitive

Below are the details received in the response whenever the **Search** is submitted:

Element Name	Type	Description
CLAIM – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Gets or sets the identifier.
SenderID	string example: LC008	Gets or sets the identifier of the sender.
ReceiverID	string example: LC01	Gets or sets the identifier of the receiver.
RecordCount	integer(\$int32) example: 2	Gets or sets the number of records.
TransactionDate	string example: 21/08/2018 12:13	Gets or sets the transaction date.
CreationDate	string example: 21/08/2018 12:17	Gets or sets the creation date.
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions

CLAIM – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: 200 = everything is correct disposition flag is test 201 = everything is correct disposition flag is Production

		• 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call • False = Validation error occurred
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest. Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – View (<https://TPO.ehc.jo/api/Claim/View>)

View individual claim from the post office. you can only view claims assigned to you or generated from you according to direction parameter.

This function takes four parameters:

- **id** (string): Transaction ID user wants to view.

- **direction** (integer): 0 for received transactions, 1 for sent transaction. Default is 0.
- **username** (string): username case sensitive
- **password** (string): password case sensitive

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Claim/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Claim/Request Structure](#)

Below are the details received in the response whenever the View is submitted:

Element Name	Type	Description
View/Body		
StatusCode	Integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 429 = Transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

API – PostSubmission (<https://TPO.ehc.jo/api/Claim/PostSubmission>)

This function used by provider to upload claim submission.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Claim/Request Structure](#)

API – PostRemittance (<https://TPO.ehc.jo/api/Claim/PostRemittance>)

This function used by payer to upload remittance file.

For JSON Object Structure and object parameters descriptions, please refer to below [Appendix A/Claim/Response Structure](#)

API – SetDownloaded (<https://TPO.ehc.jo/api/Claim/SetDownloaded>)

This function sets new transaction as downloaded according to transaction ID.

Parameter:

- **id** (string): Transaction ID user wants to set as downloaded
- **username**(string): username case sensitive
- **password** (string): password case sensitive

For JSON Object Structure and object parameters descriptions, please refer to below [Appendix A/Claim/Response Structure](#)

Authorization API

API – GetNew (<https://TPO.ehc.jo/api/Authorization/GetNew>)

GetNew API returns new transactions (**not downloaded**) up to **500** transactions. Transactions returned according to **user type**. If user is Provider, the function will return the new PriorAuthorization transactions. If user is Payer, the function will return new PriorRequest transactions.

It has 2 parameters:

- **Username** (string): Username is case-sensitive
- **Password** (string): Username is case-sensitive

Below are the details received in the response whenever the **GetNew** is submitted:

Element Name	Type	Description
Authorization/Entities		
ID	string example: 5abb3a49e6e a191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Provider, Insurer or TPA sending information
ReceiverID	string example: LC01	Provider, Insurer or TPA receiving information
RecordCount	Integer (\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than

Element Name	Type	Description
		one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	A flag in the post office to indicate of the transaction has been downloaded or not. (Returned results: "True" , "False")
Authorization/Result		
StatusCode	integer (\$int32) example: 200	The result status code. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets.

Element Name	Type	Description
		Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – Search (<https://TPO.ehc.jo/api/Authorization/Search>)

This search function support direction filtering (new transactions or sent by me). Search Post office authorizations. You can search new data or your data according to the filters provided (up to 500 transactions)

Below is a list of the possible filter parameters that can be utilized in the search criteria:

Parameters	Type	Behavior Description
license	string (query)	This Is the unique identifier given to the transaction payer or provider by the regulator. If value is set, function will return new transactions with exact match of the Sender License.
Direction	Integer (\$int32) (query)	Can use two possible values listed below to indicate the direction of the transaction being searched for: 0 = received transaction 1 = sent transactions Default value is 0 , unless it is updated by the user.
fromDate	string (query)	If value is set, function will return new transactions with creation date greater than the filter value. If toDate parameter is not set, it would be a minute after the fromDate. - Date time format: DD/MM/YYYY HH:MM - If toDate is not set, the system will return the first 500 transactions from the set fromDate
toDate	string (query)	If value is set, function will return new transactions with creation date less than the filter value. If fromDate parameter is not set, it would be a minute before the toDate. - Date time format: DD/MM/YYYY HH:MM - If fromDate is not set, the system will return the first 500 transactions prior to the set toDate
downloaded	Integer (\$int32) (query)	Can use three possible values listed below to indicate the download status of the transaction being searched for: 0 = not downloaded 1 = downloaded 2 = all Default value is 0 , unless it is updated by the user.
Id	string (query)	If value is set, the function will return new transaction with AuthorizationID matching the filter value.
Username	string (header)	Username is case sensitive

Parameters	Type	Behavior Description
Password	string (header)	Password is case sensitive

Below are the details received in the response whenever the **Search** is submitted:

Element Name	Type	Description
Authorization – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Gets or sets the identifier.
SenderID	string example: LC008	Gets or sets the identifier of the sender.
ReceiverID	string example: LC01	Gets or sets the identifier of the receiver.
RecordCount	integer(\$int32) example: 2	Gets or sets the number of records.
TransactionDate	string example: 21/08/2018 12:13	Gets or sets the transaction date.
CreationDate	string example: 21/08/2018 12:17	Gets or sets the creation date.
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions
AUTHORIZATION – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are:

Element Name	Type	Description
		• True = Successful call • False = Validation error occurred
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest. Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – View (<https://TPO.ehc.jo/api/Authorization/View>)

View transaction file. This function takes four parameters:

- **id** (string): Transaction ID user wants to view.
- **direction** (integer(\$int32)): 0 for received transactions, 1 for sent transaction. Default is 0.
- **Username** (string): Username is case-sensitive
- **Password** (string): Username is case-sensitive

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Authorization/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Authorization/Request Structure](#)

Below are the details received in the response whenever the View is submitted:

Element Name	Type	Description
View/Body		
StatusCode	Integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production

Element Name	Type	Description
		• 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provides description for the status code
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

API – PostRequest (<https://TPO.ehc.jo/api/Authorization/PostRequest>)

This function used by provider to upload prior request.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Authorization/Request Structure](#)

API – PostAuthorization (<https://TPO.ehc.jo/api/Authorization/PostAuthorization>)

This function used by payer to upload PriorAuthorization file.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Authorization/Response Structure](#)

API – SetDownloaded (<https://TPO.ehc.jo/api/Authorization/SetDownloaded>)

This function sets new transaction as downloaded according to transaction ID.

Parameters:

- **id** (string): Transaction ID user wants to set as downloaded
- **username** (string): username case sensitive
- **password**(string): username case sensitive

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Authorization/Response Structure](#)

ERX API

API – GetNew (<https://TPO.ehc.io/api/ERX/GetNew>)

This function takes no parameters. Returns new transactions (not downloaded) up to **500** transaction. Transactions returned according to **user type**. If user is Provider, the function will return the new eRxAuthorization transactions. If user is Payer, the function will return new eRxRequest transactions.

Below are the details received in the response whenever the GetNew is submitted:

Element Name	Type	Description
ErX/Entities		
ID	string example: 5abb3a49e6 ea191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Provider, Insurer or TPA sending information
ReceiverID	string example: LC01	Provider, Insurer or TPA receiving information
RecordCount	Integer (\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	A flag in the post office to indicate of the transaction has been downloaded or not. (Returned results: “True” , “False”)
ErX/Result		
StatusCode	Integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are:

Element Name	Type	Description
		True = Successful call. False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	List of Error objects generated from: - JSON parsing for syntax and data sets. - Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – Search (<https://TPO.ehc.jo/api/ERX/Search>)

This search function support direction filtering (new transactions or sent by me). Search Post office for eRx Transactions. You can search new data or your data according to the filters provided.
(up to 500 transactions)

Below is a list of the possible filter parameters that can be utilized in the search criteria:

Parameter	Type	Behavior Description
license	string (query)	Filter transactions according to sender license. If direction = 0 (received), license will be the SenderID license. If direction = 1 (sent), license will be the ReceiverID license.
direction	Integer (\$int32) (query)	Can use two possible values listed below to indicate the direction of the transaction being searched for: 0 = received transaction 1 = sent transactions Default value is 0 , unless it is updated by the user.
fromDate	string (query)	If value is set, function will return new transactions with creation date greater than the filter value. If toDate parameter is not set, it would be a minute after the fromDate. - Date time format: DD/MM/YYYY HH:MM - If toDate is not set, the system will return the first 500 transactions from the set fromDate
toDate	string (query)	If value is set, function will return new transactions with creation date less than the filter value. If fromDate parameter is not set, it would be a minute before the toDate.

Parameter	Type	Behavior Description
		- Date time format: DD/MM/YYYY HH:MM - If fromDate is not set, the system will return the first 500 transactions prior to the set toDate
downloaded	Integer (\$int32) (query)	Can use three possible values listed below to indicate the download status of the transaction being searched for: 0 = not downloaded 1 = downloaded 2 = all Default value is 0 , unless it is updated by the user.
id	string (query)	If value is set, the function will return new transaction with PrescriptionID/AuthorizationID matching the filter value.
username	string (header)	Username is case sensitive
password	string (header)	Password is case sensitive

Below are the details received in the response whenever the Search is submitted:

Element Name	Type	Description
ERX – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Gets or sets the identifier.
SenderID	string example: LC008	Gets or sets the identifier of the sender.
ReceiverID	string example: LC01	Gets or sets the identifier of the receiver.
RecordCount	integer(\$int32) example: 2	Gets or sets the number of records.
TransactionDate	string example: 21/08/2018 12:13	Gets or sets the transaction date.
CreationDate	string example: 21/08/2018 12:17	Gets or sets the creation date.
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions
ERX – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: 200 = everything is correct disposition flag is test 201 = everything is correct disposition flag is Production

Element Name	Type	Description
		400 = invalid JSON request, or TPO validation rule error 401 = pass invalid username or unauthorized operation 500 = If there is an exception in the code or insert/update/delete to DB fails
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: True = Successful call False = Validation error occurred
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest. Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: - JSON parsing for syntax and data sets. - Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – View (<https://TPO.ehc.jo/api/ERX/View>)

View individual eRx transaction from the post office. you can only view ERX assigned to you or generated from you according to direction parameter.

To View the transaction file, this function takes four parameters:

- id** (string): Transaction ID user wants to view.
- direction** (integer): 0 for received transactions, 1 for sent transaction. Default is 0.

JSON Object Structure:

- **username** (string): username case sensitive.
- **password** (string): password case sensitive.
- For provider with direction 0 as a value please refer to [Appendix A/ERX/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/ERX/Request Structure](#)

Below are the details received in the response whenever the View is submitted:

Element Name	Type	Description
View/Body		
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

API – PostRequest (<https://TPO.ehc.jo/api/ERX/PostRequest>)

This function used by provider to upload eRxRequest.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/ERX/Request Structure](#)

API – PostEditRequest (<https://TPO.ehc.jo/api/ERX/PostEditRequest>)

This function used by provider to upload or edit eRxRequest transaction.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/ERX/Request Structure](#)

API – PostAuthorization (<https://TPO.ehc.jo/api/ERX/PostAuthorization>)

This function used by payer to upload eRxAuthorization file.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/ERX/Response Structure](#)

API – SetDownloaded (<https://TPO.ehc.jo/api/ERX/SetDownloaded>)

This function sets new transaction as downloaded according to transaction ID.

Parameter:

- **id** (string): Transaction ID user wants to set as downloaded
- **username** (string): username case sensitive
- **password**(string): username case sensitive

For JSON Object Structure and object parameters descriptions, please refer to below section Appendix A/Authorization/Response Structure

API – ViewPharmacyPrescription (<https://TPO.ehc.jo/api/ERX/ViewPharmacyPrescription>)

This function can only be used by provider of type pharmacy to return the eRx prescription with the activities that are not dispensed.

Parameters:

- **reference** (string): Order reference ID/ Reference Number generated by the TPO.
- **patientIdentity** (string): patient identification number.
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

Below are the details received in the response whenever the ViewPharmacyPrescription is submitted:

Element Name	Type	Description
Entity/ ViewPharmacyPrescription		

Element Name	Type	Description
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID. This will return when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

API – CheckActivityStatus (<https://TPO.ehc.jo/api/ERX/CheckActivityStatus>)

This function can be used by the provider only to check the status for the submitted activities

Parameters:

- **id** (string): Transaction ID.
- **activityId** (string): Unique identifier of activity within the ERX (Optional, incase provider want to check the status for specific activity).
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

Below are the details received in the response whenever the CheckActivityStatus is submitted:

Element Name	Type	Description
ERX/ CheckActivityStatus		
Entities	Entities []	List of Result Entities.
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	String example: Paid	Entity Status

JSON Result Object Structure:

```
{
  "Entities": [
    {
      "ActivityID": "479",
      "Status": "Pending",
      "ActivityCode": "00214",
      "ActivityDescription": "Drug Name",
      "DispenseDate": "16/1/2019",

```

```

        "RemainingRefills": 0
    }
],
"StatusCode": 400,
"Success": false,
"Error": []
}

```

Status Expected result: “Dispensed”, “Expired”, “Cancelled”, “Partially Dispensed” and “Pending”.

Lab API

API – GetNew (<https://TPO.ehc.jo/api/Lab/GetNew>)

This function takes two parameters.

- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

Returns new transactions (not downloaded) up to **500** transaction. Transactions returned according to **user type**. If user is Provider, the function will return the new LabAuthorization transactions. If user is Payer, the function will return new LabRequest transactions.

Below are the details received in the response whenever the GetNew is submitted:

Element Name	Type	Description
Laboratory/Entities		
ID	string example: 5abb3a49e6ea191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Provider, Insurer or TPA sending information
ReceiverID	string example: LC01	Provider, Insurer or TPA receiving information
RecordCount	Integer (\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	A flag in the post office to indicate of the transaction has been downloaded or not. (Returned results: “True”, “False”)
Laboratory/Result		
StatusCode	Integer	The operation status. Possible returned status codes:

Element Name	Type	Description
	(\$int32) example: 200	200 = everything is correct disposition flag is test 201 = everything is correct disposition flag is Production 400 = invalid JSON request, or TPO validation rule error 401 = pass invalid username or unauthorized operation 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: True = Successful call. False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.
Error	Object []	List of Error objects generated from: - JSON parsing for syntax and data sets. - Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – Search (<https://TPO.ehc.jo/api/Lab/Search>)

This search function support direction filtering (new transactions or sent by me). Below is a list of the possible filter parameters that can be utilized in the search criteria:

Parameter	Type	Behavior Description
license	string (query)	This Is the unique identifier given to the transaction payer or provider by the regulator. If value is set, function will return new transactions with exact match of the Sender License.
direction	Integer (\$int32)	Can use two possible values listed below to indicate the direction of the transaction being searched for:

Parameter	Type	Behavior Description
	(query)	• 0 = received transaction • 1 = sent transactions Default value is 0 , unless it is updated by the user.
fromDate	string (query)	If value is set, function will return new transactions with creation date greater than the filter value. If toDate parameter is not set, it would be a minute after the fromDate. • Date time format: DD/MM/YYYY HH:MM • If toDate is not set, the system will return the first 500 transactions from the set fromDate
toDate	string (query)	If value is set, function will return new transactions with creation date less than the filter value. If fromDate parameter is not set, it would be a minute before the toDate. • Date time format: DD/MM/YYYY HH:MM • If fromDate is not set, the system will return the first 500 transactions prior to the set toDate
downloaded	Integer (\$int32) (query)	Can use three possible values listed below to indicate the download status of the transaction being searched for: • 0 = not downloaded • 1 = downloaded • 2 = all Default value is 0 , unless it is updated by the user.
id	string (query)	If value is set, the function will return new transaction with OrderID/ AuthorizationID matching the filter value.
username	string (header)	Username is case sensitive
password	string (header)	Password is case sensitive

Below are the details received in the response whenever the Search is submitted:

Element Name	Type	Description
LAB – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Gets or sets the identifier.
SenderID	string example: LC008	Gets or sets the identifier of the sender.
ReceiverID	string example: LC01	Gets or sets the identifier of the receiver.
RecordCount	integer(\$int32) example: 2	Gets or sets the number of records.
TransactionDate	string example: 21/08/2018 12:13	Gets or sets the transaction date.

Element Name	Type	Description
CreationDate	string example: 21/08/2018 12:17	Gets or sets the creation date.
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions
LAB – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call • False = Validation error occurred
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest. Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets.

Element Name	Type	Description
		Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – View (<https://TPO.ehc.jo/api/Lab/View>)

View individual lab transaction from the post office. you can only view Laboratory Orders assigned to you or generated from you according to direction parameter.

View transaction file. This function takes two parameters:

- **id** (string): Transaction ID user wants to view.
- **direction** (integer): 0 for received transactions, 1 for sent transaction. Default is 0.
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Lab/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Lab/Request Structure](#)

Below are the details received in the response whenever the View is submitted:

Element Name	Type	Description
View/Body		
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.

Element Name	Type	Description
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
Error	Object []	List of Error objects generated from: - JSON parsing for syntax and data sets. - Validation against the TPO business and validation rules published on the community portal

API – PostRequest (<https://TPO.ehc.jo/api/Lab/PostRequest>)

This function used by provider to upload lab request.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Lab/Request Structure](#)

API – EditRequest (<https://TPO.ehc.jo/api/Lab/EditRequest>)

This function used by provider to upload or edit lab request transaction.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Lab/Request Structure](#)

API – PostAuthorization (<https://TPO.ehc.jo/api/Lab/PostAuthorization>)

This function used by payer to upload lab authorization file.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Lab/Response Structure](#)

API – PostResult (<https://tpo.ehc.jo/api/Lab/PostResult>)

This function used by providers to upload lab order results file.

For JSON Object Structure and object parameters descriptions, please refer to below section: [AppendixA/Lab/Request Structure/Lab Result](#)

API – SetDownloaded (<https://TPO.ehc.jo/api/Lab/SetDownloaded>)

This function sets new transaction as downloaded according to transaction ID.

Parameter:

- **id** (string): Transaction ID user wants to set as downloaded
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Authorization/Response Structure](#)

API – ViewLaboratoryOrder (<https://TPO.ehc.jo/api/Lab/ViewLaboratoryOrder>)

This function can only be used by provider of type laboratory to return the Lab order with the activities that are not completed.

Parameter:

- **reference** (string): Order reference ID / Reference Number generated by the TPO.
- **patientIdentity** (string): Patient National Identification number.
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

Below are the details received in the response whenever the ViewLaboratoryOrder is submitted:

Element Name	Type	Description
Entity/ ViewLaboratoryOrder		
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751 aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

API – ViewLabResult (<https://TPO.ehc.jo/api/Lab/ViewLabResult>)

This function can be used by the provider to view the result of the laboratory request.

Parameters:

- **id** (string): Transaction ID.
- **activityId** (string): Unique identifier of activity within the lab (Optional, If user doesn't pass the activity id, the function will return the result for all the activities).

- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

Below are the details received in the response whenever the ViewLabResult is submitted:

Element Name	Type	Description
Entity/ ViewLabResult		
Entities	Object []	List of Result Entities
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

JSON Result Object Structure:

```
{
  "Entities": [
    {
      "ID": "4515609",
      "Result": [
        {
          "Type": "Text",
          "Value": "test"
        }
      ]
    }
  ],
  "StatusCode": 200,
  "Message": "Result Loaded Successfully",
  "Success": true,
  "UserMessage": "Result Loaded Successfully",
  "Error": []
}
```

API – CheckActivityStatus (<https://TPO.ehc.jo/api/Lab/CheckActivityStatus>)

This function can be used by the provider only to check the status for the submitted activities

Parameters:

- **id (string)**: Transaction ID.
- **activityId (string)**: Unique identifier of activity within the Lab (Optional, incase provider want to check the status for specific activity).
- **username (string)**: username case sensitive.
- **password (string)**: password case sensitive.

Below are the details received in the response whenever the CheckActivityStatus is submitted:

Element Name	Type	Description
LAB/ CheckActivityStatus		
Entities	Entities []	List of Result Entities
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license

Element Name	Type	Description
		500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: True = Successful call. False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751 aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	String example: Paid	Entity Status

JSON Result Object Structure:

```
{
  "Entities": [
    {
      "ActivityID": "479",
      "Status": "Pending",
      "ActivityCode": "00214",
      "ActivityDescription": "Procedure Name",
      "DispenseDate": "16/1/2019"
    }
  ],
  "StatusCode": 400,
  "Success": false,
  "Error": []
}
```

Status Expected result: "Complete", "Expired", "Cancelled" and "Pending".

Rad API

API – GetNew (<https://TPO.ehc.jo/api/Rad/GetNew>)

This function takes no parameters. Returns new transactions (not downloaded) up to **500** transaction. Transactions returned according to **user type**. If user is Provider, the function will return the new RadAuthorization transactions. If user is Payer, the function will return new RadRequest transactions.

Below are the details received in the response whenever the GetNew is submitted:

Element Name	Type	Description
Radiology/Entities		
ID	string example: 5abb3a49e6ea191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Provider, Insurer or TPA sending information
ReceiverID	string example: LC01	Provider, Insurer or TPA receiving information
RecordCount	Integer (\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:17	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	A flag in the post office to indicate of the transaction has been downloaded or not. (Returned results: "True" , "False")
Radiology/Result		
StatusCode	Integer (\$int32) example: 200	The operation status. Possible returned status codes: 200 = everything is correct disposition flag is test 201 = everything is correct disposition flag is Production 400 = invalid JSON request, or TPO validation rule error 401 = pass invalid username or unauthorized operation 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: True = Successful call. False = Validation error occurred.

Element Name	Type	Description
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

API – Search (<https://TPO.ehc.jo/api/Rad/Search>)

This search function support direction filtering (new transactions or sent by me). Below is a list of the possible filter parameters that can be utilized in the search criteria:

Parameters	Type	Behavior Description
license	string (query)	It is the unique identifier assigned to the transaction payer or provider by the regulator. If value is set, function will return new transactions with exact match of the Sender License.
direction	Integer (\$int32) (query)	Can use two possible values listed below to indicate the direction of the transaction being searched for: • 0 = received transaction • 1 = sent transactions Default value is 0 , unless it is updated by the user.
fromDate	string (query)	If value is set, function will return new transactions with creation date greater than the filter value. If toDate parameter is not set, it would be a minute after the fromDate. • Date time format: DD/MM/YYYY HH:MM • If toDate is not set, the system will return the first 500 transactions from the set fromDate
toDate	string (query)	If value is set, function will return new transactions with creation date less than the filter value. If fromDate parameter is not set, it would be a minute before the toDate. • Date time format: DD/MM/YYYY HH:MM • If fromDate is not set, the system will return the first 500 transactions prior to the set toDate
downloaded	Integer (\$int32) (query)	Can use three possible values listed below to indicate the download status of the transaction being searched for: • 0 = not downloaded • 1 = downloaded • 2 = all

Parameters	Type	Behavior Description
		Default value is 0 , unless it is updated by the user.
id	string (query)	If value is set, the function will return new transaction with OrderID/ AuthorizationID matching the filter value.
username	string (header)	Username is case sensitive
password	string (header)	Password is case sensitive

Below are the details received in the response whenever the Search is submitted:

Element Name	Type	Description
RADIOLOGY – ENTITIES		
ID	string example: 5abb3a49e6ea191ed4ab5697	Gets or sets the identifier.
SenderID	string example: LC008	Gets or sets the identifier of the sender.
ReceiverID	string example: LC01	Gets or sets the identifier of the receiver.
RecordCount	integer(\$int32) example: 2	Gets or sets the number of records.
TransactionDate	string example: 21/08/2018 12:13	Gets or sets the transaction date.
CreationDate	string example: 21/08/2018 12:17	Gets or sets the creation date.
Downloaded	boolean example: false	Gets or sets a value indicating whether it is downloaded. True = Downloaded Transactions False = Not downloaded Transactions
LAB – RESULT		
StatusCode	integer(\$int32) example: 200	The result status code. Possible returned status codes are: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails

Element Name	Type	Description
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call • False = Validation error occurred
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest. Same reference number generated by the TPO when posting eRx, Lab, or Rad Orders by the Physician.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – View (<https://TPO.ehc.jo/api/Rad/View>)

View transaction file. This function takes two parameters:

- **id** (string): Transaction ID user wants to view.
- **direction** (integer): 0 for received transactions, 1 for sent transaction. Default is 0.
- **username** (string): username case sensitive.
- **password** (string): password case sensitive.

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Rad/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Rad/Request Structure](#)

Below are the details received in the response whenever the View is submitted:

Element Name	Type	Description
View/Body		

Element Name	Type	Description
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal

API – PostRequest (<https://TPO.ehc.jo/api/Rad/PostRequest>)

This function used by provider to upload RadRequest.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Rad/Request Structure](#)

API – PostEditRequest (<https://TPO.ehc.jo/api/RAD/EditRequest>)

This function used by provider to upload or edit Rad Request transaction.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Rad/Request Structure](#)

API – PostAuthorization (<https://TPO.ehc.jo/api/Rad/PostAuthorization>)

This function used by payer to upload RadAuthorization file.

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Rad/Response Structure](#)

API – PostResult (<https://tpo.ehc.jo/api/Rad/PostResult>)

This function used by providers to upload rad order results file.

For JSON Object Structure and object parameters descriptions, please refer to below section:

[AppendixA/Rad/Request Structure/Rad Result](#)

API – SetDownloaded (<https://TPO.ehc.jo/api/Rad/SetDownloaded>)

This function sets new transaction as downloaded according to transaction ID.

Parameter:

- **id** (string): Transaction ID user wants to set as downloaded
- **username** (string): Username is case-sensitive
- **Password** (string): Username is case-sensitive

For JSON Object Structure and object parameters descriptions, please refer to below section Appendix A/Authorization/Response Structure

API – ViewRadiologyOrder (<https://TPO.ehc.jo/api/Rad/ViewRadiologyOrder>)

This function can only be used by provider of type radiology to return the Radiology order with the activities that are not completed.

Parameters:

- **reference** (string): Order reference ID / Reference Number generated by the TPO
- **patientIdentity** (string): Patient National Identification Number.
- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

Below are the details received in the response whenever the View Order (Radiology Use only) is submitted:

Element Name	Type	Description
ViewOrder/Body		
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.

Element Name	Type	Description
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID generated by TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – ViewRadResult (<https://TPO.ehc.jo/api/Rad/ViewRadResult>)

This function can be used by the provider to view the result of the radiology request.

Parameters:

- **id** (string): Transaction ID.
- **activityId** (string): Unique identifier of activity within the rad (Optional, if user doesn't pass the activity id, the function will return the result for all the activities).
- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

Below are the details received in the response whenever the ViewRadResult (Radiology Use only) is submitted:

Element Name	Type	Description
ViewRadResult/Body		
Entities	Object []	List of Result Entities.

Element Name	Type	Description
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: 200 = everything is correct disposition flag is test 201 = everything is correct disposition flag is Production 400 = invalid JSON request, or TPO validation rule error 401 = pass invalid username or unauthorized operation 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: True = Successful call. False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID generated by TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.
Error	Object []	List of Error objects generated from: - JSON parsing for syntax and data sets. - Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

JSON Result Object Structure:

```
{
  "Entities": [
    {
      "ID": "4515609",
      "Result": [
        {
          "Type": "Text",
          "Value": "test"
        }
      ]
    }
  ]
}
```

```

    }
  ]
}
],
"StatusCode": 200,
"Message": "Result Loaded Successfully",
"Success": true,
"UserMessage": "Result Loaded Successfully",
"Error": []
}

```

API – CheckActivityStatus (<https://TPO.ehc.jo/api/Rad/CheckActivityStatus>)

This function can be used by the provider only to check the status for the submitted activities

Parameters:

- **id** (string): Transaction ID.
- **activityId** (string): Unique identifier of activity within the Rad (Optional, incase provider want to check the status for specific activity).
- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

Below are the details received in the response whenever the CheckActivityStatus is submitted:

Element Name	Type	Description
Radiology/ CheckActivityStatus		
Entities	Entities []	List of Result Entities.
StatusCode	integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 429 = transaction Reached viewing Limit for license • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call.

Element Name	Type	Description
		False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c7575 1aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	Object []	Error List
EntityStatus	String example: Paid	Entity Status

JSON Result Object Structure:

```
{
  "Entities": [
    {
      "ActivityID": "479",
      "Status": "Pending",
      "ActivityCode": "00214",
      "ActivityDescription": "Procedure Name",
      "DispenseDate": "16/1/2019"
    }
  ],
  "StatusCode": 400,
  "Success": false,
  "Error": []
}
```

Status Expected result: “Complete”, “Expired”, “Cancelled” and “Pending”.

Dispense API

API – Get New Transactions (GetNew) (<https://tpo.ehc.jo/api/Dispense/GetNew>)

The Get New for Dispense has only one parameter which is “type”. This function Returns new transactions (not downloaded) up to 500 transactions.

Only Payer has access to the GetNew API, the function will return the new Prescription, Radiology, Laboratory transactions based on “type”.

Parameter:

- **Type** (string): Radiology/Laboratory/Prescription

- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

This API was done for the payers to track the Dispensed Transactions so that when a claim is sent later on, the payer can decide to reject or accept based on Dispensed Transaction. The GetNew API is only for Payers. Providers, on the other hand, can use the View API to see what trx's were dispensed from their end.

Below are the details received in the response whenever the GetNew is submitted:

Element Name	Type	Description
Dispense/Entities		
ID	string example: 5abb3a49e6ea191ed4ab5697	Auto-generated Unique identifier provided by the TPO on the successful upload of a given transaction or a file.
SenderID	string example: LC008	Provider, Insurer or TPA sending information
ReceiverID	string example: LC01	Provider, Insurer or TPA receiving information
RecordCount	Integer (\$int32) example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
TransactionDate	string example: 21/08/2018 12:17	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
CreationDate	string example: 21/08/2018 12:17	Created date based on the submit action to the TPO Date/Time Format: DD/MM/YYYY HH:MM
Downloaded	boolean example: false	A flag in the post office to indicate if the transaction has been downloaded or not. (Returned results: "True" , "False")
Dispense/Result		
StatusCode	Integer (\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.

Element Name	Type	Description
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821	This is the Reference Number generated by the TPO. This will be returned when posting ErxRequest, LabRequest, RadRequest.
Error	Object []	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal
EntityStatus	string example: Paid	Entity Status

API – Download Transactions (View) (<https://tpo.ehc.jo/api/Dispense/View>)

View individual Dispense transaction from the post office.

Parameters:

- **Id** (string): transaction id
- **Type** (string): Radiology/Laboratory/Prescription
- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

For JSON Object Structure and object parameters descriptions, please refer to below section [Appendix A/Authorization/Response Structure](#)

API – Dispense Prescription Transaction (<https://tpo.ehc.jo/api/Dispense/ErxDispense>)

Dispense Prescription Transaction.

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Dispense/Prescription/Response Structure](#)

- For payer with direction 0 as a value please refer to [Appendix A/Dispense/Prescription/Request Structure](#)

API – Dispense Laboratory Transaction (<https://tpo.ehc.jo/api/Dispense/LabDispense>)

Dispense Laboratory Transaction.

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Dispense/Lab/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Dispense/Lab/Request Structure](#)

API – Dispense Radiology Transaction (<https://tpo.ehc.jo/api/Dispense/RadDispense>)

Dispense Radiology Transaction.

JSON Object Structure:

- For provider with direction 0 as a value please refer to [Appendix A/Dispense/Rad/Response Structure](#)
- For payer with direction 0 as a value please refer to [Appendix A/Dispense/Rad/Request Structure](#)

API – Set Transaction As Downloaded (<https://tpo.ehc.jo/api/Dispense/SetDownloaded>)

This API is only used by the Payer and it Sets transaction as downloaded. you can only do this action to new transactions assigned to you.

This function sets new transaction as downloaded according to transaction ID.

Parameter:

- **id** (string): Transaction ID user wants to set as downloaded
- **type** (string): Radiology/Laboratory/Prescription
- **username** (string): Username is case-sensitive
- **password** (string): Username is case-sensitive

Attachment API

API – Upload Attachment – Post (<https://tpo.ehc.jo:8000/api/Attachments/UploadAttachment>)

This function can be used by the provider or payer to upload the attachments and share the reference ID through the transaction in order for the receiver to download it using the received ID.

Parameter:

- **File (file):** PDF Attachment Upload

API – Download Attachment - Get

<https://tpo.ehc.jo:8000/api/Attachments/DownloadAttachment/{id}>

This function can be used by the provider or the payer to download the attachment in the received transaction (if available) by using the shared Attachment ID.

Parameter:

- **ID (string):** Attachment Id the User intends to Download.

Appendix A: JSON Object Structure & Fields Descriptions

Claim Object Structure & Fields Descriptions

Request Structure – Claim PostSubmission

```
{
  "Submission": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Claim": [
      {
        "ID": "CL001",
        "IDPayer": "11125524",
        "Type": "Submission",
        "MemberID": "2152021",
        "DispensedID": "6343465",
        "ProviderID": "PR001",
        "Weight": "73.50",
        "NationalIDNumber": "1122112211",
        "Gross": "20.551",
        "PatientShare": "7.051",
        "DateOrdered": "21/08/2020",
        "Net": "11.755",
        "ReferenceNumber": "123123",
        "Encounter": {
          "EncounterID": "5325214214",
          "FacilityID": "FCL331",
          "Type": "2",
          "PatientID": "11245213",

```

```

        "Start": "21/08/2018 12:15",
        "End": "27/08/2018 12:13",
        "StartType": "2",
        "EndType": "1",
        "TransferSource": "Trust Hospital",
        "TransferDestination": "Test Hospital"
    },
    "Diagnosis": [
        {
            "Type": "Principal",
            "Code": "A06.0",
            "DateOfOnset": "18/08/2018"
        }
    ],
    "Activity": [
        {
            "ID": "AC001",
            "Start": "21/08/2018 12:13",
            "Type": "5",
            "Code": "01009-1083-04-101-01",
            "Location": "3",
            "Quantity": "3.00",
            "Net": "11.651",
            "Gross": "20.551",
            "Clinician": "CLA22",
            "PriorAuthorizationID": "PA_Test_PYR00_22",
            "DispensedActivityID": "11241",
            "Observation": [
                {
                    "Type": "LOINC",
                    "Code": "10910-8",
                    "Value": "Test",
                    "ValueType": "Test"
                }
            ]
        }
    ],
    "Resubmission": {
        "attachment": "5aaffff5ea780283848baf2ea",
        "comment": "Sample comment",
        "type": "correction"
    }
}
]
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
SUBMISSION*		
Submission/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID

Element Name	Type	Description
Submission/Claim		
ID*	string maxLength: 50 minLength: 1 example: CL001	Claim ID
IDPayer	string maxLength: 50 minLength: 0 example: 11125524	The unique number assigned by an insurer to identify the Claim
Type*	string pattern: Submission Resubmission Prescription Laboratory Radiology example: Submission	Indicating Submission/Claim type: "Submission" , "Resubmission" , "Prescription" , "Laboratory" , "Radiology"
MemberID	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 2152021	The patient's insurance member number, if the patient is claiming insurance
DispensedID	string example: 6343465	Dispensed ID, this property is Required if claim type = Prescription, or claim type = Laboratory, or claim type = Radiology. Otherwise it is not required.
ProviderID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PR001	ID of the provider claiming from the Payer
Weight*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 73.50	The patient's weight
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 1122112211	The unique National ID Number the government assigns to a citizen
Gross*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 20.551	The total amount of the charges included on the Claim.

Element Name	Type	Description
PatientShare*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 7.051	The amount a patient owes a provider according to the terms of their insurance plan/product
DateOrdered	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2020	The date on which the claim/order is submitted / ordered. Date format: DD/MM/YYYY
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 11.755	The net charges included on the Claim. This is the amount the provider is expected to be paid.
ReferenceNumber	string example: 123123	The unique number assigned to the request dispense. This is the Reference Number generated by the TPO for Lab/Rad/Erx and will ONLY be required when the Submission/Claim/Type field value = Prescription/Laboratory/Radiology.
Submission/Claim/Encounter*		
EncounterID*	string maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a health-care provider assigns to encounter.
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: FCL331	ID of the facility responsible for the Encounter
Type*	string pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 2	Type of the encounter should be one of the following: 1 = No Bed + No emergency room

Element Name	Type	Description
		2 = No Bed + Emergency room 3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
PatientID*	string maxLength: 30 minLength: 1 example: 11245213	The unique number a healthcare provider assigns to a patient
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	EncounterStart is the date and time at which the patient comes under the care of a responsible clinician Date Time format: DD/MM/YYYY HH:MM

Element Name	Type	Description
End*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?)\d{2}:\d{2} example: 27/08/2018 12:13	The time the patient ceases to be under the direct care of a responsible clinician, discharge date and time for inpatients Date Time format: DD/MM/YYYY HH:MM
StartType	string maxLength: 1 minLength: 1 example: 2	Encounter Start Type: 1 = Elective 2 = Emergency 3 = Transfer, i.e., primarily inter-hospital transfers, not between wards within a hospital 4 = Live birth 5 = Still birth 6 = Dead On Arrival 7 = Continuing Encounter
EndType	string maxLength: 1 minLength: 1 example: 1	How the patient was discharged: 1 = Discharged with approval 2 = Discharged against advice 3 = Discharged absent without leave 4 = Discharge transfer to acute care 5 = Deceased 6 = Not discharged 7 = Discharge transfer to non-acute care
TransferSource	string maxLength: 100 minLength: 1 example: Trust Hospital	EncounterTransferSource is the healthcare facility from where a hospital transfer originated (EncounterStartType = 3 Transfer)
TransferDestination	string maxLength: 100	Transfer Destination is the healthcare facility to which a

Element Name	Type	Description
	minLength: 1 example: Test Hospital	hospital transfer is made at the end of an Encounter (EncounterEndType = 4 Transfer)
Submission/Claim/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Principal	The type of diagnosis being recorded from the (ICD) published standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [S]* example: A06.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition. Date format: DD/MM/YYYY
Submission/Claim/Activity		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of activity within a claim
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM

Element Name	Type	Description
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 5	The type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 01009-1083-04-101-01	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Location	string pattern: ^[1-7]\$ example: 3	Activities location: 1 = Inpatient 2 = Outpatient 3 = Emergency 4 = Home 5 = Ambulance 6 = Health Campaign 7 = After Discharge 8 = Operation Room
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 11.651	The net charges billed by the provider to the Payer for this Activity.
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 20.551	The Approved gross value by Payer for this Activity.
Clinician*	string maxLength: 100 minLength: 1 pattern: [\S]* example: CLA22	License number of the Clinician who is providing the treatment or care for the patient
PriorAuthorizationID	string maxLength: 50 minLength: 0 example: PA_Test_PYR00_22	The Prior Authorization ID
DispensedActivityID	string example: 11241	Dispensed Activity ID. This field is required when the claim type is ("Prescription", "Radiology", "Laboratory").

Element Name	Type	Description
		Represents the activity Id from the transaction we want to dispense.
Submission/Claim/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation Value
Submission/Claim/Resubmission		
attachment	string example: 5aaff5ea780283848baf2ea	Attachment provided during the resubmission transaction if necessary
comment*	string maxLength: 2000 minLength: 1 example: Sample comment	Comments entered by the provider during the resubmission transaction
type*	string pattern: correction internal complaint example: correction	Correction or internal complaint

Response Structure – Claim PostRemittance

```
{
  "Remittance": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Claim": [
      {
        "ID": "CL002",
        "IDPayer": "1091088",
        "ProviderID": "PRO012",
        "DenialCode": "AUTH-004",
        "PaymentReference": "225412541SN",
        "DateSettlement": "21/08/2018 12:13",
        "Encounter": {
          "FacilityID": "Test"
        },
        "Activity": [
          {
            "ID": "2Act22",
            "Start": "21/08/2018 12:13",
            "Type": "3",
            "Code": "05744-2644-01-036-01",
            "Quantity": "4.00",
            "Net": "20.505",
            "List": "11.210",
            "Clinician": "CL002",
            "PriorAuthorizationID": "PA_Test_LCC_457",
            "Gross": "17.505",
            "PatientShare": "2.505",
            "PaymentAmount": "20.005",
            "DenialCode": "AUTH-011",
            "Comments": "Waiting period on pre-existing / specific
conditions"
          }
        ]
      }
    ]
  }
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
REMITTANCE*		
Remittance/Header		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-9]):[0-5]?[0-9] example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “TEST” or production “PRODUCTION” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
Remittance/Claim*		
ID*	string maxLength: 50 minLength: 1 example: CL002	Claim ID
IDPayer*	string maxLength: 50 minLength: 0 example: 1091088	The unique number assigned by an insurer to identify the Claim
ProviderID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PRO012	ID of the provider claiming from the Payer

Element Name	Type	Description
DenialCode	string maxLength: 100 minLength: 1 pattern: [\S]* example: AUTH-004	The denial code if the claim is denied by the payer
PaymentReference	string maxLength: 25 minLength: 1 pattern: [\S]* example: 225412541SN	The unique identifier for the payment transaction, which is often the Cheque number
DateSettlement	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date the payer settles the Claim. In general, this will be the date that the payment is made
Remittance/Claim/Encounter		
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: Test	ID of the facility responsible for the Encounter
Remittance/Claim/Activity		
ID*	string maxLength: 30 minLength: 1 example: 2Act22	Unique identifier of activity within a claim
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	The type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 05744-2644-01-036-01	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity*	number(\$double) example: 4.00 Identifies the number of units (quantity) for a specific Activity.	Identifies the number of units (quantity) for a specific Activity.

Element Name	Type	Description
Net*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 20.505	The net charges billed by the provider to the Payer for this Activity.
List	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,2})?\$\$ example: 11.10	ActivityList describes the list price before any adjustments of discounts
Clinician*	string maxLength: 100 minLength: 1 pattern: [\S]* example: CL002	License number of the Clinician who is providing the treatment or care for the patient
PriorAuthorizationID	string maxLength: 50 minLength: 1 pattern: [\S]* example: PA_Test_LCC_457	The Prior Authorization ID
Gross*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 17.505	The total amount of the charges included on the Claim.
PatientShare*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 2.505	Any fee the provider has effectively collected from the patient
PaymentAmount	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 20.005	Amount Approved to be paid by the payer for the activity
DenialCode	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: AUTH-011	The denial code if the Activity is denied by the payer DenailCode must have a value if Activity.Net <> Activity.PaymentAmount
Comments	string maxLength: 2000 minLength: 1 example: Waiting period on pre-existing / specific conditions	Optional comments by the payer (2000 max chars)
Remittance/Result		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.

Element Name	Type	Description
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Response Data Model – **Set Downloaded Parameters**

- **id** – string – Transaction id
- **username** – string - username case sensitive
- **password** – string - password case sensitive

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
SetDownloaded		
SetDownloaded /Result		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will return when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Authorization Object Structure & Fields Descriptions

Request Structure – Post Request

```
{
  "PriorRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Authorization": {
      "Type": "Authorization",
      "ID": "PR_Test_Test2_22121",
      "RequestType": "New",
      "RequestReferenceNumber": "2255416",
      "IDPayer": "54758445",
      "MemberID": "556652",
      "Weight": "84.70",
      "NationalIDNumber": "302894023",
      "DateOrdered": "21/08/2018",
      "Encounter": {
        "EncounterID": "5325214214",
        "FacilityID": "PPR003",
        "Type": "4"
      },
      "Diagnosis": [
        {
          "Type": "Principal",
          "Code": "A06.0",
          "DateOfOnset": "18/08/2018"
        }
      ],
      "Activity": [
        {
          "ID": "Acc123",
          "ActivityReference": "23",
          "Start": "21/08/2018 12:15",
          "Type": "3",
          "Location": "3",
          "Code": "00144",
          "Quantity": "4.00",
          "Unit": "1",
          "Net": "12.445",

```

```

    "Gross": "20.551",
    "Clinician": "CLA011",
    "Duration": "5.50",
    "Observation": [
      {
        "Type": "LOINC",
        "Code": "10910-8",
        "Value": "Test",
        "ValueType": "Test"
      }
    ]
  },
  "Resubmission": {
    "Type": "correction",
    "Comment": "Test Comment",
    "Attachment": "5b6ae93c28c75751aca5f3db"
  }
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
PRIOR-REQUEST*		
priorRequest/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Provider ID
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Insurer or TPA receiving information
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
priorRequest/Authorization*		
Type*	string pattern: Eligibility Authorization Cancellation example: Authorization	Specifies Type using Values: Eligibility, Authorization, Cancellation.
ID*	string maxLength: 50 minLength: 1 example: PR_Test_Test2_22121	Authorization ID
RequestType	string pattern: New Prescription Laboratory Radiology example: New	The Type of Request that the user wants to Authorize can have one of the following values:

Element Name	Type	Description
		1. "New": PriorRequest will be stand-alone transaction that does not authorize any previous transaction. 2. "Prescription": user wants to request authorization for ErxRequest / Prescription Dispense. 3. "Laboratory": user wants to request authorization for LabRequest / Laboratory test. 4. "Radiology": user wants to request authorization for RadRequest / Radiology examination. This field will be required and validated if the Authorization.Type = "Authorization"
RequestReference Number	string example: 2255416	The transaction reference number that user wants to request authorization for it. This field will be required and validated in the below cases: 1. If the Authorization.Type = "Authorization" 2. If the Authorization.Request Type = "Prescription" or "Laboratory" or "Radiology"
IDPayer	string maxLength: 50 minLength: 1 example: 54758445	The unique number assigned by an insurer to identify the Claim, this is the Prior Authorization number. Note: If the transaction is an Authorization Resubmission (a Prior-Request transaction is

Element Name	Type	Description
		considered a Resubmission if the priorRequest/Authorization/Resubmission part is not empty), the IDPayer value must be identical to the Authorization number/ IDPayer obtained from insurer in the response structure field PriorAuthorization/Authorization/IDPayer the first time an Authorization response was received from the insurer. This is used to allow Hospital Admissions staff to add activities to the same Prior-Request using the same Authorization number for easier Management & Tracking from the insurance side.
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 556652	The patient's insurance member number if the patient is claiming insurance
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 84.70	The patient's weight
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 302894023	The unique National ID Number the government assigns to a citizen
DateOrdered*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2018	The date on which the prescription/order is ordered/prescribed Date format: DD/MM/YYYY
priorRequest/Authorization/Encounter		
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PPR003	ID of the facility responsible for the Encounter
Type*	integer(\$int32)	Type of the encounter: check from the portal

Element Name	Type	Description
	pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 4	1 = No Bed + No emergency room 2 = No Bed + Emergency room 3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
EncounterID*	String maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a healthcare provider assigns to an Encounter. The Encounter ID is the physician visit number to link all transactions generated from the same visit for the insurance.
priorRequest/Authorization/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Principal	The type of diagnosis being recorded from the (ICD) published standard used list

Element Name	Type	Description
		Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: A06.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition. Date format: DD/MM/YYYYY
priorRequest/Authorization/Activity		
ID*	string maxLength: 30 minLength: 1 example: Acc123	Unique identifier of activity within an Authorization
ActivityReference	string example: 23	The activity ID from the transaction that user wants to request authorization for. This field will be required and validated in below cases 1. If the Authorization.Type = "Authorization" 2. If the Authorization.Request Type = "Prescription" or "Laboratory" or "Radiology"
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at which Activity started Date Time format: DD/MM/YYYYY HH:MM
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	The type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code

Element Name	Type	Description
		If the Authorization.RequestType = "Prescription" then Type should equal 5 = Drug If the Authorization.RequestType = "Laboratory" or "Radiology" then Type should equal 3 = JMA
Location	string pattern: ^[1-7]\$ example: 3	This Location field is used to identify the type of the visit when this service has been dispensed. This field has been introduced to help Payers differential activities taken / dispensed in the ER versus IP versus discharge prescription versus any other location since each group of activities serviced at different locations are subject to a different set of benefits at the Payer. The location of the activity: 1 = Inpatient 2 = Outpatient 3 = Emergency 4 = Home 5 = Ambulance 6 = Health Campaign 7 = After Discharge 8 = Operation Room
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00144	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 4.00	Identifies the number of units (quantity) for a specific Activity.
Unit	integer(\$int32) example: 1	Identifies the type of units for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$	The net charges billed by the provider to the Payer for this Activity.

Element Name	Type	Description
	example: 12.445	
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$\$ example: 20.551	The activity gross as defined in the pricelist of the insurance plan.
Clinician	string maxLength: 100 minLength: 1 pattern: [\S]* example: CLA011	License number of the Clinician who is providing the treatment or care for the patient
Duration	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 5.50	Identifies the duration in days for the prescribed activity.
priorRequest/Authorization/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation.Value
priorRequest/Authorization/Resubmission		
Type*	string pattern: correction internal complaint example: correction	Correction or internal complaint
Comment*	string maxLength: 2000 minLength: 1 example: Test Comment	Comments entered by the provider during the resubmission transaction

Element Name	Type	Description
Attachment	string example: 5b6ae93c28c75751aca5f3db	Attachment provided during the resubmission transaction if necessary

Response Structure - PostAuthorization

```
{
  "PriorAuthorization": {
    "Header": {
      "SenderID": "string",
      "ReceiverID": "string",
      "TransactionDate": "string",
      "RecordCount": integer,
      "DispositionFlag": "string",
      "PayerID": "string"
    },
    "Authorization": {
      "Result": "string",
      "ID": "string",
      "IDPayer": "string",
      "DenialCode": "string",
      "Start": "string",
      "End": "string",
      "Limit": float,
      "Comments": "string",
      "Activity": [
        {
          "ID": "string",
          "Type": "string",
          "Code": "string",
          "Quantity": float,
          "Net": float,
          "Gross": float,
          "List": float,
          "PatientShare": float,
          "PaymentAmount": float,
          "DenialCode": "string",
          "Observation": [
            {
              "Type": "string",
              "Code": "string",
              "Value": "string",
              "ValueType": "string"
            }
          ]
        }
      ],
      "Comments": "string",
    }
  }
}
```

```

    }
  }
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
PRIOR-AUTHORIZATION		
PriorAuthorization/Header*		
SenderID*	String maxLength: 100 minLength: 1 example: LCO	Payer or TPA ID
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Provider ID
TransactionDate*	String pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a "TEST" or production "PRODUCTION" file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the SenderID is TPA. If SenderID is Insurance, PayerID must be equal to SenderID

Element Name	Type	Description
PriorAuthorization/Authorization*		
Result	String pattern: Yes No example: No	The answer of the inquiry can be one of the following (Yes, No or Pending)
ID*	String maxLength: 50 minLength: 1 example: PA_Test_2254125	Authorization ID
IDPayer	String maxLength: 50 minLength: 1 example: 45674114	The unique number assigned by an insurer to identify the Claim
DenialCode	String pattern: [\S]* example: AUTH-008	The denial code if the claim is denied by the payer.
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at started Date Time format: DD/MM/YYYY HH:MM
End*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at ended Date Time format: DD/MM/YYYY HH:MM
Limit	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 7.5	Identifies the Authorization Limit
Comments	string maxLength: 2000 minLength: 0 example: Test Comment Example	The comments given to add more details on the Authorization
PriorAuthorization/Authorization/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act9958	Unique identifier of activity within an authorization
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	the type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code

Element Name	Type	Description
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00192	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$\$ example: 47.495	The net charges billed by the provider to the Payer for this Activity.
List	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 22.5	ActivityList describes the list price before any adjustments of discounts
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$\$ example: 20.551	The Approved gross value.
PatientShare	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 9.894	Any fee the provider have effectively collected from the patient
PaymentAmount*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$\$ example: 57.233	Amount Approved to be paid by the payer for the activity
DenialCode	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: MNEC-004	The denial code if the Activity is denied by the payer DenailCode must have a value if Activity.Net <> Activity.PaymentAmount
PriorAuthorization/Authorization/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal • Dental • Financial • Grouping • ERX

Element Name	Type	Description
		- Result - Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation Value
PriorAuthorization/Authorization/Activity		
Comments	string maxLength: 2000 minLength: 1 example: Service is not clinically indicated based on good clinical practice, without additional supporting diagnoses/activities	Optional comments by the payer (2000 max chars)
PriorAuthorization/Result		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Response Table – Set Downloaded

Element Name	Type	Description
SETDOWNLOADED		
PriorAuthorization/Result*		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will return when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

ERX Object Structure & Fields Descriptions

Request Structure - Erx PostRequest

```
{
  "ErxRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Prescription": {
      "ID": "Act181",
      "Type": "eRxRequest",
      "ReferenceNumber": "string",
      "Clinician": "CL000",
      "Patient": {
        "MemberID": "441554112",
        "NationalIDNumber": "524865523",
        "ContactNumber": "524865523",

```

```

    "DateOfBirth": "21/08/2010",
    "Weight": "67.00",
    "Email": "Example@tpo.com"
  },
  "Encounter": {
    "EncounterID": "5325214214",
    "FacilityID": "TEST_Hospital",
    "Type": "3"
  },
  "Diagnosis": [
    {
      "Type": "Principal",
      "Code": "A06.0",
      "DateOfOnset": "18/08/2018"
    }
  ],
  "Activity": [
    {
      "ID": "Act3",
      "Type": "5",
      "Code": "03453-1657-10-102-02",
      "Quantity": "5.00",
      "Duration": "4.00",
      "UnitId": "1",
      "Refills": "0",
      "RouteOfAdmin": "ROA075",
      "Instructions": "Test Instruction",
      "Frequency": {
        "UnitPerFrequency": "3.00",
        "FrequencyValue": "2.10",
        "FrequencyType": "Day"
      },
      "Observation": [
        {
          "Type": "LOINC",
          "Code": "10910-8",
          "Value": "Test",
          "ValueType": "Test"
        }
      ],
      "Start": "21/08/2018 12:13"
    }
  ]
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
ERX-REQUEST		
ErxRequest/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Insurer or TPA receiving information
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record, and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a "TEST" or production "PRODUCTION" file based on the selected reserved word

Element Name	Type	Description
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
ErxRequest/Prescription*		
ID*	string maxLength: 50 minLength: 1 example: Act181 Prescription ID	Prescription ID
Type*	string pattern: eRxRequest eRxCancellation example: eRxRequest	Specifies the e-Prescription (Erx) transaction type using Values: eRxRequest, eRxCancellation
ReferenceNumber	String	Transaction Reference Number: This field is used to return prescription reference number with the prescription object. Reference is generated from TPO and no need to send it from provider side (TPO will override any value sent).
Clinician*	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: CL000	In general, the Clinician is the person providing the referral for the patient

Element Name	Type	Description
ErxRequest/Prescription/Patient*		
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 441554112	In the case of an insurance patient: The patient's insurance member number
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 524865523	The unique National ID number the government assigns to a citizen
ContactNumber	String	The personal contact number of the patient Min Length: 0, Max Length:14
DateOfBirth*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2010	This Is the date on which a person was born or is officially deemed to have been born. Example: 21/08/2010
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 67.00	The patient's weight
Email	string pattern: [^@]+@[^\.]+\.\.+ example: Example@tpo.com	The personal email address of the patient
ErxRequest/Prescription/Encounter		
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: TEST_Hospital	ID of the facility responsible for the Encounter
Type*	integer(\$int32) pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 3	Type of the encounter: 1 = No Bed + No emergency room 2 = No Bed + Emergency room

Element Name	Type	Description
		3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
EncounterID*	string maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a healthcare provider assigns to an Encounter. The Encounter ID is the physician visit number to link all

Element Name	Type	Description
		transactions generated from the same visit for the insurance.
ErxRequest/Prescription/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Principal	The type of diagnosis being recorded from the (ICD) published standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: A06.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition. Date format: DD/MM/YYYY
ErxRequest/Prescription/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act3	Unique identifier of activity within a claim

Element Name	Type	Description
Type*	string pattern: ^(5 10)\$ example: 5	ActivityType classifies the type of activity. (Should have the value 5 for Drug or the value 10 for scientific code)
Code*	string maxLength: 100 minLength: 1 pattern: [S]* example: 03453-1657-10-102-02	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 5.00	Identifies the number of units (quantity) for a specific Activity.
Duration	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 4.00	Identifies the duration in days for the prescribed activity
UnitId	integer(\$int32) example: 1	Identifies the type of units for a specific Activity.
Refills	integer(\$int32) example: 0	Identifies the number of refills for a given activity
RoutOfAdmin*	string example: ROA075	Identifies the rout of admin for a given activity
Instructions*	string example: Test Instruction	Identifies the instructions for a given activity as provided by the prescribing clinician
ErxRequest/Prescription/Activity/Frequency		
UnitPerFrequency*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 3.00	Granular unit of the frequency

Element Name	Type	Description
FrequencyValue*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 2.10	Number of repetitions for a given frequency
FrequencyType*	string pattern: Hour Day Week Once example: Day	Frequency time unit
ErxRequest/Prescription/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFrom DRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation.Value
ErxRequest/Prescription/Activity		
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM

Response Structure - ErxPostRequest

```
{
  "StatusCode": "200",
```

```

"Message": "Item Added Successfully",
"Success": "true",
"UserMessage": "Item Added Successfully",
"EntityID": "5b6ae93c28c75751aca5f3db",
"ReferenceNumber": "556821",
"Error": [
  {
    "AdditionalReference": "11453",
    "AdditionalReferenceObjectName": "Claim",
    "Reference": "11453",
    "ReferenceObjectName": "Claim",
    "PropertyName": "ProviderId",
    "PropertyValue": {},
    "RuleCode": "VR08",
    "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
    "ObjectName": "Claim",
    "Transaction": "Submission"
  }
],
"EntityStatus": "Paid"
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
Erx PostREQUEST		
ErxPostRequest		
Status*	integer(\$int32) example: 200 Result status code. Enum:	Array greater than [66]
Message*	string example: Item Added Successfully	Message
Success*	boolean example: true	Success Indicator
UserMessage*	string example: Item Added Successfully	User Message
EntityID*	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber*	string example: 556821 Reference ID.	This will be returned when posting ErxRequest, LabRequest, RadRequest

Element Name	Type	Description
Error	[uniqueItems: false Error List.	description: An error. AdditionalReference string example: 11453 Additional reference. AdditionalReferenceObjectName string example: Claim Additional reference object name. Reference string example: 11453 Error reference. ReferenceObjectName string example: Claim Reference object name. PropertyName string example: ProviderId Property Name. PropertyValue { description: Property value. } RuleCode string example: VR08 Rule code. ErrorText string example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license. Error text. ObjectName string example: Claim Property name Transaction string example: Submission Transaction.
Entity Status	string example: Paid	Entity Status

Request Structure - Erx EditRequest

```
{
  "ErxRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Prescription": {
      "ID": "Act181",
      "Type": "eRxRequest",
      "ReferenceNumber": "string",
      "Clinician": "CL000",
      "Patient": {
        "MemberID": "441554112",
        "NationalIDNumber": "524865523",
        "ContactNumber": "524865523",
        "DateOfBirth": "21/08/2010",
        "Weight": "67.00",
        "Email": "Example@tpo.com"
      },
      "Encounter": {
        "EncounterID": "5325214214",
        "FacilityID": "TEST_Hospital",
        "Type": "3"
      },
      "Diagnosis": [
        {
          "Type": "Principal",
          "Code": "A06.0",
          "DateOfOnset": "18/08/2018"
        }
      ],
      "Activity": [
        {
          "ID": "Act3",
          "Type": "5",
          "Code": "03453-1657-10-102-02",
          "Quantity": "5.00",
          "Duration": "4.00",
          "UnitId": "1",
          "Refills": "0",
          "RoutOfAdmin": "ROA075",
          "Instructions": "Test Instruction",

```

```

    "Frequency": {
      "UnitPerFrequency": "3.00",
      "FrequencyValue": "2.10",
      "FrequencyType": "Day"
    },
    "Observation": [
      {
        "Type": "LOINC",
        "Code": "10910-8",
        "Value": "Test",
        "ValueType": "Test"
      }
    ],
    "Start": "21/08/2018 12:13"
  }
]
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
ERX-EDITREQUEST		
ErxEditRequest/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format:

Element Name	Type	Description
		DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record, and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a "TEST" or production "PRODUCTION" file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
ErxEditRequest/Prescription*		
ID*	string maxLength: 50 minLength: 1 example: Act181	Prescription ID
Type*	string pattern: eRxRequest eRxCancellation example: eRxRequest	Specifies the e-Prescription (Erx) transaction type using Values: eRxRequest, eRxCancellation

Element Name	Type	Description
ReferenceNumber	String	Transaction Reference Number: This field is used to return prescription reference number with the prescription object. Reference is generated from TPO and no need to send it from provider side (TPO will override any value sent).
Clinician*	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: CL000	In general, the Clinician is the person providing the referral for the patient
ErxEditRequest/Prescription/Patient*		
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 441554112	In the case of an insurance patient: The patient's insurance member number
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 524865523	The unique National ID number the government assigns to a citizen
ContactNumber	String	The personal contact number of the patient Min Length: 0, Max Length:14

Element Name	Type	Description
DateOfBirth*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2010	This Is the date on which a person was born or is officially deemed to have been born. Example: 21/08/2010
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 67.00	The patient's weight
Email	string pattern: [^@]+\@[^\.\.]+\. example: Example@tpo.com	The personal email address of the patient
ErxEditRequest/Prescription/Encounter		
EncounterID*	string maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a healthcare provider assigns to an Encounter. The Encounter ID is the physician visit number to link all transactions generated from the same visit for the insurance.
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: TEST_Hospital	ID of the facility responsible for the Encounter
Type*	integer(\$int32) pattern: ^\d{1,2}\$ example: 3	Type of the encounter: 1 = No Bed + No emergency room 2 = No Bed + Emergency room

Element Name	Type	Description
		3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
ErxEditRequest/Prescription/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Principal	The type of diagnosis being recorded from the (ICD) published

Element Name	Type	Description
		standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: A06.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition. Date format: DD/MM/YYYY
ErxEditRequest/Prescription/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act3	Unique identifier of activity within a claim
Type*	string pattern: ^(5 10)\$ example: 5	ActivityType classifies the type of activity. (Should have the value 5 for Drug or the value 10 for scientific code)
Code*	string maxLength: 100	ActivityCode is the code,

Element Name	Type	Description
	minLength: 1 pattern: [\S]* example: 03453-1657-10-102-02	specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 5.00	Identifies the number of units (quantity) for a specific Activity.
Duration	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 4.00	Identifies the duration in days for the prescribed activity
UnitId	integer(\$int32) example: 1	Identifies the type of units for a specific Activity.
Refills	integer(\$int32) example: 0	Identifies the number of refills for a given activity
RoutOfAdmin*	string example: ROA075	Identifies the rout of admin for a given activity
Instructions*	string example: Test Instruction	Identifies the instructions for a given activity as provided by the prescribing clinician
ErxEditRequest/Prescription/Activity/Frequency		
UnitPerFrequency*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 3.00	Granular unit of the frequency
FrequencyValue*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 2.10	Number of repetitions for a given frequency
FrequencyType*	string pattern: Hour Day Week Once example: Day	Frequency time unit
ErxEditRequest/Prescription/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromD	The type of the observation: • LOINC • Text

Element Name	Type	Description
	RG example: LOINC	• File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation Value
ErxEditRequest/Prescription/Activity		
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM

Response Structure - Erx EditRequest

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
```

```

        "AdditionalReferenceObjectName": "Claim",
        "Reference": "11453",
        "ReferenceObjectName": "Claim",
        "PropertyName": "ProviderId",
        "PropertyValue": {},
        "RuleCode": "VR08",
        "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
        "ObjectName": "Claim",
        "Transaction": "Submission"
    }
],
    "EntityStatus": "Paid"
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
Erx EDITREQUEST		
ErxEditRequest		
Status*	integer(\$int32) example: 200 Result status code. Enum:	Array greater than [66]
Message*	string example: Item Added Successfully	Message
Success*	boolean example: true	Success Indicator
UserMessage*	string example: Item Added Successfully	User Message
EntityID*	string example: 5b6ae93c 28c75751aca5f3db	Entity ID
Reference Number*	string example: 556821 Reference ID.	This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[uniqueItems: false Error List.	description: An error. AdditionalReference string example: 11453 Additional reference. AdditionalReferenceObjectName string example: Claim

Element Name	Type	Description
		Additional reference object name. Reference string example: 11453 Error reference. ReferenceObjectName string example: Claim Reference object name. PropertyName string example: ProviderId Property Name. PropertyValue { description: Property value. } RuleCode string example: VR08 Rule code. ErrorText string example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license. Error text. ObjectName string example: Claim Property name Transaction string example: Submission Transaction.
Entity Status	string example: Paid	Entity Status

Response Structure - Erx PostAuthorization

```
{
  "ErxAuthorization": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
```

```

    "TransactionDate": "21/08/2018 12:13",
    "RecordCount": "2",
    "DispositionFlag": "PRODUCTION",
    "PayerID": "PYR0"
  },
  "Authorization": {
    "Result": "No",
    "ID": "PA_Test_2254125",
    "IDPayer": "45674114",
    "DenialCode": "AUTH-008",
    "Start": "21/08/2018 12:15",
    "End": "21/08/2018 12:15",
    "Limit": "7.5",
    "Comments": "Test Comment Example",
    "Activity": [
      {
        "ID": "Act9958",
        "Type": "3",
        "Code": "00192",
        "Quantity": "3.00",
        "Net": "47.495",
        "List": "22.523",
        "Gross": "20.551",
        "PatientShare": "9.894",
        "PaymentAmount": "57.233",
        "DenialCode": "MNEC-004",
        "Observation": [
          {
            "Type": "LOINC",
            "Code": "10910-8",
            "Value": "Test",
            "ValueType": "Test"
          }
        ]
      },
      {
        "Comments": "Service is not clinically indicated based on
good clinical practice, without additional supporting
diagnoses/activities"
      }
    ]
  }
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
ERXAUTHORIZATION		

Element Name	Type	Description
ErxAuthorization/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “TEST” or production “PRODUCTION” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
ErxAuthorization/Authorization*		
Result	string pattern: Yes No example: No	The answer of the inquiry can be one of the following (Yes, No or Pending)
ID*	string maxLength: 50 minLength: 1 example: PA_Test_2254125	Authorization ID
IDPayer	string maxLength: 50	The unique number assigned by an insurer to identify the Claim

Element Name	Type	Description
	minLength: 1 example: 45674114	
DenialCode	string pattern: [\S]* example: AUTH-008	The denial code if the claim is denied by the payer.
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1])?\d{2}:[0-5]? example: 21/08/2018 12:15	The date and time at which Activity started Date Time format: DD/MM/YYYYY HH:MM
End*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1])?\d{2}:[0-5]? example: 21/08/2018 12:15	The date and time at which Activity ended Date Time format: DD/MM/YYYYY HH:MM
Limit	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 7.5	Identifies the Authorization Limit
Comments	string maxLength: 2000 minLength: 0 example: Test Comment Example	The comments given to add more details on the Authorization
ExrAuthorization/Authorization/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act9958	Unique identifier of activity within a claim
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	The type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code.
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00192	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$\$ example: 47.495	The net charges billed by the provider to the Payer for this Activity.

Element Name	Type	Description
List	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 22.5	ActivityList describes the list price before any adjustments of discounts
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 20.551	The Approved gross value.
PatientShare	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 9.894	Any fee the provider has effectively collected from the patient
PaymentAmount*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 57.233	Amount Approved to be paid by the payer for the activity
DenialCode	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: MNEC-004	The denial code if the Activity is denied by the payer DenailCode must have a value if Activity.Net <> Activity.PaymentAmount
ErxAuthorization/Authorization/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM Exc ludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation.Value
ErxAuthorization/Authorization/Activity		

Element Name	Type	Description
Comments	string maxLength: 2000 minLength: 1 example: Service is not clinically indicated based on good clinical practice, without additional supporting diagnoses/activities	Optional comments by the payer (2000 max chars)

Response Table – Set Downloaded

Element Name	Type	Description
SETDOWNLOADED		
ERX/Result*		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Lab Object Structure & Fields Descriptions

Request Structure - Lab PostRequest

```
{
  "LabRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
  },
}
```

```

"Order": {
  "ID": "Lb_Test_223324",
  "Type": "Request",
  "ReferenceNumber": "string",
  "Clinician": "CL3324",
  "Patient": {
    "MemberID": "441554112",
    "NationalIDNumber": "524865523",
    "ContactNumber": "524865523",
    "DateOfBirth": "21/08/2010",
    "Weight": "67.00",
    "Email": "Example@tpo.com"
  },
  "Encounter": {
    "EncounterID": "5325214214",
    "FacilityID": "TEST_ClnC",
    "Type": "4"
  },
  "Diagnosis": [
    {
      "Type": "Principal",
      "Code": "C85.25",
      "DateOfOnset": "18/08/2018"
    }
  ],
  "Activity": [
    {
      "ID": "Acc202",
      "Type": "3",
      "Code": "0015F",
      "Quantity": "2.00",
      "Instructions": "Example on instructions",
      "Observation": [
        {
          "Type": "LOINC",
          "Code": "10910-8",
          "Value": "Test",
          "ValueType": "Test"
        }
      ],
      "Start": "21/08/2018 12:13"
    }
  ]
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LAB-POSTREQUEST		
LabRequest /Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Insurer or TPA receiving information
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-9]):[0-5]?[0-9]\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record, and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “TEST” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
LabRequest/Order*		
ID*	string maxLength: 50 minLength: 1 example: Lb_Test_223324	Order ID
Type*	string pattern: Request Cancellation example: Request	Specifies the order type using Values: Request, Cancellation
ReferenceNumber	String	Transaction Reference Number: This field is used to return the Lab reference number with the Lab object. Reference is generated from TPO and no

Element Name	Type	Description
		need to send it from provider side (TPO will override any value sent).
Clinician*	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: CL3324	In general, the Clinician is the person providing the referral for the patient
LabRequest/Order/Patient*		
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 441554112	In the case of an insurance patient: The patient's insurance member number
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 524865523	The unique number the government assigns to a citizen
ContactNumber	String	The personal contact number of the patient Min Length: 0, Max Length:14
DateOfBirth*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2010	It is the date on which a person was born or is officially deemed to have been born.
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 67.00	The patient's weight
Email	string pattern: [^@]+\@[^\.]+\.\.+ example: Example@tpo.com	The personal email address of the patient
LabRequest /Order/Encounter		
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: TEST_ClnC	ID of the facility responsible for the Encounter
Type*	integer(\$int32) pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 4	Type of the encounter: 1 = No Bed + No emergency room 2 = No Bed + Emergency room 3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room

Element Name	Type	Description
		5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
EncounterID*	string maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a healthcare provider assigns to an Encounter. The Encounter ID is the physician visit number to link all transactions generated from the same visit for the insurance.
LabRequest/Order/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Principal	The type of diagnosis being recorded from the (ICD) published standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: C85.25	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the

Element Name	Type	Description
		Illness or Injury or other condition. Date format: DD/MM/YYYY
LabRequest/Order/Activity		
ID*	string maxLength: 30 minLength: 1 example: Acc202	Unique identifier of activity within an order
Type*	string pattern: 3 example: 3	ActivityType classifies the type of activity. (must have the value 3, JMA)
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 0015F	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 2.00	Identifies the number of units (quantity) for a specific Activity.
Instructions	string example: Example on instructions	Identifies the instructions for a given activity as provided by the prescribing clinician
LabRequest/Order/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation Value

Element Name	Type	Description
LabRequest/Order/Activity		
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-5]?[0-9])? example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYYY HH:MM

Response Structure – Lab PostRequest

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ],
  "EntityStatus": "Paid"
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
Lab POSTREQUEST		
LabPostRequest		
Status*	integer(\$int32) example: 200 Result status code. Enum:	Array greater than [66]
Message*	string example: Item Added Successfully	Message

Element Name	Type	Description
Success*	boolean example: true	Success Indicator
UserMessage*	string example: Item Added Successfully	User Message
EntityID*	string example: 5b6ae93c28c75751aca5f3db	Entity ID
Reference Number*	string example: 556821 Reference ID.	This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[uniqueItems: false Error List.	description: An error. AdditionalReference string example: 11453 Additional reference. AdditionalReferenceObjectName string example: Claim Additional reference object name. Reference string example: 11453 Error reference. ReferenceObjectName string example: Claim Reference object name. PropertyName string example: ProviderId Property Name. PropertyValue { description: Property value. } RuleCode string example: VR08 Rule code. ErrorText string example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license.

Element Name	Type	Description
		Error text.
		Object Name string example: Claim Property name
		Transaction string example: Submission Transaction.
Entity Status	string example: Paid	Entity Status

Request Structure - Lab EditRequest

```
{
  "LabRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Order": {
      "ID": "Lb_Test_223324",
      "Type": "Request",
      "ReferenceNumber": "string",
      "Clinician": "CL3324",
      "Patient": {
        "MemberID": "441554112",
        "NationalIDNumber": "524865523",
        "ContactNumber": "524865523",
        "DateOfBirth": "21/08/2010",
        "Weight": "67.00",
        "Email": "Example@tpo.com"
      },
      "Encounter": {
        "EncounterID": "5325214214",
        "FacilityID": "TEST_ClnC",
        "Type": "4"
      },
      "Diagnosis": [
        {
          "Type": "Principal",
          "Code": "C85.25",

```

```

        "DateOfOnset": "18/08/2018"
    },
    ],
    "Activity": [
        {
            "ID": "Acc202",
            "Type": "3",
            "Code": "0015F",
            "Quantity": "2.00",
            "Instructions": "Example on instructions",
            "Observation": [
                {
                    "Type": "LOINC",
                    "Code": "10910-8",
                    "Value": "Test",
                    "ValueType": "Test"
                }
            ],
            "Start": "21/08/2018 12:13"
        }
    ],
    ]
}
}
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LAB-EditRequest		
LabEditRequest /Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Insurer or TPA receiving information
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-5]?[0-9])? example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount	integer maximum: 2147483647	Number of sub objects in the file. The file may contain at least 1 record and may contain more

Element Name	Type	Description
DispositionFlag	minimum: 0 example: 2 string pattern: PRODUCTION TEST example: PRODUCTION	than one depending on the business and validation rules related to that specific transaction. Flag to determine if the transaction file is either a "TEST" or production "PRODUCTION" file based on the selected reserved word.
PayerID	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.

Response Structure - Lab EditRequest

```

{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ],
  "EntityStatus": "Paid"
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LAB-EditRequest		

Element Name	Type	Description
LabEditRequest /Authorization*		
StatusCode*	integer(\$int32) example: 200 Result status code. Enum: Array [66]	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
Message*	String Example: Item added successfully	Message is displayed
Success*	Boolean Example:True	Success Indicator
User Message	String Example: Item added successfully	Message is displayed
EntityID	string example: 5b6ae93c28c75751aca5f3db	ID of the entity added
ReferenceNumber	string example: 556821	Reference ID. This will returend when posting ErxRequest, LabRequest, RadRequest
EntityStatus	string example: Paid	Payment status of the entity added

Response Structure - Lab PostAuthorization

```
{
  "LabAuthorization": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Authorization": {
      "Result": "No",
      "ID": "PA_Test_2254125",
      "IDPayer": "45674114",
      "DenialCode": "AUTH-008",
      "Start": "21/08/2018 12:15",
      "End": "21/08/2018 12:15",
      "Limit": "7.5",
      "Comments": "Test Comment Example",
      "Activity": [
        {
          "ID": "Act9958",
          "Type": "3",

```

```

"Code": "00192",
"Quantity": "3.00",
"Net": "47.495",
"List": "22.523",
"Gross": "20.551",
"PatientShare": "9.894",
"PaymentAmount": "57.233",
"DenialCode": "MNEC-004",
"Observation": [
  {
    "Type": "LOINC",
    "Code": "10910-8",
    "Value": "Test",
    "ValueType": "Test"
  }
],
"Comments": "Service is not clinically indicated based on
good clinical practice, without additional supporting
diagnoses/activities"
}
]
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LAB-AUTHORIZATION		
LabAuthorization /Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM

Element Name	Type	Description
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “TEST” or production “PRODUCTION” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
LabAuthorization /Authorization*		
Result	string pattern: Yes No example: No	The answer of the inquiry can be one of the following (Yes, No or Pending)
ID*	string maxLength: 50 minLength: 1 example: PA_Test_2254125	Authorization ID
IDPayer	string maxLength: 50 minLength: 1 example: 45674114	The unique number assigned by an insurer to identify the Claim
DenialCode	string pattern: [\S]* example: AUTH-008	The denial code if the Lab is denied by the payer.
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM
End*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at which Activity ended Date Time format: DD/MM/YYYY HH:MM

Element Name	Type	Description
Limit	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 7.5	Identifies the Authorization Limit
Comments	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 7.5	The comments given to add more details on the Authorization
LabAuthorization /Authorization/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act9958	Unique identifier of activity within the lab
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	The type of activity. 3 = JMA; 4 = HCPCS; 5 = Drug; 6 = Dental; 8 = Service Code; 9 = DRG; 10 = Scientific Code.
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00192	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 47.495	The net charges billed by the provider to the Payer for this Activity.
List	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 22.5	ActivityList describes the list price before any adjustments of discounts
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 20.551	The Approved gross value.
PatientShare	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 9.894	Any fee the provider has effectively collected from the patient
PaymentAmount*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 57.233	Amount Approved to be paid by the payer for the activity
DenialCode	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: MNEC-004	The denial code if the Activity is denied by the payer

Element Name	Type	Description
		DenailCode must have a value if Activity.Net <> Activity.PaymentAmount
LabAuthorization /Authorization/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation Value
LabAuthorization /Authorization/Activity		
Comments	string maxLength: 2000 minLength: 1 example: Service is not clinically indicated based on good clinical practice, without additional supporting diagnoses/activities	Optional comments by the payer (2000 max chars)

Request Structure (Post Result) - Lab Result

```
{
  "Header": {
    "SenderID": "LC0",
    "TransactionDate": "22/02/2019 12:13",
    "TransactionReference": "4488877"
  },
  "Result": [
```

```

{
  "Id": "101010",
  "Clinician": "GD5999",
  "ActivityID": "202020",
  "BasicResult": [
    {
      "Type": "File",
      "Value": "5b6ae93c28c75751aca5f3db"
    }
  ]
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
LabResult		
LabResult/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Gets or sets the identifier of the sender.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-5]?[0-9]):[0-5]?[0-9] example: 22/02/2019 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
TransactionReference*	string example: 4488877	Transaction Reference
LabResult/Result*		
ID*	string example: 101010	Generated from the client, should be unique per request
Clinician*	string example: GD5999	Valid clinician license for the one performed the order test
ActivityID*	string example: 202020	Activity ID from the order
LabResult/Result/BasicResult*		
Type*	string pattern: Text File example: File	The type of the result that can be "File" or "Text".
Value*	string example: 5b6ae93c28c75751aca5f3db	The value of the result that can be reference ID for the uploaded file or description text.

Response Table – Set Downloaded

Element Name	Type	Description
SETDOWNLOADED		
LAB/Result*		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Response Structure - Lab Result (TPO Validation)

There is no response from the payer, only TPO validation is sent as a response to this. Because the payer has nothing to respond to.

BASIC RESULT		
Entity	Object	The object we are returning
StatusCode	Integer	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 405 = method not allowed • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	String	Status description message will be returned from the called API method that provide a text description for the status code
Success	Boolean	Indicate the status of the called API method. Returned results are:

BASIC RESULT		
		• True = Successful call. • False = Validation error occurred.
UserMessage	String	End user description message that provide a description for the status code
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal. • Example provided below (JSON Sample: Response with Error)

Rad Object Structure & Fields Descriptions

Request Structure - Rad PostRequest

```
{
  "RadRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Order": {
      "ID": "RR_Test_7769",
      "Type": "Request",
      "ReferenceNumber": "string",
      "Clinician": "CL878",
      "Patient": {
        "MemberID": "441554112",
        "NationalIDNumber": "524865523",
        "ContactNumber": "524865523",
        "DateOfBirth": "21/08/2010",
        "Weight": "67.00",
        "Email": "Example@tpo.com"
      },
      "Encounter": {
        "EncounterID": "5325214214",
        "FacilityID": "TEST_ClnC",
        "Type": "8"
      },
      "Diagnosis": [
        {
          "Type": "Secondary",
          "Code": "B97.0",

```



```

        "DateOfOnset": "18/08/2018"
    },
    ],
    "Activity": [
        {
            "ID": "Act003",
            "Type": "3",
            "Code": "00402",
            "Quantity": "3.00",
            "Instructions": "Example of Instructions",
            "Observation": [
                {
                    "Type": "LOINC",
                    "Code": "10910-8",
                    "Value": "Test",
                    "ValueType": "Test"
                }
            ],
            "Start": "21/08/2018 12:13"
        }
    ]
}

```

Below table provides you brief description about the required JSON object parameter, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
RAD-POSTREQUEST		
radRequest/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time

Element Name	Type	Description
		specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
radRequest/Order*		
ID*	string maxLength: 50 minLength: 1 example: RR_Test_7769 Order ID.	Order ID

Element Name	Type	Description
Type*	string pattern: Request Cancellation example: Request	Specifies the order type using Values: Request, Cancellation
ReferenceNumber	String	Transaction Reference Number:
Clinician*	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: CL878	In general, the Clinician is the person providing the referral for the patient
radRequest/Order/Patient*		
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 441554112	In the case of an insurance patient: The patient's insurance member number
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 524865523	The unique number the government assigns to a citizen
ContactNumber	String	The personal contact number of the patient Min Length: 0, Max Length:14
DateOfBirth*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2010	It is the date on which a person was born or is officially deemed to have been born.
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 67.00	The patient's weight
Email	string pattern: [^@]+\@[^\.]+\.\.+ example: Example@tpo.com	The personal email address of the patient
radRequest/Order/Encounter		
FacilityID*	string maxLength: 100 minLength: 1	ID of the facility responsible for the Encounter

Element Name	Type	Description
	pattern: [\S]* example: TEST_ClnC	
Type*	integer(\$int32) pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 8	Type of the encounter: 1 = No Bed + No emergency room 2 = No Bed + Emergency room 3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In
EncounterID*	string maxLength: 100	The unique number a

Element Name	Type	Description
	minLength: 1 pattern: ^\S*\$ example: 5325214214	healthcare provider assigns to an Encounter. The Encounter ID is the physician visit number to link all transactions generated from the same visit for the insurance.
radRequest/Order/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Secondary	The type of diagnosis being recorded from the (ICD) published standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: B97.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition.

Element Name	Type	Description
		Date format: DD/MM/YYYY
radRequest/Order/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act003	Unique identifier of activity within a claim
Type*	string pattern: 3 example: 3	ActivityType classifies the type of activity. (must have the value 3, JMA)
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00402	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?*\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Instructions	string example: Example of Instructions	Identifies the instructions for a given activity as provided by the prescribing clinician
radRequest/Order/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25	The code describing the

Element Name	Type	Description
	minLength: 1 example: 10910-8	Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation value
radRequest/Order/Activity		
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM

Response Structure – Rad PostRequest

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ],
  "EntityStatus": "Paid"
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
RAD POSTREQUEST		
RADPostRequest		
Status*	integer(\$int32) example: 200 Result status code. Enum:	Array greater than [66]
Message*	string example: Item Added Successfully	Message
Success*	boolean example: true	Success Indicator
UserMessage*	string example: Item Added Successfully	User Message
EntityID*	string example: 5b6ae93c 28c75751aca5f3db	Entity ID
Reference Number*	string example: 556821 Reference ID.	This will returned when posting ErxRequest, LabRequest, RadRequest
Error	[uniqueItems: false Error List.	description: An error. AdditionalReference string example: 11453 Additional reference. AdditionalReferenceObjectName string example: Claim Additional reference object name. Reference string example: 11453 Error reference. ReferenceObjectName string example: Claim Reference object name. PropertyName string example: ProviderId Property Name. PropertyValue { description: Property value.

Element Name	Type	Description
		} RuleCode string example: VR08 Rule code. ErrorText string example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license. Error text. ObjectName string example: Claim Property name Transaction string example: Submission Transaction.
Entity Status	string example: Paid	Entity Status

Request Structure – Rad EditRequest

```

{
  "RadRequest": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Order": {
      "ID": "RR_Test_7769",
      "Type": "Request",
      "ReferenceNumber": "string",
      "Clinician": "CL878",
      "Patient": {
        "MemberID": "441554112",
        "NationalIDNumber": "524865523",
        "ContactNumber": "524865523",
        "DateOfBirth": "21/08/2010",
        "Weight": "67.00",

```

```

    "Email": "Example@tpo.com"
  },
  "Encounter": {
    "EncounterID": "5325214214",
    "FacilityID": "TEST_ClnC",
    "Type": "8"
  },
  "Diagnosis": [
    {
      "Type": "Secondary",
      "Code": "B97.0",
      "DateOfOnset": "18/08/2018"
    }
  ],
  "Activity": [
    {
      "ID": "Act003",
      "Type": "3",
      "Code": "00402",
      "Quantity": "3.00",
      "Instructions": "Example of Instructions",
      "Observation": [
        {
          "Type": "LOINC",
          "Code": "10910-8",
          "Value": "Test",
          "ValueType": "Test"
        }
      ],
      "Start": "21/08/2018 12:13"
    }
  ]
}

```

Below table provides you brief description about the required JSON object parameter, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
RAD-EDIT REQUEST		
radEditRequest/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	The Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID
radEditRequest/Order*		
ID*	string maxLength: 50 minLength: 1 example: RR_Test_7769 Order ID.	Order ID

Element Name	Type	Description
Type*	string pattern: Request Cancellation example: Request	Specifies the order type using Values: Request, Cancellation
ReferenceNumber	String	Transaction Reference Number:
Clinician*	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: CL878	In general, the Clinician is the person providing the referral for the patient
radEditRequest/Order/Patient*		
MemberID*	string maxLength: 30 minLength: 1 pattern: ^\S*\$ example: 441554112	In the case of an insurance patient: The patient's insurance member number
NationalIDNumber*	string maxLength: 50 minLength: 0 pattern: ^\S*\$ example: 524865523	The unique number the government assigns to a citizen
ContactNumber	String	The personal contact number of the patient Min Length: 0, Max Length:14
DateOfBirth*	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2010	It is the date on which a person was born or is officially deemed to have been born.
Weight	number(\$double) pattern: ^\d+(\.\d{1,2})?*\$ example: 67.00	The patient's weight
Email	string pattern: [^@]+@[^\.]+\.\.+ example: Example@tpo.com	The personal email address of the patient
radEditRequest/Order/Encounter		
EncounterID*	string maxLength: 100 minLength: 1 pattern: ^\S*\$ example: 5325214214	The unique number a health-care provider assigns to encounter.

Element Name	Type	Description
FacilityID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: TEST_CInc	ID of the facility responsible for the Encounter
Type*	integer(\$int32) pattern: ^(1 2 3 4 5 6 7 8 9 12 13 15 41 42 45 46 47 48 49)\$ example: 8	Type of the encounter: 1 = No Bed + No emergency room 2 = No Bed + Emergency room 3 = Inpatient Bed + No emergency room 4 = Inpatient Bed + Emergency room 5 = Daycase Bed + No emergency room 6 = Daycase Bed + Emergency room 7 = Nationals Screening 8 = New Visa Screening 9 = Renewal Visa Screening 12 = Home 13 = Assisted Living Facility 15 = Mobile Unit 41 = Ambulance - Land 42 = Ambulance - Air or Water 45 = Laboratory Hospital Walk-In 46 = Radiology Hospital Walk-In 47 = Pharmacy Hospital Walk-In 48 = Physiotherapy Hospital Walk-In 49 = Optics Hospital Walk-In

Element Name	Type	Description
radEditRequest/Order/Diagnosis		
Type*	string pattern: Principal Secondary Admitting example: Secondary	The type of diagnosis being recorded from the (ICD) published standard used list Indicates the type of the diagnosis within this transaction. Possible values are: Principal (Maximum one), Secondary , and Admitting .
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: B97.0	The ICD value for the diagnosis
DateOfOnset	string pattern: \d{2}/\d{2}/\d{4} example: 21/08/2022	The date when insured first experienced a symptom or condition that a Provider might have used to diagnose the Illness or Injury or other condition. Date format: DD/MM/YYYY
radEditRequest/Order/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act003	Unique identifier of activity within an order
Type*	string pattern: 3 example: 3	ActivityType classifies the type of activity. (must have the value 3, JMA)
Code*	string maxLength: 100	ActivityCode is the code,

Element Name	Type	Description
	minLength: 1 pattern: [\S]* example: 00402	specified by ActivityType, for the Activity performed.
Quantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?.\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Instructions	string example: Example of Instructions	Identifies the instructions for a given activity as provided by the prescribing clinician
radEditRequest/Order/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation value
radEditRequest/Order/Activity		
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	The date and time at which Activity started

Element Name	Type	Description
		Date Time format: DD/MM/YYYY HH:MM

Response Structure – Rad EditRequest

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please  
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ],
  "EntityStatus": "Paid"
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
RAD EDITREQUEST		
RadEditRequest		
Status*	integer(\$int32) example: 200 Result status code. Enum:	Array greater than [66]
Message*	string example: Item Added Successfully	Message

Element Name	Type	Description
Success*	boolean example: true	Success Indicator
UserMessage*	string example: Item Added Successfully	User Message
EntityID*	string example: 5b6ae93c28c75751aca5f3db	Entity ID
Reference Number*	string example: 556821 Reference ID.	This will be returned when posting ErxRequest, LabRequest, RadRequest
Error	[uniqueItems: false Error List.	description: An error. AdditionalReference string example: 11453 Additional reference. AdditionalReferenceObjectName string example: Claim Additional reference object name. Reference string example: 11453 Error reference. ReferenceObjectName string example: Claim Reference object name. PropertyName string example: ProviderId Property Name. PropertyValue { description: Property value. } RuleCode string example: VR08 Rule code. ErrorText string example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license.

Element Name	Type	Description
		Error text.
		Object Name string example: Claim Property name
		Transaction string example: Submission Transaction.
Entity Status	string example: Paid	Entity Status

Response Structure - Rad PostAuthorization

```
{
  "RadAuthorization": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Authorization": {
      "Result": "No",
      "ID": "PA_Test_2254125",
      "IDPayer": "45674114",
      "DenialCode": "AUTH-008",
      "Start": "21/08/2018 12:15",
      "End": "21/08/2018 12:15",
      "Limit": "7.5",
      "Comments": "Test Comment Example",
      "Activity": [
        {
          "ID": "Act9958",
          "Type": "3",
          "Code": "00192",
          "Quantity": "3.00",
          "Net": "47.495",
          "List": "22.523",
          "Gross": "20.551",
          "PatientShare": "9.894",
          "PaymentAmount": "57.233",
          "DenialCode": "MNEC-004",

```

```

    "Observation": [
      {
        "Type": "LOINC",
        "Code": "10910-8",
        "Value": "Test",
        "ValueType": "Test"
      }
    ],
    "Comments": "Service is not clinically indicated based on
good clinical practice, without additional supporting
diagnoses/activities"
  }
]
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer Swagger for complete structure and examples.

Element Name	Type	Description
RAD-AUTHORIZATION		
radAuthorization/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Payer or TPA ID
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Provider ID
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.

Element Name	Type	Description
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “TEST” or production “PRODUCTION” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
radAuthorization/Authorization*		
Result	string pattern: Yes No example: No	The answer of the inquiry can be one of the following (Yes, No or Pending)
ID*	string maxLength: 50 minLength: 1 example: PA_Test_2254125	Authorization ID
IDPayer	string maxLength: 50 minLength: 1 example: 45674114	The unique number assigned by an insurer to identify the Claim
DenialCode	string pattern: [\S]* example: AUTH-008	The denial code if the Lab is denied by the payer.
Start*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at which Activity started Date Time format: DD/MM/YYYY HH:MM
End*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:15	The date and time at which Activity ended Date Time format: DD/MM/YYYY HH:MM
Limit	number(\$double) pattern: ^\d+(\.\d{1,2})?\$\$ example: 7.5	Identifies the Authorization Limit

Element Name	Type	Description
Comments	string maxLength: 2000 minLength: 0 example: Test Comment Example	The comments given to add more details on the Authorization
radAuthorization/Authorization/Activity		
ID*	string maxLength: 30 minLength: 1 example: Act9958	Unique identifier of activity within the lab
Type*	string pattern: ^(3 4 5 6 8 9 10)\$ example: 3	ActivityType classifies the type of activity. (must have the value 3, JMA)
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 00192	ActivityCode is the code, specified by ActivityType, for the Activity performed.
Quantity	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 3.00	Identifies the number of units (quantity) for a specific Activity.
Net*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 47.495	The net charges billed by the provider to the Payer for this Activity.
List	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 22.5	ActivityList describes the list price before any adjustments of discounts
Gross*	number(\$double) minimum: 0 pattern: ^\d+(\.\d{1,3})?\$ example: 20.551	The Approved gross value.
PatientShare	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 9.894	Any fee the provider has effectively collected from the patient
PaymentAmount*	number(\$double) pattern: ^\d+(\.\d{1,3})?\$ example: 57.233	Amount Approved to be paid by the payer for the activity
DenialCode	string maxLength: 2147483647 minLength: 1 pattern: [\S]* example: MNEC-004	The denial code if the Activity is denied by the payer DenailCode must have a value if Activity.Net

Element Name	Type	Description
		<> Activity.PaymentAmount
radAuthorization/Authorization/Activity/Observation		
Type*	string pattern: LOINC Text File Universal Dental Financial Grouping ERX Result ROM ExcludeFromDRG example: LOINC	The type of the observation: • LOINC • Text • File • Universal Dental • Financial • Grouping • ERX • Result • Excluded from DRG
Code*	string maxLength: 25 minLength: 1 example: 10910-8	The code describing the Observation value
Value	string maxLength: 2000 minLength: 1 example: Test	The observed value of the Activity
ValueType	string maxLength: 25 minLength: 1 example: Test	Unit of measure for the Observation.Value
radAuthorization/Authorization/Activity		
Comments	string maxLength: 2000 minLength: 1 example: Service is not clinically indicated based on good clinical practice, without additional supporting diagnoses/activities	Optional comments by the payer (2000 max chars)

Request Structure (Post Result) - Rad Result

```
{
  "Header": {
    "SenderID": "LC0",
    "TransactionDate": "22/02/2019 12:13",
    "TransactionReference": "4488877"
  }
}
```

```

},
"Result": [
  {
    "Id": "101010",
    "Clinician": "GD5999",
    "ActivityID": "202020",
    "BasicResult": [
      {
        "Type": "File",
        "Value": "5b6ae93c28c75751aca5f3db"
      }
    ]
  }
]
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
radResult		
radResult/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Gets or sets the identifier of the sender.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-9]):[0-5]?[0-9] example: 22/02/2019 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
TransactionReference*	string example: 4488877	Transaction Reference
radResult /Result*		
ID*	string example: 101010	Generated from the client, should be unique per request
Clinician*	string example: GD5999	Valid clinician license for the one performed the order test
ActivityID*	string example: 202020	Activity ID from the order
radResult /Result/BasicResult*		
Type*	string pattern: Text File example: File	The type of the result that can be "File" or "Text".
Value*	string example: 5b6ae93c28c75751aca5f3db	The value of the result that can be reference ID for the uploaded file or description text.

Response Structure - Rad Result (TPO Validation)

There is no response from the payer, only TPO validation is sent as a response to this. Because the payer has nothing to respond to.

BASIC RESULT		
Entity	Object	The object we are returning
StatusCode	integer(\$int32) example: 200	The operation status. Possible returned status codes: • 200 = everything is correct disposition flag is test • 201 = everything is correct disposition flag is Production • 400 = invalid JSON request, or TPO validation rule error • 401 = pass invalid username or unauthorized operation • 500 = If there is an exception in the code or insert/update/delete to DB fails.
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide a description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal. • Example provided below (JSON Sample: Response with Error)
EntityStatus	string example: Paid	Entity Status

Response Table – Set Downloaded

Element Name	Type	Description
SETDOWNLOADED		
RADIOLOGY/Result*		
StatusCode	integer(\$int32) example: 200	Result status code.
Message	string example: Item Added Successfully	Message.
Success	boolean example: true	Success indicator.
UserMessage	string example: Item Added Successfully	User Message.
EntityID	string example: 5b6ae93c28c75751aca5f3db	EntityID
ReferenceNumber	string example: 556821	Reference ID. This will return when posting ErxRequest, LabRequest, RadRequest
Error	[.....]	Error List
EntityStatus	string example: Paid	Entity status

Dispense Object Structure & Fields Descriptions

Request Structure –Dispense ERX Dispense

There is no response from the payer, only TPO validation is sent as a response to this. Because the payer has nothing to respond to. The payer only keeps the dispense to match with the claim.

```
{
  "PrescriptionDispense": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Dispense": {
      "ID": "AC001",
      "Type": "Dispense",
      "ReferenceNumber": "15151512",
      "DispenseDate": "21/08/2018 12:13",
      "Activity": [
```

```

{
  "ID": "AC001",
  "Type": "5",
  "Code": "03453-1657-10-102-02",
  "ActivityReference": "12451242",
  "Quantity": "5.00",
  "DispensedQuantity": "15.00",
  "Location": "3",
  "PerformerName": "Performer name",
  "AuthorizationID": "34589435",
  "Comments": "Test Comment Example"
}
]
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
PrescriptionDispense		
PrescriptionDispense/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\\d):[0-5]?\\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date/Time Format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST	Flag to determine if the transaction file is either a "TEST" or production "PRODUCTION" file based on the selected reserved word

Element Name	Type	Description
	example: PRODUCTION	
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYRO	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
PrescriptionDispense/Dispense		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of dispense.
Type*	string pattern: ^Dispense\$ example: Dispense	Dispense type
ReferenceNumber	string example: 15151512	This is the eRX/Prescription Reference Number, this number is the one obtained from the TPO once the Physician creates/Posts the prescription. And this is the same eRX number used at the pharmacy to download the prescription.
DispenseDate	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?[0-9]):[0-5]?[0-9] example: 21/08/2018 12:13	Dispense Date. Date Time format: DD/MM/YYYY HH:MM
PrescriptionDispense/Dispense/Activity		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of activity within the eRx: This is generated by the pharmacy system to identify the Activities / Drugs within the dispensed transaction
Type*	string pattern: ^[5 3]\$ example: 5	ActivityType classifies the type of activity. (Should have the value 5 for Drug or the value 10 for scientific code)
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 03453-1657-10-102-02	ActivityCode is the code, specified by ActivityType, for the Activity performed.
ActivityReference	string example: 12451242	Represents the activity Id from the transaction we want to dispense. This is from eRX which has been prescribed by the Physician system . It represents

Element Name	Type	Description
		the activity ID of the drugs / activity in the prescription the pharmacist wants to dispense.
Quantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 5.00	Identifies the number of units (quantity) for a specific Activity.
DispensedQuantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$ example: 15.00	Identifies the number of units (dispensed quantity) for a specific Activity.
Location	string pattern: ^[1-7]\$ example: 3	This Location field is used to identify the type of the visit when this service has been dispensed. This field has been introduced to help Payers differential activities taken / dispensed in the ER versus IP versus discharge prescription versus any other location since each group of activities serviced at different locations are subject to a different set of benefits at the Payer. Activities location: 1 = Inpatient 2 = Outpatient 3 = Emergency 4 = Home 5 = Ambulance 6 = Health Campaign 7 = After Discharge
PerformerName	string maxLength: 50 minLength: 0 example: Performer name	Optional performer name (50 max chars)
AuthorizationID	string example: 34589435	This Authorization ID is obtained from the Payer in the prior Authorization as a reference to the Authorized Activities that the pharmacist wants to dispense. This is not required and not validated in TPO because it is the payer's responsibility to validate the Authorization ID (In the dispense trx) and match it with Prior-Authorization trx (sent from payer to pharmacy).
Comments	string maxLength: 2000 minLength: 1 example: Test Comment Example	Optional comments by the sender (2000 max chars).

Response Structure – Prescription Dispense ERX Dispense

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ]
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
PrescriptionDispense		
PrescriptionDispense/Response		
StatusCode	integer(\$int32) example: 200	Result status code. Examples: • 200 = “Item Added Successfully” • 201 = “Operation Succeeded” • 400 = “Object Validation Errors” • 401 = “Unauthorized” • 405 = “Method not Allowed” • 500 = “DB Operation Failed”
Message	string example: Item Added Successfully	Message. Example: Item Added Successfully

Element Name	Type	Description
		The Messages in the Previous field examples are displayed here depending on the StatusCode.
Success	boolean example: true	Success indicator. True = Success False = Failure
UserMessage	string example: Item Added Successfully	User Message. Example: Item Added Successfully
EntityID	string example: 5b6ae93c28c75751aca5f3db	The Entity ID is the Transaction ID, this is system generated from the TPO and it can be used to view the transaction using the view API. This is the Transaction ID that the user needs to input to view the full trx details using the view API.
ReferenceNumber	string example: 556821	Reference ID
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

Request Structure – Dispense LabDispense

```
{
  "LaboratoryDispense": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Dispense": {
      "ID": "AC001",
      "Type": "Dispense",
      "ReferenceNumber": "15151512",
      "DispenseDate": "21/08/2018 12:13",
      "Activity": [
```

```

{
  "ID": "AC001",
  "Type": "5",
  "Code": "03453-1657-10-102-02",
  "ActivityReference": "12451242",
  "Quantity": "5.00",
  "DispensedQuantity": "15.00",
  "Location": "3",
  "PerformerName": "Performer name",
  "AuthorizationID": "34589435",
  "Comments": "Test Comment Example"
}
]
}
}
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LaboratoryDispense		
LaboratoryDispense/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LCO	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date Time format: DD/MM/YYYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word

Element Name	Type	Description
	example: PRODUCTION	
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
LaboratoryDispense/Dispense		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of dispense.
Type*	string pattern: ^Dispense\$ example: Dispense	Dispense Type.
ReferenceNumber	string example: 15151512	This is the same Reference Number returned by the TPO when posting a LabRequest / When the Physician creates a Lab Order.
DispenseDate	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	Dispense Date. Date Time format: DD/MM/YYYY HH:MM
LaboratoryDispense/Dispense/Activity		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of activity within the Lab Order
Type*	string pattern: ^[5 3]\$ example: 5	ActivityType classifies the type of activity. (Should have the value 3 for activity of type JMA)
Code*	string maxLength: 100 minLength: 1 pattern: [\S]* example: 03453-1657-10-102-02	ActivityCode is the code, specified by ActivityType, for the Activity performed. JMA Code of Lab Activity.
ActivityReference	string example: 12451242	Represents the activity Id from the transaction we want to dispense.
Quantity*	number(\$double) pattern:	Identifies the number of units (quantity) for a specific Activity.

Element Name	Type	Description
	^\d+(\.\d{1,2})?\$_ example: 5.00	
DispensedQuantity*	number(\$double) pattern: ^\d+(\.\d{1,2})?\$_ example: 15.00	Identifies the number of units (dispensed quantity) for a specific Activity.
Location	string pattern: ^[1-7]\$_ example: 3	Activities location: 1 = Inpatient 2 = Outpatient 3 = Emergency 4 = Home 5 = Ambulance 6 = Health Campaign 7 = After Discharge
PerformerName	string maxLength: 50 minLength: 0 example: Performer name	Optional performer name (50 max chars)
AuthorizationID	string example: 34589435	Gets or sets the Authorization id.
Comments	string maxLength: 2000 minLength: 1 example: Test Comment Example	Optional comments by the sender (2000 max chars).

Response Structure - Dispense laboratory transaction. (TPO Validation)

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
    }
  ]
}
```

```

      "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ]
}

```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LaboratoryDispense		
LaboratoryDispense/Response		
StatusCode	integer(\$int32) example: 200	Result status code. Examples: • 200 = "Item Added Successfully" • 201 = "Operation Succeeded" • 400 = "Object Validation Errors" • 401 = "Unauthorized" • 405 = "Method not Allowed" • 500 = "DB Operation Failed"
Message	string example: Item Added Successfully	Message. Example: Item Added Successfully The Messages in the Previous field examples are displayed here depending on the StatusCode.
Success	boolean example: true	Success indicator. True = Success False = Failure
UserMessage	string example: Item Added Successfully	User Message. Example: Item Added Successfully
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	This is the same Reference Number returned by the TPO when posting a LabRequest / When the Physician creates a Lab Order

Element Name	Type	Description
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

Request Structure – Dispense RadDispense.

```
{
  "RadiologyDispense": {
    "Header": {
      "SenderID": "LC0",
      "ReceiverID": "INS00",
      "TransactionDate": "21/08/2018 12:13",
      "RecordCount": "2",
      "DispositionFlag": "PRODUCTION",
      "PayerID": "PYR0"
    },
    "Dispense": {
      "ID": "AC001",
      "Type": "Dispense",
      "ReferenceNumber": "15151512",
      "DispenseDate": "21/08/2018 12:13",
      "Activity": [
        {
          "ID": "AC001",
          "Type": "5",
          "Code": "03453-1657-10-102-02",
          "ActivityReference": "12451242",
          "Quantity": "5.00",
          "DispensedQuantity": "15.00",
          "Location": "3",
          "PerformerName": "Performer name",
          "AuthorizationID": "34589435",
          "Comments": "Test Comment Example"
        }
      ]
    }
  }
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
RadiologyDispense		

Element Name	Type	Description
RadiologyDispense/Header*		
SenderID*	string maxLength: 100 minLength: 1 example: LC0	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string maxLength: 100 minLength: 1 example: INS00	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
TransactionDate*	string pattern: \d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d example: 21/08/2018 12:13	System generated date and time specifying when the transaction was generated. Date Time format: DD/MM/YYYY HH:MM
RecordCount*	integer(\$int32) maximum: 2147483647 minimum: 0 example: 2	Number of sub objects in the file. The file may contain at least 1 record and may contain more than one depending on the business and validation rules related to that specific transaction.
DispositionFlag*	string pattern: PRODUCTION TEST example: PRODUCTION	Flag to determine if the transaction file is either a “ TEST ” or production “ PRODUCTION ” file based on the selected reserved word
PayerID*	string maxLength: 100 minLength: 1 pattern: [\S]* example: PYR0	PayerID is the Insurer License if the ReceiverID is TPA. If ReceiverID is Insurance, PayerID must be equal to ReceiverID.
RadiologyDispense/Dispense		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of dispense.
Type*	string pattern: ^Dispense\$ example: Dispense	Dispense type
ReferenceNumber	string example: 15151512	This is the same Reference Number returned by the TPO when posting a RadRequest / When the Physician creates a Rad Order.
DispenseDate	string pattern: \d{2}/\d{2}/\d{4}	Dispense Date. Date Time format: DD/MM/YYYY HH:MM

Element Name	Type	Description
	(20 21 22 23 [0-1]?\\d):[0-5]?\\d example: 21/08/2018 12:13	
RadiologyDispense/Dispense/Activity		
ID*	string maxLength: 30 minLength: 1 example: AC001	Unique identifier of activity within the Rad Order
Type*	string pattern: ^[5 3]\$ example: 5	ActivityType classifies the type of activity. (Should have the value 3 for activity of type JMA)
Code*	string maxLength: 100 minLength: 1 pattern: [\\S]* example: 03453-1657-10-102-02	ActivityCode is the code, specified by ActivityType, for the Activity performed. JMA Code of Rad Activity.
ActivityReference	string example: 12451242	Represents the activity Id from the transaction we want to dispense.
Quantity*	number(\$double) pattern: ^\\d+(\\.\\d{1,2})?\$ example: 5.00	Identifies the number of units (quantity) for a specific Activity.
DispensedQuantity*	number(\$double) pattern: ^\\d+(\\.\\d{1,2})?\$ example: 15.00	Identifies the number of units (dispensed quantity) for a specific Activity.
Location	string pattern: ^[1-7]\$ example: 3	Activities location: 1 = Inpatient 2 = Outpatient 3 = Emergency 4 = Home 5 = Ambulance 6 = Health Campaign 7 = After Discharge
PerformerName	string maxLength: 50 minLength: 0 example: Performer name	Optional performer name (50 max chars)
AuthorizationID	string example: 34589435	Gets or sets the Authorization id.

Element Name	Type	Description
Comments	string maxLength: 2000 minLength: 1 example: Test Comment Example	Optional comments by the sender (2000 max chars).

Response Structure - Dispense Radiology transaction. (TPO Validation)

```
{
  "StatusCode": "200",
  "Message": "Item Added Successfully",
  "Success": "true",
  "UserMessage": "Item Added Successfully",
  "EntityID": "5b6ae93c28c75751aca5f3db",
  "ReferenceNumber": "556821",
  "Error": [
    {
      "AdditionalReference": "11453",
      "AdditionalReferenceObjectName": "Claim",
      "Reference": "11453",
      "ReferenceObjectName": "Claim",
      "PropertyName": "ProviderId",
      "PropertyValue": {},
      "RuleCode": "VR08",
      "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
      "ObjectName": "Claim",
      "Transaction": "Submission"
    }
  ]
}
```

Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
RadiologyDispense		
RadiologyDispense/Response		
StatusCode	integer(\$int32) example: 200	Result status code. Examples: 200 = "Item Added Successfully" 201 = "Operation Succeeded"

Element Name	Type	Description
		• 400 = "Object Validation Errors" • 401 = "Unauthorized" • 405 = "Method not Allowed" • 500 = "DB Operation Failed"
Message	String example: Item Added Successfully	Message. Example: Item Added Successfully The Messages in the Previous field examples are displayed here depending on the StatusCode.
Success	boolean example: true	Success indicator. True = Success False = Failure
UserMessage	string example: Item Added Successfully	User Message. Example: <i>Item Added Successfully</i>
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID.
ReferenceNumber	string example: 556821 Reference ID.	This is the same Reference Number returned by the TPO when posting a RadRequest / When the Physician creates a Rad Order.
Error	Object []	Error List
EntityStatus	string example: Paid	Entity Status

Attachment Object Structure & Fields Descriptions:

Response Structure – Upload Attachment

```
{
```



```

"StatusCode": "200",
"Message": "Item Added Successfully",
"Success": "true",
"UserMessage": "Item Added Successfully",
"EntityID": "5b6ae93c28c75751aca5f3db",
"ReferenceNumber": "556821",
"Error": [
  {
    "AdditionalReference": "11453",
    "AdditionalReferenceObjectName": "Claim",
    "Reference": "11453",
    "ReferenceObjectName": "Claim",
    "PropertyName": "ProviderId",
    "PropertyValue": {},
    "RuleCode": "VR08",
    "ErrorText": "Claim ProviderId must be valid provider, Please
fix ProviderId be a valid provider license.",
    "ObjectName": "Claim",
    "Transaction": "Submission"
  }
]
}

```

Below table provides you brief description about the returned JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
Tpo.Shared.Entities.Result		
UploadAttachment/Response		
StatusCode	integer(\$int32) example: 200	Result status code. Examples: • 200 = "Item Added Successfully" • 201 = "Operation Succeeded" • 400 = "Object Validation Errors" • 401 = "Unauthorized" • 405 = "Method not Allowed" • 500 = "DB Operation Failed"
Message	String example: Item Added Successfully	Message. Example: Item Added Successfully The Messages in the Previous field examples are displayed here depending on the StatusCode.

Element Name	Type	Description
Success	Boolean example: true	Success indicator. True = Success False = Failure
UserMessage	String example: Item Added Successfully	User Message. Example: <i>Item Added Successfully</i>
EntityID	String example: 5b6ae93c28c75751aca5f3db	This is the AttachmentID that will be used to download the attachment.
ReferenceNumber	String example: 556821	This is the same Reference Number returned by the TPO when posting a Rad/Lab Request, i.e. when the Physician creates a Rad/Lab Order.
UploadAttachment/Response/Error		
AdditionalReference	String example: 11453	Additional Reference
AdditionalReferenceObjectName	String example: Claim	Additional reference object name. Example: Claim
Reference	String example: 11453	Error reference. Example: 11453
ReferenceObjectName	String example: Claim	Reference object name. Example: Claim
PropertyName	String example: ProviderId	Property Name. Example: ProviderID
PropertyValue	String	Property value.
RuleCode	String example: VR08	Rule code. Example: VR08
ErrorText	String example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license.	Error Message description. Example: Claim ProviderId must be valid provider, Please fix ProviderId be a valid provider license.
ObjectName	String example: Claim	Object Name Example: Claim
Transaction	String example: Submission	Name of the transaction (Submission, PriorRequest, etc.).
EntityStatus	String example: Paid	Entity Status

Response Structure – Download Attachment

{
Below table provides you brief description about the required JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
LAB-REQUEST		
LabRequest	/Header*	
SenderID*	string	
maxLength:	100	
minLength:	1	
example:	LC0	Unique identifier of the Provider, Payer or TPA receiving information, as provided by the regulator.
ReceiverID*	string	
maxLength:	100	
minLength:	1	
example:	INS00	Insurer or TPA receiving information
TransactionDate*	string	
pattern:	\d{2}/\d{2}/\d{4} (20 21 22 23 [0-1]?\d):[0-5]?\d	
example:	21/08/2018 12:13	System generated date and time specifying when the transaction was generated.
Date/Time Format:	DD/MM/YYYY HH:MMu	"StatusCode": 401,
		"Message": "Invalid Token or Username or Password",
		"Success": false,
		"UserMessage": "Invalid Token or Username or Password",
		"Error": []

Below table provides you brief description about the returned JSON object parameters, and you can refer to Swagger for complete structure and examples.

Element Name	Type	Description
Download RESULT		
StatusCode	integer(\$int32) example: 200	The operation status. Possible returned status codes: • 200 = Success • 401 = Invalid Token or Username or Password • 404 = Attachment not Found • 429 = Attachment Reached viewing Limit for license
Message	string example: Item Added Successfully	Status description message will be returned from the called API method that provide a text description for the status code

Element Name	Type	Description
Success	boolean example: true	Indicate the status of the called API method. Returned results are: • True = Successful call. • False = Validation error occurred.
UserMessage	string example: Item Added Successfully	End user description message that provide a description for the status code
EntityID	string example: 5b6ae93c28c75751aca5f3db	Entity ID
ReferenceNumber	string example: 556821	Reference ID
Error	Object	List of Error objects generated from: • JSON parsing for syntax and data sets. • Validation against the TPO business and validation rules published on the community portal. • Example provided below (JSON Sample: Response with Error)
EntityStatus	string example: Paid	Entity Status