

ICANN Centralized Zone Data Service REST API (CZDS REST API)

Version 1.0.4
2018-12-04

1.	Introduction	3
1.1.	Credentials	3
1.2.	Internet Protocol	3
1.3.	Secure Communication	3
2.	Common elements used in this specification	3
3.	Authentication	4
3.1.	Obtaining a token	4
3.2.	Token Expiration	5
4.	Authorization	6
5.	Getting zone(s) information	7
5.1.	Listing zone download links	7
5.2.	Getting a zone file	8
5.3.	Checking zone file size	9

Document Revision History

Version	Publishing date	Description of the change	Projected date to start with the version of the specification in production
1.0	2018/10/19	First version.	
1.0.1	2018/11/26	Fix the authenticate curl example on page 5 and getting zone file <code>gzip</code> parameter on page 8.	
1.0.2	2018/11/28	Update the description on zone file compression in Section 5.2	
1.0.3	2018/11/29	Update Session 5.2 to remove "Accept-Encoding: <code>gzip</code> ". The zone file from the server is already compressed. It is not necessary to specify <code>gzip</code> accept-encoding.	
1.0.4	2018/12/04	Add a new section - 5.3 Checking zone file size. Update <code>access_token</code> lifetime to 24 hours.	

1. Introduction

This document describes the REST API provided by ICANN to the registered Centralized Zone Date Service (CZDS) users to download their authorized zone files.

1.1. Credentials

The CZDS Authentication API uses the same credentials as the CZDS portal site to authenticate the users. However, there is no REST API for managing the user's credentials. Any credential management operation, such as, resetting password, must go through the CZDS portal site.

1.2. Internet Protocol

The CZDS REST API supports IPv4 transport only.

1.3. Secure Communication

In order to provide confidentiality, server authentication, and integrity in the communication channel, only HTTPS is available for CZDS REST API.

2. Common elements used in this specification

In the following section, common elements used in this specification are described:

- **<auth_url>**: the URL where a registered user can obtain a token that is required by CZDS REST API.

Note: the URL for the Testbed: <https://account-api-test.icann.org/api/authenticate>

- **<username>**: the `username` registered on CZDS.
- **<password>**: the `password` credential for the user.
- **<base_url>**: the base URL of the CZDS REST API.

Note: the URL for the Testbed: <https://czds-api-test.icann.org>

- **<accessToken>**: A JSON Web token (JWT) as described in RFC 7519. A JWT is represented as a sequence of URL-safe parts separated by period ('.') characters. Each part contains a base64url-encoded value.

The `<accessToken>` can be obtained by invoking the authentication API with valid CZDS user credential. It is required to perform operations on CZDS REST API to list download links and download zone files.

- **<tld>**: Name of the TopLevel Domain or zone.
- **<exp_claim_value>**: The value of the `exp` claim of `<accessToken>` that indicates the lifetime of the token.

3. Authentication

The CZDS REST API is based on OAuth 2.0 Authorization framework as described in RFC 6749. This section describes how to obtain an Access Token with the user's credential. The credential is only needed when requesting a token. The rest of the API calls require the access token obtained here.

3.1. Obtaining a token

POST `<auth_url>`

Obtains an access token.

Parameters:

The following parameters must be provided in the request body:

- `"username": "<value>"`

Username registered in the CZDS

- `"password": "<value>"`

Password for username registered in the CZDS

The following headers must be provided in POST Method:

- `"Content-Type: application/json"`
- `"Accept: application/json"`

Possible results:

- HTTP 200, when a valid request is received (`username` and `password` from the CZDS are correct), the API method `<auth_url>` sets HTTP header Content-type to `"application/json"`, returns HTTP 200 code and provides a JSON object in the body with following keys:

`"accessToken": "<value>"` where value is a JWT token (A sequence of URL-safe parts separated by period ('.') characters)
- HTTP 400, the `<auth_url>` API method provides an HTTP 400 (Bad Request) status code when the request is malformed.

- HTTP 401, the <auth_url> API method provides an HTTP 401 status code when invalid credentials are provided. There is no text response in the body.
- HTTP 415, when unsupported content type header is sent, the API method <auth_url> sets HTTP header Content-type to "application/json", returns HTTP 415 code and provides a JSON object with following keys:
 - "timestamp": text value with timestamp of transaction
 - "status": 415
 - "error": Unsupported media type
 - "message": text value with error message
 - "path": text value with path from URL
- HTTP 500, the <auth_url> API method provides an HTTP 500 status code when an Internal Server Error is found.

Example using curl (<https://curl.haxx.se/>) for a authentication request:

Request Example:

```
curl -i -X POST \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
-d '{
  "username": "cindy.riley41@example.com",
  "password": "t1pWtpkEj8NT2#m"
}' https://account-api-test.icann.org/api/authenticate
```

Response Example:

```
{
  "accessToken":
  "eyJraWQiOiI5UUR4ci16dH1Lb1lHVEE0LS1HR3FqQ3dUVk1Fc0MxRXJNb3VtV1NEM1NBiwiYWxnIjoiUlMyNTYifQ.eyJ2ZXIiOiJEsImp0aSI6IkFULjYwdGd0MXPjQW1lRkdoUFRsSTRUTlprRHpQVhNVT0MyalFTS1mMlp0VWU1LCJpc3MiOiJodHRwczovL2Rldi05ODcyNDkub2t0YXByZXZpZXcuY29tL29hdXR0Mi9hdXNnaW42aDZ2ZzJxdkliUTBoNyIsImFlZCI6Imh0dHBzOi8vYXBpdGVzdGJlZC5pY2Fubi5vcmcicjJpYXQiOiE1NDIzMDc2MjQsImV4cCI6MTU0MjMxMTIyNCwiY2lkIjoiMG9hZ25lcTc0M2Q0T1BVVWgwaDciLCJlaWQiOiIwMHVnaWpzeDhrcFJEb1RVRTBoNyIsInNjcCI6WyJpY2Fubi1jdXN0b20iLCJvcGVuaWQiXSwic3ViIjoiZG9uZ211aS5jYW9AaWNhbm4ub3JnIiwiz212ZW5fbmFtZSI6IkRvbmdtZWkiLCJmYW1pbH1fbmFtZSI6IkNhbyIsImVtYWlsIjoiZG9uZ211aS5jYW9AaWNhbm4ub3JnIn0.NJtVnGTtpzJOClzwnw-eRjL15W5ytzg7-ZQ5tYypMuFxyP_wwgMq2tKGTi8OQdCaw9JkVzGijVRvSUGuM_aIplON5uQZIBCR59wRqPoK6H0S1Ds3IKLQSSyxRbZXwW3MXmuw1lqocBfNFwLdmUNmmuJf1RsLK4WO-OWmuOtRJPReJ3jbLv67XPNKau1QaHSvLa-2rQrpEddNxDnJuaUoZ10m3b1lmpUqlQR2JRBSr5kddsJ1uIWLrJOin-IRQEx0EyS0zOmCUeLY8N46VRmzr5WMpm0dLgrvOZRZTNK9NusP6aG6vjdTGLcIz6GHn4gdPv19s_H90Rod2cWehVoVQ"
```

Note: Every successful authentication API call will generate a brand new token.

3.2. Token Expiration

The <accessToken> obtained by the authentication API call is invalid after its expiration time which is 24 hours after the token is created.

The expiration time of the `<accessToken>` is specified by the `exp` (Expiration time) Claim. JWT claims are described in [section 4 of RFC 7519](#).

The `exp` Claim from `<accessToken>` can be obtained by following next steps:

1. Get a new `<accessToken>` using the `<auth_url>` of the CZDS RST API.

Example using curl (<https://curl.haxx.se/>) for a login request, and using sed and awk commands for output formatting:

```
access_token=`curl -d '{"username":"<username>","password":"<password>"}' -s -H
"Content-Type: application/json" -X POST
https://accounts-api-test.icann.org/api/authenticate | sed "s/\"//g" | sed "s/:/
/g" | awk '{print $2}' | sed 's/}//g'`
```

Note. The value of the `<accessToken>` is stored on `access_token` variable.

2. Obtain JWT payload from the `<accessToken>`

Example using sed and awk commands for output formatting:

```
jwt_payload=`echo ${access_token} | sed "s/\"./ /g" | awk '{print $2}'`
```

Note. The second URL-safe part of the `<accessToken>` is obtained and stored on `jwt_payload` variable

3. Decode base64url value obtained from JWT payload.

Example using node.js base64-url-cli (<https://www.npmjs.com/package/base64-url-cli>) for base64-url decoding.

```
base64url decode ${jwt_payload}
```

Note. The command will provide a JSON object where “`exp`” Claim can be parsed.

4. Convert datetime value from `exp` key from JSON object.

Example using GNU date:

```
date -d @<exp_claim_value>
```

4. Authorization

When sending a request to the CZDS REST API, the client must set HTTP header "Authorization: Bearer `<accessToken>`", where `<accessToken>` is the token obtained in the authentication API call described in the previous section.

The following response may be returned by the API call:

- HTTP/401, when no valid bearer token <accessToken>) is provided, the API method provides an HTTP/401 status code, sets the HTTP header Content-type to "text/dns". No text response is provided in the "HTTP body:".

5. Getting zone(s) information

This section describes the REST API to access the zone information in CZDS.

5.1. Listing zone download links

GET <base_url>/czds/downloads/links

Lists all the zone file download links that are authorized for the user.

Parameters:

The following headers must be provided in GET Method:

- "Authorization: Bearer <accessToken>"

Possible results:

HTTP/200, when a valid request is received, the <base_url>/czds/downloads/links API method provides an HTTP/200 status code and sets the HTTP header Content-type to "application/json; charset=UTF-8".

If a valid request is received, a JSON array with a list of authorized download zone URLs is returned in the HTTP body. For example:

```
[
  "<base_url>/czds/downloads/<tld>.zone",
  "<base_url>/czds/downloads/<tld>.zone"
]
```

Each URL in this list can be used to retrieve the respective zone file.

- HTTP 400, the <base_url> API method provides an HTTP 400 (Bad Request) status code when the request is malformed.
- HTTP 500, the <base_url>/czds/downloads/links API method provides an HTTP 500 status code when an Internal Server Error is found.

Example using curl to request list of links for authorized zones:

Request Example:

```
curl -i -X GET \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
```

```
-H "Authorization: Bearer
eyJraWQiOiI5UUR4ci16dH1LbjlhVVEE0LS1HR3FqQ3dUVVklFc0MxRXJNb3VtV1NEM1NBiwiYWxnIjoilMyNTY
ifQ.eyJ2ZXIiOiJEsImp0aSI6IklFULjYwdGd0MXpJQWllRkdoUFRsSTRUTlprRHpQVknVT0MyalFTSilmM1p0VVU
iLCJpc3MiOiJodHRwczovL2Rldi05ODcyNDkub2t0YXByZXZpZXcuY29tL29hdXR0Mi9hdXNnaW42aDZ2ZzJxdk
liUTBoNyIsImF1ZCI6Imh0dHBzOi8vYXBpdGVzdGJlZC5pY2Fubi5vcmcilLCJpYXQiOiJlNDIzMjc2MjQsImV4c
CI6MTU0MjMxMTIyNCwiY2lkIjoimG9hZ251cTc0M2Q0T1BVVWgwaDciLCJlaWQiOiIwMHVnaWpzeDhrcFJEb1RV
RTBoNyIsInNjcCI6WyJpY2FubiljdXN0b20iLCJvcGVuaWQiXSwic3ViIjoizG9uZ211aS5jYW9AaWNhbm4ub3J
nIiwiz212ZW5fbmFtZSI6IkrvbmtdZWkiLCJmYW1pbHlfbmFtZSI6IkhbyIsImVtYWlsIjoizG9uZ211aS5jYW
9AaWNhbm4ub3JnIn0.NJtVnGTtpzJOCzwnw-eRjL15W5ytzg7-ZQ5tYypMuFxyP_wwgMq2tKGTi8OQdCaw9Jk
VzGijVRvSUguM_aIplON5uQZIBCR59wRqPoK6H0S1Ds3IKLQSSYxRbZXW3MXmuw1lqocBfNFwLdmUNmmuJflRs
LK4WO-OWmuOtRJPReJ3jbLv67XPNKauiaHSvLa-2rQrpEddNxDnJuaUoZ10m3b1lmpUqlQR2JRBSr5kddsJ1uI
WLRJ0in-IRQEx0EyS0zOmCUeLY8N46VRmzr5WMpm0dLgrvOZRZTNK9NusP6aG6vjdTGLcIz6GHn4gdPv19s_H90
ROd2cWehVoVQ" \
https://czds-api-test.icann.org/czds/downloads/links
```

Response Example:

```
[
  "https://czds-api-test.icann.org/czds/downloads/example1.zone",
  "https://czds-api-test.icann.org/czds/downloads/example2.zone"
]
```

5.2. Getting a zone file

GET <base_url>/czds/downloads/<tld>.zone

Download the zone file for the given TLD. The downloaded file is in `gzip` format.

Parameters:

The following header must be provided in GET Method:

- "Authorization: Bearer <accessToken>"

Possible results:

- HTTP/200, when a valid request is received, the <base_url>/czds/downloads/<tld>.zone API method provides an HTTP/200 status code, sets the HTTP header Content-type to "text/dns" and provides in the HTTP body the contents of the zone file in `gzip` format.
- HTTP 400, the <auth_url>API method provides an HTTP 400 (Bad Request) status code when the request is malformed.
- HTTP/403, when the requested zone does not exist or the username that generated the <accessToken> has no permissions to download that zone in the CZDS system, the API method <base_url>/czds/downloads/<tld>.zone provides an HTTP/403 status code and sets the HTTP header Content-type to text/dns. No text response is provided in the "HTTP body:".
- HTTP/409, the <base_url>/czds/downloads/<tld>.zone API method provides an HTTP/409 status code when the username that generated <accessToken> has not accepted the new Terms & Condition on the CZDS system. The user will need to log in the CZDS portal to accept Terms & Conditions before use this API method.

Examples using CURL to request a zone file:

Request Example:

```
curl -i -X GET \
-H "Authorization: Bearer
eyJraWQiOiI5UUR4ci16dH1Lb1lHVVEE0LS1HR3FqQ3dUVk1Fc0MxRXJNb3VtV1NEM1NBiwiYWxnIjoiUlMyNTYifQ.eyJ2ZXIiOiJEsImp0aSI6IkdFb1lRkdoUFRsSTRTUlprRHpQVknVT0MyalFTSi1mM1p0VVUilCJpc3MiOiJodHRwczovL2Rldi05ODcyNDkub2t0YXByZXZpZDcuY29tL29hdXRoMi9hdXNnaW42aDZ2ZzJxdkliUTBoNyIsImF1ZCI6Imh0dHBzOi8vYXBpdGVzdGJlZC5pY2Fubi5vcnciLCJpYXQiOiJlNDIzMDC2MjQsImV4cCI6MTU0MjMxMTIyNCwiY2lkIjoiMG9hZ25lcTc0M2Q0T1BVVGVwaDciLCJlaWQiOiIwMHVnaWpzeDhrcFJEb1RVRTBoNyIsInNjcCI6WyJpY2Fub1ljdXN0b20iLCJvcGVuaWQiXSwic3ViIjoiZG9uZ21laS5jYW9AaWNhbm4ub3JnIiwiz212ZW5fbmFtZSI6IkdRvbmtdZWkiLCJmYW1pbHlfbmFtZSI6IkdNbbyIsImVtYWlsIjoiZG9uZ21laS5jYW9AaWNhbm4ub3JnIn0.NJtVnGTtpzJ0cLzwnw-eRjL15W5ytzg7-ZQ5tYypMuFxYp_wwgMq2tKGTi8OQdCaw9JkVzGijVRvSUGuM_aIplON5uQZIBCR59wRqPoK6H0S1Ds3IKLQSSYxRbZXxW3MXmuw1lqocBfNFwLdmUNmmuJf1RsLK4W0-OWmuOtRJPReJ3jbLv67XPNKauIqaHSvLa-2rQrpEddNxDnJuaUoZ10m3b1lmpUqlQR2JRBSr5kddsJ1uIWLrJ0in-IRQEx0Eys0zOmCUeLY8N46VRmzr5WMpm0dLgrvOZRZTNK9NusP6aG6vjdTGLcIz6GHn4gdPv19s_H90ROd2cWehVoVQ" \
https://czds-api-test.icann.org/czds/downloads/example1.zone >
/tmp/example1.zone.txt.gz
```

Note: the download file is in `gzip` format.

5.3. Checking zone file size

HEAD <base_url>/czds/downloads/<tld>.zone

Check a zone file size without downloading the zone file. The `Content-Length` header indicates the size of the zone file in bytes.

Parameters:

Same parameters are required as in [5.2 Getting a zone file](#).

Possible results:

Same possible results should be expected as in [5.2 Getting a zone file](#).

Examples using CURL to get the Content-Length header:

Request Example:

```
curl -I \
-H "Authorization: Bearer
eyJraWQiOiI5UUR4ci16dH1Lb1lHVVEE0LS1HR3FqQ3dUVk1Fc0MxRXJNb3VtV1NEM1NBiwiYWxnIjoiUlMyNTYifQ.eyJ2ZXIiOiJEsImp0aSI6IkdFb1lRkdoUFRsSTRTUlprRHpQVknVT0MyalFTSi1mM1p0VVUilCJpc3MiOiJodHRwczovL2Rldi05ODcyNDkub2t0YXByZXZpZDcuY29tL29hdXRoMi9hdXNnaW42aDZ2ZzJxdkliUTBoNyIsImF1ZCI6Imh0dHBzOi8vYXBpdGVzdGJlZC5pY2Fubi5vcnciLCJpYXQiOiJlNDIzMDC2MjQsImV4cCI6MTU0MjMxMTIyNCwiY2lkIjoiMG9hZ25lcTc0M2Q0T1BVVGVwaDciLCJlaWQiOiIwMHVnaWpzeDhrcFJEb1RVRTBoNyIsInNjcCI6WyJpY2Fub1ljdXN0b20iLCJvcGVuaWQiXSwic3ViIjoiZG9uZ21laS5jYW9AaWNhbm4ub3JnIiwiz212ZW5fbmFtZSI6IkdRvbmtdZWkiLCJmYW1pbHlfbmFtZSI6IkdNbbyIsImVtYWlsIjoiZG9uZ21laS5jYW9AaWNhbm4ub3JnIn0.NJtVnGTtpzJ0cLzwnw-eRjL15W5ytzg7-ZQ5tYypMuFxYp_wwgMq2tKGTi8OQdCaw9JkVzGijVRvSUGuM_aIplON5uQZIBCR59wRqPoK6H0S1Ds3IKLQSSYxRbZXxW3MXmuw1lqocBfNFwLdmUNmmuJf1RsLK4W0-OWmuOtRJPReJ3jbLv67XPNKauIqaHSvLa-2rQrpEddNxDnJuaUoZ10m3b1lmpUqlQR2JRBSr5kddsJ1uIWLrJ0in-IRQEx0Eys0zOmCUeLY8N46VRmzr5WMpm0dLgrvOZRZTNK9NusP6aG6vjdTGLcIz6GHn4gdPv19s_H90ROd2cWehVoVQ" \
https://czds-api-test.icann.org/czds/downloads/example1.zone
```

Response Header Example:

```
...  
Content-Type: application/x-gzip  
Content-Length: 3716  
...
```

Note: the Content-Length is in decimal number of bytes.