

Notebook

Para el regional elegimos nombre

6 de noviembre de 2025

Índice

1. Template	2		
1.1. run.sh	2		
1.2. comp.sh	2		
1.3. Makefile	2		
2. Estructuras de datos	3		
2.1. Sparse Table	3		
2.2. Segment Tree	3		
2.3. Segment Tree Lazy	3		
2.4. Segment Tree 2D	4		
2.5. Segment Tree Persistente	4		
2.6. Fenwick Tree	5		
2.7. Treap	5		
2.8. Union Find	6		
2.9. Chull Trick	6		
2.10. Chull Trick Dinámico	6		
3. Matemática	7		
3.1. Criba Lineal	7		
3.2. Phollard's Rho	7		
3.3. Divisores	8		
3.4. Inversos Modulares	8		
3.5. Catalan	8		
3.6. Lucas	9		
3.7. Stirling-Bell	9		
3.8. DP Factoriales	9		
3.9. Estructura de Fracción	9		
		3.10. Gauss	9
		3.11. FFT	10
4. Geometria	11		
4.1. Punto	11		
4.2. Linea	11		
4.3. Poligono	12		
4.4. Circulo	13		
4.5. Convex Hull	14		
4.6. Orden Radial	14		
4.7. Par de puntos más cercano	14		
4.8. Arbol KD	15		
4.9. Suma de Minkowski	15		
5. Strings	16		
5.1. Hashing	16		
5.2. Suffix Array	16		
5.3. String Functions	17		
5.4. Kmp	17		
5.5. Manacher	17		
5.6. Mínima Rotación Lexicográfica	17		
5.7. Trie	18		
5.8. Suffix Automaton	18		
6. Grafos	20		
6.1. Dijkstra	20		
6.2. LCA	20		
6.3. Binary Lifting	21		
6.4. Toposort	21		
6.5. Deteccion ciclos negativos	21		
6.6. Camino Euleriano	22		
6.7. Camino Hamiltoniano	22		
6.8. Tarjan SCC	22		
6.9. Bellman-Ford	23		
6.10. Puentes y Articulacion	23		
6.11. Kruskal	23		

6.12. Chequeo Bipartito	24
6.13. Centroid Decomposition	24
6.14. HLD	24
6.15. Max Tree Matching	25
6.16. Min Tree Vertex Cover	25
6.17. 2-SAT	25
6.18. K Colas	26
7. Flujo	26
7.1. Dinic	26
7.2. Min Cost Max Flow	27
7.3. Hopcroft Karp	28
7.4. Kuhn	28
7.5. Min Vertex Cover Bipartito	29
7.6. Hungarian	29
8. Optimización	30
8.1. Ternary Search	30
8.2. Longest Increasing Subsequence	30
9. Otros	30
9.1. Mo	30
9.2. Divide and Conquer Optimization	31
9.3. Fijar el numero de decimales	31
9.4. Hash Table (Unordered Map/ Unordered Set)	31
9.5. Indexed Set	31
9.6. Subconjuntos	31
9.7. Simpson	31
9.8. Pragmas	31
9.9. Random	32
9.10. Utilidades de strings	32

1. Template

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 #define forr(i, a, b) for (int i = int(a); i < int(b); i++)
5 #define forn(i, n) forr(i,0,n)
6 #define dforr(i, a, b) for (int i = int(b)-1; i >= int(a); i--)
7 #define dforn(i, n) dforr(i,0,n)
8 #define all(v) begin(v),end(v)
9 #define sz(v) (int(size(v)))
10 #define pb push_back
11 #define fst first
12 #define snd second
13 #define mp make_pair
14 #define endl '\n'
15 #define dprint(v) cerr << __LINE__ << ": " #v " = " << v << endl
16
17 using ll = long long;
18 using pii = pair<int,int>;
19
20 int main() {
21     ios::sync_with_stdio(0); cin.tie(0);
22 }
```

1.1. run.sh

```

1 clear
2 make -s $1 && ./ $1 < $2
```

1.2. comp.sh

```

1 clear
2 make -s $1 2>&1 | head -$2
```

1.3. Makefile

```

1 CXXFLAGS = -std=gnu++2a -O2 -g -Wall -Wextra -Wshadow -Wconversion\
2 -fsanitize=address -fsanitize=undefined
```

2. Estructuras de datos

2.1. Sparse Table

```
1 #define oper min
2 Elem st[K][1<<K]; // K tal que (1<<K) > n
3 void st_init(vector<Elem>& a) {
4     int n = sz(a); // assert(K >= 31-__builtin_clz(2*n));
5     forn(i,n) st[0][i] = a[i];
6     forr(k,1,K) forn(i,n-(1<<k)+1)
7         st[k][i] = oper(st[k-1][i], st[k-1][i+(1<<(k-1))]);
8 }
9 Elem st_query(int l, int r) { // assert(l<r);
10     int k = 31-__builtin_clz(r-l);
11     return oper(st[k][l], st[k][r-(1<<k)]);
12 }
13 // si la operacion no es idempotente
14 Elem st_query(int l, int r) {
15     int k = 31-__builtin_clz(r-l);
16     Elem res = st[k][l];
17     for (l+=(1<<k), k--; l<r; k--) {
18         if (l+(1<<k)<=r) {
19             res = oper(res, st[k][l]);
20             l += (1<<k);
21         }
22     }
23     return res;
24 }
```

2.2. Segment Tree

```
1 // Dado un array y una operacion asociativa con neutro, get(i,j)
   opera en [i,j)
2 #define oper(x, y) max(x, y)
3 const int neutro=0;
4 struct RMQ{
5     int sz;
6     tipo t[4*MAXN];
7     tipo &operator[] (int p){return t[sz+p];}
8     void init(int n){ // O(nlgn)
```

```
9         sz = 1 << (32-__builtin_clz(n));
10        forn(i, 2*sz) t[i]=neutro;
11    }
12    void updall(){dforn(i, sz) t[i]=oper(t[2*i], t[2*i+1]);} //
        O(N)
13    tipo get(int i, int j){return get(i,j,1,0,sz);}
14    tipo get(int i, int j, int n, int a, int b){ // O(lgn)
15        if(j<=a || i>=b) return neutro;
16        if(i<=a && b<=j) return t[n];
17        int c=(a+b)/2;
18        return oper(get(i, j, 2*n, a, c), get(i, j, 2*n+1, c, b));
19    }
20    void set(int p, tipo val){ // O(lgn)
21        for(p+=sz; p>0 && t[p]!=val;){
22            t[p]=val;
23            p/=2;
24            val=oper(t[p*2], t[p*2+1]);
25        }
26    }
27 }rmq;
28 // Usage:
29 cin >> n; rmq.init(n); forn(i, n) cin >> rmq[i]; rmq.updall();
```

2.3. Segment Tree Lazy

```
1 //Dado un arreglo y una operacion asociativa con neutro, get(i, j)
   opera sobre el rango [i, j).
2 typedef int Elem; //Elem de los elementos del arreglo
3 typedef int Alt; //Elem de la alteracion
4 #define oper(x,y) x+y
5 #define oper2(k,a,b) k*(b-a) //Aplicar actualizacion sobre [a, b)
6 const Elem neutro=0; const Alt neutro2=-1;
7 struct RMQ{
8     int sz;
9     Elem t[4*MAXN];
10    Alt dirty[4*MAXN]; //las alteraciones pueden ser distintas a
        Elem
11    Elem &operator[] (int p){return t[sz+p];}
12    void init(int n){ //O(nlgn)
13        sz = 1 << (32-__builtin_clz(n));
```

```

14     forn(i, 2*sz) t[i]=neutro;
15     forn(i, 2*sz) dirty[i]=neutro2;
16 }
17 void push(int n, int a, int b){//propaga el dirty a sus hijos
18     if(dirty[n]!=0){
19         t[n]+=oper2(dirty[n], a, b);//altera el nodo
20         if(n<sz){//cambiar segun el problema
21             dirty[2*n] = dirty[n];
22             dirty[2*n+1] = dirty[n];
23         }
24         dirty[n]=0;
25     }
26 }
27 Elem get(int i, int j, int n, int a, int b){//O(lgn)
28     if(j<=a || i>=b) return neutro;
29     push(n, a, b);
30     if(i<=a && b<=j) return t[n];
31     int c=(a+b)/2;
32     return oper(get(i, j, 2*n, a, c), get(i, j, 2*n+1, c, b));
33 }
34 Elem get(int i, int j){return get(i,j,1,0,sz);}
35 //altera los valores en [i, j) con una alteracion de val
36 void alterar(Alt val,int i,int j,int n,int a,int b){//O(lgn)
37     push(n, a, b);
38     if(j<=a || i>=b) return;
39     if(i<=a && b<=j){
40         dirty[n]+=val;
41         push(n, a, b);
42         return;
43     }
44     int c=(a+b)/2;
45     alterar(val, i, j, 2*n, a, c);
46     alterar(val, i, j, 2*n+1, c, b);
47     t[n]=oper(t[2*n], t[2*n+1]);
48 }
49 void alterar(Alt val, int i, int j){alterar(val,i,j,1,0,sz);}
50 }rmq;

```

2.4. Segment Tree 2D

```

1  int n,m;
2  int a[MAXN][MAXN],st[4*MAXN][4*MAXN];
3  void build(){
4      forr(i,0,n)forr(j,0,m)st[i+n][j+m]=a[i][j];
5      forr(i,0,n)for(int j=m-1;j>=0;j--){
6          st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
7      }
8      for(int i=n-1;i>=0;i--)forr(j,0,2*m){
9          st[i][j]=op(st[i<<1][j],st[i<<1|1][j]);
10     }
11 void upd(int x, int y, int v){
12     st[x+n][y+m]=v;
13     for(int j=y+m;j>1;j>>=1)st[x+n][j>>1]=op(st[x+n][j],st[x+n][j^1]);
14     for(int i=x+n;i>1;i>>=1)for(int j=y+m;j>=1;j>>=1){
15         st[i>>1][j]=op(st[i][j],st[i^1][j]);
16     }
17 int query(int x0, int x1, int y0, int y1){
18     int r=NEUT;
19     for(int i0=x0+n,i1=x1+n;i0<i1;i0>>=1,i1>>=1){
20         int t[4],q=0;
21         if(i0&1)t[q++]=i0++;
22         if(i1&1)t[q++]--i1;
23         forr(k,0,q)for(int j0=y0+m,j1=y1+m;j0<j1;j0>>=1,j1>>=1){
24             if(j0&1)r=op(r,st[t[k]][j0++]);
25             if(j1&1)r=op(r,st[t[k]][--j1]);
26         }
27     }
28     return r;

```

2.5. Segment Tree Persistente

```

1  const int LOG2N = 19; // ceil(log2(MAXN))
2  const int STLEN = 1<<LOG2N;
3
4  struct Mono {
5      // TODO agregar data
6      static Mono zero() { /* TODO */ } // neutro de la suma
7  };
8  Mono operator+ (Mono a, Mono b) { /* TODO */ } // asociativo

```

```

9
10 struct N {
11     N(Mono x_, N* l_, N* r_)
12     : x{x_}, l{l_}, r{r_} {}
13     Mono x; N* l; N* r;
14 };
15 N empty_node(Mono::zero(), &empty_node, &empty_node);
16
17 deque<N> st_alloc; // optimizacion: >30% mas rapido que 'new
    N(x, l, r)'
18 N* make_node(Mono x, N* l, N* r) {
19     st_alloc.emplace_back(x, l, r);
20     return &st_alloc.back();
21 }
22
23 N* u_(N* t, int l, int r, int i, Mono x) {
24     if (i+1 <= l || r <= i) return t;
25     if (r-l == 1) return make_node(x, nullptr, nullptr);
26     int m = (l+r)/2;
27     auto lt = u_(t->l, l, m, i, x);
28     auto rt = u_(t->r, m, r, i, x);
29     return make_node(lt->x + rt->x, lt, rt);
30 }
31
32 int ql, qr;
33 Mono q_(N* t, int l, int r) {
34     if (qr <= l || r <= ql) return Mono::zero();
35     if (ql <= l && r <= qr) return t->x;
36     int m = (l+r)/2;
37     return q_(t->l, l, m) + q_(t->r, m, r);
38 }
39
40 // suma en rango: t[l,r)
41 Mono query(N* t, int l, int r) { ql = l; qr = r; return q_(t, 0,
    STLEN); }
42
43 // asignacion en punto: t[i]=x
44 N* update(N* t, int i, Mono x) { return u_(t, 0, STLEN, i, x); }
45
46 /* uso:

```

```

47 auto t = &empty_node;
48 t = update(t, 0, Mono{10});
49 t = update(t, 5, Mono{5});
50 auto x = query(t, 0, 5); // devuelve Mono{10}
51 auto y = query(t, 0, 6); // devuelve Mono{10} + Mono{5}
52 auto z = query(t, 1, 6); // devuelve Mono{5}
53 */

```

2.6. Fenwick Tree

```

1 struct Fenwick { // 0-indexed, query [0, i), update [i]
2     int ft[MAXN+1]; // Uso: ft.u(id, val); cout << ft.q(id);
3     int u(int i0, int x) { for (int i=i0+1; i<=MAXN; i+=i&-i)
        ft[i]+=x; }
4     ll q(int i0){ ll x=0; for (int i=i0; i>0; i-=i&-i) x+=ft[i];
        return x; } };
5
6 struct RangeFT { // 0-indexed, query [0, 1), update [l, r)
7     Fenwick rate, err; // Uso: ft.u(l, r, val); cout << ft.q(l, r);
8     void u(int l, int r, int x) { // range update
9         rate.u(l, x); rate.u(r, -x); err.u(l, -x*l); err.u(r, x*r);
10        }
11     ll q(int i) { return rate.q(i) * i + err.q(i); } }; // prefix
        query

```

2.7. Treap

```

1 // representa una lista como arbol con el orden implicito
2 struct node {
3     int val, prio, tam;
4     node *l, *r;
5 };
6 node *make(int val) {
7     return new node { val, rand(), 1, nullptr, nullptr };
8 }
9 int tam(node *n) { return n ? n->tam : 0; }
10 void recalc(node *n) { n->tam = tam(n->l) + 1 + get_tam(n->r); }
11 node* merge(node* s, node* t) {
12     if (s == nullptr) return t;
13     if (t == nullptr) return s;
14     if (s->prio > t->prio) {

```

```

15     s->r = merge(s->r, t);
16     recalc(s);
17     return s;
18 } else {
19     t->l = merge(s, t->l);
20     recalc(t);
21     return t;
22 }
23 }
24 pair<node*, node*> split(node *s, int k) {
25     if (s == nullptr) return {nullptr, nullptr};
26     if (tam(s->l) < k) {
27         if (s->l == nullptr) return {nullptr, nullptr};
28         auto [l, r] = split(s->r, k-tam(s->l)-1);
29         s->r = l;
30         recalc(s);
31         return {s, r};
32     } else {
33         auto [l, r] = split(s->l, k);
34         s->l = r;
35         recalc(s);
36         return {l, s};
37     }
38 } // usage: node *list = nullptr; list = merge(list, make(5))

```

2.8. Union Find

```

1 vector<int> uf(MAXN, -1);
2 int uf_find(int x) { return uf[x]<0 ? x : uf[x] = uf_find(uf[x]); }
3 bool uf_join(int x, int y){ // True sii x e y estan en !=
    componentes
4     x = uf_find(x); y = uf_find(y);
5     if(x == y) return false;
6     if(uf[x] > uf[y]) swap(x, y);
7     uf[x] += uf[y]; uf[y] = x; return true;
8 }

```

2.9. Chull Trick

```

1 typedef ll tc;
2 struct Line{tc m,h};

```

```

3 struct CHT { // for minimum (for maximum just change the sign of
    lines)
4     vector<Line> c;
5     int pos=0;
6     tc in(Line a, Line b){
7         tc x=b.h-a.h,y=a.m-b.m;
8         return x/y+(x%y?!((x>0)^(y>0)):0); // ==ceil(x/y)
9     }
10    void add(tc m, tc h){ // m's should be non increasing
11        Line l=(Line){m,h};
12        if(sz(c)&& m==c.back().m){
13            l.h=min(h,c.back().h);c.pop_back();if(pos)pos--;
14        }
15        while(sz(c)>1&&in(c.back(),l)<=in(c[sz(c)-2],c.back())){
16            c.pop_back();if(pos)pos--;
17        }
18        c.pb(l);
19    }
20    inline bool fbin(tc x, int m){return in(c[m],c[m+1])>x;}
21    tc eval(tc x){
22        // O(log n) query:
23        int s=0,e=c.size();
24        while(e-s>1){int m=(s+e)/2;
25            if(fbin(x,m-1))e=m;
26            else s=m;
27        }
28        return c[s].m*x+c[s].h;
29        // O(1) query (for ordered x's):
30        while(pos>0&&fbin(x,pos-1))pos--;
31        while(pos<c.size()-1&&!fbin(x,pos))pos++;
32        return c[pos].m*x+c[pos].h;
33    }
34 };

```

2.10. Chull Trick Dinámico

```

1 struct Entry {
2     using It = set<Entry>::iterator;
3     bool is_query;
4     ll m, b; mutable It it, end;

```

```

5     ll x;
6 };
7 bool operator< (Entry const& a, Entry const& b) {
8     if (!b.is_query) return a.m < b.m;
9     auto ni = next(a.it);
10    if (ni == a.end) return false;
11    auto const& c = *ni;
12    return (c.b-a.b) > b.x * (a.m-c.m);
13 }
14 struct ChullTrick {
15     using It = Entry::It;
16     multiset<Entry> lines;
17     bool covered(It it) {
18         auto begin = lines.begin(), end = lines.end();
19         auto ni = next(it);
20         if (it == begin && ni == end) return false;
21         if (it == begin) return ni->m==it->m && ni->b>=it->b;
22         auto pi = prev(it);
23         if (ni == end) return pi->m==it->m && pi->b>=it->b;
24         return (it->m-pi->m)*(ni->b-pi->b) >=
            (pi->b-it->b)*(pi->m-ni->m);
25     }
26     bool add(ll m, ll b) {
27         auto it = lines.insert({false, m, b});
28         it->it = it; it->end = lines.end();
29         if (covered(it)) { lines.erase(it); return false; }
30         while (next(it) != lines.end() && covered(next(it)))
31             lines.erase(next(it));
32         while (it != lines.begin() && covered(prev(it)))
33             lines.erase(prev(it));
34         return true;
35     }
36     bool eval(ll x) {
37         auto l = *lines.lower_bound({true, -1, -1, {}, {}, x});
38         return l.m*x+l.b;
39     }
40 };

```

3. Matemática

3.1. Criba Lineal

```

1 const int N = 10'000'000;
2 vector<int> lp(N+1);
3 vector<int> pr;
4 for (int i=2; i <= N; ++i) {
5     if (lp[i] == 0) lp[i] = i, pr.push_back(i);
6     for (int j = 0; i * pr[j] <= N; ++j) {
7         lp[i * pr[j]] = pr[j];
8         if (pr[j] == lp[i]) break;
9     }
10 }

```

3.2. Phollard's Rho

```

1 ll mulmod(ll a, ll b, ll m) { return ll(__int128(a) * b % m); }
2
3 ll expmod(ll b, ll e, ll m) { // O(log b)
4     if (!e) return 1;
5     ll q=expmod(b,e/2,m); q=mulmod(q,q,m);
6     return e%2 ? mulmod(b,q,m) : q;
7 }
8
9 bool es_primo_prob(ll n, int a) {
10     if (n == a) return true;
11     ll s = 0, d = n-1;
12     while (d%2 == 0) s++, d/=2;
13     ll x = expmod(a,d,n);
14     if ((x == 1) || (x+1 == n)) return true;
15     forn(i,s-1){
16         x = mulmod(x,x,n);
17         if (x == 1) return false;
18         if (x+1 == n) return true;
19     }
20     return false;
21 }
22
23 bool rabin(ll n) { // devuelve true sii n es primo

```

```

24     if (n == 1) return false;
25     const int ar[] = {2,3,5,7,11,13,17,19,23};
26     forn(j,9) if (!es_primo_prob(n,ar[j])) return false;
27     return true;
28 }
29
30 ll rho(ll n) {
31     if ((n & 1) == 0) return 2;
32     ll x = 2, y = 2, d = 1;
33     ll c = rand() % n + 1;
34     while (d == 1) {
35         x = (mulmod(x,x,n)+c)%n;
36         y = (mulmod(y,y,n)+c)%n;
37         y = (mulmod(y,y,n)+c)%n;
38         d=gcd(x-y,n);
39     }
40     return d==n ? rho(n) : d;
41 }
42
43 void factRho(map<ll,ll>&prim, ll n){ //O (lg n)^3. un solo numero
44     if (n == 1) return;
45     if (rabin(n)) { prim[n]++; return; }
46     ll factor = rho(n);
47     factRho(factor, prim); factRho(n/factor, prim);
48 }
49 auto fact(ll n){
50     map<ll,ll>prim;
51     factRho(prim,n);
52     return prim;
53 }

```

3.3. Divisores

```

1 // Usar asi: divisores(fac, divs, fac.begin()); NO ESTA ORDENADO
2 void divisores(const map<ll,ll> &f, vector<ll> &divs, auto it, ll
   n=1){
3     if (it==f.begin()) divs.clear();
4     if (it==f.end()) { divs.pb(n); return; }
5     ll p=it->fst, k=it->snd; ++it;
6     forn(_, k+1) divisores(f,divs,it,n), n*=p;

```

```

7 }
8
9 ll sumDiv (ll n){ //suma de los divisores de n
10     ll rta = 1;
11     map<ll,ll> f=fact(n);
12     for(auto it = f.begin(); it != f.end(); it++) {
13         ll pot = 1, aux = 0;
14         forn(i, it->snd+1) aux += pot, pot *= it->fst;
15         rta*=aux;
16     }
17     return rta;
18 }

```

3.4. Inversos Modulares

```

1 pair<ll,ll> extended_euclid(ll a, ll b) {
2     if (b == 0) return {1, 0};
3     auto [y, x] = extended_euclid(b, a%b);
4     y -= (a/b)*x;
5     if (a*x + b*y < 0) x = -x, y = -y;
6     return {x, y}; // a*x + b*y = gcd(a,b)
7 }
8
9 constexpr ll MOD = 1000000007; // tmb es comun 998'244'353
10 ll invmod[MAXN]; // inversos módulo MOD hasta MAXN
11 void invmods() { // todo entero en [2,MAXN] debe ser coprimo con
   MOD
12     inv[1] = 1;
13     forr(i, 2, MAXN) inv[i] = MOD - MOD/i*inv[MOD%i] %MOD;
14 }
15
16 // si MAXN es demasiado grande o MOD no es fijo:
17 // versión corta, m debe ser primo. O(log(m))
18 ll invmod(ll a, ll m) { return expmod(a,m-2,m); }
19 // versión larga, a y m deben ser coprimos. O(log(a)), en general
   más rápido
20 ll invmod(ll a, ll m) { return (extended_euclid(a,m).fst % m + m)
   % m; }

```

3.5. Catalan


```

1 ll Cat(int n){
2     return ((F[2*n] *FI[n+1])%M *FI[n])%M;
3 }

```

3.6. Lucas

```

1 const ll MAXP = 3e3+10; //68 MB, con 1e4 int son 380 MB
2 ll C[MAXP][MAXP], P; //inicializar con el primo del input < MAXP
3 void llenar_C(){
4     forn(i, MAXP) C[i][0] = 1;
5     forr(i, 1, MAXP) forr(j, 1, i+1)
6         C[i][j]=addmod(C[i-1][j-1],C[i-1][j], P);
7 }
8 // Calcula nCk (mod p) con n, k arbitrariamente grandes y p primo
9 // <= 3000
10 ll lucas(ll N, ll K){ // llamar a llenar_C() antes
11     ll ret = 1;
12     while(N+K){
13         ret = ret * C[N%P][K%P] % P;
14         N /= P, K /= P;
15     }
16     return ret;
17 }

```

3.7. Stirling-Bell

```

1 ll STR[MAXN][MAXN], Bell[MAXN];
2 //STR[n][k] = formas de particionar un conjunto de n elementos en
3 // k conjuntos
4 //Bell[n] = formas de particionar un conjunto de n elementos
5 forn(i, 1, MAXN)STR[i][1] = 1;
6 forn(i, 2, MAXN)STR[1][i] = 0;
7 forn(i, 2, MAXN)forn(j, 2, MAXN){
8     STR[i][j] = (STR[i-1][j-1] + j*STR[i-1][j]%MOD) %MOD;
9 }
10 forn(i, MAXN){
11     Bell[i] = 0;
12     forn(j, MAXN){
13         Bell[i] = (Bell[i] + STR[i][j]) %MOD;
14     }
15 }

```

3.8. DP Factoriales

```

1 ll F[MAXN], INV[MAXN], FI[MAXN];
2 // ...
3 F[0] = 1; forr(i, 1, MAXN) F[i] = F[i-1]*i %M;
4 INV[1] = 1; forr(i, 2, MAXN) INV[i] = M - (11)(M/i)*INV[M%i] %M;
5 FI[0] = 1; forr(i, 1, MAXN) FI[i] = FI[i-1]*INV[i] %M;

```

3.9. Estructura de Fracción

```

1 tipo mcd(tipo a, tipo b){return a?mcd(b%a, a):b;}
2 struct frac{
3     tipo p,q;
4     frac(tipo p=0, tipo q=1):p(p),q(q) {norm();}
5     void norm(){
6         tipo a = mcd(p,q);
7         if(a) p/=a, q/=a;
8         else q=1;
9         if (q<0) q=-q, p=-p;}
10    frac operator+(const frac& o){
11        tipo a = mcd(q,o.q);
12        return frac(p*(o.q/a)+o.p*(q/a), q*(o.q/a));}
13    frac operator-(const frac& o){
14        tipo a = mcd(q,o.q);
15        return frac(p*(o.q/a)-o.p*(q/a), q*(o.q/a));}
16    frac operator*(frac o){
17        tipo a = mcd(q,o.p), b = mcd(o.q,p);
18        return frac((p/b)*(o.p/a), (q/a)*(o.q/b));}
19    frac operator/(frac o){
20        tipo a = mcd(q,o.q), b = mcd(o.p,p);
21        return frac((p/b)*(o.q/a), (q/a)*(o.p/b));}
22    bool operator<(const frac &o) const{return p*o.q < o.p*q;}
23    bool operator==(frac o){return p==o.p&&q==o.q;}
24 };

```

3.10. Gauss

```

1 double reduce(vector<vector<double>> &a){ //Devuelve determinante
2     si m == n
3     int m=sz(a), n=sz(a[0]), i=0, j=0; double r = 1.0;
4     while(i < m and j < n){

```

```

4     int h = i;
5     forr(k, i+1, m) if(abs(a[k][j]) > abs(a[h][j])) h = k;
6     if(abs(a[h][j]) < EPS){ j++; r=0.0; continue; }
7     if(h != i){ r = -r; swap(a[i], a[h]); }
8     r *= a[i][j];
9     dforr(k, j, n) a[i][k] /= a[i][j];
10    forr(k, 0, m) if(k != i)
11        dforr(l_, j, n) a[k][l_] -= a[k][j] * a[i][l_];
12    i++; j++;
13 }
14 return r;
15 }

```

3.11. FFT

```

1 // MAXN must be power of 2 !!, MOD-1 needs to be a multiple of
   // MAXN !!
2 typedef ll tf;
3 typedef vector<tf> poly;
4 //const tf MOD = 2305843009255636993, RT = 5;
5 const tf MOD = 998244353, RT = 3;
6 // const tf MOD2 = 897581057, RT2 = 3; // Chinese Remainder Theorem
7 /* FFT */ struct CD {
8     double r, i;
9     CD(double r_ = 0, double i_ = 0) : r(r_), i(i_) {}
10    void operator/=(const int c) { r/=c, i/=c; }
11 };
12 CD operator*(const CD& a, const CD& b){
13     return CD(a.r*b.r-a.i*b.i, a.r*b.i+a.i*b.r);}
14 CD operator+(const CD& a, const CD& b) { return CD(a.r+b.r,
15     a.i+b.i); }
16 CD operator-(const CD& a, const CD& b) { return CD(a.r-b.r,
17     a.i-b.i); }
18 /* NTT */ struct CD { tf x; CD(tf x_) : x(x_) {} CD() {} };
19 CD operator+(const CD& a, const CD& b) { return CD(addmod(a.x,
20     b.x)); } //ETC
21 vector<tf> rts(MAXN+9,-1);
22 CD root(int n, bool inv){
23     tf r = rts[n]<0 ? rts[n] = expmod(RT,(MOD-1)/n) : rts[n];
24     return CD(inv ? expmod(r, MOD-2) : r);

```

```

22 }
23 /* AMBOS */ CD cp1[MAXN+9], cp2[MAXN+9];
24 int R[MAXN+9];
25 void dft(CD* a, int n, bool inv){
26     double pi = acos(-1.0);
27     forn(i, n) if(R[i] < i) swap(a[R[i]], a[i]);
28     for(int m = 2; m <= n; m *= 2){
29         /* FFT */ double z = 2*pi/m * (inv?-1:1);
30         /* FFT */ CD wi = CD(cos(z), sin(z));
31         /* NTT */ CD wi = root(m, inv);
32         for(int j = 0; j < n; j += m){
33             CD w(1);
34             for(int k = j, k2 = j+m/2; k2 < j+m; k++, k2++){
35                 CD u = a[k]; CD v = a[k2]*w; a[k] = u+v; a[k2] =
36                     u-v; w = w*wi;
37             }
38         }
39         /* FFT */ if(inv) forn(i, n) a[i] /= n;
40         /* NTT */ if(inv){
41             CD z(expmod(n, MOD-2));
42             forn(i, n) a[i] = a[i]*z;
43         }
44     }
45 poly multiply(poly& p1, poly& p2){
46     int n = sz(p1)+sz(p2)+1;
47     int m = 1, cnt = 0;
48     while(m <= n) m *= 2, cnt++;
49     forn(i, m) { R[i] = 0; forn(j, cnt) R[i] =
50         (R[i]<<1)|((i>>j)&1); }
51     forn(i, m) cp1[i] = 0, cp2[i] = 0;
52     forn(i, sz(p1)) cp1[i] = p1[i];
53     forn(i, sz(p2)) cp2[i] = p2[i];
54     dft(cp1, m, false); dft(cp2, m, false);
55     // fast eval: forn(i, sz(p1)) p1(expmod(RT, (MOD-1)/m*i)) ==
56         cp1[i].x
57     forn(i, m) cp1[i] = cp1[i]*cp2[i];
58     dft(cp1, m, true);
59     poly res;
60     n -= 2;

```

```

59  /* FFT */ forn(i, n) res.pb((tf)floor(cp1[i].r+0.5));
60  /* NTT */ forn(i, n)res.pb(cp1[i].x);
61  return res;
62 }

```

4. Geometria

4.1. Punto

```

1  using T = double;
2  bool iszero(T u) { return abs(u)<=EPS; }
3  struct Pt {
4      T x, y;
5      T z; // only for 3d
6      Pt() {}
7      Pt(T _x, T _y) : x(_x), y(_y) {}
8      Pt(T _x, T _y, T _z) : x(_x), y(_y), z(_z) {} // for 3d
9      T norm2(){ return *this**this; }
10     T norm(){ return sqrt(norm2()); }
11     Pt operator+(Pt o){ return Pt(x+o.x,y+o.y); }
12     Pt operator-(Pt o){ return Pt(x-o.x,y-o.y); }
13     Pt operator*(T u){ return Pt(x*u,y*u); }
14     Pt operator/(T u) {
15         if (iszero(u)) return Pt(INF,INF);
16         return Pt(x/u,y/u);
17     }
18     T operator*(Pt o){ return x*o.x+y*o.y; }
19     Pt operator^(Pt p){ // only for 3D
20         return Pt(y*p.z-z*p.y, z*p.x-x*p.z, x*p.y-y*p.x); }
21     T operator%(Pt o){ return x*o.y-y*o.x; }
22     T angle(Pt o){ return atan2(*this%o, *this*o); }
23     // T angle(Pt o){ // accurate around 90 degrees
24     //     if (*this%o>0) return acos(*this*o);
25     //     return 2*M_PI-acos(*this*o); }
26     Pt unit(){ return *this/norm(); }
27     bool left(Pt p, Pt q){ // is it to the left of directed line
28         pq?
29         return ((q-p)%(*this-p))>EPS; }
30     bool operator<(Pt p)const{ // for convex hull
31         return x<p.x-EPS|| (iszero(x-p.x)&&y<p.y-EPS); }

```

```

31  bool collinear(Pt p, Pt q){
32      return iszero((p-*this)%(q-*this)); }
33  bool dir(Pt p, Pt q){ // does it have the same direction of pq?
34      return this->collinear(p, q)&&(q-p)*(*this-p)>EPS; }
35  Pt rot(Pt r){ return Pt(*this*r,*this*r); }
36  Pt rot(T a){ return rot(Pt(sin(a),cos(a))); }
37 };
38 Pt ccw90(1,0);
39 Pt cw90(-1,0);

```

4.2. Linea

```

1  using T = double;
2  int sgn2(T x){return x<0?-1:1;}
3  struct Ln {
4      Pt p,pq;
5      Ln(Pt p, Pt q):p(p),pq(q-p){}
6      Ln(){}
7      bool has(Pt r){return dist(r)<=EPS;}
8      bool seghas(Pt r){return has(r)&&(r-p)*(r-(p+pq))<=EPS;}
9      // bool operator/(Ln l){return
10         (pq.unit()^l.pq.unit()).norm()<=EPS;} // 3D
11     bool operator/(Ln l){return abs(pq.unit()^l.pq.unit())<=EPS;}
12         // 2D
13     bool operator==(Ln l){return *this/l&&has(l.p);}
14     Pt operator^(Ln l){ // intersection
15         if(*this/l)return Pt(INF,INF);
16         T a=-pq.y, b=pq.x, c=p.x*a+p.y*b;
17         T la=-l.pq.y, lb=l.pq.x, lc=l.p.x*la+l.p.y*lb;
18         T det = a * lb - b * la;
19         Pt r((lb*c-b*lc)/det, (a*lc-c*la)/det);
20         return r;
21     // Pt r=l.p+l.pq*(((p-l.p)^pq)/(l.pq^pq));
22     // if(!has(r)){return Pt(NAN,NAN,NAN);} // check only for 3D
23     }
24     T angle(Ln l){return pq.angle(l.pq);}
25     int side(Pt r){return has(r)?0:sgn2(pq^(r-p));} // 2D
26     Pt proj(Pt r){return p+pq*((r-p)*pq/pq.norm2());}
27     Pt segclosest(Pt r) {
28         T l2 = pq.norm2();

```

```

27     if(l2==0.) return p;
28     T t =((r-p)*pq)/l2;
29     return p+(pq*min(1,max(0,t)));
30 }
31 Pt ref(Pt r){return proj(r)*2-r;}
32 T dist(Pt r){return (r-proj(r)).norm();}
33 // T dist(Ln l){ // only 3D
34 //     if(*this/l)return dist(l.p);
35 //     return abs((l.p-p)*(pq~l.pq))/(pq~l.pq).norm();
36 // }
37 Ln rot(auto a){return Ln(p,p+pq.rot(a));} // 2D
38 };
39 Ln bisector(Ln l, Ln m){ // angle bisector
40     Pt p=l~m;
41     return Ln(p,p+l.pq.unit()+m.pq.unit());
42 }
43 Ln bisector(Pt p, Pt q){ // segment bisector (2D)
44     return Ln((p+q)*.5,p).rot(ccw90);
45 }

```

4.3. Poligono

```

1 using T = double;
2 struct Pol {
3     int n;vector<Pt> p;
4     Pol(){}
5     Pol(vector<Pt> _p){p=_p;n=p.size();}
6     T area() {
7         ll a = 0;
8         forr (i, 1, sz(p)-1) {
9             a += (p[i]-p[0])^(p[i+1]-p[0]);
10        }
11        return abs(a)/2;
12    }
13    bool has(Pt q){ // O(n), winding number
14        forr(i,0,n)if(Ln(p[i],p[(i+1)%n]).seghas(q))return true;
15        int cnt=0;
16        forr(i,0,n){
17            int j=(i+1)%n;
18            int k=sgn((q-p[j])^(p[i]-p[j]));

```

```

19            int u=sgn(p[i].y-q.y),v=sgn(p[j].y-q.y);
20            if(k>0&&u<0&&v>=0)cnt++;
21            if(k<0&&v<0&&u>=0)cnt--;
22        }
23        return cnt!=0;
24    }
25    void normalize(){ // (call before haslog, remove collinear
26        first)
27        if(n>=3&&p[2].left(p[0],p[1]))reverse(p.begin(),p.end());
28        int pi=min_element(p.begin(),p.end())-p.begin();
29        vector<Pt> s(n);
30        forr(i,0,n)s[i]=p[(pi+i)%n];
31        p.swap(s);
32    }
33    bool haslog(Pt q){ // O(log(n)) only CONVEX. Call normalize
34        first
35        if(q.left(p[0],p[1])||q.left(p.back(),p[0]))return false;
36        int a=1,b=p.size()-1; // returns true if point on boundary
37        while(b-a>1){ // (change sign of EPS in left
38            int c=(a+b)/2; // to return false in such case)
39            if(!q.left(p[0],p[c]))a=c;
40            else b=c;
41        }
42        return !q.left(p[a],p[a+1]);
43    }
44    bool isconvex(){//O(N), delete collinear points!
45        if(n<3) return false;
46        bool isLeft=p[0].left(p[1], p[2]);
47        forr(i, 1, n)
48            if(p[i].left(p[(i+1)%n], p[(i+2)%n])!=isLeft)
49                return false;
50        return true;
51    }
52    Pt farthest(Pt v){ // O(log(n)) only CONVEX
53        if(n<10){
54            int k=0;
55            forr(i,1,n)if(v*(p[i]-p[k])>EPS)k=i;
56            return p[k];
57        }
58        if(n==sz(p))p.pb(p[0]);

```

```

57     Pt a=p[1]-p[0];
58     int s=0,e=n,ua=v*a>EPS;
59     if(!ua&&v*(p[n-1]-p[0])<=EPS) return p[0];
60     while(1){
61         int m=(s+e)/2;Pt c=p[m+1]-p[m];
62         int uc=v*c>EPS;
63         if(!uc&&v*(p[m-1]-p[m])<=EPS) return p[m];
64         if(ua&&(!uc||v*(p[s]-p[m])>EPS))e=m;
65         else if(ua||uc||v*(p[s]-p[m])>=-EPS)s=m,a=c,ua=uc;
66         else e=m;
67         assert(e>s+1);
68     }
69 }
70 Pol cut(Ln l){ // cut CONVEX polygon by line l
71     vector<Pt> q; // returns part at left of l.pq
72     forr(i,0,n){
73         int
74         d0=sgn(l.pq^(p[i]-l.p)),d1=sgn(l.pq^(p[(i+1)%n]-l.p));
75         if(d0>=0)q.pb(p[i]);
76         Ln m(p[i],p[(i+1)%n]);
77         if(d0*d1<0&&!(1/m))q.pb(l~m);
78     }
79     return Pol(q);
80 }
81 T intercircle(circle c){ // area of intersection with circle
82     T r=0.;
83     forr(i,0,n){
84         int j=(i+1)%n;T w=c.intertriangle(p[i],p[j]);
85         if((p[j]-c.o)^(p[i]-c.o)>EPS)r+=w;
86         else r-=w;
87     }
88     return abs(r);
89 }
90 T callipers(){ // square distance of most distant points
91     T r=0; // prereq: convex, ccw, NO COLLINEAR POINTS
92     for(int i=0,j=n<2?0:1;i<j;++i){
93         for(;;j=(j+1)%n){
94             r=max(r,(p[i]-p[j]).norm2());
95             if(((p[(i+1)%n]-p[i])^(p[(j+1)%n]-p[j]))<=EPS)break;
96         }
97     }

```

```

96     }
97     return r;
98 }
99 };

```

4.4. Circulo

```

1  using T = double;
2  struct Circle {
3      Pt o;T r;
4      Circle(Pt o, T r):o(o),r(r){}
5      Circle(Pt x, Pt y, Pt
6          z){o=bisector(x,y)^bisector(x,z);r=(o-x).norm();}
7      bool has(Pt p){return (o-p).norm()<=r+EPS;}
8      vector<Pt> operator^(Circle c){ // ccw
9          vector<Pt> s;
10         T d=(o-c.o).norm();
11         if(d>r+c.r+EPS||d+min(r,c.r)+EPS<max(r,c.r))return s;
12         T x=(d*d-c.r*c.r+r*r)/(2*d);
13         T y=sqrt(r*r-x*x);
14         Pt v=(c.o-o)/d;
15         s.pb(o+v*x-v.rot(ccw90)*y);
16         if(y>EPS)s.pb(o+v*x+v.rot(ccw90)*y);
17         return s;
18     }
19     vector<Pt> operator^(Ln l){
20         vector<Pt> s;
21         Pt p=l.proj(o);
22         T d=(p-o).norm();
23         if(d-EPS>r)return s;
24         if(abs(d-r)<=EPS){s.pb(p);return s;}
25         d=sqrt(r*r-d*d);
26         s.pb(p+l.pq.unit()*d);
27         s.pb(p-l.pq.unit()*d);
28         return s;
29     }
30     vector<Pt> tang(Pt p){
31         T d=sqrt((p-o).norm2()-r*r);
32         return *this^Circle(p,d);
33     }

```

```

33 bool in(Circle c){ // non strict
34     T d=(o-c.o).norm();
35     return d+r<=c.r+EPS;
36 }
37 T intertriangle(Pt a, Pt b){ // area of intersection with oab
38     if(abs((o-a)%(o-b))<=EPS)return 0.;
39     vector<Pt> q={a},w=*this^Ln(a,b);
40     if(w.size()==2)for(auto p:w)if((a-p)*(b-p)<-EPS)q.pb(p);
41     q.pb(b);
42     if(q.size()==4&&(q[0]-q[1])*(q[2]-q[1])>EPS)swap(q[1],q[2]);
43     T s=0;
44     fore(i,0,q.size()-1){
45         if(!has(q[i])||!has(q[i+1]))s+=r*r*(q[i]-o).angle(q[i+1]-o)/2;
46         else s+=abs((q[i]-o)%(q[i+1]-o)/2);
47     }
48     return s;
49 }
50 };

```

4.5. Convex Hull

```

1 // CCW order
2 // Includes collinear points (change sign of EPS in left to
   exclude)
3 vector<Pt> chull(vector<Pt> p){
4     if(sz(p)<3)return p;
5     vector<Pt> r;
6     sort(p.begin(),p.end()); // first x, then y
7     forr(i,0,p.size()){ // lower hull
8         while(r.size()>=2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
9         r.pb(p[i]);
10    }
11    r.pop_back();
12    int k=r.size();
13    for(int i=p.size()-1;i>=0;--i){ // upper hull
14        while(r.size()>=k+2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
15        r.pb(p[i]);
16    }
17    r.pop_back();
18    return r;

```

```

19 }

```

4.6. Orden Radial

```

1 struct Radial {
2     Pt o;
3     Radial(Pt _o) : o(_o) {}
4     int cuad(Pt p) {
5         if (p.x>0 && p.y>=0) return 1;
6         if (p.x<=0 && p.y>0) return 2;
7         if (p.x<0 && p.y<=0) return 3;
8         if (p.x>=0 && p.y<0) return 4;
9         assert(p.x == 0 && p.y == 0);
10        return 0; // origen < todos
11    }
12    bool comp(Pt p, Pt q) {
13        int c1 = cuad(p), c2 = cuad(q);
14        if (c1 == c2) return p%q>EPS;
15        return c1 < c2;
16    }
17    bool operator()(const Pt &p, const Pt &q) const {
18        return comp(p-o,q-o);
19    }
20 };

```

4.7. Par de puntos más cercano

```

1 #define dist(a, b) ((a-b).norm_sq())
2 bool sortx(pt a, pt b) {
3     return mp(a.x,a.y)<mp(b.x,b.y); }
4 bool sorty(pt a, pt b) {
5     return mp(a.y,a.x)<mp(b.y,b.x); }
6 ll closest(vector<pt> &ps, int l, int r) {
7     if (l == r-1) return INF;
8     if (l == r-2) {
9         if (sorty(ps[l+1], ps[l]))
10            swap(ps[l+1], ps[l]);
11        return dist(ps[l], ps[l+1]);
12    }
13    int m = (l+r)/2; ll xm = ps[m].x;
14    ll min_dist = min(closest(ps, l, m),closest(ps, m, r));

```

```

15     vector<pt> left(&ps[l], &ps[m]), right(&ps[m], &ps[r]);
16     merge(all(left), all(right), &ps[l], sorty);
17     ll delta = ll(sqrt(min_dist));
18     vector<pt> strip;
19     forr (i, l, r) if (ps[i].x>=xm-delta&&ps[i].x<=xm+delta)
20         strip.pb(ps[i]);
21     forn (i, sz(strip)) forr (j, 1, 8) {
22         if (i+j >= sz(strip)) break;
23         min_dist = min(min_dist, dist(strip[i], strip[i+j]));
24     }
25     return min_dist;
26 }
27 ll closest(vector<pt> &ps) { // devuelve dist^2
28     sort(all(ps), sortx);
29     return closest(ps, 0, sz(ps));
30 }

```

4.8. Arbol KD

```

1 // given a set of points, answer queries of nearest point in
  // O(log(n))
2 bool onx(pt a, pt b){return a.x<b.x;}
3 bool ony(pt a, pt b){return a.y<b.y;}
4 struct Node {
5     pt pp;
6     ll x0=INF, x1=-INF, y0=INF, y1=-INF;
7     Node *first=0, *second=0;
8     ll distance(pt p){
9         ll x=min(max(x0,p.x),x1);
10        ll y=min(max(y0,p.y),y1);
11        return (pt(x,y)-p).norm2();
12    }
13    Node(vector<pt>&& vp):pp(vp[0]){
14        for(pt p:vp){
15            x0=min(x0,p.x); x1=max(x1,p.x);
16            y0=min(y0,p.y); y1=max(y1,p.y);
17        }
18        if(sz(vp)>1){
19            sort(all(vp),x1-x0>=y1-y0?onx:ony);
20            int m=sz(vp)/2;

```

```

21            first=new Node({vp.begin(),vp.begin()+m});
22            second=new Node({vp.begin()+m,vp.end()});
23        }
24    }
25 };
26 struct KDTree {
27     Node* root;
28     KDTree(const vector<pt>& vp):root(new Node({all(vp)})) {}
29     pair<ll,pt> search(pt p, Node *node){
30         if(!node->first){
31             //avoid query point as answer
32             //if(p==node->pp) {INF,pt()};
33             return {(p-node->pp).norm2(),node->pp};
34         }
35         Node *f=node->first, *s=node->second;
36         ll bf=f->distance(p), bs=s->distance(p);
37         if(bf>bs)swap(bf,bs),swap(f,s);
38         auto best=search(p,f);
39         if(bs<best.fst) best=min(best,search(p,s));
40         return best;
41     }
42     pair<ll,pt> nearest(pt p){return search(p,root);}
43 };

```

4.9. Suma de Minkowski

```

1 vector<Pt> minkowski_sum(vector<Pt> &p, vector<Pt> &q){
2     int n=sz(p),m=sz(q),x=0,y=0;
3     forr(i,0,n) if(p[i]<p[x]) x=i;
4     forr(i,0,m) if(q[i]<q[y]) y=i;
5     vector<Pt> ans={p[x]+q[y]};
6     forr(it,1,n+m){
7         Pt a=p[(x+1)%n]+q[y];
8         Pt b=p[x]+q[(y+1)%m];
9         if(b.left(ans.back(),a)) ans.pb(b), y=(y+1)%m;
10        else ans.pb(a), x=(x+1)%n;
11    }
12    return ans;
13 }
14 vector<Pt> do_minkowski(vector<Pt> &p, vector<Pt> &q) {

```

```

15     normalize(p); normalize(q);
16     vector<Pt> sum = minkowski_sum(p, q);
17     return chull(sum); // no normalizado
18 }
19 // escalar poligono
20 vector<Pt> operator*(vector<Pt> &p, td u) {
21     vector<Pt> r; forn (i, sz(p)) r.pb(p[i]*u);
22     return r;
23 }

```

5. Strings

5.1. Hashing

```

1 struct StrHash { // Hash polinomial con exponentes decrecientes.
2     static constexpr ll ms[] = {1'000'000'007, 1'000'000'403};
3     static constexpr ll b = 500'000'000;
4     vector<ll> hs[2], bs[2];
5     StrHash(string const& s) {
6         int n = sz(s);
7         forn(k, 2) {
8             hs[k].resize(n+1), bs[k].resize(n+1, 1);
9             forn(i, n) {
10                 hs[k][i+1] = (hs[k][i] * b + s[i]) % ms[k];
11                 bs[k][i+1] = bs[k][i] * b % ms[k];
12             }
13         }
14     }
15     ll get(int idx, int len) const { // Hashes en `s[idx,
16         // idx+len)`.
17         ll h[2];
18         forn(k, 2) {
19             h[k] = hs[k][idx+len] - hs[k][idx] * bs[k][len] % ms[k];
20             if (h[k] < 0) h[k] += ms[k];
21         }
22         return (h[0] << 32) | h[1];
23 };

```

5.2. Suffix Array

```

1 #define RB(x) ((x) < n ? r[x] : 0)
2 void csort(vector<int>& sa, vector<int>& r, int k) {
3     int n = sz(sa);
4     vector<int> f(max(255, n)), t(n);
5     forn(i, n) ++f[RB(i+k)];
6     int sum = 0;
7     forn(i, max(255, n)) f[i] = (sum += f[i]) - f[i];
8     forn(i, n) t[f[RB(sa[i]+k)]++] = sa[i];
9     sa = t;
10 }
11 vector<int> compute_sa(string& s){ // O(n*log2(n))
12     int n = sz(s) + 1, rank;
13     vector<int> sa(n), r(n), t(n);
14     iota(all(sa), 0);
15     forn(i, n) r[i] = s[i];
16     for (int k = 1; k < n; k *= 2) {
17         csort(sa, r, k), csort(sa, r, 0);
18         t[sa[0]] = rank = 0;
19         forr(i, 1, n) {
20             if (r[sa[i]] != r[sa[i-1]] || RB(sa[i]+k) !=
21                 RB(sa[i-1]+k)) ++rank;
22             t[sa[i]] = rank;
23         }
24         r = t;
25         if (r[sa[n-1]] == n-1) break;
26     }
27     return sa; // sa[i] = i-th suffix of s in lexicographical order
28 }
29 vector<int> compute_lcp(string& s, vector<int>& sa){
30     int n = sz(s) + 1, L = 0;
31     vector<int> lcp(n), plcp(n), phi(n);
32     phi[sa[0]] = -1;
33     forr(i, 1, n) phi[sa[i]] = sa[i-1];
34     forn(i, n) {
35         if (phi[i] < 0) { plcp[i] = 0; continue; }
36         while(s[i+L] == s[phi[i]+L]) ++L;
37         plcp[i] = L;
38         L = max(L - 1, 0);
39     }
40     forn(i, n) lcp[i] = plcp[sa[i]];

```



```

40     return lcp; // lcp[i] = longest common prefix between sa[i-1]
        and sa[i]
41 }

```

5.3. String Functions

```

1  template<class Char=char>vector<int> pfun(basic_string<Char>const&
    w) {
2      int n = sz(w), j = 0; vector<int> pi(n);
3      forr(i, 1, n) {
4          while (j != 0 && w[i] != w[j]) {j = pi[j - 1];}
5          if (w[i] == w[j]) {++j;}
6          pi[i] = j;
7      } // pi[i] = length of longest proper suffix of w[0..i] that is
        also prefix
8      return pi;
9  }
10 template<class Char=char>vector<int> zfun(const
    basic_string<Char>& w) {
11     int n = sz(w), l = 0, r = 0; vector<int> z(n);
12     forr(i, 1, n) {
13         if (i <= r) {z[i] = min(r - i + 1, z[i - 1]);}
14         while (i + z[i] < n && w[z[i]] == w[i + z[i]]) {++z[i];}
15         if (i + z[i] - 1 > r) {l = i, r = i + z[i] - 1;}
16     } // z[i] = length of longest prefix of w that also begins at
        index i
17     return z;
18 }

```

5.4. Kmp

```

1  template<class Char=char>struct Kmp {
2      using str = basic_string<Char>;
3      vector<int> pi; str pat;
4      Kmp(str const& _pat): pi(move(pfun(_pat))), pat(_pat) {}
5      vector<int> matches(str const& txt) const {
6          if (sz(pat) > sz(txt)) {return {};}
7          vector<int> occs; int m = sz(pat), n = sz(txt);
8          if (m == 0) {occs.push_back(0);}
9          int j = 0;
10         forn(i, n) {

```

```

11             while (j != 0 && txt[i] != pat[j]) {j = pi[j-1];}
12             if (txt[i] == pat[j]) {++j;}
13             if (j == m) {occs.push_back(i - j + 1);}
14         }
15         return occs;
16     }
17 };

```

5.5. Manacher

```

1  struct Manacher {
2      vector<int> p;
3      Manacher(string const& s) {
4          int n = sz(s), m = 2*n+1, l = -1, r = 1;
5          vector<char> t(m); forn(i, n) t[2*i+1] = s[i];
6          p.resize(m); forr(i, 1, m) {
7              if (i < r) p[i] = min(r-i, p[l+r-i]);
8              while (p[i] <= i && i < m-p[i] && t[i-p[i]] ==
                t[i+p[i]]) ++p[i];
9              if (i+p[i] > r) l = i-p[i], r = i+p[i];
10         }
11     } // Retorna palindromos de la forma {comienzo, largo}.
12     pii at(int i) const {int k = p[i]-1; return pair{i/2-k/2, k};}
13     pii odd(int i) const {return at(2*i+1);} // Mayor centrado en
        s[i].
14     pii even(int i) const {return at(2*i);} // Mayor centrado en
        s[i-1,i].
15 };

```

5.6. Mínima Rotación Lexicográfica

```

1  // única secuencia no-creciente de strings menores a sus rotaciones
2  vector<pii> lyndon(string const& s) {
3      vector<pii> fs;
4      int n = sz(s);
5      for (int i = 0, j, k; i < n;) {
6          for (k = i, j = i+1; j < n && s[k] <= s[j]; ++j)
7              if (s[k] < s[j]) k = j; else ++k;
8          for (int m = j-k; i <= k; i += m) fs.emplace_back(i, m);
9      }
10     return fs; // retorna substrings de la forma {comienzo, largo}

```

```

11 }
12
13 // último comienzo de la mínima rotación
14 int minrot(string const& s) {
15     auto fs = lyndon(s+s);
16     int n = sz(s), start = 0;
17     for (auto f : fs) if (f.fst < n) start = f.fst; else break;
18     return start;
19 }

```

5.7. Trie

```

1 // trie genérico. si es muy lento, se puede modificar para que los
  // hijos sean
2 // representados con un array del tamaño del alfabeto
3 template<class Char> struct Trie {
4     struct Node {
5         map<Char, Node*> child;
6         bool term;
7     };
8     Node* root;
9     static inline deque<Node> nodes;
10    static Node* make() {
11        nodes.emplace_back();
12        return &nodes.back();
13    }
14    Trie() : root{make()} {}
15    // retorna el largo del mayor prefijo de s que es prefijo de
    // algún string
16    // insertado en el trie
17    int find(basic_string<Char> const& s) const {
18        Node* curr = root;
19        forn(i,sz(s)) {
20            auto it = curr->child.find(s[i]);
21            if (it == end(curr->child)) return i;
22            curr = it->snd;
23        }
24        return sz(s);
25    }
26    // inserta s en el trie

```

```

27 void insert(basic_string<Char> const& s) {
28     Node* curr = root;
29     forn(i,sz(s)) {
30         auto it = curr->child.find(s[i]);
31         if (it == end(curr->child)) curr = curr->child[s[i]] =
            make();
32         else curr = it->snd;
33     }
34     curr->term = true;
35 }
36 // elimina s del trie
37 void erase(basic_string<Char> const& s) {
38     auto erase = [&](auto&& me, Node* curr, int i) -> bool {
39         if (i == sz(s)) {
40             curr->term = false;
41             return sz(curr->child) == 0;
42         }
43         auto it = curr->child.find(s[i]);
44         if (it == end(curr->child)) return false;
45         if (!me(me,it->snd,i+1)) return false;
46         curr->child.erase(it);
47         return sz(curr->child) == 0;
48     };
49     erase(erase,root,0);
50 }
51 };

```

5.8. Suffix Automaton

```

1 /// Minimal DFA that accepts all suffixes of a string.
2 /// - Any path starting at `0` forms a substring.
3 /// - Every substring corresponds to a path starting at `0`.
4 /// - Each state corresponds to the set of all substrings that
    // have the same
5 /// ending positions in the string, that is, each state `u`
    // represents an
6 /// equivalence class according to their ending positions
    // `endpos(u)`.
7 /// Given a state `u`, we can define the following concepts:
8 /// - `longest(u)`: longest substring corresponding to `u`.

```

```

9  /// - `len(u)`: length of `longest(u)`.
10 /// - `shortest(u)`: shortest substring corresponding to `u`.
11 /// - `minlen(u)`: length of `shortest(u)`.
12 /// Any state `u` corresponds to all suffixes of `longest(u)` no
    shorter
13 /// than `minlen(u)`.
14 /// For state `u`, `link(u)` points to the state `v` such that
    `longest(v)`
15 /// is a suffix of `longest(u)` with `len(v) == minlen(u) - 1`.
    These links
16 /// form a tree with the root in `0` and an inclusion
    relationship between
17 /// all `endpos`.
18 template<class Char=char>class SuffixAutomaton {
19     using str = basic_string<Char>;
20     void extend(Char c, int& last) {
21         txt.pb(c); int p = last; last = new_state();
22         len[last] = len[p] + 1, firstpos[last] = len[p];
23         do {next[p][c] = last, p = link[p];} while (p >= 0 &&
            !next[p].count(c));
24         if (p == -1) {link[last] = 0;} else {
25             int q = next[p][c];
26             if (len[q] == len[p] + 1) {link[last] = q;} else {
27                 int cl = copy_state(q);
28                 len[cl] = len[p] + 1; link[last] = link[q] = cl;
29                 do {next[p][c] = cl, p = link[p];} while (p >= 0 &&
                    next[p].at(c) == q);
30             }
31         }
32     }
33     int new_state() {
34         next.pb({}), link.pb(-1), len.pb(0), firstpos.pb(-1);
35         return size++;
36     }
37     int copy_state(int state) {
38         next.pb(next[state]), link.pb(link[state]);
39         len.pb(len[state]), firstpos.pb(firstpos[state]);
40         return size++;
41     }
42     void dfs(int curr=0) {

```

```

43         terminal_paths_from[curr] = term[curr];
44         paths_from[curr] = 1;
45         for(edge, next[curr]) {
46             int other = edge.snd;
47             if (!paths_from[other]) {dfs(other);}
48             terminal_paths_from[curr] += terminal_paths_from[other];
49             paths_from[curr] += paths_from[other];
50             substrings_from[curr] += substrings_from[other];
51         }
52         substrings_from[curr] += terminal_paths_from[curr];
53     }
54     void compute(int last) {
55         term.resize(size);
56         for (int curr = last; curr != -1; curr = link[curr])
57             {term[curr] = true;}
58         inv_link.resize(size);
59         forr(curr, 1, size) {inv_link[link[curr]].pb(curr);}
60     public:
61         vector<bool> term; // Terminal statuses.
62         vector<vector<int>> inv_link; // Inverse suffix links.
63         vector<map<Char, int>> next{{{}}; // Automaton transitions.
64         vector<int> len{0}; // len[u] = length of longest(u)
65         vector<int> link{-1}; // Suffix links.
66         vector<int> firstpos{-1}; // First endpos element of each
            state.
67         // Number of paths starting at each state and ending in a
            terminal state.
68         // For `0`, this is the number of suffixes (including the
            empty suffix).
69         vector<int> terminal_paths_from;
70         // Number of paths starting at each state. For `0`, this is
            the number of
71         // distinct substrings (including the empty substring).
72         vector<ll> paths_from;
73         // Number of substrings starting at each state. For `0`, this
            is the number
74         // of substrings counting repetitions (including the empty
            substring
75         // repeated `n+1` times, where `n` is the length of the

```

```

    original string).
76 vector<ll> substrings_from;
77 int size = 1; // Number of states.
78 str txt; // Original string.
79 SuffixAutomaton(str const& _txt) {
80     int last = 0;
81     fore(c, _txt) {extend(c, last);}
82     compute(last); terminal_paths_from.resize(size);
83     paths_from.resize(size); substrings_from.resize(size);
84     dfs();
85 }
86 pair<int, int> run(str const& pat) const {
87     int curr = 0, read = 0; // curr = last visited state
88     for (
89         auto it = pat.begin();
90         it != pat.end() && next[curr].count(*it);
91         curr = next[curr].at(*(it++))
92     ) {++read;} // read = number of traversed transitions
93     return {curr, read};
94 }
95 bool is_suff(str const& pat) const
96     {auto [state, read] = run(pat); return term[state] && read
97     == sz(pat);}
98 bool is_substr(str const& pat) const {return run(pat).snd ==
99     sz(pat);}
100 int num_occs(str const& pat) const {
101     auto [state, read] = run(pat);
102     return read == sz(pat) ? terminal_paths_from[state] : 0;
103 }
104 int fst_occ(str const& pat) const {
105     int m = sz(pat); auto [state, read] = run(pat);
106     return read == m ? firstpos[state] + 1 - m : -1;
107 }
108 vector<int> all_occs(str const& pat) const {
109     vector<int> occs; int m = sz(pat); auto [node, read] =
110     run(pat);
111     if (read == m) {
112         stack<int> st{{node}};
113         while (!st.empty()) {
114             int curr = st.top(); st.pop();

```

```

111         occs.pb(firstpos[curr] + 1 - m);
112         fore(child, inv_link[curr]) {st.push(child);}
113     }
114 }
115 // sort(all(occs)); occs.erase(unique(all(occs)),
116     occs.end());
117 return occs; // unsorted and nonunique by default
118 };

```

6. Grafos

6.1. Dijkstra

```

1 vector<pair<int,int>> g[MAXN]; // u->[(v,cost)]
2 ll dist[MAXN];
3 // complejidad O((E+V)*log(V))
4 void dijkstra(int x){
5     memset(dist,-1,sizeof(dist));
6     priority_queue<pair<ll,int> > q;
7     dist[x]=0;q.push({0,x});
8     while(!q.empty()){
9         x=q.top().snd;ll c=-q.top().fst;q.pop();
10        if(dist[x]!=c)continue;
11        forn(i,g[x].size()){
12            int y=g[x][i].fst; ll c=g[x][i].snd;
13            if(dist[y]<0||dist[x]+c<dist[y])
14                dist[y]=dist[x]+c,q.push({-dist[y],y});
15        }
16    }
17 }

```

6.2. LCA

```

1 int n;
2 vector<int> g[MAXN];
3
4 vector<int> depth, etour, vtime;
5
6 // operación de la sparse table, escribir `#define oper lca_oper`

```

```

7  int lca_oper(int u, int v) { return depth[u]<depth[v] ? u : v; };
8
9  void lca_dfs(int u) {
10     vtime[u] = sz(etour), etour.push_back(u);
11     for (auto v : g[u]) {
12         if (vtime[v] >= 0) continue;
13         depth[v] = depth[u]+1; lca_dfs(v); etour.push_back(u);
14     }
15 }
16 auto lca_init(int root) {
17     depth.assign(n,0), etour.clear(), vtime.assign(n,-1);
18     lca_dfs(root); st_init(etour);
19 }
20
21 auto lca(int u, int v) {
22     int l = min(vtime[u],vtime[v]);
23     int r = max(vtime[u],vtime[v])+1;
24     return st_query(l,r);
25 }
26 int dist(int u, int v) { return
    depth[u]+depth[v]-2*depth[lca(u,v)]; }

```

6.3. Binary Lifting

```

1  vector<int> g[1<<K]; int n; // K such that 2^K>=n
2  int F[K][1<<K], D[1<<K];
3  void lca_dfs(int x){
4      forn(i, sz(g[x])){
5          int y = g[x][i]; if(y==F[0][x]) continue;
6          F[0][y]=x; D[y]=D[x]+1;lca_dfs(y);
7      }
8  }
9  void lca_init(){
10     D[0]=0;F[0][0]=-1;
11     lca_dfs(0);
12     forr(k,1,K)forn(x,n)
13         if(F[k-1][x]<0)F[k][x]=-1;
14         else F[k][x]=F[k-1][F[k-1][x]];
15 }
16

```

```

17 int lca(int x, int y){
18     if(D[x]<D[y])swap(x,y);
19     for(int k = K-1;k>=0;--k) if(D[x]-(1<<k) >=D[y])x=F[k][x];
20     if(x==y)return x;
21     for(int k=K-1;k>=0;--k)if(F[k][x]!=F[k][y])x=F[k][x],y=F[k][y];
22     return F[0][x];
23 }
24
25 int dist(int x, int y){
26     return D[x] + D[y] - 2*D[lca(x,y)];
27 }

```

6.4. Toposort

```

1  vector<int> g[MAXN];int n;
2  vector<int> tsort(){ // lexicographically smallest topological sort
3      vector<int> r;priority_queue<int> q;
4      vector<int> d(2*n,0);
5      forn(i,n)forn(j,g[i].size())d[g[i][j]]++;
6      forn(i,n)if(!d[i])q.push(-i);
7      while(!q.empty()){
8          int x=-q.top();q.pop();r.pb(x);
9          forn(i,sz(g[x])){
10              d[g[x][i]]--;
11              if(!d[g[x][i]])q.push(-g[x][i]);
12          }
13      }
14      return r; // if not DAG it will have less than n elements
15 }

```

6.5. Deteccion ciclos negativos

```

1  // g[i][j]: weight of edge (i, j) or INF if there's no edge
2  // g[i][i]=0
3  ll g[MAXN][MAXN];int n;
4  void floyd(){ // O(n^3) . Replaces g with min distances
5      forn(k,n)forn(i,n)if(g[i][k]<INF)forn(j,n)if(g[k][j]<INF)
6          g[i][j]=min(g[i][j],g[i][k]+g[k][j]);
7  }
8  bool inNegCycle(int v){return g[v][v]<0;}

```

```

9 bool hasNegCycle(int a, int b){ // true iff there's neg cycle in
    between
10     forn(i,n)if(g[a][i]<INF&&g[i][b]<INF&&g[i][i]<0)return true;
11     return false;
12 }

```

6.6. Camino Euleriano

```

1 // Directed version (uncomment commented code for undirected)
2 struct edge {
3     int y;
4     // list<edge>::iterator rev;
5     edge(int y):y(y){}
6 };
7 list<edge> g[MAXN];
8 void add_edge(int a, int b){
9     g[a].push_front(edge(b));//auto ia=g[a].begin();
10    // g[b].push_front(edge(a));auto ib=g[b].begin();
11    // ia->rev=ib;ib->rev=ia;
12 }
13 vector<int> p;
14 void go(int x){
15     while(g[x].size()){
16         int y=g[x].front().y;
17         //g[y].erase(g[x].front().rev);
18         g[x].pop_front();
19         go(y);
20     }
21     p.push_back(x);
22 }
23 vector<int> get_path(int x){ // get a path that begins in x
24 // check that a path exists from x before calling to get_path!
25     p.clear();go(x);reverse(p.begin(),p.end());
26     return p;
27 }

```

6.7. Camino Hamiltoniano

```

1 constexpr int MAXN = 20;
2 int n;
3 bool adj[MAXN][MAXN];

```

```

4
5 bool seen[1<<MAXN][MAXN];
6 bool memo[1<<MAXN][MAXN];
7 // true sii existe camino simple en el conjunto s que empieza en u
8 bool hamilton(int s, int u) {
9     bool& ans = memo[s][u];
10    if (seen[s][u]) return ans;
11    seen[s][u] = true, s ^= (1<<u);
12    if (s == 0) return ans = true;
13    forn(v,n) if (adj[u][v] && (s&(1<<v)) && hamilton(s,v)) return
        ans = true;
14    return ans = false;
15 }
16 // true sii existe camino hamiltoniano. complejidad O((1<<n)*n*n)
17 bool hamilton() {
18     forn(s,1<<n) forn(u,n) seen[s][u] = false;
19     forn(u,n) if (hamilton((1<<n)-1,u)) return true;
20     return false;
21 }

```

6.8. Tarjan SCC

```

1 vector<int> g[MAXN], ss;
2 int n, num, order[MAXN], lnk[MAXN], nsc, cmp[MAXN];
3 void scc(int u) {
4     order[u] = lnk[u] = ++num;
5     ss.pb(u); cmp[u] = -2;
6     for (auto v : g[u]) {
7         if (order[v] == 0) {
8             scc(v);
9             lnk[u] = min(lnk[u], lnk[v]);
10        }
11        else if (cmp[v] == -2) {
12            lnk[u] = min(lnk[u], lnk[v]);
13        }
14    }
15    if (lnk[u] == order[u]) {
16        int v;
17        do { v = ss.back(); cmp[v] = nsc; ss.pop_back(); }
18        while (v != u);

```

```

19     nsc++;
20 }
21 }
22 void tarjan() {
23     memset(order, 0, sizeof(order)); num = 0;
24     memset(cmp, -1, sizeof(cmp)); nsc = 0;
25     forn (i, n) if (order[i] == 0) scc(i);
26 }

```

6.9. Bellman-Ford

```

1  const int INF=2e9; int n;
2  vector<pair<int,int> > g[MAXN]; // u->[(v,cost)]
3  ll dist[MAXN];
4  void bford(int src){ // O(nm)
5      fill(dist,dist+n,INF);dist[src]=0;
6      forr(_,0,n)forr(x,0,n)if(dist[x]!=INF)for(auto t:g[x]){
7          dist[t.fst]=min(dist[t.fst],dist[x]+t.snd);
8      }
9      forr(x,0,n)if(dist[x]!=INF)for(auto t:g[x]){
10         if(dist[t.fst]>dist[x]+t.snd){
11             // neg cycle: all nodes reachable from t.fst have
12             // -INF distance
13             // to reconstruct neg cycle: save "prev" of each
14             // node, go up from t.fst until repeating a node.
15             // this node and all nodes between the two
16             // occurrences form a neg cycle
17         }
18     }
19 }

```

6.10. Puentes y Articulacion

```

1  // solo para grafos no dirigidos
2  vector<int> g[MAXN];
3  int n, num, root, rootChildren;
4  int order[MAXN], lnk[MAXN], art[MAXN];
5  void bridge_art(int u, int p) {
6      order[u] = lnk[u] = ++num;
7      for (auto v : g[u]) if (v != p) {
8          if (u == root) rootChildren++;

```

```

9          if (order[v] == 0) {
10             bridge_art(v, u);
11             if (lnk[v] >= order[u]) // para puntos de
12                 art[u] = 1; // articulacion.
13             if (lnk[v] > order[u]) // para puentes.
14                 handle_bridge(u, v);
15         }
16         lnk[u] = min(lnk[u], lnk[v]);
17     }
18 }
19 void run() {
20     memset(order, 0, sizeof(order));
21     memset(art, 0, sizeof(art)); num = 0;
22     forn (i, n) {
23         if (order[i] == 0) {
24             root = i; bridge_art(i, -1);
25             art[i] = (rootChildren > 1);
26         }
27     }
28 }

```

6.11. Kruskal

```

1  int uf[MAXN];
2  void uf_init(){memset(uf,-1,sizeof(uf));}
3  int uf_find(int x){return uf[x]<0?x:uf[x]=uf_find(uf[x]);}
4  bool uf_join(int x, int y){
5      x=uf_find(x);y=uf_find(y);
6      if(x==y)return false;
7      if(uf[x]>uf[y])swap(x,y);
8      uf[x]+=uf[y];uf[y]=x;
9      return true;
10 }
11 vector<pair<ll,pair<int,int> > > es; // edges (cost,(u,v))
12 ll kruskal(){ // assumes graph is connected
13     sort(es.begin(),es.end());uf_init();
14     ll r=0;
15     forr(i,0,es.size()){
16         int x=es[i].snd.fst,y=es[i].snd.snd;
17         if(uf_join(x,y))r+=es[i].fst; // (x,y,c) belongs to mst

```

```

18     }
19     return r; // total cost
20 }

```

6.12. Chequeo Bipartito

```

1  int n;
2  vector<int> g[MAXN];
3
4  bool color[MAXN];
5  bool bicolor() {
6      vector<bool> seen(n);
7      auto dfs = [&](auto&& me, int u, bool c) -> bool {
8          color[u] = c, seen[u] = true;
9          for (int v : g[u]) {
10             if (seen[v] && color[v] == color[u]) return false;
11             if (!seen[v] && !me(me,v,!c)) return false;
12         }
13         return true;
14     };
15     forn(u,n) if (!seen[u] && !dfs(dfs,u,0)) return false;
16     return true;
17 }

```

6.13. Centroid Decomposition

```

1  bool vis[MAXN]; //para centroides
2  vector<int> g[MAXN]; int size[MAXN];
3  vector<int> g1[MAXN]; //para centroides
4  void calcsz(int u, int p) {
5      size[u] = 1;
6      for (int v : g[u]) if (v != p && !vis[v]) {
7          calcsz(v, u); size[u] += size[v]; }
8  }
9  int cendfs(int u, int p, int ts) {
10     int maximo = 0, pesado, r;
11     for (int v : g[u]) if (v != p && !vis[v]) {
12         if (maximo < size[v]) {
13             maximo = size[v]; pesado = v; }
14     }
15     if (maximo <= (ts/2)) {

```

```

16         vis[u] = true;
17         for (int v : g[u]) if (!vis[v]) {
18             if (v == p) calcsz(v, u);
19             r = cendfs(v, u, hijos[v]);
20             add_edge(g1, u, r);
21         }
22         r = u;
23     }
24     else r = cendfs(pesado, u, ts);
25     return r;
26 }
27 // euler para responder en el arbol de centroides
28 int te[MAXN], ts[MAXN]; vector<Partial> euler;
29 void do_euler(int u, int p, Partial &p) {
30     te[u] = sz(euler); euler.pb(c);
31     for (int v : g[u]) if (v != p && !vis[v]) {
32         do_euler(v, u, p); } //cambiar p
33     ts[u] = sz(euler);
34 }
35 Sol oncen(int u, int p) {
36     do_euler(u, p, Partial{});
37     vis[u] = true; //no tocar visitados
38     Sol r{};
39     for (int v : g1[u]) if (v != p) {
40         r = max(r, oncen(v, u)); }
41     return r;
42 }

```

6.14. HLD

```

1  vector<int> g[MAXN];
2  int wg[MAXN], dad[MAXN], dep[MAXN]; // weight, father, depth
3  void dfs1(int x){
4      wg[x]=1;
5      for(int y:g[x])if(y!=dad[x]){
6          dad[y]=x;dep[y]=dep[x]+1;dfs1(y);
7          wg[x]+=wg[y];
8      }
9  }
10 int curpos,pos[MAXN],head[MAXN];

```



```

11 void hld(int x, int c){
12     if(c<0)c=x;
13     pos[x]=curpos++;head[x]=c;
14     int mx=-1;
15     for(int y:g[x])if(y!=dad[x]&&(mx<0||wg[mx]<wg[y]))mx=y;
16     if(mx>=0)hld(mx,c);
17     for(int y:g[x])if(y!=mx&&y!=dad[x])hld(y,-1);
18 }
19 void hld_init(){dad[0]=-1;dep[0]=0;dfs1(0);curpos=0;hld(0,-1);}
20 int query(int x, int y, RMQ& rmq){
21     int r=neutro; //neutro del rmq
22     while(head[x]!=head[y]){
23         if(dep[head[x]]>dep[head[y]])swap(x,y);
24         r=oper(r,rmq.get(pos[head[y]],pos[y]+1));
25         y=dad[head[y]];
26     }
27     if(dep[x]>dep[y])swap(x,y); // now x is lca
28     r=oper(r,rmq.get(pos[x],pos[y]+1));
29     return r;
30 }
31 // hacer una vez al principio hld_init() después de armar el grafo
   en g
32 // para querys pasar los dos nodos del camino y un stree que tiene
   en pos[x] el valor del nodo x
33 // for updating: rmq.set(pos[x],v);
34 // queries on edges: - assign values of edges to "child" node ()
   ***
35 // - change pos[x] to pos[x]+1 in query (line 28)
36 // *** if(dep[u] > dep[v]) rmq.upd(pos[u], w) para cada arista
   (u,v)

```

6.15. Max Tree Matching

```

1 int n, r, p[MAXN]; // número de nodos, raíz, y lista de padres
2 vector<int> g[MAXN]; // lista de adyacencia
3
4 int match[MAXN];
5 // encuentra el max matching del árbol. complejidad O(n)
6 int maxmatch() {
7     fill(match,match+n,-1);

```

```

8     int size = 0;
9     auto dfs = [&](auto&& me, int u) -> int {
10         for (auto v : g[u]) if (v != p[u])
11             if (match[u] == me(me,v)) match[u] = v, match[v] = u;
12         size += match[u] >= 0;
13         return match[u];
14     };
15     dfs(dfs,r);
16     return size;
17 }

```

6.16. Min Tree Vertex Cover

```

1 int n, r, p[MAXN]; // número de nodos, raíz, y lista de padres
2 vector<int> g[MAXN]; // lista de adyacencia
3
4 bool cover[MAXN];
5 // encuentra el min vertex cover del árbol. complejidad O(n)
6 int mincover() {
7     fill(cover,cover+n,false);
8     int size = 0;
9     auto dfs = [&](auto&& me, int u) -> bool {
10         for (auto v : g[u]) if (v != p[u] && !me(me,v)) cover[u] =
            true;
11         size += cover[u];
12         return cover[u];
13     };
14     dfs(dfs,r);
15     return size;
16 }

```

6.17. 2-SAT

```

1 struct TwoSatSolver{
2     int n_vars;
3     int n_vertices;
4     vector<vector<int>>> adj, adj_t;
5     vector<bool> used;
6     vector<int> order,comp;
7     vector<bool> assignment;
8     TwoSatSolver(int n_vars) : n_vars(n_vars),

```

```

9      n_vertices(2*n_vars), adj(n_vertices),
10      adj_t(n_vertices), used(n_vertices),
11      order(), comp(n_vertices, -1), assignment(n_vars){
12      order.reserve(n_vertices);
13  }
14  void dfs1(int v){
15      used[v] = true;
16      for(int u : adj[v]){
17          if(!used[u]) dfs1(u);
18      }
19      order.pb(v);
20  }
21  void dfs2(int v, int c1){
22      comp[v] = c1;
23      for(int u : adj_t[v]){
24          if(comp[u] == -1) dfs2(u, c1);
25      }
26  }
27  bool solve_2SAT(){
28      order.clear();
29      used.assign(n_vertices, false);
30      forn(i, n_vertices){
31          if(!used[i]) dfs1(i);
32      }
33      comp.assign(n_vertices, -1);
34      for(int i = 0, j = 0; i < n_vertices; ++i){
35          int v = order[n_vertices - i - 1];
36          if(comp[v] == -1) dfs2(v, j++);
37      }
38      assignment.assign(n_vars, false);
39      for(int i = 0; i < n_vertices; i+=2){
40          if(comp[i] == comp[i+1]) return false;
41          assignment[i/2] = comp[i] > comp[i+1];
42      }
43      return true;
44  }
45  void add_disjunction(int a, bool na, int b, bool nb){
46      a = 2 * a ^ na;
47      b = 2 * b ^ nb;
48      int neg_a = a ^ 1;

```

```

49      int neg_b = b ^ 1;
50      adj[neg_a].pb(b);
51      adj[neg_b].pb(a);
52      adj_t[b].pb(neg_a);
53      adj_t[a].pb(neg_b);
54  }
55  };

```

6.18. K Colas

```

1  const int K=9999; // en general, K = MAX_DIST+1
2  vector<Datos> colas[K];
3  int cola_actual = 0, ult_cola = -1;
4  // push toma la dist actual y la siguiente
5  #define push(d,nd,args...)
6      colas[(cola_actual+nd-d)%K].emplace_back(nd, args)
7  #define pop colas[cola_actual].pop_back
8  #define top colas[cola_actual].back
9  // PUSHEAR POSICION INICIAL
10 for (; ; cola_actual = (cola_actual+1)%K) {
11     if (ult_cola == cola) break; // dimos la vuelta
12     if (colas[cola_actual].size()) ult_cola = cola;
13     while (colas[cola_actual].size()) {
14         }
15 }

```

7. Flujo

7.1. Dinic

```

1  // complejidad  $O(V^2 * E)$ 
2  struct Dinic{
3      int nodes,src,dst;
4      vector<int> dist,q,work;
5      struct edge {int to,rev;ll f,cap;};
6      vector<vector<edge>> g;
7      Dinic(int x):nodes(x),g(x),dist(x),q(x),work(x){}
8      void add_edge(int s, int t, ll cap){
9          g[s].pb((edge){t,sz(g[t]),0,cap});

```

```

10     g[t].pb((edge){s,sz(g[s])-1,0,0});
11 }
12 bool dinic_bfs(){
13     fill(all(dist),-1);dist[src]=0;
14     int qt=0;q[qt++]=src;
15     for(int qh=0;qh<qt;qh++){
16         int u=q[qh];
17         forn(i,sz(g[u])){
18             edge &e=g[u][i];int v=g[u][i].to;
19             if(dist[v]<0&&e.f<e.cap)dist[v]=dist[u]+1,q[qt++]=v;
20         }
21     }
22     return dist[dst]>=0;
23 }
24 ll dinic_dfs(int u, ll f){
25     if(u==dst)return f;
26     for(int &i=work[u];i<sz(g[u]);i++){
27         edge &e=g[u][i];
28         if(e.cap<=e.f)continue;
29         int v=e.to;
30         if(dist[v]==dist[u]+1){
31             ll df=dinic_dfs(v,min(f,e.cap-e.f));
32             if(df>0){e.f+=df;g[v][e.rev].f-=df;return df;}
33         }
34     }
35     return 0;
36 }
37 ll max_flow(int _src, int _dst){
38     src=_src;dst=_dst;
39     ll result=0;
40     while(dinic_bfs()){
41         fill(all(work),0);
42         while(ll delta=dinic_dfs(src,INF))result+=delta;
43     }
44     return result;
45 }
46 };

```

7.2. Min Cost Max Flow

```

1  typedef ll tf;
2  typedef ll tc;
3  const tf INFFLOW=1e9;
4  const tc INFCOST=1e9;
5  // complejidad  $O(V^2 * E * \log(V))$ 
6  struct MCF{
7      int n;
8      vector<tc> prio, pot; vector<tf> curflow; vector<int>
9          prevedge,prevnode;
10     priority_queue<pair<tc, int>, vector<pair<tc, int>>,
11         greater<pair<tc, int>>> q;
12     struct edge{int to, rev; tf f, cap; tc cost;};
13     vector<vector<edge>> g;
14     MCF(int
15         n):n(n),prio(n),curflow(n),prevedge(n),prevnode(n),pot(n),g(n){}
16     void add_edge(int s, int t, tf cap, tc cost) {
17         g[s].pb((edge){t,sz(g[t]),0,cap,cost});
18         g[t].pb((edge){s,sz(g[s])-1,0,0,-cost});
19     }
20     pair<tf,tc> get_flow(int s, int t) {
21         tf flow=0; tc flowcost=0;
22         while(1){
23             q.push({0, s});
24             fill(all(prio),INFCOST);
25             prio[s]=0; curflow[s]=INFFLOW;
26             while(!q.empty()) {
27                 auto cur=q.top();
28                 tc d=cur.fst;
29                 int u=cur.snd;
30                 q.pop();
31                 if(d!=prio[u]) continue;
32                 for(int i=0; i<sz(g[u]); ++i) {
33                     edge &e=g[u][i];
34                     int v=e.to;
35                     if(e.cap<=e.f) continue;
36                     tc nprio=prio[u]+e.cost+pot[u]-pot[v];
37                     if(prio[v]>nprio) {
38                         prio[v]=nprio;
39                         q.push({nprio, v});
40                         prevnode[v]=u; prevedge[v]=i;

```

```

38         curflow[v]=min(curflow[u], e.cap-e.f);
39     }
40 }
41 }
42 if(prio[t]==INFCOST) break;
43 forr(i,0,n) pot[i]+=prio[i];
44 tf df=min(curflow[t], INFFLOW-flow);
45 flow+=df;
46 for(int v=t; v!=s; v=prevnode[v]) {
47     edge &e=g[prevnode[v]][prevedge[v]];
48     e.f+=df; g[v][e.rev].f-=df;
49     flowcost+=df*e.cost;
50 }
51 }
52 return {flow,flowcost};
53 }
54 };

```

7.3. Hopcroft Karp

```

1  int n, m;           // número de nodos en ambas partes
2  vector<int> g[MAXN]; // lista de adyacencia [0,n) -> [0,m)
3
4  int mat[MAXN]; // matching [0,n) -> [0,m)
5  int inv[MAXM]; // matching [0,m) -> [0,n)
6  // encuentra el max matching del grafo bipartito
7  // complejidad  $O(\sqrt{n+m} \cdot e)$ , donde e es el número de aristas
8  int hopkarp() {
9      fill(mat,mat+n,-1);
10     fill(inv,inv+m,-1);
11     int size = 0;
12     vector<int> d(n);
13     auto bfs = [&] {
14         bool aug = false;
15         queue<int> q;
16         forn(u,n) if (mat[u] < 0) q.push(u); else d[u] = -1;
17         while (!q.empty()) {
18             int u = q.front();
19             q.pop();
20             for (auto v : g[u]) {

```

```

21                 if (inv[v] < 0) aug = true;
22                 else if (d[inv[v]] < 0) d[inv[v]] = d[u] + 1,
23                     q.push(inv[v]);
24             }
25         }
26         return aug;
27     };
28     auto dfs = [&](auto&& me, int u) -> bool {
29         for (auto v : g[u]) if (inv[v] < 0) {
30             mat[u] = v, inv[v] = u;
31             return true;
32         }
33         for (auto v : g[u]) if (d[inv[v]] > d[u] && me(me,inv[v])) {
34             mat[u] = v, inv[v] = u;
35             return true;
36         }
37         d[u] = 0;
38         return false;
39     };
40     while (bfs()) forn(u,n) if (mat[u] < 0) size += dfs(dfs,u);
41     return size;
42 }

```

7.4. Kuhn

```

1  int n, m;           // número de nodos en ambas partes
2  vector<int> g[MAXN]; // lista de adyacencia [0,n) -> [0,m)
3
4  int mat[MAXN]; // matching [0,n) -> [0,m)
5  int inv[MAXM]; // matching [0,m) -> [0,n)
6  // encuentra el max matching del grafo bipartito
7  // complejidad  $O(n \cdot e)$ , donde e es el número de aristas
8  int kuhn() {
9      fill(mat,mat+n,-1);
10     fill(inv,inv+m,-1);
11     int root, size = 0;
12     vector<int> seen(n,-1);
13     auto dfs = [&](auto&& me, int u) -> bool {
14         seen[u] = root;
15         for (auto v : g[u]) if (inv[v] < 0) {

```

```

16         mat[u] = v, inv[v] = u;
17         return true;
18     }
19     for (auto v : g[u]) if (seen[inv[v]] < root &&
20         me(me, inv[v])) {
21         mat[u] = v, inv[v] = u;
22         return true;
23     }
24     return false;
25 };
26 forn(u,n) size += dfs(dfs, root=u);
27 return size;
28 }

```

7.5. Min Vertex Cover Bipartito

```

1 // requisito: max matching bipartito, por defecto Hopcroft-Karp
2
3 vector<bool> cover[2]; // nodos cubiertos en ambas partes
4 // encuentra el min vertex cover del grafo bipartito
5 // misma complejidad que el algoritmo de max matching bipartito
  elegido
6 int konig() {
7     cover[0].assign(n, true);
8     cover[1].assign(m, false);
9     int size = hopkarp(); // alternativamente, también funciona
    con Kuhn
10    auto dfs = [&](auto&& me, int u) -> void {
11        cover[0][u] = false;
12        for (auto v : g[u]) if (!cover[1][v]) {
13            cover[1][v] = true;
14            me(me, inv[v]);
15        }
16    };
17    forn(u,n) if (mat[u] < 0) dfs(dfs, u);
18    return size;
19 }

```

7.6. Hungarian

```

1 typedef long double td; typedef vector<int> vi; typedef vector<td>
  vd;
2 const td INF=1e100; //for maximum set INF to 0, and negate costs
3 bool zero(td x){return fabs(x)<1e-9;} //change to x==0, for ints/ll
4 struct Hungarian{
5     int n; vector<vd> cs; vi L, R;
6     Hungarian(int N, int M):n(max(N,M)),cs(n,vd(n)),L(n),R(n){
7         forr(x,0,N)forr(y,0,M)cs[x][y]=INF;
8     }
9     void set(int x,int y,td c){cs[x][y]=c;}
10    td assign() {
11        int mat = 0; vd ds(n), u(n), v(n); vi dad(n), sn(n);
12        forr(i,0,n)u[i]=*min_element(all(cs[i]));
13        forr(j,0,n){
14            v[j]=cs[0][j]-u[0];
15            forr(i,1,n)v[j]=min(v[j],cs[i][j]-u[i]);
16        }
17        L=R=vi(n, -1);
18        forr(i,0,n)forr(j,0,n) {
19            if(R[j]==-1&&zero(cs[i][j]-u[i]-v[j])){
20                L[i]=j;R[j]=i;mat++;break;
21            } }
22        for(;mat<n;mat++){
23            int s=0, j=0, i;
24            while(L[s] != -1)s++;
25            fill(all(dad),-1);fill(all(sn),0);
26            forr(k,0,n)ds[k]=cs[s][k]-u[s]-v[k];
27            for(;;){
28                j = -1;
29                forr(k,0,n)if(!sn[k]&&(j==-1||ds[k]<ds[j]))j=k;
30                sn[j] = 1; i = R[j];
31                if(i == -1) break;
32                forr(k,0,n)if(!sn[k]){
33                    auto new_ds=ds[j]+cs[i][k]-u[i]-v[k];
34                    if(ds[k] > new_ds){ds[k]=new_ds;dad[k]=j;}
35                }
36            }
37            forr(k,0,n)if(k!=j&&sn[k]){auto
                w=ds[k]-ds[j];v[k]+=w,u[R[k]]-=w;}
38            u[s] += ds[j];

```

```

39         while(dad[j]>=0){int d =
            dad[j];R[j]=R[d];L[R[j]]=j;j=d;}
40         R[j]=s;L[s]=j;
41     }
42     td value=0;forr(i,0,n)value+=cs[i][L[i]];
43     return value;
44 }
45 };

```

8. Optimización

8.1. Ternary Search

```

1 // mínimo entero de f en (l,r)
2 ll ternary(auto f, ll l, ll r) {
3     for (ll d = r-l; d > 2; d = r-l) {
4         ll a = l+d/3, b = r-d/3;
5         if (f(a) > f(b)) l = a; else r = b;
6     }
7     return l+1; // retorna un punto, no un resultado de evaluar f
8 }
9
10 // mínimo real de f en (l,r)
11 // para error < EPS, usar iters = log((r-l)/EPS)/log(1.618)
12 double golden(auto f, double l, double r, int iters) {
13     constexpr double ratio = (3-sqrt(5))/2;
14     double x1 = l+(r-l)*ratio, f1 = f(x1);
15     double x2 = r-(r-l)*ratio, f2 = f(x2);
16     while (iters--) {
17         if (f1 > f2) l=x1, x1=x2, f1=f2, x2=r-(r-l)*ratio, f2=f(x2);
18         else r=x2, x2=x1, f2=f1, x1=l+(r-l)*ratio, f1=f(x1);
19     }
20     return (l+r)/2; // retorna un punto, no un resultado de
        evaluar f
21 }

```

8.2. Longest Increasing Subsequence

```

1 // subsecuencia creciente más larga
2 // para no decreciente, borrar la línea 9 con el continue

```

```

3 template<class Type> vector<int> lis(vector<Type>& a) {
4     int n = sz(a);
5     vector<int> seq, prev(n,-1), idx(n+1,-1);
6     vector<Type> dp(n+1,INF); dp[0] = -INF;
7     forn(i,n) {
8         int l = int(upper_bound(all(dp),a[i])-begin(dp));
9         if (dp[l-1] == a[i]) continue;
10        prev[i] = idx[l-1], idx[l] = i, dp[l] = a[i];
11    }
12    dforn(i,n+1) {
13        if (dp[i] < INF) {
14            for (int k = idx[i]; k >= 0; k = prev[k]) seq.pb(k);
15            reverse(all(seq));
16            break;
17        }
18    }
19    return seq;
20 }

```

9. Otros

9.1. Mo

```

1 int n,sq,nq; // array size, sqrt(array size), #queries
2 struct qu{int l,r,id;};
3 qu qs[MAXN];
4 ll ans[MAXN]; // ans[i] = answer to ith query
5 bool qcomp(const qu &a, const qu &b){
6     if(a.l/sq!=b.l/sq) return a.l<b.l;
7     return (a.l/sq)&1?a.r<b.r:a.r>b.r;
8 }
9 void mos(){
10     forn(i,nq)qs[i].id=i;
11     sq=sqrt(n)+.5;
12     sort(qs,qs+nq,qcomp);
13     int l=0,r=0;
14     init();
15     forn(i,nq){
16         qu q=qs[i];
17         while(l>q.l)add(--l);

```

```

18     while(r<q.r)add(r++);
19     while(l<q.l)remove(l++);
20     while(r>q.r)remove(--r);
21     ans[q.id]=get_ans();
22 }
23 }

```

9.2. Divide and Conquer Optimization

```

1 vector<ll> dp_ant, dp_curr;
2
3 void compute(int l, int r, int optl, int optr){
4     if(l == r) return;
5     int m = (l+r)/2;
6     ll dpm = 1e17;
7     int optm = -1;
8     forr(i, max(m+1, optl), optr+1){
9         ll cost = C(m, i) + (i == n ? 0 : dp_ant[i]);
10        if(cost < dpm) dpm = cost, optm = i;
11    }
12    dp_curr[m] = dpm;
13    compute(l, m, optl, optm);
14    compute(m+1, r, optm, optr);
15 }
16
17 forn(i, k){
18     compute(0, n, 0, n);
19     dp_ant = dp_curr;
20 }
21
22 cout << dp_curr[0] << endl;

```

9.3. Fijar el numero de decimales

```

1 // antes de imprimir decimales, con una sola vez basta
2 cout << fixed << setprecision(DECIMAL_DIG);

```

9.4. Hash Table (Unordered Map/ Unordered Set)

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;

```

```

3 template<class Key, class Val=null_type>using
    htable=gp_hash_table<Key,Val>;
4 // como unordered_map (o unordered_set si Val es vacio), pero sin
    metodo count

```

9.5. Indexed Set

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;
3 template<class Key, class Val=null_type>
4 using indexed_set = tree<Key, Val, less<Key>, rb_tree_tag,
5                        tree_order_statistics_node_update>;
6 // indexed_set<char> s;
7 // char val = *s.find_by_order(0); // acceso por indice
8 // int idx = s.order_of_key('a'); // busca indice del valor

```

9.6. Subconjuntos

```

1 // iterar por mascarar  $O(2^n)$ 
2 for(int bm=0; bm<(1<<n); bm++)
3 // subconjuntos de una mascara  $O(2^n)$ 
4 for(int sbm=bm; sbm; sbm=(sbm-1)&bm)
5 // iterar por submascaras  $O(3^n)$ 
6 for(int bm=0; bm<(1<<n); bm++)
7     for(int sbm=bm; sbm; sbm=(sbm-1)&(bm))
8 // para superconjuntos (que contienen a bm),
9 // negar la mascara: bm=~bm

```

9.7. Simpson

```

1 // integra f en [a,b] llamándola 2*n veces
2 double simpson(auto f, double a, double b, int n=1e4) {
3     double h = (b-a)/2/n, s = f(a);
4     forr(i,1,2*n) s += f(a+i*h) * ((i%2)?4:2);
5     return (s+f(b))*h/3;
6 }

```

9.8. Pragmas

```

1 #pragma GCC target("avx2")
2 #pragma GCC optimize("O3")
3 #pragma GCC optimize("unroll-loops")

```

9.9. Random

```
1 unsigned seed =
    std::chrono::steady_clock::now().time_since_epoch().count();
2 mt19937 generator(seed);
3 generator(); // generar un número aleatorio entre 0 y 4294967295
4 // existe mt19937_64 para la versión de 64 bits, que probablemente
    sea más rápido
5
6 /*
7 // también se puede hacer lo siguiente para una versión hasta 3x
    más rápida:
8 #include <ext/random>
9 using namespace __gnu_cxx;
10 unsigned seed =
    std::chrono::steady_clock::now().time_since_epoch().count();
11 sfmt19937 generator(seed); // existe también sfmt19937_64
12 */
13
14 uniform_int_distribution<ll> dist_int(L, R);
15 dist_int(generator); // generar un entero en [L, R]
    (cerrado-cerrado) con prob uniforme
16
17 uniform_real_distribution<double> dist_real(0.0, 1.0);
18 dist_real(generator); // generar un real en [0, 1)
    (cerrado-abierto) con prob uniforme
```

9.10. Utilidades de strings

```
1 getline(cin, linea); // tomar toda la línea
2 stringstream ss(linea); // tratar una línea como stream
3 ss >> s; ss << s; // leer solo hasta un espacio, escribir a ss
4 tipo n; ss >> n; // leer de un stringstream (float, int, etc.)
5 int pos = s.find_first_of("aeoiu"); // devuelve -1 si no encuentra
6 int next = s.find_first_of("aeoiu", pos);
7 // s.find_first_not_of("aeoiu"); s.find_last_of();
8 s.substr(pos, next-pos); // substr(pos, len)
9 s.c_str(); // devuelve un puntero de C
10 ss.str(); // devuelve el string en ss
11 // isspace(); islower(); isupper(); isdigit(); isalpha();
12 // tolower(); toupper();
```