

gat-typst Package Manual

Version 0.1.0

A comprehensive Typst package for academic writing, homework assignments, and cheatsheets

Contents

1	Introduction	4
1.1	Key Features	4
1.2	Installation	4
1.3	Quick Start	4
2	Important Behavior Changes	6
2.1	Math Shorthands	6
2.1.1	Complete Shorthand List	6
2.1.2	Warning About $\star$ Shorthand	6
2.1.3	Disabling Shorthands	7
2.1.4	Examples	7
2.2	Superscript Transformations	7
2.2.1	Transpose ($\top$)	7
2.2.2	Dagger ($+$)	7
2.2.3	Star ($*$)	8
2.2.4	Interaction with Shorthands	8
3	Utilities	9
3.1	Math Utilities	9
3.1.1	Statistics Functions	9
3.1.2	Reasoning Operators	9
3.1.3	Machine Learning / RL	9
3.1.4	Miscellaneous	9
3.1.5	Custom Math Function Factory	9
3.2	Box Utilities	10
3.2.1	<code>gatbox()</code>	10
3.2.1.1	Basic Usage	10
3.2.1.2	Color Cycling	10
3.2.1.3	Parameters	10
3.2.1.4	Examples	10
3.2.2	<code>showybox</code>	11
3.3	Display Utilities	11
3.3.1	Show Rules	11
4	Style Function	12
4.1	Code Styling	12
4.1.1	Automatic Changes	12

4.1.2	Example	12
4.2	Table Styling	12
5	Templates	13
5.1	Style Function	13
5.1.1	Usage	13
5.1.2	Parameters	13
5.1.3	Features Provided	13
5.1.4	Example	13
5.2	Homework Template	15
5.2.1	Usage	15
5.2.2	Parameters	15
5.2.3	Components	15
5.2.3.1	question()	15
5.2.3.2	solution()	16
5.2.3.3	boxed-solution	16
5.2.3.4	sub-solution	16
5.2.3.5	notes	16
5.2.4	Complete Example	16
5.3	Cheatsheet Template	18
5.3.1	Usage	18
5.3.2	Parameters	18
5.3.3	Features	18
5.3.4	Example	18
6	Dependencies & Imports	20
6.1	Overview	20
6.2	Diagramming	21
6.2.1	CeTZ (v0.4.2)	21
6.2.2	CeTZ Plot (v0.1.2)	21
6.2.3	Fletcher (v0.5.8)	21
6.2.4	Lilaq (v0.5.0)	22
6.3	Math	22
6.3.1	Matset (v0.1.0)	22
6.3.2	Equate (v0.3.2)	22
6.3.3	Physica (v0.9.6)	22
6.3.4	Quick-maths (v0.2.1)	23
6.3.5	Mannot (v0.3.0)	23
6.4	Code	23
6.4.1	Callisto (v0.2.4)	23
6.4.2	Lovelace (v0.3.0)	24
6.4.3	Codly (v1.3.0) + Codly Languages (v0.1.1)	24
6.4.4	Cmarker (v0.1.6)	24
6.5	Display & Formatting	25
6.5.1	Frame-it (v1.2.0)	25
6.5.2	FontAwesome (v0.6.0)	25

6.5.3	Showybox (v2.0.4)	25
6.5.4	Hydra (v0.6.2)	25
6.5.5	Booktabs (v0.0.4)	26
6.6	Compatibility	26
6.6.1	MiTeX (v0.2.5)	26
6.7	Color	26
6.7.1	Splash (v0.5.0)	26
6.7.2	Typpuccino (v0.1.0)	26
7	Complete Examples	28
7.1	Simple Homework Document	28
7.2	Math-Heavy Solution with Custom Functions	28
7.3	Compact Cheatsheet	29
8	Tips & Best Practices	31
8.1	Math Notation	31
8.2	Layout	31
8.3	Organization	32
8.4	Code	33
8.5	Performance	33
8.6	Common Pitfalls	33
9	Reference	34
9.1	Quick Import Guide	34
9.2	Template Comparison	34
9.3	Function Reference	34
9.3.1	Styling	34
9.3.2	Templates	34
9.3.3	Components	34
9.3.4	Boxes	34
9.3.5	Math (Statistics)	34
9.3.6	Math (Other)	35
9.3.7	Utilities	35
9.4	Further Reading	35
9.5	Version History	35

1 Introduction

The `gat-typst` package is a comprehensive template system for academic writing in Typst, with a focus on mathematics-heavy homework assignments, cheatsheets, and technical documents. It provides opinionated defaults, extensive math utilities, and a curated collection of the best packages from the Typst ecosystem.

This is a growing library for Gatlen Culp's personal usage and is unstable.

1.1 Key Features

- **Templates:** Ready-to-use templates for homework and cheatsheets
- **Math Utilities:** Enhanced math notation with semantic symbols and custom functions
- **Optional Styling:** Professional defaults for code, tables, equations, and math shorthands (opt-in via style)
- **Convenience Functions:** Colored boxes, custom math operators, and more
- **Integrated Packages:** Core packages for math, code, and formatting

1.2 Installation

To use this package locally, ensure it's installed in your local Typst packages directory:

```
1 # Unix-like systems
2 ~/.local/share/typst/packages/local/gat-typst/0.1.0/
3
4 # Windows
5 %APPDATA%/typst/packages/local/gat-typst/0.1.0/
```

Shell

Then import it in your Typst documents:

```
1 #import "@local/gat-typst:0.1.0": *
```

Typst

1.3 Quick Start

Here's a minimal homework document to get started:

```
1 #import "@local/gat-typst:0.1.0": *
2
3 #show: homework.with(
4   title: "Homework 1",
5   course: "CS 101",
6   university: "Your University",
7   author: "Your Name",
8   email: "you@example.com",
9   date: datetime.today(),
10 )
11
12 // Optional: Enable enhanced styling (math shorthands, code styling, etc.)
13 #show: style.with()
14
15 #question(status: "done")[
16   Prove that  $P = N P$ .
```

Typst

```
17 ]
18
19 #solution[
20     Left as an exercise to the reader.
21
22     Using our custom math utilities:
23      $E(X^2) \geq (E(X))^2$  by Jensen's inequality.
24 ]
```

2 Important Behavior Changes

When using the `style` function, several default behaviors are modified for improved mathematical typesetting and consistency. **These changes are opt-in** - you must explicitly use `#show: style.with()` to enable them.

2.1 Math Shorthands

The `style` function enables extensive math operator shorthands via the `quick-maths` package.

2.1.1 Complete Shorthand List

Operators:

1	<code>\$a ** b\$</code>	// Small asterisk	Typst
2	<code>\$a * b\$</code>	// Centered dot ⚠	
3	<code>\$a +- b\$</code>	// Plus-minus	
4	<code>\$A - B\$</code>	// Turnstile	
5	<code>\$a o+ b\$</code>	// Circled plus	
6	<code>\$a o. b\$</code>	// Circled dot	
7	<code>\$a @ b\$</code>	// Also circled dot	

$a * b$ $a \cdot b$ $a \pm b$

$A \vdash B$ $ao + b$

$ao.b$ $a@b$

Logic:

1	<code>\$a .. b\$</code>	// Spacing (quad)	Typst
2	<code>\$A :. B\$</code>	// Therefore	
3	<code>\$A :' B\$</code>	// Because	

$a \quad b$

$A \therefore B$ $A \because B$

Relations:

1	<code>\$a -<= b\$</code>	// Precedes or equals	Typst
2	<code>\$a -< b\$</code>	// Precedes	
3	<code>\$a >-= b\$</code>	// Succeeds or equals	
4	<code>\$a >- b\$</code>	// Succeeds	
5	<code>\$a -= b\$</code>	// Equivalent	
6	<code>\$a ~= b\$</code>	// Asymptotically equal	
7	<code>\$a ~~ b\$</code>	// Approximately	

$a \preceq b$ $a \prec b$

$a \succeq b$ $a \succ b$

$a \equiv b$ $a \cong b$ $a \approx b$

Brackets:

1	<code>\$<< a, b >>\$</code>	// Angle brackets	Typst
2	<code>\$a == b\$</code>	// Equals (unchanged)	

$\ll a, b \gg$

$a = b$

2.1.2 Warning About * Shorthand

The `*` $\rightarrow$ `dot.op` replacement is the most impactful change:

1	// With shorthands (default):	Typst
2	<code>\$a * b\$</code>	// Renders: $a \cdot b$
3	<code>\$a ** b\$</code>	// Renders: $a * b$ (small asterisk)
4		

```
5 // To use literal asterisk:
6 $a ast b$           // Renders: a * b
```

$a \cdot b$ (renders as $a \cdot b$)

$a * b$ (small asterisk)

$a \cdot b$ (literal asterisk)

This follows conventions in linear algebra and physics but may surprise users expecting traditional asterisk multiplication.

2.1.3 Disabling Shorthands

Shorthands are disabled by default. To enable them, use:

```
1 #show: style.with()
```

If you want to use style without shorthands, you can disable them:

```
1 #show: style.with(enable-shorthands: false)
```

Note: Currently this parameter exists but shorthands are applied regardless when `style` is used. This will be fixed in a future version.

2.1.4 Examples

```
1 // Statistics
2 $Ex(X) .. Var(X) = Ex(X^2) - (Ex(X))^2$
3
4 // Linear algebra
5 $A * B \neq B * A .. "in general"$
6
7 // Logic
8 $x > 0 \therefore x^2 > 0$
9
10 // Approximation
11 $e \approx 2.718$
12
13 // Relations
14 $x \preceq y \text{ "iff" } f(x) \leq f(y)$
```

$$\mathbb{E}[X] \quad \text{Var}[X] = \mathbb{E}[X^2] - (\mathbb{E}[X])^2$$

$$A \cdot B \neq B \cdot A \quad \text{in general}$$

$$x > 0 \therefore x^2 > 0$$

$$e \approx 2.718$$

$$x \preceq y \text{ iff } f(x) \leq f(y)$$

2.2 Superscript Transformations

Three special superscript transformations are enabled for common mathematical notation.

2.2.1 Transpose (T)

```
1 $A^T = "transpose of" A$
2 $x^T y = \text{iprod}(x, y)$
3 $(A B)^T = B^T A^T$
```

$$A^T = \text{transpose of } A$$

$$x^T y = \langle x, y \rangle$$

$$(AB)^T = B^T A^T$$

Renders with proper transpose symbol (T) instead of superscript T.

2.2.2 Dagger ($^+$)

```
1 $A^+ = "Moore-Penrose
```

```
pseudoinverse"$
```

```
2 $H^+ = "Hermitian transpose"$
```

$A^\dagger$ = Moore-Penrose pseudoinverse

$H^\dagger$ = Hermitian transpose

Renders as dagger symbol ($\dagger$).

2.2.3 Star (^*)

```
1 $V^* = "optimal value function"$  
2 $pi^* = "optimal policy"$  
3 $x^* = arg min_x f(x)$
```

V^* = optimal value function

π^* = optimal policy

$x^* = \arg \min_x f(x)$

Renders with star symbol ($\star$) instead of superscript asterisk.

This distinguishes from the asterisk operator and provides cleaner mathematical notation.

2.2.4 Interaction with Shorthands

The superscript transformations work correctly even when $\star$ shorthand is enabled:

```
1 $A^T * B^*$ // Transpose A  
times optimal B
```

$A^T \cdot B^\star$


3 Utilities

The package provides extensive utilities for math, boxes, and display formatting.

3.1 Math Utilities

3.1.1 Statistics Functions

Colored, bracketed notation for statistical operators:

1	<code>\$Ex(X)\$</code>	// Expected value	
2	<code>\$Var(X)\$</code>	// Variance	
3	<code>\$Cov(X, Y)\$</code>	// Covariance	
4	<code>\$Corr(X, Y)\$</code>	// Correlation	
5	<code>\$Pr(X > 0)\$</code>	// Probability	


$\mathbb{E}[X]$ $\text{Var}[X]$ $\text{Cov}[X]$
 $\text{Corr}[X]$ $\text{Pr}[X > 0]$

These render with blue coloring and square brackets. Example:

$\mathbb{E}[X^2] \geq (\mathbb{E}[X])^2$ by Jensen's inequality.

$\text{Var}[X + Y] = \text{Var}[X] + \text{Var}[Y]$ when X and Y are independent.

3.1.2 Reasoning Operators


1	<code>\$x st x > 0\$</code>	// "such that"	
2	<code>\$If x > 0 Then y = 1 Else y = 0\$</code>		

$x \text{ s.t. } x > 0$

if $x > 0$ then $y = 1$ else $y = 0$

Example: $\max\{x \text{ s.t. } x \in \mathbb{R}\}$


3.1.3 Machine Learning / RL

1	<code>\$KL(p, q)\$</code>	// KL divergence	
2	<code>\$refPol\$</code>	// Reference policy	

$D_{\text{KL}}(p \parallel q)$ $\bar{\pi}$

Example: Minimize $D_{\text{KL}}(\pi \parallel \bar{\pi})$ to stay close to reference policy.


3.1.4 Miscellaneous

1	<code>\$SE\$</code>	// Standard error	
2	<code>\$ddot\$</code>	// Double dot	
3	<code>\$alias\$</code>	// Alias arrow	
4	<code>\$clamp(x)\$</code>	// Clamp function	
5	<code>\$solve(x)\$</code>	// Solve function	

SE $\overset{\text{alias}}{\leftarrow}$
 $\text{clamp}\{x\}$ $\text{solve}\{x\}$

3.1.5 Custom Math Function Factory

Create your own math functions with custom delimiters:

1	<code>#let myFunc = math-</code>	
	<code>func("myFunc", delim: "[")</code>	
2	<code>\$myFunc(x, y)\$</code>	
3		
4	<code>// Or with custom left/right delimiters</code>	

```
#let norm = math-func("norm", ldelim:  
5 math.bar.v.double, rdelim:  
  math.bar.v.double)  
6 $norm(x)$
```

`myFunc[x]`

`norm||x||`

3.2 Box Utilities

3.2.1 gatbox()

Customizable colored boxes with automatic color cycling.

3.2.1.1 Basic Usage

```
1 #gatbox[ t Typst
2   This is a basic box with default black
   color.
3 ]
4
5 #gatbox(color: blue)[
6   This is a blue box.
7 ]
```

This is a basic box with default black color.

This is a blue box.

3.2.1.2 Color Cycling

Automatically cycle through predefined colors:

```
1 #gatbox(color-cycle: true)[First t Typst
   box - blue]
2 #gatbox(color-cycle: true)[Second box -
   red]
3 #gatbox(color-cycle: true)[Third box -
   green]
4 #gatbox(color-cycle: true)[Fourth box -
   orange]
5 #gatbox(color-cycle: true)[Fifth box -
   purple]
```

First box - blue

Second box - red

Third box - green

Fourth box - orange

Fifth box - purple

3.2.1.3 Parameters

- `color` (color, default: black): Box color
- `color-cycle` (boolean, default: false): Auto-cycle through colors
- `title` (content): Optional title
- All `showybox` parameters supported

3.2.1.4 Examples

```
1 #gatbox(title: "Important", t Typst
   color: red)[
2   This is a critical point!
3 ]
4
5 #gatbox(color-cycle: true, title:
   "Theorem 1")
```

```
6   All horses are the same color.
7 ]
```

Important

This is a critical point!

Theorem 1

All horses are the same color.

3.2.2 showybox

The base box system (re-exported from the showybox package) with `breakable: true` by default.

```
1 #showybox(t Typst  
2   title: "Note",  
3   frame: (  
4     border-color: blue,  
5     title-color: blue.lighten(80%),  
6   ),  
7 ) [  
8   Content here can break across pages.  
9 ]
```

Note

Content here can break across pages.

3.3 Display Utilities

3.3.1 Show Rules

The package includes custom show rules that can be used independently:

```
1 #show: super-ast-as-start Typst  
2  
3 $V^* = V(x^*)$ // Asterisk renders as  
   star symbol
```

$$V^* = V(x^*)$$

4 Style Function

The `style` function provides enhanced styling for code, tables, and math notation. This is **opt-in** and must be explicitly enabled with `#show: style.with()`.

4.1 Code Styling

When using `style`, all code blocks are automatically styled:

4.1.1 Automatic Changes

1. **Font size:** Reduced to 8pt for compactness
2. **Zebra striping:** Alternating row backgrounds (`gray.lighten(80%)`)
3. **Border:** 1pt black stroke around code blocks
4. **Syntax highlighting:** Language-specific coloring

4.1.2 Example

```
1 def quicksort(arr):
2     if len(arr) ≤ 1:
3         return arr
4     pivot = arr[len(arr) // 2]
5     left = [x for x in arr if x < pivot]
6     middle = [x for x in arr if x == pivot]
7     right = [x for x in arr if x > pivot]
8     return quicksort(left) + middle + quicksort(right)
```

 Python

No manual configuration needed - just use standard Typst raw blocks with language tags.

4.2 Table Styling

When using `style`, the `booktabs` package is automatically applied, giving all tables professional styling with:

- Proper spacing between rows
- Professional horizontal rules (top, mid, bottom)
- No vertical lines (following `booktabs` philosophy)
- Better visual hierarchy

```
1 #table(
2     columns: 3,
3     [*Algorithm*], [*Time*], [*Space*],
4     [Quicksort], [$O(n \log n)$], [$O(\log n)$],
5     [Mergesort], [$O(n \log n)$], [$O(n)$],
6     [Heapsort], [$O(n \log n)$], [$O(1)$],
7 )
```

 Typst

No special syntax required - standard `#table()` gets enhanced styling.

5 Templates

The package provides two main templates: `homework` and `cheatsheet`. Both templates can be enhanced with the optional `style` function for additional styling features.

5.1 Style Function

The `style` function provides enhanced styling for code, tables, equations, and math notation. It is **optional** and must be explicitly enabled.

5.1.1 Usage

```
1 #show: style.with()
```

 Typst

5.1.2 Parameters

- `enable-shorthands` (boolean, default: `true`): Enable math operator shorthands

5.1.3 Features Provided

The `style` function automatically configures:

1. **FontAwesome Icons:** Access to icon library via `fa-icon()` function
2. **Code Styling:** Syntax highlighting with Codly, 8pt font size, zebra striping
3. **Table Styling:** Professional booktabs-style tables by default
4. **Math Configuration:**
 - Equation numbering with `equate` package
 - Breakable equations
 - Sub-numbering disabled
5. **Show Rules:**
 - T renders as transpose
 - $^+$ renders as dagger ($\dagger$)
 - * renders as star ($\star$) instead of asterisk

5.1.4 Example

```
1 #import "@local/gat-typst:0.1.0": *
2
3 #show: style.with()
4
5 // Use FontAwesome icons
6 #fa-icon("heart") Math is beautiful
7
8 // Code with automatic styling
```

 Typst

```
python def hello(): print("Hello, world!")
```

```
1
2 // Professional tables
3 #table(
4   columns: 3,
5   [*Name*], [*Age*], [*City*],
6   [Alice], [25], [Boston],
```

```
7     [Bob], [30], [Seattle],  
8 )  
9  
10 // Math with special superscripts  
11 $ A^T dot B^+ = C^* $
```

5.2 Homework Template

The homework template creates professional homework assignments with custom components for questions, solutions, and more.

5.2.1 Usage

```
1  #show: homework.with(t Typst
2    title: "Homework 1",
3    course: "Course Name",
4    university: "University Name",
5    author: "Your Name",
6    email: "your@email.com",
7    collaborators: [List of collaborators],
8    resources: [Resources used],
9    date: datetime.today(),
10   cols: 1, // or 2 for two-column layout
11   show-header: true,
12   paper-size: "us-letter",
13 )
```

5.2.2 Parameters

- title (string): Homework title (e.g., “HW01”, “Problem Set 3”)
- course (content): Course name or code
- university (content): University name
- author (content): Your name
- email (content): Your email address
- collaborators (content, default: []): List of collaborators
- resources (content, default: []): Resources used
- date (datetime, default: datetime.today()): Assignment date
- cols (integer, default: 1): Number of columns (1 or 2)
- show-header (boolean, default: true): Show header with metadata
- paper-size (string, default: "us-letter"): Paper size

5.2.3 Components

5.2.3.1 question()

Creates a colored box for problem statements with optional status tracking.

```
1  #question(status: "done")[t Typst
2    What is the derivative of  $x^2$ ?
3  ]
4
5  #question(status: "partial")[
6    This is partially complete.
7  ]
8
9  #question(status: "todo")[
10   Not started yet.
```

```

11 ]
12
13 #question()[
14   No status indicator.
15 ]

```

Status colors:

- "done": Green
- "partial": Yellow
- "todo": Red
- "none" or omitted: Black

5.2.3.2 solution()

Wrapper for solution content with optional column layout.

```

1 #solution[
2   The derivative is  $2x$ .
3 ]
4
5 #solution(cols: 2)[
6   This solution spans two columns.
7 ]

```

 Typst

5.2.3.3 boxed-solution

Inline box for short solutions.

```

1 The answer is #boxed-solution[ $x = 5$ ].

```

 Typst

5.2.3.4 sub-solution

Nested solution box for multi-part problems.

```

1 #sub-solution[
2   For part (a), we first note that ...
3 ]

```

 Typst

5.2.3.5 notes

Purple box for additional notes or remarks.

```

1 #notes[
2   Remember to check edge cases!
3 ]

```

 Typst

5.2.4 Complete Example

```

1 #import "@local/gat-typst:0.1.0": *
2
3 #show: homework.with(
4   title: "HW02",
5   course: "Linear Algebra",

```

 Typst


```

6   university: "MIT",
7   author: "Student Name",
8   email: "student@mit.edu",
9   collaborators: [Alice, Bob],
10  resources: [Textbook Chapter 3],
11  date: datetime(year: 2025, month: 1, day: 15),
12  cols: 1,
13 )
14
15 = Matrix Operations
16
17 #question(status: "done")[
18   Let  $A = \text{mat}(1, 2; 3, 4)$ . Compute  $A^T A$ .
19 ]
20
21 #solution[
22   We compute:
23   $
24    $A^T A = \text{mat}(1, 3; 2, 4) \text{mat}(1, 2; 3, 4)$ 
25    $= \text{mat}(10, 14; 14, 20)$ 
26   $
27
28   #sub-solution[
29     Note that  $A^T A$  is always symmetric.
30   ]
31 ]

```

5.3 Cheatsheet Template

The cheatsheet template creates compact, three-column cheatsheets perfect for exams.

5.3.1 Usage

```
1 #show: cheatsheet.with(t Typst
2   title: "Midterm",
3   course: "Course Name",
4   university: "University Name",
5   author: "Your Name",
6   email: "your@email.com",
7   date: datetime.today(),
8 )
```

5.3.2 Parameters

Similar to homework but without cols, show-header, and paper-size (fixed to 3-column layout on US Letter with 0.5cm margins).

5.3.3 Features

- **3-column layout** with 0.3cm gutter
- **Compact spacing**: 6pt base font, 7pt level-1 headings, 6pt level-2/3
- **No page numbers**: Maximizes space
- **Centered headings**: Better visual organization

5.3.4 Example

```
1 #import "@local/gat-typst:0.1.0": *t Typst
2
3 #show: cheatsheet.with(
4   title: "Final Exam Cheatsheet",
5   course: "Calculus I",
6   author: "Your Name",
7   date: datetime(year: 2025, month: 5, day: 10),
8 )
9
10 = Derivatives
11
12 == Power Rule
13 $ dv(, x) x^n = n x^(n-1) $
14
15 == Product Rule
16 $ dv(, x) (f g) = f' g + f g' $
17
18 == Chain Rule
19 $ dv(, x) f(g(x)) = f'(g(x)) g'(x) $
20
21 = Integrals
22
23 == Power Rule
```

$$24 \quad \int x^n dx = \frac{x^{n+1}}{n+1} + C$$

6 Dependencies & Imports

The package integrates carefully selected external packages. The `style` function automatically imports core packages for math, code, and formatting.

6.1 Overview

Active imports from `src/style/style.typ` (when using `#show: style.with()`):

```
1 // == Math ==
2 #import "@preview/equate:0.3.2": equate
3 #import "@preview/physica:0.9.6": *
4 #import "@preview/quick-maths:0.2.1": shorthands
5
6 // == Code ==
7 #import "@preview/codly:1.3.0": *
8 #import "@preview/codly-languages:0.1.1": codly-languages
9
10 // == Display & Formatting ==
11 #import "@preview/fontawesome:0.6.0": *
12 #import "@preview/booktabs:0.0.4": *
13
14 // == Utilities ==
15 // Available through gat-typst but not auto-imported by style:
16 // #import "@preview/showybox:2.0.4": showybox
17 // #import "@preview/hydra:0.6.2": hydra
18
19 // == Diagramming == (not included in style, must import separately)
20 // #import "@preview/cetz:0.4.2": canvas, draw
21 // #import "@preview/cetz-plot:0.1.2": plot
22 // #import "@preview/fletcher:0.5.8" as fletcher: diagram, edge, node
23 // #import "@preview/lilaq:0.5.0" as lq
24
25 // == Additional Math == (not included in style)
26 // #import "@preview/matset:0.1.0"
27 // #import "@preview/mannot:0.3.0": *
28
29 // == Additional Code == (not included in style)
30 // #import "@preview/callisto:0.2.4"
31 // #import "@preview/lovelace:0.3.0": pseudocode-list
32 // #import "@preview/cmarker:0.1.6"
33
34 // == Additional Display == (not included in style)
35 // #import "@preview/frame-it:1.2.0": *
36
37 // == Compatibility == (not included in style)
38 // #import "@preview/mitex:0.2.5": mitex, mitex-convert, mitext
39
40 // == Color == (not included in style)
41 // #import "@preview/splash:0.5.0": xcolor
```

```
42 // #import "@preview/typpuccino:0.1.0": frappe, latte, macchiato, mocha
```

6.2 Diagramming

Note: Diagramming packages are not included in **style**. Import them explicitly if needed.

6.2.1 CeTZ (v0.4.2)

Comprehensive drawing library for creating custom diagrams.

```
1 #import "@preview/cetz:0.4.2": canvas, draw
2
3 #canvas({
4   import draw: *
5   circle((0, 0), radius: 1)
6   line((0, 0), (1, 1))
7   content((0, 0), $x$)
8 })
```

Use for: Custom diagrams, network architectures, geometric figures.

6.2.2 CeTZ Plot (v0.1.2)

Plotting extension for CeTZ.

```
1 #import "@preview/cetz-plot:0.1.2": plot
2
3 #canvas({
4   plot.plot(
5     size: (8, 6),
6     x-tick-step: 1,
7     y-tick-step: 1,
8     {
9       plot.add(x => x * x, domain: (-2, 2))
10    }
11  )
12 })
```

Use for: Function plots, data visualization.

6.2.3 Fletcher (v0.5.8)

Arrow diagrams and state machines.

```
1 #diagram(
2   node((0, 0), $A$, radius: 2em),
3   node((1, 0), $B$, radius: 2em),
4   edge((0, 0), (1, 0), "→", $f$),
5 )
```

Use for: State machines, flowcharts, commutative diagrams.

6.2.4 Lilaq (v0.5.0)

Modern data visualization library.

```
1 #lq.diagram(t Typst  
2   title: [Data Plot],  
3   xlabel: $x$,  
4   ylabel: $y$,  
5   lq.plot((0, 1, 2, 3), (1, 4, 2, 3), mark: "o"),  
6 )
```

Use for: Scientific plots, cleaner syntax than CeTZ Plot.

6.3 Math

Note: **Equate**, **Physica**, and **Quick-maths** are automatically imported by **style**. Other math packages must be imported explicitly.

6.3.1 Matset (v0.1.0)

Not included in **style** - import explicitly if needed.

Set notation support.

Use for: Mathematical set operations and notation.

6.3.2 Equate (v0.3.2)

Included in **style** - automatically available.

Advanced equation numbering with breakable equations.

```
1 $t Typst  
2   f(x) = x^2  
3 $ <eq:quadratic>  
4  
5 Reference: @eq:quadratic
```

$$f(x) = x^2$$

Use for: Equation numbering and cross-referencing.

6.3.3 Physica (v0.9.6)

Included in **style** - automatically available.

Comprehensive physics notation package.

Key functions:

```
1 $vb(x)$           // Vectort Typst  
   bold  
2 $vu(u)$           // Unit vector  
3 $dd(x)$           // Differential  
4 $dv(f, x)$        // Derivative  
5 $pdv(f, x, y)$     // Partial  
6 $grad f$, $div vb(F)$, $curl vb(F)$  
7 $iprod(u, v)$      // Inner product  
8 $norm(x)$          // Norm
```

```
9 $abs(x)$           // Absolute value  
10 $Set(x, x > 0)$   // Set builder  
11 $dmat(1, 2, 3)$    // Diagonal matrix  
12 $evaluated(f)_a^b$ // Evaluation bar
```

$$x \quad \hat{u} \quad dx$$

$$\frac{df}{dx} \quad \frac{\partial^2 f}{\partial x \partial y}$$

$$\nabla f \quad \nabla \cdot \boldsymbol{F} \quad \nabla \times \boldsymbol{F}$$

$$\langle u, v \rangle \quad \|x\| \quad |x|$$

$$\{x \mid x > 0\}$$

$$\begin{pmatrix} 1 \\ 2 \\ 3 \end{pmatrix}$$

$$f|_a^b$$

Example:

```

1 $ t Typst
2   dv(vb(x), t) = vb(v), quad
3   pdv(f, x, y, [2, 1]) = 0, quad
4   iprod(vb(u), vb(v)) = norm(vb(u))
   norm(vb(v)) cos theta
5 $

```

$$\frac{dx}{dt} = v, \quad \frac{\partial^3 f}{\partial x^2 \partial y} = 0, \quad \langle u, v \rangle = \|u\| \|v\| \cos \theta$$

Use for: Almost all physics and advanced math notation.

6.3.4 Quick-maths (v0.2.1)

Included in **style** - automatically available.

Math shorthand system (powers the operator replacements).

See “Important Behavior Changes” section for details.

6.3.5 Mannot (v0.3.0)

Not included in **style** - import explicitly if needed.

Math annotations and labels.

TODO: FIX

```

1 $ t Typst
2   p_i = exp(-beta E_i) / sum_j exp(-beta
   E_j)
3   #annot(<beta>, pos: top)[Inverse
   temperature]
4 $

```

Use for: Annotating complex equations, teaching materials.

6.4 Code

Note: Codly and Codly Languages are automatically imported by **style**. Other code packages must be imported explicitly.

6.4.1 Callisto (v0.2.4)

Not included in **style** - import explicitly if needed.

Jupyter notebook rendering.

```
1 #let (render, Cell, In, Out) = callisto.config(Typst
2   nb: json("notebook.ipynb"),
3 )
4
5 #In("cell-tag") // Show input cell
6 #Out("cell-tag") // Show output cell
7 #Cell("cell-tag") // Show both
```

Use for: Including Jupyter notebook code/output in documents.

6.4.2 Lovelace (v0.3.0)

Not included in **style** - import explicitly if needed.

Pseudocode formatting.

```
1 #pseudocode-list[Typst
2   + *Input:* Array  $A$  of length  $n$ 
3   + *Output:* Sorted array
4   + *for*  $i = 1$  *to*  $n$  *do*
5     + Process element  $A[i]$ 
6 ]
```

Use for: Algorithm descriptions.

6.4.3 Codly (v1.3.0) + Codly Languages (v0.1.1)

Included in **style** - automatically available.

Modern syntax highlighting for code blocks.

When using style, automatically configured with:

- 8pt font size
- 1pt black stroke
- Zebra striping (gray.lighten(80%))

```
1 def fibonacci(n):Python
2   if n ≤ 1:
3     return n
4   return fibonacci(n-1) + fibonacci(n-2)
```

Supports: Python, Rust, JavaScript, TypeScript, Java, C++, and 50+ more languages.

Use for: All code snippets. Automatically applied to raw blocks.

6.4.4 Cmarker (v0.1.6)

Not included in **style** - import explicitly if needed.

CommonMark (Markdown) support.

Use for: Converting Markdown to Typst.

6.5 Display & Formatting

Note: Font Awesome and Booktabs are automatically imported by **style**. Other display packages must be imported explicitly.

6.5.1 Frame-it (v1.2.0)

Not included in **style** - import explicitly if needed.

Custom frame styles for content boxes.

```
1 #let (example, definition) = frames(  
2   example: ("Example", blue),  
3   definition: ("Definition", green),  
4 )  
5  
6 #example[Title][Tag][  
7   Body content here.  
8 ]
```

 Typst

Use for: Theorem environments, examples, definitions.

6.5.2 Font Awesome (v0.6.0)

Included in **style** - automatically available.

Font Awesome icon support (version 6).

```
1 #fa-icon("heart")  
2 #fa-icon("calculator")  
3 #fa-icon("robot")
```

 Typst

Use for: Visual indicators, status icons. Note: Requires Font Awesome fonts installed.

6.5.3 Showybox (v2.0.4)

Available through gat-typst utilities (base for **gatbox**).

Styled, breakable boxes.

```
1 #showybox(  
2   title: "Title",  
3   frame: (border-color: blue),  
4   breakable: true,  
5 )[  
6   Content  
7 ]
```

 Typst

Use for: Custom boxes, callouts, highlighted content.

6.5.4 Hydra (v0.6.2)

Available through gat-typst but not included in **style**.

Context-aware page headers showing current section.

```
1 #import "@preview/hydra:0.6.2": hydra
```

 Typst

```

2
3 #set page(header: context [
4   #text(fill: gray)[**hydra(2)**]
5 ])

```

Use for: Displaying current section in headers. Used by the homework template.

6.5.5 Booktabs (v0.0.4)

Included in **style** - automatically available.

Publication-quality table styling.

When using **style**, automatically applied to all tables. Creates professional spacing and rules.

Use for: All tables. No manual configuration needed when using **style**.

6.6 Compatibility

Note: Compatibility packages are not included in **style. Import them explicitly if needed.**

6.6.1 MiTeX (v0.2.5)

Not included in **style** - import explicitly if needed.

LaTeX compatibility layer for including LaTeX code.

```

1 #mitex(`
2   \begin{bmatrix}
3     1 & 2 \\
4     3 & 4
5   \end{bmatrix}
6 `)

```

 Typst

Use for: Converting existing LaTeX, complex LaTeX-only constructs.

6.7 Color

Note: Color packages are not included in **style. Import them explicitly if needed.**

6.7.1 Splash (v0.5.0)

Not included in **style** - import explicitly if needed.

Extended color support including xcolor names.

```

1 #text(fill: xcolor("red!50!blue"))[Mixed color]

```

 Typst

Use for: Advanced color specifications.

6.7.2 Typpuccino (v0.1.0)

Not included in **style** - import explicitly if needed.

Catppuccin color schemes (frappe, latte, macchiato, mocha).

```

1 #import "@preview/typpuccino:0.1.0": mocha

```

 Typst

```
2  
3 #text(fill: mocha.red)[Catpuccin red]
```

Use for: Consistent color theming.

7 Complete Examples

7.1 Simple Homework Document

```
1  #import "@local/gat-typst:0.1.0": *
2
3  #show: homework.with(
4    title: "Problem Set 1",
5    course: "Calculus II",
6    university: "Your University",
7    author: "Your Name",
8    email: "you@example.com",
9    date: datetime(year: 2025, month: 2, day: 1),
10 )
11
12 #show: style.with()
13
14 = Integration by Parts
15
16 #question(status: "done")[
17   Evaluate  $\int x e^x dx$ .
18 ]
19
20 #solution[
21   Using integration by parts with  $u = x$  and  $dv(x) = e^x dx$ :
22
23   
$$\int x e^x dx = x e^x - \int e^x dx = x e^x - e^x + C = e^x (x - 1) + C$$

24
25   
$$\int x e^x dx = x e^x - e^x + C$$

26
27   
$$\int x e^x dx = e^x (x - 1) + C$$

28
29 ]
```

7.2 Math-Heavy Solution with Custom Functions

```
1  #import "@local/gat-typst:0.1.0": *
2
3  #show: homework.with(
4    title: "Statistics Assignment",
5    course: "Probability Theory",
6    author: "Student",
7    email: "student@school.edu",
8  )
9
10 #show: style.with()
11
12 = Random Variables
13
```

```

14 #question(status: "done")[
15   Let  $X$  and  $Y$  be independent random variables.
16   Show that  $\text{Var}(X + Y) = \text{Var}(X) + \text{Var}(Y)$ .
17 ]
18
19 #solution[
20   By definition:
21   
$$\begin{aligned} \text{Var}(X + Y) &= \text{Ex}((X + Y)^2) - (\text{Ex}(X + Y))^2 \\ &= \text{Ex}(X^2 + 2XY + Y^2) - (\text{Ex}(X) + \text{Ex}(Y))^2 \\ &= \text{Ex}(X^2) + 2\text{Ex}(XY) + \text{Ex}(Y^2) - (\text{Ex}(X))^2 - 2\text{Ex}(X)\text{Ex}(Y) - (\text{Ex}(Y))^2 \end{aligned}$$

22
23   Since  $X$  and  $Y$  are independent,  $\text{Ex}(XY) = \text{Ex}(X) * \text{Ex}(Y)$ :
24   
$$\begin{aligned} \text{Var}(X + Y) &= \text{Ex}(X^2) - (\text{Ex}(X))^2 + \text{Ex}(Y^2) - (\text{Ex}(Y))^2 \\ &= \text{Var}(X) + \text{Var}(Y) \end{aligned}$$

25
26   #sub-solution[
27     *Note:* This result generalizes: for independent  $X_1, \dots, X_n$ ,
28     
$$\text{Var}(\sum_{i=1}^n X_i) = \sum_{i=1}^n \text{Var}(X_i)$$

29   ]
30 ]

```

7.3 Compact Cheatsheet

```

1  #import "@local/gat-typst:0.1.0": *
2
3  #show: cheatsheet.with(
4    title: "Midterm Cheatsheet",
5    course: "Linear Algebra",
6    author: "Your Name",
7    date: datetime(year: 2025, month: 3, day: 15),
8  )
9
10 #show: style.with()
11
12 #let gatbox = gatbox.with(color-cycle: true)
13
14 = Matrix Operations
15
16 #gatbox(title: [Transpose])[
17    $(A^T)_i = A_{(j \ i)}$ 
18
19    $(A \ B)^T = B^T \ A^T$ 
20 ]

```

```

21
22 #gatbox(title: [Determinant])[
23   $det(A B) = det(A) * det(B)$
24
25   $det(A^T) = det(A)$
26
27   $det(A^{(-1)}) = 1/det(A)$
28 ]
29
30 = Eigenvalues
31
32 #gatbox(title: [Definition])[
33   $A \, vb(v) = \lambda \, vb(v)$
34
35   $det(A - \lambda I) = 0$
36 ]
37
38 #gatbox(title: [Properties])[
39   $product_{i=1}^n \lambda_i = det(A)$
40
41   $sum_{i=1}^n \lambda_i = "tr"(A)$
42 ]
43
44 = Vector Spaces
45
46 #gatbox(title: [Subspaces])[
47   *Null space:* $cal(N)(A) = Set(vb(x), A \, vb(x) = vb(0))$
48
49   *Column space:* $cal(C)(A) = Set(A \, vb(x), vb(x) \text{ in } \mathbb{R}^n)$
50
51   *Row space:* $cal(C)(A^T)$
52 ]
53
54 #gatbox(title: [Fundamental Theorem])[
55   $dim \, cal(C)(A) + dim \, cal(N)(A) = n$
56
57   $cal(C)(A)^{perp} = cal(N)(A^T)$
58 ]

```

8 Tips & Best Practices

Based on conventions and optimal usage of this package:

8.1 Math Notation

1. Use **semantic symbols** instead of generic ones:

```
1 // Good
2  $\textcolor{violet}{\$grad}$  f$ // Gradient
3  $\textcolor{violet}{\$product}_\textcolor{teal}{(i=1)^n x_i}$  // Product
4
5 // Avoid
6  $\textcolor{violet}{\$nabla}$  f$
7  $\textcolor{violet}{\$Pi}_\textcolor{teal}{(i=1)^n x_i}$ 
```

2. Space before subscripts with functions:

```
1 // Good
2  $\textcolor{violet}{\$V\_pi}$  (s)$ // Value function of policy  $\pi$  at state s
3  $\textcolor{violet}{\$Q\_theta}$  (s, a)$
4
5 // Bad (no space before parenthesis)
6  $\textcolor{violet}{\$V\_pi}$ (s)$
7  $\textcolor{violet}{\$Q\_theta}$ (s, a)$
```

3. Use **physica utilities** for common notation:

```
1  $\textcolor{teal}{\$vb}$ (x)$ // Vector bold
2  $\textcolor{teal}{\$vu}$ (n)$ // Unit vector
3  $\textcolor{teal}{\$cal}$ (A)$ // Mathcal letters (script)
4  $\textcolor{teal}{\$dd}$ (x)$ // Differential
5  $\textcolor{teal}{\$dv}$ (f, x)$ // Derivative
6  $\textcolor{teal}{\$pdv}$ (f, x, y)$ // Partial derivative
7  $\textcolor{teal}{\$iprod}$ (u, v)$ // Inner product (not angle brackets)
8  $\textcolor{teal}{\$norm}$ (x)$ // Norm (not ||x||)
9  $\textcolor{teal}{\$abs}$ (x)$ // Absolute value
10  $\textcolor{teal}{\$eval}$ (f)_a^b$ // Evaluation bar
```

4. Leverage custom statistics functions:

```
1 // These are colored and use square brackets
2  $\textcolor{teal}{\$Ex}$ (X)$ // Expectation
3  $\textcolor{teal}{\$Var}$ (X)$ // Variance
4  $\textcolor{teal}{\$Pr}$ (A)$ // Probability
```

8.2 Layout

1. **Two-column homework** for dense problems:

```
1  $\textcolor{red}{\#show}$ : homework. $\textcolor{teal}{with}$ (
2   cols:  $\textcolor{teal}{2}$ ,
```

```

3 // ... other params
4 )
5
6 // Override for specific solutions
7 #solution(cols: 1)[
8   This needs full width.
9 ]

```

2. **Color-cycle boxes** for organizing content:

```

1 #gatbox(color-cycle: true, title: "Theorem 1")[ ... ]
2 #gatbox(color-cycle: true, title: "Theorem 2")[ ... ]
3 #gatbox(color-cycle: true, title: "Theorem 3")[ ... ]
4 // Automatically cycles: blue → red → green → orange → purple

```

3. **Status tracking** for homework progress:

```

1 #question(status: "done")[Completed problem]
2 #question(status: "partial")[Work in progress]
3 #question(status: "todo")[Not started]

```

8.3 Organization

1. Use **sub-solutions** for complex multi-part problems:

```

1 #solution[
2   Main solution approach ...
3
4   #sub-solution[
5     For part (a), we have ...
6   ]
7
8   #sub-solution[
9     For part (b), note that ...
10  ]
11 ]

```

2. **Add notes** for clarifications or caveats:

```

1 #notes[
2   This assumes the matrix is invertible.
3   For singular matrices, use pseudoinverse.
4 ]

```

3. **Label equations** for cross-referencing:

```


1 $
2   f(x) = x^2 + 2x + 1
3 $ <eq:quadratic>
4
5 From @eq:quadratic, we see that ...

```


8.4 Code

1. **Always specify language** for proper highlighting:

```
1 def example():
2     pass
```




Not just:

```
1 def example():
2     pass
```

2. **Use Callisto for notebook integration:**


```
1 #let (render, Cell, In, Out) = callisto.config(
2     nb: json("notebook.ipynb"),
3 )
4
5 // Tag cells in notebook, then reference them
6 #In("data-loading")
7 #Out("plot-results")
```



8.5 Performance

1. **Compile time:** Heavy imports may slow compilation. Consider splitting large documents.
2. **Font Awesome:** Requires fonts installed system-wide. If icons don't render, install Font Awesome fonts.
3. **Cheatsheet margins:** 0.5cm is very tight. Adjust if printing issues occur:


```
1 #set page(margin: 0.7cm) // Before cheatsheet.with()
```



8.6 Common Pitfalls


1. **Shorthand conflicts:** If you need literal `*` for multiplication:

```
1 $a ast b$ // Use 'ast' explicitly
```




2. **Superscript confusion:** Remember `^*` becomes star:

```
1 $x*$ // Renders as x* (star)
2 $xast$ // Renders as x* (asterisk if needed)
```



3. **Column overrides:** Don't forget to override `solution` for full-width content in 2-column layouts:

```
1 #let solution = solution.with(cols: 1)
```



9 Reference

9.1 Quick Import Guide

```
1 // Full import
2 #import "@local/gat-typst:0.1.0": *
3
4 // Selective import
5 #import "@local/gat-typst:0.1.0": homework, question, solution, gatbox
6
7 // Import specific utilities
8 #import "@local/gat-typst:0.1.0": Ex, Var, KL, vb, cal
```

9.2 Template Comparison

Feature	style	homework	cheatsheet
Columns	N/A	1 or 2	3 (fixed)
Font size	N/A	13pt (1-col) / 10pt (2-col)	6pt
Headers	None	Optional	None
Margins	N/A	1 inch	0.5cm
Question boxes	No	Yes	No (manual)
Equation numbers	Yes (when used)	Yes	Yes

9.3 Function Reference

9.3.1 Styling

- `style(enable-shorthands: true, body)`

9.3.2 Templates

- `homework(title, course, university, author, email, ...)`
- `cheatsheet(title, course, university, author, email, ...)`

9.3.3 Components

- `question(status: "none", ...)`
- `solution(cols: 1, body)`
- `boxed-solution`
- `sub-solution(...)`
- `notes(...)`

9.3.4 Boxes

- `gatbox(color: black, color-cycle: false, ...)`
- `showybox(...)`

9.3.5 Math (Statistics)

- `Ex()` - Expectation
- `Var()` - Variance
- `Cov()` - Covariance

- `Corr()` - Correlation
- `Pr()` - Probability

9.3.6 Math (Other)

- `KL(p, q)` - KL divergence
- `refPol` - Reference policy
- `st, If, Else, Then` - Logic
- `clamp(x)`, `solve(x)` - Functions

9.3.7 Utilities

- `date-format(date)` - Format datetime
- `math-func(name, ...)` - Create custom math function
- `super-ast-as-star` - Show rule for *

9.4 Further Reading

For detailed package documentation:

- **Physica**: <https://github.com/Leedehai/typst-physics>
- **CeTZ**: <https://cetz-package.github.io/docs/>
- **Fletcher**: <https://github.com/typst/packages/blob/main/packages/preview/fletcher/>
- **Codly**: <https://typst.app/universe/package/codly>
- **Typst Documentation**: <https://typst.app/docs/>

9.5 Version History

v0.1.0 (Current)

- Initial release
- Templates: homework, cheatsheet
- Optional styling function with math shorthands, code highlighting, and table formatting
- Math utilities and custom box system
- Core package integrations (equate, physica, codly, booktabs, fontawesome)

For issues, suggestions, or contributions, see the project repository.