

# **Smt. Chandibai Himathmal Mansukhani College**

## **USCS3P01:USCS303-Operating System (OS) Practical-04**

### **Process Communication**

#### **Contents**

USCS3P01:USCS303-Operating System (OS) Practical-04 .....	1
Process Communication.....	1
<b>Practical Date</b> : 6 th August,2021 (Friday) .....	2
<b>Practical Aim</b> : (Producer – Consumer Problem ,RMI) .....	2
<b>Process Communication</b> .....	2
Producer – Consumer Problem .....	2
Using Shared Memory.....	3
1. Producer – Consumer Solution Using Shared Memory .....	5
Question – 1 .....	5
Write a java program for producer – consumer using shared memory .....	5
Implement Producer – Consumer solution using shared memory .....	5
Source Codes .....	5
Output: .....	8
Using Message Passing.....	9
2. Producer – Consumer Solution Using Message Passing .....	9
Question – 2 .....	9
Write a java program for producer – consumer using message passing.....	9
Implement Producer – Consumer solution using Message Passing .....	10
Source Code : .....	10
Output: .....	12
Remote Method Invocation .....	12
3. Implement Remote Method Invocation (RMI)Calculator .....	14
Question – 3 .....	14
Write a java program for adding , subtracting , multiplying and dividing two numbers.....	14
Source codes .....	14
Output: .....	20

# **Smt. Chandibai Himathmal Mansukhani College**

**Practical Date :** 6 th August,2021 (Friday)

**Practical Aim :** (Producer – Consumer Problem ,RMI)

**Producer – Consumer Problem**

## **Process Communication**

### **Content:**

- ❖ Solution for Producer – Consumer Problem using shared memory and message passing
- ❖ Communication in Client Server environment using Remote Method Invocation (RMI).

### **Process:**

- ❖ Producer – Consumer problem without threads and without synchronization.
- ❖ Implement remote method Invocation (RMI)

### **Prior Knowledge:**


- ❖ Concept of shared memory , message passing , interfaces and remote method Invoaction.
- ❖ Message passing and Remote proceduring cells are the most common methods of interprocess communication in distributed systems.
- ❖ A less frequently used but no less valuable method is distributed shared memory

## **Producer – Consumer Problem**

- In a producer/consumer relationship , the producer portion of an application generates data and stores it in a shared object ,and the consumer portion of an application reads data from the shared object.
- One example of a common producer/consumer relationship is print spooling. A word processor spools data to a buffer ( typically a file )and that data is subsequently consumed by the printer as it prints the document. Similarly, an application that copies data onto compact discs places data in a fixed size buffer that is emptied as the CD-RW drive burns the data onto the compact disc.

## **Using Shared Memory**

- Shared memory is memory that may be simultaneously accessed by multiple processes with an intent to provide communication among them or avoid redundant copies.
- Shared memory is an efficient means of passing data between processes.



# **Smt. Chandibai Himathmal Mansukhani College**

## **1. Producer – Consumer Solution Using Shared Memory**

### **Question – 1**

**Write a java program for producer – consumer using shared memory**

**Implement Producer – Consumer solution using shared memory**

### **Source Codes**

#### **Code 1:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN:2020016400785461**

**//Date:06-08-2021**

```
public interface P4_PC_SM_Buffer_GS  
{  
  
    //Procedures call this method  
    public void insert(String item);  
  
    //Consumers call this method  
    public String remove();  
  
}//interface ends
```

# **Smt. Chandibai Himathmal Mansukhani College**

**Code 2:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

```
public class P4_PC_SM_BufferImpl_GS implements P4_PC_SM_Buffer_GS
{
    private static final int BUFFER_SIZE = 5;
    private String[] elements;
    private int in,out,count;

    public P4_PC_SM_BufferImpl_GS()
    {
        count = 0;
        in = 0;
        out = 0;
        elements = new String[BUFFER_SIZE];
    }

    public void insert(String item)
    {
        while(count==BUFFER_SIZE);

        elements[in] = item;
        in = (in + 1)%BUFFER_SIZE;
        ++count;
        System.out.println("Item Produced " + item + " at position " + in + " having
total items " + count);
    }
    public String remove()
    {
        String item;
        while(count==0);

        item = elements[out];
        out = (out + 1)%BUFFER_SIZE;
        --count;
        System.out.println("Item Consumed " + item + " from position " + out + "
remaining total items " + count);
    }
}
```

# Smt. Chandibai Himathmal Mansukhani College

```
        return item;
    }
}
```

## Code 3:

//Name: Gaurang Sanyasi

//Batch No:B2

//PRN: 2020016400785461

//Date:06-08-2021

```
public class P4_PC_SM_GS
{
```

```
    public static void main(String[] args){
        P4_PC_SM_BufferImpl_SJ bufobj = new P4_PC_SM_BufferImpl_SJ();

        System.out.println("\n=====PRODUCER producing the
ITEMS=====\\n");
        bufobj.insert("Name: Sahil Jadhav");
        bufobj.insert("CHMCS: Batch - B2");
        bufobj.insert("PRN: 2020016400783091");
        bufobj.insert("USCSP301 - USCS303:0S Practical - P4");

        System.out.println("\n=====CONSUMER consuming the
ITEMS=====\\n");

        System.out.println(bufobj.remove());
        System.out.println(bufobj.remove());
        System.out.println(bufobj.remove());
        System.out.println(bufobj.remove());
    }
}
```

# Smt. Chandibai Himathmal Mansukhani College

## Output:

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1110]
(c) Microsoft Corporation. All rights reserved.

C:\Users\admin>D:

D:\>cd D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q1_PC_SM_GS

D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q1_PC_SM_GS>javac P4_PC_SM_GS.java

D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q1_PC_SM_GS>java P4_PC_SM_GS.java

=====PRODUCER producing the ITEMS=====

Item Produced: Name: Gaurang Sanyasi at position 1 having total items 1
Item Produced: CHMCS: Batch - B2 at position 2 having total items 2
Item Produced: PRN:2020016400785461 at position 3 having total items 3
Item Produced: USCS3P01 - USCS303: OS Practical - P4 at position 4 having total items 4

=====CONSUMER consuming the ITEMS=====

Item Consumed: Name: Gaurang Sanyasi from position1 remaining total items 3
Name: Gaurang Sanyasi
Item Consumed: CHMCS: Batch - B2 from position2 remaining total items 2
CHMCS: Batch - B2
Item Consumed: PRN:2020016400785461 from position3 remaining total items 1
PRN:2020016400785461
Item Consumed: USCS3P01 - USCS303: OS Practical - P4 from position4 remaining total items 0
USCS3P01 - USCS303: OS Practical - P4

D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q1_PC_SM_GS>
```



## **Using Message Passing**

- Message passing is the basic of most inter- process communication in distributed systems.
- It is at the lowest level of abstraction and requires the application programmer to be able to identify the destination process , the message , the source process and the data types expected from these processes.
- Communication in the message passing paradigm , in its simplest form , is performed using the send() and received() primitives. The syntax is generally of the form.

send (receiver , message)

receive (sender , message)

- The send() primitive requires the name of the destination process and the message data as parameters. The addition of the name of the sender as a parameter for the send() primitive would enable the receiver to acknowledge the message. The receive() primitive requires the name of the anticipated sender and should provide a storage buffer for the message.

# **Smt. Chandibai Himathmal Mansukhani College**

## **2. Producer – Consumer Solution Using Message Passing**

### **Question – 2**

**Write a java program for producer – consumer using message passing**

**Implement Producer – Consumer solution using Message Passing**

**Source Code :**

**Code 1:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN:2020016400783091**

**//Date:06-08-2021**

```
public interface P4_PC_MP_Channel_GS<E>
{
    // Send a message to the channel
    public void send(E item);

    // Receive a message from the channel
    public E receive();
} // interface ends
```

**Code 2:**

**//Name: Sahil Jadhav**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

**import java.util.Vector;**

```
public class P4_PC_MP_MessageQueue_GS<E> implements
P4_PC_MP_Channel_GS<E>
```

```
{
```

```
    private Vector<E> queue;
```

```
    public P4_PC_MP_MessageQueue_GS(){
```

## **Smt. Chandibai Himathmal Mansukhani College**

```
        queue = new Vector<E>();
    }

    // This implements a nonblocking send
    public void send(E item){
        queue.addElement(item);
    } // send() ends

    // This implements a nonblocking receive
    public E receive(){
        if(queue.size()==0)
            return null;
        else
            return queue.remove(0);
    } // receive() ends
} // class ends
```

**Code 3:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

```
import java.util.Date;
public class P4_PC_MP_GS
{
    public static void main(String args[])
    {
        P4_PC_MP_Channel_GS<Date> mailBox = new
P4_PC_MP_MessageQueue_GS<Date>();

        int i = 0;

        do
        {
```

# Smt. Chandibai Himathmal Mansukhani College

```
Date message = new Date();

System.out.println("Producer produced- " + (i+1)+ " : " + message);

mailBox.send(message);

Date rightNow = mailBox.receive();

if(rightNow!= null)

{

    System.out.println("Consumer consumed -" + (i+1) + " : " +

rightNow);

}


i++;

}while(i<10);

}

}
```

## Output:



```
Command Prompt
C:\Users\admin>D:
D:\>cd D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q2_PC_MP_GS
D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q2_PC_MP_GS>javac P4_PC_MP_GS.java
D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q2_PC_MP_GS>java P4_PC_MP_GS
Producer produced - 1:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 1: Mon Aug 09 21:42:25 IST 2021
Producer produced - 2:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 2: Mon Aug 09 21:42:25 IST 2021
Producer produced - 3:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 3: Mon Aug 09 21:42:25 IST 2021
Producer produced - 4:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 4: Mon Aug 09 21:42:25 IST 2021
Producer produced - 5:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 5: Mon Aug 09 21:42:25 IST 2021
Producer produced - 6:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 6: Mon Aug 09 21:42:25 IST 2021
Producer produced - 7:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 7: Mon Aug 09 21:42:25 IST 2021
Producer produced - 8:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 8: Mon Aug 09 21:42:25 IST 2021
Producer produced - 9:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 9: Mon Aug 09 21:42:25 IST 2021
Producer produced - 10:Mon Aug 09 21:42:25 IST 2021
Consumer consumed 10: Mon Aug 09 21:42:25 IST 2021
D:\USCS3P01_USCS303_OS_B2\Prac_04_GS_06_08_2021\Q2_PC_MP_GS>
```

## **Remote Method Invocation**

### **Remote Procedure Calls**

- Message passing leaves the programming with the burden of the explicit control of the movement of data. Remote procedure calls (RPC) relieves this burden by increasing the level of abstraction and providing semantics similar to a local procedure call.
- Syntax:
- The syntax of a remote procedure call is generally of the form:  
Call procedure\_name (value\_arguments; result\_arguments)
- The client process blocks at the call() until the reply is received.
- The remote procedure is the server processes which has already begun executing on a remote machine. It blocks at the receive() until it receives a message and parameters from the sender.
- The server then sends a reply() when it has finished its task.
- The syntax is as follows:  
receive procedure\_name (in value\_parameters; out result\_parameters)  
reply (caller , result\_parameters)
- In the simplest case, the execution of the call() generates a client stub which marshals the arguments into a message and sends the message to the server machine. On receipt of the message the server stub is generated and extracts the parameters from the message and passes the parameters and control to the procedure. The results are returned to the client with the same procedure in reverse.

# **Smt. Chandibai Himathmal Mansukhani College**

## **Question – 3**

**Write a java program for adding , subtracting , multiplying and dividing two numbers.**

### **3. Implement Remote Method Invocation (RMI) Calculator**

#### **Step 1:**

#### **Creating the Remote Interface**

This file defines the remote interface that is provided by the server. It contains four methods that accepts two Integer arguments and returns their sum, difference, product and quotient. All remote interfaces must extend the Remote interface, which is part of java.rmi.Remote defines no members , its purpose is simply to indicate that and interface uses remote uses remote methods.

All remote methods can throw a RemoteException.

#### **Source Codes :**

##### **Code 1:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

**import java.rmi.\*;**

**public interface P4\_RMI\_CalcServerIntf\_GS extends Remote**

**{**

**int add(int a, int b)throws RemoteException;**

**int subtract(int a, int b)throws RemoteException;**

**int multiply(int a, int b)throws RemoteException;**

**int divide(int a, int b)throws RemoteException;**

**}//interface ends**

# **Smt. Chandibai Himathmal Mansukhani College**

## **Step 2:**

### **Implementing the Remote Interface**

This file implements the remote interface. The implementation of all the four methods is straight forward. All remote methods must extend UnicastRemoteObject , which provides functionality that is needed to make objects available from remote machines.

#### **Code 2:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

**import java.rmi.\*;**

**import java.rmi.server.\*;**

**public class P4\_RMI\_CalcServerImpl\_SJ extends UnicastRemoteObject implements  
P4\_RMI\_CalcServerIntf\_GS**

**{**

**public P4\_RMI\_CalcServerImpl\_GS()throws RemoteException{**

**}**

**public int add(int a,int b)throws RemoteException**

**{**

**return a + b;**

**}**

**public int subtract(int a,int b)throws RemoteException**

**{**

**return a - b;**

**}**

**public int multiply(int a,int b)throws RemoteException**

## Smt. Chandibai Himathmal Mansukhani College

```
{  
    return a * b;  
}  
  
public int divide(int a,int b)throws RemoteException  
{  
    return a / b;  
}  
}
```

### Step 3:

#### Creating the server

This file contains the main program for the server machine. Its primary function is to update the RMI registry on that machine . This is done by using the rebind() method of the Naming class (found in java.rmi ) .that method associates a name with an object reference. The first argument to the rebind() method is a string that names the server. Its second argument is a reference to an interface of CalcServerImpl

#### **Code 3:**

**//Name: Gaurang Sanyasi**

**//Batch No:B2**

**//PRN: 2020016400785461**

**//Date:06-08-2021**

```
import java.net.*;  
import java.rmi.*;  
  
public class P4_RMI_CalcServer_GS  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            P4_RMI_CalcServerImpl_SJ csi = new P4_RMI_CalcServerImpl_GS ();  
            Naming.rebind( "CSBO" , csi );  
        }  
    }  
}
```



# Smt. Chandibai Himathmal Mansukhani College

```
        }//try ends
        catch(Exception e){
System.out.println( "Exception : " + e);
        }//catch ends
    }//main ends
}//class end
```

## Step 4:

### Creating the Client

- This file implements the client side of this distributed application. It accepts three command-line arguments .The first is the IP address or name of the server machine. The second and third arguments are the two numbers that are to be operated.
- This application begins by forming a string that follows the URL syntax.
- This URL uses the rmi protocol. The string includes the IP address or name of the server and the string “CSBO”. The program that invokes the lookup() method of the Naming class. This method accepts one argument , the rmi URL , and returns a reference to an object of type CalcServerIntf. All remote method invocations can then be directed to this object.

### **Code 4:**

```
//Name: Gaurang Sanyasi
//Batch No:B2
//PRN: 2020016400785461
//Date:06-08-2021
import java.rmi.*;
public class P4_RMI_CalcClient_GS
{
    public static void main(String args[])
    {
        try {
            String CSURL = "rmi://" + args[0] + "/CSBO";
            P4_RMI_CalcServerIntf_SJ CSIntf = (P4_RMI_CalcServerIntf_GS)
Naming.lookup(CSURL);
```

## Smt. Chandibai Himathmal Mansukhani College

```
System.out.println(" The first number is: " + args[1]);

int x = Integer.parseInt(args[1]);

System.out.println(" The second number is: " + args[2]);

int y = Integer.parseInt(args[2]);

System.out.println("-----Arithmetic Operation-----");

System.out.println("Addition : " + x + " + " + y + " = " +
CSIntf.add(x , y));

System.out.println("Subtraction : " + x + " - " + y + " = " +
CSIntf.subtract(x , y));

System.out.println("Multiplication : " + x + " * " + y + " = " +
CSIntf.multiply(x , y));

System.out.println("Division : " + x + " / " + y + " = " + CSIntf.divide(x ,
y));

    }//try ends
    catch(Exception e){

        System.out.println("Exception : " + e);

    }//catch ends
} //main ends
} //class ends
```

### Step 5:

#### Manually generate a stub, if required

Prior to Java 5, stubs needed to be built manually by using rmic. This step is not required for modern versions of Java. However, if we work in a legacy environment, then we can use rmic compiler, as shown here, to build a stub.

rmic CalcsServerImpl

# **Smt. Chandibai Himathmal Mansukhani College**

## **Step 6:**

### **Install Files on the Client and Server Machines**

- Copy P4\_RMI\_calcClient\_JD.class , P4\_RMI\_CalcServerImpl\_JD\_Stub.class(if needed),and P4\_RMI\_CalcServerintf\_JD.class to a directory on the client machine.
- Copy CalcServerintf.class , P4\_RMI\_CalcServerImpl\_JD.class , P4\_RMI\_CalcServerImpl\_JD\_Stub.class (if needed), and P4\_RMI\_CalcServer\_JD.class to a directory on the server machine.

## **Step 7:**

### **Start the RMI Registry on the ServerMachine**

- The JDK provides a program called rmiregistry , which executes on the server machine.

It maps names to object references. Start the RMI Registry form the command line , as shown here

`start rmiregistry`

- When this command returns , a new window gets created. Leave this window open until we are done experimenting with the RMI example

# Smt. Chandibai Himathmal Mansukhani College

## Step 8:

### Start the Server

The server code is started from the command line , as shown here

Java P4\_RMI\_CalcServer\_MD

## **Output:**

```
E:\>cd E:\USCS3P01_USCS303_OS_B2\Prac_04_GS_07_08_2021\Q3_PC_RMI_GS

E:\USCS3P01_USCS303_OS_B2\Prac_04_GS_07_08_2021\Q3_PC_RMI_GS>java P4_RMI_CalcClient_GS 127.0.0.1 15 5
The first number is: 15
The second number is: 5
=====Arithmetic Operations=====
Addition: 15+5=20
Subtraction: 15 - 5 = 10
Multiplication: 15 * 5 = 75
Division: 15/5 = 3

E:\USCS3P01_USCS303_OS_B2\Prac_04_GS_07_08_2021\Q3_PC_RMI_GS>
```