

UE20CS301 DBMS LAB

GAURAV MAHAJAN SEC C

LAB 3 DDL COMMANDS


Create tables for the Above-mentioned Relational design and add check, default, not null and unique constraints.

- 1) Specify PK and FK constraints for all applicable Relations
- 2) For Train_name, Train_Type in Train table add not null constraints value
- 3) Add default constraint for compartment table setting Availability attribute to Yes
- 4) train name should be unique
- 5) Add check constraints to Ticket to check if the passenger age is above 5
- 6) Rename any existing table name
- 7) use Truncate and drop commands

CREATING THE DATABASE

```
create database PES1UG20CS150_RR;
```

```
use PES1UG20CS150_RR;
```



```
XAMPP for Windows - mysql -u root
Setting environment for using XAMPP for Windows.
Gaurav@LAPTOP-JTD57DCG c:\xampp
# cd mysql/bin

Gaurav@LAPTOP-JTD57DCG c:\xampp\mysql\bin
# mysql -u root
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 16
Server version: 10.4.24-MariaDB mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> create database PES1UG20CS150_RR
-> \C
ERROR: Usage: \C charset_name | charset charset_name
-> \c
MariaDB [(none)]> create database PES1UG20CS150_RR;
Query OK, 1 row affected (0.002 sec)

MariaDB [(none)]> use database PES1UG20CS150_RR;
ERROR 1049 (42000): Unknown database 'database'
MariaDB [(none)]> use PES1UG20CS150_RR;
Database changed
```

```
create table TRAIN(Train_no integer not null, Name char(20) not null unique, Arrival
time, Destination varchar(150), Availability varchar(15) default 'Yes', Train_type varchar(150) not
null, primary key(Train_no));
```

```
desc TRAIN;
```

```
C:\XAMPP for Windows - mysql -u root
MariaDB [PES1UG20CS150_RR]> create table TRAIN(Train_no integernot null, Name char(20) not null unique, Arrival time, Destination varchar(150), Availability varchar(15) default 'Yes', Train_type varchar(150) not null, primary key(Train_no));
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MariaDB server version for the right syntax to use near 'null, Name char(20) not null unique, Arrival time, Destination varchar(150), Av...' at line 1
MariaDB [PES1UG20CS150_RR]> create table TRAIN(Train_no integer not null, Name char(20) not null unique, Arrival time, Destination varchar(150), Availability varchar(15) default 'Yes', Train_type varchar(150) not null, primary key(Train_no));
Query OK, 0 rows affected (0.017 sec)

MariaDB [PES1UG20CS150_RR]> desc TRAIN
-> \c
MariaDB [PES1UG20CS150_RR]> desc TRAIN;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Train_no   | int(11)   | NO   | PRI | NULL    |       |
| Name       | char(20)  | NO   | UNI | NULL    |       |
| Arrival    | time      | YES  |     | NULL    |       |
| Destination| varchar(150)| YES  |     | NULL    |       |
| Availability| varchar(15)| YES  |     | Yes     |       |
| Train_type | varchar(150)| NO   |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.011 sec)

MariaDB [PES1UG20CS150_RR]> create table COMPARTMENT(type varchar(50), compartment_number integer not null, capacity integer, availability varchar(25) default 'Yes', primary key(compartment_number), Train_no integer, foreign key(Train_no) references TRAIN(Train_no));
Query OK, 0 rows affected (0.019 sec)
```

```
MariaDB [PES1UG20CS150_RR]> create table COMPARTMENT(type
varchar(50), compartment_number integer not null, capacity integer, availability varchar(25) default
'Yes', primary key(compartment_number), Train_no integer, foreign key(Train_no) references
TRAIN(Train_no));
```

```
desc COMPARTMENT;
```

```
MariaDB [PES1UG20CS150_RR]> desc COMPARTMENT;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| type       | varchar(50)| YES  |     | NULL    |       |
| compartment_number | int(11)   | NO   | PRI | NULL    |       |
| capacity   | int(11)   | YES  |     | NULL    |       |
| availability| varchar(25)| YES  |     | Yes     |       |
| Train_no   | int(11)   | YES  | MUL | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.011 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
create table ROUTE_INFO(From_Station_No integer,From_Station_Name
varchar(100),To_Station_No integer,To_Station_Name varchar(100),Distance varchar(50) ,Train_no
integer,primary key(From_Station_No,To_Station_No),foreign key(Train_no) references
TRAIN(Train_no));
```

```
desc ROUTE_INFO;
```

```
MariaDB [PES1UG20CS150_RR]> create table ROUTE_INFO(From_Station_No integer,From_Station_Name varchar(100),To_Station_No integer,To_Station_Name varchar(100),Distance varchar(50) ,Train_no integer,primary key(From_Station_No,To_Station_No),foreign key(Train_no) references TRAIN(Train_no));
Query OK, 0 rows affected (0.020 sec)

MariaDB [PES1UG20CS150_RR]> desc ROUTE_INFO
-> \c
MariaDB [PES1UG20CS150_RR]> desc ROUTE_INFO;
```

Field	Type	Null	Key	Default	Extra
From_Station_No	int(11)	NO	PRI	NULL	
From_Station_Name	varchar(100)	YES		NULL	
To_Station_No	int(11)	NO	PRI	NULL	
To_Station_Name	varchar(100)	YES		NULL	
Distance	varchar(50)	YES		NULL	
Train_no	int(11)	YES	MUL	NULL	

```
6 rows in set (0.010 sec)

MariaDB [PES1UG20CS150_RR]> _
```

```
create table USER(User_id integer not null,User_type varchar(100),F_name varchar(100),L_Name
varchar(100), Age integer, DOB Date, Pincode integer, Street_no integer,primary key(User_id));
```

```
desc USER;
```

```
MariaDB [PES1UG20CS150_RR]> create table USER(User_id integer not null,User_type varchar(100),F_name varchar(100),L_Name varchar(100), Age integer, DOB Date, Pincode integer, Street_no integer,primary key(User_id));
Query OK, 0 rows affected (0.017 sec)

MariaDB [PES1UG20CS150_RR]> desc USER
-> \c
MariaDB [PES1UG20CS150_RR]> desc USER;
```

Field	Type	Null	Key	Default	Extra
User_id	int(11)	NO	PRI	NULL	
User_type	varchar(100)	YES		NULL	
F_name	varchar(100)	YES		NULL	
L_Name	varchar(100)	YES		NULL	
Age	int(11)	YES		NULL	
DOB	date	YES		NULL	
Pincode	int(11)	YES		NULL	
Street_no	int(11)	YES		NULL	

```
8 rows in set (0.011 sec)

MariaDB [PES1UG20CS150_RR]> _
```

```
create table TRAIN_USER(Train_No integer,User_id integer,Date_Time_Stamp datetime,primary
key(Train_No,User_id,Date_Time_Stamp), foreign key(Train_no) references TRAIN(Train_no),foreign
key(User_id) references USER(User_id));
```

```
desc TRAIN_USER;
```

```
MariaDB [PES1UG20CS150_RR]> create table TRAIN_USER(Train_No integer,User_id integer,Date_Time_Stamp
datetime,primary key(Train_No,User_id,Date_Time_Stamp), foreign key(Train_no) references TRAIN(Train_no),foreign
key(User_id) references USER(User_id));
Query OK, 0 rows affected (0.019 sec)

MariaDB [PES1UG20CS150_RR]> desc TRAIN_USER;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Train_No   | int(11)   | NO   | PRI | NULL    |       |
| User_id    | int(11)   | NO   | PRI | NULL    |       |
| Date_Time_Stamp | datetime | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.009 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
create table USER_PHONE(User_id integer,Phone_no varchar(20),primary key(User_id,Phone_no),
foreign key(User_id) references USER(User_id));
```

```
desc USER_PHONE;
```

```
MariaDB [PES1UG20CS150_RR]> create table USER_PHONE(User_id integer,Phone_no varchar(20),primary ke
y(User_id,Phone_no), foreign key(User_id) references USER(User_id));
Query OK, 0 rows affected (0.018 sec)

MariaDB [PES1UG20CS150_RR]> desc USER_PHONE
-> \c
MariaDB [PES1UG20CS150_RR]> desc USER_PHONE;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| User_id    | int(11)   | NO   | PRI | NULL    |       |
| Phone_no   | varchar(20) | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.008 sec)
```

```
create table TICKET(PNR integer,primary key(PNR),Train_NUmber integer,travel_date date,
Departure varchar(100),Arrival varchar(100),Departure_time time,Arrival_Time time,User_id
integer, Train_type varchar(20),Compartment_type varchar(20), Cmpt_No integer, foreign
key(User_id) references USER(User_id));
```

```
desc TICKET;
```

```
MariaDB [PES1UG20CS150_RR]> create table TICKET(PNR integer,primary key(PNR),Train_NUmber integer,t
ravel_date date, Departure varchar(100),Arrival varchar(100),Departure_time time,Arrival_Time time,
User_id integer, Train_type varchar(20),Compartment_type varchar(20), Cmpt_No integer, foreign key(
User_id) references USER(User_id));
Query OK, 0 rows affected (0.019 sec)

MariaDB [PES1UG20CS150_RR]> desc TICKET;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| PNR | int(11) | NO | PRI | NULL | |
| Train_NUmber | int(11) | YES | | NULL | |
| travel_date | date | YES | | NULL | |
| Departure | varchar(100) | YES | | NULL | |
| Arrival | varchar(100) | YES | | NULL | |
| Departure_time | time | YES | | NULL | |
| Arrival_Time | time | YES | | NULL | |
| User_id | int(11) | YES | MUL | NULL | |
| Train_type | varchar(20) | YES | | NULL | |
| Compartment_type | varchar(20) | YES | | NULL | |
| Cmpt_No | int(11) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
11 rows in set (0.010 sec)

MariaDB [PES1UG20CS150_RR]> .
```

```
create table PAYMENT_INFO(Transaction_id integer,primary key(Transaction_id),Bank varchar(100),
Card_Number integer,Price integer, PNR integer, foreign key(PNR) references TICKET(PNR));
```

```
desc PAYMENT_INFO;
```

```
MariaDB [PES1UG20CS150_RR]> create table PAYMENT_INFO(Transaction_id integer,primary key(Transactio
n_id),Bank varchar(100), Card_Number integer,Price integer, PNR integer, foreign key(PNR) reference
s TICKET(PNR));
Query OK, 0 rows affected (0.019 sec)

MariaDB [PES1UG20CS150_RR]> desc PAYMENT_INFO
-> \c
MariaDB [PES1UG20CS150_RR]> desc PAYMENT_INFO;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Transaction_id | int(11) | NO | PRI | NULL | |
| Bank | varchar(100) | YES | | NULL | |
| Card_Number | int(11) | YES | | NULL | |
| Price | int(11) | YES | | NULL | |
| PNR | int(11) | YES | MUL | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.010 sec)

MariaDB [PES1UG20CS150_RR]> .
```

```
create table TICKET_PASSENGER(Seat_No integer, primary key(Seat_No),Name varchar(20),Age integer, PNR integer, foreign key(PNR) references TICKET(PNR));
```

```
desc TICKET_PASSENGER;
```

```
MariaDB [PES1UG20CS150_RR]> create table TICKET_PASSENGER(Seat_No integer, primary key(Seat_No),Name varchar(20),Age integer, PNR integer, foreign key(PNR) references TICKET(PNR));
Query OK, 0 rows affected (0.021 sec)

MariaDB [PES1UG20CS150_RR]> desc TICKET_PASSENGER;
+-----+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Seat_No | int(11)   | NO   | PRI | NULL    |       |
| Name    | varchar(20) | YES  |     | NULL    |       |
| Age     | int(11)   | YES  |     | NULL    |       |
| PNR     | int(11)   | YES  | MUL | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.011 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
create table FARE_TABLE(Train_type varchar(100),Compartment_type varchar(100),primary key(Train_type,Compartment_type), FareperKM integer);
```

```
desc FARE_TABLE;
```

```
MariaDB [PES1UG20CS150_RR]> create table FARE_TABLE(Train_type varchar(100),Compartment_type varchar(100),primary key(Train_type,Compartment_type), FareperKM integer);
Query OK, 0 rows affected (0.023 sec)

MariaDB [PES1UG20CS150_RR]> desc FARE_TABLE;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Train_type | varchar(100) | NO   | PRI | NULL    |       |
| Compartment_type | varchar(100) | NO   | PRI | NULL    |       |
| FareperKM  | int(11)     | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.008 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
alter table TICKET_PASSENGER add check(Age>5);
```

```
desc TICKET_PASSENGER;
```

```
MariaDB [PES1UG20CS150_RR]> alter table TICKET_PASSENGER add check(Age>5);
Query OK, 0 rows affected (0.061 sec)
Records: 0 Duplicates: 0 Warnings: 0

MariaDB [PES1UG20CS150_RR]> desc TICKET_PASSENGER;
+-----+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Seat_No | int(11)   | NO   | PRI | NULL    |       |
| Name    | varchar(20) | YES  |     | NULL    |       |
| Age     | int(11)   | YES  |     | NULL    |       |
| PNR     | int(11)   | YES  | MUL | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.011 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
alter table FARE_TABLE rename FARE;
```

```
desc FARE_TABLE;
```

```
MariaDB [PES1UG20CS150_RR]> alter table FARE_TABLE rename FARE;
Query OK, 0 rows affected (0.012 sec)

MariaDB [PES1UG20CS150_RR]> desc FARE_TABLE
-> \c
MariaDB [PES1UG20CS150_RR]> desc FARE_TABLE;
ERROR 1146 (42S02): Table 'pes1ug20cs150_rr.fare_table' doesn't exist
MariaDB [PES1UG20CS150_RR]> truncate table TRAIN_USER
-> \c
```

```
truncate table TRAIN_USER;
```

```
desc TRAIN_USER;
```

```
MariaDB [PES1UG20CS150_RR]> truncate table TRAIN_USER;
Query OK, 0 rows affected (0.028 sec)

MariaDB [PES1UG20CS150_RR]> desc TRAIN_USER;
+-----+-----+-----+-----+-----+-----+
| Field          | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Train_No       | int(11)   | YES  | MUL | NULL    |       |
| User_id        | int(11)   | YES  | MUL | NULL    |       |
| Date_Time_Stamp | datetime  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.009 sec)

MariaDB [PES1UG20CS150_RR]>
```

```
drop table TRAIN_USER;
```

```
desc TRAIN_USER;
```

```
MariaDB [PES1UG20CS150_RR]> drop table TRAIN_USER;
Query OK, 0 rows affected (0.011 sec)

MariaDB [PES1UG20CS150_RR]> desc TRAIN_USER;
ERROR 1146 (42S02): Table 'pes1ug20cs150_rr.train_user' doesn't exist
MariaDB [PES1UG20CS150_RR]> _
```