RHOSO 18 Syslog Forwarding: Commands

Prepared: 12 October 2026 | Environment: RHOSO 18.0 on OpenShift 4.18 | Syslog server: 172.19.133.21, TCP 514

Syslog server: 172.19.133.21, TCP 514. Run the Control Plane commands from the bastion. Run the Data Plane commands as root on each compute node, one node at a time.

1. Control Plane (OpenShift)

1.1 Pre-checks

```
oc whoami
oc get nodes -o wide
oc get pods -n openshift-logging | grep logforwarder
oc get clusterlogforwarder logforwarder -n openshift-logging -o yaml
oc get pods -n openstack | grep -v -E "Running|Completed"
for ip in <master-ip-1> <master-ip-2> <master-ip-3>; do
  echo "== $ip"
  ssh core@$ip 'timeout 3 bash -c "</dev/tcp/172.19.133.21/514" && echo
succeeded || echo FAILED'
done
```

1.2 Backup

```
mkdir -p /root/rhoso-syslog && cd /root/rhoso-syslog
oc get clusterlogforwarder logforwarder -n openshift-logging -o json \
 | jq
'del(.metadata.resourceVersion,.metadata.uid,.metadata.managedFields,.metadat
a.creationTimestamp,.metadata.generation,.status)' \
 > clf-backup-$(date +%Y%m%d).json
ls -l
```

1.3 Create the new forwarder file

Copy of the live configuration plus three additions: input `openstack-pods`, output `remote-syslog`, pipeline `openstack-to-syslog`.

```
cat > /root/rhoso-syslog/clf-new.yaml << 'EOF'
apiVersion: observability.openshift.io/v1
kind: ClusterLogForwarder
metadata:
  name: logforwarder
  namespace: openshift-logging
spec:
  managementState: Managed
  serviceAccount:
    name: logging-collector
  inputs:
  - name: edpm-syslog-input
    type: receiver
    receiver:
      type: syslog
      port: 10514
  - name: openstack-pods
    type: application
    application:
      includes:
      - namespace: openstack
      - namespace: openstack-operators
  outputs:
  - name: lokistack-out
    type: lokiStack
    lokiStack:
      authentication:
        token:
          from: serviceAccount
      target:
        name: lokistack
        namespace: openshift-logging
    tls:
      ca:
        configMapName: openshift-service-ca.crt
        key: service-ca.crt
  - name: remote-syslog
    type: syslog
    syslog:
      url: tcp://172.19.133.21:514
      rfc: RFC5424
      facility: local6
      severity: informational
```

```
      appName: rhoso
      tuning:
        deliveryMode: AtMostOnce
  pipelines:
  - name: infra-app-logs
    inputRefs:
    - infrastructure
    - application
    - audit
    outputRefs:
    - lokistack-out
  - name: dataplane-logs
    inputRefs:
    - edpm-syslog-input
    outputRefs:
    - lokistack-out
  - name: openstack-to-syslog
    inputRefs:
    - openstack-pods
    outputRefs:
    - remote-syslog
EOF
```

1.4 Diff and dry-run (nothing changes)

```
cd /root/rhoso-syslog
oc diff -f clf-new.yaml
oc apply -f clf-new.yaml --dry-run=server --validate=strict
```

The diff must show only the three additions. Do not apply if anything existing changes.

1.5 Apply

Terminal 2:

```
oc get pods -n openshift-logging -w | grep logforwarder
```

Terminal 1:

```
cd /root/rhoso-syslog
oc get clusterlogforwarder logforwarder -n openshift-logging -o yaml > clf-
live-before-apply.yaml
oc apply -f clf-new.yaml
```

1.6 Verify

```
oc get clusterlogforwarder logforwarder -n openshift-logging -o
jsonpath='{.status.conditions}' | jq '.[] | {type,status,reason,message}'
for p in $(oc get pods -n openshift-logging -o name | grep logforwarder); do
  echo "== $p"; oc logs -n openshift-logging $p --since=10m | grep -v "too
small to fingerprint" | grep -iE "error|warn|syslog|172.19.133.21|loki" |
tail -10
done
oc get pods -n openstack | grep -v -E "Running|Completed"
oc adm top nodes
oc adm top pods -n openshift-logging
```

1.7 Confirm the connection and generate test logs

Run on each master (RHCOS: do not install tcpdump):

```
sudo conntrack -L -d 172.19.133.21 2>/dev/null | head -3
```

From the bastion:

```
oc exec -n openstack openstackclient -- openstack server list
```

1.8 Rollback

```
oc apply -f /root/rhoso-syslog/clf-backup-<date>.json
oc get pods -n openshift-logging | grep logforwarder
```

2. Data Plane (compute nodes)

Login: `ssh cloud-admin@<node-ip>` then `sudo -i`.

2.1 Pre-checks

```
hostname
ip route get 172.19.133.21 | grep -oP 'src \K\S+'
systemctl is-active rsyslog
df -h /var/lib/rsyslog
ls /etc/rsyslog.d/
getenforce
timeout 3 bash -c '</dev/tcp/172.19.133.21/514' && echo succeeded || echo
FAILED
cat /etc/rsyslog.d/10-telemetry.conf | grep -E "target|port"
ss -tnp dst 10.28.153.100 | grep rsyslogd
systemctl status rsyslog | grep -E "Active|Memory"
```

2.2 Backup

```
mkdir -p /root/rsyslog-backup && cp -a /etc/rsyslog.conf /etc/rsyslog.d
/root/rsyslog-backup/
```

2.3 Create the forwarding rule

```
tee /etc/rsyslog.d/50-forward-system.conf > /dev/null << 'EOF'
*.info;mail.none;authpriv.none;cron.none action(type="omfwd"
    target="172.19.133.21" port="514" protocol="tcp" KeepAlive="on"
    action.resumeRetryCount="-1" action.resumeInterval="30"
    queue.type="LinkedList" queue.size="10000"
    queue.maxDiskSpace="1g" queue.filename="sys_fwd"
    queue.saveOnShutdown="on" queue.timeoutEnqueue="0")
EOF
```

2.4 Validate (restart only if this ends with "End of config validation run. Bye.")

```
rsyslogd -N1
```

2.5 Restart and check

```
systemctl restart rsyslog
systemctl is-active rsyslog
ausearch -m avc -c rsyslogd -ts recent
ss -tnp dst 172.19.133.21
ss -tnp dst 10.28.153.100 | grep rsyslogd
ss -tni dst 172.19.133.21 | grep -oE "bytes_sent:[0-9]+|bytes_acked:[0-9]+"
systemctl status rsyslog | grep Memory
```

2.6 Test message

Terminal 2 (start first):

```
timeout 60 tcpdump -Z root -i any -l -s0 -nn -A 'host 172.19.133.21 and port
514' 2>/dev/null | grep -a -E "SYSLOG-PROOF|nova_compute"
```

Terminal 1 (within 60 seconds):

```
logger "SYSLOG-PROOF-$(hostname)-$(date -u +%Y%m%d_%H%M%S)"
```

2.7 Soak (every 10 minutes, for 30 minutes)

```
systemctl status rsyslog | grep Memory
ls -lh /var/lib/rsyslog/
```

2.8 Rollback

```
rm -f /etc/rsyslog.d/50-forward-system.conf
systemctl restart rsyslog
rm -f /var/lib/rsyslog/sys_fwd.*
systemctl is-active rsyslog
```