




```
final helloProvider = Provider<String>((ref) {  
    return "Hello";  
});
```




```
Provider<String>(  
  create: (context) => "Hello",  
  child: ChildA(),  
),
```



```
Provider<String>(  
  create: (context) => "Hello",  
  child: ChildB(),  
),
```

⋮



WidgetThatWantsToAccessHello

```
Provider.of<String>(context)
```

Consumer

ConsumerWidget

ConsumerStatefulWidget

<USAGE>

watch	• a widget reads the value of a provider and listens for changes in that value, and when that value changes, it <u>rebuilds the widget</u> listening to that value. • If a provider watches another provider, it will <u>rebuild the listening provider</u> when the value of the provider it is watching changes.
listen	• the widget reads the value of the provider and listens for changes in the value, but unlike watch, listen is not intended to rebuild the widget when the value of the provider changes, but to <u>perform an action</u>, such as <i>displaying a dialog</i> or <i>navigating to a new page</i>.
read	• read <u>reads a value but ignores changes</u>, so it's often used in places like a <i>button's callback</i> where you don't need to listen for changes in the value.

<CAUTION>

watch	• <code>ref.watch</code> should not be called asynchronously, such as within a button's <code>onPressed</code> callback. • It should also not be called in a widget's lifecycle method, such as <code>initState</code>. • In these cases, consider whether it is appropriate to use <code>ref.read</code>.
listen	• <code>ref.listen</code> should not be called asynchronously, as it is used within the <code>onPressed</code> callback of a button. • It should also not be called within a widget's lifecycle method, such as <code>initState</code>. • However, <code>ref</code> does have a <code>listenManual</code> function. The purpose of the <code>listenManual</code> function is similar to <code>listen</code>, but unlike <code>listen</code>, it is not safe to use within a <code>build</code> function. The <code>listenManual</code> function is designed to be used within a widget's lifecycle, such as <code>initState</code>.
read	• don't use the <code>ref.read</code> method in the <code>build</code> function. • It's easy to think that it's okay to use it because I know the value of this provider doesn't change, but Remi, the author of Riverpod, says that using <code>read</code> for this purpose is a very bad practice and can lead to very hard-to-trace bugs.