

Why to avoid using read and prefer watch, which is generally safer to use? #321

<https://github.com/rrousselGit/riverpod/issues/321>

DON'T CALL READ INSIDE THE BODY OF A PROVIDER

```
@riverpod
MyValue my(MyRef ref) {
  // Bad practice to call `read` here
  final value = ref.read(anotherProvider);
  return value;
}
```

If you used read as an attempt to avoid unwanted rebuilds of your object, refer to My_provider updates too often, what can I do?

```
ChangeNotifierProxyProvider<MyModel, MyChangeNotifier>(
  create: (_) => MyChangeNotifier(),
  update: (_, myModel, myNotifier) => myNotifier
    ..update(myModel),
  child: ...
);
```

ChangeNotifierProxyProvider2<T, T2, R extends **ChangeNotifier?**>

A **ChangeNotifierProvider** that builds and synchronizes a **ChangeNotifier** with external values.

ChangeNotifierProxyProvider3<T, T2, T3, R extends **ChangeNotifier?**>

A **ChangeNotifierProvider** that builds and synchronizes a **ChangeNotifier** with external values.

ChangeNotifierProxyProvider4<T, T2, T3, T4, R extends **ChangeNotifier?**>

A **ChangeNotifierProvider** that builds and synchronizes a **ChangeNotifier** with external values.

ChangeNotifierProxyProvider5<T, T2, T3, T4, T5, R extends **ChangeNotifier?**>

A **ChangeNotifierProvider** that builds and synchronizes a **ChangeNotifier** with external values.

ChangeNotifierProxyProvider6<T, T2, T3, T4, T5, T6, R extends **ChangeNotifier?**>

A **ChangeNotifierProvider** that builds and synchronizes a **ChangeNotifier** with external values.