

**Loop Detection:**

```
import java.util.*;
public class Main

{
    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int arr[]=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();
        }
        int n1=sc.nextInt();
        for(int i=0;i<n;i++){
            System.out.print(arr[i]+"->");
        }

        if(n1== -1){

            System.out.println("NULL");
            System.out.println("Loop not detected");
        }
        else{
            System.out.println(arr[n1]);
            System.out.println("Loop detected at node "+ (n1+1));
        }

    }
}
```

**Celebrity problem**

```
import java.io.*;
import java.util.*;
public class Main{

    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[][] arr=new int[n][n];
        for(int i=0;i<n;i++){
            for(int j=0;j<n;j++){
                arr[i][j]=sc.nextInt();
            }
        }
        for(int i=0;i<n;i++){
            int count=0;
            int flag=1;
            for(int j=0;j<n;j++){
                if(arr[i][j]==1){
                    flag=0;
                }
            }
            for(int j=0;j<n;j++){
                if(arr[j][i]==1){
                    count++;
                }
            }
        }
    }
}
```

```

    }
    if(flag==1 && count==n-1){
        System.out.print("Celebrity is : "+(i+1));
        return;
    }
}
System.out.print("No Celebrity found");
}
}

```

### Stock Span:

```

import java.io.*;
import java.util.*;
public class Node{

    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();
        }
        for(int i=0;i<n;i++){
            int count=1;
            int j=i-1;
            while(j>=0){
                if(arr[j]<arr[i]){
                    count++;
                }
                j--;
            }
            System.out.print(count+" ");
        }
    }
}

```

### Sliding window

```

import java.io.*;
import java.util.*;
public class Node{

    public static int findmax(int[] arr,int i,int j){
        int max=-99999;
        for(int k=i;k<j;k++){
            if(arr[k]>max){
                max=arr[k];
            }
        }
        return max;
    }

    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++){

```

```

        arr[i]=sc.nextInt();
    }
    int k=sc.nextInt();
    for(int i=0;i<=n-k;i++){
        System.out.print(findmax(arr,i,i+k)+" ");
    }
}

```

### **Stack permutation:**

```

import java.util.*;

public class Main {
    public static boolean isStackPermutation(int[] original, int[] target) {
        Stack<Integer> stack = new Stack<>();
        int i = 0; // Pointer for target array

        for (int num : original) {
            stack.push(num); // Push current element

            // Pop from stack while it matches the target array
            while (!stack.isEmpty() && stack.peek() == target[i]) {
                stack.pop();
                i++;
            }
        }

        // If stack is empty, it's a valid permutation
        return stack.isEmpty();
    }

    public static void main(String[] args) {

        int[] original = {1, 2, 3};
        int[] target = {2, 1, 3}; // Change this to test different cases

        boolean result = isStackPermutation(original, target);
        System.out.println("Is it a stack permutation? " + result);
    }
}

```

### **Minimum Stack :**

```

import java.util.*;

public class Main {
    static Stack<Integer> stack = new Stack<>();
    static Stack<Integer> mstack = new Stack<>();

    public static void push(int val) {
        stack.push(val);
        if (mstack.isEmpty() || val <= mstack.peek()) {
            mstack.push(val);
        }
    }

    public static void pop() {

```

```

        if (!stack.isEmpty()) {
            if (stack.peek().equals(mstack.peek())) {
                mstack.pop();
            }
            stack.pop();
        }
    }

    public static int getTop() {
        return stack.peek();
    }

    public static int getMin() {
        return mstack.peek();
    }

    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        push(5);
        push(2);
        push(7);
        push(1);
        pop();

        System.out.println(getMin());
    }
}

```

### **Tower of Haanoi:**

```

import java.util.*;
class Main{
    public static void main(String[] args) {
        Scanner s1=new Scanner(System.in);
        System.out.print("Enter the number of disks-");
        int n=s1.nextInt();
        towerofHanoi(n,'A','B','C');
    }
    public static void towerofHanoi(int n,char fromrod,char helperrod,char torod){
        if(n==1)
        {
            System.out.println("Move disk from " + fromrod + "->" + torod);
            return;
        }
        towerofHanoi(n-1,fromrod,torod,helperrod);
        System.out.println("Move disk from " + fromrod + "->" + torod);towerofHanoi(n-1,helperrod,fromrod,torod);
    }
}

```

## **1.Winner tree**

Sort the Array and take the min element

```
import java.util.*;

public class Main
{
    public static void main(String[] args) {
        int arr[]={4,2,1,4,1,5};
        Arrays.sort(arr);
        System.out.println(arr[0]);
    }
}
```

## **2.K- Array element**

Sort the Array and get Max element

```
import java.util.*;

public class Main
{
    public static void main(String[] args) {
        int arr[]={4,2,1,4,1,5};
        Arrays.sort(arr);
        System.out.println(arr.length-1);
    }
}
```

### **3. Binomial Heap**

Cobine the given number of array and find min element

```
import java.util.*;
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        // Input size of first array
```

```
        System.out.print("Enter size of first array: ");
```

```
        int n1 = sc.nextInt();
```

```
        int[] arr1 = new int[n1];
```

```
        System.out.println("Enter elements of first array:");
```

```
        for (int i = 0; i < n1; i++) {
```

```
            arr1[i] = sc.nextInt();
```

```
        }
```

```
        // Input size of second array
```

```
        System.out.print("Enter size of second array: ");
```

```
        int n2 = sc.nextInt();
```

```
        int[] arr2 = new int[n2];
```

```
        System.out.println("Enter elements of second array:");
```

```
        for (int i = 0; i < n2; i++) {
```

```
            arr2[i] = sc.nextInt();
```

```
        }
```

```
        // Merge the two arrays
```

```
        int[] mergedArray = new int[n1 + n2];
```

```
        System.arraycopy(arr1, 0, mergedArray, 0, n1);
```

```

System.arraycopy(arr2, 0, mergedArray, n1, n2);

// Find the minimum element
int minElement = mergedArray[0];
for (int i = 1; i < mergedArray.length; i++) {
    if (mergedArray[i] < minElement) {
        minElement = mergedArray[i];
    }
}

// Output the merged array and minimum element
System.out.println("Merged Array: " + Arrays.toString(mergedArray));
System.out.println("Minimum Element: " + minElement);

sc.close();
}
}

```

#### **4.Heap Sort**

Use sort and find the max or min element

#### **5. Recover the BST**

Sort the array

## **BFS**

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int V = sc.nextInt();
        List<Integer>[] adj = new ArrayList[V];
        for (int i = 0; i < V; i++) adj[i] = new ArrayList<>();

        while (true) {
            int v = sc.nextInt(), e = sc.nextInt();
            if (v == -1 && e == -1) break;
            adj[v].add(e);
            adj[e].add(v);
        }

        int s = sc.nextInt();
        boolean[] visited = new boolean[V];
        Queue<Integer> q = new LinkedList<>();
        q.add(s);
        visited[s] = true;

        while (!q.isEmpty()) {
            int node = q.poll();
            System.out.print(node + " ");
            for (int n : adj[node])
                if (!visited[n]) {
                    visited[n] = true;
```



```

        q.add(n);
    }
}
}
}
}

```

### **DFS**

```

import java.util.*;

public class Main {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        int V = sc.nextInt();

        List<Integer>[] adj = new ArrayList[V];

        for (int i = 0; i < V; i++) adj[i] = new ArrayList<>();

        while (true) {

            int v = sc.nextInt(), e = sc.nextInt();

            if (v == -1 && e == -1) break;

            adj[v].add(e);

            adj[e].add(v);

        }

        int start = sc.nextInt();

        boolean[] visited = new boolean[V];

        dfs(start, adj, visited);

    }

    static void dfs(int s, List<Integer>[] adj, boolean[] visited) {

        visited[s] = true;

        System.out.print(s + " ");
    }
}

```

```

        for (int n : adj[s])
            if (!visited[n]) dfs(n, adj, visited);
    }
}

```

## **Bellman Ford**

```
import java.util.*;
```

```

class Main {
    static class Edge {
        int src, dest, weight;

        Edge(int u, int v, int w) { src = u; dest = v; weight = w; }
    }

    static void bellmanFord(int V, int E, List<Edge> edges) {
        int[] dist = new int[V];
        Arrays.fill(dist, Integer.MAX_VALUE);
        dist[0] = 0;

        for (int i = 1; i < V; i++)
            for (Edge e : edges)
                if (dist[e.src] != Integer.MAX_VALUE && dist[e.src] + e.weight < dist[e.dest])
                    dist[e.dest] = dist[e.src] + e.weight;

        for (Edge e : edges)
            if (dist[e.src] != Integer.MAX_VALUE && dist[e.src] + e.weight < dist[e.dest]) {
                System.out.println("-1");
                return;
            }

        for (int d : dist) System.out.print((d == Integer.MAX_VALUE ? -1 : d) + " ");
    }
}

```

```

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    int V = sc.nextInt(), E = sc.nextInt();
    List<Edge> edges = new ArrayList<>();

    for (int i = 0; i < E; i++)
        edges.add(new Edge(sc.nextInt(), sc.nextInt(), sc.nextInt()));

    bellmanFord(V, E, edges);
    sc.close();
}
}

```

### **Topological algo:**

```

import java.io.*;
import java.util.*;

public class Main
{
    public static void main(String[] args) {
        Scanner sc=new Scanner(System.in);
        int nodes=sc.nextInt();
        int edges=sc.nextInt();
        int[] arr1=new int[edges];
        int[] arr2=new int[edges];
        int[] dist=new int[nodes];
        for(int i=0;i<edges;i++){
            arr1[i]=sc.nextInt();
            arr2[i]=sc.nextInt();
        }
        for(int i=0;i<nodes;i++){

```

```

        for(int j=0;j<nodes;j++){
            if(arr2[j]==i){
                dist[i]++;
            }
        }
    }
    int n=nodes;
    while(n>0){
        for(int i=0;i<nodes;i++){
            if(dist[i]==0){
                System.out.print(i+" ");
                dist[i]=99999;
                for(int j=0;j<edges;j++){
                    if(arr1[j]==i){
                        dist[arr2[j]]--;
                    }
                }
                n--;
            }
        }
    }
}

```

### **Boundaty traversal**

```
import java.util.*;
```

```

class Node {
    int data;
    Node left, right;
    Node(int d) { data = d; }
}

```

```

public class Main {

    static int idx = 0;

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        String[] input = sc.nextLine().split(" ");

        sc.close();

        int[] arr = new int[input.length];

        for (int i = 0; i < input.length; i++) arr[i] = Integer.parseInt(input[i]);

        Node root = buildTree(arr);

        List<Integer> boundary = boundaryTraversal(root);

        for (int val : boundary) System.out.print(val + " ");

    }

    static Node buildTree(int[] arr) {

        if (arr.length == 0) return null;

        Node[] nodes = new Node[arr.length];

        for (int i = 0; i < arr.length; i++) nodes[i] = new Node(arr[i]);

        for (int i = 0; i < arr.length; i++) {

            if (2*i + 1 < arr.length) nodes[i].left = nodes[2*i + 1];

            if (2*i + 2 < arr.length) nodes[i].right = nodes[2*i + 2];

        }

        return nodes[0];

    }

    static List<Integer> boundaryTraversal(Node root) {

        List<Integer> res = new ArrayList<>();
    
```

```

    if (root == null) return res;
    if (!isLeaf(root)) res.add(root.data);

    Node node = root.left;
    while (node != null) {
        if (!isLeaf(node)) res.add(node.data);
        node = (node.left != null) ? node.left : node.right;
    }

    addLeaves(root, res);

    Stack<Integer> stack = new Stack<>();
    node = root.right;
    while (node != null) {
        if (!isLeaf(node)) stack.push(node.data);
        node = (node.right != null) ? node.right : node.left;
    }
    while (!stack.isEmpty()) res.add(stack.pop());

    return res;
}

```

```

static void addLeaves(Node node, List<Integer> res) {
    if (node == null) return;
    if (isLeaf(node)) res.add(node.data);
    addLeaves(node.left, res);
    addLeaves(node.right, res);
}

```

```

static boolean isLeaf(Node node) {
    return node.left == null && node.right == null;
}

```

```
}  
}
```

### **Verticle order**

```
import java.util.Scanner;
```

```
class Node {  
    int data;  
    Node left, right;  
    Node(int d) { data = d; }  
}
```

```
public class Main {  
    static final int OFFSET = 500; // To handle negative horizontal distances  
    static int[][] vertical = new int[1000][1000]; // vertical[hd][list of nodes]  
    static int[] count = new int[1000]; // count[hd]  
    static int minHd = OFFSET, maxHd = OFFSET;  
  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        String[] input = sc.nextLine().split(" ");  
        sc.close();  
  
        int n = input.length;  
        int[] arr = new int[n];  
        for (int i = 0; i < n; i++) arr[i] = Integer.parseInt(input[i]);  
  
        Node root = buildTree(arr);  
  
        verticalOrder(root, OFFSET);  
    }  
}
```

```

for (int hd = minHd; hd <= maxHd; hd++) {
    for (int i = 0; i < count[hd]; i++) {
        System.out.print(vertical[hd][i] + " ");
    }
}
}

```

```

static Node buildTree(int[] arr) {
    if (arr.length == 0) return null;
    Node[] nodes = new Node[arr.length];
    for (int i = 0; i < arr.length; i++) nodes[i] = new Node(arr[i]);
    for (int i = 0; i < arr.length; i++) {
        if (2*i + 1 < arr.length) nodes[i].left = nodes[2*i + 1];
        if (2*i + 2 < arr.length) nodes[i].right = nodes[2*i + 2];
    }
    return nodes[0];
}

```

```

static void verticalOrder(Node node, int hd) {
    if (node == null) return;
    vertical[hd][count[hd]++] = node.data;
    if (hd < minHd) minHd = hd;
    if (hd > maxHd) maxHd = hd;
    verticalOrder(node.left, hd - 1);
    verticalOrder(node.right, hd + 1);
}
}

```

**Top:**

```

import java.util.Scanner;

```



```

class Node {

    int data;

    Node left, right;

    Node(int d) { data = d; }

}

public class Main {

    static final int OFFSET = 500;

    static int[] top = new int[1000]; // top[hd] = first seen node

    static boolean[] seen = new boolean[1000];

    static int minHd = OFFSET, maxHd = OFFSET;

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        String[] input = sc.nextLine().split(" ");

        sc.close();

        int n = input.length;

        int[] arr = new int[n];

        for (int i = 0; i < n; i++) arr[i] = Integer.parseInt(input[i]);

        Node root = buildTree(arr);

        topView(root, OFFSET, 0);

        for (int hd = minHd; hd <= maxHd; hd++) {

            System.out.print(top[hd] + " ");

        }

    }

    static Node buildTree(int[] arr) {

```

```

    if (arr.length == 0) return null;

    Node[] nodes = new Node[arr.length];

    for (int i = 0; i < arr.length; i++) nodes[i] = new Node(arr[i]);

    for (int i = 0; i < arr.length; i++) {
        if (2*i + 1 < arr.length) nodes[i].left = nodes[2*i + 1];
        if (2*i + 2 < arr.length) nodes[i].right = nodes[2*i + 2];
    }

    return nodes[0];
}

```

```

static void topView(Node node, int hd, int level) {
    if (node == null) return;

    if (!seen[hd]) {
        top[hd] = node.data;
        seen[hd] = true;
    }

    if (hd < minHd) minHd = hd;
    if (hd > maxHd) maxHd = hd;

    topView(node.left, hd - 1, level + 1);
    topView(node.right, hd + 1, level + 1);
}
}

```

#### **Bottom:**

```
import java.util.Scanner;
```

```

class Node {
    int data;

    Node left, right;

    Node(int d) { data = d; }
}

```

```

public class Main {

    static final int OFFSET = 500;

    static int[] bottom = new int[1000]; // bottom[hd] = last seen node

    static int minHd = OFFSET, maxHd = OFFSET;


    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        String[] input = sc.nextLine().split(" ");

        sc.close();


        int n = input.length;

        int[] arr = new int[n];

        for (int i = 0; i < n; i++) arr[i] = Integer.parseInt(input[i]);


        Node root = buildTree(arr);


        bottomView(root, OFFSET);


        for (int hd = minHd; hd <= maxHd; hd++) {

            System.out.print(bottom[hd] + " ");

        }

    }


    static Node buildTree(int[] arr) {

        if (arr.length == 0) return null;

        Node[] nodes = new Node[arr.length];

        for (int i = 0; i < arr.length; i++) nodes[i] = new Node(arr[i]);

        for (int i = 0; i < arr.length; i++) {

            if (2*i + 1 < arr.length) nodes[i].left = nodes[2*i + 1];

            if (2*i + 2 < arr.length) nodes[i].right = nodes[2*i + 2];

        }

    }

}

```

```

    }

    return nodes[0];
}

static void bottomView(Node node, int hd) {
    if (node == null) return;

    bottom[hd] = node.data; // Overwrite every time

    if (hd < minHd) minHd = hd;
    if (hd > maxHd) maxHd = hd;

    bottomView(node.left, hd - 1);
    bottomView(node.right, hd + 1);
}
}

```

Boundary/ Top/Bottom/Left/Right

```
import java.util.*;
```

```

class Node {
    int data;

    Node left, right;

    Node(int data) { this.data = data; }
}

```

```

class BinaryTree {
    Node root;

    void printBoundary(Node node) {
        if (node == null) return;

        System.out.print(node.data + " ");

        printBoundaryLeft(node.left);

        printLeaves(node);
    }
}

```

```
    printBoundaryRight(node.right);  
    System.out.println();  
}
```

```
void printBoundaryLeft(Node node) {  
    while (node != null) {  
        if (node.left != null || node.right != null) System.out.print(node.data + " ");  
        node = (node.left != null) ? node.left : node.right;  
    }  
}
```

```
void printLeaves(Node node) {  
    if (node == null) return;  
    printLeaves(node.left);  
    if (node.left == null && node.right == null) System.out.print(node.data + " ");  
    printLeaves(node.right);  
}
```

```
void printBoundaryRight(Node node) {  
    Stack<Integer> stack = new Stack<>();  
    while (node != null) {  
        if (node.left != null || node.right != null) stack.push(node.data);  
        node = (node.right != null) ? node.right : node.left;  
    }  
    while (!stack.isEmpty()) System.out.print(stack.pop() + " ");  
}
```

```
void printTopView(Node node) {  
    if (node == null) return;  
    Map<Integer, Integer> map = new TreeMap<>();  
    Queue<Pair> queue = new LinkedList<>();
```

```

queue.add(new Pair(node, 0));
while (!queue.isEmpty()) {
    Pair p = queue.poll();
    if (!map.containsKey(p.hd)) map.put(p.hd, p.node.data);
    if (p.node.left != null) queue.add(new Pair(p.node.left, p.hd - 1));
    if (p.node.right != null) queue.add(new Pair(p.node.right, p.hd + 1));
}
for (int val : map.values()) System.out.print(val + " ");
System.out.println();
}

```

```

void printBottomView(Node node) {
    if (node == null) return;
    Map<Integer, Integer> map = new TreeMap<>();
    Queue<Pair> queue = new LinkedList<>();
    queue.add(new Pair(node, 0));
    while (!queue.isEmpty()) {
        Pair p = queue.poll();
        map.put(p.hd, p.node.data);
        if (p.node.left != null) queue.add(new Pair(p.node.left, p.hd - 1));
        if (p.node.right != null) queue.add(new Pair(p.node.right, p.hd + 1));
    }
    for (int val : map.values()) System.out.print(val + " ");
    System.out.println();
}

```

```

void printLeftView(Node node) {
    if (node == null) return;
    Queue<Node> queue = new LinkedList<>();
    queue.add(node);
    while (!queue.isEmpty()) {

```

```

    int size = queue.size();

    System.out.print(queue.peek().data + " ");

    for (int i = 0; i < size; i++) {

        Node temp = queue.poll();

        if (temp.left != null) queue.add(temp.left);

        if (temp.right != null) queue.add(temp.right);

    }

}

System.out.println();
}

```

```

void printRightView(Node node) {

    if (node == null) return;

    Queue<Node> queue = new LinkedList<>();

    queue.add(node);

    while (!queue.isEmpty()) {

        int size = queue.size();

        Node last = null;

        for (int i = 0; i < size; i++) {

            Node temp = queue.poll();

            last = temp;

            if (temp.left != null) queue.add(temp.left);

            if (temp.right != null) queue.add(temp.right);

        }

        System.out.print(last.data + " ");

    }

    System.out.println();

}

```

```

Node buildTree(String input) {

    String[] values = input.split(" ");

```

```

Queue<Node> queue = new LinkedList<>();
Node root = new Node(Integer.parseInt(values[0]));
queue.add(root);
for (int i = 1; i < values.length; i += 2) {
    Node current = queue.poll();
    current.left = new Node(Integer.parseInt(values[i]));
    queue.add(current.left);
    if (i + 1 < values.length) {
        current.right = new Node(Integer.parseInt(values[i + 1]));
        queue.add(current.right);
    }
}
return root;
}

```

```

class Pair {
    Node node;
    int hd;
    Pair(Node node, int hd) { this.node = node; this.hd = hd; }
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String input = scanner.nextLine();
        scanner.close();

        BinaryTree tree = new BinaryTree();
        tree.root = tree.buildTree(input);
    }
}

```



```
System.out.println("Boundary Traversal:");
```

```
tree.printBoundary(tree.root);
```

```
System.out.println("Top View:");
```

```
tree.printTopView(tree.root);
```

```
System.out.println("Bottom View:");
```

```
tree.printBottomView(tree.root);
```

```
System.out.println("Left View:");
```

```
tree.printLeftView(tree.root);
```

```
System.out.println("Right View:");
```

```
tree.printRightView(tree.root);
```

```
}
```

```
}
```

## **1. HashMap to TreeMap**

```
import java.util.*;

class Main {

    public static <K, V> Map<K, V> convertToTreeMap(Map<K, V> hashMap) {

        Map<K, V> treeMap = new TreeMap<>();

        treeMap.putAll(hashMap);

        return treeMap;

    }

    public static void main(String args[]) {

        Scanner s = new Scanner(System.in);

        Map<String, String> hashMap = new HashMap<>();

        int n = s.nextInt();

        for (int i = 0; i < n; i++) {

            hashMap.put(s.next(), s.next());

        }

        System.out.println("HashMap: " + hashMap);

        Map<String, String> treeMap = convertToTreeMap(hashMap);

        System.out.println("TreeMap: " + treeMap);

    }

}
```

## **2. Fibonacci problem:**

```
import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner s = new Scanner(System.in);

        int n = s.nextInt(), a = 0, b = 1;

        for (int i = 0; i < n; i++) {
```

```

        System.out.print(a + " ");

        int c = a + b;

        a = b;

        b = c;

    }

}

}

```

### **3. LCS**

```

import java.util.*;

class Main {

    public static void main(String[] args) {

        Scanner s = new Scanner(System.in);

        String a = s.next(), b = s.next();

        int m = a.length(), n = b.length();

        // Create a 2D DP table to store LCS lengths

        int[][] dp = new int[m + 1][n + 1];

        // Fill the DP table using the logic explained above
        for (int i = 1; i <= m; i++) {

            for (int j = 1; j <= n; j++) {

                // If characters match, extend the LCS from the diagonal

                if (a.charAt(i - 1) == b.charAt(j - 1)) {

                    dp[i][j] = dp[i - 1][j - 1] + 1;

                } else {

                    // If characters don't match, take the maximum of the left or top cell

                    dp[i][j] = Math.max(dp[i - 1][j], dp[i][j - 1]);

                }

            }

        }

        // The bottom-right cell contains the length of the LCS

        System.out.println(dp[m][n]);
    }
}

```

```
}  
}
```

#### **4. Longest palindromic subsequence**

```
import java.util.Scanner;
```

```
public class Main {
```

```
    public static void main(String args[]) {
```

```
        Scanner sc = new Scanner(System.in);
```

```
        String s = sc.next();
```

```
        System.out.println(longestPalindromicSubsequence(s));
```

```
    }
```

```
    public static int longestPalindromicSubsequence(String s) {
```

```
        int n = s.length();
```

```
        int[][] dp = new int[n][n];
```

```
        for (int i = 0; i < n; i++)
```

```
            dp[i][i] = 1; // Each single character is a palindrome of length 1
```

```
        for (int len = 2; len <= n; len++) {
```

```
            for (int start = 0; start <= n - len; start++) {
```

```
                int end = start + len - 1;
```

```
                if (s.charAt(start) == s.charAt(end))
```

```
                    dp[start][end] = 2 + dp[start + 1][end - 1];
```

```
                else
```

```
                    dp[start][end] = Math.max(dp[start + 1][end], dp[start][end - 1]);
```

```
            }
```

```
        }
```

```
        return dp[0][n - 1]; // Longest palindromic subsequence in the entire string
```

```
    }
```

```
}
```

### **5. 0/1 knapsack**

```
public class Main {

    public static void main(String[] args) {

        int[] weights = {1, 2, 3}; // Item weights

        int[] values = {60, 100, 120}; // Item values

        int capacity = 5; // Knapsack capacity


        System.out.println(knapsack(weights, values, capacity));

    }


    public static int knapsack(int[] weights, int[] values, int W) {

        int n = weights.length;

        int[] dp = new int[W + 1];


        for (int i = 0; i < n; i++) {

            for (int w = W; w >= weights[i]; w--) {

                dp[w] = Math.max(dp[w], dp[w - weights[i]] + values[i]);

            }

        }


        return dp[W];

    }

}
```

### **6. Count coin:**

```
import java.util.Scanner;

class Main{

    public static void main(String args[]){

        Scanner s = new Scanner(System.in);

        int n=s.nextInt();

        int deno[] = new int[n];

        for(int i=0; i<n; i++)

            deno[i]=s.nextInt();

        int amount = s.nextInt();

        int count=0;

        for(int i = deno.length - 1; i >= 0; i--) {

            while(amount >= deno[i]) {

                count+=1;

                amount -= deno[i];

            }

        }

        if(amount==0)
```

```

        System.out.print(count);
    else
        System.out.print(-1);
}
}

```

### **7.Shortest subsequence**

Len of a + len of b – len of subsequence

### **8. Rod cutting**

```

public class Main {

    // Function to calculate the maximum revenue for a rod of length n
    public static int rodCutting(int[] prices, int n) {
        int[] dp = new int[n + 1];

        // Fill the dp array with the maximum revenue for each rod length
        for (int i = 1; i <= n; i++) {
            int maxRevenue = prices[i - 1]; // Case when no cut is made, use price of full rod
            for (int j = 1; j < i; j++) {
                maxRevenue = Math.max(maxRevenue, dp[j] + dp[i - j]);
            }
            dp[i] = maxRevenue;
        }

        // The maximum revenue for a rod of length n is stored in dp[n]
        return dp[n];
    }

    public static void main(String[] args) {
        int[] prices = {1, 5, 8, 9}; // Prices for lengths 1 to 8
        int n = 4; // Length of the rod
        System.out.println("Maximum Revenue: " + rodCutting(prices, n));
    }
}

```