

Experiment No. 1.9

Student Name: Parvinder Singh

UID: 22MCC20043

Branch: MCA - CCD

Section/Group: 22MCD-1/ Grp B

Semester: III

Subject Name: DevOps Process Automation Lab

Subject Code: 22CAP-745

1. Aim/Overview of the practical:

- Create Manifest file in Puppet Server to install http
- Check it in Puppet Agent machine to start the services of http

2. Code for experiment/practical:

A. Create Manifest file in Puppet Server to install http

- Once Puppet-Master and Puppet-Slave connection is configured, Go to Puppet-Master machine.
- Create a manifest file site.pp
sudo nano /etc/puppet/code/environments/production/manifests/site.pp

```
class webserver{
  package { 'apache2':
    ensure => 'installed',
  }

  service { 'apache2':
    ensure => 'running',
    enable => true,
    require => Package['apache2'],
  }
}
```

Save it. Ctrl+O, then Enter, then Ctrl+X.

- Then check the file by opening it.
sudo nano /etc/puppet/code/environments/production/manifests/site.pp
- Manifest file is created successfully
- Now restart the puppet-master services.
sudo systemctl restart puppet-master


```
root@ip-172-31-12-227: ~  
root@ip-172-31-12-227:~# sudo nano /etc/puppet/code/environments/production/manifests/site.pp  
root@ip-172-31-12-227:~# sudo cat /etc/puppet/code/environments/production/manifests/site.pp  
class webserver {  
  package { 'apache2':  
    ensure => 'installed',  
  }  
  
  service { 'apache2':  
    ensure => 'running',  
    enable => true,  
    require => Package['apache2'],  
  }  
}  
root@ip-172-31-12-227:~# sudo systemctl restart puppet-master
```

B. Check it in Puppet Agent machine to start the services of http

- After creating the manifest file on Puppet-Master machine, Now go to Puppet-Slave machine for start services of http manifest file.
- Run # sudo puppet agent --test

```
root@ip-172-31-0-192: /tmp  
root@ip-172-31-0-192:~# cd /tmp  
root@ip-172-31-0-192:/tmp# sudo puppet agent --test  
Info: Using configured environment 'production'  
Info: Retrieving pluginfacts  
Info: Retrieving locales  
Info: Caching catalog for ip-172-31-0-192.ap-south-1.compute.internal  
Info: Applying configuration version '1699622790'  
/usr/lib/ruby/vendor_ruby/puppet/file_system/uniquefile.rb:126: warning: $SAFE will become a normal global variable in Ruby 3.0  
/usr/lib/ruby/vendor_ruby/puppet/file_system/uniquefile.rb:126: warning: $SAFE will become a normal global variable in Ruby 3.0  
Notice: Applied catalog in 0.01 seconds  
/usr/lib/ruby/vendor_ruby/puppet/file_system/uniquefile.rb:126: warning: $SAFE will become a normal global variable in Ruby 3.0  
/usr/lib/ruby/vendor_ruby/puppet/util.rb:461: warning: URI.escape is obsolete  
/usr/lib/ruby/vendor_ruby/puppet/file_system/uniquefile.rb:126: warning: $SAFE will become a normal global variable in Ruby 3.0
```

- Now to any web browser and type the ipv4 public address of your Puppet-Slave machine (in my case it is 62.0.32.34)



- Manifest file services are configured and started successfully.