

## **Group A : Lab Assignment No. 6**

**Title : Write a PL/SQL block of code using parameterized cursor that will merge the data available in newly created table N\_RollCall with the data available in the O\_RollCall. If the data in the first table already exists in the second table then that data should be skipped.**

```
mysql> use mysql;
```

Reading table information for completion of table and column names

You can turn off this feature to get a quicker startup with -A

Database changed

```
mysql> create table o_rollcall(roll_no int,name varchar(20),address varchar(20));
```

Query OK, 0 rows affected (0.28 sec)

```
mysql> create table n_rollcall(roll_no int,namevarchar(20),address varchar(20));
```

Query OK, 0 rows affected (0.27 sec)

```
mysql> insert into o_rollcall values('1','Hitesh','Nandura'); Query OK, 1 row affected (0.05 sec)
```

```
mysql> insert into o_rollcall values('2','Piyush','MP');
```

Query OK, 1 row affected (0.06 sec)

```
mysql> insert into o_rollcall values('3','Ashley','Nsk');
```

Query OK, 1 row affected (0.05 sec)

```
mysql> insert into o_rollcall values('4','Kalpesh','Dhule');
```

Query OK, 1 row affected (0.05 sec)

```
mysql> insert into o_rollcall values('5','Abhi','Satara');
```

Query OK, 1 row affected (0.04 sec)

```
mysql> delimiter //
```

```
mysql> create procedure p3(in r1 int)
-> begin
-> declare r2 int;
-> declare exit_loop boolean;
-> declare c1 cursor for select roll_no from o_rollcall
where roll_no>r1;
-> declare continue handler for not found set
exit_loop=true;
-> open c1;
-> e_loop:loop
-> fetch c1 into r2;
-> if not exists(select * from n_rollcall whereroll_no=r2)
-> then
-> insert into n_rollcall select * from o_rollcall where
roll_no=r2;
-> end if;
-> if exit_loop
-> then
-> close c1;
-> leave e_loop;
-> end if;
-> end loop e_loop;-> end
-> //
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> call p3(3);
```

```
-> //
```

Query OK, 0 rows affected (0.10 sec)

```
mysql> select * from n_rollcall;
```

```
-> //
```

```
+ _____ + _____ + _____ +
```

```

| roll_no | name
| address |
+-----+-----+-----+
| 4 | Kalpesh | Dhule |
| 5 | Abhi | Satara
+-----+-----+-----+
2 rows in set (0.00 sec)

```

```

mysql> call p3(0);
-> //

```

Query OK, 0 rows affected (0.22 sec)

```

mysql> select * from n_rollcall;
-> //

```

```

+-----+-----+-----+
| roll_no | name
| address |
+-----+-----+-----+
| 4 | Kalpesh | Dhule |
| 5 | Abhi | Satara |
| 1 | Hitesh | Nandura |
| 2 | Piyush | MP |
| 3 | Ashley | Nsk | +-----+-----+-----+
5 rows in set (0.00 sec)

```

```

mysql> insert into o_rollcall values('6','Patil','Kolhapur');
-> //

```

Query OK, 1 row affected (0.04 sec)

```

mysql> call p3(4);
-> //

```

Query OK, 0 rows affected (0.05 sec)

```

mysql> select * from n_rollcall;
-> //

```

```

+-----+-----+-----+
| roll_no | name
| address
|

```

```
+-----+-----+-----+
| 4 | Kalpesh | Dhule |
| 5 | Abhi | Satara |
| 1 | Hitesh | Nandura |
| 2 | Piyush | MP |
| 3 | Ashley | Nsk |
| 6 | Patil | Kolhapur |
+-----+-----+-----+
6 rows in set (0.00 sec)
mysql>
```