

Experiment-9

Student Name: Gauri Prabhakar

UID: 18BCS6201

Branch: 18AITAIML-2

Section/Group: B

Semester: 7

Date of Performance: 17th November, 2021

Subject Name: Advanced Database Management Lab

Subject Code: CSP - 434

1. Aim/Overview of the practical:

To implement a Case Study explaining the need for converting tables to fourth and fifth Normal forms.

2. Task to be done:

To implement a Case Study explaining the need for converting tables to fourth and fifth Normal forms.

3. What is 4NF and 5NF?

A table is said to be in 4NF iff:

- It is in BCNF.
- It is independent of many to one relationships and multi-valued attributes.

A table is said to be in 5NF iff:

- It is in 4NF.
- It is independent of any join dependency.
- It is broken into as many tables as possible.

4. Why 4NF?

- 4NF helps reduce redundancy.
- Helps avoid contradiction.

5. Why 5NF?

- 5NF helps reduce redundancy.
- Helps avoid update anomalies.


6. Steps to be followed:

4NF:

Creating a table CANDIDATE which does not follow 4NF norms and then returning it, then creating another table CAND_OCC to eliminate multi-valued attributes:

```
1. CREATE TABLE CANDIDATE(Adhaar int, Occupation varchar(50), Specialization varchar(50));
INSERT INTO CANDIDATE VALUES( 1001, 'Student', 'AIML');
INSERT INTO CANDIDATE VALUES( 1001, 'Teacher', 'IOT');
INSERT INTO CANDIDATE VALUES( 1002, 'Engineer', 'AIML');
INSERT INTO CANDIDATE VALUES( 1002, 'Trainee', 'IOT');
SELECT * FROM CANDIDATE;
```

```
CREATE TABLE CAND_OCC(Adhaar int, Occupation varchar(50));
INSERT INTO CAND_OCC(Adhaar, Occupation) SELECT DISTINCT Adhaar, Occupation FROM
CANDIDATE;
```



```
Run SQL Command Line
SQL> CREATE TABLE CANDIDATE(Adhaar int, Occupation varchar(50), Specialization varchar(50));
Table created.
SQL> INSERT INTO CANDIDATE VALUES( 1001, 'Student', 'AIML');
1 row created.
SQL> INSERT INTO CANDIDATE VALUES( 1001, 'Teacher', 'IOT');
1 row created.
SQL> INSERT INTO CANDIDATE VALUES( 1002, 'Engineer', 'AIML');
1 row created.
SQL> INSERT INTO CANDIDATE VALUES( 1002, 'Trainee', 'IOT');
1 row created.
SQL> SELECT * FROM CANDIDATE;
  ADHAAR OCCUPATION
-----
SPECIALIZATION
-----
1001 Student
AIML
1001 Teacher
IOT
1002 Engineer
AIML
  ADHAAR OCCUPATION
-----
SPECIALIZATION
-----
1002 Trainee
IOT

SQL> CREATE TABLE CAND_OCC(Adhaar int, Occupation varchar(50));
Table created.
SQL> INSERT INTO CAND_OCC(Adhaar, Occupation) SELECT DISTINCT Adhaar, Occupation FROM CANDIDATE;
```

Creating another table CAND_SPEC to eliminate multi-valued attributes then returning both the tables:

2. CREATE TABLE CAND_SPEC(Adhaar int, Specialization varchar(50));

INSERT INTO CAND_SPEC(Adhaar, Specialization) SELECT DISTINCT Adhaar, Specialization FROM CANDIDATE;

SELECT * FROM CAND_OCC;

SELECT * FROM CAND_SPEC;

```
Run SQL Command Line
ATML

ADHAAR OCCUPATION
-----
SPECIALIZATION
-----
1002 Trainee
IOT

SQL> CREATE TABLE CAND_OCC(Adhaar int, Occupation varchar(50));
Table created.

SQL> INSERT INTO CAND_OCC(Adhaar, Occupation) SELECT DISTINCT Adhaar, Occupation FROM CANDIDATE;
4 rows created.

SQL> CREATE TABLE CAND_SPEC(Adhaar int, Specialization varchar(50));
Table created.

SQL> INSERT INTO CAND_SPEC(Adhaar, Specialization) SELECT DISTINCT Adhaar, Specialization FROM CANDIDATE;
4 rows created.

SQL> SELECT * FROM CAND_OCC;

ADHAAR OCCUPATION
-----
1002 Trainee
1001 Student
1001 Teacher
1002 Engineer

SQL> SELECT * FROM CAND_SPEC;

ADHAAR SPECIALIZATION
-----
1001 ATML
1001 IOT
1002 IOT
1002 ATML

SQL> _
```

Output:

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

ORACLE Application Express

Welcome GAURIPS (Logout)

Home Application Builder SQL Workshop Team Development Administration

Home > SQL Workshop > SQL Commands

Schema GAURIPS

Autocommit Rows 10 Save Run

```
CREATE TABLE CANDIDATE(Adhaac int, Occupation varchar(50), Specialization varchar(50));
INSERT INTO CANDIDATE VALUES( 1001, 'Student', 'AIML');
INSERT INTO CANDIDATE VALUES( 1001, 'Teacher', 'IOT');
INSERT INTO CANDIDATE VALUES( 1002, 'Engineer', 'AIML');
INSERT INTO CANDIDATE VALUES( 1002, 'Trainee', 'IOT');
SELECT * FROM CANDIDATE;

CREATE TABLE CAND_OCC(Adhaac int, Occupation varchar(50));
INSERT INTO CAND_OCC(Adhaac, Occupation) SELECT DISTINCT Adhaac, Occupation FROM CANDIDATE;

CREATE TABLE CAND_SPEC(Adhaac int, Specialization varchar(50));
INSERT INTO CAND_SPEC(Adhaac, Specialization) SELECT DISTINCT Adhaac, Specialization FROM CANDIDATE;

SELECT * FROM CAND_OCC;
SELECT * FROM CAND_SPEC;
```

Results Explain Describe Saved SQL History

| ADHAAR | OCCUPATION | SPECIALIZATION |
|--------|------------|----------------|
| 1001 | Student | AIML |
| 1001 | Teacher | IOT |
| 1002 | Engineer | AIML |
| 1002 | Trainee | IOT |

4 rows returned in 0.01 seconds Download

Application Express 4.0.2.00.09

Workspace: GAURIPS User: GAURIPS

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

ENG IN 08:45 PM 21-11-2021

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

ORACLE Application Express

Welcome GAURIPS (Logout)

Home Application Builder SQL Workshop Team Development Administration

Home > SQL Workshop > SQL Commands

Schema GAURIPS

Autocommit Rows 10 Save Run

```
CREATE TABLE CANDIDATE(Adhaac int, Occupation varchar(50), Specialization varchar(50));
INSERT INTO CANDIDATE VALUES( 1001, 'Student', 'AIML');
INSERT INTO CANDIDATE VALUES( 1001, 'Teacher', 'IOT');
INSERT INTO CANDIDATE VALUES( 1002, 'Engineer', 'AIML');
INSERT INTO CANDIDATE VALUES( 1002, 'Trainee', 'IOT');
SELECT * FROM CANDIDATE;

CREATE TABLE CAND_OCC(Adhaac int, Occupation varchar(50));
INSERT INTO CAND_OCC(Adhaac, Occupation) SELECT DISTINCT Adhaac, Occupation FROM CANDIDATE;

CREATE TABLE CAND_SPEC(Adhaac int, Specialization varchar(50));
INSERT INTO CAND_SPEC(Adhaac, Specialization) SELECT DISTINCT Adhaac, Specialization FROM CANDIDATE;

SELECT * FROM CAND_OCC;
SELECT * FROM CAND_SPEC;
```

Results Explain Describe Saved SQL History

| ADHAAR | OCCUPATION |
|--------|------------|
| 1002 | Trainee |
| 1001 | Student |
| 1001 | Teacher |
| 1002 | Engineer |

4 rows returned in 0.00 seconds Download

Application Express 4.0.2.00.09

Workspace: GAURIPS User: GAURIPS

Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

ENG IN 08:45 PM 21-11-2021

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

Apps Google TSE DSA Major Project Sem-7 Web Dev Library Genesis Gauri Prabhakar Acer Songs Nostalgic NLP COIL Documents SPARK AR Other bookmarks

ORACLE Application Express Welcome GAURIPS (Logout)

Home Application Builder SQL Workshop Team Development Administration

Home > SQL Workshop > SQL Commands Schema: GAURIPS Help

☒ Autocommit Rows: 10 Save Run

```
CREATE TABLE CANDIDATE(Adhaar int, Occupation varchar(50), Specialization varchar(50));
INSERT INTO CANDIDATE VALUES( 1001, 'Student', 'AIIML');
INSERT INTO CANDIDATE VALUES( 1001, 'Teacher', 'IOT');
INSERT INTO CANDIDATE VALUES( 1002, 'Engineer', 'AIIML');
INSERT INTO CANDIDATE VALUES( 1002, 'Trainee', 'IOT');
SELECT * FROM CANDIDATE;

CREATE TABLE CAND_OCC(Adhaar int, Occupation varchar(50));
INSERT INTO CAND_OCC(Adhaar, Occupation) SELECT DISTINCT Adhaar, Occupation FROM CANDIDATE;

CREATE TABLE CAND_SPEC(Adhaar int, Specialization varchar(50));
INSERT INTO CAND_SPEC(Adhaar, Specialization) SELECT DISTINCT Adhaar, Specialization FROM CANDIDATE;

SELECT * FROM CAND_OCC;
SELECT * FROM CAND_SPEC;
```

Results Explain Describe Saved SQL History

| ADHAAR | SPECIALIZATION |
|--------|----------------|
| 1001 | AIIML |
| 1001 | IOT |
| 1002 | IOT |
| 1002 | AIIML |

4 rows returned in 0.01 seconds Download

Workspace: GAURIPS User: GAURIPS Application Express 4.0.2.00.09 Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.


ENG IN 08:46 PM 21-11-2021

Now the table is in 4NF.

5NF:

Creating table SEMESTER which does not follow 5NF and then returning it:

```
3. CREATE TABLE SEMESTER(Subject varchar(50), Lecturer varchar(50), Semester int);
INSERT INTO SEMESTER VALUES('AIML', 'Chandler', 1);
INSERT INTO SEMESTER VALUES('AIML', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Monica', 2);
INSERT INTO SEMESTER VALUES('CLOUD', 'Rachel', 1);
SELECT * FROM SEMESTER;
```



The screenshot shows a 'Run SQL Command Line' window with the following SQL commands and their outputs:

```
SQL> CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
Table created.
SQL> INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;
4 rows created.
SQL> CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
Table created.
SQL> INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;
5 rows created.
SQL> CREATE TABLE SEM_LEC(Semester int , Lecturer varchar(50));
Table created.
SQL> INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;
4 rows created.
SQL> SELECT * FROM SEM_SUB;
SEMESTER SUBJECT
-----
1 AIML
1 IOT
2 IOT
1 CLOUD
SQL> SELECT * FROM SUB_LEC;
SUBJECT
-----
LECTURER
-----
IOT
Monica
CLOUD
Rachel
IOT
Ross
```


Creating 3 tables, SEM_SUB, SUB_LEC and SEM_LEC to convert the above table to 5NF and then returning them:

```
4. CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
   INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;

CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;

CREATE TABLE SEM_LEC(Semester int , Lecturer varchar(50));
INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;

SELECT * FROM SEM_SUB;
SELECT * FROM SUB_LEC;
SELECT * FROM SEM_LEC;
```



```
Run SQL Command Line
SQL> CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
Table created.
SQL> INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;
4 rows created.
SQL> CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
Table created.
SQL> INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;
5 rows created.
SQL> CREATE TABLE SEM_LEC(Semester int , Lecturer varchar(50));
Table created.
SQL> INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;
4 rows created.
SQL> SELECT * FROM SEM_SUB;
SEMESTER SUBJECT
-----
1 AIHL
1 IOT
2 IOT
1 CLOUD
SQL> SELECT * FROM SUB_LEC;
SUBJECT
-----
LECTURER
-----
IOT
Monica
CLOUD
Rachel
IOT
Ross
```


Output:

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

AppsGoogle TSEDSAMajor Project Sem-7Web DevLibrary GenesisGauri PrabhakarAcerSongs NostalgicNLP.COILDDocumentsSPARK AR

HomeApplication BuilderSQL WorkshopTeam DevelopmentAdministration

HomeSQL WorkshopSQL CommandsSchemaGAURIPS

☒ AutocommitRows10SaveRun

```
CREATE TABLE SEMESTER(Subject varchar(50), Lecturer varchar(50), Semester int);
INSERT INTO SEMESTER VALUES('AIML', 'Chandler', 1);
INSERT INTO SEMESTER VALUES('AIML', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Monica', 2);
INSERT INTO SEMESTER VALUES('CLOUD', 'Rachel', 1);
SELECT * FROM SEMESTER;

CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;

CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;

CREATE TABLE SEM_LEC(Semester int , Lecturer varchar(50));
INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;

SELECT * FROM SEM_SUB;
SELECT * FROM SUB_LEC;
SELECT * FROM SEM_LEC;
```

Results

ExplainDescribeSaved SQLHistory

| SUBJECT | LECTURER | SEMESTER |
|---------|----------|----------|
| AIML | Chandler | 1 |
| AIML | Ross | 1 |
| IOT | Ross | 1 |
| IOT | Monica | 2 |
| CLOUD | Rachel | 1 |

5 rows returned in 0.00 secondsDownload

Application Express 4.0 2.00.09ENG IN09:43 PM21-11-2021

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

AppsGoogle TSEDSAMajor Project Sem-7Web DevLibrary GenesisGauri PrabhakarAcerSongs NostalgicNLP.COILDDocumentsSPARK AR

HomeApplication BuilderSQL WorkshopTeam DevelopmentAdministration

HomeSQL WorkshopSQL CommandsSchemaGAURIPS

☒ AutocommitRows10SaveRun

```
CREATE TABLE SEMESTER(Subject varchar(50), Lecturer varchar(50), Semester int);
INSERT INTO SEMESTER VALUES('AIML', 'Chandler', 1);
INSERT INTO SEMESTER VALUES('AIML', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Monica', 2);
INSERT INTO SEMESTER VALUES('CLOUD', 'Rachel', 1);
SELECT * FROM SEMESTER;

CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;

CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;

CREATE TABLE SEM_LEC(Semester int , Lecturer varchar(50));
INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;

SELECT * FROM SEM_SUB;
SELECT * FROM SUB_LEC;
SELECT * FROM SEM_LEC;
```

Results

ExplainDescribeSaved SQLHistory

| SUBJECT | LECTURER | SEMESTER |
|---------|----------|----------|
| AIML | Chandler | 1 |
| AIML | Ross | 1 |
| IOT | Ross | 1 |
| IOT | Monica | 2 |
| CLOUD | Rachel | 1 |

5 rows returned in 0.00 secondsDownload

Application Express 4.0 2.00.09ENG IN09:43 PM21-11-2021

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

Home Application Builder SQL Workshop Team Development Administration

Home > SQL Workshop > SQL Commands

Schema GAURIPS

Autocommit Rows 10 Save Run

```
CREATE TABLE SEMESTER(Subject varchar(50), Lecturer varchar(50), Semester int);
INSERT INTO SEMESTER VALUES('AIML', 'Chandler', 1);
INSERT INTO SEMESTER VALUES('AIML', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Monica', 2);
INSERT INTO SEMESTER VALUES('CLOUD', 'Rachel', 1);
SELECT * FROM SEMESTER;

CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;

CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;

CREATE TABLE SEM_LEC(Semester int, Lecturer varchar(50));
INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;

SELECT * FROM SEM_SUB;
SELECT * FROM SUB_LEC;
SELECT * FROM SEM_LEC;
```

Results Explain Describe Saved SQL History

| SUBJECT | LECTURER |
|---------|----------|
| IOT | Monica |
| CLOUD | Rachel |
| IOT | Ross |
| AIML | Chandler |
| AIML | Ross |

5 rows returned in 0.00 seconds Download

Application Express 4.0.2.00.09

SQL Commands

127.0.0.1:8080/apex/?p=4500:1003:858317820172079:NO::

Home Application Builder SQL Workshop Team Development Administration

Home > SQL Workshop > SQL Commands

Schema GAURIPS

Autocommit Rows 10 Save Run

```
CREATE TABLE SEMESTER(Subject varchar(50), Lecturer varchar(50), Semester int);
INSERT INTO SEMESTER VALUES('AIML', 'Chandler', 1);
INSERT INTO SEMESTER VALUES('AIML', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Ross', 1);
INSERT INTO SEMESTER VALUES('IOT', 'Monica', 2);
INSERT INTO SEMESTER VALUES('CLOUD', 'Rachel', 1);
SELECT * FROM SEMESTER;

CREATE TABLE SEM_SUB(Semester int, Subject varchar(50));
INSERT INTO SEM_SUB(Semester, Subject) SELECT DISTINCT Semester, Subject FROM SEMESTER;

CREATE TABLE SUB_LEC(Subject varchar(50), Lecturer varchar(50));
INSERT INTO SUB_LEC(Subject, Lecturer) SELECT DISTINCT Subject, Lecturer FROM SEMESTER;

CREATE TABLE SEM_LEC(Semester int, Lecturer varchar(50));
INSERT INTO SEM_LEC(Semester, Lecturer) SELECT DISTINCT Semester, Lecturer FROM SEMESTER;

SELECT * FROM SEM_SUB;
SELECT * FROM SUB_LEC;
SELECT * FROM SEM_LEC;
```

Results Explain Describe Saved SQL History

| SEMESTER | LECTURER |
|----------|----------|
| 1 | Rachel |
| 1 | Chandler |
| 1 | Ross |
| 2 | Monica |

4 rows returned in 0.00 seconds Download

Application Express 4.0.2.00.09

Workspace: GAURIPS User: GAURIPS Language: en | Copyright © 1999, 2010, Oracle. All rights reserved.

Now the table is in 5NF.

7. Result/Output/Writing Summary:

- Successfully implemented table conversion to 4NF.
- Successfully implemented table conversion to 5NF.
- Successfully implemented operations for NORMALIZATION.
- Successfully understood the functioning and importance of the above mentioned.

8. Learning outcomes (What I have learnt):

- How to implement table conversion to 4NF on SQL Command Line.
- How to implement table conversion to 5NF on SQL Command Line.
- How to implement NORMALIZATION on a table.

Evaluation Grid (To be created as per the SOP and Assessment guidelines by the faculty):

| Sr. No. | Parameters | Marks Obtained | Maximum Marks |
|---------|------------|----------------|---------------|
| 1. | | | |
| 2. | | | |
| 3. | | | |