

Embedded SQL

1.

```
import mysql.connector
db= mysql.connector.connect( host= "localhost", user= "root", passwd="1A2b1111*",
database= "oneshop_store")
mycursor= db.cursor()

# Query to get pincode from where more than 10 orders are placed
mycursor.execute("select * from orders")
order= mycursor.fetchall()

mycursor.execute("select add_pincode from warehouse")
no_of_warehouse= len(mycursor.fetchall())

mycursor.execute("select uid, add_pincode from customer")
customers= mycursor.fetchall()

no_of_orders=[0 for _ in range (no_of_warehouse)]

for i in order :
    user_id= int (i[1])
    pin= customers[user_id][1]
    no_of_orders[pin-100001]+=1

print("Pincode ", "no of orders")
for i in range(len(no_of_orders)):
    if no_of_orders[i]>10:
        print(f'{100001+i} {no_of_orders[i]}')
```

2.

```
import mysql.connector
db= mysql.connector.connect(host= "localhost", user= "root", passwd= "1A2b1111*",
database= "oneshop_store")
mycursor= db.cursor()
mycursor.execute("""select w.add_pincode, COUNT(*) as
    Number_Of_Employees
    from warehouse as w, employee as e
    where (w.capacity>=5000) AND (w.add_pincode= e.add_pincode)
    group by w.add_pincode;

""")
ware= mycursor.fetchall()
min= 0
for i in range(len(ware)) :
    if ware[i][1]< ware[min][1]:
        min= i
print("Pincode of warehouse      No of Employees")
print(f'{ware[min][0]}           {ware[min][1]} ')

mycursor.execute("""update employee
    insert into employee
(eid,first_name,last_name,contact,mail_id,address,dob,designation,gender,add_pincode
)
    values(1001, Brock, NN, 8292918282, nbrock@gmail.com,  scholars street
110032,2008-12-16, Sales, Male, min+100001)
""")

mycursor.execute("""select w.add_pincode, COUNT(*) as
    Number_Of_Employees
    from warehouse as w, employee as e
    where (w.capacity>=5000) AND (w.add_pincode= e.add_pincode)
    group by w.add_pincode;

""")
ware= mycursor.fetchall()
print("Pincode of warehouse      No of Employees")
print(f'{ware[min][0]}           {ware[min][1]} ')
```