

# Assignment 3 (ML for TS) - MVA 2023/2024

Gauthier Multari [gauthier.multari@ens-paris-saclay.fr](mailto:gauthier.multari@ens-paris-saclay.fr)

January 22, 2024

## 1 Introduction

**Objective.** The goal is to implement (i) a signal processing pipeline with a change-point detection method and (ii) wavelets for graph signals.

### Warning and advice.

- Use code from the tutorials as well as from other sources. Do not code yourself well-known procedures (e.g. cross validation or k-means), use an existing implementation.
- The associated notebook contains some hints and several helper functions.
- Be concise. Answers are not expected to be longer than a few sentences (omitting calculations).

### Instructions.

- Fill in your names and emails at the top of the document.
- Hand in your report (one per pair of students) by Sunday 31<sup>st</sup> December 11:59 PM.
- Rename your report and notebook as follows:  
FirstnameLastname1\_FirstnameLastname1.pdf and  
FirstnameLastname2\_FirstnameLastname2.ipynb.  
For instance, LaurentOudre\_CharlesTruong.pdf.
- Upload your report (PDF file) and notebook (IPYNB file) using this link:  
[docs.google.com/forms/d/e/1FAIpQLScqLsYuKeQbsDEOie5OqpOH7YwCnWmudzApMC005HvxOaOv](https://docs.google.com/forms/d/e/1FAIpQLScqLsYuKeQbsDEOie5OqpOH7YwCnWmudzApMC005HvxOaOv)

## 2 Dual-tone multi-frequency signaling (DTMF)

Dual-tone multi-frequency signaling is a procedure to encode symbols using an audio signal. The possible symbols are 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, \*, #, A, B, C, and D. A symbol is represented by a sum of cosine waves: for  $t = 0, 1, \dots, T - 1$ ,

$$y_t = \cos(2\pi f_1 t / f_s) + \cos(2\pi f_2 t / f_s)$$

where each combination of  $(f_1, f_2)$  represents a symbols. The first frequency has four different levels (low frequencies), and the second frequency has four other levels (high frequencies); there are 16 possible combinations. In the notebook, you can find an example symbol sequence encoded with sound and corrupted by noise (white noise and a distorted sound).

### Question 1

Design a procedure that takes a sound signal as input and outputs the sequence of symbols. To that end, you can use the provided training set. The signals have a varying number of symbols with a varying duration. There is a brief silence between each symbol.

Describe in 5 to 10 lines your methodology and the calibration procedure (give the hyperparameter values). Hint: use the time-frequency representation of the signals, apply a change-point detection algorithm to find the starts and ends of the symbols and silences, and then classify each segment.

### Answer 1

We first split the training dataset in order to use 70% of the data for the training and 30% for the validation. The validation dataset is used to test the various hyperparameters combinations. The methodology used is the following. The algorithm used for the change point detection is the Linearly penalized segmentation provided in the Ruptures package. We first compute the spectrogram of the signal then we use the algorithm with a penalty of  $= 9 \cdot 10^{-4} \sigma^2 \log N$ , with  $\sigma = 2$ . To improve the results, the fit is post-processed. In each segment the two most common frequencies are selected, if they are not too distant in terms of frequency the two segments are merged. Finally we remove the segments with a low energy. The hyperparameters values that gave the best accuracy on the validation dataset (87.93%) are the following. **nperseg (512)**: Length of the segments used in the spectrogram. **noverlap (128)**: Number of points overlapping between segments. **min\_energy (0.11)**: The threshold below which a segment is filtered out.

### Question 2

What are the two symbolic sequences encoded in the test set?

### Answer 2

- Sequence 1: 7 2 1 C 9 9
- Sequence 2: 1 # 2 #

### 3 Wavelet transform for graph signals

Let  $G$  be a graph defined a set of  $n$  nodes  $V$  and a set of edges  $E$ . A specific node is denoted by  $v$  and a specific edge, by  $e$ . The eigenvalues and eigenvectors of the graph Laplacian  $L$  are  $\lambda_1 \leq \lambda_2 \leq \dots \leq \lambda_n$  and  $u_1, u_2, \dots, u_n$  respectively.

For a signal  $f \in \mathbb{R}^n$ , the Graph Wavelet Transform (GWT) of  $f$  is  $W_f : \{1, \dots, M\} \times V \longrightarrow \mathbb{R}$ :

$$W_f(m, v) := \sum_{l=1}^n \hat{g}_m(\lambda_l) \hat{f}_l u_l(v) \quad (1)$$

where  $\hat{f} = [\hat{f}_1, \dots, \hat{f}_n]$  is the Fourier transform of  $f$  and  $\hat{g}_m$  are  $M$  kernel functions. The number  $M$  of scales is a user-defined parameter and is set to  $M := 9$  in the following. Several designs are available for the  $\hat{g}_m$ ; here, we use the Spectrum Adapted Graph Wavelets (SAGW). Formally, each kernel  $\hat{g}_m$  is such that

$$\hat{g}_m(\lambda) := \hat{g}^U(\lambda - am) \quad (0 \leq \lambda \leq \lambda_n) \quad (2)$$

where  $a := \lambda_n / (M + 1 - R)$ ,

$$\hat{g}^U(\lambda) := \frac{1}{2} \left[ 1 + \cos \left( 2\pi \left( \frac{\lambda}{aR} + \frac{1}{2} \right) \right) \right] \mathbb{1}(-Ra \leq \lambda < 0) \quad (3)$$

and  $R > 0$  is defined by the user.

#### Question 3

Plot the kernel functions  $\hat{g}_m$  for  $R = 1$ ,  $R = 3$  and  $R = 5$  (take  $\lambda_n = 12$ ) on Figure 1. What is the influence of  $R$ ?

#### Answer 3




Figure 1: The SAGW kernels functions

$R$  influences the smoothness of the signal, larger  $R$  highlight large and gradual patterns over the graph.

We will study the Molene data set (the one we used in the last tutorial). The signal is the temperature.

#### **Question 4**

Construct the graph using the distance matrix and exponential smoothing (use the median heuristics for the bandwidth parameter).

- Remove all stations with missing values in the temperature.
- Choose the minimum threshold so that the network is connected and the average degree is at least 3.
- What is the time where the signal is the least smooth?
- What is the time where the signal is the smoothest?

#### **Answer 4**

The stations with missing values are: ARZAL, BATZ, BEG MEIL, BREST-GUIPAVAS, BRIGNOGAN, CAMARET, LANDIVISIAU, LANNAERO, LANVEOC, OUessant-STIFF, PLOUAY-SA, PLOUDALMEZEAU, PLOUGONVELIN, QUIMPER, RIEC SUR BELON, SIZUN, ST NAZAIRE-MONTOIR, VANNES-MEUCONS

The threshold is equal to 0.8318.

The signal is the least smooth at 2014-01-21 06:00:00

The signal is the smoothest at 2014-01-24 19:00:00

## Question 5

(For the remainder, set  $R = 3$  for all wavelet transforms.)

For each node  $v$ , the vector  $[W_f(1, v), W_f(2, v), \dots, W_f(M, v)]$  can be used as a vector of features. We can for instance classify nodes into low / medium / high frequency:

- a node is considered low frequency if the scales  $m \in \{1, 2, 3\}$  contain most of the energy,
- a node is considered medium frequency if the scales  $m \in \{4, 5, 6\}$  contain most of the energy,
- a node is considered high frequency if the scales  $m \in \{6, 7, 9\}$  contain most of the energy.

For both signals from the previous question (smoothest and least smooth) as well as the first available timestamp, apply this procedure and display on the map the result (one colour per class).

## Answer 5




Figure 2: Classification of nodes into low / medium / high frequency

### Question 6

Display the average temperature and for each timestamp, adapt the marker colour to the majority class present in the graph (see notebook for more details).

### Answer 6




Figure 3: Average temperature. Markers' colours depend on the majority class.

### Question 7

The previous graph  $G$  only uses spatial information. To take into account the temporal dynamic, we construct a larger graph  $H$  as follows: a node is now *a station at a particular time* and is connected to neighbouring stations (with respect to  $G$ ) and to itself at the previous timestamp and the following timestamp. Notice that the new spatio-temporal graph  $H$  is the Cartesian product of the spatial graph  $G$  and the temporal graph  $G'$  (which is simply a line graph, without loop).

- Express the Laplacian of  $H$  using the Laplacian of  $G$  and  $G'$  (use Kronecker products).
- Express the eigenvalues and eigenvectors of the Laplacian of  $H$  using the eigenvalues and eigenvectors of the Laplacian of  $G$  and  $G'$ .
- Compute the wavelet transform of the temperature signal.
- Classify nodes into low/medium/high frequency and display the same figure as in the previous question.

### Answer 7



Figure 4: Average temperature. Markers' colours depend on the majority class.