

Multi-Agent Optimization

Tutorial at AAMAS'23

Filippo Bistaffa Gauthier Picard Roie Zivan

Some contents adapted from previous tutorials (<http://https://www2.isye.gatech.edu/~fferdinando3/cfp/AAMAS19/>)



Introduction and Motivations

Who are we?



Filippo Bistaffa, PhD

IIIA-CSIC, Barcelona
Expertises: coalition
formation,
parallel computing, shared
mobility



Gauthier Picard, PhD, Hab.

ONERA, the French
Aerospace Lab
Expertises: DCOPs,
self-organization, resource
allocation



Roie Zivan, PhD

Ben Gurion University of the
Negev
Expertises: DCOPs, partial
cooperation


Introduction and Motivations

Multiagent Systems

- **Agent:** An entity that behaves autonomously in the pursuit of goals
- **Multi-agent system:** A system of multiple interacting agents

An agent is...

- **Autonomous:** Is of full control of itself
- **Interactive:** May communicate with other agents
- **Reactive:** Responds to changes in the environment or requests by other agents
- **Proactive:** Takes initiatives to achieve its goals



Introduction and Motivations

Research questions addressed during this tutorial



- How to make collective optimal decisions?
 - ▶ How to model the collective decision?
 - ▶ Which protocols to implement these decisions?

- How to form groups *wrt* to some utility criteria?
 - ▶ How to model the utility of each group?
 - ▶ How to express which groups are feasible or not?

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

- Characteristic Function Games

- Coalition Structure Generation

- Induced Subgraph Games

Distributed Constraint Optimization

- Motivating Examples

- Preliminaries

- DCOP Model

- DCOP Algorithms

- Extensions

Real-World Applications

- Shared Mobility

- Collective Energy Purchasing

- Self-configuration of IoT Devices

- Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up



Today's Menu

Coalition Formation on MAS

Characteristic Function Games

Coalition Structure Generation

Induced Subgraph Games

Real-World Applications

Conclusion and Wrap-up

Today's Menu

Coalition Formation on MAS

Characteristic Function Games

Coalition Structure Generation

Induced Subgraph Games

Real-World Applications

Conclusion and Wrap-up



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



$$A = \{ \text{, } \text{, } \text{, } \text{ }\}$$




- $v(\{\text{以人为中心}\}) = 0$
 - $v(\{\text{人}, \text{狗}\}) = -7$
 - $v(\{\text{人}, \text{狗}, \text{猫}\}) = 3$
 - ...



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A

$$A = \{ \text{, } \text{, } \text{img alt="Avatar of a woman with brown hair" data-bbox='530 87 560 104' style="vertical-align: middle; height: 2em;"/>, } \text{img alt="Avatar of a person with glasses and a green shirt" data-bbox='565 87 595 104' style="vertical-align: middle; height: 2em;"/> \}$$

- $v(\{\text{👤, 🧑}\}) = 0$
 - $v(\{\text{👤, 🧑, 🧑}\}) = -7$
 - $v(\{\text{👤, 🧑, 🧑}\}) = 3$
 - ...



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A

$$A = \{ \text{, } \text{, } \text{img alt="Avatar of a person with short brown hair" data-bbox='510 87 535 104' style="vertical-align: middle; height: 2em;"/>, } \text{img alt="Avatar of a person with dark skin and glasses" data-bbox='535 87 560 104' style="vertical-align: middle; height: 2em;"/> \}$$




Characteristic Function $v(\cdot)$

- $v(\{\text{Sunglasses, Girl}\}) = 0$
 - $v(\{\text{Girl, Toy, Boy}\}) = -7$
 - $v(\{\text{Sunglasses, Toy}\}) = 3$
 - ...



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A

$$A = \{ \text{John}, \text{Alice}, \text{Bob}, \text{Charlie} \}$$


Characteristic Function $v(\cdot)$

- $v(\{\text{Alec}, \text{Lena}\}) = 0$
 - $v(\{\text{Alec}, \text{Lena}, \text{Dima}\}) = -7$
 - $v(\{\text{Alec}, \text{Dima}\}) = 3$
 - ...



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A


$$A = \{ \text{}, \text{}, \text{img alt="person with short brown hair"/>}, \text{img alt="person with glasses and green shirt"/>} \}$$

Characteristic Function $v(\cdot)$

- $v(\{\text{👤, 🧑}\}) = 0$
 - $v(\{\text{👤, 🎬, 🧑}\}) = -7$
 - $v(\{\text{👤, 🎬}\}) = 3$
 - ...

Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A

$$A = \{ \text{}, \text{}, \text{img alt="person with short brown hair" data-bbox="510 87 535 103"/>}, \text{img alt="person with glasses" data-bbox="535 87 560 103"/>} \}$$

Characteristic Function $v(\cdot)$

- $v(\{\text{👤, 🧑}\}) = 0$
 - $v(\{\text{👤, 🧑, 🧑}\}) = -7$
 - $v(\{\text{👤, 🧑, 🧑}\}) = 3$
 - ...



Characteristic Function Games (CFGs)

[CHALKIADAKIS et al., 2011]



Set of Agents A

$$A = \{ \text{, } \text{, } \text{img alt="Avatar of a woman with short brown hair" data-bbox='510 78 535 94' style="vertical-align: middle; height: 2em;"/>, } \text{img alt="Avatar of a person with glasses and a yellow shirt" data-bbox='535 78 560 94' style="vertical-align: middle; height: 2em;"/> \}$$



Characteristic Function $v(\cdot)$

- $v(\{\text{Sunglasses, Girl}\}) = 0$
 - $v(\{\text{Girl, Girl, Boy}\}) = -7$
 - $v(\{\text{Sunglasses, Girl, Girl}\}) = 3$
 - ...

Characteristic Function

[CHALKIADAKIS et al., 2011]

Characteristic Function

The function $v : \mathcal{P}(A) \rightarrow \mathbb{R}$ associates a value to *every coalition* (i.e., subset) of A

Exponential Complexity


Representing $v(\cdot)$ as a *table* requires an *exponential* number of steps (i.e., $2^{|A|}$)

Mitigate this Complexity

(1) *Restrict* the set of coalitions or (2) consider $v(\cdot)$ with a specific *structure*

Cardinality-Restricted CFGs

[SHEHORY and KRAUS, 1998]



Maximum Cardinality k


E.g., only coalitions of size ≤ 3 are feasible

Polynomial Number of Coalitions

Total number of coalitions is $\sum_{i=1}^k \binom{|A|}{i} = \mathcal{O}(|A|^k)$,
 i.e., polynomial wrt $|A|$

Cardinality-Restricted CFGs

[SHEHORY and KRAUS, 1998]



Maximum Cardinality k


E.g., only coalitions of size ≤ 3 are feasible

Polynomial Number of Coalitions

Total number of coalitions is $\sum_{i=1}^k \binom{|A|}{i} = \mathcal{O}(|A|^k)$,
 i.e., polynomial wrt $|A|$

Graph-Restricted CFGs

[MYERSON, 1977], [DEMANGE, 2004]



Graph G among Agents


$$G = (\{\text{Beardy, Clown, Girl, Guy}\}, \{(\text{Beardy, Girl}), (\text{Clown, Girl}), (\text{Guy, Girl})\})$$

Connected Subgraphs

A coalition is *feasible* only if it induces a *connected* subgraph of G

Graph-Restricted CFGs

[MYERSON, 1977], [DEMANGE, 2004]



Graph G among Agents

$$G = (\{\text{bearded man}, \text{woman with blue hair}, \text{woman with brown hair}, \text{man with green hair}\}, \{(\text{bearded man}, \text{woman with brown hair}), (\text{woman with blue hair}, \text{woman with brown hair}), (\text{woman with brown hair}, \text{man with green hair})\})$$

Connected Subgraphs

A coalition is *feasible* only if it induces a *connected* subgraph of G

Real-World Example: Social Ridesharing

[BISTAFFA et al., 2017b]

Social Ridesharing


Arrange *cost-effective* shared cars among agents connected by a *social network*


Cardinality-Based Constraints

Cars (i.e., coalitions) can contain *up to 5 passengers*

Graph-Based Constraints

We only form coalitions among “*friends of friends*” (connected subgraph)





Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Characteristic Function Games

Coalition Structure Generation

Induced Subgraph Games

Distributed Constraint Optimization

Real-World Applications

Conclusion and Wrap-up

Coalition Structure Generation (CSG)

[RAHWAN et al., 2015]




Solving the Coalition Structure Generation (CSG) Problem

Compute the partition \mathcal{S} of A into *feasible* coalitions that *maximizes* the sum $\sum_{S \in \mathcal{S}} v(S)$

Coalition Structure Generation (CSG)

[RAHWAN et al., 2015]




Solving the Coalition Structure Generation (CSG) Problem

Compute the partition S of A into *feasible* coalitions that *maximizes* the sum $\sum_{S \in S} v(S)$

Graph-Restricted Coalition Structure Generation (CSG)

[RAHWAN et al., 2015]




Solving the Coalition Structure Generation (CSG) Problem

Compute the partition \mathcal{S} of A into *feasible* coalitions that *maximizes* the sum $\sum_{S \in \mathcal{S}} v(S)$

Graph-Restricted Coalition Structure Generation (CSG)

[RAHWAN et al., 2015]




Solving the Coalition Structure Generation (CSG) Problem

Compute the partition \mathcal{S} of A into *feasible* coalitions that *maximizes* the sum $\sum_{S \in \mathcal{S}} v(S)$

Graph-Restricted Coalition Structure Generation (CSG)

[RAHWAN et al., 2015]




Solving the Coalition Structure Generation (CSG) Problem

Compute the partition \mathcal{S} of A into *feasible* coalitions that *maximizes* the sum $\sum_{S \in \mathcal{S}} v(S)$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$

CSG Approaches based on Search

[BISTAFFA et al., 2017a]




Edge Contraction Operation

Contraction of edge $(S_i, S_j) \rightarrow$ form coalition $S_i \cup S_j$


CSG Approaches based on Search

[BISTAFFA et al., 2017a]




CSG Approaches based on Search

[BISTAFFA et al., 2017a]




CSG Approaches based on Search

[BISTAFFA et al., 2017a]




CSG Approaches based on Search

[BISTAFFA et al., 2017a]




CSG Approaches based on Search

[BISTAFFA et al., 2017a]



CSG Approaches based on Search


[BISTAFFA et al., 2017a]





CSG Approaches based on Search


[BISTAFFA et al., 2017a]






CSG Approaches based on Search

[BISTAFFA et al., 2017a]




CSG Approaches based on Search

[BISTAFFA et al., 2017a]



CSG Approaches based on Search

[BISTAFFA et al., 2017a]



CSG Approaches based on Search

[BISTAFFA et al., 2017a]

CFSS Algorithm

- Builds a *Binary Decision Diagram* (BDD) by **contracting** (or **not**) an edge at each step
- Each coalition structure (i.e., partition of A) is represented *only once* in the BDD
- The optimal coalition structure is computed by doing a *depth-first* traversal of the BDD

Pros

Approximate algorithm with quality guarantees if used in conjunction with *Branch-and-Bound*

Cons

Performance depends on the assumption that $v(\cdot)$ can be expressed in *closed-form*

CSG Approaches based on Search

[BISTAFFA et al., 2017a]

CFSS Algorithm

- Builds a *Binary Decision Diagram* (BDD) by **contracting** (or **not**) an edge at each step
- Each coalition structure (i.e., partition of A) is represented *only once* in the BDD
- The optimal coalition structure is computed by doing a *depth-first* traversal of the BDD

Pros

Approximate algorithm with quality guarantees if used in conjunction with *Branch-and-Bound*

Cons

Performance depends on the assumption that $v(\cdot)$ can be expressed in *closed-form*

CSG Approaches based on Search

[BISTAFFA et al., 2017a]

CFSS Algorithm

- Builds a *Binary Decision Diagram* (BDD) by **contracting** (or **not**) an edge at each step
- Each coalition structure (i.e., partition of A) is represented *only once* in the BDD
- The optimal coalition structure is computed by doing a *depth-first* traversal of the BDD

Pros

Approximate algorithm with quality guarantees if used in conjunction with *Branch-and-Bound*

Cons

Performance depends on the assumption that $v(\cdot)$ can be expressed in *closed-form*

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Weighted Knapsack Problem

We want to fill our knapsack (capacity = c) with the goal of maximizing the total value

What is the Optimal Subset of Object for $c = 5$?

- A Pick (weight = 1) → 1
- B Pick (weight = 2) → 4
- C Pick (weight = 4) → 3
- D Pick (weight = 5) → 9
- E Pick (weight = 3) → 6

$$\begin{aligned}w(\text{apple}) &= 1, v(\text{apple}) = 1 \\w(\text{diamond}) &= 2, v(\text{diamond}) = 4 \\w(\text{ring}) &= 4, v(\text{ring}) = 3 \\w(\text{crown}) &= 6, v(\text{crown}) = 1 \\w(\text{laptop}) &= 3, v(\text{laptop}) = 6\end{aligned}$$

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Our Ingredients

- Let x_A, x_B, x_C, x_D, x_E be binary decision variables (either pick the object or not)
- Objective function: maximize the value of selected objects
- Constraint: do not exceed the knapsack capacity

Integer Linear Programming (ILP) Formulation

maximize $1 \cdot x_A + 4 \cdot x_B + 3 \cdot x_C + 9 \cdot x_D + 6 \cdot x_E$ (Values of selected objects)

subject to $1 \cdot x_A + 2 \cdot x_B + 4 \cdot x_C + 5 \cdot x_D + 3 \cdot x_E \leq 5$ (Capacity constraint)

$x_A, x_B, x_C, x_D, x_E \in \{0, 1\}$ (Binary decision variables)

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Our Ingredients

- Let x_A, x_B, x_C, x_D, x_E be binary decision variables (either pick the object or not)
- Objective function: maximize the value of selected objects
- Constraint: do not exceed the knapsack capacity

Integer Linear Programming (ILP) Formulation

maximize $1 \cdot x_A + 4 \cdot x_B + 3 \cdot x_C + 9 \cdot x_D + 6 \cdot x_E$ (Values of selected objects)

subject to $1 \cdot x_A + 2 \cdot x_B + 4 \cdot x_C + 5 \cdot x_D + 3 \cdot x_E \leq 5$ (Capacity constraint)

$x_A, x_B, x_C, x_D, x_E \in \{0, 1\}$ (Binary decision variables)

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Our Ingredients

- Let x_A, x_B, x_C, x_D, x_E be binary decision variables (either pick the object or not)
- Objective function: maximize the value of selected objects
- Constraint: do not exceed the knapsack capacity

Integer Linear Programming (ILP) Formulation

maximize $1 \cdot x_A + 4 \cdot x_B + 3 \cdot x_C + 9 \cdot x_D + 6 \cdot x_E$ (Values of selected objects)

subject to $1 \cdot x_A + 2 \cdot x_B + 4 \cdot x_C + 5 \cdot x_D + 3 \cdot x_E \leq 5$ (Capacity constraint)

$x_A, x_B, x_C, x_D, x_E \in \{0, 1\}$ (Binary decision variables)

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Our Ingredients

- Let x_A, x_B, x_C, x_D, x_E be binary decision variables (either pick the object or not)
- Objective function: maximize the value of selected objects
- Constraint: do not exceed the knapsack capacity

Integer Linear Programming (ILP) Formulation

maximize $1 \cdot x_A + 4 \cdot x_B + 3 \cdot x_C + 9 \cdot x_D + 6 \cdot x_E$ (Values of selected objects)

subject to $1 \cdot x_A + 2 \cdot x_B + 4 \cdot x_C + 5 \cdot x_D + 3 \cdot x_E \leq 5$ (Capacity constraint)

$x_A, x_B, x_C, x_D, x_E \in \{0, 1\}$ (Binary decision variables)

CSG Approaches based on Integer Linear Programming

Background on Integer Linear Programming

Our Ingredients

- Let x_A, x_B, x_C, x_D, x_E be binary decision variables (either pick the object or not)
- Objective function: maximize the value of selected objects
- Constraint: do not exceed the knapsack capacity

Integer Linear Programming (ILP) Formulation

maximize $1 \cdot x_A + 4 \cdot x_B + 3 \cdot x_C + 9 \cdot x_D + 6 \cdot x_E$ (Values of selected objects)

subject to $1 \cdot x_A + 2 \cdot x_B + 4 \cdot x_C + 5 \cdot x_D + 3 \cdot x_E \leq 5$ (Capacity constraint)

$x_A, x_B, x_C, x_D, x_E \in \{0, 1\}$ (Binary decision variables)

CSG Approaches based on Integer Linear Programming

[RAHWAN et al., 2015]

- Given A and a set \mathcal{S} of *coalitions* (i.e., subsets) of A , let M be a $|A| \times |\mathcal{S}|$ matrix
- $M_{iS} = 1$ if and only if agent $a \in A$ is part of coalition $S \in \mathcal{S}$, $M_{iS} = 0$ otherwise

$$M = \begin{bmatrix} 1 & 0 & 0 & 1 & 1 & 0 & 1 \\ 0 & 1 & 0 & 1 & 0 & 1 & 1 \\ 0 & 0 & 1 & 0 & 1 & 1 & 1 \end{bmatrix}$$

CSG Approaches based on Integer Linear Programming

[RAHWAN et al., 2015]

Objective of Coalition Structure Generation

Compute the *partition* of A that *maximizes* the sum of the corresponding values

ILP Formulation for Coalition Structure Generation

$$\text{maximize} \quad \sum_{S \in \mathcal{S}} v(S) \cdot x_S \quad (\text{Value of each selected coalition})$$

$$\text{subject to} \quad \sum_{S \in \mathcal{S}} M_{iS} \cdot x_S = 1 \quad \forall i \in A \quad (\text{Each agent exactly in } \textit{one} \text{ coalition})$$

CSG Approaches based on Integer Linear Programming

[RAHWAN et al., 2015]

Solving Integer Linear Programs

ILPs can be solved with state-of-the-art solvers like CPLEX (very mature technology)

Pros

Does not require any assumption on $v(\cdot)$ (very general approach)

Cons

- Memory requirements can become unmanageable for more than 20–30 agents
- Difficult to directly exploit the structure of the problem (i.e., graph)

CSG Approaches based on Integer Linear Programming

[RAHWAN et al., 2015]

Solving Integer Linear Programs

ILPs can be solved with state-of-the-art solvers like CPLEX (very mature technology)

Pros

Does not require any assumption on $v(\cdot)$ (very general approach)

Cons

- Memory requirements can become unmanageable for more than 20–30 agents
- Difficult to directly exploit the structure of the problem (i.e., graph)

CSG Approaches based on Integer Linear Programming

[RAHWAN et al., 2015]

Solving Integer Linear Programs

ILPs can be solved with state-of-the-art solvers like CPLEX (very mature technology)

Pros

Does not require any assumption on $v(\cdot)$ (very general approach)


Cons

- Memory requirements can become unmanageable for more than 20–30 agents
- Difficult to directly exploit the structure of the problem (i.e., graph)

CSG as a COP

[BISTAFFA and FARINELLI, 2018]

Graph-Restricted CFG Example




Pseudotree among Agents (Hierarchy)

Adjacent agents in the graph fall in the same branch of the tree (e.g., and

CSG as a COP

[BISTAFFA and FARINELLI, 2018]

Graph-Restricted CFG Example



Pseudotree among Agents (Hierarchy)

Adjacent agents in the graph fall in the same branch of the tree (e.g., and

CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required* variables



CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required* variables



CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required* variables



CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required* variables



CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required* variables



CSG as a COP


[BISTAFFA and FARINELLI, 2018]

Challenge

How can we exploit the structure (i.e., hierarchy among agents)?

Main Idea

- Each coalition (i.e., decision variable) is “controlled” by the highest agent
- “Delegate” the formation of coalitions to descendants by means of *required variables*



CSG as a COP

[BISTAFFA and FARINELLI, 2018]

Required Variables

- Any two variables that require the same variable *cannot* be enabled simultaneously
- As a result *no overlapping variables* are activated *at the same time*

Number of Constraints

- Naive COP: $\binom{\text{\# coalitions}}{2}$
- This approach: linear *wrt* the number of agents

Open Question

Can we make this COP a Distributed COP (DCOP)?

CSG as a COP

[BISTAFFA and FARINELLI, 2018]

Required Variables

- Any two variables that require the same variable *cannot* be enabled simultaneously
- As a result *no overlapping variables* are activated *at the same time*

Number of Constraints

- Naive COP: $\binom{\text{\# coalitions}}{2}$
- This approach: linear *wrt* the number of agents

Open Question

Can we make this COP a Distributed COP (DCOP)?

CSG as a COP

[BISTAFFA and FARINELLI, 2018]

Required Variables

- Any two variables that require the same variable *cannot* be enabled simultaneously
- As a result *no overlapping variables* are activated *at the same time*

Number of Constraints

- Naive COP: $\binom{\text{\# coalitions}}{2}$
- This approach: linear *wrt* the number of agents

Open Question

Can we make this COP a Distributed COP (DCOP)?

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Characteristic Function Games

Coalition Structure Generation

Induced Subgraph Games

Distributed Constraint Optimization

Real-World Applications

Conclusion and Wrap-up

Characteristic Function

[CHALKIADAKIS et al., 2011]

Characteristic Function

The function $v : \mathcal{P}(A) \rightarrow \mathbb{R}$ associates a value to *every coalition* (i.e., subset) of A

Exponential Complexity


Representing $v(\cdot)$ as a *table* requires an *exponential* number of steps (i.e., $2^{|A|}$)

Mitigate this Complexity

(1) *Restrict* the set of coalitions or (2) consider $v(\cdot)$ with a specific *structure*

Induced Subgraph Games (ISGs)

[DENG and PAPADIMITRIOU, 1994]



Weighted Graph G among Agents


$$G_w = (\{ \text{Agent 1}, \text{Agent 2}, \text{Agent 3}, \text{Agent 4}, \text{Agent 5} \}, \{ (\underbrace{\text{Agent 1}, \text{Agent 2}}_2), (\underbrace{\text{Agent 1}, \text{Agent 3}}_3), (\underbrace{\text{Agent 2}, \text{Agent 4}}_1), (\text{Agent 3}, \text{Agent 5}), (\text{Agent 4}, \text{Agent 5}) \})$$

Value is the Sum of Induced Edges

$$v(\{ \text{Agent 1}, \text{Agent 2}, \text{Agent 3} \}) = 2 + 1 = 3$$

Induced Subgraph Games (ISGs)

[DENG and PAPADIMITRIOU, 1994]



Weighted Graph G among Agents

$$G_w = (\{ \text{Agent 1}, \text{Agent 2}, \text{Agent 3}, \text{Agent 4} \}, \{ (\underbrace{\text{Agent 1}, \text{Agent 2}}_2), (\underbrace{\text{Agent 1}, \text{Agent 3}}_3), (\underbrace{\text{Agent 2}, \text{Agent 4}}_1) \})$$

Value is the Sum of Induced Edges

$$v(\{ \text{Agent 1}, \text{Agent 2}, \text{Agent 3} \}) = 2 + 1 = 3$$

Induced Subgraph Games (ISGs)

[CHALKIADAKIS et al., 2011]

Succinct Game Representation

The characteristic function is *entirely* represented by the weighted graph G_w

Computational Advantages

CSG on ISGs can be treated as a *graph clustering* problem (“easier” than CSG)

Limited Representation Power

Not every characteristic function game can be *perfectly* represented as an ISG

Induced Subgraph Games (ISGs)

[CHALKIADAKIS et al., 2011]

Succinct Game Representation

The characteristic function is *entirely* represented by the weighted graph G_w

Computational Advantages


CSG on ISGs can be treated as a *graph clustering* problem (“easier” than CSG)

Limited Representation Power

Not every characteristic function game can be *perfectly* represented as an ISG

Induced Subgraph Games (ISGs)

[CHALKIADAKIS et al., 2011]




$$v(S) = \begin{cases} 0, & \text{if } |S| = 1, \\ 1, & \text{if } |S| = 2, \\ 6, & \text{if } |S| = 3. \end{cases}$$

Can We Approximate a CFG as an ISG?

[BISTAFFA et al., 2022]

Approximately Equivalent ISG (AE-ISG)


Given a CFG C , compute the ISG that *best approximates* C , namely $\text{AE-ISG}(C)$



AE-ISG as Norm Approximation (ℓ_p Linear Regression)

[BISTAFFA et al., 2022]

$$\begin{aligned}
 & \text{minimise} \quad \underbrace{\|Mw - v\|_p}_{\text{residuals}} \\
 & M = \begin{bmatrix} \vdots & \vdots & \vdots \\ 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 0 & 1 \\ \vdots & \vdots & \vdots \end{bmatrix} \quad v = \begin{bmatrix} v(\{\text{agent 1}, \text{agent 2}, \text{agent 3}\}) \\ v(\{\text{agent 1}, \text{agent 2}\}) \\ v(\{\text{agent 1}, \text{agent 2}, \text{agent 3}\}) \\ \vdots \end{bmatrix}
 \end{aligned}$$

AE-ISG as Norm Approximation (ℓ_p Linear Regression)

[BISTAFFA et al., 2022]

$$\text{minimise} \quad \|\underbrace{Mw - v}_{\text{residuals}}\|_p$$

Residual Vector

The *residual vector* $r = Mw - v$ is the vector of *differences* between *approximated* coalitional values (i.e., Mw) and *original* coalitional values (i.e., v)

Constrained Norm Approximation

Some coalitions (singletons) can be represented *exactly* via additional constraints

AE-ISG as Norm Approximation (ℓ_p Linear Regression)

[BISTAFFA et al., 2022]

Size of AE-ISG Model

Building M and v requires to go through the set of coalitional values (obviously)


Computational Complexity

If the set of feasible coalitions is *polynomial* (e.g., ridesharing), computing $\text{AE-ISG}(C)$ has a *manageable* complexity, depending on the norm ℓ_p :

- $\ell_1/\ell_\infty \rightarrow$ Linear Programming (exact, CPU)
- $\ell_2 \rightarrow$ Least Squares (exact/analytical, GPU)
- $\ell_{>2} \rightarrow$ Iteratively Reweighted Least Squares (numerical)


CSG on ISGs as Graph Clustering

[BISTAFFA et al., 2022]



CSG on ISGs as Graph Clustering

[BISTAFFA et al., 2022]



CSG on ISGs Optimisation Objective

Maximise sum of of *clusters' internal weights* (namely, *coverage measure*)



ILP for Optimal Graph Clustering (KGC)

[BISTAFFA et al., 2022]

$X_{ij} = 1 \rightarrow$ edge $\{i, j\}$ is “activated” (i and j are in the same cluster)

$$\text{maximise} \quad \sum_{i,j \in A} w_{ij} \cdot X_{ij} \quad (\text{Coverage objective function})$$

$$\text{subject to } \forall i, j, z \in A : \begin{cases} X_{ij} + X_{jz} - 2 \cdot X_{iz} \leq 1 \\ X_{iz} + X_{ij} - 2 \cdot X_{jz} \leq 1 \\ X_{jz} + X_{iz} - 2 \cdot X_{ij} \leq 1 \end{cases} \quad (\text{Transitivity})$$

$$\forall i \in A : \sum_{j \in A} X_{ij} \leq k \quad (\text{Cardinality constraint})$$

Theoretical Quality Guarantees

[BISTAFFA et al., 2022]

KGC computes the value of the optimal CSG solution for the *approximated game AE-ISG(C)*, namely $V(CS_{AE}^*)$

What about the value of the optimal CSG solution for the *original game C*, namely $V(CS_C^*)$?

We proposed a way to compute B_r , such that $V(CS_C^*) - V(CS_{AE}^*) \leq B_r$



Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms

Extensions

Real-World Applications

Conclusion and Wrap-up



Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms

Extensions


Real-World Applications

Conclusion and Wrap-up



Motivating example


Sensor networks





Motivating example


Sensor networks





Motivating example


Sensor networks





Motivating example


Sensor networks





Motivating example


Sensor networks





Motivating example

Sensor networks



| x_1 | x_3 | x_5 | Sat? |
|-------|-------|-------|------|
| N | N | N | X |
| N | N | E | X |
| ... | | | X |
| S | W | N | ✓ |
| ... | | | X |
| W | W | W | X |

Model the problem
as a CSP!

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms

Extensions

Real-World Applications

Conclusion and Wrap-up




CSP

Constraint Satisfaction

- Variables $X = \{x_1, \dots, x_n\}$
 - Domains $D = \{D_1, \dots, D_n\}$
 - Constraints $C\{c_1, \dots, c_m\}$
where a constraint $c_i \subseteq D_{i_1} \times D_{i_2} \times \dots \times D_{i_n}$ denotes the possible valid joint assignments for the variables $x_{i_1}, x_{i_2}, \dots, x_{i_n}$ it involves
 - **Goal:** Find an assignment to all variables that **satisfies all the constraints**

CSP

Constraint Satisfaction




| x_1 | x_3 | x_5 | Sat? |
|-------|-------|-------|------|
| N | N | N | X |
| N | N | E | X |
| ... | | | X |
| S | W | N | ✓ |
| ... | | | X |
| W | W | W | X |

Model the problem
as a CSP!

Max-CSP

Max Constraint Satisfaction



| x_1 | x_3 | x_5 | Sat? |
|-------|-------|-------|------|
| N | N | N | X |
| N | N | E | X |
| ... | | | X |
| S | W | N | ✓ |
| ... | | | X |
| W | W | W | X |

Model the problem as a Max-CSP!




Max-CSP

Max Constraint Satisfaction

- Variables $X = \{x_1, \dots, x_n\}$
 - Domains $D = \{D_1, \dots, D_n\}$
 - Constraints $C\{c_1, \dots, c_m\}$
where a constraint $c_i \subseteq D_{i_1} \times D_{i_2} \times \dots \times D_{i_n}$ denotes the possible valid joint assignments for the variables $x_{i_1}, x_{i_2}, \dots, x_{i_n}$ it involves
 - **Goal:** Find an assignment to all variables that **satisfies a maximum number of constraints**

Max-CSP

Max Constraint Satisfaction




| x_1 | x_3 | x_5 | Sat? |
|-------|-------|-------|------|
| N | N | N | X |
| N | N | E | X |
| ... | | | X |
| S | W | N | ✓ |
| ... | | | X |
| W | W | W | X |

Model the problem
as a Max-CSP!



WCSP (or COP)

Constraint Optimization



| x_1 | x_3 | x_5 | Cost |
|-------|-------|-------|----------|
| N | N | N | ∞ |
| N | N | E | ∞ |
| ... | | | ∞ |
| S | W | N | 10 |
| ... | | | ∞ |
| W | W | W | ∞ |


Model the problem
as a COP!



WCSP (or COP)

Constraint Optimization


- Variables $X = \{x_1, \dots, x_n\}$
 - Domains $D = \{D_1, \dots, D_n\}$
 - Constraints $C\{c_1, \dots, c_m\}$
where a constraint $c_i : D_{i_1} \times D_{i_2} \times \dots \times D_{i_n} \rightarrow \mathbb{R}_+ \cup \{\infty\}$ expresses the degree of constraint violation
 - **Goal:** Find an assignment to all variables that minimizes the sum of all the constraints





WCSP (or COP)

Constraint Optimization



Imagine that each sensor is an autonomous agent

*How should this problem be modeled
and solved in a decentralized
manner?*

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms


Extensions

Real-World Applications

Conclusion and Wrap-up

DCOP

Distributed Constraint Optimization [MODI et al., 2005]




Imagine that each sensor is an autonomous agent

How should this problem be modeled and solved in a decentralized manner?

DCOP

Distributed Constraint Optimization [MODI et al., 2005]



DCOP


Distributed Constraint Optimization [MODI et al., 2005]

- Agents $X = \{a_1, \dots, a_l\}$
- Variables $X = \{x_1, \dots, x_n\}$
- Domains $D = \{D_1, \dots, D_n\}$
- Constraints $C\{c_1, \dots, c_m\}$
- Mapping of variables to agents

- **Goal:** Find an assignment to all variables that minimizes the sum of all the constraints


DCOP

Distributed Constraint Optimization [MODI et al., 2005]



DCOP

Distributed Constraint Optimization [Modi et al., 2005]



- Variables are controlled by agents
- Communication model
- Local knowledge

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms


Extensions

Real-World Applications

Conclusion and Wrap-up


DCOP Algorithms

See [FIORETTA et al., 2018]



DCOP Algorithms

See [FIORETTA et al., 2018]




Important metrics

- Agent complexity
- Network loads
- Message size

DCOP Algorithms

See [FIORETTA et al., 2018]




Important metrics

- Agent complexity
- Network loads
- Message size

- Anytime
- Quality guarantees
- Execution time vs. solution quality

DCOP Algorithms


See [FIORETTA et al., 2018]



- Systematic process, divided in steps
- Each agent waits for particular messages before acting
- Consistent view of the search process
- Typically, increases idle-time

DCOP Algorithms


See [FIORETTA et al., 2018]



- Decision based on agents' local state
- Agents' actions do not depend on sequence of received messages
- Minimizes idle-time
- No guarantees on validity of local views

DCOP Algorithms

See [FIORETTA et al., 2018]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and YOKOO, 1997]

Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




| x_i | x_j | (A, B) | (A, C) | (B, C) | (B, C) |
|-------|-------|----------|----------|----------|----------|
| red | red | 5 | 5 | 5 | 3 |
| red | green | 8 | 10 | 4 | 8 |
| green | red | 20 | 20 | 3 | 10 |
| green | green | 3 | 3 | 3 | 3 |

How do we solve this distributedly?

Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]



| x_i | x_j | (A, B) | (A, C) | (B, C) | (B, C) |
|-------|-------|--------|--------|--------|--------|
| red | red | 5 | 5 | 5 | 3 |
| red | green | 8 | 10 | 4 | 8 |
| green | red | 20 | 20 | 3 | 10 |
| green | green | 3 | 3 | 3 | 3 |


How do we solve this distributedly?

Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]


- Agents operate on a complete ordering
- Agents exchange CPA messages containing partial assignments
- When a solution is found, its solution cost as an UB is broadcasted to all agents
- The UB is used for branch pruning

Complete ordering



Synchronous Branch-and-Bound (SBB)


[HIRAYAMA and Yokoo, 1997]



Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]

A



$UB = \infty$


B

C

D


Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]



Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]



Synchronous Branch-and-Bound (SBB)


[HIRAYAMA and Yokoo, 1997]

| | SBB |
|---|--------------------|
| Correct the solution it finds is optimal | Yes |
| Complete it terminates | Yes |
| Message complexity max size of messages | $\mathcal{O}(d)$ |
| Network load max number of messages | $\mathcal{O}(b^d)$ |
| Runtime how long it takes | $\mathcal{O}(b^d)$ |

$$\begin{aligned} \text{branching factor} &= b \\ \text{num variables} &= d \end{aligned}$$


Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]




Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]





Synchronous Branch-and-Bound (SBB)

[HIRAYAMA and Yokoo, 1997]





Pseudo-Tree



Definition (Pseudo-Tree)

A spanning tree of the constraint graph such that no two nodes in sibling subtrees share a constraint in the constraint graph

Pseudo-Tree




Definition (Pseudo-Tree)

A spanning tree of the constraint graph such that no two nodes in sibling subtrees share a constraint in the constraint graph

DCOP Algorithms

See [FIORETTA et al., 2018]




Distributed Pseudotree Optimization Procedure (DPOP)

[PETCU and FALTINGS, 2005b]

DPOP

[PETCU and FALTINGS, 2005b]

- Extension of the Bucket Elimination (BE)
- Agents operate on a pseudo-tree ordering
- UTIL phase: Leaves to root
- VALUE phase: Root to leaves



DPOP

[PETCU and FALTINGS, 2005b]


| <i>B</i> | <i>D</i> | (B, D) |
|----------|----------|----------|
| <i>r</i> | <i>r</i> | 3 |
| <i>r</i> | <i>g</i> | 8 |
| <i>g</i> | <i>r</i> | 10 |
| <i>g</i> | <i>g</i> | 3 |

$$\min\{3, 8\} = 3$$

$$\min\{10, 3\} = 3$$

Message to B

| <i>B</i> | cost |
|----------|------|
| <i>r</i> | 3 |
| <i>g</i> | 3 |




DPOP

[PETCU and FALTINGS, 2005b]

| A | B | C | (B, C) | (A, C) | cost |
|-----|-----|-----|----------|----------|------|
| r | r | r | 5 | 5 | 10 |
| r | r | g | 4 | 8 | 12 |
| r | g | r | 3 | 5 | 8 |
| r | g | g | 3 | 8 | 11 |
| g | r | r | 5 | 10 | 15 |
| g | r | g | 4 | 3 | 7 |
| g | g | r | 3 | 10 | 13 |
| g | g | g | 3 | 3 | 6 |

Message to B

| A | B | cost |
|-----|-----|------|
| r | r | 10 |
| r | g | 8 |
| g | r | 7 |
| g | g | 6 |




DPOP

[PETCU and FALTINGS, 2005b]

| A | B | (A, B) | Util C | Util D | cost |
|-----|-----|----------|----------|----------|------|
| r | r | 5 | 10 | 53 | 18 |
| r | g | 8 | 8 | 3 | 19 |
| g | r | 20 | 7 | 3 | 30 |
| g | g | 3 | 6 | 3 | 12 |

Message to A

| A | cost |
|-----|------|
| r | 18 |
| g | 12 |




DPOP

[PETCU and FALTINGS, 2005b]

| A | cost |
|---|------|
| r | 18 |
| g | 12 |

optimal cost = 12




DPOP

[PETCU and FALTINGS, 2005b]

| A | cost |
|-----|------|
| r | 18 |
| g | 12 |

- Select value for $A = g$
- Send MSG " $A = g$ " to agents B and C




DPOP

[PETCU and FALTINGS, 2005b]

| A | B | (A, B) | Util C | Util D | cost |
|-----|-----|----------|----------|----------|------|
| r | r | 5 | 10 | 53 | 18 |
| r | g | 8 | 8 | 3 | 19 |
| g | r | 20 | 7 | 3 | 30 |
| g | g | 3 | 6 | 3 | 12 |

- Select value for $B = g$
- Send MSG " $B = g$ " to agents C and D






DPOP

[PETCU and FALTINGS, 2005b]

| A | B | C | (B, C) | (A, C) | cost |
|-----|-----|----------------------|----------|----------|------|
| r | r | r | 5 | 5 | 10 |
| r | r | g | 4 | 8 | 12 |
| r | g | r | 3 | 5 | 8 |
| r | g | g | 3 | 8 | 11 |
| g | r | r | 5 | 10 | 15 |
| g | r | g | 4 | 3 | 7 |
| g | g | r | 3 | 10 | 13 |
| g | g | $\textcolor{red}{g}$ | 3 | 3 | 6 |

- Select value for $C = g$




DPOP

[PETCU and FALTINGS, 2005b]

| | | |
|----------|----------|----------|
| <i>B</i> | <i>D</i> | (B, D) |
| <i>r</i> | <i>r</i> | 3 |
| <i>r</i> | <i>g</i> | 8 |
| g | <i>r</i> | 10 |
| g | g | 3 |

$$\min\{3, 8\} = 3$$

$$\min\{10, 3\} = 3$$



- Select value for $D = g$

DPOP

[PETCU and FALTINGS, 2005b]


| | SBB | DPOP |
|---|--------------------|--------------------|
| Correct the solution it finds is optimal | Yes | Yes |
| Complete it terminates | Yes | Yes |
| Message complexity max size of messages | $\mathcal{O}(d)$ | $\mathcal{O}(b^d)$ |
| Network load max number of messages | $\mathcal{O}(b^d)$ | $\mathcal{O}(d)$ |
| Runtime how long it takes | $\mathcal{O}(b^d)$ | $\mathcal{O}(b^d)$ |

branching factor = b

num variables = d

DCOP Algorithms

See [FIORETTA et al., 2018]




Distributed Local Search

[MAHESWARAN et al., 2004; ZHANG et al., 2003]

Local Search Algorithms

- DSA: Distributed Stochastic Search [ZHANG et al., 2005]
- MGM: Maximum Gain Messages Algorithm [MAHESWARAN et al., 2004]
- Note: we now maximize utilities
- Every agent individually decides whether to change its value or not
- Decision involves
 - ▶ knowing neighbors' values
 - ▶ calculation of utility gain by changing values
 - ▶ probabilities

| x_i | x_j | (A, B) | (B, C) |
|-------|-------|--------|--------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |




DSA Algorithm

[ZHANG et al., 2005]

- All agents execute the following
 - ▶ Randomly choose a value
 - ▶ while (termination is not met)
 - ▶ if (a new value is assigned): send the new value to neighbors
 - ▶ collect neighbors' new values if any
 - ▶ select and assign the next value based on assignment rule

DSA Algorithm


[ZHANG et al., 2005]



| x_i | x_j | (A, B) | (B, C) |
|-------|-------|----------|----------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |

DSA Algorithm


[ZHANG et al., 2005]



| x_i | x_j | (A, B) | (B, C) |
|-------|-------|----------|----------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |

DSA Algorithm


[ZHANG et al., 2005]



| x_i | x_j | (A, B) | (B, C) |
|-------|-------|----------|----------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |

DSA Algorithm


[ZHANG et al., 2005]



| x_i | x_j | (A, B) | (B, C) |
|-------|-------|----------|----------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |

DSA Algorithm

[ZHANG et al., 2005]



| x_i | x_j | (A, B) | (B, C) |
|-------|-------|----------|----------|
| red | red | 5 | 5 |
| red | green | 5 | 0 |
| green | red | 0 | 0 |
| green | green | 8 | 8 |

MGM Algorithm

[MAHESWARAN et al., 2004]

- All agents execute the following
 - ▶ Randomly choose a value
 - ▶ while (termination is not met)
 - ▶ if (a new value is assigned): send the new value to neighbors
 - ▶ collect neighbors' new values if any
 - ▶ calculate gain and send it to neighbors
 - ▶ collect neighbors' gains
 - ▶ if (it has the highest gain among all neighbors): change value to the value that maximizes gain

Large Great if you need an anytime algorithm!

MGM Algorithm

[MAHESWARAN et al., 2004]

- All agents execute the following
 - ▶ Randomly choose a value
 - ▶ while (termination is not met)
 - ▶ if (a new value is assigned): send the new value to neighbors
 - ▶ collect neighbors' new values if any
 - ▶ calculate gain and send it to neighbors
 - ▶ collect neighbors' gains
 - ▶ if (it has the highest gain among all neighbors): change value to the value that maximizes gain

Large Great if you need an anytime algorithm!

MGM vs DSA




Figure: MGM




Figure: DSA

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Motivating Examples

Preliminaries

DCOP Model

DCOP Algorithms

Extensions

Real-World Applications


Conclusion and Wrap-up

Extensions to the DCOP Framework

- Dynamic DCOPs
 - ▶ SDPOP [PETCU and FALTINGS, 2005a], I-ADOPT and I-BnB-ADOPT [YEOH et al., 2011], FMS [RAMCHURN et al., 2010]
- Multi-Objective DCOPs
 - ▶ MO-SBB [MEDI et al., 2014], Pseudo-tree Based Algorithm [MATSUI et al., 2012], B-MOMS [DELLE FAVE et al., 2011], DP-AOF [OKIMOTO et al., 2013]
- Asymmetric DCOPs
 - ▶ SyncABB-2ph, SyncABB-1ph, ACLS, MCS-MGM [GRINSHPOUN et al., 2013]
- Probabilistic DCOPs
 - ▶ $\mathbb{E}[\text{DPOP}]$ and SD-DPOP [LÉAUTÉ and FALTINGS, 2011; NGUYEN et al., 2012], U-GDL [STRANDERS et al., 2011]
- Continuous DCOPs
 - ▶ CMS [STRANDERS et al., 2009], HCMS [VOICE et al., 2010], PFD [CHOUDHURY et al., 2020], EC-DPOP, AC-DPOP, CAC-DPOP, C-DSA [HOANG et al., 2020], C-CoCoA [SARKER et al., 2021]
- ...

Deeper Focus on Max-Sum

See [FIORETTA et al., 2018]



Distributed Inference, Max-Sum

[FARINELLI et al., 2008]



Roie Zivan's Talk



Today's Menu

Coalition Formation on MAS

Real-World Applications

Shared Mobility

Collective Energy Purchasing

Self-configuration of IoT Devices

Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up

Today's Menu

Coalition Formation on MAS

Real-World Applications

Shared Mobility

Collective Energy Purchasing

Self-configuration of IoT Devices

Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up




Shared Mobility as (Online) Coalition Structure Generation

[BISTAFFA et al., 2019]

What is Shared Mobility for Us?

Arrange *shared rides* (coalitions) among users that submit *real-time* requests, with the objective of *maximizing* a given *objective function*



Shared Mobility as (Online) Coalition Structure Generation

[ibid.]

Our Task

At each time step, arrange a (possibly empty) set of non-overlapping feasible cars among the requests currently active in the system

Shared Mobility as (Online) Coalition Structure Generation

[ibid.]

Our Task

At each time step, arrange a (possibly empty) set of non-overlapping feasible cars among the requests currently active in the system

Our Objective Function

Maximize environmental benefits  and quality of service 

Shared Mobility as (Online) Coalition Structure Generation

[ibid.]

Our Task

At each time step, arrange a (possibly empty) set of non-overlapping feasible cars among the requests currently active in the system

Our Objective Function

Maximize environmental benefits  and quality of service 



Our Case Study [BISTAFFA et al., 2019]

Densely populated areas (e.g., Manhattan) with request rate of 400 reqs/minute

Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Incoming Requests




"I just issued a trip request"

Waiting Trip Requests



“I am waiting to share my ride”



Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Example of a Shared Mobility Request

"I want to go from point i to point j , and I am willing to wait δ minutes to be picked up by somebody ($d = \text{false}$) / before I leave with *my own car* ($d = \text{true}$)"

- $r = \langle i, j, d, \delta \rangle$ (A request is a tuple r)
- $r \in R_t$ (The system receives a set R_t of requests at each time step t)
- $\langle R_1, \dots, R_t, \dots, R_h \rangle$ (Sequence of inputs over a time horizon h)
- The input sequence is *not known a priori* (Online optimization problem)

Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Example of a Shared Mobility Request

"I want to go from point i to point j , and I am willing to wait δ minutes to be picked up by somebody ($d = \text{false}$) / before I leave with *my own car* ($d = \text{true}$)"

- $r = \langle i, j, d, \delta \rangle$ (A request is a tuple r)
- $r \in R_t$ (The system receives a set R_t of requests at each time step t)
- $\langle R_1, \dots, R_t, \dots, R_h \rangle$ (Sequence of inputs over a time horizon h)
- The input sequence is *not known a priori* (Online optimization problem)

Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Example of a Shared Mobility Request

"I want to go from point i to point j , and I am willing to wait δ minutes to be picked up by somebody ($d = \text{false}$) / before I leave with *my own car* ($d = \text{true}$)"

- $r = \langle i, j, d, \delta \rangle$ (A request is a tuple r)
- $r \in R_t$ (The system receives a set R_t of requests at each time step t)
- $\langle R_1, \dots, R_t, \dots, R_h \rangle$ (Sequence of inputs over a time horizon h)
- The input sequence is *not known a priori* (Online optimization problem)

Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Example of a Shared Mobility Request

"I want to go from point i to point j , and I am willing to wait δ minutes to be picked up by somebody ($d = \text{false}$) / before I leave with *my own car* ($d = \text{true}$)"

- $r = \langle i, j, d, \delta \rangle$ (A request is a tuple r)
- $r \in R_t$ (The system receives a set R_t of requests at each time step t)
- $\langle R_1, \dots, R_t, \dots, R_h \rangle$ (Sequence of inputs over a time horizon h)
- The input sequence is *not known a priori* (Online optimization problem)

Input of the Online CSG Problem

[BISTAFFA et al., 2019]

Example of a Shared Mobility Request

"I want to go from point i to point j , and I am willing to wait δ minutes to be picked up by somebody ($d = \text{false}$) / before I leave with *my own car* ($d = \text{true}$)"

- $r = \langle i, j, d, \delta \rangle$ (A request is a tuple r)
- $r \in R_t$ (The system receives a set R_t of requests at each time step t)
- $\langle R_1, \dots, R_t, \dots, R_h \rangle$ (Sequence of inputs over a time horizon h)
- The input sequence is *not known a priori* (Online optimization problem)

Value $v(S)$ of a Coalition S

[BISTAFFA et al., 2019]

- The *value* (utility) of a coalition S is defined as:

$$v(S) = \overbrace{\rho_{\text{CO}_2} \cdot E_{\text{CO}_2}(S) + \rho_{\text{noise}} \cdot E_{\text{noise}}(S) + \rho_{\text{traffic}} \cdot E_{\text{traffic}}(S)}^{\text{environmental benefits}} + \overbrace{\rho_{\text{QoS}} \cdot Q(S)}^{\text{quality of service}}$$

- $|S| \leq k$ (Maximum cardinality constraint)

$$F(S) = |S| \leq k \wedge \dots$$

- $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$ (Set of feasible coalitions from a set R of requests)

Value $v(S)$ of a Coalition S

[BISTAFFA et al., 2019]

- The *value* (utility) of a coalition S is defined as:

$$v(S) = \overbrace{\rho_{\text{CO}_2} \cdot E_{\text{CO}_2}(S) + \rho_{\text{noise}} \cdot E_{\text{noise}}(S) + \rho_{\text{traffic}} \cdot E_{\text{traffic}}(S)}^{\text{environmental benefits}} + \overbrace{\rho_{\text{QoS}} \cdot Q(S)}^{\text{quality of service}}$$

- $|S| \leq k$ (Maximum cardinality constraint)

$$F(S) = |S| \leq k \wedge \dots$$

- $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$ (Set of feasible coalitions from a set R of requests)

Value $v(S)$ of a Coalition S

[BISTAFFA et al., 2019]

- The *value* (utility) of a coalition S is defined as:

$$v(S) = \overbrace{\rho_{\text{CO}_2} \cdot E_{\text{CO}_2}(S) + \rho_{\text{noise}} \cdot E_{\text{noise}}(S) + \rho_{\text{traffic}} \cdot E_{\text{traffic}}(S)}^{\text{environmental benefits}} + \overbrace{\rho_{\text{QoS}} \cdot Q(S)}^{\text{quality of service}}$$

- $|S| \leq k$ (Maximum cardinality constraint)

$$F(S) = |S| \leq k \wedge \dots$$

- $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$ (Set of feasible coalitions from a set R of requests)

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Curse of Dimensionality

[BISTAFFA et al., 2019]

- Recall that $\mathcal{F}(R) = \{S \in 2^R \mid F(S)\}$
- With $|S| \leq k$, $|\mathcal{F}(R)| \leq \sum_{i=1}^k \binom{|R|}{i}$, i.e., $\mathcal{O}(|R|^k)$ (Polynomial complexity)
- In practice, $|R_t|$ can be as high as 400 (Request rate in NY taxi dataset)

Scalability Problem

Enumerating all coalitions in $\mathcal{F}(R)$ is impractical, especially in realistic application scenarios with *very limited time budget* for the solution

Our Solution

Consider a restricted set $\hat{\mathcal{F}}(R)$ of *good candidate coalitions* instead of $\mathcal{F}(R)$

Generation of Good Candidate Coalitions (Step 1)

[BISTAFFA et al., 2019]

Cloud icon CO₂ emissions

Megaphone icon Acoustic pollution

Traffic icon Traffic congestion


Clock icon Quality of service



20 seconds




Probabilistic
Greedy
Algorithm



ILP Optimization (Step 2)

[BISTAFFA et al., 2019]

Good Candidates




40 seconds



ILP
Solver

ILP Solution



Approximated ILP Formulation

[BISTAFFA et al., 2019]

$$\begin{aligned} & \text{maximize} && \sum_{S \in \hat{\mathcal{F}}(\text{Pool})} v(S) \cdot x_S \\ & && \text{(Only good candidates)} \\ & \text{such that} && x_S + x_{S'} \leq 1 \quad \forall \hat{\mathcal{F}}(\text{Pool}) : S \cap S' \neq \emptyset \end{aligned}$$

Computational Advantage

Approximated ILP has a number of variables that is $< 0.01\%$ of the optimal ILP

Approximated ILP Formulation

[BISTAFFA et al., 2019]

$$\begin{aligned} & \text{maximize} && \sum_{S \in \hat{\mathcal{F}}(\text{Pool})} v(S) \cdot x_S \\ & && \text{(Only good candidates)} \\ & \text{such that} && x_S + x_{S'} \leq 1 \quad \forall \hat{\mathcal{F}}(\text{Pool}) : S \cap S' \neq \emptyset \end{aligned}$$

Computational Advantage

Approximated ILP has a number of variables that is $< 0.01\%$ of the optimal ILP

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Real-World Applications

Shared Mobility

Collective Energy Purchasing

Self-configuration of IoT Devices

Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up

Collective Energy Purchasing

[FARINELLI et al., 2013]

Collective Energy Purchasing Scenario

- Each agent has an energy consumption profile
- Customers form coalitions to buy energy at reduced tariffs from two different markets:
 - ▶ *Spot market*: a short-term market intended for smaller amounts of energy
 - ▶ *Forward market*: a long-term market to buy more energy at cheaper prices

Collective Energy Purchasing

[FARINELLI et al., 2013]

Collective Energy Purchasing Scenario

- Each agent has an energy consumption profile
- Customers form coalitions to buy energy at reduced tariffs from two different markets:
 - ▶ *Spot market*: a short-term market intended for smaller amounts of energy
 - ▶ *Forward market*: a long-term market to buy more energy at cheaper prices

Collective Energy Purchasing

[FARINELLI et al., 2013]

Collective Energy Purchasing Scenario

- Each agent has an energy consumption profile
- Customers form coalitions to buy energy at reduced tariffs from two different markets:
 - ▶ *Spot market*: a short-term market intended for smaller amounts of energy
 - ▶ *Forward market*: a long-term market to buy more energy at cheaper prices

Collective Energy Purchasing

[FARINELLI et al., 2013]

Collective Energy Purchasing Scenario

- Each agent has an energy consumption profile
- Customers form coalitions to buy energy at reduced tariffs from two different markets:
 - ▶ *Spot market*: a short-term market intended for smaller amounts of energy
 - ▶ *Forward market*: a long-term market to buy more energy at cheaper prices

Collective Energy Purchasing

[FARINELLI et al., 2013]

Collective Energy Purchasing Scenario

- Each agent has an energy consumption profile
- Customers form coalitions to buy energy at reduced tariffs from two different markets:
 - ▶ *Spot market*: a short-term market intended for smaller amounts of energy
 - ▶ *Forward market*: a long-term market to buy more energy at cheaper prices


Collective Energy Purchasing

[FARINELLI et al., 2013]

Profile Merging

- Peaks in energy profiles require the use of *expensive, carbon-intensive*, peaking plant generators, resulting in higher consumers electricity bill
- A *flattened profile* results in a more efficient grid, with *lower carbon emissions* and *lower prices* for consumers

Example



Value $v(S)$ of a Coalition S

[BISTAFFA et al., 2017a]

- The *value* (utility) of a coalition S is defined as:

$$v(S) = \underbrace{\sum_{t=1}^T q_S^t(S) \cdot p_S}_{\text{Spot market}} + \underbrace{T \cdot q_F(S) \cdot p_F}_{\text{Forward market}} - \kappa(S)$$

- $q_S^t(S)$: energy purchased from spot market at time t
 - $q_F(S)$: total energy purchased from forward market
 - p_S : spot market energy price
 - p_F : forward market energy price

Value $v(S)$ of a Coalition S

[BISTAFFA et al., 2017a]

- The *value* (utility) of a coalition S is defined as:

$$v(S) = \underbrace{\sum_{t=1}^T q_S^t(S) \cdot p_S}_{\text{Spot market}} + \underbrace{T \cdot q_F(S) \cdot p_F}_{\text{Forward market}} - \kappa(S)$$

Superadditive ($v^+(S)$) Subadditive ($v^-(S)$)

- $q_S^t(S)$: energy purchased from spot market at time t
- $q_F(S)$: total energy purchased from forward market
- p_S : spot market energy price
- p_F : forward market energy price

$m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]

$m + a$ Characteristic Function

- $m + a =$ Superadditive function + subadditive function
 - ▶ Superadditive: $v(S_1 \cup S_2) > v(S_1) + v(S_2)$
 - ▶ Subadditive: $v(S_1 \cup S_2) < v(S_1) + v(S_2)$

Open Question

Is the characteristic function of shared mobility $m + a$?

$m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]

$m + a$ Characteristic Function


- $m + a =$ Superadditive function + subadditive function
 - ▶ Superadditive: $v(S_1 \cup S_2) > v(S_1) + v(S_2)$
 - ▶ Subadditive: $v(S_1 \cup S_2) < v(S_1) + v(S_2)$

Open Question

Is the characteristic function of shared mobility $m + a$?

Branch-and-Bound for $m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]



Can we Find an Upper Bound on $v(\cdot)$ in this Subtree?

$$\begin{array}{ll}
 \{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}, \text{orange}, \text{orange}\} & \{\text{blue}, \text{green}\}, \{\text{blue}\}, \{\text{green}\}, \{\text{orange}\} \\
 \{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}\}, \{\text{orange}\}, \{\text{orange}\} & \{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{green}\}, \{\text{orange}\} \\
 \{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{green}\}, \{\text{orange}\} & \{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{blue}\}, \{\text{orange}\} \\
 \{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}, \text{orange}\}, \{\text{orange}\} & \{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{blue}, \text{orange}\}, \{\text{orange}\}
 \end{array}$$

Upper Bound M for $m + a$ Functions


$$M = v^+ (\text{contract all edges}) + v^- (\text{contract no edge})$$

Branch-and-Bound Algorithm

If M is $<$ than current best solution, do not visit this subtree

Branch-and-Bound for $m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]



Can we Find an Upper Bound on $v(\cdot)$ in this Subtree?

- $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}, \text{orange}, \text{brown}\}$ $\{\text{blue}, \text{green}\}, \{\text{owl}\}, \{\text{green}\}, \{\text{orange}\}, \{\text{brown}\}$
- $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}\}, \{\text{orange}\}, \{\text{brown}\}$ $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{brown}\}, \{\text{owl}\}$
- $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}\}, \{\text{orange}\}, \{\text{owl}\}$ $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{orange}\}, \{\text{owl}\}, \{\text{brown}\}$
- $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}, \text{orange}\}, \{\text{brown}\}$ $\{\text{blue}, \text{green}\}, \{\text{blue}, \text{green}, \text{orange}\}, \{\text{brown}\}$

Upper Bound M for $m + a$ Functions


$$M = v^+ (\text{contract all edges}) + v^- (\text{contract no edge})$$

Branch-and-Bound Algorithm

If M is $<$ than current best solution, do not visit this subtree

Branch-and-Bound for $m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]



Can we Find an Upper Bound on $v(\cdot)$ in this Subtree?

$$\begin{array}{ll} \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧓, 🧑}\} & \{\text{👤, 🧑}\}, \{\text{🦉}\}, \{\text{👤}\}, \{\text{👤}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{👤}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{🦉}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{🦉}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{👤}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧑}\}, \{\text{👤}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧑}\}, \{\text{👤}\}, \{\text{👤}\} \end{array}$$

Upper Bound M for $m + a$ Functions


$$M = v^+ (\text{contract all edges}) + v^- (\text{contract no edge})$$

Branch-and-Bound Algorithm

If M is $<$ than current best solution, do not visit this subtree

Branch-and-Bound for $m + a$ Characteristic Functions

[BISTAFFA et al., 2017a]



Can we Find an Upper Bound on $v(\cdot)$ in this Subtree?

$$\begin{array}{ll} \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧑, 🧑}\} & \{\text{👤, 🧑}\}, \{\text{🦉}\}, \{\text{👤}\}, \{\text{👤}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{👤}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{🦉}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤}\}, \{\text{🦉}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{👤, 🧑}\}, \{\text{🦉}\} \\ \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧑}\}, \{\text{👤}\} & \{\text{👤, 🧑}\}, \{\text{👤, 🧑, 🧑}\}, \{\text{👤}\}, \{\text{👤}\} \end{array}$$

Upper Bound M for $m + a$ Functions

$$M = v^+ (\text{contract all edges}) + v^- (\text{contract no edge})$$

Branch-and-Bound Algorithm

If M is $<$ than current best solution, do not visit this subtree

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Real-World Applications

Shared Mobility

Collective Energy Purchasing

Self-configuration of IoT Devices

Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up

SECP model

Smart Environment Configuration Problem [RUST et al., 2016]

- Example of applying DCOPs to a "real" problem
 - Coordinate objects in the building
 - Model
 - ▶ objects
 - ▶ relations between objects and environment
 - ▶ user objectives and requirements
 - Formulate the problem as an optimization problem



SECP model

Smart Environment Configuration Problem [RUST et al., 2016]

Focus on smart lighting use cases

- **Objects:** anything that can produce light: light bulbs, windows with rolling shutter, etc.
- **User preferences:** having a predefined luminosity level in a room, under some conditions
- **Energy efficiency**

Linking objects and user preferences:

- How to model the luminosity in a room ? **variable**
- How to model the dependency between the light sources and the luminosity ? **function / constraint**

SECP model

Example application to ambient intelligence scenario



■ Actuators

- ▶ Connected light bulbs, TV, Rolling shutters, ...

■ Sensors

- ▶ Presence detector, Luminosity Sensor, etc.

■ Physical Dependency Models

- ▶ E.g. Living-room light model

■ User Preferences

- ▶ Expressed as rules :

```
IF presence_living_room = 1
AND light_sensor_living_room < 60
THEN light_level_living_room ← 60
AND shutter_living_room ← 0
```

SECP model

Example application to ambient intelligence scenario



■ Actuators

- ▶ Decision variable x_i , domain \mathcal{D}_{x_i}
- ▶ Cost function $c_i : \mathcal{D}_{x_i} \rightarrow \mathbb{R}$

■ Sensors

- ▶ Read-only variable s_l , domain \mathcal{D}_{s_l}

■ Physical Dependency Models $\langle y_j, \phi_j \rangle$

- ▶ Give the expected state of the environment from a set of actuator-variables influencing this model
- ▶ Variable y_j representing the *expected* state of the environment
- ▶ Function $\phi_j : \prod_{\varsigma \in \sigma(\phi_j)} \mathcal{D}_\varsigma \rightarrow \mathcal{D}_{y_j}$

■ User Preferences

- ▶ Utility function u_k
- ▶ Distance from the current expected state to the target state of the environment

Formulating SECP as a DCOP

Multi-objective optimization problem

$$\begin{aligned} \min_{x_i \in \nu(\mathfrak{A})} \quad & \sum_{i \in \mathfrak{A}} c_i \quad \text{and} \quad \max_{\substack{x_i \in \nu(\mathfrak{A}) \\ y_j \in \nu(\Phi)}} \sum_{k \in \mathfrak{R}} u_k \\ \text{s.t. } \quad & \phi_j(x_j^1, \dots, x_j^{\overline{\phi_j}}) = y_j \quad \forall y_j \in \nu(\Phi) \end{aligned}$$


Mono-objective DCOP formulation

$$\max_{\substack{x_i \in \nu(\mathfrak{A}) \\ y_j \in \nu(\Phi)}} \quad \omega_u \sum_{k \in \mathfrak{R}} u_k - \omega_c \sum_{i \in \mathfrak{A}} c_i + \sum_{\varphi_j \in \Phi} \varphi_j$$

$$\varphi_j(x_j^1, \dots, x_j^{|\sigma(\phi_j)|}, y_j) = \begin{cases} 0 & \text{if } \phi_j(x_j^1, \dots, x_j^{|\sigma(\phi_j)|}) = y_j \\ -\infty & \text{otherwise} \end{cases}$$


Formulating SECP as a DCOP

Representing a DCOP as a factor graph





SECP Factor Graph

in a house (without rules)



Algorithms' performances



- Best solutions: DPOP, MaxSum, MGM2
- Worst runtime: DPOP
- Best compromise: MaxSum, MGM2

SECP: further readings

- Experiments with various algorithms [RUST et al., 2016, 2022]
- How to deploy DCOPs [RUST et al., 2017, 2022]
- How to adapt deployment at runtime [RUST et al., 2018, 2020, 2022]

Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Real-World Applications

Shared Mobility

Collective Energy Purchasing


Self-configuration of IoT Devices

Observation Scheduling in Multi-Owner Constellations

Conclusion and Wrap-up


Observation Scheduling in Multi-Owner Constellations [PICARD, 2022]

- Increasing size of deployed EOS constellations
 - Observe any point on Earth at higher frequency, e.g. Planet constellation
- **but**, requires to **improve coordination and cooperation** between assets and stakeholders
- We focus here on **collective observation scheduling** on a constellation where some users have **exclusive access** to **some orbit portions**
 - Answer to strong user expectations to benefit both from a shared system (to reduce costs) and a proprietary system (total control and confidentiality)




Observation Scheduling in Multi-Owner Constellations [PICARD, 2022]

- Increasing size of deployed EOS constellations
 - ⇒ Observe any point on Earth at higher frequency, e.g. Planet constellation
- **but**, requires to **improve coordination and cooperation** between assets and stakeholders
- We focus here on **collective observation scheduling** on a constellation where some users have **exclusive access to some orbit portions**
 - ⇒ Answer to strong user expectations to benefit both from a shared system (to reduce costs) and a proprietary system (total control and confidentiality)




Scheduling Observations with Multiple Exclusive Orbit Portions

Illustrative Example



Scheduling Observations with Multiple Exclusive Orbit Portions

Illustrative Example



DCOP Model

A DCOP $\langle \mathcal{A}, \mathcal{X}, \mathcal{D}, \mathcal{C}, \mu \rangle$ is defined for a given request r , and a current scheduling

- The agents are the exclusive users which can potentially schedule r :

$$\mathcal{A} = \{u \in \mathcal{U}^{\text{ex}} \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \exists o \in \theta_r \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\} \quad (1)$$

- Each agent u owns binary decision variables, one for each observation $o \in \mathcal{O}[u]^r$ and exclusive e in its exclusives e_u , stating whether it schedules o in e or not:

$$\mathcal{X} = \{x_{e,o} \mid e \in \bigcup_{u \in \mathcal{A}} e_u, o \in \mathcal{O}[u]^r\} \quad (2)$$

$$\mathcal{D} = \{\mathcal{D}_{x_{e,o}} = \{0, 1\} \mid x_{e,o} \in \mathcal{X}\} \quad (3)$$

with $\mathcal{O}[u]^r = \{o \in \theta_r \mid \exists (s, (t_o^{\text{start}}, t_o^{\text{end}})) \in e_u, \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\}$ are observations related to request r that can be scheduled on u 's exclusives

- μ associates each variable $x_{e,o}$ to e 's owner

DCOP Model

A DCOP $\langle \mathcal{A}, \mathcal{X}, \mathcal{D}, \mathcal{C}, \mu \rangle$ is defined for a given request r , and a current scheduling

- The agents are the exclusive users which can potentially schedule r :

$$\mathcal{A} = \{u \in \mathcal{U}^{\text{ex}} \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \exists o \in \theta_r \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\} \quad (1)$$

- Each agent u owns binary decision variables, one for each observation $o \in \mathcal{O}[u]^r$ and exclusive e in its exclusives e_u , stating whether it schedules o in e or not:

$$\mathcal{X} = \{x_{e,o} \mid e \in \bigcup_{u \in \mathcal{A}} e_u, o \in \mathcal{O}[u]^r\} \quad (2)$$

$$\mathcal{D} = \{\mathcal{D}_{x_{e,o}} = \{0, 1\} \mid x_{e,o} \in \mathcal{X}\} \quad (3)$$

with $\mathcal{O}[u]^r = \{o \in \theta_r \mid \exists (s, (t_o^{\text{start}}, t_o^{\text{end}})) \in e_u, \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\}$ are observations related to request r that can be scheduled on u 's exclusives

- μ associates each variable $x_{e,o}$ to e 's owner

DCOP Model

A DCOP $\langle \mathcal{A}, \mathcal{X}, \mathcal{D}, \mathcal{C}, \mu \rangle$ is defined for a given request r , and a current scheduling

- The agents are the exclusive users which can potentially schedule r :

$$\mathcal{A} = \{u \in \mathcal{U}^{\text{ex}} \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \exists o \in \theta_r \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\} \quad (1)$$

- Each agent u owns binary decision variables, one for each observation $o \in \mathcal{O}[u]^r$ and exclusive e in its exclusives e_u , stating whether it schedules o in e or not:

$$\mathcal{X} = \{x_{e,o} \mid e \in \bigcup_{u \in \mathcal{A}} e_u, o \in \mathcal{O}[u]^r\} \quad (2)$$

$$\mathcal{D} = \{\mathcal{D}_{x_{e,o}} = \{0, 1\} \mid x_{e,o} \in \mathcal{X}\} \quad (3)$$

with $\mathcal{O}[u]^r = \{o \in \theta_r \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\}$ are observations related to request r that can be scheduled on u 's exclusives

- μ associates each variable $x_{e,o}$ to e 's owner

DCOP Model

A DCOP $\langle \mathcal{A}, \mathcal{X}, \mathcal{D}, \mathcal{C}, \mu \rangle$ is defined for a given request r , and a current scheduling

- The agents are the exclusive users which can potentially schedule r :

$$\mathcal{A} = \{u \in \mathcal{U}^{\text{ex}} \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \exists o \in \theta_r \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\} \quad (1)$$

- Each agent u owns binary decision variables, one for each observation $o \in \mathcal{O}[u]^r$ and exclusive e in its exclusives e_u , stating whether it schedules o in e or not:

$$\mathcal{X} = \{x_{e,o} \mid e \in \bigcup_{u \in \mathcal{A}} e_u, o \in \mathcal{O}[u]^r\} \quad (2)$$

$$\mathcal{D} = \{\mathcal{D}_{x_{e,o}} = \{0, 1\} \mid x_{e,o} \in \mathcal{X}\} \quad (3)$$

with $\mathcal{O}[u]^r = \{o \in \theta_r \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\}$ are observations related to request r that can be scheduled on u 's exclusives

- μ associates each variable $x_{e,o}$ to e 's owner

DCOP Model

A DCOP $\langle \mathcal{A}, \mathcal{X}, \mathcal{D}, \mathcal{C}, \mu \rangle$ is defined for a given request r , and a current scheduling

- The agents are the exclusive users which can potentially schedule r :

$$\mathcal{A} = \{u \in \mathcal{U}^{\text{ex}} \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \exists o \in \theta_r \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\} \quad (1)$$

- Each agent u owns binary decision variables, one for each observation $o \in \mathcal{O}[u]^r$ and exclusive e in its exclusives e_u , stating whether it schedules o in e or not:

$$\mathcal{X} = \{x_{e,o} \mid e \in \bigcup_{u \in \mathcal{A}} e_u, o \in \mathcal{O}[u]^r\} \quad (2)$$

$$\mathcal{D} = \{\mathcal{D}_{x_{e,o}} = \{0, 1\} \mid x_{e,o} \in \mathcal{X}\} \quad (3)$$

with $\mathcal{O}[u]^r = \{o \in \theta_r \mid \exists (s, (t_u^{\text{start}}, t_u^{\text{end}})) \in e_u, \text{ s.t. } s_o = s, [t_u^{\text{start}}, t_u^{\text{end}}] \cap [t_o^{\text{start}}, t_o^{\text{end}}] \neq \emptyset\}$ are observations related to request r that can be scheduled on u 's exclusives

- μ associates each variable $x_{e,o}$ to e 's owner

DCOP Model (cont.)

- Constraints should check that at most one observation is scheduled per request (4), that satellites are not overloaded (5), that at most one agent serves the same observation (6)

$$\sum_{e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq 1, \quad \forall u \in \mathcal{X}, \forall o \in \mathcal{O}[u]^r \quad (4)$$

$$\sum_{o \in \{o \in \mathcal{O}[u]^r | u \in \mathcal{A}, s_o = s\}, e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq \kappa_s^*, \quad \forall s \in \mathcal{S} \quad (5)$$

$$\sum_{e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq 1, \quad \forall o \in \mathcal{O} \quad (6)$$

- The cost to integrate an observation in the current user's schedule should be assessed to guide the optimization process

$$c(x_{e,o}) = \pi(o, \mathcal{M}_{u_o}), \quad \forall x_{e,o} \in \mathcal{X} \quad (7)$$

where π evaluates the best cost obtained when scheduling o and any combination of observations from \mathcal{M}_{u_o} , as to consider all possible revisions of u_o 's current schedule

$$\mathcal{C} = \{(4), (5), (6), (7)\} \quad (8)$$

DCOP Model (cont.)

- Constraints should check that at most one observation is scheduled per request (4), that satellites are not overloaded (5), that at most one agent serves the same observation (6)

$$\sum_{e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq 1, \quad \forall u \in \mathcal{X}, \forall o \in \mathcal{O}[u]^r \quad (4)$$

$$\sum_{o \in \{o \in \mathcal{O}[u]^r \mid u \in \mathcal{A}, s_o = s\}, e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq \kappa_s^*, \quad \forall s \in \mathcal{S} \quad (5)$$

$$\sum_{e \in \bigcup_{u \in \mathcal{A}} e_u} x_{e,o} \leq 1, \quad \forall o \in \mathcal{O} \quad (6)$$

- The cost to integrate an observation in the current user's schedule should be assessed to guide the optimization process





$$c(x_{e,o}) = \pi(o, \mathcal{M}_{u_o}), \quad \forall x_{e,o} \in \mathcal{X} \quad (7)$$

where π evaluates the best cost obtained when scheduling o and any combination of observations from \mathcal{M}_{u_o} , as to consider all possible revisions of u_o 's current schedule

$$\mathcal{C} = \{(4), (5), (6), (7)\} \quad (8)$$





Highly conflicting randomly generated problems

5-min horizon with overlapping requests and limited capacity



Realistic randomly generated problems

6-hour horizon with numerous requests and large capacity



Today's Menu

Introduction and Motivations

Coalition Formation on MAS

Distributed Constraint Optimization

Real-World Applications

Conclusion and Wrap-up

Conclusion and Wrap-up

What We've Seen Today

- 2 major multi-agent constraint optimization frameworks: **DCOP, CF**
 - ▶ DCOP: how to **collectively solve** constraint optimization problems
 - ▶ CF: how to **form coalitions/groups** with respect to some criteria and constraints
- Various **techniques and algorithms** to attack these problems
- Examples of **applications** in the transportation, IoT, space and energy domain

Conclusion and Wrap-up

Open questions

Distributed constraint optimization

- How to **decompose or regroup** as to reduce **interactions**?
- How to **structure** the system as to improve **parallelism**?
- How to deploy and make systems robust and resilient in **dynamic environments**?

Coalition formation

- Which other **realistic** scenarios can we model as $m + a$?
- Can we exploit some other **properties** for scenarios that are not $m + a$ (e.g., shared mobility)?
- More in general, how can we **improve** the **scalability** of CF approaches?

Common questions

- How to use DCOPs in CF and vice versa?
- Maintaining libraries and data sets

Special Thanks

Special thanks to all previous contributors to tutorials on multi-agent optimization and related topics, notably

Ferdinando Fioretto, Long Tran-Thanh, Pierre Rust, Enrico Pontelli, William Yeoh, Jesus Cerquides, Juan Antonio Rodriguez Aguilar, Alessandro Farinelli, Pedro Meseguer, Sarvapali Ramchurn, Amnon Meisels

References

-  BACCHUS, Fahiem and Peter VAN BEEK (1998). "On the Conversion between Non-Binary and Binary Constraint Satisfaction Problems". In: *Proceedings of the 15th National Conference on Artificial Intelligence (AAAI-98) and of the 10th Conference on Innovative Applications of Artificial Intelligence (IAAI-98)*. AAAI Press, pp. 311–318.
-  BISTAFFA, Filippo, Christian BLUM, Jesús CERQUIDES, Alessandro FARINELLI, and Juan A RODRÍGUEZ-AGUILAR (2019). "A computational approach to quantify the benefits of ridesharing for policy makers and travellers". In: *IEEE Transactions on Intelligent Transportation Systems* 22.1, pp. 119–130.
-  BISTAFFA, Filippo, Georgios CHALKIADAKIS, and Alessandro FARINELLI (2022). "Efficient Coalition Structure Generation via Approximately Equivalent Induced Subgraph Games". In: *IEEE transactions on cybernetics* 52.6, pp. 5548–5558.
-  BISTAFFA, Filippo and Alessandro FARINELLI (2018). "A COP model for graph-constrained coalition formation". In: *Journal of Artificial Intelligence Research* 62, pp. 133–153.
-  BISTAFFA, Filippo, Alessandro FARINELLI, Jesús CERQUIDES, Juan RODRÍGUEZ-AGUILAR, and Sarvapali D RAMCHURN (2017a). "Algorithms for graph-constrained coalition formation in the real world". In: *ACM Transactions on Intelligent Systems and Technology* 8.4, pp. 1–24.
-  BISTAFFA, Filippo, Alessandro FARINELLI, Georgios CHALKIADAKIS, and Sarvapali D. RAMCHURN (2017b). "A cooperative game-theoretic approach to the social ridesharing problem". In: *Artificial Intelligence* 246, pp. 86–117.
-  CHALKIADAKIS, Georgios, Edith ELKIND, and Michael WOOLDRIDGE (2011). *Computational aspects of cooperative game theory*. Morgan & Claypool Publishers.

References (cont.)



CHOWDHURY, Moumita, Saaduddin MAHMUD, and Md. Mosaddek KHAN (2020). "A Particle Swarm Based Algorithm for Functional Distributed Constraint Optimization Problems". In: *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*. AAAI Press, pp. 7111–7118. URL: <https://ojs.aaai.org/index.php/AAAI/article/view/6198>.



DECHTER, Rina (2003). *Constraint Processing*. Morgan Kaufmann.



DELLE FAVE, F.M., R. STRANDERS, A. ROGERS, and N.R. JENNINGS (2011). "Bounded Decentralised Coordination over Multiple Objectives". In: *The 10th International Conference on Autonomous Agents and Multiagent Systems (AAMAS '11)*, pp. 371–378.



DEMANGE, Gabrielle (2004). "On group stability in hierarchies and networks". In: *Journal of Political Economy* 112.4, pp. 754–778.



DENG, Xiaotie and Christos H PAPADIMITRIOU (1994). "On the Complexity of Cooperative Solution Concepts". In: *Mathematics of Operations Research* 19.2, pp. 257–266.



FARINELLI, A., A. ROGERS, A. PETCU, and N. R. JENNINGS (2008). "Decentralised Coordination of Low-power Embedded Devices Using the Max-sum Algorithm". In: *Proceedings of the 7th International Joint Conference on Autonomous Agents and Multiagent Systems - Volume 2*. AAMAS '08. International Foundation for Autonomous Agents and Multiagent Systems, pp. 639–646. ISBN: 978-0-9817381-1-6.



FARINELLI, Alessandro, Manuele BICEGO, Sarvapali RAMCHURN, and Mauro ZUCCELLI (2013). "C-link: A hierarchical clustering approach to large-scale near-optimal coalition formation". In: *Twenty-third international joint conference on artificial intelligence*.

References (cont.)

-  FIORETTI, F., E. PONTELLI, and W. YEOH (2018). "Distributed Constraint Optimization Problems and Applications: A Survey". In: *Journal of Artificial Intelligence Research* 61, pp. 623–698.
-  FITZPATRICK, Stephen and Lambert MEERTENS (2003). "Distributed Coordination through Anarchic Optimization". In: *Distributed Sensor Networks: A Multiagent Perspective*. Ed. by Victor LESSER, Charles L. ORTIZ, and Milind TAMBE. Boston, MA: Springer US, pp. 257–295. ISBN: 978-1-4615-0363-7.
-  GRINSHPOUN, T., A. GRUBSHTAIN, R. ZIVAN, A. NETZER, and A. MEISELS (2013). "Asymmetric Distributed Constraint Optimization Problems". In: *J. Artif. Int. Res.* 47.1, pp. 613–647. ISSN: 1076-9757. URL: <http://dl.acm.org/citation.cfm?id=2566972.2566988>.
-  HIRAYAMA, K. and M. Yokoo (1997). "Distributed partial constraint satisfaction problem". In: *Principles and Practice of Constraint Programming-CP97*. Springer, pp. 222–236. ISBN: 978-3-540-69642-1.
-  — (2005). "The distributed breakout algorithms". In: *Artificial Intelligence* 161.1-2, pp. 89–115. ISSN: 0004-3702.
-  HOANG, Khoi D., William YEOH, Makoto YOKOO, and Zinovi RABINOVICH (2020). "New Algorithms for Continuous Distributed Constraint Optimization Problems". In: *Proceedings of the 19th International Conference on Autonomous Agents and MultiAgent Systems*. AAMAS '20. Auckland, New Zealand: International Foundation for Autonomous Agents and Multiagent Systems, p. 502510. ISBN: 9781450375184.
-  LÉAUTÉ, T. and B. FALTINGS (2011). "Distributed Constraint Optimization Under Stochastic Uncertainty". In: *Proceedings of the Twenty-Fifth AAAI Conference on Artificial Intelligence (AAAI'11)*. AAAI Press, pp. 68–73. URL: <http://dl.acm.org/citation.cfm?id=2900423.2900434>.

References (cont.)

-  LÉAUTÉ, Thomas, Brammert OTTENS, and Radoslaw SZYMANEK (2009). "FRODO 2.0: An Open-Source Framework for Distributed Constraint Optimization". In: *Proceedings of the IJCAI'09 Distributed Constraint Reasoning Workshop (DCR'09)*. <https://frodo-ai.tech>. Pasadena, California, USA, pp. 160–164.
-  LUTATI, Benny, Inna GONTMAKHER, Michael LANDO, Arnon NETZER, Amnon MEISELS, and Alon GRUBSHTAIN (2014). "AgentZero: A framework for simulating and evaluating multi-agent algorithms". In: *Agent-Oriented Software Engineering: Reflections on Architectures, Methodologies, Languages, and Frameworks*. Vol. 9783642544323. ISBN: 9783642544323. DOI: 10.1007/978-3-642-54432-3_16.
-  MAHESWARAN, R.T., J.P. PEARCE, and M. TAMBE (2004). "Distributed Algorithms for DCOP: A Graphical-Game-Based Approach". In: *Proceedings of the 17th International Conference on Parallel and Distributed Computing Systems (PDCS), San Francisco, CA*, pp. 432–439.
-  MAILLER, R. (2005). "Comparing two approaches to dynamic, distributed constraint satisfaction". In: *Proceedings of the Fourth International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS'05)*. ACM Press, pp. 1049–1056.
-  MAILLER, R. and V. LESSER (2004a). "Solving Distributed Constraint Optimization Problems Using Cooperative Mediation". In: *Proceedings of Third International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS'04)*. IEEE Computer Society, pp. 438–445.
-  — (2004b). "Using Cooperative Mediation to Solve Distributed Constraint Satisfaction Problems". In: *Proceedings of Third International Joint Conference on Autonomous Agents and MultiAgent Systems (AAMAS'04)*. Vol. 1. IEEE Computer Society, pp. 446–453.

References (cont.)

-  MAILLER, R. and V. R. LESSER (2006). "Asynchronous Partial Overlay: A New Algorithm for Solving Distributed Constraint Satisfaction Problems". In: *Journal of Artificial Intelligence Research* 25, pp. 529–576.
-  MATSUI, T., M. SILAGHI, K. HIRAYAMA, M. YOKOO, and H. MATSUO (2012). "Distributed Search Method with Bounded Cost Vectors on Multiple Objective DCOPs". In: *PRIMA 2012: Principles and Practice of Multi-Agent Systems*. Springer, pp. 137–152. ISBN: 978-3-642-32729-2.
-  MEDI, A., T. OKIMOTO, and K. INOUE (July 2014). "A two-phase complete algorithm for multi-objective distributed constraint optimization". In: 18, pp. 573–580.
-  MODI, P. J., W. SHEN, M. TAMBE, and M. YOKOO (2005). "ADOPT: Asynchronous Distributed Constraint Optimization with Quality Guarantees". In: *Artificial Intelligence* 161.2, pp. 149–180.
-  MYERSON, Roger B (1977). "Graphs and cooperation in games". In: *Mathematics of operations research* 2.3, pp. 225–229.
-  NGUYEN, D.T., W. YEOH, and H.C. LAU (2012). "Stochastic Dominance in Stochastic DCOPs for Risk-sensitive Applications". In: *Proceedings of the 11th International Conference on Autonomous Agents and Multiagent Systems (AAMAS '12)*. Valencia, Spain, pp. 257–264. ISBN: 0-9817381-1-7, 978-0-9817381-1-6. URL: <http://dl.acm.org/citation.cfm?id=2343576.2343613>.
-  OKIMOTO, T., M. CLEMENT, and K. INOUE (2013). "AOF-Based Algorithm for Dynamic Multi-Objective Distributed Constraint Optimization". In: *Proceedings of the 7th International Workshop on Multi-disciplinary Trends in Artificial Intelligence (MIWAI'13)*. Springer, pp. 175–186. ISBN: 978-3-642-44948-2. DOI: 10.1007/978-3-642-44949-9_17. URL: http://dx.doi.org/10.1007/978-3-642-44949-9_17.

References (cont.)

-  PETCU, A. and B. FALTINGS (2005a). "Superstabilizing, Fault-containing Distributed Combinatorial Optimization". In: *Proceedings of the 20th National Conference on Artificial Intelligence (AAAI'05)*. AAAI Press, pp. 449–454. ISBN: 1-57735-236-x. URL: <http://dl.acm.org/citation.cfm?id=1619332.1619405>.
-  PETCU, Adrian and Boi FALTINGS (2005b). "A scalable method for multiagent constraint optimization". In: *IJCAI International Joint Conference on Artificial Intelligence*, pp. 266–271. ISBN: 1045-0823.
-  PICARD, G. and P. GLIZE (2006). "Model and Analysis of Local Decision Based on Cooperative Self-Organization for Problem Solving". In: *Multiagent and Grid Systems (MAGS) 2.3*, pp. 253–265.
-  PICARD, Gauthier (2022). "Auction-based and Distributed Optimization Approaches for Scheduling Observations in Satellite Constellations with Exclusive Orbit Portions". In: *International Conference on Autonomous Agents and Multiagent Systems (AAMAS-22)*. IFAAMAS.
-  RAHWAN, Talal, Tomasz P MICHALAK, Michael WOOLDRIDGE, and Nicholas R JENNINGS (2015). "Coalition structure generation: A survey". In: *Artificial Intelligence* 229, pp. 139–174.
-  RAMCHURN, S. D., A. FARINELLI, K. S. MACARTHUR, and N. R. JENNINGS (2010). "Decentralized Coordination in RoboCup Rescue". In: *Comput. J.* 53.9, pp. 1447–1461. ISSN: 0010-4620. DOI: 10.1093/comjnl/bxq022. URL: <http://dx.doi.org/10.1093/comjnl/bxq022>.
-  RUSSEL, S. and P. NORVIG (1995). *Artificial Intelligence: a Modern Approach*. Prentice-Hall.

References (cont.)

-  RUST, Pierre, Gauthier PICARD, and Fano RAMPARANY (2016). "Using Message-passing DCOP Algorithms to Solve Energy-efficient Smart Environment Configuration Problems". In: *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence (IJCAI-16)*. Ed. by S. KAMBHAMPATI. AAAI Press, pp. 468–474. URL: <http://www.ijcai.org/Proceedings/2016/>.
-  — (2017). "On the Deployment of Factor Graph Elements to Operate Max-Sum in Dynamic Ambient Environments". In: *Autonomous Agents and Multiagent Systems – AAMAS 2017 Workshops, Best Papers, Sao Paulo, Brazil, May 8-12, 2017, Revised Selected Papers*. Ed. by G. SUKTHANKAR and J.A. RODRIGUEZ-AGUILAR. Vol. 10642. Lecture Notes in Artificial Intelligence (LNAI). Extended Version. Springer, pp. 116–137. doi: [10.1007/978-3-319-71682-4_8](https://doi.org/10.1007/978-3-319-71682-4_8).
-  — (2018). "Self-Organized and Resilient Distribution of Decisions over Dynamic Multi-Agent Systems". In: *International Workshop on Optimisation in Multi-Agent Systems (OptMAS@AAMAS 2018)*. URL: http://www-personal.umich.edu/~fioretto/cfp/OPTMAS18/papers/paper_13.pdf.
-  — (2019). "pyDCOP, a DCOP library for IoT and dynamic systems". In: *International Workshop on Optimisation in Multi-Agent Systems (OptMAS@AAMAS 2019)*.
-  — (2020). "Resilient Distributed Constraint Optimization in Physical Multi-Agent Systems". In: *European Conference on Artificial Intelligence (ECAI)*. Vol. 325. Frontiers in Artificial Intelligence and Applications. IOS Press, pp. 195–202. doi: [10.3233/FAIA200093](https://doi.org/10.3233/FAIA200093). URL: http://ecai2020.eu/papers/108_paper.pdf.
-  — (2022). "Resilient Distributed Constraint Reasoning to Autonomously Configure and Adapt IoT Environments". In: *ACM Transactions on Internet of Things*. in press. doi: <http://dx.doi.org/10.1145/3507907>.

References (cont.)

-  SARKER, Amit, Moumita CHOUDHURY, and Md. Mosaddek KHAN (2021). "A Local Search Based Approach to Solve Continuous DCOPs". In: *Proceedings of the 20th International Conference on Autonomous Agents and MultiAgent Systems*. AAMAS '21. Virtual Event, United Kingdom: International Foundation for Autonomous Agents and Multiagent Systems, p. 11271135. ISBN: 9781450383073.
-  SHEHORY, Onn and Sarit KRAUS (May 1998). "Methods for Task Allocation via Agent Coalition Formation". In: *Artificial Intelligence* 101.1-2, pp. 165–200.
-  SHOHAM, Y. and K. LEYTON-BROWN (2008). *Multiagent Systems: Algorithmic, Game-Theoretic, and Logical Foundations*. Cambridge University Press.
-  STRANDERS, R., F.M. DELLE FAVE, A. ROGERS, and N.R. JENNINGS (2011). "U-GDL: A decentralised algorithm for DCOPs with Uncertainty". Project Report. URL: <https://eprints.soton.ac.uk/273037/>.
-  STRANDERS, R., A. FARINELLI, A. ROGERS, and N. R. JENNINGS (2009). "Decentralised Coordination of Continuously Valued Control Parameters Using the Max-Sum Algorithm". In: *Proceedings of The 8th International Conference on Autonomous Agents and Multiagent Systems - Volume 1*. AAMAS '09. Budapest, Hungary: International Foundation for Autonomous Agents and Multiagent Systems, p. 601608. ISBN: 9780981738161.
-  VINYALS, Meritxell, Juan A. RODRÍGUEZ-AGUILAR, and Jesus CERQUIDES (2011). "Constructing a unifying theory of dynamic programming DCOP algorithms via the generalized distributive law". In: *Autonomous Agents and Multi-Agent Systems* 3.22, pp. 439–464. ISSN: 1387-2532. DOI: 10.1007/s10458-010-9132-7.
-  VOICE, Thomas, Ruben STRANDERS, Alex ROGERS, and Nicholas R. JENNINGS (2010). "A Hybrid Continuous Max-Sum Algorithm for Decentralised Coordination". In: *Proceedings of the 2010 Conference on ECAI 2010: 19th European Conference on Artificial Intelligence*. NLD: IOS Press, p. 6166. ISBN: 9781607506058.

References (cont.)

-  WAHBI, Mohamed, Redouane EZZAHIR, Christian BESSIÈRE, and El Houssine BOUYAKHF (2011). "DisChoco 2: A Platform for Distributed Constraint Reasoning". In: *Proceedings of the IJCAI'11 workshop on Distributed Constraint Reasoning*. DCR'11. Barcelona, Catalonia, Spain, pp. 112–121. URL: <http://dischoco.sourceforge.net/>.
-  YEOH, W., P. VARAKANTHAM, X. SUN, and S. KOENIG (2011). "Incremental DCOP Search Algorithms for Solving Dynamic DCOPs". In: *The 10th International Conference on Autonomous Agents and Multiagent Systems (AAMAS '11)*, pp. 1069–1070. ISBN: 0-9826571-7-X, 978-0-9826571-7-1.
-  YOKOO, M. (1994). "Weak-Commitment Search for Solving Constraint Satisfaction Problems". In: *Proceedings of the 12th National Conference on Artificial Intelligence (AAAI-94)*. AAAI Press, pp. 313–318.
-  — (2001). *Distributed Constraint Satisfaction: Foundations of Cooperation in Multi-Agent Systems*. Springer.
-  ZHANG, W., G. WANG, Z. XING, and L. WITTENBURG (2005). "Distributed stochastic search and distributed breakout: properties, comparison and applications to constraint optimization problems in sensor networks.". In: *Journal of Artificial Intelligence Research (JAIR)* 161.1-2, pp. 55–87.
-  ZHANG, Weixiong, Guandong WANG, Zhao XING, and Lars WITTENBURG (2003). "A Comparative Study of Distributed Constraint Algorithms". In: *Distributed Sensor Networks: A Multiagent Perspective*. Ed. by Victor LESSER, Charles L. ORTIZ, and Milind TAMBE. Boston, MA: Springer US, pp. 319–338.