

## 00. INTRODUCTION

### data compression

- types of compression
  - lossless compression** - can recover the contents
  - lossy compression** - lose some quality - cannot convert back to the higher-quality version
- examples
  - sparse binary string - storing positions of 1s
  - equal number of 0/1s -  $L \geq \log_2 \binom{64}{32} \approx 60.7$
  - english text - using relative frequency
  - morse code is NOT binary (contains spaces)
- info theory uses **probabilistic models** (letter frequency, sequence probabilities)
- 2 distinct approaches to compression:
  - variable length** - map more probable sequences to shorter binary strings
  - fixed length** - map most probable sequences to strings of a given length
    - insufficient strings for low-probability sequences
    - tradeoff between length/failure probability


### information theory concepts

- speed: **rate**  $\rightarrow \frac{k}{n}$  (mapping  $k$  bits to  $n$  bits)
- reliability:  $\mathbb{P}[\text{error}] = \mathbb{P}[\text{estimated msg} \neq \text{true msg}]$
- source coding theorem**  $\rightarrow$  the fundamental compression limit is given by a source-dependent quantity known as the **(Shannon) entropy**  $H$ . The (average) storage length can be arbitrarily close to  $H$ , but can never be any lower than  $H$ .
  - $H$  is a property of the *probability distribution*
- channel coding theorem**  $\rightarrow$  there exists a channel-dependent quantity called the **(Shannon) capacity**  $C$  such that arbitrarily small error probability can be achieved only for rates  $< C$ 
  - can achieve  $\mathbb{P}[\text{error}] \leq \epsilon \iff \text{rate} < C$

### data communication example

- a "transmitter" sends a sequence of 0s and 1s
- a "receiver" sends a sequence *with some corruptions*

### channel transition diagram



- each bit is flipped independently with probability  $\delta \in (0, \frac{1}{2})$


### naive

- uncoded communication** -  $\mathbb{P}[\text{correct}] = (1 - \delta)^N$
- repetition code** - transmit "000" for "0", "111" for "1"
  - $\mathbb{P}[\text{correct}] = [(1 - \delta)^3 + 3\delta(1 - \delta)^2]^N$
  - more reliable but 3x slower!

### Hamming code

- able to correct one bit flip
- maps binary string of length 4 to binary string of length 7

- fill in  $b_1 b_2 b_3 b_4$  and assign  $c_1 c_2 c_3$  such that the sum of bits in each circle is even



- $\mathbb{P}[\text{correct}] \geq \mathbb{P}[\leq 1 \text{ bit flips}] = (1 - \delta)^7 + 7\delta(1 - \delta)^6$
- with  $\delta = 1$ : Shannon capacity  $C \approx 0.531$

## 01. INFORMATION MEASURES


### information of an event

- entropy**  $\rightarrow$  measure of "uncertainty" or "information" in a random variable
- given event  $A$  with some  $\mathbb{P}[A] = p$ , how much "information" learned by being told  $A$  occurred?
  - only  $\mathbb{P}[A]$  matters
- if  $A$  occurs with probability  $p$ , then  $\text{Information}(A) = \psi(p)$  for some function  $\psi(\cdot)$

### axioms for $\psi(\cdot)$

$$\psi(p) = \log_b \frac{1}{p} \text{ (for some base } b > 0)$$

we gain  $\log_2 \frac{1}{p}$  "bits" of info if a probability- $p$  event occurs.



- only  $\psi(p) = \log_b \frac{1}{p}$  satisfies all axioms
- we focus on  $b = 2$ 
  - information measured in bits
- all choices of  $b$  are equivalent up to scaling by a universal constant
  - e.g. # of nats =  $\log_e 2 \times$  # of bits

- $\psi(p) \geq 0$  (**non-negativity**)
- $\psi(1) = 0$  (**zero for definite events**)
- if  $p \leq p'$ , then  $\psi(p) \geq \psi(p')$  (**monotonicity**)
  - the less likely an event is, the more information was learnt by the fact that it occurred
- $\psi(p)$  in continuous in  $p$  (**continuity**)
  - small change in probability: no drastic change in info
- $\psi(p_1 p_2) = \psi(p_1) + \psi(p_2)$  (**additivity under independence**) if  $A$  and  $B$  are independent events with probabilities  $p_1$  and  $p_2$ , then  $\mathbb{P}[A \cap B] = p_1 p_2$ , and the information learnt from both  $A$  and  $B$  occurring is the sum of the two individual amounts of information (because they are independent)
  - $\psi(\mathbb{P}[A_1 \cap A_2]) = \psi(\mathbb{P}[A_1]) + \psi(\mathbb{P}[A_2])$

### information of a random variable - entropy

- let  $X$  be a discrete r.v. with pmf  $P_X$
- if we observe  $X = x$  then we have learnt  $\log_2 \frac{1}{P_X(x)}$  bits of information

#### (Shannon) entropy

is the average *information/uncertainty* in  $X$  wrt  $P_X$ :

$$H(X) = \mathbb{E}_{X \sim P_X} \left[ \log_2 \frac{1}{P_X(X)} \right] = \sum_x P_X(x) \log_2 \frac{1}{P_X(x)}$$

### • binary entropy function $\rightarrow$

$$H_2(p) = p \log_2 \frac{1}{p} + (1 - p) \log_2 \frac{1}{1 - p}$$

#### • e.g.

- binary source:  $X \sim \text{Bernoulli}(p)$ ,  $p \in (0, 1)$ 

$$\Rightarrow H(X) = H_2(p)$$
- uniform source:  $X$  is uniform on a finite set  $\mathcal{X}$ 

$$P_X(x) = \frac{1}{|\mathcal{X}|}$$

$$\Rightarrow H(X) = \mathbb{E} \left[ \log_2 \frac{1}{1/|\mathcal{X}|} \right] = \log_2 |\mathcal{X}|$$

#### • entropy $\neq$ variance

- entropy depends *only* on the probability values

### axiomatic view (Shannon)

$X$  is a d.r.v. taking  $N$  values with  $\mathbf{p} = (p_1, \dots, p_N)$ . We consider a general information measure of the form

$$\Phi(\mathbf{p}) = \Phi(p_1, \dots, p_N)$$

only  $\Phi(X) = \text{constant} \times H(X)$  satisfies all axioms.

- $\Psi(\mathbf{p})$  is continuous on  $p$  (**continuity**)
- if  $p_i = \frac{1}{N}$ , then  $\Psi(\mathbf{p})$  is increasing in  $N$  (**uniform case**)
  - uniformity over a larger set of outcomes always means more uncertainty
- (successive decisions)**  $\Psi(p_1, \dots, p_N) = \Psi(p_1 + p_2, p_3, \dots, p_N) + (p_1 + p_2) \Psi(\frac{p_1}{p_1 + p_2}, \frac{p_2}{p_1 + p_2})$

### variations

- joint entropy** of two random variables  $(X, Y) \rightarrow$

$$H(X, Y) = \mathbb{E}_{(X, Y) \sim P_{XY}} \left[ \log_2 \frac{1}{P_{XY}(X, Y)} \right] = \sum_{x, y} P_{XY}(x, y) \log_2 \frac{1}{P_{XY}(x, y)}$$

- conditional entropy** of  $Y$  given  $X \rightarrow$

$$H(Y|X) = \mathbb{E}_{(X, Y) \sim P_{XY}} \left[ \log_2 \frac{1}{P_{Y|X}(Y|X)} \right] = \sum_{x, y} P_{XY}(x, y) \log_2 \frac{1}{P_{Y|X}(y|x)} = \sum_x P_X(x) H(Y|X = x)$$

- on average, knowing  $X$  reduces uncertainty about  $Y$  ( $H(Y|X) \leq H(Y)$ ), but seeing a *specific* outcome of  $X$  may increase uncertainty about  $Y$  ( $H(Y|X = i) > H(Y)$  for some values of  $i$ )

### properties of entropy

- $H(X) \geq 0$  (**non-negativity**)
  - $H(X) = 0 \iff X$  if deterministic
  - Proof.* information  $\log_2 \frac{1}{p} \geq 0$  for  $p \in [0, 1]$ , so entropy is the average of a non-negative quantity, and itself is non-negative
- $H(X) \leq \log_2 |\mathcal{X}|$  (**upper bound**)
  - if  $X$  takes values on a finite alphabet  $\mathcal{X}$
  - $H(X) = \log_2 |\mathcal{X}| \iff X \sim \text{Uniform}(\mathcal{X})$
  - implies  $H(X|Y) \leq \log_2 |\mathcal{X}|$
- $H(X, Y) = H(X) + H(Y|X)$  (**chain rule**)
  - or  $H(X, Y) = H(Y) + H(X|Y)$

- overall information in  $(X, Y)$  is the information in  $X$  plus the remaining information in  $Y$  after observing  $X$ .
- general chain rule:  $H(X_1, \dots, X_n) = \sum_{i=1}^n H(X_i | X_1, \dots, X_{i-1})$
- $H(X|Y) \leq H(X)$  (**conditioning reduces entropy**)
  - $H(X|Y) = H(X) \iff X$  and  $Y$  are independent
  - additional information  $Y$  can't increase uncertainty on average but can have  $H(X|Y = y) > H(X)$
- $H(X_1, \dots, X_n) \leq \sum_{i=1}^n H(X_i)$  (**sub-additivity**)
  - equality  $\iff X$  and  $Y$  are independent

## KL Divergence

for two pmfs  $P$  and  $Q$  on a finite alphabet  $\mathcal{X}$ , the **Kullback-Leibler (KL) divergence** or **relative entropy** is given by

$$D(P||Q) = \sum_x P(x) \log_2 \frac{P(x)}{Q(x)} = \mathbb{E}_{X \sim P} \left[ \log_2 \frac{P(X)}{Q(X)} \right]$$

- $D(P||Q) \neq D(Q||P)$
- $D(P||Q) \geq 0$ 
  - Proof.*  $-D(P||Q) = -\sum_x P(x) \log_2 \frac{P(x)}{Q(x)} \leq \sum_x P(x) (\frac{Q(x)}{P(x)} - 1) = \sum_x Q(x) - \sum_x P(x) = 0$  (using property that  $x - 1 > \ln x$ )
- $D(P||Q) = 0 \iff P = Q$ 
  - Proof.* same as above, using  $\ln a = a - 1 \iff a = 1$  (then  $\frac{P(x)}{Q(x)} = 1$ )

## 02. SYMBOL-WISE SOURCE CODING

$X$  is a d.r.v. with pmf  $P_X$  over an alphabet  $\mathcal{X}$  (set of symbols).

**symbol-wise source coding** maps each  $x \in \mathcal{X}$  to some binary sequence  $C(x)$  of length  $\ell(x)$ .

**average length** of a code  $C(\cdot)$ ,

$$L(C) = \sum_{x \in \mathcal{X}} P_X(x) \ell(x)$$

### decodability conditions

- nonsingular property**  $\rightarrow C(x) \neq C(x') \iff x \neq x'$
- a code  $C(\cdot)$  is **uniquely decodable**  $\rightarrow$  no 2 sequences (of equal or differing lengths) of symbols in  $\mathcal{X}$  are coded to the same concatenated binary sequence.
  - $x_1, \dots, x_n$  can be always uniquely identified from the string  $C(x_1) \dots C(x_n)$
- $C(\cdot)$  is **prefix-free**  $\rightarrow$  no codeword is a prefix of another
  - aka **instantaneous code**

## Kraft's Inequality and Entropy Bound

### Kraft's inequality

if  $C(\cdot)$  is *prefix-free*, then  $\sum_{x \in \mathcal{X}} 2^{-\ell(x)} \leq 1$

- Proof.* represent the codewords by a binary tree. If there is a codeword at some point in the tree, there are no codewords further down the tree. probability of branching to a codeword  $= 2^{-\ell(x)}$  and sum of probabilities cannot exceed 1
- existence property**  $\rightarrow$  if a set of integers  $\{\ell(x)\}_{x \in \mathcal{X}}$  satisfies  $\sum_{x \in \mathcal{X}} 2^{-\ell(x)} \leq 1$ , then it is possible to construct a *prefix-free* code that maps each  $x \in \mathcal{X}$  to a codeword of length  $\ell(x)$ .

entropy bound

- entropy bound
- expected length,  $L(C) \geq H(X)$
- with equality  $\iff P_X(x) = 2^{-\ell(x)}$
- entropy gives a *fundamental compression limit*
    - average length is at least equal to entropy
    - if all probabilities are negative powers of 2, we can match the entropy bound (optimal code)
  - Proof.* manipulate to get  $L(C) - H(X) \geq D(P_X || Q) \geq 0$