

# CS2030S cheatsheet (1)

## TYPES

- **S is a subtype of T**, `S <: T` if a piece of code written for variables of type `S` can also be safely used on variables of type `T`.
  - *widening* conversion  $\Rightarrow$  a type `S` can be put into a variable of type `T` if `S <: T`.
  - *narrowing* conversion  $\Rightarrow$  requires typecasting
- **reflexive** - `T <: T`
- **transitive** - if `S <: T` and `T <: U`, then `S <: U`
- `S instanceof T` returns true if `S <: T`

## primitive types

```
byte <: short <: int <: long <: float <: double
char <: int
```

## Liskov substitution principle

- if `S <: T`, then
  - any property of `T` should also be a property of `S`. (includes fields, methods)
  - an object of type `T` can be replaced by an object of type `S` without changing some desirable property of the program.

## RUN-TIME vs COMPILE-TIME TYPES

```
Circle c = new ColouredCircle(p, 0, red);
// ColouredCircle <: Circle
```

- compile-time type: `Circle`
- run-time type: `ColouredCircle`



`this` - reference variable that refers to the instance

## JAVA

### access modifiers

`private`  $\rightarrow$  only within the class

`default`  $\rightarrow$  only within the package

`protected`  $\rightarrow$  only within the package or outside the package through the child class

`public`  $\rightarrow$  everywhere

### the `Object` class

- provides `equals(Object obj)` and `toString()`

`final`

- `final` class  $\rightarrow$  cannot be inherited from
- `final` method  $\rightarrow$  cannot be overridden

## OOP PRINCIPLES

### encapsulation

- composite data types
- abstraction barrier - hide information & implementation
- `private` attributes, `public` methods

### inheritance

- "is-a" relationship  $\rightarrow$  `extends` (subtyping)
- vs "has-a" relationship  $\rightarrow$  use composition

### tell, don't ask

- abstract out computation

### method overriding

- same method signature (method name + type of arguments)

### polymorphism

- **dynamic binding**  $\rightarrow$  method invoked is determined at runtime

## ABSTRACT CLASSES

```
abstract class Shape { ... }
```

- cannot be inherited
- a concrete class cannot have abstract methods
  - as long as one method is abstract, the whole class is abstract
- an abstract class can have concrete and/or abstract methods

## INTERFACE

```
interface getAreable {
    // methods are public and abstract by default
    double getArea();
}
```

- abstract class
  - concrete classes implementing the interface have to implement the body of the methods
- if class `C` implements interface `I`, then `C <: I`.
- a class can extend multiple interfaces

```
class C implements A, B { ... }
```

- an interface can extend multiple interfaces

```
interface I extends A, B { ... }
```

- an interface cannot implement other interfaces (abstract!!)

## WRAPPER CLASS

```
Integer i = new Integer(2);
int j = i.intValue();
```

### (un)boxing

```
int i = 1;      // i is an int
Integer j = i;  // j is an Integer
int k = j;      // k is an int
```

- compile-time type: `Circle`
- run-time type: `ColouredCircle`

## CASTING

```
// Circle <: Shape <: GetAreable
GetAreable findLargest(GetAreable[] array) { ... }
GetAreable ga = findLargest(circles); // ok
Circle c1 = findLargest(circles); // error
Circle c2 = (Circle) findLargest(circles); // ok
```

- only cast when you can prove that it is safe

### variance

Let  $C(T)$  be a complex type based on type  $T$ . The complex type  $C$  is:

- **covariant** if  $S <: T$  implies  $C(S) <: C(T)$
- **contravariant** if  $S <: T$  implies  $C(T) <: C(S)$
- **invariant** if  $C$  is neither covariant nor contravariant

(Java array is covariant)

## EXCEPTIONS

```
try {
    new Circle(new Point(1, 1), 0);
    // everything afterwards is skipped
    System.out.println("This will never reach");
} catch (IllegalArgumentException e) {
    // runs if there is an exception
} finally {
    // always runs
}
```

- exception will be passed up the call stack until it is caught
- after exception is caught: everything else proceeds normally

### `throw` exceptions

```
public Circle(Point c, double r) throws IllegalArgumentException {
    if (r < 0) {
        throw new IllegalArgumentException("radius cannot be negative.");
    }
    // anything from here will not run if r<0
}
```

- `throw` causes method to immediately return

## GENERICIS

- allow classes/methods (that use reference types) to be defined without resorting to using the Object type.
  - ensures **type safety** → binds a generic type to a specific type at compile time
  - ✓ errors will be at compile time instead of runtime
- generics are **invariant** in Java

### generic class

```
class Pair<S extends Comparable<S>, T> implements Comparable<Pair<S, T>> {...}
class DictEntry<T> extends Pair<String,T> {...}
```

### generic method

```
public static <T> boolean contains(T[] arr, T obj) {...}
// to call a generic method:
A.<String>contains(strArray, "hello");
```

- type parameter `<T>` is declared *before* the return type

## TYPE ERASURE

### type erasure

- at compile time, type parameters are replaced by `Object` or the bounds (e.g. `T extends Shape` is replaced by `Shape`)

### suppress warnings

- `@SuppressWarnings` can only apply to declaration

```
@SuppressWarnings("unchecked")
T[] a = (T[]) new Object[size];
this.array = a;
```



### PECS PRINCIPLE

Producer `extends`; Consumer `super`

## WILDCARDS

### upper-bounded: `? extends`

- covariant* - if `S <: T`, then `A<? extends S> <: A<? extends T>`

### lower-bounded: `? super`

- contravariant* - if `S <: T`, then `A<? super T> <: A<? super S>`

### unbounded: `?`

- `Array<?>` is the supertype of all generic `Array<T>`

## RAW TYPES

- a generic type used without type arguments
- only acceptable as an operand of `instanceof`

## TYPE INFERENCE

### diamond operator: `<>`

```
Pair<String,Integer> p = new Pair<>();
```

- only for instantiating a generic type - not as a type
- generic methods: type inference is automatic
  - `A.contains()` not `A.<>contains()`

### constraints for type inference

- target typing → the type of the expression (e.g. `Shape`)
- type parameter bounds → `<T extends GetAreable>`
- parameter bounds → `Array<Circle> <: Array<? extends T>`, so `T :> Circle`

```
public static <T extends GetAreable> T findLargest(Array<? extends T> array)
Shape o = A.findLargest(new Array<Circle>(0));
```