deeplearning.ai

Setting up your optimization problem

Gradient Checking

Gradient check for a neural network

Take $W^{[1]}, b^{[1]}, \ldots, W^{[L]}, b^{[L]}$ and reshape into a big vector θ.

concatenate

$J(W^{[1]}, b^{[1]}, \ldots, W^{[L]}, b^{[L]}) = J(\theta)$

Take $dW^{[1]}, db^{[1]}, \ldots, dW^{[L]}, db^{[L]}$ and reshape into a big vector $d\theta$.

concatenate

Is $d\theta$ the gradient of $J(\theta)$?

Gradient checking (Grad check)

$J(\theta) = J(\theta_1, \theta_2, \theta_3, \ldots)$

for each i:

$$\rightarrow d\theta_{approx}[i] = \frac{J(\theta_1, \theta_2, \ldots, \theta_i + \varepsilon, \ldots) - J(\theta_1, \theta_2, \ldots, \theta_i - \varepsilon, \ldots)}{2\varepsilon}$$

$$\approx d\theta[i] = \frac{\partial J}{\partial \theta_i}$$

$d\theta_{approx} \overset{?}{\approx} d\theta$

Check $\dfrac{\|d\theta_{approx} - d\theta\|_2}{\|d\theta_{approx}\|_2 + \|d\theta\|_2}$

$\varepsilon = 10^{-7}$

$\approx 10^{-7}$ — great! ←

10^{-5}

$\rightarrow 10^{-3}$ — worry. ←

Andrew Ng

deeplearning.ai

Setting up your optimization problem

Gradient Checking implementation notes

Gradient checking implementation notes

- Don't use in training – only to debug

$d\theta_{approx}[i] \approx d\theta[i]$

- If algorithm fails grad check, look at components to try to identify bug.

$db^{[l]}$ $dW^{[l]}$

- Remember regularization.

$J(\theta) = \frac{1}{m} \sum_i \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2m} \sum_l \|W^{[l]}\|_F^2$

$d\theta$ = gradient of J wrt. θ

- Doesn't work with dropout.

J keep-prob = 1.0

- Run at random initialization; perhaps again after some training.

$W, b \approx 0$