

Application Laboratory

Lecture 03

R.S. Madanayake

Shutdown and Reboot

- Shutdown `-h now`
- Shutdown `-r now`
- In some Linux systems; `poweroff`, `reboot`

The vi editor

\$ vi <filename> — Open or edit a file.

i — Switch to Insert mode.

Esc — Switch to Command mode.

:w — Save and continue editing.

:wq or ZZ — Save and quit/exit vi.

:q! — Quit vi and do not save changes.

yy — Yank (copy) a line of text.

p — Paste a line of yanked text below the current line.

- p — Paste a line of yanked text below the current line.
- o — Open a new line under the current line.
- O — Open a new line above the current line.
- A — Append to the end of the line.
- a — Append after the cursor's current position.
- I — Insert text at the beginning of the current line.
- b — Go to the beginning of the word.
- e — Go to the end of the word.

x — Delete a single character.

dd — Delete an entire line.

Xdd — Delete X number of lines.

Xyy — Yank X number of lines.

G — Go to the last line in a file.

XG — Go to line X in a file.

gg — Go to the first line in a file.

:num — Display the current line's line number.

h — Move left one character.

j — Move down one line.

k — Move up one line.

l — Move right one character.

Ref:

The Blog by Ken Hess

<https://www.redhat.com/en/blog/introduction-vi-editor>

- Please note that reading is important. That is one reason why a blog is given in the previous page.

Runlevels

- A **runlevel** is a mode of operation in the computer [operating systems](#) that implements Unix [System V](#)-style [initialization](#).
Conventionally, **seven runlevels** exist, numbered from zero to six. *S* is sometimes used as a synonym for one of the levels.

- Only one runlevel is executed on startup; run levels are not executed one after another (i.e. only runlevel 2, 3, or 4 is executed, not more of them sequentially or in any other order).

- A runlevel defines the state of the machine after boot. That would also mean how much of the services/daemons are up and running.

Linux Standard Base specification [\[edit \]](#)

Systems conforming to the [Linux Standard Base](#) (LSB) need not provide the exact run levels given here or give them the meanings described here, and may map any level described here to a different level which provides the equivalent functionality.^[1]

LSB 4.1.0

ID	Name	Description
0	Off	Turns off the device.
1	Single-user mode	Mode for administrative tasks. ^{[2][b]}
2	Multi-user mode	Does not configure network interfaces and does not export networks services. ^[c]
3	Multi-user mode with networking	Starts the system normally. ^[1]
4	Not used/user-definable	For special purposes.
5	Full mode	Same as runlevel 3 + display manager .
6	Reboot	Reboots the device.

What is the Linux Standard Base?

- The **Linux Standard Base (LSB)** was a joint project by several [Linux distributions](#)^[*which?*] under the organizational structure of the [Linux Foundation](#) to standardize the software system structure, including the [Filesystem Hierarchy Standard](#). LSB was based on the [POSIX](#) specification, the [Single UNIX Specification](#) (SUS), and several other open standards, but extended them in certain areas.

- [Slackware Linux](#) uses runlevel 1 for maintenance, as on other Linux distributions; runlevels 2, 3 and 5 identically configured for a console (with all services active); and runlevel 4 adds the X Window System.

Slackware Linux runlevels^[3]

ID	Description
0	Off
1	Single-user mode
2	Unused but configured the same as runlevel 3
3	Multi-user mode without display manager
4	Multi-user mode with display manager (X11 or a session manager)
5	Full mode
6	Reboot

Gentoo Linux [\[edit \]](#)

Gentoo Linux runlevels^[4]

ID	Description
0	Off
1 or S	Single-user mode
2	Multi-user mode without networking.
3	Multi-user mode
4	Aliased for runlevel 3
5	Full mode
6	Reboot

Debian GNU/Linux [\[edit \]](#)

Debian GNU/Linux runlevels^[5]

ID	Description
0	Off
1	Recovery mode
2,3,4	Partial mode
5	Full mode
6	Reboot

Comparison of Linux Commandline & MsDOS

- Md vs mkdir
- Del, dir commands

Network Commands, Linux vs MsDOS

- Ipconfig/ifconfig
- Ping
- Tracert/traceroute

Browsers on Linux

- (Mozilla) Firefox, Google Chrome, Chromium, Brave, and Opera all can run on Ubuntu
- Can Microsoft Edge or Internet Explorer run on any version of Linux?