


SCS1312 Operating System Concepts

Dr. Chamath Keppitiyagama

University of Colombo School of Computing


x86 Rings




At the Beginning ...

·	101111
·	101010
·	101011
·	111000
·	101110
·	111010
·	111011
·	101010
·	101010
2	100010
1	101011
0	111010


PC ??




Hard Coded PC



Hard Coded PC





Basic Input Output System - BIOS





Write the following value (decimal) as a hexadecimal number.

$$2^{20} - 1$$











```
sudo cat /proc/iomem | grep ROM
```


Basic Input Output System - BIOS




Basic Input Output System - BIOS




Basic Input Output System - BIOS




Basic Input Output System - BIOS




Basic Input Output System - BIOS




Basic Input Output System - BIOS




Basic Input Output System - BIOS




Master Boot Record




MSB and LSB



Big-Endian




Little-Endian




Little-Endian


0xAA55



Booting




Booting




Real Mode - Ring 0

Interrupt Descriptor Table Register (IDTR)


Interrupt Vector



Interrupt Vector



init/systemd First Userland Process - PID 1




```
int f()  
{  
    // Some stuff here  
  
    return 0;  
}
```

```
f:
    movl $20, %eax
    movl $10, %ebx
    ....
    ....
    ret
```

```
int main(void)
{
    // Some stuff here

    f();

    // Some other stuff here
    return 0;
}
```

```
main:
    movl $100, %eax
    movl $125, %ebx
    ....
    ....
    call _f
    addl %eax, %ebx
    ...
    ...
    ...
```

Calling Functions

1000	movl 100 eax
1001	movl 125 ebx
.	...
1100	call 3000
1101	addl eax ebx
.	...
3000	movl 20 eax
.	movl 10 ebx
.	...
3200	ret
.	...
.	...