

ACTIVITY

- Define a class to create a new datatype called Date (Should include day, month and year)
- Define two functions called
 - setDate to initialize values by passing parameters
 - getDate to print the value (Date) on the console
- Create a variable called “today” of data type Date
- Set the value to 28/November/2024
- Display the value on the console

CLASS: DATE

```
1  #include<iostream>
2  using namespace std;
3
4  class date
5  {
6      int day;
7      string month;
8      int year;
9
10     void setDate(int D,string M,int Y){
11         day = D;
12         month = M;
13         year = Y;
14     }
15
16     void getDate(){
17         cout<<"Day:"<<day<<" Month:"<<month<<" Year:"<<year<<endl;
18     }
19 }; // end of class definition
20
```

CLASS AS A DATA TYPE

- Once a class has been declared, it can be used as object/array declarations

Example:



```
Car carObj,           // object of type Car  
Car carArray[10];     // array of Car objects  
Car *newCar;          // Object pointer
```

The class name becomes
the new type specifier.

DATA MEMBERS AND MEMBER FUNCTIONS

Accessing Data members / Member functions

- DOT (.) Operator
 - Example: `MyObject.variableX; MyObject.func();`
- Refer to a member of a class via a pointer to an object, (->) Operator

A pointer variable, or simply a pointer, contains the location, or address in the memory, of a memory cell

ACTIVITY

- Define a class to create a new datatype called Date (Should include day, month and year)
- Define two functions called
 - setDate to initialize values by passing parameters
 - getDate to print the value (Date) on the console
- Create a variable called “today” of data type Date
- Set the value to 28/November/2024
- Display the value on the console
- **Create a pointer variable called ptrDate to assign the value of “today”**
- **Display the value of ptrDate**

ACCESS OPERATOR (->): EXAMPLE

```
int main()
{
    date today;
    today.setDate(5,"December",2024);

    date *ptrDate;
    ptrDate=&today;

    cout<<"CHECK POINTER"<<endl;
    ptrDate->getDate();
}
```

Date today;



DATA MEMBERS AND MEMBER FUNCTIONS

Accessing Data members / member functions

- DOT (.) Operator
 - Example: `MyObject.variableX; MyObject.func();`
- Refer to a member of a class via a pointer to an object, (->) Operator
- Accessing a data member depends on the access modifier of the data member.

Defining Member functions in classes

- Inside class definition
- Outside class definition
 - use the scope resolution :: operator along with class name and function name.

```

4 class Date{
5     int day;
6     string month;
7     int year;
8
9     public:
10    void setDate(int, string, int);
11    void getDate();
12 };
13
14 void Date::setDate(int d, string m, int y){
15     day=d;
16     month=m;
17     year=y;
18 }
19
20 void Date::getDate(){
21     cout<<"Day: "<<day<<" Month: "<<month<<" Year: "<<year<<endl;
22 }

```


DEFINING MEMBER FUNCTIONS

- The scope resolution operator (::) can be used to define member functions outside the class definition.
- Member functions defined inside a class definition are automatically treated as inline functions.
- Member functions that contain more than one statement should be defined outside their class definition.
- Members of a class have class scope – data members can be referred to directly inside the member functions from that class.



SCOPE RESOLUTION OPERATOR



Different Functions ...

45

TO ACCESS THE GLOBAL VARIABLE

Scope Resolution Operator

ACTIVITY

```
1  #include<iostream>
2  using namespace std;
3
4  int a=3;
5
6  void func (int x) {
7      int b, a=100;
8      b=x;
9      cout<<"Calling from the Func Function: "<<endl;
10     cout<<"Variable a is "<<a<<endl;
11     cout<<"Variable b is "<<b<<endl;
12 }
13
14 int main()
15 {
16     int a=0;
17     cout<<"Value of the Variable a: " <<a<<endl;
18     func(67);
19 }
```

Value of the Variable a: 0
Calling from the Func Function:
Variable a is 100
Variable b is 67

SCOPE OF VARIABLES

- The extent of the program code within which the variable can be accessed or declared or worked with.
- **Local Variables**
 - Variables defined within a function or block are local to those functions.
 - Declared inside a block.
 - Local variables **do not exist** outside the block
 - **Can not** be accessed or used outside that block.
- **Global Variables**
 - Can be accessed from any part of the program.
 - Available throughout the lifetime of a program.
 - Declared at the top of the program outside all of the functions or blocks.

SCOPE OF VARIABLES...

- Usually two variables with the same name are NOT allowed to be defined.
 - Within the SCOPE
- If the variables are defined in different scopes then the compiler allows it.
- If there is a local variable and a global variable with the same name
 - The **compiler gives precedence to the local variable**
- **How can you ACCESS the global variable???**
 - Use the **scope resolution operator**.

▪ SCOPE RESOLUTION OPERATOR ■ ■

```

1  #include<iostream>
2  using namespace std;
3
4  int a=3;
5
6  void func (int x)
7  {
8      int b, a=100;
9      b=x;
10     cout<<"Calling from the Func Function: "<<endl;
11     cout<<"Variable a is "<<a<<endl;
12     cout<<"Variable b is "<<b<<endl;
13 }
14
15 int main()
16 {
17     int a=0;
18
19     cout<<"Value of the Local Variable a in Main: " <<a<<endl;
20     cout<<"Value of the Global Variable a " <<::a<<endl;
21     func(67);
22 }

```

```

Value of the Local Variable a in Main: 0
Value of the Global Variable a 3
Calling from the Func Function:
Variable a is 100
Variable b is 67

```

ACTIVITY

ACTIVITY

```
40
3
X-a = 2
1
```

```
1  #include<iostream>
2  using namespace std;
3
4  int a=3;
5
6  class X{
7      int a;
8
9      public:
10
11     void setValue(int x){
12         a=x;
13     }
14
15     int increment_a(){
16         return (a++);
17     }
18
19     void printX(){
20         cout<<"X-a = "<<a<<endl;}
21 }b;
```

```
24 int main()
25 {
26     int a=40;
27     b.setValue(0);
28
29     cout<<a<<endl;
30     cout<<::a<<endl;
31
32     a=b.increment_a();
33     a=b.increment_a();
34     b.printX();
35
36     cout<<endl<<a<<endl;
37 }
```


SCOPE RESOLUTION OPERATOR

Used to

- **access** a **global variable** when there is a local variable with the same name,
- **define** a function **outside a class**.

Activity

- **access** elements having the same name inside **two namespaces**
 - Use the namespace name with the scope resolution operator to refer to that class
using namespace std; & cout<< OR
std::cout

52

TO ACCESS ELEMENTS HAVING THE SAME NAME INSIDE TWO NAMESPACES

Scope Resolution Operator

NAMESPACE

- A space where we can define or declare identifiers i.e. variables, methods, and classes.
- Can define Functions, classes, variables having the same name in different libraries.
- Syntax:

```
namespace namespace_name
{
    // code declarations i.e. variable (int a;)
    method (void add();)
    classes ( class student{};)
}
```

Calling the namespace

namespace_name::code; // code could be variable , function or class.

ACTIVITY

```
Inside second_space
Inside first_space
```

```
1  #include <iostream>
2  using namespace std;
3  // first name space
4  namespace first_space{
5      void func(){
6          cout << "Inside first_space" << endl;
7      }
8  }
9
10 // second name space
11 namespace second_space{
12     void func(){
13         cout << "Inside second_space" << endl;
14     }
15 }
16
17 using namespace second_space;
18 int main ()
19 {
20     func();
21     first_space::func();
22 }
```

SCOPE RESOLUTION OPERATOR

Used to

- **access** a **global variable** when there is a local variable with same name,
- **define** a function **outside a class**.
- **access** elements having the same name inside **two namespaces**
 - Use the namespace name with the scope resolution operator to refer to that class
using namespace std; & cout<< OR
std::cout
- **refer** to a **class inside** another **class**

56

TO REFER TO A CLASS INSIDE ANOTHER CLASS

Scope Resolution Operator

ACTIVITY

```
1 // Use of scope resolution operator: class inside another class.
2 #include<iostream>
3 using namespace std;
4
5 class outside
6 {
7     public:
8         int x=0;
9
10        class inside
11        {
12            public:
13                int x = 1;
14                int y = 56;
15                int foo(){
16                    return x;
17                }
18        };
19    };
21 int main(){
22     outside A;
23     outside::inside B;
24     cout<<B.foo()<<endl;
25     cout<<B.y<<endl;
26 }
```

```
1
56
```

ACTIVITY

```
2  #include<iostream>
3  using namespace std;
4
5  class outside
6  {
7  public:
8      int x=0;
9
10     class inside
11     {
12     public:
13         int x = 1;
14         int y = 56;
15         int foo(){
16             return x;
17         }
18     };
19 };
20
```

```
26 int main(){
27
28     outside A;  //local object
29     outside::inside B;
30
31     cout<<B.foo()<<endl;
32     cout<<outside::inside::y<<endl;
33     cout<<A.y<<endl;
34     cout<<B.v<<endl;
35
36 }
```

9 - ... In function 'int main()':

Obj... [Error] 'class outside' has no member named 'y'

ACTIVITY

```
2  #include<iostream>
3  using namespace std;
4
5  class outside
6  {
7  public:
8      int x=0;
9
10     class inside
11     {
12     public:
13         int x = 1;
14         static int y;
15         int foo(){
16             return x;
17         }
18     };
19 };
```

```
22  outside C; //Global object
23
24  int outside::inside::y = 5;
25
26  int main(){
27
28      outside A; //local object
29      outside::inside B;
30
31      cout<<B.foo()<<endl;
32      cout<<outside::inside::y<<endl;
33      cout<<B.y<<endl;
34      cout<<C.x<<endl;
35 }
```

1
5
5
0

SCOPE RESOLUTION OPERATOR

Used to

- **access a global variable** when there is a local variable with same name,
- **define** a function **outside a class**.
- **access** elements having the same name inside **two namespaces**
 - Use the namespace name with the scope resolution operator to refer to that class
using namespace std; & cout<< OR
std::cout
- **refer** to a **class inside** another **class**
- **access** a class's **static variables**.
- **access variables** with the same name in two ancestor classes in **multiple inheritance**.

ACTIVITY

```
1  #include<iostream>
2  using namespace std;
3
4  class Enclosing {
5      int x=0;
6      /* start of Nested class declaration */
7      class Nested {
8          int y=1;
9      }; // declaration Nested class ends here
10
11  void EnclosingFun(Nested *n) {
12      cout<<n->y;
13      cout<<x<<endl;
14      cout<<y<<endl;
15  }
16  }; // declaration Enclosing class ends here
17
18  int main()
19  {
20
21  }
```

DYNAMIC MEMORY ALLOCATION

- Static Memory allocation: Global and Local variables
 - The memory space is allocated by the compiler.
 - Done before the program executes.
- Can one explicitly allocate and deallocate space at *run-time*?
 - *YES / WHY?*
 - Advantages:
 - No need to know how much amount of memory is needed beforehand.
 - *Dynamically* allocate exactly the correct amount of space for the variables
 - Use the memory space more efficiently...etc.
 - Use a pre-defined keyword
 - new** to allocate storage and
 - delete** to deallocate the storage

DYNAMIC MEMORY ALLOCATION:

NEW/DELETE

```
int main()
{
    // Allocated memory dynamically.
    int *intPtr1 = new int;
    int *intArrayPtr2 = new int[10];

    // Dynamically allocated memory is deallocated
    delete intPtr1;
    delete [] intArrayPtr2;
}
```

'new' allocates storage for the object and returns a pointer to the allocated storage

Good Coding Practise: Free dynamic memory when no longer required. Use the **delete** operator to release dynamic memory

//Don't forget the square brackets [] for an array

DYNAMIC MEMORY ALLOCATION:

NEW/DELETE

- Always check whether the memory has been successfully allocated

```
#include <cassert>
```

```
Time *timearrayPtr = new Time[10];
```

```
assert(timeArrayPtr != 0);
```

- **new** returns a null pointer if the allocation is unsuccessful