Experiment No 6: Sorting

Date: 04-10-2020

NAME: Gayathri M
REG.NO: 185001050

A. AIM:

Program for sorting in ascending order.

ALGORITHM:

- Initialize the data segment.
- Move data segment address to ds
- Initialize ah with 00h.
- Move row value to al and col value to bl.
- Multiply al with bl.
- Decrement ax.
- Here :
    - Move ax value to cx
    - Load offset of matrix1 to si
- Here1 :
    - Move contents pointed by si to bl
    - Compare contents pointed by si+1 with bl
    - If bl is less than or equal to [si+1] jump to next
    - Exchange values of bl and [si+1]
    - Move bl to matrix1
- next :
    - Increment si
    - Loop here1
    - Decrement ax
    - Jump to here if not equal to zero
    - Terminate the program

PROGRAM:

PROGRAM	**COMMENTS**

start:
mov ax,data
mov ds,ax
mov ah,00h
mov al,row
mov bl,col
mul bl
dec ax
	
	Load data segment to ds
	
	Initialise ah with 00h
	Move row value to ah
	Move col value to bl
	Multiply al with bl
	Decrement ax

Here: mov cx,ax mov si, offset matrix1	 Move contents of ax to cx. Move offset of matrix1 to si.

here1:
mov bl, [si]
cmp bl,[si+1]
jle next
xchg bl,[si+1]
mov [si],bl
	
	Move contents pointed by si to bl
	Move contents pointed by si+1 to bl
	If bl is less than or equal to [si+1] jump to next
	Exchange values of bl and [si+1]
	Move bl to matrix1

next: inc si loop here1 dec ax jnz here mov ah,4ch int 21h	 Increment si Start loop here1 Decrement ax Jump to here if not equal to 0 Terminate the program

UNASSEMBLED CODE:



SAMPLE INPUT/OUTPUT:



RESULT:

Thus sorting in ascending order is achieved.

B. AIM:

Program for sorting in descending order.

ALGORITHM:

- Initialize the data segment.
- Move data segment address to ds
- Load al with count value
- Initialize ah with 00h.
- Decrement ax.
- Here :
    - Move ax value to cx
    - Load offset of matrix1 to si
- Here1 :
    - Move contents pointed by si to bl
    - Compare contents pointed by si+1 with bl
    - If bl is greater than or equal to [si+1] jump to next
    - Exchange values of bl and [si+1]
    - Move bl to matrix1
- next :
    - Increment si
    - Loop here1
    - Decrement ax
    - Jump to here if not equal to zero
    - Terminate the program

PROGRAM:

PROGRAM	**COMMENTS**

start:
mov ax,data
mov ds,ax
mov al,count
mov ah,00h
dec ax
	
	Load data segment to ds
	
	Load al with count.
	Initialise ah with 00h
	Decrement ax

Here: mov cx,ax mov si, offset matrix1	 Move contents of ax to cx. Move offset of matrix1 to si.

here1:
mov bl, [si]
cmp bl,[si+1]
jge next
xchg bl,[si+1]
mov [si],bl
	
	Move contents pointed by si to bl
	Move contents pointed by si+1 to bl
	If bl is greater than or equal to [si+1] jump to next
	Exchange values of bl and [si+1]
	Move bl to matrix1

next: inc si loop here1 dec ax jnz here mov ah,4ch int 21h	 Increment si Start loop here1 Decrement ax Jump to here if not equal to 0 Terminate the program

UNASSEMBLED CODE:



SAMPLE INPUT/OUTPUT



RESULT:

Thus sorting in descending order is achieved.