

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
(An Autonomous Institution, Affiliated to Anna University, Chennai)
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

UCS1411 - OPERATING SYSTEMS LAB

Lab Exercise 4: Implementation of CPU Scheduling Policies: Priority and Round Robin

NAME: GAYATHRI M
REG NO.: 185001050

PROGRAM:

```
#include<stdio.h>
#include<stdlib.h>
#include<string.h>

typedef struct
{
    char pid[10];
    int start, arr, burst, pri, rem, wait, turn, flag;
}job;

void gantt(job arr[], int n, int tot_time)
{
    if(n <= 0)
        return;

    printf("\n\n\tGANTT CHART");

    int i, j;

    printf("\n\n\t ");
    for(i=0; i<n-1; i++)
    {
        for(j=arr[i].start; j<arr[i+1].start; j++)
            printf("--");
        printf(" ");
    }

    for(j=0; j<tot_time - arr[n-1].start; j++)
        printf("--");
    printf(" ");
```

```

printf("\n\t| ");

for(i=0; i<n-1; i++)
{
for(j=arr[i].start; j<arr[i+1].start - 1; j++)
printf(" ");
printf("%s", arr[i].pid);

for(j=arr[i].start; j<arr[i+1].start - 1; j++)
printf(" ");
printf(" | ");
}

for(j=0; j<tot_time - arr[n-1].start - 1; j++)
printf(" ");
printf("%s", arr[n-1].pid);
for(j=0; j<tot_time - arr[n-1].start - 1; j++)
printf(" ");
printf(" | ");

printf("\n\t ");

for(i=0; i<n-1; i++)
{
for(j=arr[i].start; j<arr[i+1].start; j++)
printf("--");
printf(" ");
}

for(j=0; j<tot_time - arr[n-1].start; j++)
printf("--");
printf(" ");

printf("\n\t");

for(i=0; i<n-1; i++)
{
printf("%d", arr[i].start);
for(j=arr[i].start; j<arr[i+1].start; j++)
printf(" ");
if(arr[i].start > 9)
printf("\b");
}

printf("%d", arr[n-1].start);
for(j=0; j<tot_time - arr[n-1].start; j++)
printf(" ");
if(tot_time > 9)
printf("\b%d", tot_time);
printf("\n");
}

```

```

void display(job ar[],int n)
{
    float avgturn=0,avgwait=0;
    job temp;
    for(int i=0;i<n-1;i++)
    {
        for(int j=i+1;j<n;j++)
        {
            if(strcmp(ar[j].pid,ar[i].pid)<0)
            {
                temp=ar[j];
                ar[j]=ar[i];
                ar[i]=temp;
            }
        }
    }
    printf("\n-----\n");
    printf("\nProcess ID\tArrival Time\tBurst Time\tTurnaround\tWaiting\nTime");
    printf("\n-----\n");
    for(int i=0;i<n;i++)
    {
        printf("\n%s\t\t%d\t\t%d\t\t%d\t\t%d",ar[i].pid,ar[i].arr,ar[i].burst,ar[i].turn,ar[i].wait);
        avgturn+=ar[i].turn;
        avgwait+=ar[i].wait;
    }
    printf("\n\t\t\t\t\tAverage: \t\t%.2f\t\t%.2f",avgturn/n,avgwait/n);
    printf("\n");
}

```

```

void rr(job ar[],int n)
{
    int time=0;
    float avgturn=0,avgwait=0;
    int prev=-1;
    printf("\n\n\t\tROUND ROBIN\n");
    time=0;
    int remain=0,endtime;
    int q;
    q=2;
    int t=0;
    int i=0;
    job temp;
    job g[10];
}

```

```

int count=0;

for(int i=0;i<n-1;i++)
{
    for(int j=i+1;j<n;j++)
    {
        if(ar[j].arr<ar[i].arr)
        {
            temp=ar[j];
            ar[j]=ar[i];
            ar[i]=temp;
        }
    }
}

for(int i=0;i<n;i++)
{
    time+=ar[i].burst;
}

while(remain!=n)
{
    if(ar[i].flag==0)
    {
        if(ar[i].rem>q && ar[i].flag==0)
        {
            ar[i].start=t;
            g[count++]=ar[i];
            t=t+q;
            ar[i].rem-=q;
        }
        else if(ar[i].flag==0)
        {
            ar[i].start=t;
            g[count++]=ar[i];
            t=t+ar[i].rem;
            ar[i].rem=0;
        }
        if(ar[i].rem==0)
        {
            remain++;
            endtime=t;
            ar[i].turn=endtime-ar[i].arr;
            ar[i].wait=endtime-ar[i].burst-ar[i].arr;
            ar[i].flag=1;
        }
        i=(i+1)%n;
    }
    else
    {

```

```
void priority_np(job ar[],int n)
{
```

```
printf("\n\n\t\tPRIORITY (Non Pre Emptive)\n");  
time=0;  
for(int i=0;i<n;i++)  
{  
    time+=ar[i].burst;  
}
```

```
void priority_p(job ar[],int n)
```

```

{
    int time=0;
    float avgturn=0,avgwait=0;

```



```

{
    for(int i=0;i<n;i++)
    {
        printf("\nEnter PID : ");
        scanf("%s",ar[i].pid);
        printf("Enter Arrival Time : ");
        scanf("%d",&ar[i].arr);
        printf("Enter Burst Time : ");
        scanf("%d",&ar[i].burst);
        printf("Enter Priority : ");
        scanf("%d",&ar[i].pri);
        ar[i].rem=ar[i].burst;
        ar[i].flag=0;
    }
    printf("\n");
}

int main()
{
    job ar[10];
    int n;
    int time=0;
    float avgturn=0,avgwait=0;
    int min;
    int index;
    int choice=3;
    while(choice!=0)
    {
        printf("\n\n\t\tCPU SCHEDULING ALGORITHMS\n");
        printf("1.ROUND ROBIN\n2.PRIORITY\n0.EXIT\nEnter Choice : ");
        scanf("%d",&choice);
        switch(choice)
        {
            case 1:
                printf("\t\tROUND ROBIN CPU SCHEDULER\n");
                printf("Enter Number of Processes : ");
                scanf("%d",&n);
                input(ar,n);
                rr(ar,n);
                break;
            case 2:
                printf("\t\tPRIORITY CPU SCHEDULER\n");
                printf("1. Non Preemptive PRIORITY\n2. Pre emptive\n");
                printf("Enter your option : ");
                scanf("%d",&choice);
                printf("Enter Number of Processes : ");
                scanf("%d",&n);
                input(ar,n);
                if(choice==1)
                    priority_np(ar,n);
                else if(choice==2)

```

```

        priority_p(ar,n);
    else
        printf("Invalid Choice !!!\n");
        break;
    }
}
return 0;
}

```

OUTPUT:

(base) MSMLs-iMac:ex4 msml\$./rr_priority

CPU SCHEDULING ALGORITHMS

1.ROUND ROBIN
 2.PRIORITY
 0.EXIT

Enter Choice : 1

ROUND ROBIN CPU SCHEDULER

Enter Number of Processes : 5

Enter PID : P1

Enter Arrival Time : 0

Enter Burst Time : 6

Enter Priority : 2

Enter PID : P2

Enter Arrival Time : 1

Enter Burst Time : 2

Enter Priority : 2

Enter PID : P3

Enter Arrival Time : 1

Enter Burst Time : 3

Enter Priority : 4

Enter PID : P4

Enter Arrival Time : 2

Enter Burst Time : 1

Enter Priority : 1

Enter PID : P5

Enter Arrival Time : 2
Enter Burst Time : 2
Enter Priority : 3

ROUND ROBIN

Process ID	Arrival Time	Burst Time	Turnaround	Waiting Time
P1	0	6	14	8
P2	1	2	3	1
P3	1	3	11	8
P4	2	1	5	4
P5	2	2	7	5
Average:			8.00	5.20

GANTT CHART

P1	P2	P3	P4	P5	P1	P3	P1	
0	2	4	6	7	9	11	12	14

CPU SCHEDULING ALGORITHMS

1.ROUND ROBIN
2.PRIORITY
0.EXIT
Enter Choice : 1

PRIORITY CPU SCHEDULER

1. Non Preemptive PRIORITY
2. Pre emptive PRIORITY
Enter your option : 1

Enter Number of Processes : 5

Enter PID : P1
Enter Arrival Time : 0
Enter Burst Time : 6

Enter Priority : 2

Enter PID : P2

Enter Arrival Time : 1

Enter Burst Time : 2

Enter Priority : 2

Enter PID : P3

Enter Arrival Time : 1

Enter Burst Time : 3

Enter Priority : 4

Enter PID : P4

Enter Arrival Time : 2

Enter Burst Time : 1

Enter Priority : 1

Enter PID : P5

Enter Arrival Time : 2

Enter Burst Time : 2

Enter Priority : 3

PRIORITY (Non Pre Emptive)

Process ID	Arrival Time	Burst Time	Turnaround	Waiting Time
P1	0	6	6	0
P2	1	2	8	6
P3	1	3	13	10
P4	2	1	5	4
P5	2	2	9	7
		Average:	8.20	5.40

GANTT CHART

	P1		P4		P2		P5		P3	
0		6	7	9	11	14				

CPU SCHEDULING ALGORITHMS

1.ROUND ROBIN

2.PRIORITY

0.EXIT

Enter Choice : 1

PRIORITY CPU SCHEDULER

1. Non Preemptive PRIORITY

2. Pre emptive PRIORITY

Enter your option : 2

Enter Number of Processes : 5

Enter PID : P1

Enter Arrival Time : 0

Enter Burst Time : 6

Enter Priority : 2

Enter PID : P2

Enter Arrival Time : 1

Enter Burst Time : 2

Enter Priority : 2

Enter PID : P3

Enter Arrival Time : 1

Enter Burst Time : 3

Enter Priority : 4

Enter PID : P4

Enter Arrival Time : 2

Enter Burst Time : 1

Enter Priority : 1

Enter PID : P5

Enter Arrival Time : 2

Enter Burst Time : 2

Enter Priority : 3

PRIORITY (Pre Emptive)

Process ID	Arrival Time	Burst Time	Turnaround	Waiting Time
P1	0	6	7	1
P2	1	2	8	6

P3	1	3	13	10
P4	2	1	1	0
P5	2	2	9	7
Average:			7.60	4.80

GANTT CHART

P1	P4	P1	P2	P5	P3	

0	2	3	7	9	11	14

CPU SCHEDULING ALGORITHMS

1.ROUND ROBIN

2.PRIORITY

0.EXIT

Enter Choice : 0