

1. Two Sum

Easy

381271220Add to ListShare

Given an array of integers `nums` and an integer `target`, return *indices of the two numbers such that they add up to target*.

You may assume that each input would have **exactly one solution**, and you may not use the *same* element twice.

You can return the answer in any order.

Example 1:

Input: `nums = [2,7,11,15]`, `target = 9`

Output: `[0,1]`

Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.

Example 2:

Input: `nums = [3,2,4]`, `target = 6`

Output: `[1,2]`

Example 3:

Input: `nums = [3,3]`, `target = 6`

Output: `[0,1]`

Constraints:

- $2 \leq \text{nums.length} \leq 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $-10^9 \leq \text{target} \leq 10^9$
- **Only one valid answer exists.**

2. Add Two Numbers




Medium

216884249Add to ListShare

You are given two **non-empty** linked lists representing two non-negative integers. The digits are stored in **reverse order**, and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list.

You may assume the two numbers do not contain any leading zero, except the number 0 itself.

Example 1:



Input: l1 = [2,4,3], l2 = [5,6,4]

Output: [7,0,8]

Explanation: 342 + 465 = 807.

Example 2:

Input: l1 = [0], l2 = [0]

Output: [0]

Example 3:

Input: l1 = [9,9,9,9,9,9,9], l2 = [9,9,9,9]

Output: [8,9,9,9,0,0,0,1]

Constraints:

- The number of nodes in each linked list is in the range [1, 100].
- $0 \leq \text{Node.val} \leq 9$
- It is guaranteed that the list represents a number that does not have leading zeros.

3. Longest Substring Without Repeating Characters

Medium

289161231Add to ListShare

Given a string `s`, find the length of the **longest substring** without repeating characters.

Example 1:

Input: `s = "abcabcbb"`

Output: 3

Explanation: The answer is "abc", with the length of 3.

Example 2:

Input: `s = "bbbbbb"`

Output: 1

Explanation: The answer is "b", with the length of 1.

Example 3:

Input: `s = "pwwkew"`

Output: 3

Explanation: The answer is "wke", with the length of 3.

Notice that the answer must be a substring, "pwke" is a subsequence and not a substring.

Constraints:

- $0 \leq s.length \leq 5 * 10^4$
- `s` consists of English letters, digits, symbols and spaces.

4. Median of Two Sorted Arrays

Hard

196942253Add to ListShare

Given two sorted arrays `nums1` and `nums2` of size `m` and `n` respectively, return **the median** of the two sorted arrays.

The overall run time complexity should be $O(\log(m+n))$.

Example 1:**Input:** nums1 = [1,3], nums2 = [2]**Output:** 2.00000**Explanation:** merged array = [1,2,3] and median is 2.**Example 2:****Input:** nums1 = [1,2], nums2 = [3,4]**Output:** 2.50000**Explanation:** merged array = [1,2,3,4] and median is $(2 + 3) / 2 = 2.5$.**Constraints:**

- nums1.length == m
- nums2.length == n
- $0 \leq m \leq 1000$
- $0 \leq n \leq 1000$
- $1 \leq m + n \leq 2000$
- $-10^6 \leq \text{nums1}[i], \text{nums2}[i] \leq 10^6$

5. Longest Palindromic Substring

Medium

216881244Add to ListShare

Given a string *s*, return *the longest palindromic substring* in *s*.

A string is called a palindrome string if the reverse of that string is the same as the original string.

Example 1:**Input:** s = "babad"**Output:** "bab"**Explanation:** "aba" is also a valid answer.**Example 2:****Input:** s = "cbbd"

Output: "bb"

Constraints:

- `1 <= s.length <= 1000`
- `s` consist of only digits and English letters.

6. Zigzag Conversion

Medium

43879710 Add to List Share

The string "PAYPALISHIRING" is written in a zigzag pattern on a given number of rows like this:
(you may want to display this pattern in a fixed font for better legibility)

```
P   A   H   N
A P L S I I G
Y   I   R
```

And then read line by line: "PAHNAPLSIIGYIR"

Write the code that will take a string and make this conversion given a number of rows:

```
string convert(string s, int numRows);
```

Example 1:

Input: `s = "PAYPALISHIRING", numRows = 3`

Output: "PAHNAPLSIIGYIR"

Example 2:

Input: `s = "PAYPALISHIRING", numRows = 4`

Output: "PINALSIGYAHRPI"

Explanation:

```
P       I       N
A       L   S   I   G
Y   A   H   R
P       I
```

Example 3:**Input:** s = "A", numRows = 1**Output:** "A"**Constraints:**

- $1 \leq s.length \leq 1000$
- s consists of English letters (lower-case and upper-case), ' ', ' ' and ' '.
- $1 \leq \text{numRows} \leq 1000$

7. Reverse Integer**Medium**

849910750Add to ListShare

Given a signed 32-bit integer x , return x with its digits reversed. If reversing x causes the value to go outside the signed 32-bit integer range $[-2^{31}, 2^{31} - 1]$, then return 0.

Assume the environment does not allow you to store 64-bit integers (signed or unsigned).

Example 1:**Input:** x = 123**Output:** 321**Example 2:****Input:** x = -123**Output:** -321**Example 3:****Input:** x = 120**Output:** 21**Constraints:**

- $-2^{31} \leq x \leq 2^{31} - 1$

8. String to Integer (atoi)

Medium

23476791 Add to List Share

Implement the `myAtoi(string s)` function, which converts a string to a 32-bit signed integer (similar to C/C++'s `atoi` function).

The algorithm for `myAtoi(string s)` is as follows:

1. Read in and ignore any leading whitespace.
2. Check if the next character (if not already at the end of the string) is `'-'` or `'+'`. Read this character in if it is either. This determines if the final result is negative or positive respectively. Assume the result is positive if neither is present.
3. Read in next the characters until the next non-digit character or the end of the input is reached. The rest of the string is ignored.
4. Convert these digits into an integer (i.e. `"123" -> 123`, `"0032" -> 32`). If no digits were read, then the integer is `0`. Change the sign as necessary (from step 2).
5. If the integer is out of the 32-bit signed integer range $[-2^{31}, 2^{31} - 1]$, then clamp the integer so that it remains in the range. Specifically, integers less than -2^{31} should be clamped to -2^{31} , and integers greater than $2^{31} - 1$ should be clamped to $2^{31} - 1$.
6. Return the integer as the final result.

Note:

- Only the space character `' '` is considered a whitespace character.
- **Do not ignore** any characters other than the leading whitespace or the rest of the string after the digits.

Example 1:

Input: `s = "42"`

Output: `42`

Explanation: The underlined characters are what is read in, the caret is the current reader position.

Step 1: `"42"` (no characters read because there is no leading whitespace)

^

Step 2: `"42"` (no characters read because there is neither a `'-'` nor `'+'`)

^

Step 3: `42"` (`"42"` is read in)

^

The parsed integer is 42.

Since 42 is in the range $[-2^{31}, 2^{31} - 1]$, the final result is 42.

Example 2:

Input: `s = " -42"`

Output: -42

Explanation:

Step 1: " -42" (leading whitespace is read and ignored)

 ^

Step 2: " -42" ('-' is read, so the result should be negative)

 ^

Step 3: " -42" ("42" is read in)

 ^

The parsed integer is -42.

Since -42 is in the range $[-2^{31}, 2^{31} - 1]$, the final result is -42.

Example 3:

Input: `s = "4193 with words"`

Output: 4193

Explanation:

Step 1: "4193 with words" (no characters read because there is no leading whitespace)

 ^

Step 2: "4193 with words" (no characters read because there is neither a '-' nor '+')

 ^

Step 3: "4193 with words" ("4193" is read in; reading stops because the next character is a non-digit)

 ^

The parsed integer is 4193.

Since 4193 is in the range $[-2^{31}, 2^{31} - 1]$, the final result is 4193.

Constraints:

- $0 \leq s.length \leq 200$
- s consists of English letters (lower-case and upper-case), digits (0-9), ' ', '+', ' - ', and '.'.

9. Palindrome Number**Easy**

73092306Add to ListShare

Given an integer x , return `true` if x is palindrome integer.An integer is a **palindrome** when it reads the same backward as forward.

- For example, `121` is a palindrome while `123` is not.

Example 1:**Input:** $x = 121$ **Output:** `true`**Explanation:** 121 reads as 121 from left to right and from right to left.**Example 2:****Input:** $x = -121$ **Output:** `false`**Explanation:** From left to right, it reads -121 . From right to left, it becomes $121-$. Therefore it is not a palindrome.**Example 3:****Input:** $x = 10$ **Output:** `false`**Explanation:** Reads 01 from right to left. Therefore it is not a palindrome.**Constraints:**

- $-2^{31} \leq x \leq 2^{31} - 1$

10. Regular Expression Matching

Hard

92861466Add to ListShare

Given an input string `s` and a pattern `p`, implement regular expression matching with support for `'.'` and `'*'` where:

- `'.'` Matches any single character.
- `'*'` Matches zero or more of the preceding element.

The matching should cover the **entire** input string (not partial).

Example 1:

Input: `s = "aa"`, `p = "a"`

Output: `false`

Explanation: `"a"` does not match the entire string `"aa"`.

Example 2:

Input: `s = "aa"`, `p = "a*"`

Output: `true`

Explanation: `'*'` means zero or more of the preceding element, `'a'`. Therefore, by repeating `'a'` once, it becomes `"aa"`.

Example 3:

Input: `s = "ab"`, `p = ".*"`

Output: `true`

Explanation: `".*"` means "zero or more (*) of any character (.)".

Constraints:

- `1 <= s.length <= 20`
- `1 <= p.length <= 30`
- `s` contains only lowercase English letters.
- `p` contains only lowercase English letters, `'.'`, and `'*'`.
- It is guaranteed for each appearance of the character `'*'`, there will be a previous valid character to match.

11. Container With Most Water

Medium

202981073Add to ListShare


You are given an integer array `height` of length `n`. There are `n` vertical lines drawn such that the two endpoints of the `ith` line are `(i, 0)` and `(i, height[i])`.

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return *the maximum amount of water a container can store*.

Notice that you may not slant the container.

Example 1:



Explanation: The above vertical lines are represented by array `[1,8,6,2,5,4,8,3,7]`. In this case, the max area of water (blue section) the container can contain is 49.

Example 2:

Input: `height = [1,1]`

Output: 1

Constraints:

- `n == height.length`
- `2 <= n <= 105`
- `0 <= height[i] <= 104`

12. Integer to Roman**Medium**

40674442Add to ListShare

Roman numerals are represented by seven different symbols: `I`, `V`, `X`, `L`, `C`, `D` and `M`.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, `2` is written as `II` in Roman numeral, just two one's added together. `12` is written as `XII`, which is simply `X` + `II`. The number `27` is written as `XXVII`, which is `XX` + `V` + `II`.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not `IIII`. Instead, the number four is written as `IV`. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as `IX`. There are six instances where subtraction is used:

- `I` can be placed before `V` (5) and `X` (10) to make 4 and 9.
- `X` can be placed before `L` (50) and `C` (100) to make 40 and 90.
- `C` can be placed before `D` (500) and `M` (1000) to make 400 and 900.

Given an integer, convert it to a roman numeral.

Example 1:**Input:** num = 3**Output:** "III"

Explanation: 3 is represented as 3 ones.

Example 2:

Input: num = 58

Output: "LVIII"

Explanation: L = 50, V = 5, III = 3.

Example 3:

Input: num = 1994

Output: "MCMXCIV"

Explanation: M = 1000, CM = 900, XC = 90 and IV = 4.

Constraints:

- $1 \leq \text{num} \leq 3999$

13. Roman to Integer

Easy

7108425Add to ListShare

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two ones added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we

subtract it making four. The same principle applies to the number nine, which is written as `IX`. There are six instances where subtraction is used:

- `I` can be placed before `V` (5) and `X` (10) to make 4 and 9.
- `X` can be placed before `L` (50) and `C` (100) to make 40 and 90.
- `C` can be placed before `D` (500) and `M` (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Example 1:

Input: `s = "III"`

Output: 3

Explanation: `III` = 3.

Example 2:

Input: `s = "LVIII"`

Output: 58

Explanation: `L` = 50, `V` = 5, `III` = 3.

Example 3:

Input: `s = "MCMXCIV"`

Output: 1994

Explanation: `M` = 1000, `CM` = 900, `XC` = 90 and `IV` = 4.

Constraints:

- `1 <= s.length <= 15`
- `s` contains only the characters ('I', 'V', 'X', 'L', 'C', 'D', 'M').
- It is **guaranteed** that `s` is a valid roman numeral in the range [1, 3999].

14. Longest Common Prefix

Easy

104473398Add to ListShare

Write a function to find the longest common prefix string amongst an array of strings.

If there is no common prefix, return an empty string `""`.

Example 1:

Input: strs = ["flower", "flow", "flight"]

Output: "fl"

Example 2:

Input: strs = ["dog", "racecar", "car"]

Output: ""

Explanation: There is no common prefix among the input strings.

Constraints:

- $1 \leq \text{strs.length} \leq 200$
- $0 \leq \text{strs[i].length} \leq 200$
- `strs[i]` consists of only lowercase English letters.

15.3Sum**Medium**

214801988Add to ListShare

Given an integer array `nums`, return all the triplets `[nums[i], nums[j], nums[k]]` such that `i != j, i != k, and j != k, and nums[i] + nums[j] + nums[k] == 0`.

Notice that the solution set must not contain duplicate triplets.

Example 1:

Input: nums = [-1,0,1,2,-1,-4]

Output: [[-1,-1,2],[-1,0,1]]

Explanation:

`nums[0] + nums[1] + nums[2] = (-1) + 0 + 1 = 0.`

`nums[1] + nums[2] + nums[4] = 0 + 1 + (-1) = 0.`

`nums[0] + nums[3] + nums[4] = (-1) + 2 + (-1) = 0.`

The distinct triplets are [-1,0,1] and [-1,-1,2].

Notice that the order of the output and the order of the triplets does not matter.

Example 2:

Input: `nums = [0,1,1]`

Output: `[]`

Explanation: The only possible triplet does not sum up to 0.

Example 3:

Input: `nums = [0,0,0]`

Output: `[[0,0,0]]`

Explanation: The only possible triplet sums up to 0.

Constraints:

- $3 \leq \text{nums.length} \leq 3000$
- $-10^5 \leq \text{nums}[i] \leq 10^5$

16. 3Sum Closest

Medium

6961371Add to ListShare

Given an integer array `nums` of length `n` and an integer `target`, find three integers in `nums` such that the sum is closest to `target`.

Return *the sum of the three integers*.

You may assume that each input would have exactly one solution.

Example 1:

Input: `nums = [-1,2,1,-4], target = 1`

Output: `2`

Explanation: The sum that is closest to the target is 2. $(-1 + 2 + 1 = 2)$.

Example 2:

Input: `nums = [0,0,0], target = 1`

Output: `0`

Constraints:

- $3 \leq \text{nums.length} \leq 1000$
- $-1000 \leq \text{nums}[i] \leq 1000$
- $-10^4 \leq \text{target} \leq 10^4$

17. Letter Combinations of a Phone Number**Medium**

12642761Add to ListShare

Given a string containing digits from 2–9 inclusive, return all possible letter combinations that the number could represent. Return the answer in **any order**.

A mapping of digits to letters (just like on the telephone buttons) is given below. Note that 1 does not map to any letters.



Example 1:**Input:** digits = "23"**Output:** ["ad", "ae", "af", "bd", "be", "bf", "cd", "ce", "cf"]**Example 2:****Input:** digits = ""**Output:** []**Example 3:****Input:** digits = "2"**Output:** ["a", "b", "c"]**Constraints:**

- $0 \leq \text{digits.length} \leq 4$
- $\text{digits}[i]$ is a digit in the range $['2', '9']$.

18.4Sum**Medium**

7688893Add to ListShare

Given an array `nums` of n integers, return an array of all the **unique** quadruplets $[\text{nums}[a], \text{nums}[b], \text{nums}[c], \text{nums}[d]]$ such that:

- $0 \leq a, b, c, d < n$
- $a, b, c,$ and d are **distinct**.
- $\text{nums}[a] + \text{nums}[b] + \text{nums}[c] + \text{nums}[d] == \text{target}$

You may return the answer in **any order**.

Example 1:**Input:** nums = [1,0,-1,0,-2,2], target = 0**Output:** [[-2,-1,1,2],[-2,0,0,2],[-1,0,0,1]]**Example 2:****Input:** nums = [2,2,2,2,2], target = 8

Output: [[2,2,2,2]]

Constraints:

- $1 \leq \text{nums.length} \leq 200$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $-10^9 \leq \text{target} \leq 10^9$


19. Remove Nth Node From End of List

Medium

12560540Add to ListShare

Given the `head` of a linked list, remove the n^{th} node from the end of the list and return its head.

Example 1:



Input: head = [1,2,3,4,5], n = 2

Output: [1,2,3,5]

Example 2:

Input: head = [1], n = 1

Output: []

Example 3:

Input: head = [1,2], n = 1

Output: [1]

Constraints:

- The number of nodes in the list is `sz`.
- $1 \leq sz \leq 30$
- $0 \leq \text{Node.val} \leq 100$
- $1 \leq n \leq sz$

20. Valid Parentheses**Easy**

15785783Add to ListShare

Given a string `s` containing just the characters ' '(),()' ', ' {}', ' []' and ' []', determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Example 1:**Input:** `s = "()"`**Output:** `true`**Example 2:****Input:** `s = "()[{}]"`**Output:** `true`**Example 3:****Input:** `s = "()"`**Output:** `false`**Constraints:**

- $1 \leq s.length \leq 10^4$
- `s` consists of parentheses only ' () [] {}'.

21. Merge Two Sorted Lists

Easy


150241321Add to ListShare

You are given the heads of two sorted linked lists `list1` and `list2`.

Merge the two lists in a one **sorted** list. The list should be made by splicing together the nodes of the first two lists.

Return *the head of the merged linked list*.

Example 1:



Input: `list1 = [1,2,4]`, `list2 = [1,3,4]`

Output: `[1,1,2,3,4,4]`

Example 2:

Input: `list1 = []`, `list2 = []`

Output: `[]`

Example 3:

Input: `list1 = []`, `list2 = [0]`

Output: `[0]`

Constraints:

- The number of nodes in both lists is in the range [0, 50].
- `-100 <= Node.val <= 100`
- Both `list1` and `list2` are sorted in **non-decreasing** order.

22. Generate Parentheses

Medium

15231580Add to ListShare

Given `n` pairs of parentheses, write a function to *generate all combinations of well-formed parentheses*.

Example 1:

Input: `n = 3`

Output: `["((()))","(()())","((())()","()((()))","()()()"]`

Example 2:

Input: `n = 1`

Output: `["()"]`

Constraints:

- `1 <= n <= 8`

23. Merge k Sorted Lists

Hard

14231532Add to ListShare

You are given an array of `k` linked-lists `lists`, each linked-list is sorted in ascending order.

Merge all the linked-lists into one sorted linked-list and return it.

Example 1:

Input: `lists = [[1,4,5],[1,3,4],[2,6]]`

Output: `[1,1,2,3,4,4,5,6]`

Explanation: The linked-lists are:

[

```

1->4->5,
1->3->4,
2->6
]

merging them into one sorted list:
1->1->2->3->4->4->5->6

```

Example 2:

Input: lists = []

Output: []

Example 3:

Input: lists = [[]]

Output: []

Constraints:

- `k == lists.length`
- `0 <= k <= 104`
- `0 <= lists[i].length <= 500`
- `-104 <= lists[i][j] <= 104`
- `lists[i]` is sorted in **ascending order**.
- The sum of `lists[i].length` will not exceed `104`.


24. Swap Nodes in Pairs

Medium

8153332 Add to List Share

Given a linked list, swap every two adjacent nodes and return its head. You must solve the problem without modifying the values in the list's nodes (i.e., only nodes themselves may be changed.)

Example 1:



Input: head = [1,2,3,4]

Output: [2,1,4,3]

Example 2:

Input: head = []

Output: []

Example 3:

Input: head = [1]

Output: [1]

Constraints:

- The number of nodes in the list is in the range [0, 100].
- $0 \leq \text{Node.val} \leq 100$

25. Reverse Nodes in k-Group

Hard


9157538Add to ListShare

Given the `head` of a linked list, reverse the nodes of the list `k` at a time, and return *the modified list*.

`k` is a positive integer and is less than or equal to the length of the linked list. If the number of nodes is not a multiple of `k` then left-out nodes, in the end, should remain as it is.

You may not alter the values in the list's nodes, only nodes themselves may be changed.


Example 1:



Input: head = [1,2,3,4,5], k = 2

Output: [2,1,4,3,5]

Example 2:



Input: head = [1,2,3,4,5], k = 3

Output: [3,2,1,4,5]

Constraints:

- The number of nodes in the list is n .
- $1 \leq k \leq n \leq 5000$
- $0 \leq \text{Node.val} \leq 1000$

26. Remove Duplicates from Sorted Array

Easy

824711932Add to ListShare

Given an integer array `nums` sorted in **non-decreasing order**, remove the duplicates **in-place** such that each unique element appears only **once**. The **relative order** of the elements should be kept the **same**.

Since it is impossible to change the length of the array in some languages, you must instead have the result be placed in the **first part** of the array `nums`. More formally, if there are `k` elements after removing the duplicates, then the first `k` elements of `nums` should hold the final result. It does not matter what you leave beyond the first `k` elements.

Return `k` *after placing the final result in the first `k` slots of `nums`*.

Do **not** allocate extra space for another array. You must do this by **modifying the input array in-place** with $O(1)$ extra memory.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int[] expectedNums = [...]; // The expected answer with correct length

int k = removeDuplicates(nums); // Calls your implementation

assert k == expectedNums.length;
for (int i = 0; i < k; i++) {
    assert nums[i] == expectedNums[i];
}
```

If all assertions pass, then your solution will be **accepted**.

Example 1:

Input: `nums = [1,1,2]`

Output: `2, nums = [1,2,_]`

Explanation: Your function should return `k = 2`, with the first two elements of `nums` being 1 and 2 respectively.

It does not matter what you leave beyond the returned `k` (hence they are underscores).

Example 2:

Input: `nums = [0,0,1,1,1,2,2,3,3,4]`

Output: `5, nums = [0,1,2,3,4,_,_,_,_,_]`

Explanation: Your function should return `k = 5`, with the first five elements of `nums` being `0, 1, 2, 3, and 4` respectively.

It does not matter what you leave beyond the returned `k` (hence they are underscores).

Constraints:

- `1 <= nums.length <= 3 * 104`
- `-100 <= nums[i] <= 100`
- `nums` is sorted in **non-decreasing** order.

27. Remove Element**Easy**

44106166Add to ListShare

Given an integer array `nums` and an integer `val`, remove all occurrences of `val` in `nums` **in-place**. The relative order of the elements may be changed.

Since it is impossible to change the length of the array in some languages, you must instead have the result be placed in the **first part** of the array `nums`. More formally, if there are `k` elements after removing the duplicates, then the first `k` elements of `nums` should hold the final result. It does not matter what you leave beyond the first `k` elements.

Return `k` *after placing the final result in the first `k` slots of `nums`*.

Do **not** allocate extra space for another array. You must do this by **modifying the input array in-place** with $O(1)$ extra memory.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array
int val = ...; // Value to remove
int[] expectedNums = [...]; // The expected answer with correct length.

// It is sorted with no values equaling val.
```

```

int k = removeElement(nums, val); // Calls your implementation

assert k == expectedNums.length;

sort(nums, 0, k); // Sort the first k elements of nums

for (int i = 0; i < actualLength; i++) {

    assert nums[i] == expectedNums[i];

}

```

If all assertions pass, then your solution will be **accepted**.

Example 1:

Input: nums = [3,2,2,3], val = 3

Output: 2, nums = [2,2,_,_]

Explanation: Your function should return k = 2, with the first two elements of nums being 2.

It does not matter what you leave beyond the returned k (hence they are underscores).

Example 2:

Input: nums = [0,1,2,2,3,0,4,2], val = 2

Output: 5, nums = [0,1,4,0,3,_,_,_]

Explanation: Your function should return k = 5, with the first five elements of nums containing 0, 0, 1, 3, and 4.

Note that the five elements can be returned in any order.

It does not matter what you leave beyond the returned k (hence they are underscores).

Constraints:

- $0 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 50$
- $0 \leq \text{val} \leq 100$

28. Find the Index of the First Occurrence in a String

Medium

36021Add to ListShare

Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or `-1` if `needle` is not part of `haystack`.

Example 1:

Input: `haystack = "sadbutsad", needle = "sad"`

Output: `0`

Explanation: "sad" occurs at index 0 and 6.

The first occurrence is at index 0, so we return 0.

Example 2:

Input: `haystack = "leetcode", needle = "leeto"`

Output: `-1`

Explanation: "leeto" did not occur in "leetcode", so we return -1.

Constraints:

- `1 <= haystack.length, needle.length <= 104`
- `haystack` and `needle` consist of only lowercase English characters.

29. Divide Two Integers**Medium**

350511732Add to ListShare

Given two integers `dividend` and `divisor`, divide two integers **without** using multiplication, division, and mod operator.

The integer division should truncate toward zero, which means losing its fractional part. For example, `8.345` would be truncated to `8`, and `-2.7335` would be truncated to `-2`.

Return *the quotient after dividing dividend by divisor*.

Note: Assume we are dealing with an environment that could only store integers within the **32-bit** signed integer range: $[-2^{31}, 2^{31} - 1]$. For this problem, if the quotient is **strictly greater than** $2^{31} - 1$, then return $2^{31} - 1$, and if the quotient is **strictly less than** -2^{31} , then return -2^{31} .

Example 1:**Input:** dividend = 10, divisor = 3**Output:** 3**Explanation:** $10/3 = 3.33333\ldots$ which is truncated to 3.**Example 2:****Input:** dividend = 7, divisor = -3**Output:** -2**Explanation:** $7/-3 = -2.33333\ldots$ which is truncated to -2.**Constraints:**

- $-2^{31} \leq \text{dividend}, \text{divisor} \leq 2^{31} - 1$
- $\text{divisor} \neq 0$

30. Substring with Concatenation of All Words

Hard

18614Add to ListShare

You are given a string `s` and an array of strings `words`. All the strings of `words` are of **the same length**.

A **concatenated substring** in `s` is a substring that contains all the strings of any permutation of `words` concatenated.

- For example, if `words` = `["ab", "cd", "ef"]`, then `"abcdef"`, `"abefcd"`, `"cdabef"`, `"cdefab"`, `"efabcd"`, and `"efcdab"` are all concatenated strings. `"acdbef"` is not a concatenated substring because it is not the concatenation of any permutation of `words`.

Return *the starting indices of all the concatenated substrings in `s`*. You can return the answer in **any order**.

Example 1:**Input:** `s` = "barfoothefoobarman", `words` = `["foo", "bar"]`**Output:** `[0,9]`

Explanation: Since `words.length == 2` and `words[i].length == 3`, the concatenated substring has to be of length 6.

The substring starting at 0 is "barfoo". It is the concatenation of `["bar", "foo"]` which is a permutation of words.

The substring starting at 9 is "foobar". It is the concatenation of `["foo", "bar"]` which is a permutation of words.

The output order does not matter. Returning `[9,0]` is fine too.

Example 2:

Input: `s = "wordgoodgoodgoodbestword", words = ["word", "good", "best", "word"]`

Output: `[]`

Explanation: Since `words.length == 4` and `words[i].length == 4`, the concatenated substring has to be of length 16.

There is no substring of length 16 in `s` that is equal to the concatenation of any permutation of words.

We return an empty array.

Example 3:

Input: `s = "barfoofoobarthefoobarman", words = ["bar", "foo", "the"]`

Output: `[6,9,12]`

Explanation: Since `words.length == 3` and `words[i].length == 3`, the concatenated substring has to be of length 9.

The substring starting at 6 is "foobarthe". It is the concatenation of `["foo", "bar", "the"]` which is a permutation of words.

The substring starting at 9 is "barthefoo". It is the concatenation of `["bar", "the", "foo"]` which is a permutation of words.

The substring starting at 12 is "thefoobar". It is the concatenation of `["the", "foo", "bar"]` which is a permutation of words.

Constraints:

- `1 <= s.length <= 104`
- `1 <= words.length <= 5000`
- `1 <= words[i].length <= 30`
- `s` and `words[i]` consist of lowercase English letters.

31. Next Permutation

Medium

130023782Add to ListShare

A **permutation** of an array of integers is an arrangement of its members into a sequence or linear order.

- For example, for `arr = [1, 2, 3]`, the following are all the permutations of `arr`: `[1, 2, 3]`, `[1, 3, 2]`, `[2, 1, 3]`, `[2, 3, 1]`, `[3, 1, 2]`, `[3, 2, 1]`.

The **next permutation** of an array of integers is the next lexicographically greater permutation of its integer. More formally, if all the permutations of the array are sorted in one container according to their lexicographical order, then the **next permutation** of that array is the permutation that follows it in the sorted container. If such arrangement is not possible, the array must be rearranged as the lowest possible order (i.e., sorted in ascending order).

- For example, the next permutation of `arr = [1, 2, 3]` is `[1, 3, 2]`.
- Similarly, the next permutation of `arr = [2, 3, 1]` is `[3, 1, 2]`.
- While the next permutation of `arr = [3, 2, 1]` is `[1, 2, 3]` because `[3, 2, 1]` does not have a lexicographical larger rearrangement.

Given an array of integers `nums`, *find the next permutation of `nums`*.

The replacement must be in place and use only constant extra memory.

Example 1:

Input: `nums = [1, 2, 3]`

Output: `[1, 3, 2]`

Example 2:

Input: `nums = [3, 2, 1]`

Output: `[1, 2, 3]`

Example 3:

Input: `nums = [1, 1, 5]`

Output: `[1, 5, 1]`

Constraints:

- `1 <= nums.length <= 100`
- `0 <= nums[i] <= 100`

32. Longest Valid Parentheses

Hard

9721308Add to ListShare

Given a string containing just the characters `'('` and `')'`, find the length of the longest valid (well-formed) parentheses substring.

Example 1:

Input: `s = "(()"`

Output: 2

Explanation: The longest valid parentheses substring is `"()"`.

Example 2:

Input: `s = ")()())"`

Output: 4

Explanation: The longest valid parentheses substring is `"()()"`.

Example 3:

Input: `s = ""`

Output: 0

Constraints:

- `0 <= s.length <= 3 * 104`
- `s[i]` is `'('` or `')'`.

33. Search in Rotated Sorted Array

Medium

176601064Add to ListShare

There is an integer array `nums` sorted in ascending order (with **distinct** values).

Prior to being passed to your function, `nums` is **possibly rotated** at an unknown pivot index `k` (`1 <= k < nums.length`) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1],`

`nums[0], nums[1], ..., nums[k-1]` (**0-indexed**). For example, `[0,1,2,4,5,6,7]` might be rotated at pivot index `3` and become `[4,5,6,7,0,1,2]`.

Given the array `nums` **after** the possible rotation and an integer `target`, return *the index of target if it is in nums, or -1 if it is not in nums*.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [4,5,6,7,0,1,2]`, `target = 0`

Output: `4`

Example 2:

Input: `nums = [4,5,6,7,0,1,2]`, `target = 3`

Output: `-1`

Example 3:

Input: `nums = [1]`, `target = 0`

Output: `-1`

Constraints:

- $1 \leq \text{nums.length} \leq 5000$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- All values of `nums` are **unique**.
- `nums` is an ascending array that is possibly rotated.
- $-10^4 \leq \text{target} \leq 10^4$

34. Find First and Last Position of Element in Sorted Array

Medium

13988345 Add to List Share

Given an array of integers `nums` sorted in non-decreasing order, find the starting and ending position of a given `target` value.

If `target` is not found in the array, return `[-1, -1]`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: nums = [5,7,7,8,8,10], target = 8

Output: [3,4]

Example 2:

Input: nums = [5,7,7,8,8,10], target = 6

Output: [-1,-1]

Example 3:

Input: nums = [], target = 0

Output: [-1,-1]

Constraints:

- $0 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- nums is a non-decreasing array.
- $-10^9 \leq \text{target} \leq 10^9$

35. Search Insert Position

Easy

9794469Add to ListShare

Given a sorted array of distinct integers and a target value, return the index if the target is found. If not, return the index where it would be if it were inserted in order.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: nums = [1,3,5,6], target = 5

Output: 2

Example 2:

Input: nums = [1,3,5,6], target = 2

Output: 1

Example 3:

Input: nums = [1,3,5,6], target = 7

Output: 4

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- `nums` contains **distinct** values sorted in **ascending** order.
- $-10^4 \leq \text{target} \leq 10^4$

36. Valid Sudoku

Medium

6467796Add to ListShare

Determine if a 9×9 Sudoku board is valid. Only the filled cells need to be validated **according to the following rules:**

1. Each row must contain the digits 1–9 without repetition.
2. Each column must contain the digits 1–9 without repetition.
3. Each of the nine 3×3 sub-boxes of the grid must contain the digits 1–9 without repetition.

Note:

- A Sudoku board (partially filled) could be valid but is not necessarily solvable.
- Only the filled cells need to be validated according to the mentioned rules.

Example 1:

5	3		7				
6		1	9	5			
9	8				6		
8		6				3	
4		8	3			1	
7		2				6	
6				2	8		
	4	1	9			5	
		8		7	9		

Input: board =

```
[[ "5", "3", ".", ".", "7", ".", ".", ".", "."]
 , [ "6", ".", ".", "1", "9", "5", ".", ".", "."]
 , [ ".", "9", "8", ".", ".", ".", ".", "6", "."]
 , [ "8", ".", ".", ".", "6", ".", ".", ".", "3"]
 , [ "4", ".", ".", "8", ".", "3", ".", ".", "1"]
 , [ "7", ".", ".", ".", "2", ".", ".", ".", "6"]
 , [ ".", "6", ".", ".", ".", "2", "8", "."]
 , [ ".", "4", "1", "9", ".", ".", "7", "9"]]
```

Output: true

Example 2:

Input: board =

```
[[ "8", "3", ".", ".", "7", ".", ".", ".", "."]
 , [ "6", ".", ".", "1", "9", "5", ".", ".", "."]
 , [ ".", "9", "8", ".", ".", ".", ".", "6", "."]
 , [ "8", ".", ".", ".", "6", ".", ".", ".", "3"]
 , [ "4", ".", ".", "8", ".", "3", ".", ".", "1"]
 , [ "7", ".", ".", ".", "2", ".", ".", ".", "6"]]
```

```
[[".", "6", ".", ".", ".", ".", "2", "8", "."]  
,[[".", ".", ".", "4", "1", "9", ".", ".", "5"]]  
,[[".", ".", ".", ".", "8", ".", ".", "7", "9"]]
```

Output: false

Explanation: Same as Example 1, except with the 5 in the top left corner being modified to 8. Since there are two 8's in the top left 3x3 sub-box, it is invalid.

Constraints:

- `board.length == 9`
- `board[i].length == 9`
- `board[i][j]` is a digit 1-9 or '.'.

37. Sudoku Solver

Hard

6562176Add to ListShare

Write a program to solve a Sudoku puzzle by filling the empty cells.

A sudoku solution must satisfy **all of the following rules**:

1. Each of the digits 1-9 must occur exactly once in each row.
2. Each of the digits 1-9 must occur exactly once in each column.
3. Each of the digits 1-9 must occur exactly once in each of the 9 3x3 sub-boxes of the grid.

The '.' character indicates empty cells.

Example 1:

5	3		7					
6		1	9	5				
9	8				6			
8		6				3		
4		8	3			1		
7		2				6		
6				2	8			
	4	1	9			5		
	8			7	9			

Input: board =

```
[[ "5", "3", ".", ".", "7", ".", ".", ".", "."], [ "6", ".", ".", "1", "9", "5", ".", ".", "."], [ ".", "9", "8", ".", ".", "6", "."], [ "8", ".", ".", "6", ".", ".", "3"], [ "4", ".", ".", "8", ".", "3", ".", "1"], [ "7", ".", ".", "2", ".", ".", "6"], [ "6", ".", "2", "8", "."], [ "4", "1", "9", ".", "5"], [ "8", "7", "9", "6", "1", "5", "2", "3"], [ "9", "6", "1", "5", "3", "7", "8", "4"], [ "2", "8", "7", "4", "1", "9", "6", "3", "5"], [ "3", "4", "5", "2", "8", "6", "1", "7", "9"]]
```

Output:

```
[[ "5", "3", "4", "6", "7", "8", "9", "1", "2"], [ "6", "7", "2", "1", "9", "5", "3", "4", "8"], [ "1", "9", "8", "3", "4", "2", "5", "6", "7"], [ "8", "5", "9", "7", "6", "1", "4", "2", "3"], [ "4", "2", "6", "8", "5", "3", "7", "9", "1"], [ "7", "1", "3", "9", "2", "4", "8", "5", "6"], [ "9", "6", "1", "5", "3", "7", "2", "8", "4"], [ "2", "8", "7", "4", "1", "9", "6", "3", "5"], [ "3", "4", "5", "2", "8", "6", "1", "7", "9"]]
```

Explanation: The input board is shown above and the only valid solution is shown below:

5	3	4	6	7	8	9	1	2
6	7	2	1	9	5	3	4	8
1	9	8	3	4	2	5	6	7
8	5	9	7	6	1	4	2	3
4	2	6	8	5	3	7	9	1
7	1	3	9	2	4	8	5	6
9	6	1	5	3	7	2	8	4
2	8	7	4	1	9	6	3	5
3	4	5	2	8	6	1	7	9

Constraints:

- `board.length == 9`
- `board[i].length == 9`
- `board[i][j]` is a digit or `'.'`.
- It is **guaranteed** that the input board has only one solution.

38. Count and Say**Medium**

20144511 Add to List Share

The **count-and-say** sequence is a sequence of digit strings defined by the recursive formula:

- `countAndSay(1) = "1"`
- `countAndSay(n)` is the way you would "say" the digit string from `countAndSay(n-1)`, which is then converted into a different digit string.

To determine how you "say" a digit string, split it into the **minimal** number of substrings such that each substring contains exactly **one** unique digit. Then for each substring, say the number of digits, then say the digit. Finally, concatenate every said digit.

For example, the saying and conversion for digit string "3322251":

"3322251
two 3's, three 2's, one 5, and one 1
2 3 + 3 2 + 1 5 + 1 1
"23321511

Given a positive integer `n`, return *the n^{th} term of the count-and-say sequence*.

Example 1:**Input:** `n = 1`**Output:** "1"**Explanation:** This is the base case.**Example 2:****Input:** `n = 4`

Output: "1211"

Explanation:

countAndSay(1) = "1"

countAndSay(2) = say "1" = one 1 = "11"

countAndSay(3) = say "11" = two 1's = "21"

countAndSay(4) = say "21" = one 2 + one 1 = "12" + "11" = "1211"

Constraints:

- $1 \leq n \leq 30$

39. Combination Sum

Medium

13482276Add to ListShare

Given an array of **distinct** integers `candidates` and a target integer `target`, return a *list of all unique combinations* of `candidates` where the chosen numbers sum to `target`. You may return the combinations in **any order**.

The **same** number may be chosen from `candidates` an **unlimited number of times**. Two combinations are unique if the frequency of at least one of the chosen numbers is different.

The test cases are generated such that the number of unique combinations that sum up to `target` is less than 150 combinations for the given input.

Example 1:

Input: candidates = [2,3,6,7], target = 7

Output: [[2,2,3],[7]]

Explanation:

2 and 3 are candidates, and $2 + 2 + 3 = 7$. Note that 2 can be used multiple times.

7 is a candidate, and $7 = 7$.

These are the only two combinations.

Example 2:

Input: candidates = [2,3,5], target = 8

Output: [[2,2,2,2],[2,3,3],[3,5]]

Example 3:

Input: candidates = [2], target = 1

Output: []

Constraints:

- $1 \leq \text{candidates.length} \leq 30$
- $2 \leq \text{candidates}[i] \leq 40$
- All elements of `candidates` are **distinct**.
- $1 \leq \text{target} \leq 500$

40. Combination Sum II

Medium

6919169Add to ListShare

Given a collection of candidate numbers (`candidates`) and a target number (`target`), find all unique combinations in `candidates` where the candidate numbers sum to `target`.

Each number in `candidates` may only be used **once** in the combination.

Note: The solution set must not contain duplicate combinations.

Example 1:

Input: candidates = [10,1,2,7,6,1,5], target = 8

Output:

[

[1,1,6],

[1,2,5],

[1,7],

[2,6]

]

Example 2:

Input: candidates = [2,5,2,1,2], target = 5

Output:

```
[  
[1,2,2],  
[5]  
]
```

Constraints:

- $1 \leq \text{candidates.length} \leq 100$
- $1 \leq \text{candidates}[i] \leq 50$
- $1 \leq \text{target} \leq 30$

41. First Missing Positive

Hard

117541458Add to ListShare

Given an unsorted integer array `nums`, return the smallest missing positive integer.

You must implement an algorithm that runs in $O(n)$ time and uses constant extra space.

Example 1:

Input: `nums = [1,2,0]`

Output: 3

Explanation: The numbers in the range [1,2] are all in the array.

Example 2:

Input: `nums = [3,4,-1,1]`

Output: 2

Explanation: 1 is in the array but 2 is missing.

Example 3:

Input: `nums = [7,8,9,11,12]`

Output: 1

Explanation: The smallest positive integer 1 is missing.

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

42. Trapping Rain Water**Hard**

22986312Add to ListShare

Given n non-negative integers representing an elevation map where the width of each bar is 1, compute how much water it can trap after raining.

Example 1:

Input: height = [0,1,0,2,1,0,1,3,2,1,2,1]

Output: 6

Explanation: The above elevation map (black section) is represented by array [0,1,0,2,1,0,1,3,2,1,2,1]. In this case, 6 units of rain water (blue section) are being trapped.

Example 2:

Input: height = [4,2,0,3,2,5]

Output: 9

Constraints:

- $n == \text{height.length}$
- $1 \leq n \leq 2 * 10^4$
- $0 \leq \text{height}[i] \leq 10^5$

43. Multiply Strings

Medium

51802174Add to ListShare

Given two non-negative integers `num1` and `num2` represented as strings, return the product of `num1` and `num2`, also represented as a string.

Note: You must not use any built-in BigInteger library or convert the inputs to integer directly.

Example 1:

Input: `num1 = "2", num2 = "3"`

Output: "6"

Example 2:

Input: `num1 = "123", num2 = "456"`

Output: "56088"

Constraints:

- `1 <= num1.length, num2.length <= 200`
- `num1` and `num2` consist of digits only.
- Both `num1` and `num2` do not contain any leading zero, except the number `0` itself.

44. Wildcard Matching

Hard

5813253Add to ListShare

Given an input string (`s`) and a pattern (`p`), implement wildcard pattern matching with support for `'?'` and `'*'` where:

- `'?'` Matches any single character.
- `'*'` Matches any sequence of characters (including the empty sequence).

The matching should cover the **entire** input string (not partial).

Example 1:

Input: `s = "aa", p = "a"`

Output: false

Explanation: "a" does not match the entire string "aa".

Example 2:

Input: s = "aa", p = "*"

Output: true

Explanation: '*' matches any sequence.

Example 3:

Input: s = "cb", p = "?a"

Output: false

Explanation: '?' matches 'c', but the second letter is 'a', which does not match 'b'.

Constraints:

- $0 \leq s.length, p.length \leq 2000$
- s contains only lowercase English letters.
- p contains only lowercase English letters, '?' or '*'.

45. Jump Game II

Medium

9658342 Add to List Share

Given an array of non-negative integers `nums`, you are initially positioned at the first index of the array.

Each element in the array represents your maximum jump length at that position.

Your goal is to reach the last index in the minimum number of jumps.

You can assume that you can always reach the last index.

Example 1:

Input: nums = [2,3,1,1,4]

Output: 2

Explanation: The minimum number of jumps to reach the last index is 2. Jump 1 step from index 0 to 1, then 3 steps to the last index.

Example 2:**Input:** nums = [2,3,0,1,4]**Output:** 2**Constraints:**

- $1 \leq \text{nums.length} \leq 10^4$
- $0 \leq \text{nums}[i] \leq 1000$

46. Permutations**Medium**

13049220Add to ListShare

Given an array `nums` of distinct integers, return *all the possible permutations*. You can return the answer in **any order**.

Example 1:**Input:** nums = [1,2,3]**Output:** [[1,2,3],[1,3,2],[2,1,3],[2,3,1],[3,1,2],[3,2,1]]**Example 2:****Input:** nums = [0,1]**Output:** [[0,1],[1,0]]**Example 3:****Input:** nums = [1]**Output:** [[1]]**Constraints:**

- $1 \leq \text{nums.length} \leq 6$
- $-10 \leq \text{nums}[i] \leq 10$
- All the integers of `nums` are **unique**.

47. Permutations II

Medium

6511113Add to ListShare

Given a collection of numbers, `nums`, that might contain duplicates, return *all possible unique permutations in any order*.

Example 1:

Input: `nums = [1,1,2]`

Output:

```
[[1,1,2],  
 [1,2,1],  
 [2,1,1]]
```

Example 2:

Input: `nums = [1,2,3]`

Output: `[[1,2,3],[1,3,2],[2,1,3],[2,3,1],[3,1,2],[3,2,1]]`

Constraints:

- `1 <= nums.length <= 8`
- `-10 <= nums[i] <= 10`

48. Rotate Image**Medium**


12250581Add to ListShare

You are given an `n x n` 2D `matrix` representing an image, rotate the image by **90** degrees (clockwise).

You have to rotate the image **in-place**, which means you have to modify the input 2D matrix directly. **DO NOT** allocate another 2D matrix and do the rotation.

Example 1:

1	2	3
4	5	6
7	8	9




7	4	1
8	5	2
9	6	3

Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]

Output: [[7,4,1],[8,5,2],[9,6,3]]

Example 2:

5	1	9	11
2	4	8	10
13	3	6	7
15	14	12	16



15	13	2	5
14	3	4	1
12	6	8	9
16	7	10	11

Input: matrix = [[5,1,9,11],[2,4,8,10],[13,3,6,7],[15,14,12,16]]

Output: [[15,13,2,5],[14,3,4,1],[12,6,8,9],[16,7,10,11]]

Constraints:

- $n == \text{matrix.length} == \text{matrix}[i].length$
- $1 \leq n \leq 20$
- $-1000 \leq \text{matrix}[i][j] \leq 1000$

49. Group Anagrams

Medium

11799370 Add to List Share

Given an array of strings `strs`, group **the anagrams** together. You can return the answer in **any order**.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: `strs = ["eat", "tea", "tan", "ate", "nat", "bat"]`

Output: `[["bat"], ["nat", "tan"], ["ate", "eat", "tea"]]`

Example 2:

Input: `strs = [""]`

Output: `[[""]]`

Example 3:

Input: `strs = ["a"]`

Output: `[["a"]]`

Constraints:

- $1 \leq \text{strs.length} \leq 10^4$
- $0 \leq \text{strs[i].length} \leq 100$
- `strs[i]` consists of lowercase English letters.

50. Pow(x, n)

Medium

57816335Add to ListShare

Implement `pow(x, n)`, which calculates `x` raised to the power `n` (i.e., x^n).

Example 1:

Input: `x = 2.00000, n = 10`

Output: `1024.00000`

Example 2:

Input: x = 2.10000, n = 3

Output: 9.26100

Example 3:

Input: x = 2.00000, n = -2

Output: 0.25000

Explanation: $2^{-2} = 1/2^2 = 1/4 = 0.25$

Constraints:

- $-100.0 < x < 100.0$
- $-2^{31} \leq n \leq 2^{31}-1$
- n is an integer.
- $-10^4 \leq x^n \leq 10^4$

51. N-Queens

Hard


8360189 Add to List Share

The **n-queens** puzzle is the problem of placing n queens on an n x n chessboard such that no two queens attack each other.

Given an integer n, return *all distinct solutions to the n-queens puzzle*. You may return the answer in **any order**.

Each solution contains a distinct board configuration of the n-queens' placement, where 'Q' and '.' both indicate a queen and an empty space, respectively.

Example 1:



Input: $n = 4$

Output: `[[".Q..", "...Q", "Q...", "...Q."], ["..Q.", "Q...", "...Q", ".Q.."]]`

Explanation: There exist two distinct solutions to the 4-queens puzzle as shown above

Example 2:

Input: $n = 1$

Output: `[["Q"]]`

Constraints:

- $1 \leq n \leq 9$

52. N-Queens II


Hard

2805230Add to ListShare

The **n-queens** puzzle is the problem of placing n queens on an $n \times n$ chessboard such that no two queens attack each other.

Given an integer n , return *the number of distinct solutions to the n-queens puzzle*.

Example 1:



Input: n = 4

Output: 2

Explanation: There are two distinct solutions to the 4-queens puzzle as shown.

Example 2:

Input: n = 1

Output: 1

Constraints:

- 1 <= n <= 9

53. Maximum Subarray

Medium

252041159Add to ListShare

Given an integer array `nums`, find the contiguous subarray (containing at least one number) which has the largest sum and return *its sum*.

A **subarray** is a **contiguous** part of an array.

Example 1:

Input: `nums` = [-2,1,-3,4,-1,2,1,-5,4]

Output: 6

Explanation: [4, -1, 2, 1] has the largest sum = 6.

Example 2:

Input: nums = [1]

Output: 1

Example 3:

Input: nums = [5, 4, -1, 7, 8]

Output: 23

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$


54. Spiral Matrix

Medium

8999922Add to ListShare

Given an $m \times n$ matrix, return all elements of the matrix in spiral order.


Example 1:



Input: matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]

Output: [1, 2, 3, 6, 9, 8, 7, 4, 5]

Example 2:



Input: matrix = [[1,2,3,4],[5,6,7,8],[9,10,11,12]]

Output: [1,2,3,4,8,12,11,10,9,5,6,7]

Constraints:

- `m == matrix.length`
- `n == matrix[i].length`
- `1 <= m, n <= 10`
- `-100 <= matrix[i][j] <= 100`

55. Jump Game

Medium

13128690 Add to List Share

You are given an integer array `nums`. You are initially positioned at the array's **first index**, and each element in the array represents your maximum jump length at that position.

Return `true` if you can reach the last index, or `false` otherwise.

Example 1:

Input: `nums = [2,3,1,1,4]`

Output: `true`

Explanation: Jump 1 step from index 0 to 1, then 3 steps to the last index.

Example 2:

Input: `nums = [3,2,1,0,4]`

Output: false

Explanation: You will always arrive at index 3 no matter what. Its maximum jump length is 0, which makes it impossible to reach the last index.

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $0 \leq \text{nums[i]} \leq 10^5$

56. Merge Intervals

Medium

16291582Add to ListShare

Given an array of `intervals` where `intervals[i] = [start}_i, end}_i`, merge all overlapping intervals, and return *an array of the non-overlapping intervals that cover all the intervals in the input*.

Example 1:

Input: `intervals = [[1,3],[2,6],[8,10],[15,18]]`

Output: `[[1,6],[8,10],[15,18]]`

Explanation: Since intervals `[1,3]` and `[2,6]` overlap, merge them into `[1,6]`.

Example 2:

Input: `intervals = [[1,4],[4,5]]`

Output: `[[1,5]]`

Explanation: Intervals `[1,4]` and `[4,5]` are considered overlapping.

Constraints:

- $1 \leq \text{intervals.length} \leq 10^4$
- $\text{intervals[i].length} == 2$
- $0 \leq \text{start}_i \leq \text{end}_i \leq 10^4$

57. Insert Interval

Medium

5935404Add to ListShare

You are given an array of non-overlapping intervals `intervals` where `intervals[i] = [starti, endi]` represent the start and the end of the *ith* interval and `intervals` is sorted in ascending order by `starti`. You are also given an interval `newInterval = [start, end]` that represents the start and end of another interval.

Insert `newInterval` into `intervals` such that `intervals` is still sorted in ascending order by `starti` and `intervals` still does not have any overlapping intervals (merge overlapping intervals if necessary).

Return `intervals` after the insertion.

Example 1:

Input: `intervals = [[1,3],[6,9]]`, `newInterval = [2,5]`

Output: `[[1,5],[6,9]]`

Example 2:

Input: `intervals = [[1,2],[3,5],[6,7],[8,10],[12,16]]`, `newInterval = [4,8]`

Output: `[[1,2],[3,10],[12,16]]`

Explanation: Because the new interval `[4,8]` overlaps with `[3,5],[6,7],[8,10]`.

Constraints:

- $0 \leq \text{intervals.length} \leq 10^4$
- $\text{intervals}[i].length == 2$
- $0 \leq \text{start}_i \leq \text{end}_i \leq 10^5$
- `intervals` is sorted by `starti` in **ascending** order.
- `newInterval.length == 2`
- $0 \leq \text{start} \leq \text{end} \leq 10^5$

58. Length of Last Word

Easy

1782119Add to ListShare

Given a string `s` consisting of words and spaces, return the length of the **last** word in the string.

A **word** is a maximal substring consisting of non-space characters only.

Example 1:

Input: s = "Hello World"

Output: 5

Explanation: The last word is "World" with length 5.

Example 2:

Input: s = " fly me to the moon "

Output: 4

Explanation: The last word is "moon" with length 4.

Example 3:

Input: s = "luffy is still joyboy"

Output: 6

Explanation: The last word is "joyboy" with length 6.

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of only English letters and spaces ' '.
- There will be at least one word in s.


59. Spiral Matrix II

Medium

4199198Add to ListShare

Given a positive integer n, generate an $n \times n$ matrix filled with elements from 1 to n^2 in spiral order.

Example 1:



Input: $n = 3$

Output: $[[1, 2, 3], [8, 9, 4], [7, 6, 5]]$

Example 2:

Input: $n = 1$

Output: $[[1]]$

Constraints:

- $1 \leq n \leq 20$

60. Permutation Sequence

Hard

4802419 Add to List Share

The set $[1, 2, 3, \dots, n]$ contains a total of $n!$ unique permutations.

By listing and labeling all of the permutations in order, we get the following sequence for $n = 3$:

1. "123"
2. "132"
3. "213"
4. "231"
5. "312"
6. "321"




Given n and k , return the k^{th} permutation sequence.

Example 1:**Input:** n = 3, k = 3**Output:** "213"**Example 2:****Input:** n = 4, k = 9**Output:** "2314"**Example 3:****Input:** n = 3, k = 1**Output:** "123"**Constraints:**

- $1 \leq n \leq 9$
- $1 \leq k \leq n!$

61. Rotate List**Medium**


63861311Add to ListShare

Given the `head` of a linked list, rotate the list to the right by `k` places.**Example 1:****rotate 1****rotate 2**


Input: head = [1,2,3,4,5], k = 2

Output: [4,5,1,2,3]


Example 2:




rotate 1




rotate 2



rotate 3



rotate 4



Input: head = [0,1,2], k = 4

Output: [2,0,1]

Constraints:

- The number of nodes in the list is in the range [0, 500].
- $-100 \leq \text{Node.val} \leq 100$
- $0 \leq k \leq 2 * 10^9$

62. Unique Paths

Medium

11804347 Add to List Share

There is a robot on an $m \times n$ grid. The robot is initially located at the **top-left corner** (i.e., $\text{grid}[0][0]$). The robot tries to move to the **bottom-right corner** (i.e., $\text{grid}[m - 1][n - 1]$). The robot can only move either down or right at any point in time.

Given the two integers m and n , return *the number of possible unique paths that the robot can take to reach the bottom-right corner*.

The test cases are generated so that the answer will be less than or equal to $2 * 10^9$.

Example 1:



Input: $m = 3$, $n = 7$

Output: 28

Example 2:

Input: $m = 3$, $n = 2$

Output: 3

Explanation: From the top-left corner, there are a total of 3 ways to reach the bottom-right corner:

1. Right \rightarrow Down \rightarrow Down
2. Down \rightarrow Down \rightarrow Right
3. Down \rightarrow Right \rightarrow Down

Constraints:

- $1 \leq m, n \leq 100$

63. Unique Paths II

Medium

5998415Add to ListShare


You are given an $m \times n$ integer array `grid`. There is a robot initially located at the **top-left corner** (i.e., `grid[0][0]`). The robot tries to move to the **bottom-right corner** (i.e., `grid[m-1][n-1]`). The robot can only move either down or right at any point in time.

An obstacle and space are marked as `1` or `0` respectively in `grid`. A path that the robot takes cannot include **any** square that is an obstacle.

Return *the number of possible unique paths that the robot can take to reach the bottom-right corner*.

The testcases are generated so that the answer will be less than or equal to $2 * 10^9$.

Example 1:



Input: `obstacleGrid = [[0,0,0],[0,1,0],[0,0,0]]`


Output: 2

Explanation: There is one obstacle in the middle of the 3x3 grid above.

There are two ways to reach the bottom-right corner:

1. Right \rightarrow Right \rightarrow Down \rightarrow Down
2. Down \rightarrow Down \rightarrow Right \rightarrow Right

Example 2:



Input: obstacleGrid = [[0,1],[0,0]]

Output: 1

Constraints:

- `m == obstacleGrid.length`
- `n == obstacleGrid[i].length`
- `1 <= m, n <= 100`
- `obstacleGrid[i][j]` is 0 or 1.

64. Minimum Path Sum

Medium

8635112Add to ListShare

Given a `m x n` grid filled with non-negative numbers, find a path from top left to bottom right, which minimizes the sum of all numbers along its path.

Note: You can only move either down or right at any point in time.

Example 1:

1	3	1
1	5	1
4	2	1

Input: grid = [[1,3,1],[1,5,1],[4,2,1]]

Output: 7

Explanation: Because the path 1 → 3 → 1 → 1 → 1 minimizes the sum.

Example 2:

Input: grid = [[1,2,3],[4,5,6]]

Output: 12

Constraints:

- `m == grid.length`
- `n == grid[i].length`
- `1 <= m, n <= 200`
- `0 <= grid[i][j] <= 100`

65. Valid Number

Hard

7461312Add to ListShare

A **valid number** can be split up into these components (in order):

1. A **decimal number** or an **integer**.
2. (Optional) An `'e'` or `'E'`, followed by an **integer**.

A **decimal number** can be split up into these components (in order):

1. (Optional) A sign character (either `'+'` or `'-'`).
2. One of the following formats:
 1. One or more digits, followed by a dot `'.'`.
 2. One or more digits, followed by a dot `'.'`, followed by one or more digits.
 3. A dot `'.'`, followed by one or more digits.

An **integer** can be split up into these components (in order):

1. (Optional) A sign character (either `'+'` or `'-'`).
2. One or more digits.

For example, all the following are valid numbers: `["2", "0089", "-0.1", "+3.14", "4.", "-.9", "2e10", "-90E3", "3e+7", "+6e-1", "53.5e93", "-123.456e789"]`, while the following are not valid numbers: `["abc", "1a", "1e", "e3", "99e2.5", "--6", "-+3", "95a54e53"]`.

Given a string `s`, return `true` if `s` is a **valid number**.

Example 1:

Input: `s = "0"`

Output: `true`

Example 2:

Input: `s = "e"`

Output: `false`

Example 3:

Input: `s = "."`

Output: `false`

Constraints:

- `1 <= s.length <= 20`
- `s` consists of only English letters (both uppercase and lowercase), digits (0–9), plus `+`, minus `-`, or dot `.`.

66. Plus One

Easy

53524472Add to ListShare

You are given a **large integer** represented as an integer array `digits`, where each `digits[i]` is the `ith` digit of the integer. The digits are ordered from most significant to least significant in left-to-right order. The large integer does not contain any leading 0's.

Increment the large integer by one and return *the resulting array of digits*.

Example 1:

Input: `digits = [1,2,3]`

Output: `[1,2,4]`

Explanation: The array represents the integer 123.

Incrementing by one gives $123 + 1 = 124$.

Thus, the result should be $[1,2,4]$.

Example 2:

Input: digits = [4,3,2,1]

Output: [4,3,2,2]

Explanation: The array represents the integer 4321.

Incrementing by one gives $4321 + 1 = 4322$.

Thus, the result should be [4,3,2,2].

Example 3:

Input: digits = [9]

Output: [1,0]

Explanation: The array represents the integer 9.

Incrementing by one gives $9 + 1 = 10$.

Thus, the result should be [1,0].

Constraints:

- $1 \leq \text{digits.length} \leq 100$
- $0 \leq \text{digits}[i] \leq 9$
- `digits` does not contain any leading 0's.

67. Add Binary

Easy

5940629Add to ListShare

Given two binary strings `a` and `b`, return *their sum as a binary string*.

Example 1:

Input: a = "11", b = "1"

Output: "100"

Example 2:

Input: a = "1010", b = "1011"

Output: "10101"

Constraints:

- $1 \leq a.length, b.length \leq 10^4$
- a and b consist only of '0' or '1' characters.
- Each string does not contain leading zeros except for the zero itself.

68. Text Justification

Hard

20453248Add to ListShare

Given an array of strings `words` and a width `maxWidth`, format the text such that each line has exactly `maxWidth` characters and is fully (left and right) justified.

You should pack your words in a greedy approach; that is, pack as many words as you can in each line. Pad extra spaces ' ' when necessary so that each line has exactly `maxWidth` characters.

Extra spaces between words should be distributed as evenly as possible. If the number of spaces on a line does not divide evenly between words, the empty slots on the left will be assigned more spaces than the slots on the right.

For the last line of text, it should be left-justified, and no extra space is inserted between words.

Note:

- A word is defined as a character sequence consisting of non-space characters only.
- Each word's length is guaranteed to be greater than 0 and not exceed `maxWidth`.
- The input array `words` contains at least one word.

Example 1:

Input: words = ["This", "is", "an", "example", "of", "text", "justification."],
`maxWidth` = 16

Output:

[

```
"This    is    an",
"example  of text",
```

```

"justification.  "
]

```

Example 2:

Input: words = ["What", "must", "be", "acknowledgment", "shall", "be"], maxWidth = 16

Output:

```

[
  "What    must    be",
  "acknowledgment  ",
  "shall be        "
]

```

Explanation: Note that the last line is "shall be " instead of "shall be", because the last line must be left-justified instead of fully-justified.

Note that the second line is also left-justified because it contains only one word.

Example 3:

Input: words = ["Science", "is", "what", "we", "understand", "well", "enough", "to", "explain", "to", "a", "computer.", "Art", "is", "everything", "else", "we", "do"], maxWidth = 20

Output:

```

[
  "Science is what we",
  "understand      well",
  "enough to explain to",
  "a  computer. Art is",
  "everything else we",
  "do                "
]

```

Constraints:

- $1 \leq \text{words.length} \leq 300$
- $1 \leq \text{words[i].length} \leq 20$
- `words[i]` consists of only English letters and symbols.
- $1 \leq \text{maxWidth} \leq 100$
- $\text{words[i].length} \leq \text{maxWidth}$

69. Sqrt(x)

Easy

48873556Add to ListShare

Given a non-negative integer `x`, compute and return *the square root of x*.

Since the return type is an integer, the decimal digits are **truncated**, and only **the integer part** of the result is returned.

Note: You are not allowed to use any built-in exponent function or operator, such as `pow(x, 0.5)` or `x ** 0.5`.

Example 1:

Input: `x = 4`

Output: 2

Example 2:

Input: `x = 8`

Output: 2

Explanation: The square root of 8 is 2.82842..., and since the decimal part is truncated, 2 is returned.

Constraints:

- $0 \leq x \leq 2^{31} - 1$

70. Climbing Stairs

Easy

14551429Add to ListShare

You are climbing a staircase. It takes `n` steps to reach the top.

Each time you can either climb `1` or `2` steps. In how many distinct ways can you climb to the top?

Example 1:**Input:** n = 2**Output:** 2**Explanation:** There are two ways to climb to the top.

1. 1 step + 1 step
2. 2 steps

Example 2:**Input:** n = 3**Output:** 3**Explanation:** There are three ways to climb to the top.

1. 1 step + 1 step + 1 step
2. 1 step + 2 steps
3. 2 steps + 1 step

Constraints:

- 1 <= n <= 45

71. Simplify Path

Medium

2893569Add to ListShare

Given a string `path`, which is an **absolute path** (starting with a slash `'/'`) to a file or directory in a Unix-style file system, convert it to the simplified **canonical path**.

In a Unix-style file system, a period `'.'` refers to the current directory, a double period `'..'` refers to the directory up a level, and any multiple consecutive slashes (i.e. `'//'`) are treated as a single slash `'/'`. For this problem, any other format of periods such as `'...'` are treated as file/directory names.

The **canonical path** should have the following format:

- The path starts with a single slash `' / '`.
- Any two directories are separated by a single slash `' / '`.
- The path does not end with a trailing `' / '`.
- The path only contains the directories on the path from the root directory to the target file or directory (i.e., no period `' .. '` or double period `' ... '`)

Return *the simplified canonical path*.

Example 1:

Input: path = `"/home/"`

Output: `"/home"`

Explanation: Note that there is no trailing slash after the last directory name.

Example 2:

Input: path = `"/../"`

Output: `"/"`

Explanation: Going one level up from the root directory is a no-op, as the root level is the highest level you can go.

Example 3:

Input: path = `"/home//foo/"`

Output: `"/home/foo"`

Explanation: In the canonical path, multiple consecutive slashes are replaced by a single one.

Constraints:

- `1 <= path.length <= 3000`
- `path` consists of English letters, digits, period `' .. '`, slash `' / '` or `' _ '`.
- `path` is a valid absolute Unix path.

72. Edit Distance

Hard

10040115Add to ListShare

Given two strings `word1` and `word2`, return *the minimum number of operations required to convert* `word1` *to* `word2`.

You have the following three operations permitted on a word:

- Insert a character
- Delete a character
- Replace a character

Example 1:

Input: word1 = "horse", word2 = "ros"

Output: 3

Explanation:

horse -> rorse (replace 'h' with 'r')

rorse -> rose (remove 'r')

rose -> ros (remove 'e')

Example 2:

Input: word1 = "intention", word2 = "execution"

Output: 5

Explanation:

intention -> inention (remove 't')

inention -> enention (replace 'i' with 'e')

enention -> exention (replace 'n' with 'x')

exention -> exection (replace 'n' with 'c')

exection -> execution (insert 'u')

Constraints:

- $0 \leq \text{word1.length}, \text{word2.length} \leq 500$
- `word1` and `word2` consist of lowercase English letters.

73. Set Matrix Zeroes


Medium

9241551Add to ListShare

Given an $m \times n$ integer matrix `matrix`, if an element is `0`, set its entire row and column to `0`'s.

You must do it in place.

Example 1:




1	1	1
1	0	1
1	1	1

1	0	1
0	0	0
1	0	1

Input: `matrix = [[1,1,1],[1,0,1],[1,1,1]]`

Output: `[[1,0,1],[0,0,0],[1,0,1]]`

Example 2:



0	1	2	0
3	4	5	2
1	3	1	5

0	0	0	0
0	4	5	0
0	3	1	0

Input: `matrix = [[0,1,2,0],[3,4,5,2],[1,3,1,5]]`

Output: `[[0,0,0,0],[0,4,5,0],[0,3,1,0]]`

Constraints:

- `m == matrix.length`
- `n == matrix[0].length`
- `1 <= m, n <= 200`

- $-2^{31} \leq \text{matrix}[i][j] \leq 2^{31} - 1$

Follow up:

- A straightforward solution using $O(mn)$ space is probably a bad idea.
- A simple improvement uses $O(m + n)$ space, but still not the best solution.
- Could you devise a constant space solution?

74. Search a 2D Matrix

Medium

9768306 Add to List Share

Write an efficient algorithm that searches for a value `target` in an $m \times n$ integer matrix `matrix`.

This matrix has the following properties:

- Integers in each row are sorted from left to right.
- The first integer of each row is greater than the last integer of the previous row.

Example 1:

1	3	5	7
10	11	16	20
23	30	34	60

Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 3`

Output: `true`

Example 2:

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 13

Output: false

Constraints:

- `m == matrix.length`
- `n == matrix[i].length`
- `1 <= m, n <= 100`
- `-104 <= matrix[i][j], target <= 104`

75. Sort Colors

Medium

12279462 Add to List Share

Given an array `nums` with `n` objects colored red, white, or blue, sort them in-place so that objects of the same color are adjacent, with the colors in the order red, white, and blue.

We will use the integers `0`, `1`, and `2` to represent the color red, white, and blue, respectively.

You must solve this problem without using the library's sort function.

Example 1:

Input: `nums = [2,0,2,1,1,0]`

Output: `[0,0,1,1,2,2]`

Example 2:

Input: `nums = [2,0,1]`

Output: [0,1,2]

Constraints:

- `n == nums.length`
- `1 <= n <= 300`
- `nums[i]` is either 0, 1, or 2.

76. Minimum Window Substring

Hard

12312570Add to ListShare

Given two strings `s` and `t` of lengths `m` and `n` respectively, return the **minimum window substring** of `s` such that every character in `t` (including duplicates) is included in the window. If there is no such substring, return the empty string `""`.

The testcases will be generated such that the answer is **unique**.

A **substring** is a contiguous sequence of characters within the string.

Example 1:

Input: `s = "ADOBECODEBANC", t = "ABC"`

Output: "BANC"

Explanation: The minimum window substring "BANC" includes 'A', 'B', and 'C' from string `t`.

Example 2:

Input: `s = "a", t = "a"`

Output: "a"

Explanation: The entire string `s` is the minimum window.

Example 3:

Input: `s = "a", t = "aa"`

Output: ""

Explanation: Both 'a's from `t` must be included in the window.

Since the largest window of `s` only has one 'a', return empty string.

Constraints:

- `m == s.length`
- `n == t.length`
- `1 <= m, n <= 10^5`
- `s` and `t` consist of uppercase and lowercase English letters.

77. Combinations

Medium

5068164Add to ListShare

Given two integers `n` and `k`, return *all possible combinations of `k` numbers chosen from the range `[1, n]`*.

You may return the answer in **any order**.

Example 1:

Input: `n = 4, k = 2`

Output: `[[1,2],[1,3],[1,4],[2,3],[2,4],[3,4]]`

Explanation: There are $4 \text{ choose } 2 = 6$ total combinations.

Note that combinations are unordered, i.e., `[1,2]` and `[2,1]` are considered to be the same combination.

Example 2:

Input: `n = 1, k = 1`

Output: `[[1]]`

Explanation: There is $1 \text{ choose } 1 = 1$ total combination.

Constraints:

- `1 <= n <= 20`
- `1 <= k <= n`

78. Subsets

Medium

12143176Add to ListShare

Given an integer array `nums` of **unique** elements, return *all possible subsets* (the power set).

The solution set **must not** contain duplicate subsets. Return the solution in **any order**.

Example 1:

Input: `nums` = [1,2,3]

Output: [[], [1], [2], [1,2], [3], [1,3], [2,3], [1,2,3]]

Example 2:

Input: `nums` = [0]

Output: [[], [0]]

Constraints:

- $1 \leq \text{nums.length} \leq 10$
- $-10 \leq \text{nums}[i] \leq 10$
- All the numbers of `nums` are **unique**.

79. Word Search

Medium

10996420Add to ListShare

Given an $m \times n$ grid of characters `board` and a string `word`, return `true` if `word` exists in the grid.

The word can be constructed from letters of sequentially adjacent cells, where adjacent cells are horizontally or vertically neighboring. The same letter cell may not be used more than once.

Example 1:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A", "B", "C", "E"], ["S", "F", "C", "S"], ["A", "D", "E", "E"]], word = "ABCED"

Output: true

Example 2:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A", "B", "C", "E"], ["S", "F", "C", "S"], ["A", "D", "E", "E"]], word = "SEE"

Output: true

Example 3:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A", "B", "C", "E"], ["S", "F", "C", "S"], ["A", "D", "E", "E"]], word = "ABCB"

Output: false

Constraints:

- `m == board.length`
- `n = board[i].length`
- `1 <= m, n <= 6`
- `1 <= word.length <= 15`
- `board` and `word` consists of only lowercase and uppercase English letters.

80. Remove Duplicates from Sorted Array II

Medium

4041943Add to ListShare

Given an integer array `nums` sorted in **non-decreasing order**, remove some duplicates **in-place** such that each unique element appears **at most twice**. The **relative order** of the elements should be kept the **same**.

Since it is impossible to change the length of the array in some languages, you must instead have the result be placed in the **first part** of the array `nums`. More formally, if there are `k` elements after removing the duplicates, then the first `k` elements of `nums` should hold the final result. It does not matter what you leave beyond the first `k` elements.

Return `k` after placing the final result in the first `k` slots of `nums`.

Do **not** allocate extra space for another array. You must do this by **modifying the input array in-place** with $O(1)$ extra memory.

Custom Judge:

The judge will test your solution with the following code:

```
int[] nums = [...]; // Input array

int[] expectedNums = [...]; // The expected answer with correct length

int k = removeDuplicates(nums); // Calls your implementation

assert k == expectedNums.length;
for (int i = 0; i < k; i++) {
    assert nums[i] == expectedNums[i];
}
```

If all assertions pass, then your solution will be **accepted**.

Example 1:

Input: nums = [1,1,1,2,2,3]

Output: 5, nums = [1,1,2,2,3,]

Explanation: Your function should return k = 5, with the first five elements of nums being 1, 1, 2, 2 and 3 respectively.

It does not matter what you leave beyond the returned k (hence they are underscores).

Example 2:

Input: nums = [0,0,1,1,1,2,3,3]

Output: 7, nums = [0,0,1,1,2,3,3,_,]

Explanation: Your function should return k = 7, with the first seven elements of nums being 0, 0, 1, 1, 2, 3 and 3 respectively.

It does not matter what you leave beyond the returned k (hence they are underscores).

Constraints:

- $1 \leq \text{nums.length} \leq 3 * 10^4$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

- `nums` is sorted in **non-decreasing** order.

81. Search in Rotated Sorted Array II

Medium

5128779Add to ListShare

There is an integer array `nums` sorted in non-decreasing order (not necessarily with **distinct** values).

Before being passed to your function, `nums` is **rotated** at an unknown pivot index `k` ($0 \leq k < \text{nums.length}$) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1], nums[0], nums[1], ..., nums[k-1]]` (**0-indexed**). For example, `[0,1,2,4,4,4,5,6,6,7]` might be rotated at pivot index `5` and become `[4,5,6,6,7,0,1,2,4,4]`.

Given the array `nums` **after** the rotation and an integer `target`, return `true` if `target` is in `nums`, or `false` if it is not in `nums`.

You must decrease the overall operation steps as much as possible.

Example 1:

Input: `nums = [2,5,6,0,0,1,2]`, `target = 0`

Output: `true`

Example 2:

Input: `nums = [2,5,6,0,0,1,2]`, `target = 3`

Output: `false`

Constraints:

- $1 \leq \text{nums.length} \leq 5000$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- `nums` is guaranteed to be rotated at some pivot.
- $-10^4 \leq \text{target} \leq 10^4$


82. Remove Duplicates from Sorted List II

Medium

6596183Add to ListShare

Given the `head` of a sorted linked list, *delete all nodes that have duplicate numbers, leaving only distinct numbers from the original list*. Return the linked list **sorted** as well.


Example 1:



Input: head = [1,2,3,3,4,4,5]

Output: [1,2,5]

Example 2:



Input: head = [1,1,1,2,3]

Output: [2,3]

Constraints:

- The number of nodes in the list is in the range [0, 300].
- $-100 \leq \text{Node.val} \leq 100$
- The list is guaranteed to be **sorted** in ascending order.

83. Remove Duplicates from Sorted List




Easy

5868207Add to ListShare

Given the head of a sorted linked list, *delete all duplicates such that each element appears only once*.

Return the linked list **sorted** as well.




Example 1:



Input: head = [1,1,2]

Output: [1,2]

Example 2:



Input: head = [1,1,2,3,3]

Output: [1,2,3]

Constraints:

- The number of nodes in the list is in the range `[0, 300]`.
- `-100 <= Node.val <= 100`
- The list is guaranteed to be **sorted** in ascending order.


84. Largest Rectangle in Histogram

Hard

12129169Add to ListShare

Given an array of integers `heights` representing the histogram's bar height where the width of each bar is `1`, return *the area of the largest rectangle in the histogram*.

Example 1:




Input: `heights = [2,1,5,6,2,3]`

Output: 10

Explanation: The above is a histogram where width of each bar is 1.

The largest rectangle is shown in the red area, which has an area = 10 units.

Example 2:



Input: heights = [2,4]

Output: 4

Constraints:

- $1 \leq \text{heights.length} \leq 10^5$
- $0 \leq \text{heights}[i] \leq 10^4$

85. Maximal Rectangle

Hard

7667124Add to ListShare

Given a `rows x cols` binary matrix filled with 0's and 1's, find the largest rectangle containing only 1's and return *its area*.

Example 1:

1	0	1	0	0
1	0	1	1	1
1	1	1	1	1
1	0	0	1	0

Input: matrix =
`[[1,"0","1","0","0"],["1","0","1","1","1"],["1","1","1","1","1"],["1","0","0","1","0"]]`

Output: 6

Explanation: The maximal rectangle is shown in the above picture.

Example 2:

Input: matrix = `[[0]]`

Output: 0

Example 3:

Input: matrix = `[[1]]`

Output: 1

Constraints:

- `rows == matrix.length`
- `cols == matrix[i].length`
- `1 <= row, cols <= 200`
- `matrix[i][j] is '0' or '1'.`

86. Partition List


Medium

4827577Add to ListShare

Given the `head` of a linked list and a value `x`, partition it such that all nodes **less than** `x` come before nodes **greater than or equal** to `x`.

You should **preserve** the original relative order of the nodes in each of the two partitions.

Example 1:



Input: `head = [1,4,3,2,5,2]`, `x = 3`

Output: `[1,2,2,4,3,5]`

Example 2:

Input: `head = [2,1]`, `x = 2`

Output: `[1,2]`

Constraints:

- The number of nodes in the list is in the range `[0, 200]`.
- `-100 <= Node.val <= 100`
- `-200 <= x <= 200`

87. Scramble String

Hard

1820966Add to ListShare

We can scramble a string `s` to get a string `t` using the following algorithm:

1. If the length of the string is 1, stop.
2. If the length of the string is > 1 , do the following:

- Split the string into two non-empty substrings at a random index, i.e., if the string is s , divide it to x and y where $s = x + y$.
- **Randomly** decide to swap the two substrings or to keep them in the same order. i.e., after this step, s may become $s = x + y$ or $s = y + x$.
- Apply step 1 recursively on each of the two substrings x and y .

Given two strings s_1 and s_2 of **the same length**, return `true` if s_2 is a scrambled string of s_1 , otherwise, return `false`.

Example 1:

Input: $s_1 = \text{"great"}$, $s_2 = \text{"rgeat"}$

Output: `true`

Explanation: One possible scenario applied on s_1 is:

$\text{"great" } \rightarrow \text{"gr/eat" } // \text{ divide at random index.}$

$\text{"gr/eat" } \rightarrow \text{"gr/eat" } // \text{ random decision is not to swap the two substrings and keep them in order.}$

$\text{"gr/eat" } \rightarrow \text{"g/r / e/at" } // \text{ apply the same algorithm recursively on both substrings. divide at random index each of them.}$

$\text{"g/r / e/at" } \rightarrow \text{"r/g / e/at" } // \text{ random decision was to swap the first substring and to keep the second substring in the same order.}$

$\text{"r/g / e/at" } \rightarrow \text{"r/g / e/ a/t" } // \text{ again apply the algorithm recursively, divide "at" to "a/t".}$

$\text{"r/g / e/ a/t" } \rightarrow \text{"r/g / e/ a/t" } // \text{ random decision is to keep both substrings in the same order.}$

The algorithm stops now, and the result string is "rgeat" which is s_2 .

As one possible scenario led s_1 to be scrambled to s_2 , we return `true`.

Example 2:

Input: $s_1 = \text{"abcde"}$, $s_2 = \text{"caebd"}$

Output: `false`

Example 3:

Input: $s_1 = \text{"a"}$, $s_2 = \text{"a"}$

Output: `true`

Constraints:

- `s1.length == s2.length`
- `1 <= s1.length <= 30`
- `s1` and `s2` consist of lowercase English letters.

88. Merge Sorted Array**Easy**

7604673Add to ListShare

You are given two integer arrays `nums1` and `nums2`, sorted in **non-decreasing order**, and two integers `m` and `n`, representing the number of elements in `nums1` and `nums2` respectively.

Merge `nums1` and `nums2` into a single array sorted in **non-decreasing order**.

The final sorted array should not be returned by the function, but instead be *stored inside the array* `nums1`. To accommodate this, `nums1` has a length of `m + n`, where the first `m` elements denote the elements that should be merged, and the last `n` elements are set to `0` and should be ignored. `nums2` has a length of `n`.

Example 1:

Input: `nums1 = [1,2,3,0,0,0]`, `m = 3`, `nums2 = [2,5,6]`, `n = 3`

Output: `[1,2,2,3,5,6]`

Explanation: The arrays we are merging are `[1,2,3]` and `[2,5,6]`.

The result of the merge is `[1,2,2,3,5,6]` with the underlined elements coming from `nums1`.

Example 2:

Input: `nums1 = [1]`, `m = 1`, `nums2 = []`, `n = 0`

Output: `[1]`

Explanation: The arrays we are merging are `[1]` and `[]`.

The result of the merge is `[1]`.

Example 3:

Input: `nums1 = [0]`, `m = 0`, `nums2 = [1]`, `n = 1`

Output: `[1]`

Explanation: The arrays we are merging are [] and [1].

The result of the merge is [1].

Note that because $m = 0$, there are no elements in nums1 . The 0 is only there to ensure the merge result can fit in nums1 .

Constraints:

- $\text{nums1.length} == m + n$
- $\text{nums2.length} == n$
- $0 \leq m, n \leq 200$
- $1 \leq m + n \leq 200$
- $-10^9 \leq \text{nums1}[i], \text{nums2}[j] \leq 10^9$

89. Gray Code

Medium

16482383Add to ListShare

An **n-bit gray code sequence** is a sequence of 2^n integers where:

- Every integer is in the **inclusive** range $[0, 2^n - 1]$,
- The first integer is 0,
- An integer appears **no more than once** in the sequence,
- The binary representation of every pair of **adjacent** integers differs by **exactly one bit**, and
- The binary representation of the **first** and **last** integers differs by **exactly one bit**.

Given an integer n , return *any valid n-bit gray code sequence*.

Example 1:

Input: $n = 2$

Output: $[0,1,3,2]$

Explanation:

The binary representation of $[0,1,3,2]$ is $[00,01,11,10]$.

- 00 and 01 differ by one bit
- 01 and 11 differ by one bit
- 11 and 10 differ by one bit

- 10 and 00 differ by one bit

[0,2,3,1] is also a valid gray code sequence, whose binary representation is [00,10,11,01].

- 00 and 10 differ by one bit

- 10 and 11 differ by one bit

- 11 and 01 differ by one bit

- 01 and 00 differ by one bit

Example 2:

Input: n = 1

Output: [0,1]

Constraints:

- 1 <= n <= 16

90. Subsets II

Medium

6647185Add to ListShare

Given an integer array `nums` that may contain duplicates, return *all possible subsets (the power set)*.

The solution set **must not** contain duplicate subsets. Return the solution in **any order**.

Example 1:

Input: nums = [1,2,2]

Output: [[], [1], [1,2], [1,2,2], [2], [2,2]]

Example 2:

Input: nums = [0]

Output: [[], [0]]

Constraints:

- $1 \leq \text{nums.length} \leq 10$
- $-10 \leq \text{nums}[i] \leq 10$

91. Decode Ways

Medium

79894012Add to ListShare

A message containing letters from $A-Z$ can be **encoded** into numbers using the following mapping:

```
'A' -> "1"
'B' -> "2"
...
'Z' -> "26"
```

To **decode** an encoded message, all the digits must be grouped then mapped back into letters using the reverse of the mapping above (there may be multiple ways). For example, "11106" can be mapped into:

- "AAJF" with the grouping (1 1 10 6)
- "KJF" with the grouping (11 10 6)

Note that the grouping (1 11 06) is invalid because "06" cannot be mapped into 'F' since "6" is different from "06".

Given a string s containing only digits, return *the number of ways to decode it*.

The test cases are generated so that the answer fits in a **32-bit** integer.

Example 1:

Input: $s = "12"$

Output: 2

Explanation: "12" could be decoded as "AB" (1 2) or "L" (12).

Example 2:

Input: $s = "226"$

Output: 3

Explanation: "226" could be decoded as "BZ" (2 26), "VF" (22 6), or "BBF" (2 2 6).

Example 3:

Input: s = "06"

Output: 0

Explanation: "06" cannot be mapped to "F" because of the leading zero ("6" is different from "06").

Constraints:

- `1 <= s.length <= 100`
- `s` contains only digits and may contain leading zero(s).


92. Reverse Linked List II

Medium

7982350Add to ListShare

Given the `head` of a singly linked list and two integers `left` and `right` where `left <= right`, reverse the nodes of the list from position `left` to position `right`, and return *the reversed list*.

Example 1:



Input: head = [1,2,3,4,5], left = 2, right = 4

Output: [1,4,3,2,5]

Example 2:

Input: head = [5], left = 1, right = 1

Output: [5]

Constraints:

- The number of nodes in the list is `n`.
- `1 <= n <= 500`
- `-500 <= Node.val <= 500`
- `1 <= left <= right <= n`

93. Restore IP Addresses

Medium

3110643Add to ListShare

A **valid IP address** consists of exactly four integers separated by single dots. Each integer is between `0` and `255` (**inclusive**) and cannot have leading zeros.

- For example, `"0.1.2.201"` and `"192.168.1.1"` are **valid** IP addresses, but `"0.011.255.245"`, `"192.168.1.312"` and `"192.168@1.1"` are **invalid** IP addresses.

Given a string `s` containing only digits, return *all possible valid IP addresses that can be formed by inserting dots into `s`*. You are **not** allowed to reorder or remove any digits in `s`. You may return the valid IP addresses in **any** order.

Example 1:

Input: `s = "25525511135"`

Output: `["255.255.11.135", "255.255.111.35"]`

Example 2:

Input: `s = "0000"`

Output: `["0.0.0.0"]`

Example 3:

Input: `s = "101023"`

Output: `["1.0.10.23", "1.0.102.3", "10.1.0.23", "10.10.2.3", "101.0.2.3"]`

Constraints:

- `1 <= s.length <= 20`
- `s` consists of digits only.


94. Binary Tree Inorder Traversal

Easy

9695460Add to ListShare

Given the `root` of a binary tree, return *the inorder traversal of its nodes' values*.

Example 1:



Input: `root = [1,null,2,3]`

Output: `[1,3,2]`

Example 2:

Input: `root = []`

Output: `[]`

Example 3:

Input: `root = [1]`

Output: `[1]`

Constraints:

- The number of nodes in the tree is in the range `[0, 100]`.

- $-100 \leq \text{Node.val} \leq 100$


95. Unique Binary Search Trees II

Medium

5365352Add to ListShare

Given an integer n , return *all the structurally unique BST's (binary search trees)*, which has *exactly n nodes of unique values from 1 to n*. Return the answer in **any order**.

Example 1:



Input: $n = 3$

Output: `[[1,null,2,null,3],[1,null,3,2],[2,1,3],[3,1,null,null,2],[3,2,null,1]]`

Example 2:

Input: $n = 1$

Output: `[[1]]`

Constraints:

- $1 \leq n \leq 8$


96. Unique Binary Search Trees

Medium

8182321Add to ListShare

Given an integer n , return *the number of structurally unique BST's (binary search trees)* which has *exactly n nodes of unique values from 1 to n*.

Example 1:



Input: n = 3

Output: 5

Example 2:

Input: n = 1

Output: 1

Constraints:

- 1 <= n <= 19

97. Interleaving String

Medium

5861353Add to ListShare


Given strings s_1 , s_2 , and s_3 , find whether s_3 is formed by an **interleaving** of s_1 and s_2 .

An **interleaving** of two strings s and t is a configuration where s and t are divided into n and m **non-empty** substrings respectively, such that:

- $s = s_1 + s_2 + \dots + s_n$
- $t = t_1 + t_2 + \dots + t_m$
- $|n - m| \leq 1$
- The **interleaving** is $s_1 + t_1 + s_2 + t_2 + s_3 + t_3 + \dots$ or $t_1 + s_1 + t_2 + s_2 + t_3 + s_3 + \dots$

Note: $a + b$ is the concatenation of strings a and b .

Example 1:



Input: $s1 = "aabcc"$, $s2 = "dbbca"$, $s3 = "aadbcbcbac"$

Output: true

Explanation: One way to obtain $s3$ is:

Split $s1$ into $s1 = "aa" + "bc" + "c"$, and $s2$ into $s2 = "dbbc" + "a"$.

Interleaving the two splits, we get $"aa" + "dbbc" + "bc" + "a" + "c" = "aadbcbcbac"$.

Since $s3$ can be obtained by interleaving $s1$ and $s2$, we return true.

Example 2:

Input: $s1 = "aabcc"$, $s2 = "dbbca"$, $s3 = "aadbbbaccc"$

Output: false

Explanation: Notice how it is impossible to interleave $s2$ with any other string to obtain $s3$.

Example 3:

Input: $s1 = "", s2 = "", s3 = ""$

Output: true

Constraints:

- $0 \leq s1.length, s2.length \leq 100$
- $0 \leq s3.length \leq 200$
- $s1, s2$, and $s3$ consist of lowercase English letters.

98. Validate Binary Search Tree

Medium


126081014Add to ListShare

Given the `root` of a binary tree, determine if it is a valid binary search tree (BST).

A **valid BST** is defined as follows:

- The left subtree of a node contains only nodes with keys **less than** the node's key.
- The right subtree of a node contains only nodes with keys **greater than** the node's key.
- Both the left and right subtrees must also be binary search trees.


Example 1:



Input: root = [2,1,3]

Output: true

Example 2:



Input: root = [5,1,4,null,null,3,6]

Output: false

Explanation: The root node's value is 5 but its right child's value is 4.

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-2^{31} \leq \text{Node.val} \leq 2^{31} - 1$


99. Recover Binary Search Tree

Medium

6135203Add to ListShare

You are given the `root` of a binary search tree (BST), where the values of **exactly** two nodes of the tree were swapped by mistake. *Recover the tree without changing its structure.*

Example 1:




Input: `root = [1,3,null,null,2]`

Output: `[3,1,null,null,2]`

Explanation: 3 cannot be a left child of 1 because $3 > 1$. Swapping 1 and 3 makes the BST valid.

Example 2:



Input: root = [3,1,4,null,null,2]

Output: [2,1,4,null,null,3]

Explanation: 2 cannot be in the right subtree of 3 because $2 < 3$. Swapping 2 and 3 makes the BST valid.

Constraints:

- The number of nodes in the tree is in the range [2, 1000].
- $-2^{31} \leq \text{Node.val} \leq 2^{31} - 1$

100. Same Tree


Easy

7162152 Add to List Share

Given the roots of two binary trees p and q , write a function to check if they are the same or not.

Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.


Example 1:



Input: p = [1,2,3], q = [1,2,3]

Output: true


Example 2:



Input: p = [1,2], q = [1,null,2]

Output: false

Example 3:



Input: p = [1,2,1], q = [1,1,2]

Output: false

Constraints:

- The number of nodes in both trees is in the range `[0, 100]`.
- $-10^4 \leq \text{Node.val} \leq 10^4$


101. Symmetric Tree

Easy

11108253Add to ListShare

Given the `root` of a binary tree, *check whether it is a mirror of itself* (i.e., symmetric around its center).


Example 1:



Input: `root = [1,2,2,3,4,4,3]`

Output: `true`

Example 2:



Input: root = [1,2,2,null,3,null,3]

Output: false

Constraints:

- The number of nodes in the tree is in the range [1, 1000].
- `-100 <= Node.val <= 100`


102. Binary Tree Level Order Traversal

Medium

109207Add to ListShare

Given the `root` of a binary tree, return *the level order traversal of its nodes' values*. (i.e., from left to right, level by level).

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: [[3],[9,20],[15,7]]

Example 2:

Input: root = [1]

Output: [[1]]

Example 3:

Input: root = []

Output: []

Constraints:


- The number of nodes in the tree is in the range [0, 2000].
- $-1000 \leq \text{Node.val} \leq 1000$

103. Binary Tree Zigzag Level Order Traversal

Medium

7267194Add to ListShare

Given the `root` of a binary tree, return *the zigzag level order traversal of its nodes' values*. (i.e., from left to right, then right to left for the next level and alternate between).

Example 1:

Input: root = [3,9,20,null,null,15,7]

Output: [[3],[20,9],[15,7]]

Example 2:

Input: root = [1]

Output: [[1]]

Example 3:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range [0, 2000].
- $-100 \leq \text{Node.val} \leq 100$

104. Maximum Depth of Binary Tree


Easy

8533137Add to ListShare

Given the `root` of a binary tree, return its *maximum depth*.

A binary tree's **maximum depth** is the number of nodes along the longest path from the root node down to the farthest leaf node.

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: 3

Example 2:

Input: root = [1,null,2]

Output: 2

Constraints:


- The number of nodes in the tree is in the range `[0, 104]`.
- `-100 <= Node.val <= 100`

105. Construct Binary Tree from Preorder and Inorder Traversal

Medium

11064305 Add to List Share

Given two integer arrays `preorder` and `inorder` where `preorder` is the preorder traversal of a binary tree and `inorder` is the inorder traversal of the same tree, construct and return *the binary tree*.

Example 1:

Input: preorder = [3,9,20,15,7], inorder = [9,3,15,20,7]

Output: [3,9,20,null,null,15,7]

Example 2:

Input: preorder = [-1], inorder = [-1]

Output: [-1]

Constraints:

- $1 \leq \text{preorder.length} \leq 3000$
- $\text{inorder.length} == \text{preorder.length}$
- $-3000 \leq \text{preorder}[i], \text{inorder}[i] \leq 3000$
- **preorder and inorder consist of unique values.**
- Each value of **inorder** also appears in **preorder**.
- **preorder** is **guaranteed** to be the preorder traversal of the tree.
- **inorder** is **guaranteed** to be the inorder traversal of the tree.


106. Construct Binary Tree from Inorder and Postorder Traversal

Medium

529379 Add to List Share

Given two integer arrays `inorder` and `postorder` where `inorder` is the inorder traversal of a binary tree and `postorder` is the postorder traversal of the same tree, construct and return *the binary tree*.

Example 1:



Input: `inorder = [9,3,15,20,7]`, `postorder = [9,15,7,20,3]`

Output: `[3,9,20,null,null,15,7]`

Example 2:

Input: `inorder = [-1]`, `postorder = [-1]`

Output: `[-1]`

Constraints:


- $1 \leq \text{inorder.length} \leq 3000$
- $\text{postorder.length} == \text{inorder.length}$
- $-3000 \leq \text{inorder[i]}, \text{postorder[i]} \leq 3000$
- `inorder` and `postorder` consist of **unique** values.
- Each value of `postorder` also appears in `inorder`.
- `inorder` is **guaranteed** to be the inorder traversal of the tree.
- `postorder` is **guaranteed** to be the postorder traversal of the tree.

107. Binary Tree Level Order Traversal II

Medium

3781299Add to ListShare

Given the `root` of a binary tree, return *the bottom-up level order traversal of its nodes' values*. (i.e., from left to right, level by level from leaf to root).

Example 1:

Input: root = [3,9,20,null,null,15,7]

Output: [[15,7],[9,20],[3]]

Example 2:

Input: root = [1]

Output: [[1]]

Example 3:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range [0, 2000].
- $-1000 \leq \text{Node.val} \leq 1000$

108. Convert Sorted Array to Binary Search Tree


Easy

8221413Add to ListShare

Given an integer array `nums` where the elements are sorted in **ascending order**, convert *it to a height-balanced binary search tree*.

A **height-balanced** binary tree is a binary tree in which the depth of the two subtrees of every node never differs by more than one.


Example 1:




Input: `nums = [-10, -3, 0, 5, 9]`

Output: `[0, -3, 9, -10, null, 5]`

Explanation: `[0, -10, 5, null, -3, null, 9]` is also accepted:



Example 2:



Input: `nums = [1,3]`

Output: `[3,1]`

Explanation: `[1,null,3]` and `[3,1]` are both height-balanced BSTs.

Constraints:

- `1 <= nums.length <= 104`
- `-104 <= nums[i] <= 104`
- `nums` is sorted in a **strictly increasing** order.

109. Convert Sorted List to Binary Search Tree


Medium

5236121Add to ListShare

Given the `head` of a singly linked list where elements are **sorted in ascending order**, convert it to a height balanced BST.

For this problem, a height-balanced binary tree is defined as a binary tree in which the depth of the two subtrees of *every* node never differ by more than 1.

Example 1:



Input: head = [-10,-3,0,5,9]

Output: [0,-3,9,-10,null,5]

Explanation: One possible answer is [0,-3,9,-10,null,5], which represents the shown height balanced BST.

Example 2:

Input: head = []

Output: []

Constraints:

- The number of nodes in head is in the range [0, 2 * 10⁴].
- -10⁵ <= Node.val <= 10⁵

110. Balanced Binary Tree

Easy


7347385Add to ListShare

Given a binary tree, determine if it is height-balanced.

For this problem, a height-balanced binary tree is defined as:

a binary tree in which the left and right subtrees of *every* node differ in height by no more than 1.


Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: true

Example 2:



Input: root = [1,2,2,3,3,null,null,4,4]

Output: false

Example 3:

Input: root = []

Output: true

Constraints:

- The number of nodes in the tree is in the range [0, 5000].
- $-10^4 \leq \text{Node.val} \leq 10^4$

111. Minimum Depth of Binary Tree

Easy


48601004Add to ListShare

Given a binary tree, find its minimum depth.

The minimum depth is the number of nodes along the shortest path from the root node down to the nearest leaf node.

Note: A leaf is a node with no children.

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: 2

Example 2:

Input: root = [2,null,3,null,4,null,5,null,6]

Output: 5

Constraints:

- The number of nodes in the tree is in the range $[0, 10^5]$.
- $-1000 \leq \text{Node.val} \leq 1000$

112. Path Sum


Easy

6573835Add to ListShare

Given the `root` of a binary tree and an integer `targetSum`, return `true` if the tree has a **root-to-leaf** path such that adding up all the values along the path equals `targetSum`.

A **leaf** is a node with no children.

Example 1:




Input: root = [5,4,8,11,null,13,4,7,2,null,null,null,1], targetSum = 22

Output: true

Explanation: The root-to-leaf path with the target sum is shown.

Example 2:



Input: root = [1,2,3], targetSum = 5

Output: false

Explanation: There two root-to-leaf paths in the tree:

(1 --> 2): The sum is 3.

(1 --> 3): The sum is 4.

There is no root-to-leaf path with sum = 5.

Example 3:

Input: root = [], targetSum = 0

Output: false

Explanation: Since the tree is empty, there are no root-to-leaf paths.

Constraints:

- The number of nodes in the tree is in the range [0, 5000].
- $-1000 \leq \text{Node.val} \leq 1000$
- $-1000 \leq \text{targetSum} \leq 1000$

113. Path Sum II


Medium

6233130Add to ListShare

Given the `root` of a binary tree and an integer `targetSum`, return *all root-to-leaf paths where the sum of the node values in the path equals `targetSum`*. Each path should be returned as a list of the node **values**, not node references.

A **root-to-leaf** path is a path starting from the root and ending at any leaf node. A **leaf** is a node with no children.

Example 1:



Input: root = [5,4,8,11,null,13,4,7,2,null,null,5,1], targetSum = 22


Output: [[5,4,11,2],[5,8,4,5]]

Explanation: There are two paths whose sum equals targetSum:

$$5 + 4 + 11 + 2 = 22$$

$$5 + 8 + 4 + 5 = 22$$

Example 2:



Input: root = [1,2,3], targetSum = 5

Output: []

Example 3:**Input:** root = [1,2], targetSum = 0**Output:** []**Constraints:**


- The number of nodes in the tree is in the range [0, 5000].
- $-1000 \leq \text{Node.val} \leq 1000$
- $-1000 \leq \text{targetSum} \leq 1000$

114. Flatten Binary Tree to Linked List**Medium**

9291497Add to ListShare

Given the `root` of a binary tree, flatten the tree into a "linked list":

- The "linked list" should use the same `TreeNode` class where the `right` child pointer points to the next node in the list and the `left` child pointer is always `null`.
- The "linked list" should be in the same order as a **pre-order traversal** of the binary tree.

Example 1:**Input:** root = [1,2,5,3,4,null,6]**Output:** [1,null,2,null,3,null,4,null,5,null,6]**Example 2:**

Input: root = []

Output: []

Example 3:

Input: root = [0]

Output: [0]

Constraints:

- The number of nodes in the tree is in the range [0, 2000].
- $-100 \leq \text{Node.val} \leq 100$

115. Distinct Subsequences

Hard

4435178Add to ListShare

Given two strings s and t , return *the number of distinct subsequences of s which equals t* .

A string's **subsequence** is a new string formed from the original string by deleting some (can be none) of the characters without disturbing the remaining characters' relative positions. (i.e., "ACE" is a subsequence of "ABCDE" while "AEC" is not).

The test cases are generated so that the answer fits on a 32-bit signed integer.

Example 1:

Input: s = "rabbbit", t = "rabbit"

Output: 3

Explanation:

As shown below, there are 3 ways you can generate "rabbit" from s .

rabbbit

rabbbit

rabbbit

Example 2:

Input: s = "babgbag", t = "bag"

Output: 5

Explanation:

As shown below, there are 5 ways you can generate "bag" from s.

babgbag

babgbag

babgbag

babgbag

babgbag

Constraints:

- $1 \leq s.length, t.length \leq 1000$
- s and t consist of English letters.

116. Populating Next Right Pointers in Each Node

Medium

7697261 Add to List Share

You are given a **perfect binary tree** where all leaves are on the same level, and every parent has two children. The binary tree has the following definition:

```
struct Node {
    int val;
    Node *left;
    Node *right;
    Node *next;
}
```

Populate each next pointer to point to its next right node. If there is no next right node, the next pointer should be set to `NULL`.

Initially, all next pointers are set to `NULL`.


Example 1:

Figure A




Figure B

Input: root = [1,2,3,4,5,6,7]

Output: [1,#,2,3,#,4,5,6,7,#]

Explanation: Given the above perfect binary tree (Figure A), your function should populate each next pointer to point to its next right node, just like in Figure B. The serialized output is in level order as connected by the next pointers, with '#' signifying the end of each level.

Example 2:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range $[0, 2^{12} - 1]$.
- $-1000 \leq \text{Node.val} \leq 1000$

Follow-up:

- You may only use constant extra space.
- The recursive approach is fine. You may assume implicit stack space does not count as extra space for this problem.

117. Populating Next Right Pointers in Each Node II

Medium

4837281Add to ListShare

Given a binary tree

```
struct Node {
    int val;
    Node *left;
    Node *right;
    Node *next;
}
```

Populate each next pointer to point to its next right node. If there is no next right node, the next pointer should be set to `NULL`.

Initially, all next pointers are set to `NULL`.

Example 1:




Figure A




Figure B

Input: `root = [1,2,3,4,5,null,7]`

Output: `[1,#,2,3,#,4,5,7,#]`

Explanation: Given the above binary tree (Figure A), your function should populate each next pointer to point to its next right node, just like in Figure B. The serialized output is in level order as connected by the next pointers, with '#' signifying the end of each level.

Example 2:

Input: `root = []`

Output: `[]`

Constraints:

- The number of nodes in the tree is in the range `[0, 6000]`.
- `-100 <= Node.val <= 100`


118. Pascal's Triangle

Easy

7940266Add to ListShare

Given an integer `numRows`, return the first `numRows` of **Pascal's triangle**.

In **Pascal's triangle**, each number is the sum of the two numbers directly above it as shown:



Example 1:

Input: `numRows = 5`

Output: `[[1], [1, 1], [1, 2, 1], [1, 3, 3, 1], [1, 4, 6, 4, 1]]`

Example 2:

Input: `numRows = 1`

Output: `[[1]]`

Constraints:

- `1 <= numRows <= 30`


119. Pascal's Triangle II

Easy

3161281Add to ListShare

Given an integer `rowIndex`, return the `rowIndexth` (0-indexed) row of the **Pascal's triangle**.

In **Pascal's triangle**, each number is the sum of the two numbers directly above it as shown:



Example 1:

Input: `rowIndex = 3`

Output: `[1,3,3,1]`

Example 2:

Input: `rowIndex = 0`

Output: `[1]`

Example 3:

Input: `rowIndex = 1`

Output: `[1,1]`

Constraints:

- `0 <= rowIndex <= 33`

120. Triangle

Medium

6942443Add to ListShare

Given a `triangle` array, return *the minimum path sum from top to bottom*.

For each step, you may move to an adjacent number of the row below. More formally, if you are on index `i` on the current row, you may move to either index `i` or index `i + 1` on the next row.

Example 1:

Input: `triangle = [[2],[3,4],[6,5,7],[4,1,8,3]]`

Output: 11

Explanation: The triangle looks like:

```

2

3 4

6 5 7

4 1 8 3

```

The minimum path sum from top to bottom is $2 + 3 + 5 + 1 = 11$ (underlined above).

Example 2:

Input: `triangle = [[-10]]`

Output: -10

Constraints:

- $1 \leq \text{triangle.length} \leq 200$
- $\text{triangle[0].length} == 1$
- $\text{triangle[i].length} == \text{triangle[i - 1].length} + 1$
- $-10^4 \leq \text{triangle[i][j]} \leq 10^4$

121. Best Time to Buy and Sell Stock

Easy

20275650 Add to List Share

You are given an array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

You want to maximize your profit by choosing a **single day** to buy one stock and choosing a **different day in the future** to sell that stock.

Return *the maximum profit you can achieve from this transaction*. If you cannot achieve any profit, return 0.

Example 1:

Input: prices = [7,1,5,3,6,4]

Output: 5

Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6-1 = 5.

Note that buying on day 2 and selling on day 1 is not allowed because you must buy before you sell.

Example 2:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: In this case, no transactions are done and the max profit = 0.

Constraints:

- $1 \leq \text{prices.length} \leq 10^5$
- $0 \leq \text{prices}[i] \leq 10^4$

122. Best Time to Buy and Sell Stock II

Medium

92822456Add to ListShare

You are given an integer array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

On each day, you may decide to buy and/or sell the stock. You can only hold **at most one** share of the stock at any time. However, you can buy it then immediately sell it on the **same day**.

Find and return *the maximum profit you can achieve*.

Example 1:

Input: prices = [7,1,5,3,6,4]

Output: 7

Explanation: Buy on day 2 (price = 1) and sell on day 3 (price = 5), profit = 5-1 = 4.

Then buy on day 4 (price = 3) and sell on day 5 (price = 6), profit = 6-3 = 3.
 Total profit is 4 + 3 = 7.

Example 2:

Input: prices = [1,2,3,4,5]

Output: 4

Explanation: Buy on day 1 (price = 1) and sell on day 5 (price = 5), profit = 5-1 = 4.

Total profit is 4.

Example 3:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: There is no way to make a positive profit, so we never buy the stock to achieve the maximum profit of 0.

Constraints:

- $1 \leq \text{prices.length} \leq 3 * 10^4$
- $0 \leq \text{prices}[i] \leq 10^4$

123. Best Time to Buy and Sell Stock III

Hard

7043140Add to ListShare

You are given an array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

Find the maximum profit you can achieve. You may complete **at most two transactions**.

Note: You may not engage in multiple transactions simultaneously (i.e., you must sell the stock before you buy again).

Example 1:

Input: prices = [3,3,5,0,0,3,1,4]

Output: 6

Explanation: Buy on day 4 (price = 0) and sell on day 6 (price = 3), profit = 3-0 = 3.

Then buy on day 7 (price = 1) and sell on day 8 (price = 4), profit = 4-1 = 3.

Example 2:

Input: prices = [1,2,3,4,5]

Output: 4

Explanation: Buy on day 1 (price = 1) and sell on day 5 (price = 5), profit = 5-1 = 4.

Note that you cannot buy on day 1, buy on day 2 and sell them later, as you are engaging multiple transactions at the same time. You must sell before buying again.

Example 3:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: In this case, no transaction is done, i.e. max profit = 0.

Constraints:

- $1 \leq \text{prices.length} \leq 10^5$
- $0 \leq \text{prices}[i] \leq 10^5$

123. Best Time to Buy and Sell Stock III

Hard

7043140Add to ListShare

You are given an array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

Find the maximum profit you can achieve. You may complete **at most two transactions**.

Note: You may not engage in multiple transactions simultaneously (i.e., you must sell the stock before you buy again).

Example 1:

Input: prices = [3,3,5,0,0,3,1,4]

Output: 6

Explanation: Buy on day 4 (price = 0) and sell on day 6 (price = 3), profit = 3-0 = 3.

Then buy on day 7 (price = 1) and sell on day 8 (price = 4), profit = 4-1 = 3.

Example 2:

Input: prices = [1,2,3,4,5]

Output: 4

Explanation: Buy on day 1 (price = 1) and sell on day 5 (price = 5), profit = 5-1 = 4.

Note that you cannot buy on day 1, buy on day 2 and sell them later, as you are engaging multiple transactions at the same time. You must sell before buying again.

Example 3:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: In this case, no transaction is done, i.e. max profit = 0.

Constraints:

- $1 \leq \text{prices.length} \leq 10^5$
- $0 \leq \text{prices}[i] \leq 10^5$

125. Valid Palindrome

Easy

49086012Add to ListShare

A phrase is a **palindrome** if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers.

Given a string `s`, return `true` if it is a **palindrome**, or `false` otherwise.

Example 1:

Input: s = "A man, a plan, a canal: Panama"

Output: true

Explanation: "amanaplanacanalpanama" is a palindrome.

Example 2:**Input:** s = "race a car"**Output:** false**Explanation:** "raceacar" is not a palindrome.**Example 3:****Input:** s = " "**Output:** true**Explanation:** s is an empty string "" after removing non-alphanumeric characters.

Since an empty string reads the same forward and backward, it is a palindrome.

Constraints:

- $1 \leq s.length \leq 2 * 10^5$
- s consists only of printable ASCII characters.

126. Word Ladder II**Hard**

4760613Add to ListShare

A **transformation sequence** from word `beginWord` to word `endWord` using a dictionary `wordList` is a sequence of words $beginWord \rightarrow s_1 \rightarrow s_2 \rightarrow \dots \rightarrow s_k$ such that:

- Every adjacent pair of words differs by a single letter.
- Every s_i for $1 \leq i \leq k$ is in `wordList`. Note that `beginWord` does not need to be in `wordList`.
- $s_k == endWord$

Given two words, `beginWord` and `endWord`, and a dictionary `wordList`, return *all the shortest transformation sequences* from `beginWord` to `endWord`, or an empty list if no such sequence exists. Each sequence should be returned as a list of the words `[beginWord, s1, s2, ..., sk]`.

Example 1:**Input:** beginWord = "hit", endWord = "cog", wordList = ["hot", "dot", "dog", "lot", "log", "cog"]**Output:** [[["hit", "hot", "dot", "dog", "cog"], ["hit", "hot", "lot", "log", "cog"]]]

Explanation: There are 2 shortest transformation sequences:

"hit" -> "hot" -> "dot" -> "dog" -> "cog"

"hit" -> "hot" -> "lot" -> "log" -> "cog"

Example 2:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot", "dot", "dog", "lot", "log"]

Output: []

Explanation: The endWord "cog" is not in wordList, therefore there is no valid transformation sequence.

Constraints:

- $1 \leq \text{beginWord.length} \leq 5$
- $\text{endWord.length} == \text{beginWord.length}$
- $1 \leq \text{wordList.length} \leq 500$
- $\text{wordList}[i].length == \text{beginWord.length}$
- $\text{beginWord}, \text{endWord}, \text{and } \text{wordList}[i]$ consist of lowercase English letters.
- $\text{beginWord} \neq \text{endWord}$
- All the words in `wordList` are **unique**.
- The **sum** of all shortest transformation sequences does not exceed 10^5 .

127. Word Ladder

Hard

91021725Add to ListShare

A **transformation sequence** from word `beginWord` to word `endWord` using a dictionary `wordList` is a sequence of words $\text{beginWord} \rightarrow s_1 \rightarrow s_2 \rightarrow \dots \rightarrow s_k$ such that:

- Every adjacent pair of words differs by a single letter.
- Every s_i for $1 \leq i \leq k$ is in `wordList`. Note that `beginWord` does not need to be in `wordList`.
- $s_k == \text{endWord}$

Given two words, `beginWord` and `endWord`, and a dictionary `wordList`, return the **number of words** in the **shortest transformation sequence** from `beginWord` to `endWord`, or 0 if no such sequence exists.

Example 1:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot", "dot", "dog", "lot", "log", "cog"]

Output: 5

Explanation: One shortest transformation sequence is "hit" -> "hot" -> "dot" -> "dog" -> "cog", which is 5 words long.

Example 2:

Input: beginWord = "hit", endWord = "cog", wordList = ["hot", "dot", "dog", "lot", "log"]

Output: 0

Explanation: The endWord "cog" is not in wordList, therefore there is no valid transformation sequence.

Constraints:

- $1 \leq \text{beginWord.length} \leq 10$
- $\text{endWord.length} == \text{beginWord.length}$
- $1 \leq \text{wordList.length} \leq 5000$
- $\text{wordList}[i].length == \text{beginWord.length}$
- $\text{beginWord}, \text{endWord}, \text{and wordList}[i]$ consist of lowercase English letters.
- $\text{beginWord} \neq \text{endWord}$
- All the words in `wordList` are **unique**.

128. Longest Consecutive Sequence

Medium

13351555Add to ListShare

Given an unsorted array of integers `nums`, return the length of the longest consecutive elements sequence.

You must write an algorithm that runs in $O(n)$ time.

Example 1:

Input: `nums` = [100, 4, 200, 1, 3, 2]

Output: 4

Explanation: The longest consecutive elements sequence is [1, 2, 3, 4]. Therefore its length is 4.

Example 2:

Input: `nums = [0,3,7,2,5,8,4,6,0,1]`

Output: 9

Constraints:

- $0 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

129. Sum Root to Leaf Numbers

Medium

488592 Add to List Share

You are given the `root` of a binary tree containing digits from 0 to 9 only.


Each root-to-leaf path in the tree represents a number.

- For example, the root-to-leaf path `1 -> 2 -> 3` represents the number `123`.

Return *the total sum of all root-to-leaf numbers*. Test cases are generated so that the answer will fit in a **32-bit** integer.

A **leaf** node is a node with no children.

Example 1:



Input: `root = [1,2,3]`

Output: 25


Explanation:

The root-to-leaf path `1->2` represents the number `12`.

The root-to-leaf path `1->3` represents the number `13`.

Therefore, $\text{sum} = 12 + 13 = 25$.

Example 2:



Input: root = [4,9,0,5,1]

Output: 1026

Explanation:

The root-to-leaf path 4->9->5 represents the number 495.

The root-to-leaf path 4->9->1 represents the number 491.

The root-to-leaf path 4->0 represents the number 40.

Therefore, $\text{sum} = 495 + 491 + 40 = 1026$.

Constraints:

- The number of nodes in the tree is in the range `[1, 1000]`.
- `0 <= Node.val <= 9`
- The depth of the tree will not exceed `10`.

130. Surrounded Regions


Medium

58001350Add to ListShare

Given an $m \times n$ matrix `board` containing '`X`' and '`O`', capture all regions that are 4-directionally surrounded by '`X`'.

A region is **captured** by flipping all 'O's into 'X's in that surrounded region.

Example 1:



Input: board =

```
[[ "X", "X", "X", "X" ], [ "X", "O", "O", "X" ], [ "X", "X", "O", "X" ], [ "X", "O", "X", "X" ]]
```

Output: [["X", "X", "X", "X"], ["X", "X", "X", "X"], ["X", "X", "X", "X"], ["X", "O", "X", "X"]]

Explanation: Notice that an 'O' should not be flipped if:

- It is on the border, or
- It is adjacent to an 'O' that should not be flipped.

The bottom 'O' is on the border, so it is not flipped.

The other three 'O' form a surrounded region, so they are flipped.

Example 2:

Input: board = [["X"]]

Output: [["X"]]

Constraints:

- $m == \text{board.length}$
- $n == \text{board}[i].length$
- $1 \leq m, n \leq 200$
- $\text{board}[i][j]$ is 'X' or 'O'.

131. Palindrome Partitioning

Medium

8336254Add to ListShare

Given a string `s`, partition `s` such that every substring of the partition is a **palindrome**. Return all possible palindrome partitioning of `s`.

A **palindrome** string is a string that reads the same backward as forward.

Example 1:

Input: `s = "aab"`

Output: `[["a", "a", "b"], ["aa", "b"]]`

Example 2:

Input: `s = "a"`

Output: `[["a"]]`

Constraints:

- `1 <= s.length <= 16`
- `s` contains only lowercase English letters.

132. Palindrome Partitioning II

Hard

408695Add to ListShare

Given a string `s`, partition `s` such that every substring of the partition is a palindrome.

Return *the minimum cuts needed* for a palindrome partitioning of `s`.

Example 1:

Input: `s = "aab"`

Output: `1`

Explanation: The palindrome partitioning `["aa", "b"]` could be produced using 1 cut.

Example 2:

Input: s = "a"

Output: 0

Example 3:

Input: s = "ab"

Output: 1

Constraints:

- $1 \leq s.length \leq 2000$
- s consists of lowercase English letters only.

133. Clone Graph

Medium

67622811 Add to List Share

Given a reference of a node in a connected undirected graph.

Return a **deep copy** (clone) of the graph.

Each node in the graph contains a value (`int`) and a list (`List[Node]`) of its neighbors.


```
class Node {
    public int val;
    public List<Node> neighbors;
}
```

Test case format:

For simplicity, each node's value is the same as the node's index (1-indexed). For example, the first node with `val == 1`, the second node with `val == 2`, and so on. The graph is represented in the test case using an adjacency list.

An adjacency list is a collection of unordered **lists** used to represent a finite graph. Each list describes the set of neighbors of a node in the graph.

The given node will always be the first node with `val = 1`. You must return the **copy of the given node** as a reference to the cloned graph.

Example 1:

Input: adjList = [[2,4],[1,3],[2,4],[1,3]]

Output: [[2,4],[1,3],[2,4],[1,3]]

Explanation: There are 4 nodes in the graph.

1st node (val = 1)'s neighbors are 2nd node (val = 2) and 4th node (val = 4).

2nd node (val = 2)'s neighbors are 1st node (val = 1) and 3rd node (val = 3).

3rd node (val = 3)'s neighbors are 2nd node (val = 2) and 4th node (val = 4).

4th node (val = 4)'s neighbors are 1st node (val = 1) and 3rd node (val = 3).

Example 2:



Input: adjList = [[]]

Output: [[]]

Explanation: Note that the input contains one empty list. The graph consists of only one node with val = 1 and it does not have any neighbors.

Example 3:

Input: adjList = []

Output: []

Explanation: This an empty graph, it does not have any nodes.

Constraints:

- The number of nodes in the graph is in the range [0, 100].
- $1 \leq \text{Node.val} \leq 100$
- `Node.val` is unique for each node.
- There are no repeated edges and no self-loops in the graph.
- The Graph is connected and all nodes can be visited starting from the given node.

134. Gas Station

Medium

7055669Add to ListShare

There are `n` gas stations along a circular route, where the amount of gas at the i^{th} station is `gas[i]`.

You have a car with an unlimited gas tank and it costs `cost[i]` of gas to travel from the i^{th} station to its next $(i + 1)^{\text{th}}$ station. You begin the journey with an empty tank at one of the gas stations.

Given two integer arrays `gas` and `cost`, return the starting gas station's index if you can travel around the circuit once in the clockwise direction, otherwise return `-1`. If there exists a solution, it is **guaranteed** to be **unique**

Example 1:

Input: `gas = [1,2,3,4,5]`, `cost = [3,4,5,1,2]`

Output: 3

Explanation:

Start at station 3 (index 3) and fill up with 4 unit of gas. Your tank = $0 + 4 = 4$

Travel to station 4. Your tank = $4 - 1 + 5 = 8$

Travel to station 0. Your tank = $8 - 2 + 1 = 7$

Travel to station 1. Your tank = $7 - 3 + 2 = 6$

Travel to station 2. Your tank = $6 - 4 + 3 = 5$

Travel to station 3. The cost is 5. Your gas is just enough to travel back to station 3.

Therefore, return 3 as the starting index.

Example 2:

Input: `gas = [2,3,4]`, `cost = [3,4,3]`

Output: -1

Explanation:

You can't start at station 0 or 1, as there is not enough gas to travel to the next station.

Let's start at station 2 and fill up with 4 unit of gas. Your tank = $0 + 4 = 4$

Travel to station 0. Your tank = $4 - 3 + 2 = 3$

Travel to station 1. Your tank = $3 - 3 + 3 = 3$

You cannot travel back to station 2, as it requires 4 unit of gas but you only have 3.

Therefore, you can't travel around the circuit once no matter where you start.

Constraints:

- `n == gas.length == cost.length`
- `1 <= n <= 105`
- `0 <= gas[i], cost[i] <= 104`

135. Candy**Hard**

4745319Add to ListShare

There are `n` children standing in a line. Each child is assigned a rating value given in the integer array `ratings`.

You are giving candies to these children subjected to the following requirements:

- Each child must have at least one candy.
- Children with a higher rating get more candies than their neighbors.

Return *the minimum number of candies you need to have to distribute the candies to the children.*

Example 1:

Input: `ratings = [1,0,2]`

Output: 5

Explanation: You can allocate to the first, second and third child with 2, 1, 2 candies respectively.

Example 2:

Input: `ratings = [1,2,2]`

Output: 4

Explanation: You can allocate to the first, second and third child with 1, 2, 1 candies respectively.

The third child gets 1 candy because it satisfies the above two conditions.

Constraints:

- `n == ratings.length`
- `1 <= n <= 2 * 104`
- `0 <= ratings[i] <= 2 * 104`

136. Single Number

Easy

11517439Add to ListShare

Given a **non-empty** array of integers `nums`, every element appears *twice* except for one. Find that single one.

You must implement a solution with a linear runtime complexity and use only constant extra space.

Example 1:

Input: `nums` = [2,2,1]

Output: 1

Example 2:

Input: `nums` = [4,1,2,1,2]

Output: 4

Example 3:

Input: `nums` = [1]

Output: 1

Constraints:

- $1 \leq \text{nums.length} \leq 3 * 10^4$
- $-3 * 10^4 \leq \text{nums}[i] \leq 3 * 10^4$
- Each element in the array appears twice except for one element which appears only once.

137. Single Number II

Medium

4702509Add to ListShare

Given an integer array `nums` where every element appears **three times** except for one, which appears **exactly once**. *Find the single element and return it.*

You must implement a solution with a linear runtime complexity and use only constant extra space.

Example 1:

Input: `nums = [2,2,3,2]`

Output: `3`

Example 2:

Input: `nums = [0,1,0,1,0,1,99]`

Output: `99`

Constraints:

- $1 \leq \text{nums.length} \leq 3 * 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- Each element in `nums` appears exactly **three times** except for one element which appears **once**.

138. Copy List with Random Pointer

Medium

98991074Add to ListShare

A linked list of length `n` is given such that each node contains an additional random pointer, which could point to any node in the list, or `null`.

Construct a **deep copy** of the list. The deep copy should consist of exactly `n` **brand new** nodes, where each new node has its value set to the value of its corresponding original node. Both the `next` and `random` pointer of the new nodes should point to new nodes in the copied list such that the pointers in the original list and copied list represent the same list state. **None of the pointers in the new list should point to nodes in the original list.**


For example, if there are two nodes `X` and `Y` in the original list, where `X.random --> Y`, then for the corresponding two nodes `x` and `y` in the copied list, `x.random --> y`.

Return *the head of the copied linked list*.

The linked list is represented in the input/output as a list of `n` nodes. Each node is represented as a pair of `[val, random_index]` where:


- `val`: an integer representing `Node.val`
- `random_index`: the index of the node (range from `0` to `n-1`) that the `random` pointer points to, or `null` if it does not point to any node.

Your code will **only** be given the `head` of the original linked list.

Example 1:


Input: head = [[7,null],[13,0],[11,4],[10,2],[1,0]]

Output: [[7,null],[13,0],[11,4],[10,2],[1,0]]

Example 2:

Input: head = [[1,1],[2,1]]

Output: [[1,1],[2,1]]

Example 3:

Input: head = [[3,null],[3,0],[3,null]]

Output: [[3,null],[3,0],[3,null]]

Constraints:

- $0 \leq n \leq 1000$
- $-10^4 \leq \text{Node.val} \leq 10^4$
- Node.random is `null` or is pointing to some node in the linked list.

139. Word Break

Medium

12297524 Add to List Share

Given a string `s` and a dictionary of strings `wordDict`, return `true` if `s` can be segmented into a space-separated sequence of one or more dictionary words.

Note that the same word in the dictionary may be reused multiple times in the segmentation.

Example 1:

Input: `s = "leetcode", wordDict = ["leet", "code"]`

Output: `true`

Explanation: Return `true` because "leetcode" can be segmented as "leet code".

Example 2:

Input: `s = "applepenapple", wordDict = ["apple", "pen"]`

Output: `true`

Explanation: Return `true` because "applepenapple" can be segmented as "apple pen apple".

Note that you are allowed to reuse a dictionary word.

Example 3:

Input: `s = "catsandog", wordDict = ["cats", "dog", "sand", "and", "cat"]`

Output: `false`

Constraints:

- `1 <= s.length <= 300`
- `1 <= wordDict.length <= 1000`
- `1 <= wordDict[i].length <= 20`
- `s` and `wordDict[i]` consist of only lowercase English letters.
- All the strings of `wordDict` are **unique**.

140. Word Break II

Hard

5446490Add to ListShare

Given a string `s` and a dictionary of strings `wordDict`, add spaces in `s` to construct a sentence where each word is a valid dictionary word. Return all such possible sentences in **any order**.

Note that the same word in the dictionary may be reused multiple times in the segmentation.

Example 1:

Input: s = "catsanddog", wordDict = ["cat", "cats", "and", "sand", "dog"]

Output: ["cats and dog", "cat sand dog"]

Example 2:

Input: s = "pineapplepenapple", wordDict = ["apple", "pen", "applepen", "pine", "pineapple"]

Output: ["pine apple pen apple", "pineapple pen apple", "pine applepen apple"]

Explanation: Note that you are allowed to reuse a dictionary word.

Example 3:

Input: s = "catsandog", wordDict = ["cats", "dog", "sand", "and", "cat"]

Output: []

Constraints:

- `1 <= s.length <= 20`
- `1 <= wordDict.length <= 1000`
- `1 <= wordDict[i].length <= 10`
- `s` and `wordDict[i]` consist of only lowercase English letters.
- All the strings of `wordDict` are **unique**.

141. Linked List Cycle

Easy


10039875 Add to List Share

Given `head`, the head of a linked list, determine if the linked list has a cycle in it.

There is a cycle in a linked list if there is some node in the list that can be reached again by continuously following the `next` pointer. Internally, `pos` is used to denote the index of the node that tail's `next` pointer is connected to. **Note that `pos` is not passed as a parameter.**

Return `true` if there is a cycle in the linked list. Otherwise, return `false`.

Example 1:




Input: head = [3,2,0,-4], pos = 1

Output: true

Explanation: There is a cycle in the linked list, where the tail connects to the 1st node (0-indexed).

Example 2:



Input: head = [1,2], pos = 0

Output: true

Explanation: There is a cycle in the linked list, where the tail connects to the 0th node.

Example 3:



Input: head = [1], pos = -1

Output: false

Explanation: There is no cycle in the linked list.

Constraints:

- The number of the nodes in the list is in the range $[0, 10^4]$.
- $-10^5 \leq \text{Node.val} \leq 10^5$
- pos is -1 or a **valid index** in the linked-list.

142. Linked List Cycle II

Medium


8991620Add to ListShare

Given the `head` of a linked list, return *the node where the cycle begins*. If there is no cycle, return `null`.

There is a cycle in a linked list if there is some node in the list that can be reached again by continuously following the `next` pointer. Internally, `pos` is used to denote the index of the node that tail's `next` pointer is connected to (**0-indexed**). It is `-1` if there is no cycle. **Note that `pos` is not passed as a parameter.**

Do not modify the linked list.

Example 1:




Input: `head = [3,2,0,-4]`, `pos = 1`

Output: tail connects to node index 1

Explanation: There is a cycle in the linked list, where tail connects to the second node.

Example 2:




Input: `head = [1,2]`, `pos = 0`

Output: tail connects to node index 0

Explanation: There is a cycle in the linked list, where tail connects to the first node.

Example 3:



Input: head = [1], pos = -1

Output: no cycle

Explanation: There is no cycle in the linked list.

Constraints:

- The number of the nodes in the list is in the range $[0, 10^4]$.
- $-10^5 \leq \text{Node.val} \leq 10^5$
- pos is -1 or a **valid index** in the linked-list.

143. Reorder List

Medium

7224249Add to ListShare

You are given the head of a singly linked-list. The list can be represented as:



$L_0 \rightarrow L_1 \rightarrow \dots \rightarrow L_{n-1} \rightarrow L_n$

Reorder the list to be on the following form:

$L_0 \rightarrow L_n \rightarrow L_1 \rightarrow L_{n-1} \rightarrow L_2 \rightarrow L_{n-2} \rightarrow \dots$

You may not modify the values in the list's nodes. Only nodes themselves may be changed.


Example 1:



Input: head = [1,2,3,4]

Output: [1,4,2,3]

Example 2:



Input: head = [1,2,3,4,5]

Output: [1,5,2,4,3]

Constraints:

- The number of nodes in the list is in the range $[1, 5 * 10^4]$.
- $1 \leq \text{Node.val} \leq 1000$


144. Binary Tree Preorder Traversal

Easy

5039140Add to ListShare

Given the `root` of a binary tree, return *the preorder traversal of its nodes' values*.

Example 1:



Input: root = [1,null,2,3]

Output: [1,2,3]

Example 2:

Input: root = []

Output: []

Example 3:

Input: root = [1]

Output: [1]

Constraints:


- The number of nodes in the tree is in the range [0, 100].
- $-100 \leq \text{Node.val} \leq 100$

145. Binary Tree Postorder Traversal

Easy

5005155Add to ListShare

Given the `root` of a binary tree, return *the postorder traversal of its nodes' values*.

Example 1:**Input:** root = [1,null,2,3]**Output:** [3,2,1]**Example 2:****Input:** root = []**Output:** []**Example 3:****Input:** root = [1]**Output:** [1]**Constraints:**

- The number of the nodes in the tree is in the range [0, 100].
- $-100 \leq \text{Node.val} \leq 100$

146. LRU Cache

Medium

15246635 Add to ListShare

Design a data structure that follows the constraints of a Least Recently Used (LRU) cache.

Implement the `LRUCache` class:

- `LRUCache(int capacity)` Initialize the LRU cache with **positive** size `capacity`.
- `int get(int key)` Return the value of the `key` if the key exists, otherwise return `-1`.
- `void put(int key, int value)` Update the value of the `key` if the `key` exists. Otherwise, add the `key-value` pair to the cache. If the number of keys exceeds the `capacity` from this operation, **evict** the least recently used key.

The functions `get` and `put` must each run in $O(1)$ average time complexity.

Example 1:

Input

```
["LRUCache", "put", "put", "get", "put", "get", "put", "get", "put", "get"]
[[2], [1, 1], [2, 2], [1], [3, 3], [2], [4, 4], [1], [3], [4]]
```

Output

```
[null, null, null, 1, null, -1, null, -1, 3, 4]
```

Explanation

```
LRUCache lRUCache = new LRUCache(2);

lRUCache.put(1, 1); // cache is {1=1}

lRUCache.put(2, 2); // cache is {1=1, 2=2}

lRUCache.get(1);    // return 1

lRUCache.put(3, 3); // LRU key was 2, evicts key 2, cache is {1=1, 3=3}

lRUCache.get(2);    // returns -1 (not found)

lRUCache.put(4, 4); // LRU key was 1, evicts key 1, cache is {4=4, 3=3}

lRUCache.get(1);    // return -1 (not found)

lRUCache.get(3);    // return 3

lRUCache.get(4);    // return 4
```

Constraints:

- $1 \leq \text{capacity} \leq 3000$
- $0 \leq \text{key} \leq 10^4$
- $0 \leq \text{value} \leq 10^5$
- At most $2 * 10^5$ calls will be made to `get` and `put`.

147. Insertion Sort List**Medium**

2283812 Add to List Share

Given the `head` of a singly linked list, sort the list using **insertion sort**, and return *the sorted list's head*.


The steps of the **insertion sort** algorithm:

1. Insertion sort iterates, consuming one input element each repetition and growing a sorted output list.
2. At each iteration, insertion sort removes one element from the input data, finds the location it belongs within the sorted list and inserts it there.
3. It repeats until no input elements remain.

The following is a graphical example of the insertion sort algorithm. The partially sorted list (black) initially contains only the first element in the list. One element (red) is removed from the input data and inserted in-place into the sorted list with each iteration.

6 5 3 1 8 7 2 4


Example 1:



Input: head = [4,2,1,3]

Output: [1,2,3,4]

Example 2:



Input: head = [-1,5,3,4,0]

Output: [-1,0,3,4,5]

Constraints:


- The number of nodes in the list is in the range `[1, 5000]`.
 - $-5000 \leq \text{Node.val} \leq 5000$

148. Sort List

Medium


8283255Add to ListShare

Given the `head` of a linked list, return *the list after sorting it in **ascending order***.

Example 1:

Input: head = [4,2,1,3]

Output: [1,2,3,4]

Example 2:

Input: head = [-1,5,3,4,0]

Output: [-1,0,3,4,5]

Example 3:

Input: head = []

Output: []


Constraints:


- The number of nodes in the list is in the range `[0, 5 * 104]`.
- $-10^5 \leq \text{Node.val} \leq 10^5$

149. Max Points on a Line**Hard**

1532241Add to ListShare

Given an array of `points` where `points[i] = [xi, yi]` represents a point on the **X-Y** plane, return *the maximum number of points that lie on the same straight line*.

Example 1:**Input:** `points = [[1,1],[2,2],[3,3]]`**Output:** 3**Example 2:**



Constraints:

- $1 \leq \text{points.length} \leq 300$
- $\text{points}[i].length == 2$
- $-10^4 \leq x_i, y_i \leq 10^4$
- All the `points` are **unique**.

150. Evaluate Reverse Polish Notation

Medium

3969708Add to ListShare

Evaluate the value of an arithmetic expression in [Reverse Polish Notation](#).

Valid operators are `+`, `-`, `*`, and `/`. Each operand may be an integer or another expression.

Note that division between two integers should truncate toward zero.

It is guaranteed that the given RPN expression is always valid. That means the expression would always evaluate to a result, and there will not be any division by zero operation.

Example 1:

Input: tokens = ["2", "1", "+", "3", "*"]

Output: 9

Explanation: $((2 + 1) * 3) = 9$

Example 2:

Input: tokens = ["4", "13", "5", "/", "+"]

Output: 6

Explanation: $(4 + (13 / 5)) = 6$

Example 3:

Input: tokens = ["10", "6", "9", "3", "+", "-11", "*", "/", "*", "17", "+", "5", "+"]

Output: 22

Explanation: $((10 * (6 / ((9 + 3) * -11))) + 17) + 5$

$$= ((10 * (6 / (12 * -11))) + 17) + 5$$

$$= ((10 * (6 / -132)) + 17) + 5$$

$$= ((10 * 0) + 17) + 5$$

$$= (0 + 17) + 5$$

$$= 17 + 5$$

$$= 22$$

Constraints:

- $1 \leq \text{tokens.length} \leq 10^4$
- $\text{tokens}[i]$ is either an operator: "+", "-", "*", or "/", or an integer in the range $[-200, 200]$.

151. Reverse Words in a String

Medium

40214147Add to ListShare

Given an input string `s`, reverse the order of the **words**.

A **word** is defined as a sequence of non-space characters. The **words** in `s` will be separated by at least one space.

Return a *string of the words in reverse order concatenated by a single space*.

Note that `s` may contain leading or trailing spaces or multiple spaces between two words. The returned string should only have a single space separating the words. Do not include any extra spaces.

Example 1:

Input: `s = "the sky is blue"`

Output: `"blue is sky the"`

Example 2:

Input: `s = " hello world "`

Output: `"world hello"`

Explanation: Your reversed string should not contain leading or trailing spaces.

Example 3:

Input: `s = "a good example"`

Output: `"example good a"`

Explanation: You need to reduce multiple spaces between two words to a single space in the reversed string.

Constraints:

- `1 <= s.length <= 104`
- `s` contains English letters (upper-case and lower-case), digits, and spaces ' '.
- There is **at least one** word in `s`.

152. Maximum Product Subarray

Medium

13791411Add to ListShare

Given an integer array `nums`, find a contiguous non-empty subarray within the array that has the largest product, and return *the product*.

The test cases are generated so that the answer will fit in a **32-bit** integer.

A **subarray** is a contiguous subsequence of the array.

Example 1:

Input: `nums = [2,3,-2,4]`

Output: 6

Explanation: `[2,3]` has the largest product 6.

Example 2:

Input: `nums = [-2,0,-1]`

Output: 0

Explanation: The result cannot be 2, because `[-2,-1]` is not a subarray.

Constraints:

- $1 \leq \text{nums.length} \leq 2 * 10^4$
- $-10 \leq \text{nums}[i] \leq 10$
- The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

153. Find Minimum in Rotated Sorted Array

Medium

8503429Add to ListShare

Suppose an array of length `n` sorted in ascending order is **rotated** between `1` and `n` times. For example, the array `nums = [0,1,2,4,5,6,7]` might become:

- `[4,5,6,7,0,1,2]` if it was rotated 4 times.
- `[0,1,2,4,5,6,7]` if it was rotated 7 times.

Notice that **rotating** an array `[a[0], a[1], a[2], ..., a[n-1]]` 1 time results in the array `[a[n-1], a[0], a[1], a[2], ..., a[n-2]]`.

Given the sorted rotated array `nums` of **unique** elements, return *the minimum element of this array*.

You must write an algorithm that runs in $O(\log n)$ time.

Example 1:

Input: `nums` = [3,4,5,1,2]

Output: 1

Explanation: The original array was [1,2,3,4,5] rotated 3 times.

Example 2:

Input: `nums` = [4,5,6,7,0,1,2]

Output: 0

Explanation: The original array was [0,1,2,4,5,6,7] and it was rotated 4 times.

Example 3:

Input: `nums` = [11,13,15,17]

Output: 11

Explanation: The original array was [11,13,15,17] and it was rotated 4 times.

Constraints:

- `n == nums.length`
- `1 <= n <= 5000`
- `-5000 <= nums[i] <= 5000`
- All the integers of `nums` are **unique**.
- `nums` is sorted and rotated between `1` and `n` times.

154. Find Minimum in Rotated Sorted Array II

Hard

3410397Add to ListShare

Suppose an array of length `n` sorted in ascending order is **rotated** between `1` and `n` times. For example, the array `nums` = [0,1,4,4,5,6,7] might become:

- [4,5,6,7,0,1,4] if it was rotated 4 times.
- [0,1,4,4,5,6,7] if it was rotated 7 times.

Notice that **rotating** an array `[a[0], a[1], a[2], ..., a[n-1]]` 1 time results in the array `[a[n-1], a[0], a[1], a[2], ..., a[n-2]]`.

Given the sorted rotated array `nums` that may contain **duplicates**, return *the minimum element of this array*.

You must decrease the overall operation steps as much as possible.

Example 1:

Input: `nums = [1,3,5]`

Output: `1`

Example 2:

Input: `nums = [2,2,2,0,1]`

Output: `0`

Constraints:

- `n == nums.length`
- `1 <= n <= 5000`
- `-5000 <= nums[i] <= 5000`
- `nums` is sorted and rotated between `1` and `n` times.

155. Min Stack

Medium

9685678Add to ListShare

Design a stack that supports push, pop, top, and retrieving the minimum element in constant time.

Implement the `MinStack` class:

- `MinStack()` initializes the stack object.
- `void push(int val)` pushes the element `val` onto the stack.
- `void pop()` removes the element on the top of the stack.
- `int top()` gets the top element of the stack.
- `int getMin()` retrieves the minimum element in the stack.

You must implement a solution with $O(1)$ time complexity for each function.

Example 1:**Input**

```
["MinStack","push","push","push","getMin","pop","top","getMin"]
[[],[-2],[0],[-3],[],[],[],[]]
```

Output

```
[null,null,null,null,-3,null,0,-2]
```

Explanation

```
MinStack minStack = new MinStack();

minStack.push(-2);
minStack.push(0);
minStack.push(-3);

minStack.getMin(); // return -3
minStack.pop();

minStack.top();    // return 0
minStack.getMin(); // return -2
```

Constraints:

- $-2^{31} \leq \text{val} \leq 2^{31} - 1$
- Methods `pop`, `top` and `getMin` operations will always be called on **non-empty** stacks.
- At most $3 * 10^4$ calls will be made to `push`, `pop`, `top`, and `getMin`.


160. Intersection of Two Linked Lists**Easy**

111801019 Add to List Share

Given the heads of two singly linked-lists `headA` and `headB`, return *the node at which the two lists intersect*. If the two linked lists have no intersection at all, return `null`.

For example, the following two linked lists begin to intersect at node `c1`:

A:



B:



The test cases are generated such that there are no cycles anywhere in the entire linked structure.

Note that the linked lists must **retain their original structure** after the function returns.

Custom Judge:


The inputs to the **judge** are given as follows (your program is **not** given these inputs):

- `intersectVal` - The value of the node where the intersection occurs. This is `0` if there is no intersected node.
- `listA` - The first linked list.
- `listB` - The second linked list.
- `skipA` - The number of nodes to skip ahead in `listA` (starting from the head) to get to the intersected node.
- `skipB` - The number of nodes to skip ahead in `listB` (starting from the head) to get to the intersected node.


The judge will then create the linked structure based on these inputs and pass the two heads, `headA` and `headB` to your program. If you correctly return the intersected node, then your solution will be **accepted**.

Example 1:

A:



B:



Input: intersectVal = 8, listA = [4,1,8,4,5], listB = [5,6,1,8,4,5], skipA = 2, skipB = 3

Output: Intersected at '8'


Explanation: The intersected node's value is 8 (note that this must not be 0 if the two lists intersect).

From the head of A, it reads as [4,1,8,4,5]. From the head of B, it reads as [5,6,1,8,4,5]. There are 2 nodes before the intersected node in A; There are 3 nodes before the intersected node in B.

- Note that the intersected node's value is not 1 because the nodes with value 1 in A and B (2nd node in A and 3rd node in B) are different node references. In other words, they point to two different locations in memory, while the nodes with value 8 in A and B (3rd node in A and 4th node in B) point to the same location in memory.

Example 2:

A:



B:


Input: intersectVal = 2, listA = [1,9,1,2,4], listB = [3,2,4], skipA = 3, skipB = 1

Output: Intersected at '2'

Explanation: The intersected node's value is 2 (note that this must not be 0 if the two lists intersect).

From the head of A, it reads as [1,9,1,2,4]. From the head of B, it reads as [3,2,4]. There are 3 nodes before the intersected node in A; There are 1 node before the intersected node in B.

Example 3:



Input: intersectVal = 0, listA = [2,6,4], listB = [1,5], skipA = 3, skipB = 2

Output: No intersection

Explanation: From the head of A, it reads as [2,6,4]. From the head of B, it reads as [1,5]. Since the two lists do not intersect, intersectVal must be 0, while skipA and skipB can be arbitrary values.

Explanation: The two lists do not intersect, so return null.

Constraints:

- The number of nodes of listA is in the m.
- The number of nodes of listB is in the n.
- $1 \leq m, n \leq 3 * 10^4$
- $1 \leq \text{Node.val} \leq 10^5$
- $0 \leq \text{skipA} < m$
- $0 \leq \text{skipB} < n$
- intersectVal is 0 if listA and listB do not intersect.
- intersectVal == listA[skipA] == listB[skipB] if listA and listB intersect.

162. Find Peak Element

Medium

74084024Add to ListShare

A peak element is an element that is strictly greater than its neighbors.

Given a **0-indexed** integer array `nums`, find a peak element, and return its index. If the array contains multiple peaks, return the index to **any of the peaks**.

You may imagine that `nums[-1] = nums[n] = -∞`. In other words, an element is always considered to be strictly greater than a neighbor that is outside the array.

You must write an algorithm that runs in $O(\log n)$ time.

Example 1:

Input: `nums = [1,2,3,1]`

Output: 2

Explanation: 3 is a peak element and your function should return the index number 2.

Example 2:

Input: `nums = [1,2,1,3,5,6,4]`

Output: 5

Explanation: Your function can return either index number 1 where the peak element is 2, or index number 5 where the peak element is 6.

Constraints:

- $1 \leq \text{nums.length} \leq 1000$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- $\text{nums}[i] \neq \text{nums}[i + 1]$ for all valid i .

164. Maximum Gap

Hard

2434312Add to ListShare

Given an integer array `nums`, return *the maximum difference between two successive elements in its sorted form*. If the array contains less than two elements, return 0.

You must write an algorithm that runs in linear time and uses linear extra space.

Example 1:

Input: `nums = [3,6,9,1]`

Output: 3

Explanation: The sorted form of the array is [1,3,6,9], either (3,6) or (6,9) has the maximum difference 3.

Example 2:

Input: nums = [10]

Output: 0

Explanation: The array contains less than 2 elements, therefore return 0.

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $0 \leq \text{nums[i]} \leq 10^9$

165. Compare Version Numbers

Medium

17622354Add to ListShare

Given two version numbers, `version1` and `version2`, compare them.

Version numbers consist of **one or more revisions** joined by a dot `'.'`. Each revision consists of **digits** and may contain leading **zeros**. Every revision contains **at least one character**. Revisions are **0-indexed from left to right**, with the leftmost revision being revision 0, the next revision being revision 1, and so on. For example `2.5.33` and `0.1` are valid version numbers.

To compare version numbers, compare their revisions in **left-to-right order**. Revisions are compared using their **integer value ignoring any leading zeros**. This means that revisions `1` and `001` are considered **equal**. If a version number does not specify a revision at an index, then **treat the revision as 0**. For example, version `1.0` is less than version `1.1` because their revision 0s are the same, but their revision 1s are `0` and `1` respectively, and `0 < 1`.

Return the following:

- If `version1 < version2`, return `-1`.
- If `version1 > version2`, return `1`.
- Otherwise, return `0`.

Example 1:

Input: `version1 = "1.01", version2 = "1.001"`

Output: 0

Explanation: Ignoring leading zeroes, both "01" and "001" represent the same integer "1".

Example 2:

Input: version1 = "1.0", version2 = "1.0.0"

Output: 0

Explanation: version1 does not specify revision 2, which means it is treated as "0".

Example 3:

Input: version1 = "0.1", version2 = "1.1"

Output: -1

Explanation: version1's revision 0 is "0", while version2's revision 0 is "1". $0 < 1$, so version1 < version2.

Constraints:

- $1 \leq \text{version1.length, version2.length} \leq 500$
- `version1` and `version2` only contain digits and '.'.
- `version1` and `version2` are valid version numbers.
- All the given revisions in `version1` and `version2` can be stored in a **32-bit integer**.

166. Fraction to Recurring Decimal

Medium

17403189 Add to List Share

Given two integers representing the `numerator` and `denominator` of a fraction, return *the fraction in string format*.

If the fractional part is repeating, enclose the repeating part in parentheses.

If multiple answers are possible, return **any of them**.

It is **guaranteed** that the length of the answer string is less than 10^4 for all the given inputs.

Example 1:

Input: numerator = 1, denominator = 2

Output: "0.5"

Example 2:

Input: numerator = 2, denominator = 1

Output: "2"

Example 3:

Input: numerator = 4, denominator = 333

Output: "0.(012)"

Constraints:

- $-2^{31} \leq \text{numerator}, \text{denominator} \leq 2^{31} - 1$
- $\text{denominator} \neq 0$

167. Two Sum II - Input Array Is Sorted

Medium

77191076Add to ListShare

Given a **1-indexed** array of integers `numbers` that is already **sorted in non-decreasing order**, find two numbers such that they add up to a specific `target` number. Let these two numbers be `numbers[index1]` and `numbers[index2]` where $1 \leq \text{index}_1 < \text{index}_2 \leq \text{numbers.length}$.

Return *the indices of the two numbers, `index1` and `index2`, added by one as an integer array `[index1, index2]` of length 2*.

The tests are generated such that there is **exactly one solution**. You **may not** use the same element twice.

Your solution must use only constant extra space.

Example 1:

Input: `numbers = [2,7,11,15]`, `target = 9`

Output: `[1,2]`

Explanation: The sum of 2 and 7 is 9. Therefore, $\text{index}_1 = 1$, $\text{index}_2 = 2$. We return `[1, 2]`.

Example 2:

Input: numbers = [2,3,4], target = 6

Output: [1,3]

Explanation: The sum of 2 and 4 is 6. Therefore $\text{index}_1 = 1$, $\text{index}_2 = 3$. We return [1, 3].

Example 3:

Input: numbers = [-1,0], target = -1

Output: [1,2]

Explanation: The sum of -1 and 0 is -1. Therefore $\text{index}_1 = 1$, $\text{index}_2 = 2$. We return [1, 2].

Constraints:

- $2 \leq \text{numbers.length} \leq 3 * 10^4$
- $-1000 \leq \text{numbers}[i] \leq 1000$
- **numbers is sorted in non-decreasing order.**
- $-1000 \leq \text{target} \leq 1000$
- The tests are generated such that there is **exactly one solution**.

168. Excel Sheet Column Title

Easy

3198467Add to ListShare

Given an integer `columnNumber`, return its corresponding column title as it appears in an Excel sheet.

For example:

A -> 1

B -> 2

C -> 3

...

Z -> 26

AA -> 27

AB -> 28

...

Example 1:**Input:** columnNumber = 1**Output:** "A"**Example 2:****Input:** columnNumber = 28**Output:** "AB"**Example 3:****Input:** columnNumber = 701**Output:** "ZY"**Constraints:**

- $1 \leq \text{columnNumber} \leq 2^{31} - 1$

169. Majority Element**Easy**

12015384Add to ListShare

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:**Input:** nums = [3,2,3]**Output:** 3**Example 2:****Input:** nums = [2,2,1,1,1,2,2]**Output:** 2**Constraints:**

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-109 <= nums[i] <= 109`

171. Excel Sheet Column Number

Easy

3641294Add to ListShare

Given a string `columnTitle` that represents the column title as appears in an Excel sheet, return *its corresponding column number*.

For example:

`A -> 1`

`B -> 2`

`C -> 3`

`...`

`Z -> 26`

`AA -> 27`

`AB -> 28`

`...`

Example 1:

Input: `columnTitle = "A"`

Output: 1

Example 2:

Input: `columnTitle = "AB"`

Output: 28

Example 3:

Input: `columnTitle = "ZY"`

Output: 701

Constraints:

- `1 <= columnTitle.length <= 7`
- `columnTitle` consists only of uppercase English letters.
- `columnTitle` is in the range `["A", "FXSHRXW"]`.

172. Factorial Trailing Zeroes**Medium**

22601739Add to ListShare

Given an integer `n`, return *the number of trailing zeroes in $n!$* .Note that $n! = n * (n - 1) * (n - 2) * \dots * 3 * 2 * 1$.**Example 1:****Input:** `n = 3`**Output:** `0`**Explanation:** $3! = 6$, no trailing zero.**Example 2:****Input:** `n = 5`**Output:** `1`**Explanation:** $5! = 120$, one trailing zero.**Example 3:****Input:** `n = 0`**Output:** `0`**Constraints:**

- `0 <= n <= 104`

173. Binary Search Tree Iterator**Medium**

6816419Add to ListShare


Implement the `BSTIterator` class that represents an iterator over the in-order traversal of a binary search tree (BST):

- `BSTIterator (TreeNode root)` Initializes an object of the `BSTIterator` class. The `root` of the BST is given as part of the constructor. The pointer should be initialized to a non-existent number smaller than any element in the BST.
- `boolean hasNext ()` Returns `true` if there exists a number in the traversal to the right of the pointer, otherwise returns `false`.
- `int next ()` Moves the pointer to the right, then returns the number at the pointer.

Notice that by initializing the pointer to a non-existent smallest number, the first call to `next ()` will return the smallest element in the BST.

You may assume that `next ()` calls will always be valid. That is, there will be at least a next number in the in-order traversal when `next ()` is called.

Example 1:



Input

```
["BSTIterator", "next", "next", "hasNext", "next", "hasNext", "next", "hasNext",
"next", "hasNext"]
[[[7, 3, 15, null, null, 9, 20]], [], [], [], [], [], [], [], []]
```

Output

```
[null, 3, 7, true, 9, true, 15, true, 20, false]
```

Explanation

```
BSTIterator bSTIterator = new BSTIterator([7, 3, 15, null, null, 9, 20]);
bSTIterator.next();    // return 3
bSTIterator.next();    // return 7
```

```
bSTIterator.hasNext(); // return True
bSTIterator.next(); // return 9
bSTIterator.hasNext(); // return True
bSTIterator.next(); // return 15
bSTIterator.hasNext(); // return True
bSTIterator.next(); // return 20
bSTIterator.hasNext(); // return False
```

Constraints:

- The number of nodes in the tree is in the range $[1, 10^5]$.
- $0 \leq \text{Node.val} \leq 10^6$
- At most 10^5 calls will be made to `hasNext`, and `next`.

174. Dungeon Game

Hard

460984Add to ListShare

The demons had captured the princess and imprisoned her in **the bottom-right corner** of a dungeon. The dungeon consists of $m \times n$ rooms laid out in a 2D grid. Our valiant knight was initially positioned in **the top-left room** and must fight his way through dungeon to rescue the princess.

The knight has an initial health point represented by a positive integer. If at any point his health point drops to 0 or below, he dies immediately.

Some of the rooms are guarded by demons (represented by negative integers), so the knight loses health upon entering these rooms; other rooms are either empty (represented as 0) or contain magic orbs that increase the knight's health (represented by positive integers).

To reach the princess as quickly as possible, the knight decides to move only **rightward** or **downward** in each step.

Return *the knight's minimum initial health so that he can rescue the princess*.

Note that any room can contain threats or power-ups, even the first room the knight enters and the bottom-right room where the princess is imprisoned.

Example 1:

-2	-3	3
-5	-10	1
10	30	-5

Input: dungeon = [[-2,-3,3],[-5,-10,1],[10,30,-5]]

Output: 7

Explanation: The initial health of the knight must be at least 7 if he follows the optimal path: RIGHT-> RIGHT -> DOWN -> DOWN.

Example 2:

Input: dungeon = [[0]]

Output: 1

Constraints:

- `m == dungeon.length`
- `n == dungeon[i].length`
- `1 <= m, n <= 200`
- `-1000 <= dungeon[i][j] <= 1000`

175. Combine Two Tables

Easy

2353199Add to ListShare

SQL Schema

Table: Person

Column Name	Type

personId	int
lastName	varchar
firstName	varchar

personId is the primary key column for this table.

This table contains information about the ID of some persons and their first and last names.

Table: `Address`

Column Name	Type
addressId	int
personId	int
city	varchar
state	varchar

addressId is the primary key column for this table.

Each row of this table contains information about the city and state of one person with ID = PersonId.

Write an SQL query to report the first name, last name, city, and state of each person in the `Person` table. If the address of a `personId` is not present in the `Address` table, report `null` instead.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:**Input:**

Person table:

personId	lastName	firstName
1	Wang	Allen
2	Alice	Bob

Address table:

addressId	personId	city	state
1	2	New York City	New York
2	3	Leetcode	California

Output:

firstName	lastName	city	state
Allen	Wang	Null	Null
Bob	Alice	New York City	New York

Explanation:

There is no address in the address table for the personId = 1 so we return null in their city and state.

addressId = 1 contains information about the address of personId = 2.

176. Second Highest Salary

Medium

2315770Add to ListShare
SQL Schema

Table: `Employee`

Column Name	Type
<code>id</code>	<code>int</code>
<code>salary</code>	<code>int</code>

`id` is the primary key column for this table.

Each row of this table contains information about the salary of an employee.

Write an SQL query to report the second highest salary from the `Employee` table. If there is no second highest salary, the query should report `null`.

The query result format is in the following example.

Example 1:

Input:

Employee table:

id	salary
1	100
2	200
3	300

Output:

SecondHighestSalary
200

Example 2:**Input:**

Employee table:

id	salary
1	100

Output:

SecondHighestSalary
null

177. Nth Highest Salary**Medium**

1309703Add to ListShare

SQL Schema

Table: Employee

Column Name	Type
id	int

```
| salary      | int  |
```

```
+-----+-----+
```

id is the primary key column for this table.

Each row of this table contains information about the salary of an employee.

Write an SQL query to report the n^{th} highest salary from the Employee table. If there is no n^{th} highest salary, the query should report `null`.

The query result format is in the following example.

Example 1:

Input:

Employee table:

```
+-----+-----+
```

id	salary
1	100
2	200
3	300

```
+-----+-----+
```

$n = 2$

Output:

```
+-----+
```

getNthHighestSalary(2)
200

```
+-----+
```

Example 2:

Input:

Employee table:

id	salary
1	100

n = 2

Output:

getNthHighestSalary(2)
null

178. Rank Scores

Medium

1540222Add to ListShare

SQL Schema

Table: Scores

Column Name	Type
id	int
score	decimal

id is the primary key for this table.

Each row of this table contains the score of a game. Score is a floating point value with two decimal places.

Write an SQL query to rank the scores. The ranking should be calculated according to the following rules:

- The scores should be ranked from the highest to the lowest.
- If there is a tie between two scores, both should have the same ranking.
- After a tie, the next ranking number should be the next consecutive integer value. In other words, there should be no holes between ranks.

Return the result table ordered by `score` in descending order.

The query result format is in the following example.

Example 1:

Input:

Scores table:

id	score
1	3.50
2	3.65
3	4.00
4	3.85
5	4.00
6	3.65

Output:

score	rank
4.00	1
4.00	1

3.85	2	
3.65	3	
3.65	3	
3.50	4	
-----+-----+		

179. Largest Number

Medium

5769481Add to ListShare

Given a list of non-negative integers `nums`, arrange them such that they form the largest number and return it.

Since the result may be very large, so you need to return a string instead of an integer.

Example 1:

Input: `nums = [10,2]`

Output: "210"

Example 2:

Input: `nums = [3,30,34,5,9]`

Output: "9534330"

Constraints:

- `1 <= nums.length <= 100`
- `0 <= nums[i] <= 109`

180. Consecutive Numbers

Medium

1227210Add to ListShare

SQL Schema

Table: `Logs`

-----+-----+

```

| Column Name | Type      |
+-----+-----+
| id          | int       |
| num         | varchar  |
+-----+-----+
id is the primary key for this table.
id is an autoincrement column.

```

Write an SQL query to find all numbers that appear at least three times consecutively.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Logs table:

```

+---+---+
| id | num |
+---+---+
| 1  | 1   |
| 2  | 1   |
| 3  | 1   |
| 4  | 2   |
| 5  | 1   |
| 6  | 2   |
| 7  | 2   |
+---+---+

```

Output:

ConsecutiveNums
1

Explanation: 1 is the only number that appears consecutively for at least three times.

181. Employees Earning More Than Their Managers

Easy

1707180Add to ListShare

SQL Schema

Table: Employee

Column Name	Type
id	int
name	varchar
salary	int
managerId	int

id is the primary key column for this table.

Each row of this table indicates the ID of an employee, their name, salary, and the ID of their manager.

Write an SQL query to find the employees who earn more than their managers.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Employee table:

id	name	salary	managerId
1	Joe	70000	3
2	Henry	80000	4
3	Sam	60000	Null
4	Max	90000	Null

Output:

Employee
Joe

Explanation: Joe is the only employee who earns more than his manager.**182. Duplicate Emails****Easy**

135752Add to ListShare

SQL Schema

Table: Person

Column Name	Type
id	int
email	varchar

`id` is the primary key column for this table.

Each row of this table contains an email. The emails will not contain uppercase letters.

Write an SQL query to report all the duplicate emails.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Person table:

id	email
1	a@b.com
2	c@d.com
3	a@b.com

Output:

Email
a@b.com

Explanation: `a@b.com` is repeated two times.

183. Customers Who Never Order

Easy

154392 Add to ListShare

SQL Schema

Table: `Customers`

Column Name	Type
<code>id</code>	<code>int</code>
<code>name</code>	<code>varchar</code>

`id` is the primary key column for this table.

Each row of this table indicates the ID and name of a customer.

Table: `Orders`

Column Name	Type
<code>id</code>	<code>int</code>
<code>customerId</code>	<code>int</code>

`id` is the primary key column for this table.

`customerId` is a foreign key of the ID from the `Customers` table.

Each row of this table indicates the ID of an order and the ID of the customer who ordered it.

Write an SQL query to report all customers who never order anything.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:**Input:**

Customers table:

id	name
1	Joe
2	Henry
3	Sam
4	Max

Orders table:

id	customerId
1	3
2	1

Output:

Customers
Henry
Max

184. Department Highest Salary**Medium**

1355167Add to ListShare

SQL Schema

Table: Employee

Column Name	Type
id	int
name	varchar
salary	int
departmentId	int

id is the primary key column for this table.

departmentId is a foreign key of the ID from the Department table.

Each row of this table indicates the ID, name, and salary of an employee. It also contains the ID of their department.

Table: Department

Column Name	Type
id	int
name	varchar

id is the primary key column for this table.

Each row of this table indicates the ID of a department and its name.

Write an SQL query to find employees who have the highest salary in each of the departments.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Employee table:

id	name	salary	departmentId
1	Joe	70000	1
2	Jim	90000	1
3	Henry	80000	2
4	Sam	60000	2
5	Max	90000	1

Department table:

id	name
1	IT
2	Sales

Output:

Department	Employee	Salary
IT	Jim	90000
Sales	Henry	80000

IT	Max	90000
-----+-----+-----+		

Explanation: Max and Jim both have the highest salary in the IT department and Henry has the highest salary in the Sales department.

185. Department Top Three Salaries

Hard

1269194Add to ListShare

SQL Schema

Table: Employee

Column Name	Type
-----+-----+	
id	int
name	varchar
salary	int
departmentId	int
-----+-----+	

id is the primary key column for this table.

departmentId is a foreign key of the ID from the Department table.

Each row of this table indicates the ID, name, and salary of an employee. It also contains the ID of their department.

Table: Department

Column Name	Type
-----+-----+	
id	int
name	varchar
-----+-----+	

`id` is the primary key column for this table.

Each row of this table indicates the ID of a department and its name.

A company's executives are interested in seeing who earns the most money in each of the company's departments. A **high earner** in a department is an employee who has a salary in the **top three unique** salaries for that department.

Write an SQL query to find the employees who are **high earners** in each of the departments.

Return the result table **in any order**.

The query result format is in the following example.

Example 1:

Input:

Employee table:

<code>id</code>	<code>name</code>	<code>salary</code>	<code>departmentId</code>
1	Joe	85000	1
2	Henry	80000	2
3	Sam	60000	2
4	Max	90000	1
5	Janet	69000	1
6	Randy	85000	1
7	Will	70000	1

Department table:

<code>id</code>	<code>name</code>
1	Engineering

```
+---+-----+
| 1 | IT    |
| 2 | Sales |
+---+-----+
```

Output:

```
+-----+-----+-----+
| Department | Employee | Salary |
+-----+-----+-----+
| IT        | Max      | 90000  |
| IT        | Joe      | 85000  |
| IT        | Randy    | 85000  |
| IT        | Will     | 70000  |
| Sales     | Henry    | 80000  |
| Sales     | Sam      | 60000  |
+-----+-----+-----+
```

Explanation:

In the IT department:

- Max earns the highest unique salary
- Both Randy and Joe earn the second-highest unique salary
- Will earns the third-highest unique salary

In the Sales department:

- Henry earns the highest salary
- Sam earns the second-highest salary
- There is no third-highest salary as there are only two employees

187. Repeated DNA Sequences

Medium

2400440Add to ListShare

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

- For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

Input: `s = "AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT"`

Output: `["AAAAACCCCC", "CCCCCAAAAA"]`

Example 2:

Input: `s = "AAAAAAAAAAAAAA"`

Output: `["AAAAAAAAAA"]`

Constraints:

- `1 <= s.length <= 105`
- `s[i]` is either 'A', 'C', 'G', or 'T'.

188. Best Time to Buy and Sell Stock IV

Hard

5657191Add to ListShare

You are given an integer array `prices` where `prices[i]` is the price of a given stock on the `ith` day, and an integer `k`.

Find the maximum profit you can achieve. You may complete at most `k` transactions.

Note: You may not engage in multiple transactions simultaneously (i.e., you must sell the stock before you buy again).

Example 1:

Input: `k = 2, prices = [2,4,1]`

Output: `2`

Explanation: Buy on day 1 (price = 2) and sell on day 2 (price = 4), profit = 4-2 = 2.

Example 2:

Input: $k = 2$, $\text{prices} = [3, 2, 6, 5, 0, 3]$

Output: 7

Explanation: Buy on day 2 (price = 2) and sell on day 3 (price = 6), profit = 6-2 = 4. Then buy on day 5 (price = 0) and sell on day 6 (price = 3), profit = 3-0 = 3.

Constraints:

- $1 \leq k \leq 100$
- $1 \leq \text{prices.length} \leq 1000$
- $0 \leq \text{prices}[i] \leq 1000$

189. Rotate Array

Medium

113921409Add to ListShare

Given an array, rotate the array to the right by k steps, where k is non-negative.

Example 1:

Input: $\text{nums} = [1, 2, 3, 4, 5, 6, 7]$, $k = 3$

Output: $[5, 6, 7, 1, 2, 3, 4]$

Explanation:

rotate 1 steps to the right: $[7, 1, 2, 3, 4, 5, 6]$

rotate 2 steps to the right: $[6, 7, 1, 2, 3, 4, 5]$

rotate 3 steps to the right: $[5, 6, 7, 1, 2, 3, 4]$

Example 2:

Input: $\text{nums} = [-1, -100, 3, 99]$, $k = 2$

Output: $[3, 99, -1, -100]$

Explanation:

rotate 1 steps to the right: $[99, -1, -100, 3]$

```
rotate 2 steps to the right: [3,99,-1,-100]
```

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- $0 \leq k \leq 10^5$

190. Reverse Bits

Easy

3638923Add to ListShare

Reverse bits of a given 32 bits unsigned integer.

Note:

- Note that in some languages, such as Java, there is no unsigned integer type. In this case, both input and output will be given as a signed integer type. They should not affect your implementation, as the integer's internal binary representation is the same, whether it is signed or unsigned.
- In Java, the compiler represents the signed integers using [2's complement notation](#). Therefore, in **Example 2** above, the input represents the signed integer `-3` and the output represents the signed integer `-1073741825`.

Example 1:

Input: `n = 00000010100101000001111010011100`

Output: `964176192 (00111001011110000010100101000000)`

Explanation: The input binary string `00000010100101000001111010011100` represents the unsigned integer `43261596`, so return `964176192` which its binary representation is `00111001011110000010100101000000`.

Example 2:

Input: `n = 111111111111111111111111111101`

Output: `3221225471 (10111111111111111111111111111111)`

Explanation: The input binary string `111111111111111111111111111101` represents the unsigned integer `4294967293`, so return `3221225471` which its binary representation is `10111111111111111111111111111111`.

Constraints:

- The input must be a **binary string** of length 32

191. Number of 1 Bits

Easy

4306932Add to ListShare

Write a function that takes an unsigned integer and returns the number of '1' bits it has (also known as the [Hamming weight](#)).

Note:

- Note that in some languages, such as Java, there is no unsigned integer type. In this case, the input will be given as a signed integer type. It should not affect your implementation, as the integer's internal binary representation is the same, whether it is signed or unsigned.
 - In Java, the compiler represents the signed integers using [2's complement notation](#). Therefore, in **Example 3**, the input represents the signed integer. -3 .

Example 1:

Output: 3

Explanation: The input binary string `00000000000000000000000000001011` has a total of three '1' bits.

Example 2:

Input: $n = 000000000000000000000000000000010000000$

Output: 1

Explanation: The input binary string `00000000000000000000000000000010000000` has a total of one '1' bit.

Example 3:

Output: 31

Explanation: The input binary string **11111111111111111111111111111101** has a total of thirty one '1' bits.

Constraints:

- The input must be a **binary string** of length 32.

192. Word Frequency**Medium**

406263Add to ListShare

Write a bash script to calculate the frequency of each word in a text file `words.txt`.

For simplicity sake, you may assume:

- `words.txt` contains only lowercase characters and space ' ' characters.
- Each word must consist of lowercase characters only.
- Words are separated by one or more whitespace characters.

Example:Assume that `words.txt` has the following content:

the day is sunny the the

the sunny is is

Your script should output the following, sorted by descending frequency:

the 4

is 3

sunny 2

day 1

Note:

- Don't worry about handling ties, it is guaranteed that each word's frequency count is unique.
- Could you write it in one-line using [Unix pipes](#)?

193. Valid Phone Numbers**Easy**

303784Add to ListShare

Given a text file `file.txt` that contains a list of phone numbers (one per line), write a one-liner bash script to print all valid phone numbers.

You may assume that a valid phone number must appear in one of the following two formats: (xxx) xxx-xxxx or xxx-xxx-xxxx. (x means a digit)

You may also assume each line in the text file must not contain leading or trailing white spaces.

Example:

Assume that `file.txt` has the following content:

```
987-123-4567
```

```
123 456 7890
```

```
(123) 456-7890
```

Your script should output the following valid phone numbers:

```
987-123-4567
```

```
(123) 456-7890
```

194. Transpose File

Medium

117254Add to ListShare

Given a text file `file.txt`, transpose its content.

You may assume that each row has the same number of columns, and each field is separated by the `' '` character.

Example:

If `file.txt` has the following content:

```
name age
```

```
alice 21
```

```
ryan 30
```

Output the following:

```
name alice ryan
```

```
age 21 30
```

195. Tenth Line

Easy

290375Add to ListShare

Given a text file `file.txt`, print just the 10th line of the file.

Example:

Assume that `file.txt` has the following content:

Line 1

Line 2

Line 3

Line 4

Line 5

Line 6

Line 7

Line 8

Line 9

Line 10

Your script should output the tenth line, which is:

Line 10

Note:

1. If the file contains less than 10 lines, what should you output?
2. There's at least three different solutions. Try to explore all possibilities.

196. Delete Duplicate Emails

Easy

573109Add to ListShare

SQL Schema

Table: `Person`

Column Name	Type
<code>id</code>	<code>int</code>
<code>email</code>	<code>varchar</code>

`id` is the primary key column for this table.

Each row of this table contains an email. The emails will not contain uppercase letters.

Write an SQL query to **delete** all the duplicate emails, keeping only one unique email with the smallest `id`. Note that you are supposed to write a `DELETE` statement and not a `SELECT` one.

After running your script, the answer shown is the `Person` table. The driver will first compile and run your piece of code and then show the `Person` table. The final order of the `Person` table **does not matter**.

The query result format is in the following example.

Example 1:

Input:

Person table:

id	email
1	john@example.com
2	bob@example.com
3	john@example.com

Output:

id	email
1	john@example.com
2	bob@example.com

Explanation: `john@example.com` is repeated two times. We keep the row with the smallest `Id = 1`.

197. Rising Temperature

Easy

1190407Add to ListShare

SQL Schema

Table: `Weather`

```
+-----+-----+
| Column Name | Type   |
+-----+-----+
| id          | int    |
| recordDate  | date   |
| temperature | int    |
+-----+-----+
```

`id` is the primary key for this table.

This table contains information about the temperature on a certain day.

Write an SQL query to find all dates' `Id` with higher temperatures compared to its previous dates (yesterday).

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Weather table:

```
+-----+-----+
| id | recordDate | temperature |
+-----+-----+
| 1  | 2015-01-01 | 10          |
| 2  | 2015-01-02 | 25          |
+-----+-----+
```

3 2015-01-03 20			
4 2015-01-04 30			
-----+-----+-----+			

Output:

-----+-----+-----+
id
-----+-----+
2
4
-----+-----+

Explanation:

In 2015-01-02, the temperature was higher than the previous day (10 -> 25).

In 2015-01-04, the temperature was higher than the previous day (20 -> 30).

198. House Robber

Medium

14689298Add to ListShare

You are a professional robber planning to rob houses along a street. Each house has a certain amount of money stashed, the only constraint stopping you from robbing each of them is that adjacent houses have security systems connected and **it will automatically contact the police if two adjacent houses were broken into on the same night.**

Given an integer array `nums` representing the amount of money of each house, return *the maximum amount of money you can rob tonight **without alerting the police***.

Example 1:

Input: `nums = [1,2,3,1]`

Output: 4

Explanation: Rob house 1 (money = 1) and then rob house 3 (money = 3).

Total amount you can rob = 1 + 3 = 4.

Example 2:

Input: nums = [2,7,9,3,1]

Output: 12

Explanation: Rob house 1 (money = 2), rob house 3 (money = 9) and rob house 5 (money = 1).

Total amount you can rob = $2 + 9 + 1 = 12$.

Constraints:

- $1 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 400$


199. Binary Tree Right Side View

Medium

8622501Add to ListShare

Given the `root` of a binary tree, imagine yourself standing on the **right side** of it, return *the values of the nodes you can see ordered from top to bottom*.

Example 1:



Input: root = [1,2,3,null,5,null,4]

Output: [1,3,4]

Example 2:

Input: root = [1,null,3]

Output: [1,3]

Example 3:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range [0, 100].
- $-100 \leq \text{Node.val} \leq 100$

200. Number of Islands

Medium

17120394Add to ListShare

Given an $m \times n$ 2D binary grid `grid` which represents a map of '1's (land) and '0's (water), return *the number of islands*.

An **island** is surrounded by water and is formed by connecting adjacent lands horizontally or vertically. You may assume all four edges of the grid are all surrounded by water.

Example 1:

Input: grid = [
 ["1","1","1","1","0"],
 ["1","1","0","1","0"],
 ["1","1","0","0","0"],
 ["0","0","0","0","0"]
]

Output: 1

Example 2:

Input: grid = [
 ["1","1","0","0","0"],
 ["1","1","0","0","0"]]

```

["1","1","0","0","0"],
["0","0","1","0","0"],
["0","0","0","1","1"]
]

```

Output: 3

Constraints:

- $m == \text{grid.length}$
- $n == \text{grid[i].length}$
- $1 \leq m, n \leq 300$
- $\text{grid[i][j] is '0' or '1'}$.

201. Bitwise AND of Numbers Range

Medium

2504187 Add to List Share

Given two integers `left` and `right` that represent the range `[left, right]`, return *the bitwise AND of all numbers in this range, inclusive*.

Example 1:

Input: `left = 5, right = 7`

Output: 4

Example 2:

Input: `left = 0, right = 0`

Output: 0

Example 3:

Input: `left = 1, right = 2147483647`

Output: 0

Constraints:

- `0 <= left <= right <= 231 - 1`

202. Happy Number

Easy

6828849Add to ListShare

Write an algorithm to determine if a number `n` is happy.

A **happy number** is a number defined by the following process:

- Starting with any positive integer, replace the number by the sum of the squares of its digits.
- Repeat the process until the number equals 1 (where it will stay), or it **loops endlessly in a cycle** which does not include 1.
- Those numbers for which this process **ends in 1** are happy.

Return `true` if `n` is a happy number, and `false` if not.

Example 1:

Input: `n = 19`

Output: `true`

Explanation:

$1^2 + 9^2 = 82$

$8^2 + 2^2 = 68$

$6^2 + 8^2 = 100$

$1^2 + 0^2 + 0^2 = 1$

Example 2:

Input: `n = 2`

Output: `false`

Constraints:


- `1 <= n <= 231 - 1`

203. Remove Linked List Elements

Easy

5979182Add to ListShare

Given the `head` of a linked list and an integer `val`, remove all the nodes of the linked list that has `Node.val == val`, and return *the new head*.

Example 1:

Input: `head = [1,2,6,3,4,5,6]`, `val = 6`

Output: `[1,2,3,4,5]`

Example 2:

Input: `head = []`, `val = 1`

Output: `[]`

Example 3:

Input: `head = [7,7,7,7]`, `val = 7`

Output: `[]`

Constraints:

- The number of nodes in the list is in the range $[0, 10^4]$.
- $1 \leq \text{Node.val} \leq 50$
- $0 \leq \text{val} \leq 50$

204. Count Primes**Medium**

56281108Add to ListShare

Given an integer `n`, return *the number of prime numbers that are strictly less than n*.

Example 1:**Input:** n = 10**Output:** 4**Explanation:** There are 4 prime numbers less than 10, they are 2, 3, 5, 7.**Example 2:****Input:** n = 0**Output:** 0**Example 3:****Input:** n = 1**Output:** 0**Constraints:**

- $0 \leq n \leq 5 * 10^6$

205. Isomorphic Strings

Easy

4879895Add to ListShare

Given two strings `s` and `t`, determine if they are isomorphic.Two strings `s` and `t` are isomorphic if the characters in `s` can be replaced to get `t`.

All occurrences of a character must be replaced with another character while preserving the order of characters. No two characters may map to the same character, but a character may map to itself.


Example 1:**Input:** s = "egg", t = "add"**Output:** true**Example 2:****Input:** s = "foo", t = "bar"**Output:** false



Example 3:**Input:** s = "paper", t = "title"**Output:** true**Constraints:**

- $1 \leq s.length \leq 5 * 10^4$
- $t.length == s.length$
- s and t consist of any valid ascii character.

206. Reverse Linked List**Easy**

14727249Add to ListShare

Given the `head` of a singly linked list, reverse the list, and return *the reversed list*.**Example 1:****Input:** head = [1,2,3,4,5]**Output:** [5,4,3,2,1]**Example 2:**



Input: head = [1,2]

Output: [2,1]

Example 3:

Input: head = []

Output: []

Constraints:

- The number of nodes in the list is in the range [0, 5000].
- $-5000 \leq \text{Node.val} \leq 5000$

207. Course Schedule

Medium

11421441Add to ListShare

There are a total of `numCourses` courses you have to take, labeled from `0` to `numCourses - 1`. You are given an array `prerequisites` where `prerequisites[i] = [ai, bi]` indicates that you **must** take course `bi` first if you want to take course `ai`.

- For example, the pair `[0, 1]`, indicates that to take course `0` you have to first take course `1`.

Return `true` if you can finish all courses. Otherwise, return `false`.

Example 1:

Input: `numCourses = 2, prerequisites = [[1,0]]`

Output: true

Explanation: There are a total of 2 courses to take.

To take course 1 you should have finished course 0. So it is possible.

Example 2:

Input: numCourses = 2, prerequisites = [[1,0],[0,1]]

Output: false

Explanation: There are a total of 2 courses to take.

To take course 1 you should have finished course 0, and to take course 0 you should also have finished course 1. So it is impossible.

Constraints:

- `1 <= numCourses <= 2000`
- `0 <= prerequisites.length <= 5000`
- `prerequisites[i].length == 2`
- `0 <= ai, bi < numCourses`
- All the pairs `prerequisites[i]` are **unique**.

208. Implement Trie (Prefix Tree)

Medium

8230102Add to ListShare

A **trie** (pronounced as "try") or **prefix tree** is a tree data structure used to efficiently store and retrieve keys in a dataset of strings. There are various applications of this data structure, such as autocomplete and spellchecker.

Implement the Trie class:

- `Trie()` Initializes the trie object.
- `void insert(String word)` Inserts the string `word` into the trie.
- `boolean search(String word)` Returns `true` if the string `word` is in the trie (i.e., was inserted before), and `false` otherwise.
- `boolean startsWith(String prefix)` Returns `true` if there is a previously inserted string `word` that has the prefix `prefix`, and `false` otherwise.

Example 1:

Input

```
["Trie", "insert", "search", "search", "startsWith", "insert", "search"]
[[], ["apple"], ["apple"], ["app"], ["app"], ["app"], ["app"]]
```

Output

```
[null, null, true, false, true, null, true]
```

Explanation

```
Trie trie = new Trie();
trie.insert("apple");
trie.search("apple");    // return True
trie.search("app");     // return False
trie.startsWith("app"); // return True
trie.insert("app");
trie.search("app");     // return True
```

Constraints:

- $1 \leq \text{word.length, prefix.length} \leq 2000$
- `word` and `prefix` consist only of lowercase English letters.
- At most $3 * 10^4$ calls in total will be made to `insert`, `search`, and `startsWith`.

209. Minimum Size Subarray Sum

Medium

7878218Add to ListShare

Given an array of positive integers `nums` and a positive integer `target`, return the minimal length of a **contiguous subarray** $[nums_1, nums_{1+1}, \dots, nums_{r-1}, nums_r]$ of which the sum is greater than or equal to `target`. If there is no such subarray, return `0` instead.

Example 1:

Input: `target = 7, nums = [2,3,1,2,4,3]`

Output: 2

Explanation: The subarray $[4,3]$ has the minimal length under the problem constraint.

Example 2:

Input: target = 4, nums = [1,4,4]

Output: 1

Example 3:

Input: target = 11, nums = [1,1,1,1,1,1,1,1]

Output: 0

Constraints:

- $1 \leq \text{target} \leq 10^9$
- $1 \leq \text{nums.length} \leq 10^5$
- $1 \leq \text{nums}[i] \leq 10^4$

210. Course Schedule II**Medium**

7933266Add to ListShare

There are a total of `numCourses` courses you have to take, labeled from `0` to `numCourses - 1`. You are given an array `prerequisites` where `prerequisites[i] = [ai, bi]` indicates that you **must** take course `bi` first if you want to take course `ai`.

- For example, the pair `[0, 1]`, indicates that to take course `0` you have to first take course `1`.

Return *the ordering of courses you should take to finish all courses*. If there are many valid answers, return **any** of them. If it is impossible to finish all courses, return **an empty array**.

Example 1:

Input: `numCourses = 2, prerequisites = [[1,0]]`

Output: `[0,1]`

Explanation: There are a total of 2 courses to take. To take course 1 you should have finished course 0. So the correct course order is `[0,1]`.

Example 2:

Input: `numCourses = 4, prerequisites = [[1,0],[2,0],[3,1],[3,2]]`

Output: [0,2,1,3]

Explanation: There are a total of 4 courses to take. To take course 3 you should have finished both courses 1 and 2. Both courses 1 and 2 should be taken after you finished course 0.

So one correct course order is [0,1,2,3]. Another correct ordering is [0,2,1,3].

Example 3:

Input: numCourses = 1, prerequisites = []

Output: [0]

Constraints:

- $1 \leq \text{numCourses} \leq 2000$
- $0 \leq \text{prerequisites.length} \leq \text{numCourses} * (\text{numCourses} - 1)$
- $\text{prerequisites}[i].length == 2$
- $0 \leq a_i, b_i < \text{numCourses}$
- $a_i \neq b_i$
- All the pairs $[a_i, b_i]$ are **distinct**.

211. Design Add and Search Words Data Structure

Medium

5475291 Add to List Share

Design a data structure that supports adding new words and finding if a string matches any previously added string.

Implement the `WordDictionary` class:

- `WordDictionary()` Initializes the object.
- `void addWord(word)` Adds `word` to the data structure, it can be matched later.
- `bool search (word)` Returns `true` if there is any string in the data structure that matches `word` or `false` otherwise. `word` may contain dots `'.'` where dots can be matched with any letter.

Example:

Input

```
["WordDictionary", "addWord", "addWord", "addWord", "search", "search", "search", "search"]
[[], ["bad"], ["dad"], ["mad"], ["pad"], ["bad"], [".ad"], ["b.."]]
```

Output

```
[null,null,null,null,false,true,true,true]
```

Explanation

```
WordDictionary wordDictionary = new WordDictionary();
wordDictionary.addWord("bad");
wordDictionary.addWord("dad");
wordDictionary.addWord("mad");
wordDictionary.search("pad"); // return False
wordDictionary.search("bad"); // return True
wordDictionary.search(".ad"); // return True
wordDictionary.search("b.."); // return True
```

Constraints:

- `1 <= word.length <= 25`
- `word` in `addWord` consists of lowercase English letters.
- `word` in `search` consist of `'.'` or lowercase English letters.
- There will be at most 3 dots in `word` for `search` queries.
- At most 10^4 calls will be made to `addWord` and `search`.

212. Word Search II**Hard**

6810289Add to ListShare

Given an `m x n` board of characters and a list of strings `words`, return *all words on the board*.

Each word must be constructed from letters of sequentially adjacent cells, where **adjacent cells** are horizontally or vertically neighboring. The same letter cell may not be used more than once in a word.

Example 1:

o	a	a	n
e	t	a	e
i	h	k	r
i	f	l	v

Input: board =
`[["o", "a", "a", "n"], ["e", "t", "a", "e"], ["i", "h", "k", "r"], ["i", "f", "l", "v"]], words = ["oath", "pea", "eat", "rain"]`

Output: ["eat", "oath"]

Example 2:

a	b
c	d

Input: board = [["a", "b"], ["c", "d"]], words = ["abcb"]

Output: []

Constraints:

- `m == board.length`
- `n == board[i].length`
- `1 <= m, n <= 12`
- `board[i][j]` is a lowercase English letter.
- `1 <= words.length <= 3 * 104`
- `1 <= words[i].length <= 10`

- `words[i]` consists of lowercase English letters.
- All the strings of `words` are unique.

213. House Robber II

Medium

6882105Add to ListShare

You are a professional robber planning to rob houses along a street. Each house has a certain amount of money stashed. All houses at this place are **arranged in a circle**. That means the first house is the neighbor of the last one. Meanwhile, adjacent houses have a security system connected, and **it will automatically contact the police if two adjacent houses were broken into on the same night**.

Given an integer array `nums` representing the amount of money of each house, return *the maximum amount of money you can rob tonight **without alerting the police***.

Example 1:

Input: `nums = [2,3,2]`

Output: 3

Explanation: You cannot rob house 1 (`money = 2`) and then rob house 3 (`money = 2`), because they are adjacent houses.

Example 2:

Input: `nums = [1,2,3,1]`

Output: 4

Explanation: Rob house 1 (`money = 1`) and then rob house 3 (`money = 3`).

Total amount you can rob = $1 + 3 = 4$.

Example 3:

Input: `nums = [1,2,3]`

Output: 3

Constraints:

- $1 \leq \text{nums.length} \leq 100$
- $0 \leq \text{nums}[i] \leq 1000$

214. Shortest Palindrome

Hard

2782202Add to ListShare

You are given a string `s`. You can convert `s` to a palindrome by adding characters in front of it.

Return *the shortest palindrome you can find by performing this transformation.*

Example 1:

Input: `s = "aacecaaa"`

Output: `"aaacecaaa"`

Example 2:

Input: `s = "abcd"`

Output: `"dcbabcd"`

Constraints:

- $0 \leq s.length \leq 5 * 10^4$
- `s` consists of lowercase English letters only.

215. Kth Largest Element in an Array

Medium

11959606Add to ListShare

Given an integer array `nums` and an integer `k`, return *the k^{th} largest element in the array.*

Note that it is the k^{th} largest element in the sorted order, not the k^{th} distinct element.

You must solve it in $O(n)$ time complexity.

Example 1:

Input: `nums = [3,2,1,5,6,4], k = 2`

Output: `5`

Example 2:

Input: `nums = [3,2,3,1,2,4,5,5,6], k = 4`

Output: 4

Constraints:

- $1 \leq k \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

216. Combination Sum III

Medium

422792Add to ListShare

Find all valid combinations of k numbers that sum up to n such that the following conditions are true:

- Only numbers 1 through 9 are used.
- Each number is used **at most once**.

Return a *list of all possible valid combinations*. The list must not contain the same combination twice, and the combinations may be returned in any order.

Example 1:

Input: $k = 3$, $n = 7$

Output: $[[1,2,4]]$

Explanation:

$$1 + 2 + 4 = 7$$

There are no other valid combinations.

Example 2:

Input: $k = 3$, $n = 9$

Output: $[[1,2,6],[1,3,5],[2,3,4]]$

Explanation:

$$1 + 2 + 6 = 9$$

$$1 + 3 + 5 = 9$$

$$2 + 3 + 4 = 9$$

There are no other valid combinations.

Example 3:**Input:** k = 4, n = 1**Output:** []**Explanation:** There are no valid combinations.

Using 4 different numbers in the range [1,9], the smallest sum we can get is $1+2+3+4 = 10$ and since $10 > 1$, there are no valid combination.

Constraints:

- $2 \leq k \leq 9$
- $1 \leq n \leq 60$

217. Contains Duplicate**Easy**

66821028Add to ListShare

Given an integer array `nums`, return `true` if any value appears **at least twice** in the array, and return `false` if every element is distinct.

Example 1:**Input:** `nums` = [1,2,3,1]**Output:** `true`**Example 2:****Input:** `nums` = [1,2,3,4]**Output:** `false`**Example 3:****Input:** `nums` = [1,1,1,3,3,4,3,2,4,2]**Output:** `true`**Constraints:**

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

218. The Skyline Problem

Hard

4194214Add to ListShare

A city's **skyline** is the outer contour of the silhouette formed by all the buildings in that city when viewed from a distance. Given the locations and heights of all the buildings, return *the skyline formed by these buildings collectively*.

The geometric information of each building is given in the array `buildings` where `buildings[i] = [lefti, righti, heighti]`:


- `lefti` is the x coordinate of the left edge of the `ith` building.
- `righti` is the x coordinate of the right edge of the `ith` building.
- `heighti` is the height of the `ith` building.

You may assume all buildings are perfect rectangles grounded on an absolutely flat surface at height 0.

The **skyline** should be represented as a list of "key points" **sorted by their x-coordinate** in the form `[[x1, y1], [x2, y2], ...]`. Each key point is the left endpoint of some horizontal segment in the skyline except the last point in the list, which always has a y-coordinate 0 and is used to mark the skyline's termination where the rightmost building ends. Any ground between the leftmost and rightmost buildings should be part of the skyline's contour.

Note: There must be no consecutive horizontal lines of equal height in the output skyline. For instance, `[..., [2 3], [4 5], [7 5], [11 5], [12 7], ...]` is not acceptable; the three lines of height 5 should be merged into one in the final output as such: `[..., [2 3], [4 5], [12 7], ...]`

Example 1:



Input: `buildings = [[2,9,10],[3,7,15],[5,12,12],[15,20,10],[19,24,8]]`

Output: `[[2,10],[3,15],[7,12],[12,0],[15,10],[20,8],[24,0]]`

Explanation:

Figure A shows the buildings of the input.

Figure B shows the skyline formed by those buildings. The red points in figure B represent the key points in the output list.

Example 2:

Input: `buildings = [[0,2,3],[2,5,3]]`

Output: `[[0,3],[5,0]]`

Constraints:

- $1 \leq \text{buildings.length} \leq 10^4$
- $0 \leq \text{left}_i < \text{right}_i \leq 2^{31} - 1$
- $1 \leq \text{height}_i \leq 2^{31} - 1$
- `buildings` is sorted by `lefti` in non-decreasing order.

219. Contains Duplicate II

Easy

31742134Add to ListShare

Given an integer array `nums` and an integer `k`, return `true` if there are two **distinct indices** `i` and `j` in the array such that `nums[i] == nums[j]` and `abs(i - j) <= k`.

Example 1:

Input: `nums = [1,2,3,1], k = 3`

Output: `true`

Example 2:

Input: `nums = [1,0,1,1], k = 1`

Output: `true`

Example 3:

Input: `nums = [1,2,3,1,2,3], k = 2`

Output: `false`

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $0 \leq k \leq 10^5$

220. Contains Duplicate III**Hard**

682Add to ListShare

You are given an integer array `nums` and two integers `indexDiff` and `valueDiff`.Find a pair of indices `(i, j)` such that:

- $i \neq j$,
- $\text{abs}(i - j) \leq \text{indexDiff}$.
- $\text{abs}(\text{nums}[i] - \text{nums}[j]) \leq \text{valueDiff}$, and

Return `true` if such pair exists or `false` otherwise.**Example 1:****Input:** `nums = [1,2,3,1]`, `indexDiff = 3`, `valueDiff = 0`**Output:** `true`**Explanation:** We can choose $(i, j) = (0, 3)$.

We satisfy the three conditions:

 $i \neq j \rightarrow 0 \neq 3$ $\text{abs}(i - j) \leq \text{indexDiff} \rightarrow \text{abs}(0 - 3) \leq 3$ $\text{abs}(\text{nums}[i] - \text{nums}[j]) \leq \text{valueDiff} \rightarrow \text{abs}(1 - 1) \leq 0$ **Example 2:****Input:** `nums = [1,5,9,1,5,9]`, `indexDiff = 2`, `valueDiff = 3`**Output:** `false`**Explanation:** After trying all the possible pairs (i, j) , we cannot satisfy the three conditions, so we return `false`.

Constraints:

- $2 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $1 \leq \text{indexDiff} \leq \text{nums.length}$
- $0 \leq \text{valueDiff} \leq 10^9$

221. Maximal Square**Medium**

8052176Add to ListShare

Given an $m \times n$ binary matrix filled with 0's and 1's, find the largest square containing only 1's and return its area.

Example 1:

1	0	1	0	0
1	0	1	1	1
1	1	1	1	1
1	0	0	1	0

Input: matrix =
`[[["1","0","1","0","0"],["1","0","1","1","1"],["1","1","1","1","1"],["1","0","0","1","0"]]]`

Output: 4**Example 2:**

0	1
1	0

Input: matrix = [["0","1"],["1","0"]]

Output: 1

Example 3:

Input: matrix = [["0"]]

Output: 0

Constraints:

- $m == \text{matrix.length}$
- $n == \text{matrix}[i].length$
- $1 \leq m, n \leq 300$
- $\text{matrix}[i][j]$ is '0' or '1'.

222. Count Complete Tree Nodes

Medium


5709330Add to ListShare

Given the `root` of a **complete** binary tree, return the number of the nodes in the tree.

According to [Wikipedia](#), every level, except possibly the last, is completely filled in a complete binary tree, and all nodes in the last level are as far left as possible. It can have between 1 and 2^h nodes inclusive at the last level h .

Design an algorithm that runs in less than $O(n)$ time complexity.

Example 1:



Input: root = [1,2,3,4,5,6]

Output: 6

Example 2:

Input: root = []

Output: 0

Example 3:

Input: root = [1]

Output: 1

Constraints:

- The number of nodes in the tree is in the range `[0, 5 * 104]`.
- `0 <= Node.val <= 5 * 104`
- The tree is guaranteed to be **complete**.

223. Rectangle Area

Medium


8441074Add to ListShare

Given the coordinates of two **rectilinear** rectangles in a 2D plane, return *the total area covered by the two rectangles*.

The first rectangle is defined by its **bottom-left** corner (ax_1, ay_1) and its **top-right** corner (ax_2, ay_2) .

The second rectangle is defined by its **bottom-left** corner (bx_1, by_1) and its **top-right** corner (bx_2, by_2) .

Example 1:



Input: $ax_1 = -3, ay_1 = 0, ax_2 = 3, ay_2 = 4, bx_1 = 0, by_1 = -1, bx_2 = 9, by_2 = 2$

Output: 45

Example 2:

Input: $ax_1 = -2, ay_1 = -2, ax_2 = 2, ay_2 = 2, bx_1 = -2, by_1 = -2, bx_2 = 2, by_2 = 2$

Output: 16

Constraints:

- $-10^4 \leq ax_1 \leq ax_2 \leq 10^4$
- $-10^4 \leq ay_1 \leq ay_2 \leq 10^4$
- $-10^4 \leq bx_1 \leq bx_2 \leq 10^4$
- $-10^4 \leq by_1 \leq by_2 \leq 10^4$

224. Basic Calculator

Hard

4097326Add to ListShare

Given a string `s` representing a valid expression, implement a basic calculator to evaluate it, and return *the result of the evaluation*.

Note: You are **not** allowed to use any built-in function which evaluates strings as mathematical expressions, such as `eval()`.

Example 1:

Input: `s = "1 + 1"`

Output: 2

Example 2:

Input: `s = " 2-1 + 2 "`

Output: 3

Example 3:

Input: `s = "(1+(4+5+2)-3)+(6+8)"`

Output: 23

Constraints:

- `1 <= s.length <= 3 * 105`
- `s` consists of digits, `'+'`, `'-'`, `'('`, `')'`, and `' '`.
- `s` represents a valid expression.
- `'+'` is **not** used as a unary operation (i.e., `"+1"` and `"+(2 + 3)"` is invalid).
- `'-'` could be used as a unary operation (i.e., `"-1"` and `"-(2 + 3)"` is valid).
- There will be no two consecutive operators in the input.
- Every number and running calculation will fit in a signed 32-bit integer.

225. Implement Stack using Queues

Easy

3477911Add to ListShare

Implement a last-in-first-out (LIFO) stack using only two queues. The implemented stack should support all the functions of a normal stack (`push`, `top`, `pop`, and `empty`).

Implement the `MyStack` class:

- `void push(int x)` Pushes element x to the top of the stack.
- `int pop()` Removes the element on the top of the stack and returns it.
- `int top()` Returns the element on the top of the stack.
- `boolean empty()` Returns `true` if the stack is empty, `false` otherwise.

Notes:

- You must use **only** standard operations of a queue, which means that only `push to back`, `peek/pop from front`, `size` and `is empty` operations are valid.
- Depending on your language, the queue may not be supported natively. You may simulate a queue using a list or deque (double-ended queue) as long as you use only a queue's standard operations.

Example 1:

Input

```
["MyStack", "push", "push", "top", "pop", "empty"]
[[], [1], [2], [], [], []]
```

Output

```
[null, null, null, 2, 2, false]
```

Explanation

```
MyStack myStack = new MyStack();
myStack.push(1);
myStack.push(2);
myStack.top(); // return 2
myStack.pop(); // return 2
myStack.empty(); // return False
```

Constraints:

- $1 \leq x \leq 9$
- At most 100 calls will be made to `push`, `pop`, `top`, and `empty`.
- All the calls to `pop` and `top` are valid.


226. Invert Binary Tree

Easy


9880136Add to ListShare

Given the `root` of a binary tree, invert the tree, and return *its root*.

Example 1:



Example 2:



Example 3:

Input: `root = []`

Output: `[]`

Constraints:

- The number of nodes in the tree is in the range `[0, 100]`.
- `-100 <= Node.val <= 100`

227. Basic Calculator II**Medium**

4878632Add to ListShare

Given a string `s` which represents an expression, *evaluate this expression and return its value*.

The integer division should truncate toward zero.

You may assume that the given expression is always valid. All intermediate results will be in the range of $[-2^{31}, 2^{31} - 1]$.**Note:** You are not allowed to use any built-in function which evaluates strings as mathematical expressions, such as `eval()`.**Example 1:****Input:** `s = "3+2*2"`**Output:** 7**Example 2:****Input:** `s = " 3/2 "`**Output:** 1**Example 3:****Input:** `s = " 3+5 / 2 "`**Output:** 5**Constraints:**

- `1 <= s.length <= 3 * 10^5`
- `s` consists of integers and operators `('+', '−', '∗', '÷')` separated by some number of spaces.
- `s` represents a **valid expression**.
- All the integers in the expression are non-negative integers in the range `[0, 2^{31} - 1]`.
- The answer is **guaranteed** to fit in a **32-bit integer**.

228. Summary Ranges

Easy

22581242Add to ListShare

You are given a **sorted unique** integer array `nums`.

A **range** $[a, b]$ is the set of all integers from a to b (inclusive).

Return *the smallest sorted list of ranges that cover all the numbers in the array exactly*. That is, each element of `nums` is covered by exactly one of the ranges, and there is no integer x such that x is in one of the ranges but not in `nums`.

Each range $[a, b]$ in the list should be output as:

- `"a->b"` if $a \neq b$
- `"a"` if $a == b$

Example 1:

Input: `nums = [0,1,2,4,5,7]`

Output: `["0->2", "4->5", "7"]`

Explanation: The ranges are:

`[0,2]` --> `"0->2"`

`[4,5]` --> `"4->5"`

`[7,7]` --> `"7"`

Example 2:

Input: `nums = [0,2,3,4,6,8,9]`

Output: `["0", "2->4", "6", "8->9"]`

Explanation: The ranges are:

`[0,0]` --> `"0"`

`[2,4]` --> `"2->4"`

`[6,6]` --> `"6"`

`[8,9]` --> `"8->9"`

Constraints:

- $0 \leq \text{nums.length} \leq 20$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- All the values of `nums` are **unique**.
- `nums` is sorted in ascending order.

229. Majority Element II**Medium**

6044312Add to ListShare


Given an integer array of size `n`, find all elements that appear more than $\lfloor n/3 \rfloor$ times.**Example 1:****Input:** `nums = [3,2,3]`**Output:** `[3]`**Example 2:****Input:** `nums = [1]`**Output:** `[1]`**Example 3:****Input:** `nums = [1,2]`**Output:** `[1,2]`**Constraints:**

- $1 \leq \text{nums.length} \leq 5 * 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

230. Kth Smallest Element in a BST**Medium**


8395147Add to ListShare

Given the `root` of a binary search tree, and an integer `k`, return the k^{th} smallest value (**1-indexed**) of all the values of the nodes in the tree.

Example 1:

Input: root = [3,1,4,null,2], k = 1

Output: 1

Example 2:

Input: root = [5,3,6,2,4,null,null,1], k = 3

Output: 3

Constraints:

- The number of nodes in the tree is `n`.
- $1 \leq k \leq n \leq 10^4$
- $0 \leq \text{Node.val} \leq 10^4$

231. Power of Two

Easy

4138318Add to ListShare

Given an integer `n`, return `true` if it is a power of two. Otherwise, return `false`.

An integer `n` is a power of two, if there exists an integer `x` such that `n == 2x`.

Example 1:

Input: `n = 1`

Output: `true`

Explanation: $2^0 = 1$

Example 2:

Input: `n = 16`

Output: `true`

Explanation: $2^4 = 16$

Example 3:

Input: `n = 3`

Output: `false`

Constraints:

- $-2^{31} \leq n \leq 2^{31} - 1$

232. Implement Queue using Stacks

Easy

4334275Add to ListShare

Implement a first in first out (FIFO) queue using only two stacks. The implemented queue should support all the functions of a normal queue (`push`, `peek`, `pop`, and `empty`).

Implement the `MyQueue` class:

- `void push(int x)` Pushes element `x` to the back of the queue.
- `int pop()` Removes the element from the front of the queue and returns it.
- `int peek()` Returns the element at the front of the queue.
- `boolean empty()` Returns `true` if the queue is empty, `false` otherwise.

Notes:

- You must use **only** standard operations of a stack, which means only `push to top`, `peek/pop from top`, `size`, and `is empty` operations are valid.
- Depending on your language, the stack may not be supported natively. You may simulate a stack using a list or deque (double-ended queue) as long as you use only a stack's standard operations.

Example 1:

Input

```
["MyQueue", "push", "push", "peek", "pop", "empty"]
[], [1], [2], [], [], []
```

Output

```
[null, null, null, 1, 1, false]
```

Explanation

```
MyQueue myQueue = new MyQueue();
myQueue.push(1); // queue is: [1]
myQueue.push(2); // queue is: [1, 2] (leftmost is front of the queue)
myQueue.peek(); // return 1
myQueue.pop(); // return 1, queue is [2]
myQueue.empty(); // return false
```

Constraints:

- `1 <= x <= 9`

- At most 100 calls will be made to `push`, `pop`, `peek`, and `empty`.
- All the calls to `pop` and `peek` are valid.

233. Number of Digit One

Hard

9051160Add to ListShare

Given an integer `n`, count the total number of digit 1 appearing in all non-negative integers less than or equal to `n`.

Example 1:

Input: `n = 13`

Output: 6

Example 2:

Input: `n = 0`

Output: 0

Constraints:

- `0 <= n <= 109`


234. Palindrome Linked List

Easy

11808656Add to ListShare

Given the `head` of a singly linked list, return `true` if it is a palindrome or `false` otherwise.


Example 1:



Input: `head = [1,2,2,1]`

Output: `true`

Example 2:



Input: head = [1, 2]

Output: false

Constraints:

- The number of nodes in the list is in the range [1, 10^5].
- $0 \leq \text{Node.val} \leq 9$

235. Lowest Common Ancestor of a Binary Search Tree


Medium

7849233Add to ListShare

Given a binary search tree (BST), find the lowest common ancestor (LCA) node of two given nodes in the BST.

According to the [definition of LCA on Wikipedia](#): "The lowest common ancestor is defined between two nodes p and q as the lowest node in T that has both p and q as descendants (where we allow a node to be a descendant of itself)."

Example 1:




Input: root = [6,2,8,0,4,7,9,null,null,3,5], p = 2, q = 8

Output: 6

Explanation: The LCA of nodes 2 and 8 is 6.

Example 2:



Input: root = [6,2,8,0,4,7,9,null,null,3,5], p = 2, q = 4

Output: 2

Explanation: The LCA of nodes 2 and 4 is 2, since a node can be a descendant of itself according to the LCA definition.

Example 3:

Input: root = [2,1], p = 2, q = 1

Output: 2

Constraints:

- The number of nodes in the tree is in the range $[2, 10^5]$.
- $-10^9 \leq \text{Node.val} \leq 10^9$
- All `Node.val` are **unique**.
- $p \neq q$
- p and q will exist in the BST.

236. Lowest Common Ancestor of a Binary Tree


Medium

12445307 Add to List Share

Given a binary tree, find the lowest common ancestor (LCA) of two given nodes in the tree.

According to the [definition of LCA on Wikipedia](#): "The lowest common ancestor is defined between two nodes p and q as the lowest node in T that has both p and q as descendants (where we allow a node to be a descendant of itself)."

Example 1:




Input: root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 1

Output: 3

Explanation: The LCA of nodes 5 and 1 is 3.

Example 2:



Input: root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 4

Output: 5

Explanation: The LCA of nodes 5 and 4 is 5, since a node can be a descendant of itself according to the LCA definition.

Example 3:

Input: root = [1,2], p = 1, q = 2

Output: 1

Constraints:

- The number of nodes in the tree is in the range $[2, 10^5]$.
- $-10^9 \leq \text{Node.val} \leq 10^9$
- All `Node.val` are **unique**.
- $p \neq q$

- `p` and `q` will exist in the tree.

237. Delete Node in a Linked List

Medium

36068Add to ListShare

There is a singly-linked list `head` and we want to delete a node `node` in it.

You are given the node to be deleted `node`. You will **not be given access** to the first node of `head`.

All the values of the linked list are **unique**, and it is guaranteed that the given node `node` is not the last node in the linked list.


Delete the given node. Note that by deleting the `node`, we do not mean removing it from memory. We mean:

- The value of the given node should not exist in the linked list.
- The number of nodes in the linked list should decrease by one.
- All the values before `node` should be in the same order.
- All the values after `node` should be in the same order.

Custom testing:

- For the input, you should provide the entire linked list `head` and the node to be given `node`. `node` should not be the last node of the list and should be an actual node in the list.
- We will build the linked list and pass the node to your function.
- The output will be the entire list after calling your function.

Example 1:





Input: head = [4,5,1,9], node = 5

Output: [4,1,9]

Explanation: You are given the second node with value 5, the linked list should become 4 -> 1 -> 9 after calling your function.

Example 2:



Input: head = [4,5,1,9], node = 1

Output: [4,5,9]

Explanation: You are given the third node with value 1, the linked list should become $4 \rightarrow 5 \rightarrow 9$ after calling your function.

Constraints:

- The number of the nodes in the given list is in the range `[2, 1000]`.
- `-1000 <= Node.val <= 1000`
- The value of each node in the list is **unique**.
- The `node` to be deleted is **in the list** and is **not a tail** node.

238. Product of Array Except Self

Medium

14667843Add to ListShare

Given an integer array `nums`, return an array `answer` such that `answer[i]` is equal to the product of all the elements of `nums` except `nums[i]`.

The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

You must write an algorithm that runs in $O(n)$ time and without using the division operation.

Example 1:

Input: `nums = [1,2,3,4]`

Output: `[24,12,8,6]`

Example 2:

Input: `nums = [-1,1,0,-3,3]`

Output: `[0,0,9,0,0]`

Constraints:

- $2 \leq \text{nums.length} \leq 10^5$
- $-30 \leq \text{nums}[i] \leq 30$
- The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

239. Sliding Window Maximum

Hard

12190389Add to ListShare

You are given an array of integers `nums`, there is a sliding window of size `k` which is moving from the very left of the array to the very right. You can only see the `k` numbers in the window. Each time the sliding window moves right by one position.

Return *the max sliding window*.

Example 1:

Input: `nums = [1,3,-1,-3,5,3,6,7], k = 3`

Output: `[3,3,5,5,6,7]`

Explanation:

Window position	Max
-----	-----
<code>[1 3 -1] -3 5 3 6 7</code>	<code>3</code>

```

1 [3 -1 -3] 5 3 6 7      3
1 3 [-1 -3 5] 3 6 7      5
1 3 -1 [-3 5 3] 6 7      5
1 3 -1 -3 [5 3 6] 7      6
1 3 -1 -3 5 [3 6 7]      7

```

Example 2:

Input: `nums = [1], k = 1`

Output: `[1]`

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- $1 \leq k \leq \text{nums.length}$

240. Search a 2D Matrix II

Medium

9275154Add to ListShare

Write an efficient algorithm that searches for a value `target` in an $m \times n$ integer matrix `matrix`.

This matrix has the following properties:

- Integers in each row are sorted in ascending from left to right.
- Integers in each column are sorted in ascending from top to bottom.

Example 1:

1	4	7	11	15
2	5	8	12	19
3	6	9	16	22
10	13	14	17	24
18	21	23	26	30

Input: matrix =
[[1,4,7,11,15],[2,5,8,12,19],[3,6,9,16,22],[10,13,14,17,24],[18,21,23,26,30]], target = 5

Output: true

Example 2:

1	4	7	11	15
2	5	8	12	19
3	6	9	16	22
10	13	14	17	24
18	21	23	26	30

Input: matrix =
`[[1,4,7,11,15],[2,5,8,12,19],[3,6,9,16,22],[10,13,14,17,24],[18,21,23,26,30]]`, target = 20

Output: false

Constraints:

- `m == matrix.length`
- `n == matrix[i].length`
- `1 <= n, m <= 300`
- `-109 <= matrix[i][j] <= 109`
- All the integers in each row are **sorted** in ascending order.
- All the integers in each column are **sorted** in ascending order.
- `-109 <= target <= 109`

241. Different Ways to Add Parentheses

Medium

4202206Add to ListShare

Given a string `expression` of numbers and operators, return *all possible results from computing all the different possible ways to group numbers and operators*. You may return the answer in **any order**.

The test cases are generated such that the output values fit in a 32-bit integer and the number of different results does not exceed 10^4 .

Example 1:

Input: expression = "2-1-1"

Output: [0,2]

Explanation:

$((2-1)-1) = 0$

$(2-(1-1)) = 2$

Example 2:

Input: expression = "2*3-4*5"

Output: [-34, -14, -10, -10, 10]

Explanation:

$(2*(3-(4*5))) = -34$

$((2*3)-(4*5)) = -14$

$((2*(3-4))*5) = -10$

$(2*((3-4)*5)) = -10$

$((2*3)-4)*5) = 10$

Constraints:

- $1 \leq \text{expression.length} \leq 20$
- expression consists of digits and the operator '+', '-' , and '*' .
- All the integer values in the input expression are in the range [0, 99].

242. Valid Anagram

Easy

7057240Add to ListShare

Given two strings `s` and `t`, return `true` if `t` is an anagram of `s`, and `false` otherwise.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: s = "anagram", t = "nagaram"

Output: true

Example 2:

Input: s = "rat", t = "car"

Output: false

Constraints:

- $1 \leq s.length, t.length \leq 5 * 10^4$
- s and t consist of lowercase English letters.

257. Binary Tree Paths


Easy

4900212 Add to List Share

Given the `root` of a binary tree, return *all root-to-leaf paths in any order*.

A **leaf** is a node with no children.

Example 1:



Input: root = [1,2,3,null,5]

Output: ["1->2->5","1->3"]

Example 2:

Input: root = [1]

Output: ["1"]

Constraints:

- The number of nodes in the tree is in the range [1, 100].
- $-100 \leq \text{Node.val} \leq 100$

258. Add Digits

Easy

27741699Add to ListShare

Given an integer `num`, repeatedly add all its digits until the result has only one digit, and return it.

Example 1:

Input: num = 38

Output: 2

Explanation: The process is

```
38 --> 3 + 8 --> 11
```

```
11 --> 1 + 1 --> 2
```

Since 2 has only one digit, return it.

Example 2:

Input: num = 0

Output: 0

Constraints:

- $0 \leq \text{num} \leq 2^{31} - 1$

260. Single Number III

Medium

4327198Add to ListShare

Given an integer array `nums`, in which exactly two elements appear only once and all the other elements appear exactly twice. Find the two elements that appear only once. You can return the answer in **any order**.

You must write an algorithm that runs in linear runtime complexity and uses only constant extra space.

Example 1:

Input: nums = [1,2,1,3,2,5]

Output: [3,5]

Explanation: [5, 3] is also a valid answer.

Example 2:

Input: nums = [-1,0]

Output: [-1,0]

Example 3:

Input: nums = [0,1]

Output: [1,0]

Constraints:

- $2 \leq \text{nums.length} \leq 3 * 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- Each integer in `nums` will appear twice, only two integers will appear once.

262. Trips and Users

Hard

874520Add to ListShare

SQL Schema

Table: `Trips`

Column Name	Type
<code>id</code>	<code>int</code>
<code>client_id</code>	<code>int</code>
<code>driver_id</code>	<code>int</code>
<code>city_id</code>	<code>int</code>
<code>status</code>	<code>enum</code>
<code>request_at</code>	<code>date</code>

`id` is the primary key for this table.

The table holds all taxi trips. Each trip has a unique `id`, while `client_id` and `driver_id` are foreign keys to the `users_id` at the `Users` table.

`Status` is an ENUM type of ('completed', 'cancelled_by_driver', 'cancelled_by_client').

Table: `Users`

Column Name	Type
users_id	int
banned	enum
role	enum

users_id is the primary key for this table.

The table holds all users. Each user has a unique users_id, and role is an ENUM type of ('client', 'driver', 'partner').

banned is an ENUM type of ('Yes', 'No').

The **cancellation rate** is computed by dividing the number of canceled (by client or driver) requests with unbanned users by the total number of requests with unbanned users on that day.

Write a SQL query to find the **cancellation rate** of requests with unbanned users (**both client and driver must not be banned**) each day between "2013-10-01" and "2013-10-03".

Round Cancellation Rate to **two decimal** points.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Trips table:

id	client_id	driver_id	city_id	status	request_at
1	1	10	1	completed	2013-10-01
2	2	11	1	cancelled_by_driver	2013-10-01

3	3	12	6	completed	2013-10-01
4	4	13	6	cancelled_by_client	2013-10-01
5	1	10	1	completed	2013-10-02
6	2	11	6	completed	2013-10-02
7	3	12	6	completed	2013-10-02
8	2	12	12	completed	2013-10-03
9	3	10	12	completed	2013-10-03
10	4	13	12	cancelled_by_driver	2013-10-03

Users table:

users_id	banned	role
1	No	client
2	Yes	client
3	No	client
4	No	client
10	No	driver
11	No	driver
12	No	driver
13	No	driver

Output:

Day	Cancellation Rate
2013-10-01	0.33

2013-10-02	0.00	
2013-10-03	0.50	
-----+-----+-----+		

Explanation:

On 2013-10-01:

- There were 4 requests in total, 2 of which were canceled.
- However, the request with Id=2 was made by a banned client (User_Id=2), so it is ignored in the calculation.
- Hence there are 3 unbanned requests in total, 1 of which was canceled.
- The Cancellation Rate is $(1 / 3) = 0.33$

On 2013-10-02:

- There were 3 requests in total, 0 of which were canceled.
- The request with Id=6 was made by a banned client, so it is ignored.
- Hence there are 2 unbanned requests in total, 0 of which were canceled.
- The Cancellation Rate is $(0 / 2) = 0.00$

On 2013-10-03:

- There were 3 requests in total, 1 of which was canceled.
- The request with Id=8 was made by a banned client, so it is ignored.
- Hence there are 2 unbanned requests in total, 1 of which were canceled.
- The Cancellation Rate is $(1 / 2) = 0.50$

263. Ugly Number

Easy

17071126Add to ListShare

An **ugly number** is a positive integer whose prime factors are limited to 2, 3, and 5.

Given an integer `n`, return `true` if `n` is an **ugly number**.

Example 1:

Input: `n = 6`

Output: true

Explanation: $6 = 2 \times 3$

Example 2:

Input: $n = 1$

Output: true

Explanation: 1 has no prime factors, therefore all of its prime factors are limited to 2, 3, and 5.

Example 3:

Input: $n = 14$

Output: false

Explanation: 14 is not ugly since it includes the prime factor 7.

Constraints:

- $-2^{31} \leq n \leq 2^{31} - 1$

264. Ugly Number II

Medium

4649237Add to ListShare

An **ugly number** is a positive integer whose prime factors are limited to 2, 3, and 5.

Given an integer n , return *the n^{th} ugly number*.

Example 1:

Input: $n = 10$

Output: 12

Explanation: [1, 2, 3, 4, 5, 6, 8, 9, 10, 12] is the sequence of the first 10 ugly numbers.

Example 2:

Input: $n = 1$

Output: 1

Explanation: 1 has no prime factors, therefore all of its prime factors are limited to 2, 3, and 5.

Constraints:

- $1 \leq n \leq 1690$

268. Missing Number

Easy

74602977Add to ListShare

Given an array `nums` containing `n` distinct numbers in the range $[0, n]$, return *the only number in the range that is missing from the array*.

Example 1:

Input: `nums = [3,0,1]`

Output: 2

Explanation: $n = 3$ since there are 3 numbers, so all numbers are in the range $[0,3]$. 2 is the missing number in the range since it does not appear in `nums`.

Example 2:

Input: `nums = [0,1]`

Output: 2

Explanation: $n = 2$ since there are 2 numbers, so all numbers are in the range $[0,2]$. 2 is the missing number in the range since it does not appear in `nums`.

Example 3:

Input: `nums = [9,6,4,2,3,5,7,0,1]`

Output: 8

Explanation: $n = 9$ since there are 9 numbers, so all numbers are in the range $[0,9]$. 8 is the missing number in the range since it does not appear in `nums`.

Constraints:

- $n == \text{nums.length}$
- $1 \leq n \leq 10^4$

- $0 \leq \text{nums}[i] \leq n$
- All the numbers of `nums` are **unique**.

273. Integer to English Words

Hard

23675488Add to ListShare

Convert a non-negative integer `num` to its English words representation.

Example 1:

Input: `num = 123`

Output: "One Hundred Twenty Three"

Example 2:

Input: `num = 12345`

Output: "Twelve Thousand Three Hundred Forty Five"

Example 3:

Input: `num = 1234567`

Output: "One Million Two Hundred Thirty Four Thousand Five Hundred Sixty Seven"

Constraints:

- $0 \leq \text{num} \leq 2^{31} - 1$

274. H-Index

Medium

13581976Add to ListShare

Given an array of integers `citations` where `citations[i]` is the number of citations a researcher received for their i^{th} paper, return compute the researcher's **h-index**.

According to the [definition of h-index on Wikipedia](#): A scientist has an index `h` if `h` of their `n` papers have at least `h` citations each, and the other `n - h` papers have no more than `h` citations each.

If there are several possible values for `h`, the maximum one is taken as the **h-index**.

Example 1:

Input: citations = [3,0,6,1,5]

Output: 3

Explanation: [3,0,6,1,5] means the researcher has 5 papers in total and each of them had received 3, 0, 6, 1, 5 citations respectively.

Since the researcher has 3 papers with at least 3 citations each and the remaining two with no more than 3 citations each, their h-index is 3.

Example 2:

Input: citations = [1,3,1]

Output: 1

Constraints:

- `n == citations.length`
- `1 <= n <= 5000`
- `0 <= citations[i] <= 1000`

275. H-Index II

Medium

7951159Add to ListShare

Given an array of integers `citations` where `citations[i]` is the number of citations a researcher received for their i^{th} paper and `citations` is sorted in an **ascending order**, return compute the researcher's **h-index**.

According to the [definition of h-index on Wikipedia](#): A scientist has an index `h` if `h` of their `n` papers have at least `h` citations each, and the other `n - h` papers have no more than `h` citations each.

If there are several possible values for `h`, the maximum one is taken as the **h-index**.

You must write an algorithm that runs in logarithmic time.

Example 1:

Input: citations = [0,1,3,5,6]

Output: 3

Explanation: `[0,1,3,5,6]` means the researcher has 5 papers in total and each of them had received 0, 1, 3, 5, 6 citations respectively.

Since the researcher has 3 papers with at least 3 citations each and the remaining two with no more than 3 citations each, their h-index is 3.

Example 2:

Input: `citations = [1,2,100]`

Output: 2

Constraints:

- `n == citations.length`
- `1 <= n <= 105`
- `0 <= citations[i] <= 1000`
- `citations` is sorted in **ascending order**.

278. First Bad Version

Easy

61132306Add to ListShare

You are a product manager and currently leading a team to develop a new product. Unfortunately, the latest version of your product fails the quality check. Since each version is developed based on the previous version, all the versions after a bad version are also bad.

Suppose you have `n` versions `[1, 2, ..., n]` and you want to find out the first bad one, which causes all the following ones to be bad.

You are given an API `bool isBadVersion(version)` which returns whether `version` is bad. Implement a function to find the first bad version. You should minimize the number of calls to the API.

Example 1:

Input: `n = 5, bad = 4`

Output: 4

Explanation:

`call isBadVersion(3) -> false`

```
call isBadVersion(5) -> true
```

```
call isBadVersion(4) -> true
```

Then 4 is the first bad version.

Example 2:

Input: n = 1, bad = 1

Output: 1

Constraints:

- $1 \leq \text{bad} \leq \text{n} \leq 2^{31} - 1$

279. Perfect Squares

Medium

7515320Add to ListShare

Given an integer n , return *the least number of perfect square numbers that sum to n* .

A **perfect square** is an integer that is the square of an integer; in other words, it is the product of some integer with itself. For example, 1, 4, 9, and 16 are perfect squares while 3 and 11 are not.

Example 1:

Input: n = 12

Output: 3

Explanation: $12 = 4 + 4 + 4$.

Example 2:

Input: n = 13

Output: 2

Explanation: $13 = 4 + 9$.

Constraints:

- $1 \leq n \leq 10^4$

282. Expression Add Operators

Hard

2696483Add to ListShare

Given a string `num` that contains only digits and an integer `target`, return ***all possibilities*** to insert the binary operators `'+'`, `'-'`, and/or `'*'` between the digits of `num` so that the resultant expression evaluates to the `target` value.

Note that operands in the returned expressions **should not** contain leading zeros.

Example 1:

Input: `num = "123", target = 6`

Output: `["1*2*3", "1+2+3"]`

Explanation: Both `"1*2*3"` and `"1+2+3"` evaluate to 6.

Example 2:

Input: `num = "232", target = 8`

Output: `["2*3+2", "2+3*2"]`

Explanation: Both `"2*3+2"` and `"2+3*2"` evaluate to 8.

Example 3:

Input: `num = "3456237490", target = 9191`

Output: `[]`

Explanation: There are no expressions that can be created from `"3456237490"` to evaluate to 9191.

Constraints:

- `1 <= num.length <= 10`
- `num` consists of only digits.
- `-231 <= target <= 231 - 1`

283. Move Zeroes

Easy

11154274Add to ListShare

Given an integer array `nums`, move all `0`'s to the end of it while maintaining the relative order of the non-zero elements.

Note that you must do this in-place without making a copy of the array.

Example 1:

Input: `nums = [0,1,0,3,12]`

Output: `[1,3,12,0,0]`

Example 2:

Input: `nums = [0]`

Output: `[0]`

Constraints:

- `1 <= nums.length <= 104`
- `-231 <= nums[i] <= 231 - 1`

284. Peeking Iterator

Medium

1635963Add to ListShare

Design an iterator that supports the `peek` operation on an existing iterator in addition to the `hasNext` and the `next` operations.

Implement the `PeekingIterator` class:

- `PeekingIterator(Iterator<int> nums)` Initializes the object with the given integer iterator `iterator`.
- `int next()` Returns the next element in the array and moves the pointer to the next element.
- `boolean hasNext()` Returns `true` if there are still elements in the array.
- `int peek()` Returns the next element in the array **without** moving the pointer.

Note: Each language may have a different implementation of the constructor and `Iterator`, but they all support the `int next()` and `boolean hasNext()` functions.

Example 1:**Input**

```
["PeekingIterator", "next", "peek", "next", "next", "hasNext"]
```

```
[[[1, 2, 3]], [], [], [], [], []]
```

Output

```
[null, 1, 2, 2, 3, false]
```

Explanation

```
PeekingIterator peekingIterator = new PeekingIterator([1, 2, 3]); // [1,2,3]
peekingIterator.next(); // return 1, the pointer moves to the next element [1,2,3].
peekingIterator.peek(); // return 2, the pointer does not move [1,2,3].
peekingIterator.next(); // return 2, the pointer moves to the next element [1,2,3]
peekingIterator.next(); // return 3, the pointer moves to the next element [1,2,3]
peekingIterator.hasNext(); // return False
```

Constraints:

- $1 \leq \text{nums.length} \leq 1000$
- $1 \leq \text{nums}[i] \leq 1000$
- All the calls to `next` and `peek` are valid.
- At most 1000 calls will be made to `next`, `hasNext`, and `peek`.

287. Find the Duplicate Number**Medium**

165072182 Add to List Share

Given an array of integers `nums` containing $n + 1$ integers where each integer is in the range $[1, n]$ inclusive.

There is only **one repeated number** in `nums`, return *this repeated number*.

You must solve the problem **without** modifying the array `nums` and uses only constant extra space.

Example 1:

Input: nums = [1,3,4,2,2]

Output: 2

Example 2:

Input: nums = [3,1,3,4,2]

Output: 3

Constraints:

- $1 \leq n \leq 10^5$
- `nums.length == n + 1`
- $1 \leq \text{nums}[i] \leq n$
- All the integers in `nums` appear only **once** except for **precisely one integer** which appears **two or more** times.

289. Game of Life

Medium


5191460Add to ListShare

According to [Wikipedia's article](#): "The **Game of Life**, also known simply as **Life**, is a cellular automaton devised by the British mathematician John Horton Conway in 1970."

The board is made up of an `m x n` grid of cells, where each cell has an initial state: **live** (represented by a 1) or **dead** (represented by a 0). Each cell interacts with its eight neighbors (horizontal, vertical, diagonal) using the following four rules (taken from the above Wikipedia article):


1. Any live cell with fewer than two live neighbors dies as if caused by under-population.
2. Any live cell with two or three live neighbors lives on to the next generation.
3. Any live cell with more than three live neighbors dies, as if by over-population.
4. Any dead cell with exactly three live neighbors becomes a live cell, as if by reproduction.

The next state is created by applying the above rules simultaneously to every cell in the current state, where births and deaths occur simultaneously. Given the current state of the `m x n` grid `board`, return *the next state*.

Example 1:

Input: board = [[0,1,0],[0,0,1],[1,1,1],[0,0,0]]

Output: [[0,0,0],[1,0,1],[0,1,1],[0,1,0]]

Example 2:

Input: board = [[1,1],[1,0]]

Output: [[1,1],[1,1]]

Constraints:

- $m == \text{board.length}$
- $n == \text{board}[i].length$
- $1 \leq m, n \leq 25$
- $\text{board}[i][j]$ is 0 or 1.

290. Word Pattern

Easy

4044462Add to ListShare

Given a `pattern` and a string `s`, find if `s` follows the same pattern.

Here **follow** means a full match, such that there is a bijection between a letter in `pattern` and a **non-empty** word in `s`.

Example 1:

Input: `pattern = "abba"`, `s = "dog cat cat dog"`

Output: `true`

Example 2:

Input: `pattern = "abba"`, `s = "dog cat cat fish"`

Output: `false`

Example 3:

Input: `pattern = "aaaa"`, `s = "dog cat cat dog"`

Output: `false`

Constraints:

- `1 <= pattern.length <= 300`
- `pattern` contains only lower-case English letters.
- `1 <= s.length <= 3000`
- `s` contains only lowercase English letters and spaces ' '.
- `s` **does not contain** any leading or trailing spaces.
- All the words in `s` are separated by a **single space**.

292. Nim Game

Easy

12052363Add to ListShare

You are playing the following Nim Game with your friend:

- Initially, there is a heap of stones on the table.

- You and your friend will alternate taking turns, and **you go first**.
- On each turn, the person whose turn it is will remove 1 to 3 stones from the heap.
- The one who removes the last stone is the winner.

Given `n`, the number of stones in the heap, return `true` if you can win the game assuming both you and your friend play optimally, otherwise return `false`.

Example 1:

Input: `n = 4`

Output: `false`

Explanation: These are the possible outcomes:

1. You remove 1 stone. Your friend removes 3 stones, including the last stone. Your friend wins.
2. You remove 2 stones. Your friend removes 2 stones, including the last stone. Your friend wins.
3. You remove 3 stones. Your friend removes the last stone. Your friend wins.

In all outcomes, your friend wins.

Example 2:

Input: `n = 1`

Output: `true`

Example 3:

Input: `n = 2`

Output: `true`

Constraints:

- `1 <= n <= 231 - 1`

295. Find Median from Data Stream

Hard

8285150Add to ListShare

The **median** is the middle value in an ordered integer list. If the size of the list is even, there is no middle value and the median is the mean of the two middle values.

- For example, for `arr = [2, 3, 4]`, the median is 3.
- For example, for `arr = [2, 3]`, the median is $(2 + 3) / 2 = 2.5$.

Implement the `MedianFinder` class:

- `MedianFinder()` initializes the `MedianFinder` object.
- `void addNum(int num)` adds the integer `num` from the data stream to the data structure.
- `double findMedian()` returns the median of all elements so far. Answers within 10^{-5} of the actual answer will be accepted.

Example 1:

Input

```
["MedianFinder", "addNum", "addNum", "findMedian", "addNum", "findMedian"]
[[], [1], [2], [], [3], []]
```

Output

```
[null, null, null, 1.5, null, 2.0]
```

Explanation

```
MedianFinder medianFinder = new MedianFinder();

medianFinder.addNum(1);      // arr = [1]
medianFinder.addNum(2);      // arr = [1, 2]
medianFinder.findMedian();  // return 1.5 (i.e., (1 + 2) / 2)
medianFinder.addNum(3);      // arr[1, 2, 3]
medianFinder.findMedian();  // return 2.0
```

Constraints:

- $-10^5 \leq \text{num} \leq 10^5$
- There will be at least one element in the data structure before calling `findMedian`.
- At most $5 * 10^4$ calls will be made to `addNum` and `findMedian`.

297. Serialize and Deserialize Binary Tree

Hard


7766286Add to ListShare

Serialization is the process of converting a data structure or object into a sequence of bits so that it can be stored in a file or memory buffer, or transmitted across a network connection link to be reconstructed later in the same or another computer environment.

Design an algorithm to serialize and deserialize a binary tree. There is no restriction on how your serialization/deserialization algorithm should work. You just need to ensure that a binary tree can be serialized to a string and this string can be deserialized to the original tree structure.

Clarification: The input/output format is the same as [how LeetCode serializes a binary tree](#). You do not necessarily need to follow this format, so please be creative and come up with different approaches yourself.

Example 1:



Input: root = [1,2,3,null,null,4,5]

Output: [1,2,3,null,null,4,5]

Example 2:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range `[0, 104]`.
- `-1000 <= Node.val <= 1000`

299. Bulls and Cows

Medium

16891501Add to ListShare

You are playing the **Bulls and Cows** game with your friend.

You write down a secret number and ask your friend to guess what the number is. When your friend makes a guess, you provide a hint with the following info:

- The number of "bulls", which are digits in the guess that are in the correct position.
- The number of "cows", which are digits in the guess that are in your secret number but are located in the wrong position. Specifically, the non-bull digits in the guess that could be rearranged such that they become bulls.

Given the secret number `secret` and your friend's guess `guess`, return *the hint for your friend's guess*.

The hint should be formatted as "`xAyB`", where `x` is the number of bulls and `y` is the number of cows. Note that both `secret` and `guess` may contain duplicate digits.

Example 1:

Input: `secret = "1807", guess = "7810"`

Output: `"1A3B"`

Explanation: Bulls are connected with a '`|`' and cows are underlined:

`"1807"`

`|`

`"7810"`

Example 2:

Input: `secret = "1123", guess = "0111"`

Output: `"1A1B"`

Explanation: Bulls are connected with a '`|`' and cows are underlined:

```
"1123"      "1123"
|       or    |
"0111"      "0111"
```

Note that only one of the two unmatched 1s is counted as a cow since the non-bull digits can only be rearranged to allow one 1 to be a bull.

Constraints:

- `1 <= secret.length, guess.length <= 1000`
- `secret.length == guess.length`
- `secret` and `guess` consist of digits only.

300. Longest Increasing Subsequence

Medium

15110269 Add to List Share

Given an integer array `nums`, return the length of the longest strictly increasing subsequence.

A **subsequence** is a sequence that can be derived from an array by deleting some or no elements without changing the order of the remaining elements. For example, `[3, 6, 2, 7]` is a subsequence of the array `[0, 3, 1, 6, 2, 2, 7]`.

Example 1:

Input: `nums = [10,9,2,5,3,7,101,18]`

Output: 4

Explanation: The longest increasing subsequence is `[2,3,7,101]`, therefore the length is 4.

Example 2:

Input: `nums = [0,1,0,3,2,3]`

Output: 4

Example 3:

Input: `nums = [7,7,7,7,7,7,7]`

Output: 1

Constraints:

- $1 \leq \text{nums.length} \leq 2500$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

301. Remove Invalid Parentheses**Hard**

5092251Add to ListShare

Given a string s that contains parentheses and letters, remove the minimum number of invalid parentheses to make the input string valid.

Return *all the possible results*. You may return the answer in **any order**.

Example 1:**Input:** $s = "())()()$ **Output:** $["((())()", "())()"]$ **Example 2:****Input:** $s = "(a)())()$ **Output:** $["(a())()", "(a)()()"]$ **Example 3:****Input:** $s = ")("$ **Output:** $[""]$ **Constraints:**

- $1 \leq s.length \leq 25$
- s consists of lowercase English letters and parentheses ' $($ ' and ' $)$ '.
- There will be at most 20 parentheses in s .

303. Range Sum Query - Immutable**Easy**

23371711Add to ListShare

Given an integer array nums , handle multiple queries of the following type:

1. Calculate the **sum** of the elements of `nums` between indices `left` and `right` **inclusive** where `left <= right`.

Implement the `NumArray` class:

- `NumArray(int[] nums)` Initializes the object with the integer array `nums`.
- `int sumRange(int left, int right)` Returns the **sum** of the elements of `nums` between indices `left` and `right` **inclusive** (i.e. `nums[left] + nums[left + 1] + ... + nums[right]`).

Example 1:

Input

```
["NumArray", "sumRange", "sumRange", "sumRange"]
[[[-2, 0, 3, -5, 2, -1]], [0, 2], [2, 5], [0, 5]]
```

Output

```
[null, 1, -1, -3]
```

Explanation

```
NumArray numArray = new NumArray([-2, 0, 3, -5, 2, -1]);
numArray.sumRange(0, 2); // return (-2) + 0 + 3 = 1
numArray.sumRange(2, 5); // return 3 + (-5) + 2 + (-1) = -1
numArray.sumRange(0, 5); // return (-2) + 0 + 3 + (-5) + 2 + (-1) = -3
```

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^5 \leq \text{nums}[i] \leq 10^5$
- $0 \leq \text{left} \leq \text{right} < \text{nums.length}$
- At most 10^4 calls will be made to `sumRange`.

304. Range Sum Query 2D - Immutable

Medium

3993311Add to ListShare

Given a 2D matrix `matrix`, handle multiple queries of the following type:

- Calculate the **sum** of the elements of `matrix` inside the rectangle defined by its **upper left corner** `(row1, col1)` and **lower right corner** `(row2, col2)`.

Implement the `NumMatrix` class:

- `NumMatrix(int[][] matrix)` Initializes the object with the integer matrix `matrix`.
- `int sumRegion(int row1, int col1, int row2, int col2)` Returns the **sum** of the elements of `matrix` inside the rectangle defined by its **upper left corner** `(row1, col1)` and **lower right corner** `(row2, col2)`.

You must design an algorithm where `sumRegion` works on $O(1)$ time complexity.

Example 1:

3	0	1	4	2
5	6	3	2	1
1	2	0	1	5
4	1	0	1	7
1	0	3	0	5

Input

```
["NumMatrix", "sumRegion", "sumRegion", "sumRegion"]
[[[[3, 0, 1, 4, 2], [5, 6, 3, 2, 1], [1, 2, 0, 1, 5], [4, 1, 0, 1, 7], [1, 0, 3, 0, 5]], [2, 1, 4, 3], [1, 1, 2, 2], [1, 2, 2, 4]]]
```

Output

```
[null, 8, 11, 12]
```

Explanation

```
NumMatrix numMatrix = new NumMatrix([[3, 0, 1, 4, 2], [5, 6, 3, 2, 1], [1, 2, 0, 1, 5], [4, 1, 0, 1, 7], [1, 0, 3, 0, 5]]);

numMatrix.sumRegion(2, 1, 4, 3); // return 8 (i.e sum of the red rectangle)

numMatrix.sumRegion(1, 1, 2, 2); // return 11 (i.e sum of the green rectangle)

numMatrix.sumRegion(1, 2, 2, 4); // return 12 (i.e sum of the blue rectangle)
```

Constraints:

- $m == \text{matrix.length}$
- $n == \text{matrix}[i].length$
- $1 \leq m, n \leq 200$
- $-10^4 \leq \text{matrix}[i][j] \leq 10^4$
- $0 \leq \text{row1} \leq \text{row2} < m$
- $0 \leq \text{col1} \leq \text{col2} < n$
- At most 10^4 calls will be made to `sumRegion`.

306. Additive Number

Medium

843682Add to ListShare

An **additive number** is a string whose digits can form an **additive sequence**.

A valid **additive sequence** should contain **at least** three numbers. Except for the first two numbers, each subsequent number in the sequence must be the sum of the preceding two.

Given a string containing only digits, return `true` if it is an **additive number** or `false` otherwise.

Note: Numbers in the additive sequence **cannot** have leading zeros, so sequence `1, 2, 03` or `1, 02, 3` is invalid.

Example 1:

Input: "112358"

Output: true

Explanation:

The digits can form an additive sequence: 1, 1, 2, 3, 5, 8.

$1 + 1 = 2$, $1 + 2 = 3$, $2 + 3 = 5$, $3 + 5 = 8$

Example 2:

Input: "199100199"

Output: true

Explanation:

The additive sequence is: 1, 99, 100, 199.

$1 + 99 = 100$, $99 + 100 = 199$

Constraints:

- $1 \leq \text{num.length} \leq 35$
- num consists only of digits.

307. Range Sum Query - Mutable

Medium

4051223Add to ListShare

Given an integer array `nums`, handle multiple queries of the following types:

1. **Update** the value of an element in `nums`.
2. Calculate the **sum** of the elements of `nums` between indices `left` and `right` **inclusive** where `left \leq right`.

Implement the `NumArray` class:

- `NumArray(int[] nums)` Initializes the object with the integer array `nums`.
- `void update(int index, int val)` **Updates** the value of `nums[index]` to be `val`.
- `int sumRange(int left, int right)` Returns the **sum** of the elements of `nums` between indices `left` and `right` **inclusive** (i.e. `nums[left] + nums[left + 1] + ... + nums[right]`).

Example 1:

Input

```
[ "NumArray", "sumRange", "update", "sumRange" ]
[[[1, 3, 5]], [0, 2], [1, 2], [0, 2]]
```

Output

```
[null, 9, null, 8]
```

Explanation

```
NumArray numArray = new NumArray([1, 3, 5]);
numArray.sumRange(0, 2); // return 1 + 3 + 5 = 9
numArray.update(1, 2); // nums = [1, 2, 5]
numArray.sumRange(0, 2); // return 1 + 2 + 5 = 8
```

Constraints:

- $1 \leq \text{nums.length} \leq 3 * 10^4$
- $-100 \leq \text{nums}[i] \leq 100$
- $0 \leq \text{index} < \text{nums.length}$
- $-100 \leq \text{val} \leq 100$
- $0 \leq \text{left} \leq \text{right} < \text{nums.length}$
- At most $3 * 10^4$ calls will be made to `update` and `sumRange`.

309. Best Time to Buy and Sell Stock with Cooldown

Medium

6672230Add to ListShare

You are given an array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

Find the maximum profit you can achieve. You may complete as many transactions as you like (i.e., buy one and sell one share of the stock multiple times) with the following restrictions:

- After you sell your stock, you cannot buy stock on the next day (i.e., cooldown one day).

Note: You may not engage in multiple transactions simultaneously (i.e., you must sell the stock before you buy again).

Example 1:

Input: `prices = [1,2,3,0,2]`

Output: 3

Explanation: transactions = [buy, sell, cooldown, buy, sell]

Example 2:

Input: prices = [1]

Output: 0

Constraints:

- $1 \leq \text{prices.length} \leq 5000$
- $0 \leq \text{prices}[i] \leq 1000$

310. Minimum Height Trees

Medium

6003256Add to ListShare


A tree is an undirected graph in which any two vertices are connected by *exactly* one path. In other words, any connected graph without simple cycles is a tree.

Given a tree of n nodes labelled from 0 to $n - 1$, and an array of $n - 1$ edges where $\text{edges}[i] = [a_i, b_i]$ indicates that there is an undirected edge between the two nodes a_i and b_i in the tree, you can choose any node of the tree as the root. When you select a node x as the root, the result tree has height h . Among all possible rooted trees, those with minimum height (i.e. $\min(h)$) are called **minimum height trees** (MHTs).

Return a list of all MHTs' root labels. You can return the answer in **any order**.

The **height** of a rooted tree is the number of edges on the longest downward path between the root and a leaf.

Example 1:




Input: $n = 4$, $\text{edges} = [[1,0],[1,2],[1,3]]$

Output: [1]

Explanation: As shown, the height of the tree is 1 when the root is the node with label 1 which is the only MHT.

Example 2:



Input: $n = 6$, $\text{edges} = [[3,0],[3,1],[3,2],[3,4],[5,4]]$

Output: [3,4]

Constraints:

- $1 \leq n \leq 2 * 10^4$
- $\text{edges.length} == n - 1$
- $0 \leq a_i, b_i < n$
- $a_i \neq b_i$
- All the pairs (a_i, b_i) are distinct.
- The given input is **guaranteed** to be a tree and there will be **no repeated** edges.

312. Burst Balloons

Hard

6854177 Add to List Share

You are given n balloons, indexed from 0 to $n - 1$. Each balloon is painted with a number on it represented by an array nums . You are asked to burst all the balloons.

If you burst the i^{th} balloon, you will get $\text{nums}[i - 1] * \text{nums}[i] * \text{nums}[i + 1]$ coins. If $i - 1$ or $i + 1$ goes out of bounds of the array, then treat it as if there is a balloon with a 1 painted on it.

Return *the maximum coins you can collect by bursting the balloons wisely.*

Example 1:**Input:** nums = [3,1,5,8]**Output:** 167**Explanation:**

nums = [3,1,5,8] --> [3,5,8] --> [3,8] --> [8] --> []

coins = 3*1*5 + 3*5*8 + 1*3*8 + 1*8*1 = 167

Example 2:**Input:** nums = [1,5]**Output:** 10**Constraints:**

- n == nums.length
- 1 <= n <= 300
- 0 <= nums[i] <= 100

313. Super Ugly Number**Medium**

1710315Add to ListShare

A **super ugly number** is a positive integer whose prime factors are in the array `primes`.Given an integer `n` and an array of integers `primes`, return *the nth super ugly number*.The `nth` **super ugly number** is **guaranteed** to fit in a **32-bit** signed integer.**Example 1:****Input:** n = 12, primes = [2,7,13,19]**Output:** 32**Explanation:** [1,2,4,7,8,13,14,16,19,26,28,32] is the sequence of the first 12 super ugly numbers given `primes = [2,7,13,19]`.**Example 2:**

Input: n = 1, primes = [2,3,5]

Output: 1

Explanation: 1 has no prime factors, therefore all of its prime factors are in the array primes = [2,3,5].

Constraints:

- $1 \leq n \leq 10^5$
- $1 \leq \text{primes.length} \leq 100$
- $2 \leq \text{primes}[i] \leq 1000$
- `primes[i]` is **guaranteed** to be a prime number.
- All the values of `primes` are **unique** and sorted in **ascending order**.

315. Count of Smaller Numbers After Self

Hard

7513203Add to ListShare

Given an integer array `nums`, return an integer array `counts` where `counts[i]` is the number of smaller elements to the right of `nums[i]`.

Example 1:

Input: nums = [5,2,6,1]

Output: [2,1,1,0]

Explanation:

To the right of 5 there are 2 smaller elements (2 and 1).

To the right of 2 there is only 1 smaller element (1).

To the right of 6 there is 1 smaller element (1).

To the right of 1 there is 0 smaller element.

Example 2:

Input: nums = [-1]

Output: [0]

Example 3:

Input: nums = [-1,-1]

Output: [0,0]

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums[i]} \leq 10^4$

316. Remove Duplicate Letters

Medium

6014385Add to ListShare

Given a string s , remove duplicate letters so that every letter appears once and only once. You must make sure your result is **the smallest in lexicographical order** among all possible results.

Example 1:

Input: $s = \text{"bcabc"}$

Output: "abc"

Example 2:

Input: $s = \text{"cbacdcbc"}$

Output: "acdb"

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of lowercase English letters.

318. Maximum Product of Word Lengths

Medium

3031121Add to ListShare

Given a string array words , return the maximum value of $\text{length}(\text{word}[i]) * \text{length}(\text{word}[j])$ where the two words do not share common letters. If no such two words exist, return 0.

Example 1:

Input: words = ["abcw", "baz", "foo", "bar", "xtfn", "abcdef"]

Output: 16

Explanation: The two words can be "abcw", "xtfn".

Example 2:

Input: words = ["a", "ab", "abc", "d", "cd", "bcd", "abcd"]

Output: 4

Explanation: The two words can be "ab", "cd".

Example 3:

Input: words = ["a", "aa", "aaa", "aaaa"]

Output: 0

Explanation: No such pair of words.

Constraints:

- $2 \leq \text{words.length} \leq 1000$
- $1 \leq \text{words}[i].length \leq 1000$
- $\text{words}[i]$ consists only of lowercase English letters.

319. Bulb Switcher

Medium

10581775Add to ListShare

There are n bulbs that are initially off. You first turn on all the bulbs, then you turn off every second bulb.

On the third round, you toggle every third bulb (turning on if it's off or turning off if it's on). For the i^{th} round, you toggle every i bulb. For the n^{th} round, you only toggle the last bulb.

Return *the number of bulbs that are on after n rounds*.

Example 1:



Round 1



Round 2



Round 3



Input: $n = 3$

Output: 1

Explanation: At first, the three bulbs are [off, off, off].

After the first round, the three bulbs are [on, on, on].

After the second round, the three bulbs are [on, off, on].

After the third round, the three bulbs are [on, off, off].

So you should return 1 because there is only one bulb is on.

Example 2:

Input: $n = 0$

Output: 0

Example 3:

Input: $n = 1$

Output: 1

Constraints:

- $0 \leq n \leq 10^9$

321. Create Maximum Number

Hard

1507323Add to ListShare

You are given two integer arrays `nums1` and `nums2` of lengths `m` and `n` respectively. `nums1` and `nums2` represent the digits of two numbers. You are also given an integer `k`.

Create the maximum number of length `k` $\leq m + n$ from digits of the two numbers. The relative order of the digits from the same array must be preserved.

Return an array of the `k` digits representing the answer.

Example 1:

Input: `nums1 = [3,4,6,5]`, `nums2 = [9,1,2,5,8,3]`, `k = 5`

Output: `[9,8,6,5,3]`

Example 2:

Input: `nums1 = [6,7]`, `nums2 = [6,0,4]`, `k = 5`

Output: `[6,7,6,0,4]`

Example 3:

Input: `nums1 = [3,9]`, `nums2 = [8,9]`, `k = 3`

Output: `[9,8,9]`

Constraints:

- `m == nums1.length`
- `n == nums2.length`
- `1 \leq m, n \leq 500`
- `0 \leq nums1[i], nums2[i] \leq 9`
- `1 \leq k \leq m + n`

322. Coin Change

Medium

13967314Add to ListShare

You are given an integer array `coins` representing coins of different denominations and an integer `amount` representing a total amount of money.

Return *the fewest number of coins that you need to make up that amount*. If that amount of money cannot be made up by any combination of the coins, return `-1`.

You may assume that you have an infinite number of each kind of coin.

Example 1:

Input: `coins = [1,2,5]`, `amount = 11`

Output: `3`

Explanation: $11 = 5 + 5 + 1$

Example 2:

Input: `coins = [2]`, `amount = 3`

Output: `-1`

Example 3:

Input: `coins = [1]`, `amount = 0`

Output: `0`

Constraints:

- $1 \leq \text{coins.length} \leq 12$
- $1 \leq \text{coins}[i] \leq 2^{31} - 1$
- $0 \leq \text{amount} \leq 10^4$

324. Wiggle Sort II

Medium

2392850Add to ListShare

Given an integer array `nums`, reorder it such that `nums[0] < nums[1] > nums[2] < nums[3] ...`

You may assume the input array always has a valid answer.

Example 1:

Input: `nums = [1,5,1,1,6,4]`

Output: `[1,6,1,5,1,4]`

Explanation: `[1,4,1,5,1,6]` is also accepted.

Example 2:

Input: `nums = [1,3,2,2,3,1]`

Output: `[2,3,1,3,1,2]`

Constraints:

- $1 \leq \text{nums.length} \leq 5 * 10^4$
- $0 \leq \text{nums}[i] \leq 5000$
- It is guaranteed that there will be an answer for the given input `nums`.

326. Power of Three

Easy

2089198Add to ListShare

Given an integer `n`, return `true` if it is a power of three. Otherwise, return `false`.

An integer `n` is a power of three, if there exists an integer `x` such that `n == 3x`.

Example 1:

Input: `n = 27`

Output: `true`

Explanation: $27 = 3^3$

Example 2:

Input: `n = 0`

Output: `false`

Explanation: There is no x where $3^x = 0$.

Example 3:

Input: `n = -1`

Output: `false`

Explanation: There is no x where $3^x = (-1)$.

Constraints:

- $-2^{31} \leq n \leq 2^{31} - 1$

327. Count of Range Sum**Hard**

1790191Add to ListShare

Given an integer array `nums` and two integers `lower` and `upper`, return *the number of range sums that lie in $[lower, upper]$ inclusive*.

Range sum $S(i, j)$ is defined as the sum of the elements in `nums` between indices `i` and `j` inclusive, where `i <= j`.

Example 1:

Input: `nums = [-2,5,-1]`, `lower = -2`, `upper = 2`

Output: 3

Explanation: The three ranges are: $[0,0]$, $[2,2]$, and $[0,2]$ and their respective sums are: -2, -1, 2.

Example 2:

Input: `nums = [0]`, `lower = 0`, `upper = 0`

Output: 1

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- $-10^5 \leq \text{lower} \leq \text{upper} \leq 10^5$
- The answer is **guaranteed** to fit in a **32-bit** integer.

328. Odd Even Linked List**Medium**

6189394Add to ListShare


Given the `head` of a singly linked list, group all the nodes with odd indices together followed by the nodes with even indices, and return *the reordered list*.

The **first** node is considered **odd**, and the **second** node is **even**, and so on.


Note that the relative order inside both the even and odd groups should remain as it was in the input.

You must solve the problem in $O(1)$ extra space complexity and $O(n)$ time complexity.

Example 1:



Example 2:



Constraints:

- The number of nodes in the linked list is in the range $[0, 10^4]$.
- $-10^6 \leq \text{Node.val} \leq 10^6$

329. Longest Increasing Path in a Matrix

Hard

7206111Add to ListShare

Given an $m \times n$ integers `matrix`, return the length of the longest increasing path in `matrix`.

From each cell, you can either move in four directions: left, right, up, or down. You **may not** move **diagonally** or move **outside the boundary** (i.e., wrap-around is not allowed).

Example 1:

9	9	4
6	6	8
2	1	1

Input: `matrix` = `[[9,9,4],[6,6,8],[2,1,1]]`

Output: 4

Explanation: The longest increasing path is [1, 2, 6, 9].

Example 2:

3	4	5
3	2	6
2	2	1

Input: matrix = [[3,4,5],[3,2,6],[2,2,1]]

Output: 4

Explanation: The longest increasing path is [3, 4, 5, 6]. Moving diagonally is not allowed.

Example 3:

Input: matrix = [[1]]

Output: 1

Constraints:

- $m == \text{matrix.length}$
- $n == \text{matrix}[i].length$
- $1 \leq m, n \leq 200$
- $0 \leq \text{matrix}[i][j] \leq 2^{31} - 1$

330. Patching Array

Hard

1192119 Add to List Share

Given a sorted integer array `nums` and an integer `n`, add/patch elements to the array such that any number in the range `[1, n]` inclusive can be formed by the sum of some elements in the array.

Return *the minimum number of patches required*.

Example 1:

Input: nums = [1,3], n = 6

Output: 1

Explanation:

Combinations of `nums` are [1], [3], [1,3], which form possible sums of: 1, 3, 4.

Now if we add/patch 2 to `nums`, the combinations are: [1], [2], [3], [1,3], [2,3], [1,2,3].

Possible sums are 1, 2, 3, 4, 5, 6, which now covers the range [1, 6].

So we only need 1 patch.

Example 2:

Input: nums = [1,5,10], n = 20

Output: 2

Explanation: The two patches can be [2, 4].

Example 3:

Input: nums = [1,2,2], n = 5

Output: 0

Constraints:


- $1 \leq \text{nums.length} \leq 1000$
- $1 \leq \text{nums}[i] \leq 10^4$
- **nums is sorted in ascending order.**
- $1 \leq n \leq 2^{31} - 1$

331. Verify Preorder Serialization of a Binary Tree

Medium

187394Add to ListShare

One way to serialize a binary tree is to use **preorder traversal**. When we encounter a non-null node, we record the node's value. If it is a null node, we record using a sentinel value such as '#'.



For example, the above binary tree can be serialized to the string "9,3,4,#,#,1,#,#,2,#,6,#,#", where '#' represents a null node.

Given a string of comma-separated values `preorder`, return `true` if it is a correct preorder traversal serialization of a binary tree.

It is **guaranteed** that each comma-separated value in the string must be either an integer or a character `'#'` representing null pointer.

You may assume that the input format is always valid.

- For example, it could never contain two consecutive commas, such as `"1,,3"`.

Note: You are not allowed to reconstruct the tree.

Example 1:

Input: `preorder = "9,3,4,#,#,1,#,#,2,#,6,#,#"`

Output: `true`

Example 2:

Input: `preorder = "1,#"`

Output: `false`

Example 3:

Input: `preorder = "9,#,#,1"`

Output: `false`

Constraints:

- $1 \leq \text{preorder.length} \leq 10^4$
- `preorder` consist of integers in the range `[0, 100]` and `'#'` separated by commas `', '`.

332. Reconstruct Itinerary

Hard

42751611Add to ListShare


You are given a list of airline `tickets` where `tickets[i] = [fromi, toi]` represent the departure and the arrival airports of one flight. Reconstruct the itinerary in order and return it.

All of the tickets belong to a man who departs from `"JFK"`, thus, the itinerary must begin with `"JFK"`. If there are multiple valid itineraries, you should return the itinerary that has the smallest lexical order when read as a single string.

- For example, the itinerary `["JFK", "LGA"]` has a smaller lexical order than `["JFK", "LGB"]`.

You may assume all tickets form at least one valid itinerary. You must use all the tickets once and only once.


Example 1:



Input: `tickets = [["MUC", "LHR"], ["JFK", "MUC"], ["SFO", "SJC"], ["LHR", "SFO"]]`

Output: `["JFK", "MUC", "LHR", "SFO", "SJC"]`

Example 2:



Input: `tickets = [["JFK", "SFO"], ["JFK", "ATL"], ["SFO", "ATL"], ["ATL", "JFK"], ["ATL", "SFO"]]`

Output: `["JFK", "ATL", "JFK", "SFO", "ATL", "SFO"]`

Explanation: Another possible reconstruction is `["JFK", "SFO", "ATL", "JFK", "ATL", "SFO"]` but it is larger in lexical order.

Constraints:

- `1 <= tickets.length <= 300`
- `tickets[i].length == 2`
- `fromi.length == 3`
- `toi.length == 3`
- `fromi` and `toi` consist of uppercase English letters.
- `fromi != toi`

334. Increasing Triplet Subsequence**Medium**

4409225Add to ListShare

Given an integer array `nums`, return `true` if there exists a triple of indices `(i, j, k)` such that `i < j < k` and `nums[i] < nums[j] < nums[k]`. If no such indices exists, return `false`.

Example 1:**Input:** `nums = [1,2,3,4,5]`**Output:** `true`**Explanation:** Any triplet where `i < j < k` is valid.**Example 2:****Input:** `nums = [5,4,3,2,1]`**Output:** `false`**Explanation:** No triplet exists.**Example 3:****Input:** `nums = [2,1,5,0,4,6]`**Output:** `true`**Explanation:** The triplet `(3, 4, 5)` is valid because `nums[3] == 0 < nums[4] == 4 < nums[5] == 6`.**Constraints:**

- `1 <= nums.length <= 5 * 105`

- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

335. Self Crossing

Hard


277468Add to ListShare

You are given an array of integers `distance`.

You start at point `(0, 0)` on an **X-Y** plane and you move `distance[0]` meters to the north, then `distance[1]` meters to the west, `distance[2]` meters to the south, `distance[3]` meters to the east, and so on. In other words, after each move, your direction changes counter-clockwise.

Return `true` if your path crosses itself, and `false` if it does not.


Example 1:



Input: distance = [2,1,1,2]

Output: true


Example 2:



Input: distance = [1,2,3,4]

Output: false

Example 3:



Input: distance = [1,1,1,1]

Output: true

Constraints:

- $1 \leq \text{distance.length} \leq 10^5$
- $1 \leq \text{distance}[i] \leq 10^5$

336. Palindrome Pairs

Hard

3959414Add to ListShare

You are given a **0-indexed** array of **unique** strings `words`.A **palindrome pair** is a pair of integers `(i, j)` such that:

- `0 <= i, j < word.length`,
- `i != j`, and
- `words[i] + words[j]` (the concatenation of the two strings) is a palindrome string.

Return *an array of all the **palindrome pairs** of `words`*.**Example 1:****Input:** `words = ["abcd", "dcba", "lls", "s", "sssll"]`**Output:** `[[0,1],[1,0],[3,2],[2,4]]`**Explanation:** The palindromes are `["abcddcba", "dcbaabcd", "slls", "llssssll"]`**Example 2:****Input:** `words = ["bat", "tab", "cat"]`**Output:** `[[0,1],[1,0]]`**Explanation:** The palindromes are `["battab", "tabbat"]`**Example 3:****Input:** `words = ["a", ""]`**Output:** `[[0,1],[1,0]]`**Explanation:** The palindromes are `["a", "a"]`**Constraints:**

- `1 <= words.length <= 5000`
- `0 <= words[i].length <= 300`
- `words[i]` consists of lowercase English letters.

337. House Robber III**Medium**


6973101Add to ListShare

The thief has found himself a new place for his thievery again. There is only one entrance to this area, called `root`.

Besides the `root`, each house has one and only one parent house. After a tour, the smart thief realized that all houses in this place form a binary tree. It will automatically contact the police if **two directly-linked houses were broken into on the same night**.

Given the `root` of the binary tree, return *the maximum amount of money the thief can rob without alerting the police*.

Example 1:




Input: `root = [3,2,3,null,3,null,1]`

Output: 7

Explanation: Maximum amount of money the thief can rob = $3 + 3 + 1 = 7$.

Example 2:



Input: root = [3,4,5,1,3,null,1]

Output: 9

Explanation: Maximum amount of money the thief can rob = 4 + 5 = 9.

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^4$

338. Counting Bits

Easy

7790369Add to ListShare

Given an integer n , return an array ans of length $n + 1$ such that for each i ($0 \leq i \leq n$), $\text{ans}[i]$ is the **number of 1's** in the binary representation of i .

Example 1:

Input: n = 2

Output: [0,1,1]

Explanation:

0 --> 0

1 --> 1

```
2 --> 10
```

Example 2:

Input: n = 5

Output: [0,1,1,2,1,2]

Explanation:

```
0 --> 0
```

```
1 --> 1
```

```
2 --> 10
```

```
3 --> 11
```

```
4 --> 100
```

```
5 --> 101
```

Constraints:

- $0 \leq n \leq 10^5$

341. Flatten Nested List Iterator

Medium

39371374Add to ListShare

You are given a nested list of integers `nestedList`. Each element is either an integer or a list whose elements may also be integers or other lists. Implement an iterator to flatten it.

Implement the `NestedIterator` class:

- `NestedIterator(List<NestedInteger> nestedList)` Initializes the iterator with the nested list `nestedList`.
- `int next()` Returns the next integer in the nested list.
- `boolean hasNext()` Returns `true` if there are still some integers in the nested list and `false` otherwise.

Your code will be tested with the following pseudocode:

```
initialize iterator with nestedList
```

```
res = []
```

```

while iterator.hasNext()
    append iterator.next() to the end of res
return res

```

If `res` matches the expected flattened list, then your code will be judged as correct.

Example 1:

Input: `nestedList = [[1,1],2,[1,1]]`

Output: `[1,1,2,1,1]`

Explanation: By calling `next` repeatedly until `hasNext` returns `false`, the order of elements returned by `next` should be: `[1,1,2,1,1]`.

Example 2:

Input: `nestedList = [1,[4,[6]]]`

Output: `[1,4,6]`

Explanation: By calling `next` repeatedly until `hasNext` returns `false`, the order of elements returned by `next` should be: `[1,4,6]`.

Constraints:

- `1 <= nestedList.length <= 500`
- The values of the integers in the nested list is in the range `[-106, 106]`

342. Power of Four

Easy

2627314Add to ListShare

Given an integer `n`, return `true` if it is a power of four. Otherwise, return `false`.

An integer `n` is a power of four, if there exists an integer `x` such that `n == 4x`.

Example 1:

Input: `n = 16`

Output: `true`

Example 2:**Input:** n = 5**Output:** false**Example 3:****Input:** n = 1**Output:** true**Constraints:**

- $-2^{31} \leq n \leq 2^{31} - 1$

343. Integer Break**Medium**

3228343Add to ListShare

Given an integer n , break it into the sum of k **positive integers**, where $k \geq 2$, and maximize the product of those integers.

Return *the maximum product you can get.*

Example 1:**Input:** n = 2**Output:** 1**Explanation:** $2 = 1 + 1$, $1 \times 1 = 1$.**Example 2:****Input:** n = 10**Output:** 36**Explanation:** $10 = 3 + 3 + 4$, $3 \times 3 \times 4 = 36$.**Constraints:**

- $2 \leq n \leq 58$

344. Reverse String

Easy

6103996Add to ListShare

Write a function that reverses a string. The input string is given as an array of characters `s`.

You must do this by modifying the input array in-place with $O(1)$ extra memory.

Example 1:

Input: `s = ["h", "e", "l", "l", "o"]`

Output: `["o", "l", "l", "e", "h"]`

Example 2:

Input: `s = ["H", "a", "n", "n", "a", "h"]`

Output: `["h", "a", "n", "n", "a", "H"]`

Constraints:

- $1 \leq s.length \leq 10^5$
- `s[i]` is a printable ascii character.

345. Reverse Vowels of a String

Easy

19192002Add to ListShare

Given a string `s`, reverse only all the vowels in the string and return it.

The vowels are `'a'`, `'e'`, `'i'`, `'o'`, and `'u'`, and they can appear in both cases.

Example 1:

Input: `s = "hello"`

Output: `"holle"`

Example 2:

Input: `s = "leetcode"`

Output: "leotcede"

Constraints:

- $1 \leq s.length \leq 3 * 10^5$
- s consist of **printable ASCII** characters.

347. Top K Frequent Elements

Medium

11186417Add to ListShare

Given an integer array nums and an integer k , return *the k most frequent elements*. You may return the answer in **any order**.

Example 1:

Input: $\text{nums} = [1,1,1,2,2,3]$, $k = 2$

Output: $[1,2]$

Example 2:

Input: $\text{nums} = [1]$, $k = 1$

Output: $[1]$

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- k is in the range $[1, \text{the number of unique elements in the array}]$.
- It is **guaranteed** that the answer is **unique**.

349. Intersection of Two Arrays

Easy

36821996Add to ListShare

Given two integer arrays nums1 and nums2 , return *an array of their intersection*. Each element in the result must be **unique** and you may return the result in **any order**.

Example 1:

Input: nums1 = [1,2,2,1], nums2 = [2,2]

Output: [2]

Example 2:

Input: nums1 = [4,9,5], nums2 = [9,4,9,8,4]

Output: [9,4]

Explanation: [4,9] is also accepted.

Constraints:

- $1 \leq \text{nums1.length}, \text{nums2.length} \leq 1000$
- $0 \leq \text{nums1[i]}, \text{nums2[i]} \leq 1000$

350. Intersection of Two Arrays II

Easy

5347783Add to ListShare

Given two integer arrays `nums1` and `nums2`, return *an array of their intersection*. Each element in the result must appear as many times as it shows in both arrays and you may return the result in **any order**.

Example 1:

Input: nums1 = [1,2,2,1], nums2 = [2,2]

Output: [2,2]

Example 2:

Input: nums1 = [4,9,5], nums2 = [9,4,9,8,4]

Output: [4,9]

Explanation: [9,4] is also accepted.

Constraints:

- $1 \leq \text{nums1.length}, \text{nums2.length} \leq 1000$
- $0 \leq \text{nums1[i]}, \text{nums2[i]} \leq 1000$

352. Data Stream as Disjoint Intervals

Hard

700163Add to ListShare

Given a data stream input of non-negative integers a_1, a_2, \dots, a_n , summarize the numbers seen so far as a list of disjoint intervals.

Implement the `SummaryRanges` class:

- `SummaryRanges()` Initializes the object with an empty stream.
- `void addNum(int value)` Adds the integer `value` to the stream.
- `int[][] getIntervals()` Returns a summary of the integers in the stream currently as a list of disjoint intervals $[start_i, end_i]$. The answer should be sorted by `start_i`.

Example 1:

Input

```
["SummaryRanges", "addNum", "getIntervals", "addNum", "getIntervals", "addNum",
 "getIntervals", "addNum", "getIntervals", "addNum", "getIntervals"]

[], [1], [], [3], [], [7], [], [2], [], [6], []]
```

Output

```
null, null, [[1, 1]], null, [[1, 1], [3, 3]], null, [[1, 1], [3, 3], [7, 7]], null,
 [[1, 3], [7, 7]], null, [[1, 3], [6, 7]]]
```

Explanation

```
SummaryRanges summaryRanges = new SummaryRanges();

summaryRanges.addNum(1);      // arr = [1]
summaryRanges getIntervals(); // return [[1, 1]]
summaryRanges.addNum(3);      // arr = [1, 3]
summaryRanges getIntervals(); // return [[1, 1], [3, 3]]
summaryRanges.addNum(7);      // arr = [1, 3, 7]
summaryRanges getIntervals(); // return [[1, 1], [3, 3], [7, 7]]
summaryRanges.addNum(2);      // arr = [1, 2, 3, 7]
```

```
summaryRanges.getIntervals(); // return [[1, 3], [7, 7]]
summaryRanges.addNum(6);      // arr = [1, 2, 3, 6, 7]
summaryRanges.getIntervals(); // return [[1, 3], [6, 7]]
```

Constraints:

- $0 \leq \text{value} \leq 10^4$
- At most $3 * 10^4$ calls will be made to `addNum` and `getIntervals`.

354. Russian Doll Envelopes

Hard

4619113Add to ListShare

You are given a 2D array of integers `envelopes` where `envelopes[i] = [wi, hi]` represents the width and the height of an envelope.

One envelope can fit into another if and only if both the width and height of one envelope are greater than the other envelope's width and height.

Return *the maximum number of envelopes you can Russian doll (i.e., put one inside the other)*.

Note: You cannot rotate an envelope.

Example 1:

Input: `envelopes = [[5,4],[6,4],[6,7],[2,3]]`

Output: 3

Explanation: The maximum number of envelopes you can Russian doll is 3 (`[2,3] => [5,4] => [6,7]`).

Example 2:

Input: `envelopes = [[1,1],[1,1],[1,1]]`

Output: 1

Constraints:

- $1 \leq envelopes.length \leq 10^5$
- $envelopes[i].length == 2$
- $1 \leq w_i, h_i \leq 10^5$

355. Design Twitter

Medium

2491325Add to ListShare

Design a simplified version of Twitter where users can post tweets, follow/unfollow another user, and is able to see the 10 most recent tweets in the user's news feed.

Implement the `Twitter` class:

- `Twitter()` Initializes your `twitter` object.
- `void postTweet(int userId, int tweetId)` Composes a new tweet with ID `tweetId` by the user `userId`. Each call to this function will be made with a unique `tweetId`.
- `List<Integer> getNewsFeed(int userId)` Retrieves the 10 most recent tweet IDs in the user's news feed. Each item in the news feed must be posted by users who the user followed or by the user themselves. Tweets must be **ordered from most recent to least recent**.
- `void follow(int followerId, int followeeId)` The user with ID `followerId` started following the user with ID `followeeId`.
- `void unfollow(int followerId, int followeeId)` The user with ID `followerId` started unfollowing the user with ID `followeeId`.

Example 1:

Input

```
["Twitter", "postTweet", "getNewsFeed", "follow", "postTweet", "getNewsFeed",
"unfollow", "getNewsFeed"]
```

```
[[], [1, 5], [1], [1, 2], [2, 6], [1], [1, 2], [1]]
```

Output

```
[null, null, [5], null, null, [6, 5], null, [5]]
```

Explanation

```
Twitter twitter = new Twitter();
twitter.postTweet(1, 5); // User 1 posts a new tweet (id = 5).
```

```

twitter.getNewsFeed(1); // User 1's news feed should return a list with 1 tweet id -> [5]. return [5]

twitter.follow(1, 2); // User 1 follows user 2.

twitter.postTweet(2, 6); // User 2 posts a new tweet (id = 6).

twitter.getNewsFeed(1); // User 1's news feed should return a list with 2 tweet ids -> [6, 5]. Tweet id 6 should precede tweet id 5 because it is posted after tweet id 5.

twitter.unfollow(1, 2); // User 1 unfollows user 2.

twitter.getNewsFeed(1); // User 1's news feed should return a list with 1 tweet id -> [5], since user 1 is no longer following user 2.

```

Constraints:

- $1 \leq \text{userId}, \text{followerId}, \text{followeeId} \leq 500$
- $0 \leq \text{tweetId} \leq 10^4$
- All the tweets have **unique** IDs.
- At most $3 * 10^4$ calls will be made to `postTweet`, `getNewsFeed`, `follow`, and `unfollow`.

357. Count Numbers with Unique Digits

Medium

10861313Add to ListShare

Given an integer n , return the count of all numbers with unique digits, x , where $0 \leq x < 10^n$.

Example 1:

Input: $n = 2$

Output: 91

Explanation: The answer should be the total numbers in the range of $0 \leq x < 100$, excluding 11, 22, 33, 44, 55, 66, 77, 88, 99

Example 2:

Input: $n = 0$

Output: 1

Constraints:

- $0 \leq n \leq 8$

363. Max Sum of Rectangle No Larger Than K

Hard

3093154Add to ListShare

Given an $m \times n$ matrix `matrix` and an integer `k`, return the *max sum of a rectangle in the matrix such that its sum is no larger than `k`*.

It is **guaranteed** that there will be a rectangle with a sum no larger than `k`.

Example 1:

1	0	1
0	-2	3

Input: `matrix = [[1,0,1],[0,-2,3]]`, `k = 2`

Output: 2

Explanation: Because the sum of the blue rectangle $[[0, 1], [-2, 3]]$ is 2, and 2 is the max number no larger than `k` (`k = 2`).

Example 2:

Input: `matrix = [[2,2,-1]]`, `k = 3`

Output: 3

Constraints:

- $m == \text{matrix.length}$
- $n == \text{matrix[i].length}$
- $1 \leq m, n \leq 100$
- $-100 \leq \text{matrix[i][j]} \leq 100$
- $-10^5 \leq k \leq 10^5$

365. Water and Jug Problem

Medium

9741256Add to ListShare

You are given two jugs with capacities `jug1Capacity` and `jug2Capacity` liters. There is an infinite amount of water supply available. Determine whether it is possible to measure exactly `targetCapacity` liters using these two jugs.

If `targetCapacity` liters of water are measurable, you must have `targetCapacity` liters of water contained **within one or both buckets** by the end.

Operations allowed:

- Fill any of the jugs with water.
- Empty any of the jugs.
- Pour water from one jug into another till the other jug is completely full, or the first jug itself is empty.

Example 1:

Input: `jug1Capacity` = 3, `jug2Capacity` = 5, `targetCapacity` = 4

Output: true

Explanation: The famous Die Hard example

Example 2:

Input: `jug1Capacity` = 2, `jug2Capacity` = 6, `targetCapacity` = 5

Output: false

Example 3:

Input: `jug1Capacity` = 1, `jug2Capacity` = 2, `targetCapacity` = 3

Output: true

Constraints:

- $1 \leq \text{jug1Capacity}, \text{jug2Capacity}, \text{targetCapacity} \leq 10^6$

367. Valid Perfect Square

Easy

2861253Add to ListShare

Given a **positive** integer *num*, write a function which returns True if *num* is a perfect square else False.

Follow up: Do not use any built-in library function such as `sqrt`.

Example 1:

Input: num = 16

Output: true

Example 2:

Input: num = 14

Output: false

Constraints:

- `1 <= num <= 2^31 - 1`

368. Largest Divisible Subset**Medium**

3781160Add to ListShare

Given a set of **distinct** positive integers `nums`, return the largest subset `answer` such that every pair `(answer[i], answer[j])` of elements in this subset satisfies:

- `answer[i] % answer[j] == 0`, or
- `answer[j] % answer[i] == 0`

If there are multiple solutions, return any of them.

Example 1:

Input: nums = [1,2,3]

Output: [1,2]

Explanation: [1,3] is also accepted.

Example 2:**Input:** nums = [1,2,4,8]**Output:** [1,2,4,8]**Constraints:**

- $1 \leq \text{nums.length} \leq 1000$
- $1 \leq \text{nums}[i] \leq 2 * 10^9$
- All the integers in `nums` are **unique**.

371. Sum of Two Integers**Medium**

30014312Add to ListShare

Given two integers `a` and `b`, return *the sum of the two integers without using the operators + and -*.**Example 1:****Input:** a = 1, b = 2**Output:** 3**Example 2:****Input:** a = 2, b = 3**Output:** 5**Constraints:**

- $-1000 \leq a, b \leq 1000$

372. Super Pow**Medium**

5761196Add to ListShare

Your task is to calculate $a^b \bmod 1337$ where `a` is a positive integer and `b` is an extremely large positive integer given in the form of an array.

Example 1:**Input:** a = 2, b = [3]**Output:** 8**Example 2:****Input:** a = 2, b = [1,0]**Output:** 1024**Example 3:****Input:** a = 1, b = [4,3,3,8,5,2]**Output:** 1**Constraints:**

- $1 \leq a \leq 2^{31} - 1$
- $1 \leq b.length \leq 2000$
- $0 \leq b[i] \leq 9$
- b does not contain leading zeros.

373. Find K Pairs with Smallest Sums**Medium**

3569217Add to ListShare

You are given two integer arrays `nums1` and `nums2` sorted in **ascending order** and an integer `k`.

Define a pair (u, v) which consists of one element from the first array and one element from the second array.

Return *the k pairs* $(u_1, v_1), (u_2, v_2), \dots, (u_k, v_k)$ *with the smallest sums.*

Example 1:**Input:** `nums1 = [1,7,11]`, `nums2 = [2,4,6]`, `k = 3`**Output:** `[[1,2],[1,4],[1,6]]`

Explanation: The first 3 pairs are returned from the sequence:
`[1,2],[1,4],[1,6],[7,2],[7,4],[11,2],[7,6],[11,4],[11,6]`

Example 2:

Input: `nums1 = [1,1,2], nums2 = [1,2,3], k = 2`

Output: `[[1,1],[1,1]]`

Explanation: The first 2 pairs are returned from the sequence:
`[1,1],[1,1],[1,2],[2,1],[1,2],[2,2],[1,3],[1,3],[2,3]`

Example 3:

Input: `nums1 = [1,2], nums2 = [3], k = 3`

Output: `[[1,3],[2,3]]`

Explanation: All possible pairs are returned from the sequence: `[1,3],[2,3]`

Constraints:

- `1 <= nums1.length, nums2.length <= 105`
- `-109 <= nums1[i], nums2[i] <= 109`
- `nums1` and `nums2` both are sorted in **ascending order**.
- `1 <= k <= 104`

374. Guess Number Higher or Lower

Easy

1567225Add to ListShare

We are playing the Guess Game. The game is as follows:

I pick a number from `1` to `n`. You have to guess which number I picked.

Every time you guess wrong, I will tell you whether the number I picked is higher or lower than your guess.

You call a pre-defined API `int guess(int num)`, which returns three possible results:

- `-1`: Your guess is higher than the number I picked (i.e. `num > pick`).
- `1`: Your guess is lower than the number I picked (i.e. `num < pick`).
- `0`: your guess is equal to the number I picked (i.e. `num == pick`).

Return *the number that I picked*.

Example 1:

Input: `n = 10, pick = 6`

Output: `6`

Example 2:

```
Input: n = 1, pick = 1
```

```
Output: 1
```

Example 3:

```
Input: n = 2, pick = 1
```

```
Output: 1
```

Constraints:

- $1 \leq n \leq 2^{31} - 1$
- $1 \leq \text{pick} \leq n$

375. Guess Number Higher or Lower II**Medium**


16291887Add to ListShare

We are playing the Guessing Game. The game will work as follows:

1. I pick a number between 1 and n.
2. You guess a number.
3. If you guess the right number, **you win the game**.
4. If you guess the wrong number, then I will tell you whether the number I picked is **higher or lower**, and you will continue guessing.
5. Every time you guess a wrong number x , you will pay x dollars. If you run out of money, **you lose the game**.

Given a particular n, return the minimum amount of money you need to **guarantee a win regardless of what number I pick**.

Example 1:



Input: $n = 10$

Output: 16

Explanation: The winning strategy is as follows:

- The range is $[1,10]$. Guess 7.
 - If this is my number, your total is \$0. Otherwise, you pay \$7.
 - If my number is higher, the range is $[8,10]$. Guess 9.
 - If this is my number, your total is \$7. Otherwise, you pay \$9.
 - If my number is higher, it must be 10. Guess 10. Your total is $$7 + \$9 = \$16$.
 - If my number is lower, it must be 8. Guess 8. Your total is $$7 + \$9 = \$16$.
 - If my number is lower, the range is $[1,6]$. Guess 3.
 - If this is my number, your total is \$7. Otherwise, you pay \$3.
 - If my number is higher, the range is $[4,6]$. Guess 5.
 - If this is my number, your total is $$7 + \$3 = \$10$. Otherwise, you pay \$5.
 - If my number is higher, it must be 6. Guess 6. Your total is $$7 + \$3 + \$5 = \15 .

- If my number is lower, it must be 4. Guess 4. Your total is $\$7 + \$3 + \$5 = \15 .

- If my number is lower, the range is $[1,2]$. Guess 1.

- If this is my number, your total is $\$7 + \$3 = \$10$. Otherwise, you pay $\$1$.

- If my number is higher, it must be 2. Guess 2. Your total is $\$7 + \$3 + \$1 = \11 .

The worst case in all these scenarios is that you pay $\$16$. Hence, you only need $\$16$ to guarantee a win.

Example 2:

Input: $n = 1$

Output: 0

Explanation: There is only one possible number, so you can guess 1 and not have to pay anything.

Example 3:

Input: $n = 2$

Output: 1

Explanation: There are two possible numbers, 1 and 2.

- Guess 1.

- If this is my number, your total is $\$0$. Otherwise, you pay $\$1$.

- If my number is higher, it must be 2. Guess 2. Your total is $\$1$.

The worst case is that you pay $\$1$.

Constraints:

- $1 \leq n \leq 200$

376. Wiggle Subsequence

Medium

4344141Add to ListShare

A **wiggle sequence** is a sequence where the differences between successive numbers strictly alternate between positive and negative. The first difference (if one exists) may be either positive or

negative. A sequence with one element and a sequence with two non-equal elements are trivially wiggle sequences.

- For example, `[1, 7, 4, 9, 2, 5]` is a **wiggle sequence** because the differences `(6, -3, 5, -7, 3)` alternate between positive and negative.
- In contrast, `[1, 4, 7, 2, 5]` and `[1, 7, 4, 5, 5]` are not wiggle sequences. The first is not because its first two differences are positive, and the second is not because its last difference is zero.

A **subsequence** is obtained by deleting some elements (possibly zero) from the original sequence, leaving the remaining elements in their original order.

Given an integer array `nums`, return *the length of the longest wiggle subsequence of `nums`*.

Example 1:

Input: `nums = [1,7,4,9,2,5]`

Output: 6

Explanation: The entire sequence is a wiggle sequence with differences `(6, -3, 5, -7, 3)`.

Example 2:

Input: `nums = [1,17,5,10,13,15,10,5,16,8]`

Output: 7

Explanation: There are several subsequences that achieve this length.

One is `[1, 17, 10, 13, 10, 16, 8]` with differences `(16, -7, 3, -3, 6, -8)`.

Example 3:

Input: `nums = [1,2,3,4,5,6,7,8,9]`

Output: 2

Constraints:

- `1 <= nums.length <= 1000`
- `0 <= nums[i] <= 1000`

377. Combination Sum IV

Medium

5177535Add to ListShare

Given an array of **distinct** integers `nums` and a target integer `target`, return *the number of possible combinations that add up to target*.

The test cases are generated so that the answer can fit in a **32-bit** integer.

Example 1:

Input: `nums = [1,2,3]`, `target = 4`

Output: 7

Explanation:

The possible combination ways are:

(1, 1, 1, 1)
 (1, 1, 2)
 (1, 2, 1)
 (1, 3)
 (2, 1, 1)
 (2, 2)
 (3, 1)

Note that different sequences are counted as different combinations.

Example 2:

Input: `nums = [9]`, `target = 3`

Output: 0

Constraints:

- `1 <= nums.length <= 200`
- `1 <= nums[i] <= 1000`
- All the elements of `nums` are **unique**.
- `1 <= target <= 1000`

378. Kth Smallest Element in a Sorted Matrix

Medium

8173293Add to ListShare

Given an $n \times n$ matrix where each of the rows and columns is sorted in ascending order, return the k^{th} smallest element in the matrix.

Note that it is the k^{th} smallest element **in the sorted order**, not the k^{th} **distinct** element.

You must find a solution with a memory complexity better than $O(n^2)$.

Example 1:

Input: matrix = [[1,5,9],[10,11,13],[12,13,15]], k = 8

Output: 13

Explanation: The elements in the matrix are [1,5,9,10,11,12,13,13,15], and the 8th smallest number is 13

Example 2:

Input: matrix = [[-5]], k = 1

Output: -5

Constraints:

- $n == \text{matrix.length} == \text{matrix[i].length}$
- $1 \leq n \leq 300$
- $-10^9 \leq \text{matrix[i][j]} \leq 10^9$
- All the rows and columns of `matrix` are **guaranteed** to be sorted in **non-decreasing order**.
- $1 \leq k \leq n^2$

380. Insert Delete GetRandom O(1)

Medium

6054319Add to ListShare

Implement the `RandomizedSet` class:

- `RandomizedSet()` Initializes the `RandomizedSet` object.

- `bool insert(int val)` Inserts an item `val` into the set if not present. Returns `true` if the item was not present, `false` otherwise.
- `bool remove(int val)` Removes an item `val` from the set if present. Returns `true` if the item was present, `false` otherwise.
- `int getRandom()` Returns a random element from the current set of elements (it's guaranteed that at least one element exists when this method is called). Each element must have the **same probability** of being returned.

You must implement the functions of the class such that each function works in **average** $O(1)$ time complexity.

Example 1:

Input

```
["RandomizedSet", "insert", "remove", "insert", "getRandom", "remove", "insert", "getRandom"]
[[], [1], [2], [2], [], [1], [2], []]
```

Output

```
[null, true, false, true, 2, true, false, 2]
```

Explanation

```
RandomizedSet randomizedSet = new RandomizedSet();

randomizedSet.insert(1); // Inserts 1 to the set. Returns true as 1 was inserted successfully.

randomizedSet.remove(2); // Returns false as 2 does not exist in the set.

randomizedSet.insert(2); // Inserts 2 to the set, returns true. Set now contains [1,2].

randomizedSet.getRandom(); // getRandom() should return either 1 or 2 randomly.

randomizedSet.remove(1); // Removes 1 from the set, returns true. Set now contains [2,].

randomizedSet.insert(2); // 2 was already in the set, so return false.

randomizedSet.getRandom(); // Since 2 is the only number in the set, getRandom() will always return 2.
```

Constraints:

- $-2^{31} \leq \text{val} \leq 2^{31} - 1$
- At most $2 * 10^5$ calls will be made to `insert`, `remove`, and `getRandom`.
- There will be **at least one** element in the data structure when `getRandom` is called.

381. Insert Delete GetRandom O(1) - Duplicates allowed

Hard

1803127 Add to List Share

`RandomizedCollection` is a data structure that contains a collection of numbers, possibly duplicates (i.e., a multiset). It should support inserting and removing specific elements and also removing a random element.

Implement the `RandomizedCollection` class:

- `RandomizedCollection()` Initializes the empty `RandomizedCollection` object.
- `bool insert(int val)` Inserts an item `val` into the multiset, even if the item is already present. Returns `true` if the item is not present, `false` otherwise.
- `bool remove(int val)` Removes an item `val` from the multiset if present. Returns `true` if the item is present, `false` otherwise. Note that if `val` has multiple occurrences in the multiset, we only remove one of them.
- `int getRandom()` Returns a random element from the current multiset of elements. The probability of each element being returned is **linearly related** to the number of same values the multiset contains.

You must implement the functions of the class such that each function works on **average** $O(1)$ time complexity.

Note: The test cases are generated such that `getRandom` will only be called if there is **at least one** item in the `RandomizedCollection`.

Example 1:

Input

```
["RandomizedCollection", "insert", "insert", "insert", "getRandom", "remove", "getRandom"]
[[], [1], [1], [2], [], [1], []]
```

Output

```
[null, true, false, true, 2, true, 1]
```

Explanation

```

RandomizedCollection randomizedCollection = new RandomizedCollection();

randomizedCollection.insert(1);    // return true since the collection does not
contain 1.

                                         // Inserts 1 into the collection.

randomizedCollection.insert(1);    // return false since the collection contains 1.

                                         // Inserts another 1 into the collection.

Collection now contains [1,1].
```

randomizedCollection.insert(2); // return true since the collection does not
contain 2.

 // Inserts 2 into the collection. Collection now
contains [1,1,2].

randomizedCollection.getRandom(); // getRandom should:

// - return 1 with probability 2/3, or

// - return 2 with probability 1/3.

randomizedCollection.remove(1); // return true since the collection contains 1.

 // Removes 1 from the collection. Collection now
contains [1,2].

randomizedCollection.getRandom(); // getRandom should return 1 or 2, both equally
likely.

Constraints:

- $-2^{31} \leq \text{val} \leq 2^{31} - 1$
- At most $2 * 10^5$ calls **in total** will be made to `insert`, `remove`, and `getRandom`.
- There will be **at least one** element in the data structure when `getRandom` is called.

382. Linked List Random Node

Medium


1844455Add to ListShare

Given a singly linked list, return a random node's value from the linked list. Each node must have the **same probability** of being chosen.

Implement the `Solution` class:

- `Solution(ListNode head)` Initializes the object with the head of the singly-linked list `head`.
- `int getRandom()` Chooses a node randomly from the list and returns its value. All the nodes of the list should be equally likely to be chosen.

Example 1:



Input

```

["Solution", "getRandom", "getRandom", "getRandom", "getRandom", "getRandom"]
[[[1, 2, 3]], [], [], [], [], []]
  
```

Output

```
[null, 1, 3, 2, 2, 3]
```

Explanation

```

Solution solution = new Solution([1, 2, 3]);
solution.getRandom(); // return 1
solution.getRandom(); // return 3
solution.getRandom(); // return 2
solution.getRandom(); // return 2
solution.getRandom(); // return 3
// getRandom() should return either 1, 2, or 3 randomly. Each element should have
equal probability of returning.
  
```

Constraints:

- The number of nodes in the linked list will be in the range `[1, 104]`.
- $-10^4 \leq \text{Node.val} \leq 10^4$
- At most 10^4 calls will be made to `getRandom`.

383. Ransom Note

Easy

3121366Add to ListShare

Given two strings `ransomNote` and `magazine`, return `true` if `ransomNote` can be constructed by using the letters from `magazine` and `false` otherwise.

Each letter in `magazine` can only be used once in `ransomNote`.

Example 1:

Input: `ransomNote = "a"`, `magazine = "b"`

Output: `false`

Example 2:

Input: `ransomNote = "aa"`, `magazine = "ab"`

Output: `false`

Example 3:

Input: `ransomNote = "aa"`, `magazine = "aab"`

Output: `true`

Constraints:

- `1 <= ransomNote.length, magazine.length <= 105`
- `ransomNote` and `magazine` consist of lowercase English letters.

384. Shuffle an Array**Medium**

960763Add to ListShare

Given an integer array `nums`, design an algorithm to randomly shuffle the array. All permutations of the array should be **equally likely** as a result of the shuffling.

Implement the `Solution` class:

- `Solution(int[] nums)` Initializes the object with the integer array `nums`.
- `int[] reset()` Resets the array to its original configuration and returns it.
- `int[] shuffle()` Returns a random shuffling of the array.

Example 1:**Input**

```
["Solution", "shuffle", "reset", "shuffle"]
[[[1, 2, 3]], [], [], []]
```

Output

```
[null, [3, 1, 2], [1, 2, 3], [1, 3, 2]]
```

Explanation

```
Solution solution = new Solution([1, 2, 3]);
solution.shuffle();      // Shuffle the array [1,2,3] and return its result.
                        // Any permutation of [1,2,3] must be equally likely to be
returned.
                        // Example: return [3, 1, 2]
solution.reset();      // Resets the array back to its original configuration
[1,2,3]. Return [1, 2, 3]
solution.shuffle();      // Returns the random shuffling of array [1,2,3]. Example:
return [1, 3, 2]
```

Constraints:

- $1 \leq \text{nums.length} \leq 50$
- $-10^6 \leq \text{nums}[i] \leq 10^6$
- All the elements of `nums` are **unique**.
- At most 10^4 calls **in total** will be made to `reset` and `shuffle`.

385. Mini Parser**Medium**

3961202Add to ListShare

Given a string `s` represents the serialization of a nested list, implement a parser to deserialize it and return *the deserialized* `NestedInteger`.

Each element is either an integer or a list whose elements may also be integers or other lists.

Example 1:**Input:** s = "324"**Output:** 324**Explanation:** You should return a NestedInteger object which contains a single integer 324.**Example 2:****Input:** s = "[123,[456,[789]]]"**Output:** [123,[456,[789]]]**Explanation:** Return a NestedInteger object containing a nested list with 2 elements:

1. An integer containing value 123.
2. A nested list containing two elements:
 - i. An integer containing value 456.
 - ii. A nested list with one element:
 - a. An integer containing value 789

Constraints:

- $1 \leq s.length \leq 5 * 10^4$
- s consists of digits, square brackets "[]", negative sign '-', and commas ','.
- s is the serialization of valid NestedInteger.
- All the values in the input are in the range $[-10^6, 10^6]$.

386. Lexicographical Numbers**Medium**

1445122Add to ListShare

Given an integer n, return all the numbers in the range [1, n] sorted in lexicographical order.

You must write an algorithm that runs in $O(n)$ time and uses $O(1)$ extra space.**Example 1:****Input:** n = 13

Output: [1,10,11,12,13,2,3,4,5,6,7,8,9]

Example 2:

Input: n = 2

Output: [1,2]

Constraints:

- $1 \leq n \leq 5 * 10^4$

387. First Unique Character in a String

Easy

6686229Add to ListShare

Given a string s , find the first non-repeating character in it and return its index. If it does not exist, return -1 .

Example 1:

Input: s = "leetcode"

Output: 0

Example 2:

Input: s = "loveleetcode"

Output: 2

Example 3:

Input: s = "aabb"

Output: -1

Constraints:


- $1 \leq s.length \leq 10^5$
- s consists of only lowercase English letters.

388. Longest Absolute File Path

Medium

10722258Add to ListShare

Suppose we have a file system that stores both files and directories. An example of one system is represented in the following picture:



Here, we have `dir` as the only directory in the root. `dir` contains two subdirectories, `subdir1` and `subdir2`. `subdir1` contains a file `file1.ext` and subdirectory `subsubdir1`. `subdir2` contains a subdirectory `subsubdir2`, which contains a file `file2.ext`.

In text form, it looks like this (with \rightarrow representing the tab character):

```

dir
→ subdir1
→ → file1.ext
→ → subsubdir1
→ subdir2
→ → subsubdir2
→ → → file2.ext
  
```


If we were to write this representation in code, it will look like this: `"dir\n\tsubdir1\n\t\tfile1.ext\n\t\tsubsubdir1\n\t\tsubdir2\n\t\t\tsubsubdir2\n\t\t\t\tfile2.ext"`. Note that the `'\n'` and `'\t'` are the new-line and tab characters.

Every file and directory has a unique **absolute path** in the file system, which is the order of directories that must be opened to reach the file/directory itself, all concatenated by '/'s. Using the above example, the **absolute path** to `file2.ext` is `"dir/subdir2/subsubdir2/file2.ext"`. Each directory name consists of letters, digits, and/or spaces. Each file name is of the form `name.extension`, where `name` and `extension` consist of letters, digits, and/or spaces.

Given a string `input` representing the file system in the explained format, return *the length of the longest absolute path* to a **file** in the abstracted file system. If there is no file in the system, return 0.

Note that the testcases are generated such that the file system is valid and no file or directory name has length 0.

Example 1:




Input: `input = "dir\n\tsubdir1\n\tsubdir2\n\t\tfile.ext"`

Output: 20

Explanation: We have only one file, and the absolute path is "dir/subdir2/file.ext" of length 20.

Example 2:



Input: input =
 "dir\n\tsubdir1\n\t\tfile1.ext\n\t\tsubsubdir1\n\t\tsubdir2\n\t\t\tsubsubdir2\n\t\t\t\tfile2.ext"

Output: 32

Explanation: We have two files:

"dir/subdir1/file1.ext" of length 21

"dir/subdir2/subsubdir2/file2.ext" of length 32.

We return 32 since it is the longest absolute path to a file.

Example 3:

Input: input = "a"

Output: 0

Explanation: We do not have any files, just a single directory named "a".

Constraints:

- $1 \leq \text{input.length} \leq 10^4$
- `input` may contain lowercase or uppercase English letters, a new line character '`\n`', a tab character '`\t`', a dot '`.`', a space '', and digits.
- All file and directory names have **positive** length.

389. Find the Difference

Easy

3212397Add to ListShare

You are given two strings `s` and `t`.

String `t` is generated by random shuffling string `s` and then add one more letter at a random position.

Return the letter that was added to `t`.

Example 1:

Input: `s = "abcd"`, `t = "abcde"`

Output: "e"

Explanation: 'e' is the letter that was added.

Example 2:

Input: `s = ""`, `t = "y"`

Output: "y"

Constraints:

- `0 <= s.length <= 1000`
- `t.length == s.length + 1`
- `s` and `t` consist of lowercase English letters.

390. Elimination Game**Medium**

971570Add to ListShare

You have a list `arr` of all integers in the range `[1, n]` sorted in a strictly increasing order. Apply the following algorithm on `arr`:

- Starting from left to right, remove the first number and every other number afterward until you reach the end of the list.
- Repeat the previous step again, but this time from right to left, remove the rightmost number and every other number from the remaining numbers.
- Keep repeating the steps again, alternating left to right and right to left, until a single number remains.

Given the integer `n`, return *the last number that remains in arr*.

Example 1:**Input:** n = 9**Output:** 6**Explanation:**

arr = [1, 2, 3, 4, 5, 6, 7, 8, 9]

arr = [2, 4, 6, 8]

arr = [2, 6]

arr = [6]

Example 2:**Input:** n = 1**Output:** 1**Constraints:**

- $1 \leq n \leq 10^9$


391. Perfect Rectangle**Hard**

654103Add to ListShare

Given an array `rectangles` where `rectangles[i] = [xi, yi, ai, bi]` represents an axis-aligned rectangle. The bottom-left point of the rectangle is (x_i, y_i) and the top-right point of it is (a_i, b_i) .

Return `true` if all the rectangles together form an exact cover of a rectangular region.

Example 1:




Input: rectangles = [[1,1,3,3],[3,1,4,2],[3,2,4,4],[1,3,2,4],[2,3,3,4]]

Output: true

Explanation: All 5 rectangles together form an exact cover of a rectangular region.

Example 2:




Input: rectangles = [[1,1,2,3],[1,3,2,4],[3,1,4,2],[3,2,4,4]]

Output: false

Explanation: Because there is a gap between the two rectangular regions.

Example 3:



Input: rectangles = [[1,1,3,3],[3,1,4,2],[1,3,2,4],[2,2,4,4]]

Output: false

Explanation: Because two of the rectangles overlap with each other.

Constraints:

- $1 \leq \text{rectangles.length} \leq 2 * 10^4$
- $\text{rectangles[i].length} == 4$
- $-10^5 \leq x_i, y_i, a_i, b_i \leq 10^5$

392. Is Subsequence

Easy

5850330Add to ListShare

Given two strings `s` and `t`, return `true` if `s` is a **subsequence** of `t`, or `false` otherwise.

A **subsequence** of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not).

Example 1:

Input: s = "abc", t = "ahbgdc"

Output: true

Example 2:

Input: s = "axc", t = "ahbgdc"

Output: false

Constraints:

- $0 \leq s.length \leq 100$
- $0 \leq t.length \leq 10^4$
- s and t consist only of lowercase English letters.

393. UTF-8 Validation

Medium

8272731Add to ListShare

Given an integer array data representing the data, return whether it is a valid **UTF-8** encoding (i.e. it translates to a sequence of valid UTF-8 encoded characters).

A character in **UTF8** can be from **1 to 4 bytes** long, subjected to the following rules:

1. For a **1-byte** character, the first bit is a 0, followed by its Unicode code.
2. For an **n-bytes** character, the first n bits are all one's, the n + 1 bit is 0, followed by n - 1 bytes with the most significant 2 bits being 10.

This is how the UTF-8 encoding would work:

Number of Bytes		UTF-8 Octet Sequence
		(binary)
-----+-----		
1		0xxxxxxxx
2		110xxxxx 10xxxxxx

3		1110xxxx 10xxxxxx 10xxxxxx
4		11110xxx 10xxxxxx 10xxxxxx 10xxxxxx

x denotes a bit in the binary form of a byte that may be either 0 or 1.

Note: The input is an array of integers. Only the **least significant 8 bits** of each integer is used to store the data. This means each integer represents only 1 byte of data.

Example 1:

Input: data = [197,130,1]

Output: true

Explanation: data represents the octet sequence: 11000101 10000010 00000001.

It is a valid utf-8 encoding for a 2-bytes character followed by a 1-byte character.

Example 2:

Input: data = [235,140,4]

Output: false

Explanation: data represented the octet sequence: 11101011 10001100 00000100.

The first 3 bits are all one's and the 4th bit is 0 means it is a 3-bytes character.

The next byte is a continuation byte which starts with 10 and that's correct.

But the second continuation byte does not start with 10, so it is invalid.

Constraints:

- $1 \leq \text{data.length} \leq 2 * 10^4$
- $0 \leq \text{data}[i] \leq 255$

394. Decode String

Medium

9409414Add to ListShare

Given an encoded string, return its decoded string.

The encoding rule is: $k[\text{encoded_string}]$, where the `encoded_string` inside the square brackets is being repeated exactly k times. Note that k is guaranteed to be a positive integer.

You may assume that the input string is always valid; there are no extra white spaces, square brackets are well-formed, etc. Furthermore, you may assume that the original data does not contain any digits and that digits are only for those repeat numbers, `k`. For example, there will not be input like `3a` or `2[4]`.

The test cases are generated so that the length of the output will never exceed 10^5 .

Example 1:

Input: `s = "3[a]2[bc]"`

Output: "aaabcbc"

Example 2:

Input: `s = "3[a2[c]]"`

Output: "accaccacc"

Example 3:

Input: `s = "2[abc]3[cd]ef"`

Output: "abcabcccdcdcdef"

Constraints:

- `1 <= s.length <= 30`
- `s` consists of lowercase English letters, digits, and square brackets '`[]`'.
- `s` is guaranteed to be a **valid** input.
- All the integers in `s` are in the range `[1, 300]`.

395. Longest Substring with At Least K Repeating Characters

Medium

4583378Add to ListShare

Given a string `s` and an integer `k`, return the length of the longest substring of `s` such that the frequency of each character in this substring is greater than or equal to `k`.

Example 1:

Input: `s = "aaabb", k = 3`

Output: 3

Explanation: The longest substring is "aaa", as 'a' is repeated 3 times.

Example 2:

Input: $s = \text{"ababb"}$, $k = 2$

Output: 5

Explanation: The longest substring is "ababb", as 'a' is repeated 2 times and 'b' is repeated 3 times.

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of only lowercase English letters.
- $1 \leq k \leq 10^5$

396. Rotate Function

Medium

995227Add to ListShare

You are given an integer array nums of length n .

Assume arr_k to be an array obtained by rotating nums by k positions clock-wise. We define the **rotation function** F on nums as follow:

- $F(k) = 0 * \text{arr}_k[0] + 1 * \text{arr}_k[1] + \dots + (n - 1) * \text{arr}_k[n - 1]$.

Return the maximum value of $F(0), F(1), \dots, F(n-1)$.

The test cases are generated so that the answer fits in a **32-bit** integer.

Example 1:

Input: $\text{nums} = [4, 3, 2, 6]$

Output: 26

Explanation:

$$F(0) = (0 * 4) + (1 * 3) + (2 * 2) + (3 * 6) = 0 + 3 + 4 + 18 = 25$$

$$F(1) = (0 * 6) + (1 * 4) + (2 * 3) + (3 * 2) = 0 + 4 + 6 + 6 = 16$$

$$F(2) = (0 * 2) + (1 * 6) + (2 * 4) + (3 * 3) = 0 + 6 + 8 + 9 = 23$$

$$F(3) = (0 * 3) + (1 * 2) + (2 * 6) + (3 * 4) = 0 + 2 + 12 + 12 = 26$$

So the maximum value of $F(0)$, $F(1)$, $F(2)$, $F(3)$ is $F(3) = 26$.

Example 2:

Input: `nums = [100]`

Output: `0`

Constraints:

- `n == nums.length`
- `1 <= n <= 105`
- `-100 <= nums[i] <= 100`

397. Integer Replacement

Medium

958447 Add to List Share

Given a positive integer `n`, you can apply one of the following operations:

1. If `n` is even, replace `n` with `n / 2`.
2. If `n` is odd, replace `n` with either `n + 1` or `n - 1`.

Return *the minimum number of operations needed for `n` to become 1*.

Example 1:

Input: `n = 8`

Output: `3`

Explanation: `8 -> 4 -> 2 -> 1`

Example 2:

Input: `n = 7`

Output: `4`

Explanation: `7 -> 8 -> 4 -> 2 -> 1`

or `7 -> 6 -> 3 -> 2 -> 1`

Example 3:

Input: n = 4

Output: 2

Constraints:

- $1 \leq n \leq 2^{31} - 1$

398. Random Pick Index

Medium

10291140Add to ListShare

Given an integer array `nums` with possible **duplicates**, randomly output the index of a given `target` number. You can assume that the given target number must exist in the array.

Implement the `Solution` class:

- `Solution(int[] nums)` Initializes the object with the array `nums`.
- `int pick(int target)` Picks a random index `i` from `nums` where `nums[i] == target`. If there are multiple valid `i`'s, then each index should have an equal probability of returning.

Example 1:

Input

```
["Solution", "pick", "pick", "pick"]
[[[1, 2, 3, 3, 3]], [3], [1], [3]]
```

Output

```
[null, 4, 0, 2]
```

Explanation

```
Solution solution = new Solution([1, 2, 3, 3, 3]);
solution.pick(3); // It should return either index 2, 3, or 4 randomly. Each index
should have equal probability of returning.

solution.pick(1); // It should return 0. Since in the array only nums[0] is equal to
1.

solution.pick(3); // It should return either index 2, 3, or 4 randomly. Each index
should have equal probability of returning.
```

Constraints:

- $1 \leq \text{nums.length} \leq 2 * 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$
- `target` is an integer from `nums`.
- At most 10^4 calls will be made to `pick`.

399. Evaluate Division**Medium**

6456552Add to ListShare

You are given an array of variable pairs `equations` and an array of real numbers `values`, where `equations[i] = [Ai, Bi]` and `values[i]` represent the equation $A_i / B_i = \text{values}[i]$. Each A_i or B_i is a string that represents a single variable.

You are also given some `queries`, where `queries[j] = [Cj, Dj]` represents the j^{th} query where you must find the answer for $C_j / D_j = ?$.

Return *the answers to all queries*. If a single answer cannot be determined, return `-1.0`.

Note: The input is always valid. You may assume that evaluating the queries will not result in division by zero and that there is no contradiction.

Example 1:

Input: `equations = [["a", "b"], ["b", "c"]], values = [2.0, 3.0], queries = [["a", "c"], ["b", "a"], ["a", "e"], ["a", "a"], ["x", "x"]]`

Output: `[6.00000, 0.50000, -1.00000, 1.00000, -1.00000]`

Explanation:

Given: $a / b = 2.0$, $b / c = 3.0$

queries are: $a / c = ?$, $b / a = ?$, $a / e = ?$, $a / a = ?$, $x / x = ?$

return: `[6.0, 0.5, -1.0, 1.0, -1.0]`

Example 2:

Input: `equations = [["a", "b"], ["b", "c"], ["bc", "cd"]], values = [1.5, 2.5, 5.0], queries = [["a", "c"], ["c", "b"], ["bc", "cd"], ["cd", "bc"]]`

Output: `[3.75000, 0.40000, 5.00000, 0.20000]`

Example 3:

Input: equations = [["a","b"]], values = [0.5], queries = [[["a","b"],[["b","a"],[["a","c"],[["x","y"]]]]]

Output: [0.50000,2.00000,-1.00000,-1.00000]

Constraints:

- $1 \leq \text{equations.length} \leq 20$
- $\text{equations[i].length} == 2$
- $1 \leq A_i.length, B_i.length \leq 5$
- $\text{values.length} == \text{equations.length}$
- $0.0 < \text{values}[i] \leq 20.0$
- $1 \leq \text{queries.length} \leq 20$
- $\text{queries[i].length} == 2$
- $1 \leq C_j.length, D_j.length \leq 5$
- A_i, B_i, C_j, D_j consist of lower case English letters and digits.

400. Nth Digit

Medium

7471672Add to ListShare

Given an integer n , return the n^{th} digit of the infinite integer sequence [1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, ...].

Example 1:

Input: $n = 3$

Output: 3

Example 2:

Input: $n = 11$

Output: 0

Explanation: The 11^{th} digit of the sequence 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, ... is a 0, which is part of the number 10.

Constraints:

- $1 \leq n \leq 2^{31} - 1$

401. Binary Watch

Easy

10591980Add to ListShare

A binary watch has 4 LEDs on the top to represent the hours (0-11), and 6 LEDs on the bottom to represent the minutes (0-59). Each LED represents a zero or one, with the least significant bit on the right.

- For example, the below binary watch reads "4:51".



Given an integer `turnedOn` which represents the number of LEDs that are currently on (ignoring the PM), return *all possible times the watch could represent*. You may return the answer in **any order**.

The hour must not contain a leading zero.

- For example, "01:00" is not valid. It should be "1:00".

The minute must be consist of two digits and may contain a leading zero.

- For example, "10:2" is not valid. It should be "10:02".

Example 1:**Input:** turnedOn = 1**Output:** ["0:01", "0:02", "0:04", "0:08", "0:16", "0:32", "1:00", "2:00", "4:00", "8:00"]**Example 2:****Input:** turnedOn = 9**Output:** []**Constraints:**

- $0 \leq \text{turnedOn} \leq 10$

402. Remove K Digits**Medium**

6703281Add to ListShare

Given string `num` representing a non-negative integer `num`, and an integer `k`, return *the smallest possible integer after removing `k` digits from `num`*.

Example 1:**Input:** num = "1432219", k = 3**Output:** "1219"

Explanation: Remove the three digits 4, 3, and 2 to form the new number 1219 which is the smallest.

Example 2:**Input:** num = "10200", k = 1**Output:** "200"

Explanation: Remove the leading 1 and the number is 200. Note that the output must not contain leading zeroes.

Example 3:**Input:** num = "10", k = 2

Output: "0"

Explanation: Remove all the digits from the number and it is left with nothing which is 0.

Constraints:

- `1 <= k <= num.length <= 105`
- `num` consists of only digits.
- `num` does not have any leading zeros except for the zero itself.

403. Frog Jump

Hard

3173178Add to ListShare

A frog is crossing a river. The river is divided into some number of units, and at each unit, there may or may not exist a stone. The frog can jump on a stone, but it must not jump into the water.

Given a list of `stones`' positions (in units) in sorted **ascending order**, determine if the frog can cross the river by landing on the last stone. Initially, the frog is on the first stone and assumes the first jump must be `1` unit.

If the frog's last jump was `k` units, its next jump must be either `k - 1`, `k`, or `k + 1` units. The frog can only jump in the forward direction.

Example 1:

Input: `stones = [0,1,3,5,6,8,12,17]`

Output: `true`

Explanation: The frog can jump to the last stone by jumping 1 unit to the 2nd stone, then 2 units to the 3rd stone, then 2 units to the 4th stone, then 3 units to the 6th stone, 4 units to the 7th stone, and 5 units to the 8th stone.

Example 2:

Input: `stones = [0,1,2,3,4,8,9,11]`

Output: `false`


Explanation: There is no way to jump to the last stone as the gap between the 5th and 6th stone is too large.

Constraints:

- `2 <= stones.length <= 2000`
- `0 <= stones[i] <= 231 - 1`
- `stones[0] == 0`
- `stones` is sorted in a strictly increasing order.

404. Sum of Left Leaves**Easy**

3872261Add to ListShare

Given the `root` of a binary tree, return *the sum of all left leaves*.A **leaf** is a node with no children. A **left leaf** is a leaf that is the left child of another node.**Example 1:****Input:** `root = [3,9,20,null,null,15,7]`**Output:** 24**Explanation:** There are two left leaves in the binary tree, with values 9 and 15 respectively.**Example 2:****Input:** `root = [1]`**Output:** 0

Constraints:

- The number of nodes in the tree is in the range `[1, 1000]`.
- $-1000 \leq \text{Node.val} \leq 1000$

405. Convert a Number to Hexadecimal**Easy**

990182Add to ListShare

Given an integer `num`, return a string representing its hexadecimal representation. For negative integers, two's complement method is used.

All the letters in the answer string should be lowercase characters, and there should not be any leading zeros in the answer except for the zero itself.

Note: You are not allowed to use any built-in library method to directly solve this problem.

Example 1:

Input: `num = 26`

Output: "1a"

Example 2:

Input: `num = -1`

Output: "ffffffff"

Constraints:

- $-2^{31} \leq \text{num} \leq 2^{31} - 1$

406. Queue Reconstruction by Height**Medium**

6403643Add to ListShare

You are given an array of people, `people`, which are the attributes of some people in a queue (not necessarily in order). Each `people[i] = [hi, ki]` represents the *ith* person of height `hi` with **exactly** `ki` other people in front who have a height greater than or equal to `hi`.

Reconstruct and return *the queue that is represented by the input array* `people`. The returned queue should be formatted as an array `queue`, where `queue[j] = [hj, kj]` is the attributes of the j^{th} person in the queue (`queue[0]` is the person at the front of the queue).

Example 1:

Input: `people = [[7,0],[4,4],[7,1],[5,0],[6,1],[5,2]]`

Output: `[[5,0],[7,0],[5,2],[6,1],[4,4],[7,1]]`

Explanation:

Person 0 has height 5 with no other people taller or the same height in front.

Person 1 has height 7 with no other people taller or the same height in front.

Person 2 has height 5 with two persons taller or the same height in front, which is person 0 and 1.

Person 3 has height 6 with one person taller or the same height in front, which is person 1.

Person 4 has height 4 with four people taller or the same height in front, which are people 0, 1, 2, and 3.

Person 5 has height 7 with one person taller or the same height in front, which is person 1.

Hence `[[5,0],[7,0],[5,2],[6,1],[4,4],[7,1]]` is the reconstructed queue.

Example 2:

Input: `people = [[6,0],[5,0],[4,0],[3,2],[2,2],[1,4]]`

Output: `[[4,0],[5,0],[2,2],[3,2],[1,4],[6,0]]`

Constraints:

- $1 \leq \text{people.length} \leq 2000$
- $0 \leq h_i \leq 10^6$
- $0 \leq k_i < \text{people.length}$
- It is guaranteed that the queue can be reconstructed.


407. Trapping Rain Water II

Hard

310273Add to ListShare

Given an $m \times n$ integer matrix `heightMap` representing the height of each unit cell in a 2D elevation map, return *the volume of water it can trap after raining*.

Example 1:



Input: `heightMap = [[1,4,3,1,3,2],[3,2,1,3,2,4],[2,3,3,2,3,1]]`


Output: 4

Explanation: After the rain, water is trapped between the blocks.

We have two small ponds 1 and 3 units trapped.

The total volume of water trapped is 4.

Example 2:



Input: heightMap = [[3,3,3,3,3],[3,2,2,2,3],[3,2,1,2,3],[3,2,2,2,3],[3,3,3,3,3]]

Output: 10

Constraints:

- `m == heightMap.length`
- `n == heightMap[i].length`
- `1 <= m, n <= 200`
- `0 <= heightMap[i][j] <= 2 * 104`

409. Longest Palindrome

Easy

3611214Add to ListShare

Given a string `s` which consists of lowercase or uppercase letters, return *the length of the longest palindrome* that can be built with those letters.

Letters are **case sensitive**, for example, "Aa" is not considered a palindrome here.

Example 1:

Input: `s = "abccccdd"`

Output: 7

Explanation: One longest palindrome that can be built is "dccaccd", whose length is 7.

Example 2:

Input: s = "a"

Output: 1

Explanation: The longest palindrome that can be built is "a", whose length is 1.

Constraints:

- $1 \leq s.length \leq 2000$
- s consists of lowercase **and/or** uppercase English letters only.

410. Split Array Largest Sum

Hard

6864159Add to ListShare

Given an array `nums` which consists of non-negative integers and an integer `m`, you can split the array into `m` non-empty continuous subarrays.

Write an algorithm to minimize the largest sum among these `m` subarrays.

Example 1:

Input: nums = [7,2,5,10,8], m = 2

Output: 18

Explanation:

There are four ways to split `nums` into two subarrays.

The best way is to split it into [7,2,5] and [10,8],

where the largest sum among the two subarrays is only 18.

Example 2:

Input: nums = [1,2,3,4,5], m = 2

Output: 9

Example 3:

Input: `nums = [1,4,4], m = 3`

Output: `4`

Constraints:

- `1 <= nums.length <= 1000`
- `0 <= nums[i] <= 106`
- `1 <= m <= min(50, nums.length)`

412. Fizz Buzz

Easy

957158Add to ListShare

Given an integer `n`, return a string array `answer` (**1-indexed**) where:

- `answer[i] == "FizzBuzz"` if `i` is divisible by 3 and 5.
- `answer[i] == "Fizz"` if `i` is divisible by 3.
- `answer[i] == "Buzz"` if `i` is divisible by 5.
- `answer[i] == i` (as a string) if none of the above conditions are true.

Example 1:

Input: `n = 3`

Output: `["1", "2", "Fizz"]`

Example 2:

Input: `n = 5`

Output: `["1", "2", "Fizz", "4", "Buzz"]`

Example 3:

Input: `n = 15`

Output:

`["1", "2", "Fizz", "4", "Buzz", "Fizz", "7", "8", "Fizz", "Buzz", "11", "Fizz", "13", "14", "FizzBuzz"]`

Constraints:

- `1 <= n <= 104`

413. Arithmetic Slices

Medium

4273263Add to ListShare

An integer array is called arithmetic if it consists of **at least three elements** and if the difference between any two consecutive elements is the same.

- For example, `[1, 3, 5, 7, 9]`, `[7, 7, 7, 7]`, and `[3, -1, -5, -9]` are arithmetic sequences.

Given an integer array `nums`, return *the number of arithmetic subarrays* of `nums`.

A **subarray** is a contiguous subsequence of the array.

Example 1:

Input: `nums = [1, 2, 3, 4]`

Output: 3

Explanation: We have 3 arithmetic slices in `nums`: `[1, 2, 3]`, `[2, 3, 4]` and `[1, 2, 3, 4]` itself.

Example 2:

Input: `nums = [1]`

Output: 0

Constraints:

- `1 <= nums.length <= 5000`
- `-1000 <= nums[i] <= 1000`

414. Third Maximum Number

Easy

20042512Add to ListShare

Given an integer array `nums`, return *the third distinct maximum number* in this array. If the third maximum does not exist, return the **maximum** number.

Example 1:

Input: `nums = [3, 2, 1]`

Output: 1

Explanation:

The first distinct maximum is 3.

The second distinct maximum is 2.

The third distinct maximum is 1.

Example 2:

Input: nums = [1,2]

Output: 2

Explanation:

The first distinct maximum is 2.

The second distinct maximum is 1.

The third distinct maximum does not exist, so the maximum (2) is returned instead.

Example 3:

Input: nums = [2,2,3,1]

Output: 1

Explanation:

The first distinct maximum is 3.

The second distinct maximum is 2 (both 2's are counted together since they have the same value).

The third distinct maximum is 1.

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

415. Add Strings

Easy

3798598Add to ListShare

Given two non-negative integers, `num1` and `num2` represented as string, return *the sum of num1 and num2 as a string*.

You must solve the problem without using any built-in library for handling large integers (such as `BigInteger`). You must also not convert the inputs to integers directly.

Example 1:

Input: `num1 = "11", num2 = "123"`

Output: `"134"`

Example 2:

Input: `num1 = "456", num2 = "77"`

Output: `"533"`

Example 3:

Input: `num1 = "0", num2 = "0"`

Output: `"0"`

Constraints:

- `1 <= num1.length, num2.length <= 104`
- `num1` and `num2` consist of only digits.
- `num1` and `num2` don't have any leading zeros except for the zero itself.

416. Partition Equal Subset Sum

Medium

8931150Add to ListShare

Given a **non-empty** array `nums` containing **only positive integers**, find if the array can be partitioned into two subsets such that the sum of elements in both subsets is equal.

Example 1:

Input: `nums = [1,5,11,5]`

Output: `true`

Explanation: The array can be partitioned as `[1, 5, 5]` and `[11]`.

Example 2:

Input: nums = [1,2,3,5]

Output: false

Explanation: The array cannot be partitioned into equal sum subsets.

Constraints:

- $1 \leq \text{nums.length} \leq 200$
- $1 \leq \text{nums}[i] \leq 100$

417. Pacific Atlantic Water Flow

Medium

56251060Add to ListShare

There is an $m \times n$ rectangular island that borders both the **Pacific Ocean** and **Atlantic Ocean**.


The **Pacific Ocean** touches the island's left and top edges, and the **Atlantic Ocean** touches the island's right and bottom edges.

The island is partitioned into a grid of square cells. You are given an $m \times n$ integer matrix `heights` where `heights[r][c]` represents the **height above sea level** of the cell at coordinate `(r, c)`.

The island receives a lot of rain, and the rain water can flow to neighboring cells directly north, south, east, and west if the neighboring cell's height is **less than or equal to** the current cell's height. Water can flow from any cell adjacent to an ocean into the ocean.

Return a **2D list** of grid coordinates `result` where `result[i] = [ri, ci]` denotes that rain water can flow from cell `(ri, ci)` to **both** the Pacific and Atlantic oceans.

Example 1:



Input: heights = [[1,2,2,3,5],[3,2,3,4,4],[2,4,5,3,1],[6,7,1,4,5],[5,1,1,2,4]]

Output: [[0,4],[1,3],[1,4],[2,2],[3,0],[3,1],[4,0]]

Explanation: The following cells can flow to the Pacific and Atlantic oceans, as shown below:

[0,4]: [0,4] -> Pacific Ocean

[0,4] -> Atlantic Ocean

[1,3]: [1,3] -> [0,3] -> Pacific Ocean

[1,3] -> [1,4] -> Atlantic Ocean

[1,4]: [1,4] -> [1,3] -> [0,3] -> Pacific Ocean

[1,4] -> Atlantic Ocean

```
[2,2]: [2,2] -> [1,2] -> [0,2] -> Pacific Ocean
      [2,2] -> [2,3] -> [2,4] -> Atlantic Ocean
[3,0]: [3,0] -> Pacific Ocean
      [3,0] -> [4,0] -> Atlantic Ocean
[3,1]: [3,1] -> [3,0] -> Pacific Ocean
      [3,1] -> [4,1] -> Atlantic Ocean
[4,0]: [4,0] -> Pacific Ocean
      [4,0] -> Atlantic Ocean
```

Note that there are other possible paths for these cells to flow to the Pacific and Atlantic oceans.

Example 2:

Input: heights = [[1]]

Output: [[0,0]]

Explanation: The water can flow from the only cell to the Pacific and Atlantic oceans.

Constraints:

- $m == \text{heights.length}$
- $n == \text{heights}[r].length$
- $1 \leq m, n \leq 200$
- $0 \leq \text{heights}[r][c] \leq 10^5$

419. Battleships in a Board

Medium

1736823Add to ListShare

Given an $m \times n$ matrix `board` where each cell is a battleship '`X`' or empty '`.`', return *the number of the battleships* on `board`.

Battleships can only be placed horizontally or vertically on `board`. In other words, they can only be made of the shape $1 \times k$ (1 row, k columns) or $k \times 1$ (k rows, 1 column), where k can be of any size. At least one horizontal or vertical cell separates between two battleships (i.e., there are no adjacent battleships).

Example 1:

X			X
			X
			X

Input: board = [["X", ".", ".", "X"], [".", ".", ".", "X"], [".", ".", ".", "X"]]

Output: 2

Example 2:

Input: board = [["."]]

Output: 0

Constraints:

- $m == \text{board.length}$
- $n == \text{board}[i].length$
- $1 \leq m, n \leq 200$
- $\text{board}[i][j]$ is either `'.'` or `'X'`.

420. Strong Password Checker

Hard

5741399Add to ListShare

A password is considered strong if the below conditions are all met:

- It has at least 6 characters and at most 20 characters.

- It contains at least **one lowercase** letter, at least **one uppercase** letter, and at least **one digit**.
- It does not contain three repeating characters in a row (i.e., "...aaa..." is weak, but "...aa...a..." is strong, assuming other conditions are met).

Given a string `password`, return *the minimum number of steps required to make `password` strong*. If `password` is already strong, return `0`.

In one step, you can:

- Insert one character to `password`,
- Delete one character from `password`, or
- Replace one character of `password` with another character.

Example 1:

Input: `password` = "a"

Output: 5

Example 2:

Input: `password` = "aA1"

Output: 3

Example 3:

Input: `password` = "1337C0d3"

Output: 0

Constraints:

- `1 <= password.length <= 50`
- `password` consists of letters, digits, dot '.' or exclamation mark '!'.

421. Maximum XOR of Two Numbers in an Array

Medium

4414343Add to ListShare

Given an integer array `nums`, return *the maximum result of `nums[i] XOR nums[j]`, where `0 <= i <= j < n`*.

Example 1:

Input: nums = [3,10,5,25,2,8]

Output: 28

Explanation: The maximum result is 5 XOR 25 = 28.

Example 2:

Input: nums = [14,70,53,83,49,91,36,80,92,51,66,70]

Output: 127

Constraints:

- $1 \leq \text{nums.length} \leq 2 * 10^5$
- $0 \leq \text{nums}[i] \leq 2^{31} - 1$

423. Reconstruct Original Digits from English

Medium

6762281Add to ListShare

Given a string s containing an out-of-order English representation of digits 0–9, return the digits in **ascending order**.

Example 1:

Input: s = "owoztneoer"

Output: "012"

Example 2:

Input: s = "fviefuro"

Output: "45"

Constraints:

- $1 \leq s.length \leq 10^5$
- $s[i]$ is one of the characters ["e", "g", "f", "i", "h", "o", "n", "s", "r", "u", "t", "w", "v", "x", "z"].
- s is **guaranteed** to be valid.

424. Longest Repeating Character Replacement

Medium

6193243Add to ListShare

You are given a string `s` and an integer `k`. You can choose any character of the string and change it to any other uppercase English character. You can perform this operation at most `k` times.

Return the length of the longest substring containing the same letter you can get after performing the above operations.

Example 1:

Input: `s = "ABAB", k = 2`

Output: 4

Explanation: Replace the two 'A's with two 'B's or vice versa.

Example 2:

Input: `s = "AABABBA", k = 1`

Output: 4

Explanation: Replace the one 'A' in the middle with 'B' and form "AABBBA".

The substring "BBBB" has the longest repeating letters, which is 4.

Constraints:

- `1 <= s.length <= 105`
- `s` consists of only uppercase English letters.
- `0 <= k <= s.length`

427. Construct Quad Tree

Medium

555750Add to ListShare

Given a `n * n` matrix `grid` of 0's and 1's only. We want to represent the `grid` with a Quad-Tree.

Return the root of the Quad-Tree representing the `grid`.

Notice that you can assign the value of a node to **True** or **False** when `isLeaf` is **False**, and both are **accepted** in the answer.

A Quad-Tree is a tree data structure in which each internal node has exactly four children. Besides, each node has two attributes:

- `val`: True if the node represents a grid of 1's or False if the node represents a grid of 0's.
- `isLeaf`: True if the node is leaf node on the tree or False if the node has the four children.

```
class Node {

    public boolean val;

    public boolean isLeaf;

    public Node topLeft;

    public Node topRight;


    public Node bottomLeft;

    public Node bottomRight;

}
```

We can construct a Quad-Tree from a two-dimensional area using the following steps:

1. If the current grid has the same value (i.e all 1's or all 0's) set `isLeaf` True and set `val` to the value of the grid and set the four children to Null and stop.
2. If the current grid has different values, set `isLeaf` to False and set `val` to any value and divide the current grid into four sub-grids as shown in the photo.
3. Recurse for each of the children with the proper sub-grid.



If you want to know more about the Quad-Tree, you can refer to the [wiki](#).

Quad-Tree format:

The output represents the serialized format of a Quad-Tree using level order traversal, where `null` signifies a path terminator where no node exists below.

It is very similar to the serialization of the binary tree. The only difference is that the node is represented as a list `[isLeaf, val]`.

If the value of `isLeaf` or `val` is True we represent it as **1** in the list `[isLeaf, val]` and if the value of `isLeaf` or `val` is False we represent it as **0**.

Example 1:


0	1
1	0

Input: `grid = [[0,1],[1,0]]`

Output: `[[0,1],[1,0],[1,1],[1,1],[1,0]]`

Explanation: The explanation of this example is shown below:

Notice that 0 represents False and 1 represents True in the photo representing the Quad-Tree.



Example 2:

1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0

Input: grid =
`[[1,1,1,1,0,0,0,0],[1,1,1,1,0,0,0,0],[1,1,1,1,1,1,1,1],[1,1,1,1,1,1,1,1],[1,1,1,1,0,0,0,0],[1,1,1,1,0,0,0,0],[1,1,1,1,0,0,0,0]]`

Output: `[[0,1],[1,1],[0,1],[1,1],[1,0],null,null,null,[1,0],[1,0],[1,1],[1,1]]`


Explanation: All values in the grid are not the same. We divide the grid into four sub-grids.

The `topLeft`, `bottomLeft` and `bottomRight` each has the same value.

The `topRight` have different values so we divide it into 4 sub-grids where each has the same value.

Explanation is shown in the photo below:

1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0
1	1	1	1	0	0	0	0



Constraints:

- `n == grid.length == grid[i].length`
- `n == 2x where 0 <= x <= 6`


429. N-ary Tree Level Order Traversal

Medium

3109121Add to ListShare

Given an n-ary tree, return the *level order* traversal of its nodes' values.


Nary-Tree input serialization is represented in their level order traversal, each group of children is separated by the null value (See examples).

Example 1:

Input: root = [1,null,3,2,4,null,5,6]

Output: [[1],[3,2,4],[5,6]]

Example 2:



Input: root = [1,null,2,3,4,5,null,null,6,7,null,8,null,9,10,null,null,11,null,12,null,13,null,null,14]

Output: [[1],[2,3,4,5],[6,7,8,9,10],[11,12,13],[14]]

Constraints:

- The height of the n-ary tree is less than or equal to 1000
- The total number of nodes is between [0, 10⁴]

430. Flatten a Multilevel Doubly Linked List

Medium


4136283Add to ListShare

You are given a doubly linked list, which contains nodes that have a next pointer, a previous pointer, and an additional **child pointer**. This child pointer may or may not point to a separate doubly linked list, also containing these special nodes. These child lists may have one or more children of their own, and so on, to produce a **multilevel data structure** as shown in the example below.

Given the `head` of the first level of the list, **flatten** the list so that all the nodes appear in a single-level, doubly linked list. Let `curr` be a node with a child list. The nodes in the child list should appear **after** `curr` and **before** `curr.next` in the flattened list.

Return the `head` of the flattened list. The nodes in the list must have **all** of their child pointers set to `null`.

Example 1:




Input: `head = [1,2,3,4,5,6,null,null,null,7,8,9,10,null,null,11,12]`


Output: `[1,2,3,7,8,11,12,9,10,4,5,6]`

Explanation: The multilevel linked list in the input is shown.

After flattening the multilevel linked list it becomes:



Example 2:




Input: head = [1,2,null,3]

Output: [1,3,2]

Explanation: The multilevel linked list in the input is shown.

After flattening the multilevel linked list it becomes:



Example 3:

Input: head = []

Output: []

Explanation: There could be empty list in the input.

Constraints:

- The number of Nodes will not exceed 1000.
- $1 \leq \text{Node.val} \leq 10^5$

How the multilevel linked list is represented in test cases:

We use the multilevel linked list from **Example 1** above:

```
1---2---3---4---5---6---NULL
```

```
|
```

```
7---8---9---10---NULL
```

```
|
```

```
11---12---NULL
```

The serialization of each level is as follows:

```
[1,2,3,4,5,6,null]
```

```
[7,8,9,10,null]
```

```
[11,12,null]
```

To serialize all levels together, we will add nulls in each level to signify no node connects to the upper node of the previous level. The serialization becomes:

```
[1, 2, 3, 4, 5, 6, null]
```

```
|
```

```
[null, null, 7, 8, 9, 10, null]
```

```
|
```

```
[null, null, 11, 12, null]
```

Merging the serialization of each level and removing trailing nulls we obtain:

```
[1,2,3,4,5,6,null,null,null,7,8,9,10,null,null,11,12]
```

432. All One Data Structure

Hard

1244142Add to ListShare

Design a data structure to store the strings' count with the ability to return the strings with minimum and maximum counts.

Implement the `AllOne` class:

- `AllOne()` Initializes the object of the data structure.
- `inc(String key)` Increments the count of the string `key` by `1`. If `key` does not exist in the data structure, insert it with count `1`.
- `dec(String key)` Decrements the count of the string `key` by `1`. If the count of `key` is `0` after the decrement, remove it from the data structure. It is guaranteed that `key` exists in the data structure before the decrement.
- `getMaxKey()` Returns one of the keys with the maximal count. If no element exists, return an empty string `""`.
- `getMinKey()` Returns one of the keys with the minimum count. If no element exists, return an empty string `""`.

Note that each function must run in $O(1)$ average time complexity.

Example 1:

Input

```
["AllOne", "inc", "inc", "getMaxKey", "getMinKey", "inc", "getMaxKey", "getMinKey"]
[[], ["hello"], ["hello"], [], [], ["leet"], [], []]
```

Output

```
[null, null, null, "hello", "hello", null, "hello", "leet"]
```

Explanation

```
AllOne allOne = new AllOne();
allOne.inc("hello");
allOne.inc("hello");
allOne.getMaxKey(); // return "hello"
allOne.getMinKey(); // return "hello"
allOne.inc("leet");
allOne.getMaxKey(); // return "hello"
allOne.getMinKey(); // return "leet"
```

Constraints:

- $1 \leq \text{key.length} \leq 10$
- `key` consists of lowercase English letters.
- It is guaranteed that for each call to `dec`, `key` is existing in the data structure.
- At most $5 * 10^4$ calls will be made to `inc`, `dec`, `getMaxKey`, and `getMinKey`.

433. Minimum Genetic Mutation

Medium

1087113Add to ListShare

A gene string can be represented by an 8-character long string, with choices from '`A`', '`C`', '`G`', and '`T`'.

Suppose we need to investigate a mutation from a gene string `start` to a gene string `end` where one mutation is defined as one single character changed in the gene string.

- For example, "`AACCGGTT`" \rightarrow "`AACCGGTA`" is one mutation.

There is also a gene bank `bank` that records all the valid gene mutations. A gene must be in `bank` to make it a valid gene string.

Given the two gene strings `start` and `end` and the gene bank `bank`, return the *minimum number of mutations needed to mutate from `start` to `end`*. If there is no such a mutation, return `-1`.

Note that the starting point is assumed to be valid, so it might not be included in the bank.

Example 1:

Input: `start = "AACCGGTT", end = "AACCGGTA", bank = ["AACCGGTA"]`

Output: 1

Example 2:

Input: `start = "AACCGGTT", end = "AAACGGTA", bank = ["AACCGGTA", "AACCGCTA", "AAACGGTA"]`

Output: 2

Example 3:

Input: `start = "AAAAACCC", end = "AACCCCCC", bank = ["AAAACCCC", "AAACCCCC", "AACCCCCC"]`

Output: 3

Constraints:

- `start.length == 8`
- `end.length == 8`
- `0 <= bank.length <= 10`
- `bank[i].length == 8`
- `start, end, and bank[i] consist of only the characters ['A', 'C', 'G', 'T'].`

434. Number of Segments in a String**Easy**

5171061Add to ListShare

Given a string `s`, return *the number of segments in the string*.A **segment** is defined to be a contiguous sequence of **non-space characters**.**Example 1:****Input:** `s = "Hello, my name is John"`**Output:** 5**Explanation:** The five segments are `["Hello,", "my", "name", "is", "John"]`**Example 2:****Input:** `s = "Hello"`**Output:** 1**Constraints:**

- `0 <= s.length <= 300`
- `s` consists of lowercase and uppercase English letters, digits, or one of the following characters `!@#$%^&*()_+-=,.:`
- The only space character in `s` is `' '`.

435. Non-overlapping Intervals**Medium**

4812138Add to ListShare

Given an array of intervals `intervals` where `intervals[i] = [starti, endi]`, return *the minimum number of intervals you need to remove to make the rest of the intervals non-overlapping*.

Example 1:

Input: intervals = [[1,2],[2,3],[3,4],[1,3]]

Output: 1

Explanation: [1,3] can be removed and the rest of the intervals are non-overlapping.

Example 2:

Input: intervals = [[1,2],[1,2],[1,2]]

Output: 2

Explanation: You need to remove two [1,2] to make the rest of the intervals non-overlapping.

Example 3:

Input: intervals = [[1,2],[2,3]]

Output: 0

Explanation: You don't need to remove any of the intervals since they're already non-overlapping.

Constraints:

- $1 \leq \text{intervals.length} \leq 10^5$
- $\text{intervals}[i].length == 2$
- $-5 * 10^4 \leq \text{start}_i < \text{end}_i \leq 5 * 10^4$

436. Find Right Interval

Medium

1429271Add to ListShare

You are given an array of `intervals`, where `intervals[i] = [starti, endi]` and each `starti` is **unique**.

The **right interval** for an interval `i` is an interval `j` such that `startj >= endi` and `startj` is **minimized**. Note that `i` may equal `j`.

Return *an array of right interval indices for each interval i*. If no **right interval** exists for interval `i`, then put `-1` at index `i`.

Example 1:

Input: intervals = [[1,2]]

Output: [-1]

Explanation: There is only one interval in the collection, so it outputs -1.

Example 2:

Input: intervals = [[3,4],[2,3],[1,2]]

Output: [-1,0,1]

Explanation: There is no right interval for [3,4].

The right interval for [2,3] is [3,4] since $\text{start}_0 = 3$ is the smallest start that is $\geq \text{end}_1 = 3$.

The right interval for [1,2] is [2,3] since $\text{start}_1 = 2$ is the smallest start that is $\geq \text{end}_2 = 2$.

Example 3:

Input: intervals = [[1,4],[2,3],[3,4]]

Output: [-1,2,-1]

Explanation: There is no right interval for [1,4] and [3,4].

The right interval for [2,3] is [3,4] since $\text{start}_2 = 3$ is the smallest start that is $\geq \text{end}_1 = 3$.

Constraints:

- $1 \leq \text{intervals.length} \leq 2 * 10^4$
- $\text{intervals}[i].length == 2$
- $-10^6 \leq \text{start}_i \leq \text{end}_i \leq 10^6$
- The start point of each interval is **unique**.


437. Path Sum III

Medium

8628413Add to ListShare

Given the `root` of a binary tree and an integer `targetSum`, return the number of paths where the sum of the values along the path equals `targetSum`.

The path does not need to start or end at the root or a leaf, but it must go downwards (i.e., traveling only from parent nodes to child nodes).

Example 1:

Input: root = [10,5,-3,3,2,null,11,3,-2,null,1], targetSum = 8

Output: 3

Explanation: The paths that sum to 8 are shown.

Example 2:

Input: root = [5,4,8,11,null,13,4,7,2,null,null,5,1], targetSum = 22

Output: 3

Constraints:

- The number of nodes in the tree is in the range [0, 1000].
- $-10^9 \leq \text{Node.val} \leq 10^9$
- $-1000 \leq \text{targetSum} \leq 1000$

438. Find All Anagrams in a String

Medium

8739271Add to ListShare

Given two strings `s` and `p`, return *an array of all the start indices of `p`'s anagrams in `s`*. You may return the answer in **any order**.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: `s = "cbaebabacd"`, `p = "abc"`

Output: `[0,6]`

Explanation:

The substring with start index = 0 is "cba", which is an anagram of "abc".

The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab"`, `p = "ab"`

Output: `[0,1,2]`

Explanation:

The substring with start index = 0 is "ab", which is an anagram of "ab".

The substring with start index = 1 is "ba", which is an anagram of "ab".

The substring with start index = 2 is "ab", which is an anagram of "ab".

Constraints:

- $1 \leq s.length, p.length \leq 3 * 10^4$
- `s` and `p` consist of lowercase English letters.

440. K-th Smallest in Lexicographical Order

Hard

62574Add to ListShare

Given two integers `n` and `k`, return *the k^{th} lexicographically smallest integer in the range `[1, n]`*.

Example 1:**Input:** n = 13, k = 2**Output:** 10**Explanation:** The lexicographical order is [1, 10, 11, 12, 13, 2, 3, 4, 5, 6, 7, 8, 9], so the second smallest number is 10.**Example 2:****Input:** n = 1, k = 1**Output:** 1**Constraints:**

- $1 \leq k \leq n \leq 10^9$

441. Arranging Coins**Easy**

26691107Add to ListShare

You have n coins and you want to build a staircase with these coins. The staircase consists of k rows where the i^{th} row has exactly i coins. The last row of the staircase **may be** incomplete.

Given the integer n , return *the number of complete rows of the staircase you will build*.

Example 1:




Input: $n = 5$

Output: 2

Explanation: Because the 3rd row is incomplete, we return 2.

Example 2:



Input: $n = 8$

Output: 3

Explanation: Because the 4th row is incomplete, we return 3.

Constraints:

- $1 \leq n \leq 2^{31} - 1$

442. Find All Duplicates in an Array

Medium

7337280Add to ListShare

Given an integer array `nums` of length `n` where all the integers of `nums` are in the range `[1, n]` and each integer appears **once** or **twice**, return *an array of all the integers that appears twice*.

You must write an algorithm that runs in $O(n)$ time and uses only constant extra space.

Example 1:

Input: `nums` = [4,3,2,7,8,2,3,1]

Output: [2,3]

Example 2:

Input: `nums` = [1,1,2]

Output: [1]

Example 3:

Input: `nums` = [1]

Output: []

Constraints:

- $n == \text{nums.length}$
- $1 \leq n \leq 10^5$
- $1 \leq \text{nums}[i] \leq n$
- Each element in `nums` appears **once** or **twice**.

443. String Compression

Medium

24084540Add to ListShare

Given an array of characters `chars`, compress it using the following algorithm:

Begin with an empty string `s`. For each group of **consecutive repeating characters** in `chars`:

- If the group's length is `1`, append the character to `s`.

- Otherwise, append the character followed by the group's length.

The compressed string `s` **should not be returned separately**, but instead, be stored **in the input character array `chars`**. Note that group lengths that are `10` or longer will be split into multiple characters in `chars`.

After you are done **modifying the input array**, return *the new length of the array*.

You must write an algorithm that uses only constant extra space.

Example 1:

Input: `chars = ["a", "a", "b", "b", "c", "c", "c"]`

Output: Return `6`, and the first `6` characters of the input array should be: `["a", "2", "b", "2", "c", "3"]`

Explanation: The groups are `"aa"`, `"bb"`, and `"ccc"`. This compresses to `"a2b2c3"`.

Example 2:

Input: `chars = ["a"]`

Output: Return `1`, and the first character of the input array should be: `["a"]`

Explanation: The only group is `"a"`, which remains uncompressed since it's a single character.

Example 3:

Input: `chars = ["a", "b", "b"]`

Output: Return `4`, and the first `4` characters of the input array should be: `["a", "b", "1", "2"]`.

Explanation: The groups are `"a"` and `"bbbbbbbbbb"`. This compresses to `"ab12"`.

Constraints:

- `1 <= chars.length <= 2000`
- `chars[i]` is a lowercase English letter, uppercase English letter, digit, or symbol.

445. Add Two Numbers II




Medium

3976236Add to ListShare

You are given two **non-empty** linked lists representing two non-negative integers. The most significant digit comes first and each of their nodes contains a single digit. Add the two numbers and return the sum as a linked list.

You may assume the two numbers do not contain any leading zero, except the number 0 itself.

Example 1:



Input: $l1 = [7, 2, 4, 3]$, $l2 = [5, 6, 4]$

Output: $[7, 8, 0, 7]$

Example 2:

Input: $l1 = [2, 4, 3]$, $l2 = [5, 6, 4]$

Output: $[8, 0, 7]$

Example 3:

Input: $l1 = [0]$, $l2 = [0]$

Output: $[0]$

Constraints:

- The number of nodes in each linked list is in the range `[1, 100]`.
- `0 <= Node.val <= 9`
- It is guaranteed that the list represents a number that does not have leading zeros.

446. Arithmetic Slices II - Subsequence

Hard

147890Add to ListShare

Given an integer array `nums`, return *the number of all the arithmetic subsequences of `nums`*.

A sequence of numbers is called arithmetic if it consists of **at least three elements** and if the difference between any two consecutive elements is the same.

- For example, `[1, 3, 5, 7, 9]`, `[7, 7, 7, 7]`, and `[3, -1, -5, -9]` are arithmetic sequences.
- For example, `[1, 1, 2, 5, 7]` is not an arithmetic sequence.

A **subsequence** of an array is a sequence that can be formed by removing some elements (possibly none) of the array.

- For example, `[2, 5, 10]` is a subsequence of `[1, 2, 1, 2, 4, 1, 5, 10]`.

The test cases are generated so that the answer fits in **32-bit** integer.

Example 1:

Input: `nums = [2,4,6,8,10]`

Output: 7

Explanation: All arithmetic subsequence slices are:

`[2,4,6]`

`[4,6,8]`

`[6,8,10]`

`[2,4,6,8]`

`[4,6,8,10]`

`[2,4,6,8,10]`

`[2,6,10]`

Example 2:**Input:** nums = [7,7,7,7,7]**Output:** 16**Explanation:** Any subsequence of this array is arithmetic.**Constraints:**

- $1 \leq \text{nums.length} \leq 1000$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

447. Number of Boomerangs**Medium**

673918Add to ListShare

You are given `n` points in the plane that are all **distinct**, where `points[i] = [xi, yi]`.A **boomerang** is a tuple of points `(i, j, k)` such that the distance between `i` and `j` equals the distance between `i` and `k` (**the order of the tuple matters**).Return *the number of boomerangs*.**Example 1:****Input:** points = [[0,0],[1,0],[2,0]]**Output:** 2**Explanation:** The two boomerangs are [[1,0],[0,0],[2,0]] and [[1,0],[2,0],[0,0]].**Example 2:****Input:** points = [[1,1],[2,2],[3,3]]**Output:** 2**Example 3:****Input:** points = [[1,1]]**Output:** 0**Constraints:**

- `n == points.length`
- `1 <= n <= 500`
- `points[i].length == 2`
- `-104 <= xi, yi <= 104`
- All the points are **unique**.

448. Find All Numbers Disappeared in an Array

Easy

7375408Add to ListShare

Given an array `nums` of `n` integers where `nums[i]` is in the range `[1, n]`, return *an array of all the integers in the range `[1, n]` that do not appear in `nums`*.

Example 1:

Input: `nums = [4,3,2,7,8,2,3,1]`

Output: `[5,6]`

Example 2:

Input: `nums = [1,1]`

Output: `[2]`

Constraints:

- `n == nums.length`
- `1 <= n <= 105`
- `1 <= nums[i] <= n`

449. Serialize and Deserialize BST

Medium

2978143Add to ListShare

Serialization is converting a data structure or object into a sequence of bits so that it can be stored in a file or memory buffer, or transmitted across a network connection link to be reconstructed later in the same or another computer environment.

Design an algorithm to serialize and deserialize a **binary search tree**. There is no restriction on how your serialization/deserialization algorithm should work. You need to ensure that a binary search tree can be serialized to a string, and this string can be deserialized to the original tree structure.

The encoded string should be as compact as possible.

Example 1:

Input: root = [2,1,3]

Output: [2,1,3]

Example 2:

Input: root = []

Output: []

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^4$
- The input tree is **guaranteed** to be a binary search tree.

450. Delete Node in a BST

Medium

6307166Add to ListShare


Given a root node reference of a BST and a key, delete the node with the given key in the BST.

Return *the root node reference (possibly updated) of the BST*.

Basically, the deletion can be divided into two stages:

1. Search for a node to remove.
2. If the node is found, delete the node.

Example 1:




Input: root = [5,3,6,2,4,null,7], key = 3

Output: [5,4,6,2,null,null,7]

Explanation: Given key to delete is 3. So we find the node with value 3 and delete it.

One valid answer is [5,4,6,2,null,null,7], shown in the above BST.

Please notice that another valid answer is [5,2,6,null,4,null,7] and it's also accepted.



Example 2:

Input: root = [5,3,6,2,4,null,7], key = 0

Output: [5,3,6,2,4,null,7]

Explanation: The tree does not contain a node with value = 0.

Example 3:

Input: root = [], key = 0

Output: []

Constraints:

- The number of nodes in the tree is in the range [0, 10⁴].
- -10⁵ <= Node.val <= 10⁵
- Each node has a **unique** value.
- root is a valid binary search tree.
- -10⁵ <= key <= 10⁵

451. Sort Characters By Frequency

Medium

4870193Add to ListShare

Given a string s, sort it in **decreasing order** based on the **frequency** of the characters. The **frequency** of a character is the number of times it appears in the string.

Return *the sorted string*. If there are multiple answers, return *any of them*.

Example 1:

Input: s = "tree"

Output: "eert"

Explanation: 'e' appears twice while 'r' and 't' both appear once.

So 'e' must appear before both 'r' and 't'. Therefore "eetr" is also a valid answer.

Example 2:

Input: s = "cccaaa"

Output: "aaaccc"

Explanation: Both 'c' and 'a' appear three times, so both "cccaaa" and "aaaccc" are valid answers.

Note that "cacaca" is incorrect, as the same characters must be together.

Example 3:

Input: s = "Aabb"

Output: "bbAa"

Explanation: "bbaA" is also a valid answer, but "Aabb" is incorrect.

Note that 'A' and 'a' are treated as two different characters.

Constraints:

- $1 \leq s.length \leq 5 * 10^5$
- s consists of uppercase and lowercase English letters and digits.

452. Minimum Number of Arrows to Burst Balloons

Medium

3787108Add to ListShare

There are some spherical balloons taped onto a flat wall that represents the XY-plane. The balloons are represented as a 2D integer array `points` where `points[i] = [xstart, xend]` denotes a balloon whose **horizontal diameter** stretches between `xstart` and `xend`. You do not know the exact y-coordinates of the balloons.

Arrows can be shot up **directly vertically** (in the positive y-direction) from different points along the x-axis. A balloon with `xstart` and `xend` is **burst** by an arrow shot at `x` if `xstart \leq x \leq xend`. There is **no limit** to the number of arrows that can be shot. A shot arrow keeps traveling up infinitely, bursting any balloons in its path.

Given the array `points`, return the **minimum** number of arrows that must be shot to burst all balloons.

Example 1:

Input: `points = [[10,16],[2,8],[1,6],[7,12]]`

Output: 2

Explanation: The balloons can be burst by 2 arrows:

- Shoot an arrow at $x = 6$, bursting the balloons `[2,8]` and `[1,6]`.
- Shoot an arrow at $x = 11$, bursting the balloons `[10,16]` and `[7,12]`.

Example 2:

Input: `points = [[1,2],[3,4],[5,6],[7,8]]`

Output: 4

Explanation: One arrow needs to be shot for each balloon for a total of 4 arrows.

Example 3:

Input: points = [[1,2],[2,3],[3,4],[4,5]]

Output: 2

Explanation: The balloons can be burst by 2 arrows:

- Shoot an arrow at $x = 2$, bursting the balloons [1,2] and [2,3].
- Shoot an arrow at $x = 4$, bursting the balloons [3,4] and [4,5].

Constraints:

- $1 \leq \text{points.length} \leq 10^5$
- $\text{points}[i].length == 2$
- $-2^{31} \leq x_{\text{start}} < x_{\text{end}} \leq 2^{31} - 1$

453. Minimum Moves to Equal Array Elements

Medium

18771752Add to ListShare

Given an integer array `nums` of size `n`, return *the minimum number of moves required to make all array elements equal*.

In one move, you can increment `n - 1` elements of the array by 1.

Example 1:

Input: nums = [1,2,3]

Output: 3

Explanation: Only three moves are needed (remember each move increments two elements):

[1,2,3] \Rightarrow [2,3,3] \Rightarrow [3,4,3] \Rightarrow [4,4,4]

Example 2:

Input: nums = [1,1,1]

Output: 0

Constraints:

- $n == \text{nums.length}$
- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- The answer is guaranteed to fit in a **32-bit** integer.

454. 4Sum II**Medium**

4119120Add to ListShare

Given four integer arrays `nums1`, `nums2`, `nums3`, and `nums4` all of length `n`, return the number of tuples `(i, j, k, l)` such that:

- $0 \leq i, j, k, l < n$
- $\text{nums1}[i] + \text{nums2}[j] + \text{nums3}[k] + \text{nums4}[l] == 0$

Example 1:

Input: `nums1 = [1,2]`, `nums2 = [-2,-1]`, `nums3 = [-1,2]`, `nums4 = [0,2]`

Output: 2

Explanation:

The two tuples are:

1. $(0, 0, 0, 1) \rightarrow \text{nums1}[0] + \text{nums2}[0] + \text{nums3}[0] + \text{nums4}[1] = 1 + (-2) + (-1) + 2 = 0$
2. $(1, 1, 0, 0) \rightarrow \text{nums1}[1] + \text{nums2}[1] + \text{nums3}[0] + \text{nums4}[0] = 2 + (-1) + (-1) + 0 = 0$

Example 2:

Input: `nums1 = [0]`, `nums2 = [0]`, `nums3 = [0]`, `nums4 = [0]`

Output: 1

Constraints:

- $n == \text{nums1.length}$
- $n == \text{nums2.length}$
- $n == \text{nums3.length}$
- $n == \text{nums4.length}$
- $1 \leq n \leq 200$

- $-2^{28} \leq \text{nums1}[i], \text{nums2}[i], \text{nums3}[i], \text{nums4}[i] \leq 2^{28}$

455. Assign Cookies

Easy

1747183Add to ListShare

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor $g[i]$, which is the minimum size of a cookie that the child will be content with; and each cookie j has a size $s[j]$. If $s[j] \geq g[i]$, we can assign the cookie j to the child i , and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input: $g = [1,2,3]$, $s = [1,1]$

Output: 1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Example 2:

Input: $g = [1,2]$, $s = [1,2,3]$

Output: 2

Explanation: You have 2 children and 3 cookies. The greed factors of 2 children are 1, 2.

You have 3 cookies and their sizes are big enough to gratify all of the children,

You need to output 2.

Constraints:

- $1 \leq g.length \leq 3 * 10^4$
- $0 \leq s.length \leq 3 * 10^4$
- $1 \leq g[i], s[j] \leq 2^{31} - 1$

456. 132 Pattern

Medium

5085287Add to ListShare

Given an array of n integers `nums`, a **132 pattern** is a subsequence of three integers `nums[i]`, `nums[j]` and `nums[k]` such that $i < j < k$ and $nums[i] < nums[k] < nums[j]$.

Return `true` if there is a **132 pattern** in `nums`, otherwise, return `false`.

Example 1:

Input: `nums = [1,2,3,4]`

Output: `false`

Explanation: There is no 132 pattern in the sequence.

Example 2:

Input: `nums = [3,1,4,2]`

Output: `true`

Explanation: There is a 132 pattern in the sequence: `[1, 4, 2]`.

Example 3:

Input: `nums = [-1,3,2,0]`

Output: `true`

Explanation: There are three 132 patterns in the sequence: `[-1, 3, 2]`, `[-1, 3, 0]` and `[-1, 2, 0]`.

Constraints:

- $n == \text{nums.length}$
- $1 \leq n \leq 2 * 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

457. Circular Array Loop

Medium

448409Add to ListShare

You are playing a game involving a **circular** array of non-zero integers `nums`. Each `nums[i]` denotes the number of indices forward/backward you must move if you are located at index `i`:

- If `nums[i]` is positive, move `nums[i]` steps **forward**, and
- If `nums[i]` is negative, move `nums[i]` steps **backward**.


Since the array is **circular**, you may assume that moving forward from the last element puts you on the first element, and moving backwards from the first element puts you on the last element.

A **cycle** in the array consists of a sequence of indices `seq` of length `k` where:

- Following the movement rules above results in the repeating index sequence `seq[0] -> seq[1] -> ... -> seq[k - 1] -> seq[0] -> ...`
- Every `nums[seq[j]]` is either **all positive** or **all negative**.
- `k > 1`

Return `true` if there is a **cycle** in `nums`, or `false` otherwise.

Example 1:




Input: `nums = [2, -1, 1, 2, 2]`

Output: `true`

Explanation: The graph shows how the indices are connected. White nodes are jumping forward, while red is jumping backward.

We can see the cycle `0 --> 2 --> 3 --> 0 --> ...`, and all of its nodes are white (jumping in the same direction).

Example 2:




Input: nums = [-1, -2, -3, -4, -5, 6]

Output: false

Explanation: The graph shows how the indices are connected. White nodes are jumping forward, while red is jumping backward.

The only cycle is of size 1, so we return false.

Example 3:



Input: nums = [1, -1, 5, 1, 4]

Output: true

Explanation: The graph shows how the indices are connected. White nodes are jumping forward, while red is jumping backward.

We can see the cycle $0 \rightarrow 1 \rightarrow 0 \rightarrow \dots$, and while it is of size > 1 , it has a node jumping forward and a node jumping backward, so **it is not a cycle**.

We can see the cycle $3 \rightarrow 4 \rightarrow 3 \rightarrow \dots$, and all of its nodes are white (jumping in the same direction).

Constraints:

- $1 \leq \text{nums.length} \leq 5000$
- $-1000 \leq \text{nums}[i] \leq 1000$
- $\text{nums}[i] \neq 0$

458. Poor Pigs

Hard

13032689 Add to List Share

There are `buckets` buckets of liquid, where **exactly one** of the buckets is poisonous. To figure out which one is poisonous, you feed some number of (poor) pigs the liquid to see whether they will die or not. Unfortunately, you only have `minutesToTest` minutes to determine which bucket is poisonous.

You can feed the pigs according to these steps:

1. Choose some live pigs to feed.
2. For each pig, choose which buckets to feed it. The pig will consume all the chosen buckets simultaneously and will take no time. Each pig can feed from any number of buckets, and each bucket can be fed from by any number of pigs.
3. Wait for `minutesToDie` minutes. You may **not** feed any other pigs during this time.
4. After `minutesToDie` minutes have passed, any pigs that have been fed the poisonous bucket will die, and all others will survive.
5. Repeat this process until you run out of time.

Given `buckets`, `minutesToDie`, and `minutesToTest`, return the **minimum** number of pigs needed to figure out which bucket is poisonous within the allotted time.

Example 1:

Input: `buckets = 4, minutesToDie = 15, minutesToTest = 15`

Output: 2

Explanation: We can determine the poisonous bucket as follows:

At time 0, feed the first pig buckets 1 and 2, and feed the second pig buckets 2 and 3.

At time 15, there are 4 possible outcomes:

- If only the first pig dies, then bucket 1 must be poisonous.
- If only the second pig dies, then bucket 3 must be poisonous.
- If both pigs die, then bucket 2 must be poisonous.
- If neither pig dies, then bucket 4 must be poisonous.

Example 2:

Input: buckets = 4, minutesToDie = 15, minutesToTest = 30

Output: 2

Explanation: We can determine the poisonous bucket as follows:

At time 0, feed the first pig bucket 1, and feed the second pig bucket 2.

At time 15, there are 2 possible outcomes:

- If either pig dies, then the poisonous bucket is the one it was fed.
- If neither pig dies, then feed the first pig bucket 3, and feed the second pig bucket 4.

At time 30, one of the two pigs must die, and the poisonous bucket is the one it was fed.

Constraints:

- $1 \leq \text{buckets} \leq 1000$
- $1 \leq \text{minutesToDie} \leq \text{minutesToTest} \leq 100$

459. Repeated Substring Pattern

Easy

3805351Add to ListShare

Given a string s , check if it can be constructed by taking a substring of it and appending multiple copies of the substring together.

Example 1:

Input: s = "abab"

Output: true

Explanation: It is the substring "ab" twice.

Example 2:

Input: s = "aba"

Output: false

Example 3:

Input: s = "abcababcabc"

Output: true

Explanation: It is the substring "abc" four times or the substring "abca" twice.

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of lowercase English letters.

460. LFU Cache

Hard

3753229Add to ListShare

Design and implement a data structure for a Least Frequently Used (LFU) cache.

Implement the `LFUCache` class:

- `LFUCache(int capacity)` Initializes the object with the `capacity` of the data structure.
- `int get(int key)` Gets the value of the `key` if the `key` exists in the cache. Otherwise, returns `-1`.
- `void put(int key, int value)` Update the value of the `key` if present, or inserts the `key` if not already present. When the cache reaches its `capacity`, it should invalidate and remove the **least frequently used** key before inserting a new item. For this problem, when there is a **tie** (i.e., two or more keys with the same frequency), the **least recently used** `key` would be invalidated.

To determine the least frequently used key, a **use counter** is maintained for each key in the cache. The key with the smallest **use counter** is the least frequently used key.

When a key is first inserted into the cache, its **use counter** is set to 1 (due to the `put` operation). The **use counter** for a key in the cache is incremented either a `get` or `put` operation is called on it.

The functions `get` and `put` must each run in $O(1)$ average time complexity.

Example 1:

Input

```
["LFUCache", "put", "put", "get", "put", "get", "get", "put", "get", "get", "get"]
[[2], [1, 1], [2, 2], [1], [3, 3], [2], [3], [4, 4], [1], [3], [4]]
```

Output

```
[null, null, null, 1, null, -1, 3, null, -1, 3, 4]
```

Explanation

```
// cnt(x) = the use counter for key x

// cache=[] will show the last used order for tiebreakers (leftmost element is most
recent)

LFUCache lfu = new LFUCache(2);

lfu.put(1, 1);    // cache=[1,_], cnt(1)=1

lfu.put(2, 2);    // cache=[2,1], cnt(2)=1, cnt(1)=1

lfu.get(1);       // return 1

                    // cache=[1,2], cnt(2)=1, cnt(1)=2

lfu.put(3, 3);    // 2 is the LFU key because cnt(2)=1 is the smallest, invalidate 2.

                    // cache=[3,1], cnt(3)=1, cnt(1)=2

lfu.get(2);       // return -1 (not found)

lfu.get(3);       // return 3

                    // cache=[3,1], cnt(3)=2, cnt(1)=2

lfu.put(4, 4);    // Both 1 and 3 have the same cnt, but 1 is LRU, invalidate 1.

                    // cache=[4,3], cnt(4)=1, cnt(3)=2

lfu.get(1);       // return -1 (not found)
```

```

lfu.get(3);      // return 3
                // cache=[3,4], cnt(4)=1, cnt(3)=3

lfu.get(4);      // return 4
                // cache=[4,3], cnt(4)=2, cnt(3)=3

```

Constraints:

- $0 \leq \text{capacity} \leq 10^4$
- $0 \leq \text{key} \leq 10^5$
- $0 \leq \text{value} \leq 10^9$
- At most $2 * 10^5$ calls will be made to `get` and `put`.

461. Hamming Distance

Easy

3279202Add to ListShare

The Hamming distance between two integers is the number of positions at which the corresponding bits are different.

Given two integers `x` and `y`, return *the Hamming distance between them*.

Example 1:

Input: `x = 1, y = 4`

Output: 2

Explanation:

1 (0 0 0 1)

4 (0 1 0 0)

↑ ↑

The above arrows point to positions where the corresponding bits are different.

Example 2:

Input: `x = 3, y = 1`

Output: 1

Constraints:

- $0 \leq x, y \leq 2^{31} - 1$

462. Minimum Moves to Equal Array Elements II

Medium

2761106Add to ListShare

Given an integer array `nums` of size `n`, return *the minimum number of moves required to make all array elements equal*.

In one move, you can increment or decrement an element of the array by 1.

Test cases are designed so that the answer will fit in a **32-bit** integer.

Example 1:

Input: `nums` = [1,2,3]

Output: 2

Explanation:

Only two moves are needed (remember each move increments or decrements one element):

[1,2,3] \Rightarrow [2,2,3] \Rightarrow [2,2,2]

Example 2:

Input: `nums` = [1,10,2,9]

Output: 16

Constraints:

- $n == \text{nums.length}$
- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

463. Island Perimeter

Easy


4958254Add to ListShare

You are given `row x col grid` representing a map where `grid[i][j] = 1` represents land and `grid[i][j] = 0` represents water.

Grid cells are connected **horizontally/vertically** (not diagonally). The `grid` is completely surrounded by water, and there is exactly one island (i.e., one or more connected land cells).

The island doesn't have "lakes", meaning the water inside isn't connected to the water around the island. One cell is a square with side length 1. The grid is rectangular, width and height don't exceed 100. Determine the perimeter of the island.

Example 1:



Input: `grid = [[0,1,0,0],[1,1,1,0],[0,1,0,0],[1,1,0,0]]`

Output: 16

Explanation: The perimeter is the 16 yellow stripes in the image above.

Example 2:

Input: `grid = [[1]]`

Output: 4

Example 3:

Input: `grid = [[1,0]]`

Output: 4

Constraints:

- `row == grid.length`

- `col == grid[i].length`
- `1 <= row, col <= 100`
- `grid[i][j]` is `0` or `1`.
- There is exactly one island in `grid`.

464. Can I Win

Medium

2082321Add to ListShare

In the "100 game" two players take turns adding, to a running total, any integer from `1` to `10`. The player who first causes the running total to **reach or exceed** `100` wins.

What if we change the game so that players **cannot** re-use integers?

For example, two players might take turns drawing from a common pool of numbers from `1` to `15` without replacement until they reach a total ≥ 100 .

Given two integers `maxChoosableInteger` and `desiredTotal`, return `true` if the first player to move can force a win, otherwise, return `false`. Assume both players play **optimally**.

Example 1:

Input: `maxChoosableInteger = 10, desiredTotal = 11`

Output: `false`

Explanation:

No matter which integer the first player choose, the first player will lose.

The first player can choose an integer from `1` up to `10`.

If the first player choose `1`, the second player can only choose integers from `2` up to `10`.

The second player will win by choosing `10` and get a total = `11`, which is \geq `desiredTotal`.

Same with other integers chosen by the first player, the second player will always win.

Example 2:

Input: `maxChoosableInteger = 10, desiredTotal = 0`

Output: `true`

Example 3:

Input: maxChoosableInteger = 10, desiredTotal = 1

Output: true

Constraints:

- $1 \leq \text{maxChoosableInteger} \leq 20$
- $0 \leq \text{desiredTotal} \leq 300$

466. Count The Repetitions

Hard

335285Add to ListShare

We define `str = [s, n]` as the string `str` which consists of the string `s` concatenated `n` times.

- For example, `str == ["abc", 3] == "abcabcabc"`.

We define that string `s1` can be obtained from string `s2` if we can remove some characters from `s2` such that it becomes `s1`.

- For example, `s1 = "abc"` can be obtained from `s2 = "abdbcc"` based on our definition by removing the bolded underlined characters.

You are given two strings `s1` and `s2` and two integers `n1` and `n2`. You have the two strings `str1 = [s1, n1]` and `str2 = [s2, n2]`.

Return *the maximum integer m such that str = [str2, m] can be obtained from str1*.

Example 1:

Input: `s1 = "acb", n1 = 4, s2 = "ab", n2 = 2`

Output: 2

Example 2:

Input: `s1 = "acb", n1 = 1, s2 = "acb", n2 = 1`

Output: 1

Constraints:

- $1 \leq s1.length, s2.length \leq 100$

- `s1` and `s2` consist of lowercase English letters.
- $1 \leq n1, n2 \leq 10^6$

467. Unique Substrings in Wraparound String

Medium

1194147Add to ListShare

We define the string `s` to be the infinite wraparound string of `"abcdefghijklmnopqrstuvwxyz"`, so `s` will look like this:

- `....zabcdefghijklmnopqrstuvwxyzabcdefghijklmnopqrstuvwxyzabcdefghijklmnopqrstuvwxyz....`.

Given a string `p`, return *the number of unique non-empty substrings of `p` are present in `s`*.

Example 1:

Input: `p = "a"`

Output: 1

Explanation: Only the substring "a" of `p` is in `s`.

Example 2:

Input: `p = "cac"`

Output: 2

Explanation: There are two substrings ("a", "c") of `p` in `s`.

Example 3:

Input: `p = "zab"`

Output: 6

Explanation: There are six substrings ("z", "a", "b", "za", "ab", and "zab") of `p` in `s`.

Constraints:

- $1 \leq p.length \leq 10^5$
- `p` consists of lowercase English letters.

468. Validate IP Address

Medium

7592476Add to ListShare

Given a string `queryIP`, return "IPv4" if IP is a valid IPv4 address, "IPv6" if IP is a valid IPv6 address or "Neither" if IP is not a correct IP of any type.

A valid IPv4 address is an IP in the form "`x1.x2.x3.x4`" where $0 \leq x_i \leq 255$ and `xi` **cannot contain** leading zeros. For example, "192.168.1.1" and "192.168.1.0" are valid IPv4 addresses while "192.168.01.1", "192.168.1.00", and "192.168@1.1" are invalid IPv4 addresses.

A valid IPv6 address is an IP in the form "`x1:x2:x3:x4:x5:x6:x7:x8`" where:

- $1 \leq x_i.length \leq 4$
- `xi` is a **hexadecimal string** which may contain digits, lowercase English letter ('a' to 'f') and upper-case English letters ('A' to 'F').
- Leading zeros are allowed in `xi`.

For example, "2001:0db8:85a3:0000:0000:8a2e:0370:7334" and "2001:db8:85a3:0:0:8A2E:0370:7334" are valid IPv6 addresses, while "2001:0db8:85a3::8A2E:037j:7334" and "02001:0db8:85a3:0000:0000:8a2e:0370:7334" are invalid IPv6 addresses.

Example 1:

Input: `queryIP` = "172.16.254.1"

Output: "IPv4"

Explanation: This is a valid IPv4 address, return "IPv4".

Example 2:

Input: `queryIP` = "2001:0db8:85a3:0:0:8A2E:0370:7334"

Output: "IPv6"

Explanation: This is a valid IPv6 address, return "IPv6".

Example 3:

Input: `queryIP` = "256.256.256.256"

Output: "Neither"

Explanation: This is neither a IPv4 address nor a IPv6 address.

Constraints:

- `queryIP` consists only of English letters, digits and the characters `'.'` and `'.'`.

470. Implement Rand10() Using Rand7()**Medium**

927310Add to ListShare

Given the **API** `rand7()` that generates a uniform random integer in the range `[1, 7]`, write a function `rand10()` that generates a uniform random integer in the range `[1, 10]`. You can only call the API `rand7()`, and you shouldn't call any other API. Please **do not** use a language's built-in random API.

Each test case will have one **internal** argument `n`, the number of times that your implemented function `rand10()` will be called while testing. Note that this is **not an argument** passed to `rand10()`.

Example 1:**Input:** `n = 1`**Output:** `[2]`**Example 2:****Input:** `n = 2`**Output:** `[2,8]`**Example 3:****Input:** `n = 3`**Output:** `[3,8,10]`**Constraints:**

- `1 <= n <= 105`

472. Concatenated Words**Hard**

2262233Add to ListShare

Given an array of strings `words` (**without duplicates**), return *all the concatenated words in the given list of words*.

A **concatenated word** is defined as a string that is comprised entirely of at least two shorter words in the given array.

Example 1:

Input: `words = ["cat", "cats", "catsdogcats", "dog", "dogcatsdog", "hippopotamuses", "rat", "ratcatdogcat"]`

Output: `["catsdogcats", "dogcatsdog", "ratcatdogcat"]`

Explanation: "catsdogcats" can be concatenated by "cats", "dog" and "cats";

"dogcatsdog" can be concatenated by "dog", "cats" and "dog";

"ratcatdogcat" can be concatenated by "rat", "cat", "dog" and "cat".

Example 2:

Input: `words = ["cat", "dog", "catdog"]`

Output: `["catdog"]`

Constraints:

- `1 <= words.length <= 104`
- `1 <= words[i].length <= 30`
- `words[i]` consists of only lowercase English letters.
- All the strings of `words` are **unique**.
- `1 <= sum(words[i].length) <= 105`

473. Matchsticks to Square


Medium

3231255Add to ListShare

You are given an integer array `matchsticks` where `matchsticks[i]` is the length of the `ith` matchstick. You want to use **all the matchsticks** to make one square. You **should not break** any stick, but you can link them up, and each matchstick must be used **exactly one time**.

Return `true` if you can make this square and `false` otherwise.

Example 1:



Input: matchsticks = [1,1,2,2,2]

Output: true

Explanation: You can form a square with length 2, one side of the square came two sticks with length 1.

Example 2:

Input: matchsticks = [3,3,3,3,4]

Output: false

Explanation: You cannot find a way to form a square with all the matchsticks.

Constraints:

- $1 \leq \text{matchsticks.length} \leq 15$
- $1 \leq \text{matchsticks}[i] \leq 10^8$

474. Ones and Zeroes

Medium

4420408Add to ListShare

You are given an array of binary strings `strs` and two integers `m` and `n`.

Return *the size of the largest subset of `strs` such that there are **at most** `m` 0's and `n` 1's in the subset.*

A set `x` is a **subset** of a set `y` if all elements of `x` are also elements of `y`.

Example 1:

Input: `strs = ["10", "0001", "111001", "1", "0"]`, `m = 5`, `n = 3`

Output: 4

Explanation: The largest subset with at most 5 0's and 3 1's is `{"10", "0001", "1", "0"}`, so the answer is 4.

Other valid but smaller subsets include `{"0001", "1"}` and `{"10", "1", "0"}`.

`{"111001"}` is an invalid subset because it contains 4 1's, greater than the maximum of 3.

Example 2:

Input: `strs = ["10", "0", "1"]`, `m = 1`, `n = 1`

Output: 2

Explanation: The largest subset is `{"0", "1"}`, so the answer is 2.

Constraints:

- `1 <= strs.length <= 600`
- `1 <= strs[i].length <= 100`
- `strs[i]` consists only of digits '0' and '1'.
- `1 <= m, n <= 100`

475. Heaters

Medium

15371069Add to ListShare

Winter is coming! During the contest, your first job is to design a standard heater with a fixed warm radius to warm all the houses.

Every house can be warmed, as long as the house is within the heater's warm radius range.

Given the positions of `houses` and `heaters` on a horizontal line, return *the minimum radius standard of heaters so that those heaters could cover all houses*.

Notice that all the `heaters` follow your radius standard, and the warm radius will be the same.

Example 1:

Input: `houses = [1,2,3]`, `heaters = [2]`

Output: 1

Explanation: The only heater was placed in the position 2, and if we use the radius 1 standard, then all the houses can be warmed.

Example 2:

Input: houses = [1,2,3,4], heaters = [1,4]

Output: 1

Explanation: The two heater was placed in the position 1 and 4. We need to use radius 1 standard, then all the houses can be warmed.

Example 3:

Input: houses = [1,5], heaters = [2]

Output: 3

Constraints:

- $1 \leq \text{houses.length}, \text{heaters.length} \leq 3 * 10^4$
- $1 \leq \text{houses}[i], \text{heaters}[i] \leq 10^9$

476. Number Complement

Easy

2178108Add to ListShare

The **complement** of an integer is the integer you get when you flip all the 0's to 1's and all the 1's to 0's in its binary representation.

- For example, The integer 5 is "101" in binary and its **complement** is "010" which is the integer 2.

Given an integer `num`, return *its complement*.

Example 1:

Input: num = 5

Output: 2

Explanation: The binary representation of 5 is 101 (no leading zero bits), and its complement is 010. So you need to output 2.

Example 2:

Input: num = 1

Output: 0

Explanation: The binary representation of 1 is 1 (no leading zero bits), and its complement is 0. So you need to output 0.

Constraints:

- $1 \leq \text{num} < 2^{31}$

477. Total Hamming Distance

Medium

180183Add to ListShare

The Hamming distance between two integers is the number of positions at which the corresponding bits are different.

Given an integer array `nums`, return *the sum of Hamming distances between all the pairs of the integers in `nums`*.

Example 1:

Input: nums = [4,14,2]

Output: 6

Explanation: In binary representation, the 4 is 0100, 14 is 1110, and 2 is 0010 (just showing the four bits relevant in this case).

The answer will be:

`HammingDistance(4, 14) + HammingDistance(4, 2) + HammingDistance(14, 2) = 2 + 2 + 2 = 6.`

Example 2:

Input: nums = [4,14,4]

Output: 4

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $0 \leq \text{nums}[i] \leq 10^9$
- The answer for the given input will fit in a **32-bit** integer.

478. Generate Random Point in a Circle**Medium**

38699Add to ListShare

Given the radius and the position of the center of a circle, implement the function `randPoint` which generates a uniform random point inside the circle.

Implement the `Solution` class:

- `Solution(double radius, double x_center, double y_center)` initializes the object with the radius of the circle `radius` and the position of the center `(x_center, y_center)`.
- `randPoint()` returns a random point inside the circle. A point on the circumference of the circle is considered to be in the circle. The answer is returned as an array `[x, y]`.

Example 1:**Input**

```
["Solution", "randPoint", "randPoint", "randPoint"]
[[1.0, 0.0, 0.0], [], [], []]
```

Output

```
[null, [-0.02493, -0.38077], [0.82314, 0.38945], [0.36572, 0.17248]]
```

Explanation

```
Solution solution = new Solution(1.0, 0.0, 0.0);
solution.randPoint(); // return [-0.02493, -0.38077]
solution.randPoint(); // return [0.82314, 0.38945]
solution.randPoint(); // return [0.36572, 0.17248]
```

Constraints:

- $0 < \text{radius} \leq 10^8$
- $-10^7 \leq \text{x_center}, \text{y_center} \leq 10^7$
- At most $3 * 10^4$ calls will be made to `randPoint`.

479. Largest Palindrome Product

Hard

1381478Add to ListShare

Given an integer n , return the **largest palindromic integer** that can be represented as the product of two n -digits integers. Since the answer can be very large, return it **modulo 1337**.

Example 1:

Input: $n = 2$

Output: 987

Explanation: $99 \times 91 = 9009$, $9009 \% 1337 = 987$

Example 2:

Input: $n = 1$

Output: 9

Constraints:

- $1 \leq n \leq 8$

480. Sliding Window Median

Hard

2496146Add to ListShare

The **median** is the middle value in an ordered integer list. If the size of the list is even, there is no middle value. So the median is the mean of the two middle values.

- For examples, if $\text{arr} = [2, 3, 4]$, the median is 3.
- For examples, if $\text{arr} = [1, 2, 3, 4]$, the median is $(2 + 3) / 2 = 2.5$.

You are given an integer array `nums` and an integer `k`. There is a sliding window of size `k` which is moving from the very left of the array to the very right. You can only see the `k` numbers in the window. Each time the sliding window moves right by one position.

Return the median array for each window in the original array. Answers within 10^{-5} of the actual value will be accepted.

Example 1:

Input: nums = [1,3,-1,-3,5,3,6,7], k = 3

Output: [1.00000, -1.00000, -1.00000, 3.00000, 5.00000, 6.00000]

Explanation:

Window position	Median
-----	-----
[1 3 -1] -3 5 3 6 7	1
1 [3 -1 -3] 5 3 6 7	-1
1 3 [-1 -3 5] 3 6 7	-1
1 3 -1 [-3 5 3] 6 7	3
1 3 -1 -3 [5 3 6] 7	5
1 3 -1 -3 5 [3 6 7]	6

Example 2:

Input: nums = [1,2,3,4,2,3,1,4,2], k = 3

Output: [2.00000, 3.00000, 3.00000, 3.00000, 2.00000, 3.00000, 2.00000]

Constraints:

- $1 \leq k \leq \text{nums.length} \leq 10^5$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

481. Magical String

Medium

2081017Add to ListShare

A magical string s consists of only '1' and '2' and obeys the following rules:

- The string s is magical because concatenating the number of contiguous occurrences of characters '1' and '2' generates the string s itself.

The first few elements of s is $s = "1221121221221121122....."$. If we group the consecutive 1's and 2's in s , it will be "1 22 11 2 1 22 1 22 11 2 11 22 " and the occurrences of 1's

or 2's in each group are "1 2 2 1 1 2 1 2 2 1 2 2". You can see that the occurrence sequence is `s` itself.

Given an integer `n`, return the number of 1's in the first `n` number in the magical string `s`.

Example 1:

Input: `n` = 6

Output: 3

Explanation: The first 6 elements of magical string `s` is "122112" and it contains three 1's, so return 3.

Example 2:

Input: `n` = 1

Output: 1

Constraints:

- `1 <= n <= 105`

482. License Key Formatting

Easy

8481170Add to ListShare

You are given a license key represented as a string `s` that consists of only alphanumeric characters and dashes. The string is separated into `n + 1` groups by `n` dashes. You are also given an integer `k`.

We want to reformat the string `s` such that each group contains exactly `k` characters, except for the first group, which could be shorter than `k` but still must contain at least one character. Furthermore, there must be a dash inserted between two groups, and you should convert all lowercase letters to uppercase.

Return *the reformatted license key*.

Example 1:

Input: `s` = "5F3Z-2e-9-w", `k` = 4

Output: "5F3Z-2E9W"

Explanation: The string `s` has been split into two parts, each part has 4 characters.

Note that the two extra dashes are not needed and can be removed.

Example 2:

Input: `s = "2-5g-3-J"`, `k = 2`

Output: `"2-5G-3J"`

Explanation: The string `s` has been split into three parts, each part has 2 characters except the first part as it could be shorter as mentioned above.

Constraints:

- `1 <= s.length <= 105`
- `s` consists of English letters, digits, and dashes `'-'`.
- `1 <= k <= 104`

483. Smallest Good Base

Hard

300449Add to ListShare

Given an integer `n` represented as a string, return *the smallest **good base** of n*.

We call `k >= 2` a **good base** of `n`, if all digits of `n` base `k` are 1's.

Example 1:

Input: `n = "13"`

Output: `"3"`

Explanation: `13` base `3` is `111`.

Example 2:

Input: `n = "4681"`

Output: `"8"`

Explanation: `4681` base `8` is `11111`.

Example 3:

Input: `n = "10000000000000000000000000"`

Output: "999999999999999999"

Explanation: 10000000000000000000 base 9999999999999999 is 11.

Constraints:

- `n` is an integer in the range $[3, 10^{18}]$.
- `n` does not contain any leading zeros.

485. Max Consecutive Ones

Easy

3403409Add to ListShare

Given a binary array `nums`, return *the maximum number of consecutive 1's in the array*.

Example 1:

Input: `nums = [1,1,0,1,1,1]`

Output: 3

Explanation: The first two digits or the last three digits are consecutive 1s. The maximum number of consecutive 1s is 3.

Example 2:

Input: `nums = [1,0,1,1,0,1]`

Output: 2

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- `nums[i]` is either 0 or 1.

486. Predict the Winner

Medium

3385160Add to ListShare

You are given an integer array `nums`. Two players are playing a game with this array: player 1 and player 2.

Player 1 and player 2 take turns, with player 1 starting first. Both players start the game with a score of 0. At each turn, the player takes one of the numbers from either end of the array (i.e., `nums[0]` or `nums[nums.length - 1]`) which reduces the size of the array by 1. The player adds the chosen number to their score. The game ends when there are no more elements in the array.

Return `true` if Player 1 can win the game. If the scores of both players are equal, then player 1 is still the winner, and you should also return `true`. You may assume that both players are playing optimally.

Example 1:

Input: `nums = [1,5,2]`

Output: `false`

Explanation: Initially, player 1 can choose between 1 and 2.

If he chooses 2 (or 1), then player 2 can choose from 1 (or 2) and 5. If player 2 chooses 5, then player 1 will be left with 1 (or 2).

So, final score of player 1 is $1 + 2 = 3$, and player 2 is 5.

Hence, player 1 will never be the winner and you need to return `false`.

Example 2:

Input: `nums = [1,5,233,7]`

Output: `true`

Explanation: Player 1 first chooses 1. Then player 2 has to choose between 5 and 7. No matter which number player 2 choose, player 1 can choose 233.

Finally, player 1 has more score (234) than player 2 (12), so you need to return `True` representing player1 can win.

Constraints:

- $1 \leq \text{nums.length} \leq 20$
- $0 \leq \text{nums}[i] \leq 10^7$

488. Zuma Game

Hard

369435Add to ListShare

You are playing a variation of the game Zuma.

In this variation of Zuma, there is a **single row** of colored balls on a board, where each ball can be colored red '`R`', yellow '`Y`', blue '`B`', green '`G`', or white '`W`'. You also have several colored balls in your hand.

Your goal is to **clear all** of the balls from the board. On each turn:

- Pick **any** ball from your hand and insert it in between two balls in the row or on either end of the row.
- If there is a group of **three or more consecutive balls** of the **same color**, remove the group of balls from the board.
 - If this removal causes more groups of three or more of the same color to form, then continue removing each group until there are none left.
- If there are no more balls on the board, then you win the game.
- Repeat this process until you either win or do not have any more balls in your hand.

Given a string `board`, representing the row of balls on the board, and a string `hand`, representing the balls in your hand, return *the minimum number of balls you have to insert to clear all the balls from the board. If you cannot clear all the balls from the board using the balls in your hand, return `-1`.*

Example 1:

Input: `board = "WRRBBW", hand = "RB"`

Output: `-1`

Explanation: It is impossible to clear all the balls. The best you can do is:

- Insert '`R`' so the board becomes `WRRRBBW`. `WRRRBBW` → `WBBW`.
- Insert '`B`' so the board becomes `WBBBW`. `WBBBW` → `WW`.

There are still balls remaining on the board, and you are out of balls to insert.

Example 2:

Input: `board = "WWRRBBWW", hand = "WRBRW"`

Output: `2`

Explanation: To make the board empty:

- Insert '`R`' so the board becomes `WWRRRBBWW`. `WWRRRBBWW` → `WWBBWW`.
- Insert '`B`' so the board becomes `WWBBBW`. `WWBBBW` → `WWWW` → empty.

2 balls from your hand were needed to clear the board.

Example 3:

Input: board = "G", hand = "GGGGG"

Output: 2

Explanation: To make the board empty:

- Insert 'G' so the board becomes GG.
- Insert 'G' so the board becomes GGG. GGG -> empty.

2 balls from your hand were needed to clear the board.

Constraints:

- `1 <= board.length <= 16`
- `1 <= hand.length <= 5`
- `board` and `hand` consist of the characters '`R`', '`Y`', '`B`', '`G`', and '`W`'.
- The initial row of balls on the board will **not** have any groups of three or more consecutive balls of the same color.

491. Increasing Subsequences

Medium

1701155Add to ListShare

Given an integer array `nums`, return all the different possible increasing subsequences of the given array with **at least two elements**. You may return the answer in **any order**.

The given array may contain duplicates, and two equal integers should also be considered a special case of increasing sequence.

Example 1:

Input: `nums = [4,6,7,7]`

Output: `[[4,6],[4,6,7],[4,6,7,7],[4,7],[4,7,7],[6,7],[6,7,7],[7,7]]`

Example 2:

Input: `nums = [4,4,3,2,1]`

Output: `[[4,4]]`

Constraints:

- $1 \leq \text{nums.length} \leq 15$
- $-100 \leq \text{nums}[i] \leq 100$

492. Construct the Rectangle**Easy**

473340Add to ListShare

A web developer needs to know how to design a web page's size. So, given a specific rectangular web page's area, your job by now is to design a rectangular web page, whose length L and width W satisfy the following requirements:

1. The area of the rectangular web page you designed must equal to the given target area.
2. The width W should not be larger than the length L , which means $L \geq W$.
3. The difference between length L and width W should be as small as possible.

Return an array $[L, W]$ where L and W are the length and width of the web page you designed in sequence.

Example 1:**Input:** area = 4**Output:** [2,2]

Explanation: The target area is 4, and all the possible ways to construct it are [1,4], [2,2], [4,1].

But according to requirement 2, [1,4] is illegal; according to requirement 3, [4,1] is not optimal compared to [2,2]. So the length L is 2, and the width W is 2.

Example 2:**Input:** area = 37**Output:** [37,1]**Example 3:****Input:** area = 122122**Output:** [427,286]**Constraints:**

- $1 \leq \text{area} \leq 10^7$

493. Reverse Pairs

Hard

3919206Add to ListShare

Given an integer array `nums`, return *the number of reverse pairs in the array*.

A **reverse pair** is a pair (i, j) where:

- $0 \leq i < j < \text{nums.length}$ and
- $\text{nums}[i] > 2 * \text{nums}[j]$.

Example 1:

Input: `nums = [1,3,2,3,1]`

Output: 2

Explanation: The reverse pairs are:

$(1, 4) \rightarrow \text{nums}[1] = 3, \text{nums}[4] = 1, 3 > 2 * 1$

$(3, 4) \rightarrow \text{nums}[3] = 3, \text{nums}[4] = 1, 3 > 2 * 1$

Example 2:

Input: `nums = [2,4,3,5,1]`

Output: 3

Explanation: The reverse pairs are:

$(1, 4) \rightarrow \text{nums}[1] = 4, \text{nums}[4] = 1, 4 > 2 * 1$

$(2, 4) \rightarrow \text{nums}[2] = 3, \text{nums}[4] = 1, 3 > 2 * 1$

$(3, 4) \rightarrow \text{nums}[3] = 5, \text{nums}[4] = 1, 5 > 2 * 1$

Constraints:

- $1 \leq \text{nums.length} \leq 5 * 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

494. Target Sum

Medium

8095293Add to ListShare

You are given an integer array `nums` and an integer `target`.

You want to build an **expression** out of `nums` by adding one of the symbols `'+'` and `'-'` before each integer in `nums` and then concatenate all the integers.

- For example, if `nums = [2, 1]`, you can add a `'+'` before `2` and a `'-'` before `1` and concatenate them to build the expression `"+2-1"`.

Return the number of different **expressions** that you can build, which evaluates to `target`.

Example 1:

Input: `nums = [1,1,1,1,1]`, `target = 3`

Output: 5

Explanation: There are 5 ways to assign symbols to make the sum of `nums` be `target` 3.

`-1 + 1 + 1 + 1 + 1 = 3`

`+1 - 1 + 1 + 1 + 1 = 3`

`+1 + 1 - 1 + 1 + 1 = 3`

`+1 + 1 + 1 - 1 + 1 = 3`

`+1 + 1 + 1 + 1 - 1 = 3`

Example 2:

Input: `nums = [1]`, `target = 1`

Output: 1

Constraints:

- `1 <= nums.length <= 20`
- `0 <= nums[i] <= 1000`
- `0 <= sum(nums[i]) <= 1000`
- `-1000 <= target <= 1000`

495. Teemo Attacking**Easy**

59554Add to ListShare

Our hero Teemo is attacking an enemy Ashe with poison attacks! When Teemo attacks Ashe, Ashe gets poisoned for a exactly `duration` seconds. More formally, an attack at second `t` will mean Ashe is poisoned during the **inclusive** time interval `[t, t + duration - 1]`. If Teemo attacks again **before** the poison effect ends, the timer for it is **reset**, and the poison effect will end `duration` seconds after the new attack.

You are given a **non-decreasing** integer array `timeSeries`, where `timeSeries[i]` denotes that Teemo attacks Ashe at second `timeSeries[i]`, and an integer `duration`.

Return *the total number of seconds that Ashe is poisoned*.

Example 1:

Input: `timeSeries = [1,4]`, `duration = 2`

Output: 4

Explanation: Teemo's attacks on Ashe go as follows:

- At second 1, Teemo attacks, and Ashe is poisoned for seconds 1 and 2.
- At second 4, Teemo attacks, and Ashe is poisoned for seconds 4 and 5.

Ashe is poisoned for seconds 1, 2, 4, and 5, which is 4 seconds in total.

Example 2:

Input: `timeSeries = [1,2]`, `duration = 2`

Output: 3

Explanation: Teemo's attacks on Ashe go as follows:

- At second 1, Teemo attacks, and Ashe is poisoned for seconds 1 and 2.
- At second 2 however, Teemo attacks again and resets the poison timer. Ashe is poisoned for seconds 2 and 3.

Ashe is poisoned for seconds 1, 2, and 3, which is 3 seconds in total.

Constraints:

- $1 \leq \text{timeSeries.length} \leq 10^4$
- $0 \leq \text{timeSeries}[i], \text{duration} \leq 10^7$
- `timeSeries` is sorted in **non-decreasing** order.

496. Next Greater Element I

Easy

4367264Add to ListShare

The **next greater element** of some element x in an array is the **first greater** element that is **to the right** of x in the same array.

You are given two **distinct 0-indexed** integer arrays nums1 and nums2 , where nums1 is a subset of nums2 .

For each $0 \leq i < \text{nums1.length}$, find the index j such that $\text{nums1}[i] == \text{nums2}[j]$ and determine the **next greater element** of $\text{nums2}[j]$ in nums2 . If there is no next greater element, then the answer for this query is -1 .

Return an array ans of length nums1.length such that $\text{ans}[i]$ is the **next greater element** as described above.

Example 1:

Input: $\text{nums1} = [4,1,2]$, $\text{nums2} = [1,3,4,2]$

Output: $[-1,3,-1]$

Explanation: The next greater element for each value of nums1 is as follows:

- 4 is underlined in $\text{nums2} = [1,3,\underline{4},2]$. There is no next greater element, so the answer is -1 .
- 1 is underlined in $\text{nums2} = [\underline{1},3,4,2]$. The next greater element is 3 .
- 2 is underlined in $\text{nums2} = [1,3,4,\underline{2}]$. There is no next greater element, so the answer is -1 .

Example 2:

Input: $\text{nums1} = [2,4]$, $\text{nums2} = [1,2,3,4]$

Output: $[3,-1]$

Explanation: The next greater element for each value of nums1 is as follows:

- 2 is underlined in $\text{nums2} = [1,\underline{2},3,4]$. The next greater element is 3 .
- 4 is underlined in $\text{nums2} = [1,2,3,\underline{4}]$. There is no next greater element, so the answer is -1 .

Constraints:

- $1 \leq \text{nums1.length} \leq \text{nums2.length} \leq 1000$
- $0 \leq \text{nums1}[i], \text{nums2}[i] \leq 10^4$
- All integers in `nums1` and `nums2` are **unique**.
- All the integers of `nums1` also appear in `nums2`.

497. Random Point in Non-overlapping Rectangles

Medium

402618Add to ListShare

You are given an array of non-overlapping axis-aligned rectangles `rects` where `rects[i] = [ai, bi, xi, yi]` indicates that (a_i, b_i) is the bottom-left corner point of the i^{th} rectangle and (x_i, y_i) is the top-right corner point of the i^{th} rectangle. Design an algorithm to pick a random integer point inside the space covered by one of the given rectangles. A point on the perimeter of a rectangle is included in the space covered by the rectangle.


Any integer point inside the space covered by one of the given rectangles should be equally likely to be returned.

Note that an integer point is a point that has integer coordinates.

Implement the `Solution` class:

- `Solution(int[][] rects)` Initializes the object with the given rectangles `rects`.
- `int[] pick()` Returns a random integer point $[u, v]$ inside the space covered by one of the given rectangles.

Example 1:

**Input**

```
["Solution", "pick", "pick", "pick", "pick", "pick"]
[[[[-2, -2, 1, 1], [2, 2, 4, 6]]], [], [], [], [], []]
```

Output

```
null, [1, -2], [1, -1], [-1, -2], [-2, -2], [0, 0]]
```

Explanation

```
Solution solution = new Solution([[-2, -2, 1, 1], [2, 2, 4, 6]]);

solution.pick(); // return [1, -2]

solution.pick(); // return [1, -1]
```

```

solution.pick(); // return [-1, -2]
solution.pick(); // return [-2, -2]
solution.pick(); // return [0, 0]

```

Constraints:

- $1 \leq \text{rects.length} \leq 100$
- $\text{rects}[i].length == 4$
- $-10^9 \leq a_i < x_i \leq 10^9$
- $-10^9 \leq b_i < y_i \leq 10^9$
- $x_i - a_i \leq 2000$
- $y_i - b_i \leq 2000$
- All the rectangles do not overlap.
- At most 10^4 calls will be made to `pick`.


498. Diagonal Traverse

Medium

2561575Add to ListShare

Given an $m \times n$ matrix `mat`, return an array of all the elements of the array in a diagonal order.

Example 1:



Input: `mat = [[1,2,3],[4,5,6],[7,8,9]]`

Output: [1,2,4,7,5,3,6,8,9]

Example 2:

Input: mat = [[1,2],[3,4]]

Output: [1,2,3,4]

Constraints:

- `m == mat.length`
- `n == mat[i].length`
- `1 <= m, n <= 10^4`
- `1 <= m * n <= 10^4`
- `-10^5 <= mat[i][j] <= 10^5`

500. Keyboard Row


Easy

1070984 Add to List Share

Given an array of strings `words`, return the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".



Example 1:

Input: words = ["Hello", "Alaska", "Dad", "Peace"]

Output: ["Alaska", "Dad"]

Example 2:

Input: words = ["omk"]

Output: []

Example 3:

Input: words = ["adsdf", "sfd"]

Output: ["adsdf", "sfd"]

Constraints:

- $1 \leq \text{words.length} \leq 20$
- $1 \leq \text{words[i].length} \leq 100$
- `words[i]` consists of English letters (both lowercase and uppercase).

501. Find Mode in Binary Search Tree

Easy

2527606 Add to List Share


Given the `root` of a binary search tree (BST) with duplicates, return *all the mode(s)* (i.e., the most frequently occurred element) in it.

If the tree has more than one mode, return them in **any order**.

Assume a BST is defined as follows:

- The left subtree of a node contains only nodes with keys **less than or equal to** the node's key.
- The right subtree of a node contains only nodes with keys **greater than or equal to** the node's key.
- Both the left and right subtrees must also be binary search trees.

Example 1:



Input: root = [1,null,2,2]

Output: [2]

Example 2:

Input: root = [0]

Output: [0]

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-10^5 \leq \text{Node.val} \leq 10^5$

502. IPO

Hard

93785Add to ListShare

Suppose LeetCode will start its **IPO** soon. In order to sell a good price of its shares to Venture Capital, LeetCode would like to work on some projects to increase its capital before the **IPO**. Since it has limited resources, it can only finish at most k distinct projects before the **IPO**. Help LeetCode design the best way to maximize its total capital after finishing at most k distinct projects.

You are given n projects where the i^{th} project has a pure profit $\text{profits}[i]$ and a minimum capital of $\text{capital}[i]$ is needed to start it.

Initially, you have w capital. When you finish a project, you will obtain its pure profit and the profit will be added to your total capital.

Pick a list of **at most** k distinct projects from given projects to **maximize your final capital**, and return *the final maximized capital*.

The answer is guaranteed to fit in a 32-bit signed integer.

Example 1:

Input: $k = 2$, $w = 0$, $\text{profits} = [1, 2, 3]$, $\text{capital} = [0, 1, 1]$

Output: 4

Explanation: Since your initial capital is 0, you can only start the project indexed 0.

After finishing it you will obtain profit 1 and your capital becomes 1.

With capital 1, you can either start the project indexed 1 or the project indexed 2.

Since you can choose at most 2 projects, you need to finish the project indexed 2 to get the maximum capital.

Therefore, output the final maximized capital, which is $0 + 1 + 3 = 4$.

Example 2:

Input: $k = 3$, $w = 0$, $\text{profits} = [1, 2, 3]$, $\text{capital} = [0, 1, 2]$

Output: 6

Constraints:

- $1 \leq k \leq 10^5$
- $0 \leq w \leq 10^9$
- $n == \text{profits.length}$
- $n == \text{capital.length}$
- $1 \leq n \leq 10^5$
- $0 \leq \text{profits}[i] \leq 10^4$
- $0 \leq \text{capital}[i] \leq 10^9$

503. Next Greater Element II

Medium

5510151Add to ListShare

Given a circular integer array nums (i.e., the next element of $\text{nums}[\text{nums.length} - 1]$ is $\text{nums}[0]$), return *the next greater number* for every element in nums .

The **next greater number** of a number x is the first greater number to its traversing-order next in the array, which means you could search circularly to find its next greater number. If it doesn't exist, return `-1` for this number.

Example 1:

Input: `nums = [1,2,1]`

Output: `[2,-1,2]`

Explanation: The first 1's next greater number is 2;

The number 2 can't find next greater number.

The second 1's next greater number needs to search circularly, which is also 2.

Example 2:

Input: `nums = [1,2,3,4,3]`

Output: `[2,3,4,-1,4]`

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

504. Base 7

Easy

541197Add to ListShare

Given an integer `num`, return a string of its **base 7** representation.

Example 1:

Input: `num = 100`

Output: `"202"`

Example 2:

Input: `num = -7`

Output: `"-10"`

Constraints:

- $-10^7 \leq \text{num} \leq 10^7$

506. Relative Ranks**Easy**

69240Add to ListShare

You are given an integer array `score` of size `n`, where `score[i]` is the score of the `ith` athlete in a competition. All the scores are guaranteed to be **unique**.

The athletes are **placed** based on their scores, where the `1st` place athlete has the highest score, the `2nd` place athlete has the `2nd` highest score, and so on. The placement of each athlete determines their rank:

- The `1st` place athlete's rank is "Gold Medal".
- The `2nd` place athlete's rank is "Silver Medal".
- The `3rd` place athlete's rank is "Bronze Medal".
- For the `4th` place to the `nth` place athlete, their rank is their placement number (i.e., the `xth` place athlete's rank is "`x`").

Return an array `answer` of size `n` where `answer[i]` is the **rank** of the `ith` athlete.

Example 1:

Input: `score = [5,4,3,2,1]`

Output: `["Gold Medal", "Silver Medal", "Bronze Medal", "4", "5"]`

Explanation: The placements are `[1st, 2nd, 3rd, 4th, 5th]`.

Example 2:

Input: `score = [10,3,8,9,4]`

Output: `["Gold Medal", "5", "Bronze Medal", "Silver Medal", "4"]`

Explanation: The placements are `[1st, 5th, 3rd, 2nd, 4th]`.

Constraints:

- `n == score.length`
- `1 <= n <= 104`
- `0 <= score[i] <= 106`
- All the values in `score` are **unique**.

507. Perfect Number

Easy

664921Add to ListShare

A **perfect number** is a **positive integer** that is equal to the sum of its **positive divisors**, excluding the number itself. A **divisor** of an integer `x` is an integer that can divide `x` evenly.

Given an integer `n`, return `true` if `n` is a perfect number, otherwise return `false`.

Example 1:

Input: `num = 28`

Output: `true`

Explanation: $28 = 1 + 2 + 4 + 7 + 14$

`1, 2, 4, 7, and 14` are all divisors of `28`.

Example 2:

Input: `num = 7`

Output: `false`

Constraints:

- `1 <= num <= 108`


508. Most Frequent Subtree Sum

Medium

1743260Add to ListShare


Given the `root` of a binary tree, return the most frequent **subtree sum**. If there is a tie, return all the values with the highest frequency in any order.

The **subtree sum** of a node is defined as the sum of all the node values formed by the subtree rooted at that node (including the node itself).

Example 1:

Input: root = [5,2,-3]

Output: [2,-3,4]

Example 2:

Input: root = [5,2,-5]

Output: [2]

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-10^5 \leq \text{Node.val} \leq 10^5$

509. Fibonacci Number

Easy

5199292Add to ListShare

The **Fibonacci numbers**, commonly denoted $F(n)$ form a sequence, called the **Fibonacci sequence**, such that each number is the sum of the two preceding ones, starting from 0 and 1. That is,

$$F(0) = 0, F(1) = 1$$

$$F(n) = F(n - 1) + F(n - 2), \text{ for } n > 1.$$

Given n , calculate $F(n)$.

Example 1:

Input: $n = 2$

Output: 1

Explanation: $F(2) = F(1) + F(0) = 1 + 0 = 1$.

Example 2:

Input: $n = 3$

Output: 2

Explanation: $F(3) = F(2) + F(1) = 1 + 1 = 2$.

Example 3:

Input: $n = 4$

Output: 3

Explanation: $F(4) = F(3) + F(2) = 2 + 1 = 3$.

Constraints:

- $0 \leq n \leq 30$

511. Game Play Analysis I

Easy

37914Add to ListShare

SQL Schema

Table: `Activity`

Column Name	Type
<code>player_id</code>	int
<code>device_id</code>	int

```

| event_date | date      |
| games_played | int      |
+-----+-----+
(player_id, event_date) is the primary key of this table.

This table shows the activity of players of some games.

Each row is a record of a player who logged in and played a number of games (possibly
0) before logging out on someday using some device.

```

Write an SQL query to report the **first login date** for each player.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Activity table:

```

+-----+-----+-----+-----+
| player_id | device_id | event_date | games_played |
+-----+-----+-----+-----+
| 1         | 2         | 2016-03-01 | 5           |
| 1         | 2         | 2016-05-02 | 6           |
| 2         | 3         | 2017-06-25 | 1           |
| 3         | 1         | 2016-03-02 | 0           |
| 3         | 4         | 2018-07-03 | 5           |
+-----+-----+-----+-----+

```

Output:

```

+-----+
| player_id | first_login |
+-----+

```

1		2016-03-01
2		2017-06-25
3		2016-03-02


513. Find Bottom Left Tree Value

Medium

2512231Add to ListShare

Given the `root` of a binary tree, return the leftmost value in the last row of the tree.


Example 1:



Input: root = [2,1,3]

Output: 1

Example 2:



Input: root = [1,2,3,4,null,5,6,null,null,7]

Output: 7

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-2^{31} \leq \text{Node.val} \leq 2^{31} - 1$

514. Freedom Trail

Hard

75335Add to ListShare

In the video game Fallout 4, the quest "**Road to Freedom**" requires players to reach a metal dial called the "**Freedom Trail Ring**" and use the dial to spell a specific keyword to open the door.


Given a string `ring` that represents the code engraved on the outer ring and another string `key` that represents the keyword that needs to be spelled, return *the minimum number of steps to spell all the characters in the keyword*.

Initially, the first character of the ring is aligned at the "12:00" direction. You should spell all the characters in `key` one by one by rotating `ring` clockwise or anticlockwise to make each character of the string `key` aligned at the "12:00" direction and then by pressing the center button.

At the stage of rotating the ring to spell the key character `key[i]`:

1. You can rotate the ring clockwise or anticlockwise by one place, which counts as **one step**. The final purpose of the rotation is to align one of `ring`'s characters at the "12:00" direction, where this character must equal `key[i]`.
2. If the character `key[i]` has been aligned at the "12:00" direction, press the center button to spell, which also counts as **one step**. After the pressing, you could begin to spell the next character in the key (next stage). Otherwise, you have finished all the spelling.

Example 1:



Input: ring = "godding", key = "gd"

Output: 4

Explanation:

For the first key character 'g', since it is already in place, we just need 1 step to spell this character.

For the second key character 'd', we need to rotate the ring "godding" anticlockwise by two steps to make it become "ddinggo".

Also, we need 1 more step for spelling.


So the final output is 4.

Example 2:**Input:** ring = "godding", key = "godding"**Output:** 13**Constraints:**

- `1 <= ring.length, key.length <= 100`
- `ring` and `key` consist of only lower case English letters.
- It is guaranteed that `key` could always be spelled by rotating `ring`.

515. Find Largest Value in Each Tree Row**Medium**

233891Add to ListShare

Given the `root` of a binary tree, return *an array of the largest value in each row of the tree (0-indexed)*.**Example 1:****Input:** root = [1,3,2,5,3,null,9]**Output:** [1,3,9]**Example 2:**

Input: root = [1,2,3]

Output: [1,3]

Constraints:

- The number of nodes in the tree will be in the range [0, 10⁴].
- -2³¹ <= Node.val <= 2³¹ - 1

516. Longest Palindromic Subsequence

Medium

6311256Add to ListShare

Given a string `s`, find the longest palindromic **subsequence**'s length in `s`.

A **subsequence** is a sequence that can be derived from another sequence by deleting some or no elements without changing the order of the remaining elements.

Example 1:

Input: s = "bbbab"

Output: 4

Explanation: One possible longest palindromic subsequence is "bbbb".

Example 2:

Input: s = "cbbd"

Output: 2

Explanation: One possible longest palindromic subsequence is "bb".

Constraints:

- 1 <= s.length <= 1000
- `s` consists only of lowercase English letters.

517. Super Washing Machines

Hard

597194Add to ListShare

You have n super washing machines on a line. Initially, each washing machine has some dresses or is empty.

For each move, you could choose any m ($1 \leq m \leq n$) washing machines, and pass one dress of each washing machine to one of its adjacent washing machines at the same time.

Given an integer array `machines` representing the number of dresses in each washing machine from left to right on the line, return *the minimum number of moves to make all the washing machines have the same number of dresses*. If it is not possible to do it, return `-1`.

Example 1:

Input: `machines = [1,0,5]`

Output: 3

Explanation:

1st move: 1 0 <-- 5 => 1 1 4

2nd move: 1 <-- 1 <-- 4 => 2 1 3

3rd move: 2 1 <-- 3 => 2 2 2

Example 2:

Input: `machines = [0,3,0]`

Output: 2

Explanation:

1st move: 0 <-- 3 0 => 1 2 0

2nd move: 1 2 --> 0 => 1 1 1

Example 3:

Input: `machines = [0,2,0]`

Output: -1

Explanation:

It's impossible to make all three washing machines have the same number of dresses.

Constraints:

- `n == machines.length`
- `1 <= n <= 104`
- `0 <= machines[i] <= 105`

518. Coin Change II

Medium

6239114Add to ListShare

You are given an integer array `coins` representing coins of different denominations and an integer `amount` representing a total amount of money.

Return *the number of combinations that make up that amount*. If that amount of money cannot be made up by any combination of the coins, return `0`.

You may assume that you have an infinite number of each kind of coin.

The answer is **guaranteed** to fit into a signed **32-bit** integer.

Example 1:

Input: `amount = 5, coins = [1,2,5]`

Output: `4`

Explanation: there are four ways to make up the amount:

`5=5`

`5=2+2+1`

`5=2+1+1+1`

`5=1+1+1+1+1`

Example 2:

Input: `amount = 3, coins = [2]`

Output: `0`

Explanation: the amount of 3 cannot be made up just with coins of 2.

Example 3:

Input: `amount = 10, coins = [10]`

Output: `1`

Constraints:

- `1 <= coins.length <= 300`
- `1 <= coins[i] <= 5000`
- All the values of `coins` are **unique**.
- `0 <= amount <= 5000`

519. Random Flip Matrix**Medium**

33592Add to ListShare

There is an `m x n` binary grid `matrix` with all the values set `0` initially. Design an algorithm to randomly pick an index `(i, j)` where `matrix[i][j] == 0` and flips it to `1`. All the indices `(i, j)` where `matrix[i][j] == 0` should be equally likely to be returned.

Optimize your algorithm to minimize the number of calls made to the **built-in** random function of your language and optimize the time and space complexity.

Implement the `Solution` class:

- `Solution(int m, int n)` Initializes the object with the size of the binary matrix `m` and `n`.
- `int[] flip()` Returns a random index `[i, j]` of the matrix where `matrix[i][j] == 0` and flips it to `1`.
- `void reset()` Resets all the values of the matrix to be `0`.

Example 1:**Input**

```
["Solution", "flip", "flip", "flip", "reset", "flip"]
[[3, 1], [], [], [], [], []]
```

Output

```
[null, [1, 0], [2, 0], [0, 0], null, [2, 0]]
```

Explanation

```
Solution solution = new Solution(3, 1);
solution.flip(); // return [1, 0], [0,0], [1,0], and [2,0] should be equally likely
to be returned.

solution.flip(); // return [2, 0], Since [1,0] was returned, [2,0] and [0,0]
```

```

solution.flip(); // return [0, 0], Based on the previously returned indices, only
[0,0] can be returned.

solution.reset(); // All the values are reset to 0 and can be returned.

solution.flip(); // return [2, 0], [0,0], [1,0], and [2,0] should be equally likely
to be returned.

```

Constraints:

- $1 \leq m, n \leq 10^4$
- There will be at least one free cell for each call to `flip`.
- At most `1000` calls will be made to `flip` and `reset`.

520. Detect Capital

Easy

1756372 Add to List Share

We define the usage of capitals in a word to be right when one of the following cases holds:

- All letters in this word are capitals, like "USA".
- All letters in this word are not capitals, like "leetcode".
- Only the first letter in this word is capital, like "Google".

Given a string `word`, return `true` if the usage of capitals in it is right.

Example 1:

Input: word = "USA"

Output: true

Example 2:

Input: word = "FlaG"

Output: false

Constraints:

- $1 \leq \text{word.length} \leq 100$
- `word` consists of lowercase and uppercase English letters.

521. Longest Uncommon Subsequence I

Easy

6365850Add to ListShare

Given two strings `a` and `b`, return *the length of the longest uncommon subsequence between `a` and `b`*. If the longest uncommon subsequence does not exist, return `-1`.

An **uncommon subsequence** between two strings is a string that is a **subsequence of one but not the other**.

A **subsequence** of a string `s` is a string that can be obtained after deleting any number of characters from `s`.

- For example, "abc" is a subsequence of "a`ebdc`" because you can delete the underlined characters in "a`ebdc`" to get "abc". Other subsequences of "a`ebdc`" include "a`ebdc`", "a`eb`", and "" (empty string).

Example 1:

Input: `a` = "aba", `b` = "cdc"

Output: 3

Explanation: One longest uncommon subsequence is "aba" because "aba" is a subsequence of "aba" but not "cdc".

Note that "cdc" is also a longest uncommon subsequence.

Example 2:

Input: `a` = "aaa", `b` = "bbb"

Output: 3

Explanation: The longest uncommon subsequences are "aaa" and "bbb".

Example 3:

Input: `a` = "aaa", `b` = "aaa"

Output: -1

Explanation: Every subsequence of string `a` is also a subsequence of string `b`. Similarly, every subsequence of string `b` is also a subsequence of string `a`.

Constraints:

- $1 \leq a.length, b.length \leq 100$
- a and b consist of lower-case English letters.

522. Longest Uncommon Subsequence II

Medium

4121139Add to ListShare

Given an array of strings $strs$, return the length of the **longest uncommon subsequence** between them. If the longest uncommon subsequence does not exist, return -1 .

An **uncommon subsequence** between an array of strings is a string that is a **subsequence of one string but not the others**.

A **subsequence** of a string s is a string that can be obtained after deleting any number of characters from s .

- For example, "abc" is a subsequence of "aebdc" because you can delete the underlined characters in "a \underline{ebdc} " to get "abc". Other subsequences of "aebdc" include "aebdc", "aeb", and "" (empty string).

Example 1:

Input: $strs = ["aba", "cdc", "eae"]$

Output: 3

Example 2:

Input: $strs = ["aaa", "aaa", "aa"]$

Output: -1

Constraints:

- $2 \leq strs.length \leq 50$
- $1 \leq strs[i].length \leq 10$
- $strs[i]$ consists of lowercase English letters.

523. Continuous Subarray Sum

Medium

2517314Add to ListShare

Given an integer array $nums$ and an integer k , return **true** if $nums$ has a continuous subarray of size **at least two** whose elements sum up to a multiple of k , or **false** otherwise.

An integer x is a multiple of k if there exists an integer n such that $x = n * k$. 0 is **always** a multiple of k .

Example 1:

Input: `nums = [23, 2, 4, 6, 7], k = 6`

Output: `true`

Explanation: `[2, 4]` is a continuous subarray of size 2 whose elements sum up to 6.

Example 2:

Input: `nums = [23, 2, 6, 4, 7], k = 6`

Output: `true`

Explanation: `[23, 2, 6, 4, 7]` is an continuous subarray of size 5 whose elements sum up to 42.

42 is a multiple of 6 because $42 = 7 * 6$ and 7 is an integer.

Example 3:

Input: `nums = [23, 2, 6, 4, 7], k = 13`

Output: `false`

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $0 \leq \text{nums}[i] \leq 10^9$
- $0 \leq \text{sum}(\text{nums}[i]) \leq 2^{31} - 1$
- $1 \leq k \leq 2^{31} - 1$

524. Longest Word in Dictionary through Deleting

Medium

147338Add to ListShare

Given a string s and a string array dictionary , return the longest string in the dictionary that can be formed by deleting some of the given string characters. If there is more than one possible result, return the longest word with the smallest lexicographical order. If there is no possible result, return the empty string.

Example 1:

Input: s = "abpcplea", dictionary = ["ale", "apple", "monkey", "plea"]

Output: "apple"

Example 2:

Input: s = "abpcplea", dictionary = ["a", "b", "c"]

Output: "a"

Constraints:

- $1 \leq s.length \leq 1000$
- $1 \leq \text{dictionary.length} \leq 1000$
- $1 \leq \text{dictionary}[i].length \leq 1000$
- s and $\text{dictionary}[i]$ consist of lowercase English letters.

525. Contiguous Array

Medium

5814239Add to ListShare

Given a binary array `nums`, return *the maximum length of a contiguous subarray with an equal number of 0 and 1*.

Example 1:

Input: nums = [0,1]

Output: 2

Explanation: [0, 1] is the longest contiguous subarray with an equal number of 0 and 1.

Example 2:

Input: nums = [0,1,0]

Output: 2

Explanation: [0, 1] (or [1, 0]) is a longest contiguous subarray with equal number of 0 and 1.

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $\text{nums}[i]$ is either 0 or 1.

526. Beautiful Arrangement

Medium

2536313Add to ListShare

Suppose you have n integers labeled 1 through n . A permutation of those n integers $\text{perm}(1\text{-indexed})$ is considered a **beautiful arrangement** if for every i ($1 \leq i \leq n$), **either** of the following is true:

- $\text{perm}[i]$ is divisible by i .
- i is divisible by $\text{perm}[i]$.

Given an integer n , return *the number of the beautiful arrangements that you can construct.*

Example 1:

Input: $n = 2$

Output: 2

Explanation:

The first beautiful arrangement is $[1, 2]$:

- $\text{perm}[1] = 1$ is divisible by $i = 1$
- $\text{perm}[2] = 2$ is divisible by $i = 2$

The second beautiful arrangement is $[2, 1]$:

- $\text{perm}[1] = 2$ is divisible by $i = 1$
- $i = 2$ is divisible by $\text{perm}[2] = 1$

Example 2:

Input: $n = 1$

Output: 1

Constraints:

- $1 \leq n \leq 15$

528. Random Pick with Weight

Medium

1099481Add to ListShare

You are given a **0-indexed** array of positive integers `w` where `w[i]` describes the **weight** of the `ith` index.

You need to implement the function `pickIndex()`, which **randomly** picks an index in the range `[0, w.length - 1]` (**inclusive**) and returns it. The **probability** of picking an index `i` is `w[i] / sum(w)`.

- For example, if `w = [1, 3]`, the probability of picking index `0` is `1 / (1 + 3) = 0.25` (i.e., 25%), and the probability of picking index `1` is `3 / (1 + 3) = 0.75` (i.e., 75%).

Example 1:

Input

```
["Solution","pickIndex"]
[[[1]],[]]
```

Output

```
[null,0]
```

Explanation

```
Solution solution = new Solution([1]);
solution.pickIndex(); // return 0. The only option is to return 0 since there is only
one element in w.
```

Example 2:

Input

```
["Solution","pickIndex","pickIndex","pickIndex","pickIndex","pickIndex"]
[[[1,3]],[[],[],[],[],[],[]]]
```

Output

```
[null,1,1,1,1,0]
```

Explanation

```

Solution solution = new Solution([1, 3]);

solution.pickIndex(); // return 1. It is returning the second element (index = 1)
that has a probability of 3/4.

solution.pickIndex(); // return 1

solution.pickIndex(); // return 1

solution.pickIndex(); // return 1

solution.pickIndex(); // return 0. It is returning the first element (index = 0) that
has a probability of 1/4.

```

Since this is a randomization problem, multiple answers are allowed.

All of the following outputs can be considered correct:

[null,1,1,1,1,0]

[null,1,1,1,1,1]

[null,1,1,1,0,0]

[null,1,1,1,0,1]

[null,1,0,1,0,0]

.....

and so on.

Constraints:

- $1 \leq w.length \leq 10^4$
- $1 \leq w[i] \leq 10^5$
- `pickIndex` will be called at most 10^4 times.

529. Minesweeper

Medium

1573923Add to ListShare

Let's play the minesweeper game ([Wikipedia](#), [online game](#))!

You are given an $m \times n$ char matrix `board` representing the game board where:


- 'M' represents an unrevealed mine,
- 'E' represents an unrevealed empty square,
- 'B' represents a revealed blank square that has no adjacent mines (i.e., above, below, left, right, and all 4 diagonals),
- digit ('1' to '8') represents how many mines are adjacent to this revealed square, and
- 'X' represents a revealed mine.

You are also given an integer array `click` where `click = [clickr, clickc]` represents the next click position among all the unrevealed squares ('M' or 'E').

Return *the board after revealing this position according to the following rules*:

1. If a mine 'M' is revealed, then the game is over. You should change it to 'X'.
2. If an empty square 'E' with no adjacent mines is revealed, then change it to a revealed blank 'B' and all of its adjacent unrevealed squares should be revealed recursively.
3. If an empty square 'E' with at least one adjacent mine is revealed, then change it to a digit ('1' to '8') representing the number of adjacent mines.
4. Return the board when no more squares will be revealed.


Example 1:



```
Input: board =
[[["E", "E", "E", "E", "E"], ["E", "E", "M", "E", "E"], ["E", "E", "E", "E", "E"], ["E", "E", "E", "E", "E"], ["E", "E", "E", "E", "E"]], click = [3,0]
```

Output:

```
[[["B", "1", "E", "1", "B"], ["B", "1", "M", "1", "B"], ["B", "1", "1", "1", "B"], ["B", "B", "B", "B", "B"]]]
```

Example 2:

Input: board =
`[[["B", "1", "E", "1", "B"], ["B", "1", "M", "1", "B"], ["B", "1", "1", "1", "B"], ["B", "B", "B", "B", "B"]], click = [1, 2]]`

Output:

```
[[["B", "1", "E", "1", "B"], ["B", "1", "X", "1", "B"], ["B", "1", "1", "1", "B"], ["B", "B", "B", "B", "B"]]]
```

Constraints:


- `m == board.length`
- `n == board[i].length`
- `1 <= m, n <= 50`
- `board[i][j]` is either `'M'`, `'E'`, `'B'`, or a digit from `'1'` to `'8'`.
- `click.length == 2`
- `0 <= clickr < m`
- `0 <= clickc < n`
- `board[clickr][clickc]` is either `'M'` or `'E'`.

530. Minimum Absolute Difference in BST**Easy**

2392130Add to ListShare

Given the `root` of a Binary Search Tree (BST), return *the minimum absolute difference between the values of any two different nodes in the tree*.


Example 1:



Input: root = [4,2,6,1,3]

Output: 1

Example 2:



Input: root = [1,0,48,null,null,12,49]

Output: 1

Constraints:

- The number of nodes in the tree is in the range $[2, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^5$

532. K-diff Pairs in an Array

Medium

29202128Add to ListShare

Given an array of integers `nums` and an integer `k`, return *the number of unique k-diff pairs in the array*.

A **k-diff** pair is an integer pair $(\text{nums}[i], \text{nums}[j])$, where the following are true:

- $0 \leq i, j < \text{nums.length}$
- $i \neq j$
- $|\text{nums}[i] - \text{nums}[j]| == k$

Notice that $|\text{val}|$ denotes the absolute value of `val`.

Example 1:

Input: `nums = [3,1,4,1,5]`, `k = 2`

Output: 2

Explanation: There are two 2-diff pairs in the array, $(1, 3)$ and $(3, 5)$.

Although we have two 1s in the input, we should only return the number of **unique** pairs.

Example 2:

Input: `nums = [1,2,3,4,5]`, `k = 1`

Output: 4

Explanation: There are four 1-diff pairs in the array, $(1, 2)$, $(2, 3)$, $(3, 4)$ and $(4, 5)$.

Example 3:

Input: `nums = [1,3,1,5,4]`, `k = 0`

Output: 1

Explanation: There is one 0-diff pair in the array, (1, 1).

Constraints:

- `1 <= nums.length <= 104`
- `-107 <= nums[i] <= 107`
- `0 <= k <= 107`

535. Encode and Decode TinyURL

Medium

16753245 Add to List Share

Note: This is a companion problem to the [System Design](#) problem: [Design TinyURL](#).

TinyURL is a URL shortening service where you enter a URL such as <https://leetcode.com/problems/design-tinyurl> and it returns a short URL such as <http://tinyurl.com/4e9iAk>. Design a class to encode a URL and decode a tiny URL.

There is no restriction on how your encode/decode algorithm should work. You just need to ensure that a URL can be encoded to a tiny URL and the tiny URL can be decoded to the original URL.

Implement the `Solution` class:

- `Solution()` Initializes the object of the system.
- `String encode(String longUrl)` Returns a tiny URL for the given `longUrl`.
- `String decode(String shortUrl)` Returns the original long URL for the given `shortUrl`. It is guaranteed that the given `shortUrl` was encoded by the same object.

Example 1:

Input: url = "https://leetcode.com/problems/design-tinyurl"

Output: "https://leetcode.com/problems/design-tinyurl"

Explanation:

```
Solution obj = new Solution();

String tiny = obj.encode(url); // returns the encoded tiny url.

String ans = obj.decode(tiny); // returns the original url after decoding it.
```

Constraints:

- $1 \leq \text{url.length} \leq 10^4$
- `url` is guaranteed to be a valid URL.

537. Complex Number Multiplication

Medium

5571166Add to ListShare

A complex number can be represented as a string on the form "`real+imaginaryi`" where:

- `real` is the real part and is an integer in the range $[-100, 100]$.
- `imaginary` is the imaginary part and is an integer in the range $[-100, 100]$.
- $i^2 == -1$.

Given two complex numbers `num1` and `num2` as strings, return a *string of the complex number that represents their multiplications*.

Example 1:

Input: `num1 = "1+1i", num2 = "1+1i"`

Output: `"0+2i"`

Explanation: $(1 + i) * (1 + i) = 1 + i2 + 2 * i = 2i$, and you need convert it to the form of `0+2i`.

Example 2:

Input: `num1 = "1+-1i", num2 = "1+-1i"`

Output: `"0+-2i"`

Explanation: $(1 - i) * (1 - i) = 1 + i2 - 2 * i = -2i$, and you need convert it to the form of `0+-2i`.

Constraints:

- `num1` and `num2` are valid complex numbers.

538. Convert BST to Greater Tree

Medium


4514165Add to ListShare

Given the `root` of a Binary Search Tree (BST), convert it to a Greater Tree such that every key of the original BST is changed to the original key plus the sum of all keys greater than the original key in BST.

As a reminder, a *binary search tree* is a tree that satisfies these constraints:

- The left subtree of a node contains only nodes with keys **less than** the node's key.
- The right subtree of a node contains only nodes with keys **greater than** the node's key.
- Both the left and right subtrees must also be binary search trees.

Example 1:



Input: `root = [4,1,6,0,2,5,7,null,null,null,3,null,null,null,8]`

Output: `[30,36,21,36,35,26,15,null,null,null,33,null,null,null,8]`

Example 2:

Input: `root = [0,null,1]`

Output: [1,null,1]

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $-10^4 \leq \text{Node.val} \leq 10^4$
- All the values in the tree are **unique**.
- `root` is guaranteed to be a valid binary search tree.

539. Minimum Time Difference

Medium

1287228Add to ListShare

Given a list of 24-hour clock time points in "**HH:MM**" format, return *the minimum **minutes** difference between any two time-points in the list*.

Example 1:

Input: timePoints = ["23:59", "00:00"]

Output: 1

Example 2:

Input: timePoints = ["00:00", "23:59", "00:00"]

Output: 0

Constraints:

- $2 \leq \text{timePoints.length} \leq 2 * 10^4$
- `timePoints[i]` is in the format "**HH:MM**".

540. Single Element in a Sorted Array

Medium

6271115Add to ListShare

You are given a sorted array consisting of only integers where every element appears exactly twice, except for one element which appears exactly once.

Return *the single element that appears only once*.

Your solution must run in $O(\log n)$ time and $O(1)$ space.

Example 1:

Input: `nums = [1,1,2,3,3,4,4,8,8]`

Output: `2`

Example 2:

Input: `nums = [3,3,7,7,10,11,11]`

Output: `10`

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $0 \leq \text{nums}[i] \leq 10^5$

541. Reverse String II

Easy

12572755Add to ListShare

Given a string `s` and an integer `k`, reverse the first `k` characters for every `2k` characters counting from the start of the string.

If there are fewer than `k` characters left, reverse all of them. If there are less than `2k` but greater than or equal to `k` characters, then reverse the first `k` characters and leave the other as original.

Example 1:

Input: `s = "abcdefg", k = 2`

Output: `"bacdfeg"`

Example 2:

Input: `s = "abcd", k = 2`

Output: `"bacd"`

Constraints:

- $1 \leq s.length \leq 10^4$
- s consists of only lowercase English letters.
- $1 \leq k \leq 10^4$

542.01 Matrix

Medium

5688286Add to ListShare

Given an $m \times n$ binary matrix mat , return the distance of the nearest 0 for each cell.

The distance between two adjacent cells is 1 .

Example 1:

0	0	0
0	1	0
0	0	0

Input: $mat = [[0,0,0],[0,1,0],[0,0,0]]$

Output: $[[0,0,0],[0,1,0],[0,0,0]]$

Example 2:

0	0	0
0	1	0
1	1	1

Input: mat = [[0,0,0],[0,1,0],[1,1,1]]

Output: [[0,0,0],[0,1,0],[1,2,1]]

Constraints:

- m == mat.length
- n == mat[i].length
- 1 <= m, n <= 10^4
- 1 <= m * n <= 10^4
- mat[i][j] is either 0 or 1.
- There is at least one 0 in mat.

543. Diameter of Binary Tree

Easy


9612594Add to ListShare

Given the `root` of a binary tree, return the *length of the diameter of the tree*.

The **diameter** of a binary tree is the **length** of the longest path between any two nodes in a tree. This path may or may not pass through the `root`.

The **length** of a path between two nodes is represented by the number of edges between them.

Example 1:



Input: root = [1,2,3,4,5]

Output: 3

Explanation: 3 is the length of the path [4,2,1,3] or [5,2,1,3].

Example 2:

Input: root = [1,2]

Output: 1

Constraints:

- The number of nodes in the tree is in the range [1, 10⁴].
- $-100 \leq \text{Node.val} \leq 100$

546. Remove Boxes

Hard

170498Add to ListShare

You are given several `boxes` with different colors represented by different positive numbers.

You may experience several rounds to remove boxes until there is no box left. Each time you can choose some continuous boxes with the same color (i.e., composed of `k` boxes, $k \geq 1$), remove them and get $k * k$ points.

Return *the maximum points you can get*.

Example 1:

Input: boxes = [1,3,2,2,2,3,4,3,1]

Output: 23

Explanation:

[1, 3, 2, 2, 2, 3, 4, 3, 1]

----> [1, 3, 3, 4, 3, 1] (3*3=9 points)

----> [1, 3, 3, 3, 1] (1*1=1 points)

----> [1, 1] (3*3=9 points)

----> [] (2*2=4 points)

Example 2:

Input: boxes = [1,1,1]

Output: 9

Example 3:

Input: boxes = [1]

Output: 1

Constraints:

- $1 \leq \text{boxes.length} \leq 100$
- $1 \leq \text{boxes}[i] \leq 100$

547. Number of Provinces

Medium


6197268Add to ListShare

There are n cities. Some of them are connected, while some are not. If city a is connected directly with city b , and city b is connected directly with city c , then city a is connected indirectly with city c .

A **province** is a group of directly or indirectly connected cities and no other cities outside of the group.


You are given an $n \times n$ matrix `isConnected` where `isConnected[i][j] = 1` if the i^{th} city and the j^{th} city are directly connected, and `isConnected[i][j] = 0` otherwise.

Return *the total number of provinces*.

Example 1:

Input: isConnected = [[1,1,0],[1,1,0],[0,0,1]]

Output: 2

Example 2:

Input: isConnected = [[1,0,0],[0,1,0],[0,0,1]]

Output: 3

Constraints:

- $1 \leq n \leq 200$
- $n == \text{isConnected.length}$
- $n == \text{isConnected}[i].length$
- $\text{isConnected}[i][j]$ is 1 or 0.
- $\text{isConnected}[i][i] == 1$
- $\text{isConnected}[i][j] == \text{isConnected}[j][i]$

551. Student Attendance Record I

Easy

4025Add to ListShare

You are given a string s representing an attendance record for a student where each character signifies whether the student was absent, late, or present on that day. The record only contains the following three characters:

- 'A': Absent.
- 'L': Late.
- 'P': Present.

The student is eligible for an attendance award if they meet **both** of the following criteria:

- The student was absent ('A') for **strictly** fewer than 2 days **total**.
- The student was **never** late ('L') for 3 or more **consecutive** days.

Return `true` if the student is eligible for an attendance award, or `false` otherwise.

Example 1:

Input: `s = "PPALLP"`

Output: `true`

Explanation: The student has fewer than 2 absences and was never late 3 or more consecutive days.

Example 2:

Input: `s = "PPALLL"`

Output: `false`

Explanation: The student was late 3 consecutive days in the last 3 days, so is not eligible for the award.

Constraints:

- `1 <= s.length <= 1000`
- `s[i]` is either 'A', 'L', or 'P'.

552. Student Attendance Record II

Hard

1403231Add to ListShare

An attendance record for a student can be represented as a string where each character signifies whether the student was absent, late, or present on that day. The record only contains the following three characters:

- 'A': Absent.
- 'L': Late.
- 'P': Present.

Any student is eligible for an attendance award if they meet **both** of the following criteria:

- The student was absent ('A') for **strictly** fewer than 2 days **total**.
- The student was **never** late ('L') for 3 or more **consecutive** days.

Given an integer `n`, return *the number of possible attendance records of length n that make a student eligible for an attendance award. The answer may be very large, so return it modulo $10^9 + 7$.*

Example 1:

Input: `n = 2`

Output: 8

Explanation: There are 8 records with length 2 that are eligible for an award:

"PP", "AP", "PA", "LP", "PL", "AL", "LA", "LL"

Only "AA" is not eligible because there are 2 absences (there need to be fewer than 2).

Example 2:

Input: `n = 1`

Output: 3

Example 3:

Input: `n = 10101`

Output: 183236316

Constraints:

- $1 \leq n \leq 10^5$

553. Optimal Division

Medium

2981442Add to ListShare

You are given an integer array `nums`. The adjacent integers in `nums` will perform the float division.

- For example, for `nums = [2, 3, 4]`, we will evaluate the expression "2/3/4".

However, you can add any number of parenthesis at any position to change the priority of operations. You want to add these parentheses such the value of the expression after the evaluation is maximum.

Return *the corresponding expression that has the maximum value in string format*.

Note: your expression should not contain redundant parenthesis.

Example 1:

Input: `nums = [1000,100,10,2]`

Output: `"1000/(100/10/2)"`

Explanation: $1000/(100/10/2) = 1000/((100/10)/2) = 200$

However, the bold parenthesis in `"1000/((100/10)/2)"` are redundant since they do not influence the operation priority.

So you should return `"1000/(100/10/2)"`.

Other cases:

$1000/(100/10)/2 = 50$

$1000/(100/(10/2)) = 50$

$1000/100/10/2 = 0.5$

$1000/100/(10/2) = 2$

Example 2:

Input: `nums = [2,3,4]`

Output: `"2/(3/4)"`

Explanation: $(2/(3/4)) = 8/3 = 2.667$

It can be shown that after trying all possibilities, we cannot get an expression with evaluation greater than 2.667

Constraints:

- $1 \leq \text{nums.length} \leq 10$
- $2 \leq \text{nums}[i] \leq 1000$
- There is only one optimal division for the given input.

554. Brick Wall

Medium


1938107Add to ListShare

There is a rectangular brick wall in front of you with n rows of bricks. The i^{th} row has some number of bricks each of the same height (i.e., one unit) but they can be of different widths. The total width of each row is the same.

Draw a vertical line from the top to the bottom and cross the least bricks. If your line goes through the edge of a brick, then the brick is not considered as crossed. You cannot draw a line just along one of the two vertical edges of the wall, in which case the line will obviously cross no bricks.

Given the 2D array `wall` that contains the information about the wall, return *the minimum number of crossed bricks after drawing such a vertical line*.

Example 1:



Input: wall = [[1,2,2,1],[3,1,2],[1,3,2],[2,4],[3,1,2],[1,3,1,1]]

Output: 2

Example 2:

Input: wall = [[1],[1],[1]]

Output: 3

Constraints:

- $n == \text{wall.length}$
- $1 \leq n \leq 10^4$
- $1 \leq \text{wall}[i].length \leq 10^4$

- $1 \leq \text{sum}(\text{wall}[i].\text{length}) \leq 2 * 10^4$
- $\text{sum}(\text{wall}[i])$ is the same for each row i .
- $1 \leq \text{wall}[i][j] \leq 2^{31} - 1$

556. Next Greater Element III

Medium

2701374Add to ListShare

Given a positive integer n , find the smallest integer which has exactly the same digits existing in the integer n and is greater in value than n . If no such positive integer exists, return -1 .

Note that the returned integer should fit in **32-bit integer**, if there is a valid answer but it does not fit in **32-bit integer**, return -1 .

Example 1:

Input: $n = 12$

Output: 21

Example 2:

Input: $n = 21$

Output: -1

Constraints:

- $1 \leq n \leq 2^{31} - 1$

557. Reverse Words in a String III

Easy

4126209Add to ListShare

Given a string s , reverse the order of characters in each word within a sentence while still preserving whitespace and initial word order.

Example 1:

Input: $s = \text{"Let's take LeetCode contest"}$

Output: $\text{"s'teL ekat edoCteeL tsetnoc"}$

Example 2:

Input: s = "God Ding"

Output: "doG gniD"

Constraints:

- $1 \leq s.length \leq 5 * 10^4$
- s contains printable **ASCII** characters.
- s does not contain any leading or trailing spaces.
- There is **at least one** word in s .
- All the words in s are separated by a single space.

558. Logical OR of Two Binary Grids Represented as Quad-Trees

Medium

145438Add to ListShare

A Binary Matrix is a matrix in which all the elements are either **0** or **1**.

Given `quadTree1` and `quadTree2`. `quadTree1` represents a $n * n$ binary matrix and `quadTree2` represents another $n * n$ binary matrix.

Return a *Quad-Tree* representing the $n * n$ binary matrix which is the result of **logical bitwise OR** of the two binary matrixes represented by `quadTree1` and `quadTree2`.

Notice that you can assign the value of a node to **True** or **False** when `isLeaf` is **False**, and both are **accepted** in the answer.

A Quad-Tree is a tree data structure in which each internal node has exactly four children. Besides, each node has two attributes:

- `val`: True if the node represents a grid of 1's or False if the node represents a grid of 0's.
- `isLeaf`: True if the node is leaf node on the tree or False if the node has the four children.

```
class Node {

    public boolean val;

    public boolean isLeaf;

    public Node topLeft;

    public Node topRight;

    public Node bottomLeft;
```

```


    public Node bottomRight;
}

}

```

We can construct a Quad-Tree from a two-dimensional area using the following steps:

1. If the current grid has the same value (i.e all 1's or all 0's) set `isLeaf` True and set `val` to the value of the grid and set the four children to Null and stop.
2. If the current grid has different values, set `isLeaf` to False and set `val` to any value and divide the current grid into four sub-grids as shown in the photo.
3. Recurse for each of the children with the proper sub-grid.



If you want to know more about the Quad-Tree, you can refer to the [wiki](#).



Quad-Tree format:

The input/output represents the serialized format of a Quad-Tree using level order traversal, where `null` signifies a path terminator where no node exists below.

It is very similar to the serialization of the binary tree. The only difference is that the node is represented as a list `[isLeaf, val]`.

If the value of `isLeaf` or `val` is True we represent it as **1** in the list `[isLeaf, val]` and if the value of `isLeaf` or `val` is False we represent it as **0**.

Example 1:



Input: quadTree1 = [[0,1],[1,1],[1,1],[1,0],[1,0]]


```
, quadTree2 =
[[0,1],[1,1],[0,1],[1,1],[1,0],null,null,null,null,[1,0],[1,0],[1,1],[1,1]]
```

Output: [[0,0],[1,1],[1,1],[1,1],[1,0]]

Explanation: quadTree1 and quadTree2 are shown above. You can see the binary matrix which is represented by each Quad-Tree.

If we apply logical bitwise OR on the two binary matrices we get the binary matrix below which is represented by the result Quad-Tree.

Notice that the binary matrices shown are only for illustration, you don't have to construct the binary matrix to get the result tree.



Example 2:

Input: quadTree1 = [[1,0]], quadTree2 = [[1,0]]

Output: [[1,0]]

Explanation: Each tree represents a binary matrix of size 1*1. Each matrix contains only zero.

The resulting matrix is of size 1*1 with also zero.

Constraints:

- quadTree1 and quadTree2 are both **valid** Quad-Trees each representing a $n * n$ grid.
- $n == 2^x$ where $0 \leq x \leq 9$.

559. Maximum Depth of N-ary Tree

Easy


222876Add to ListShare

Given a n-ary tree, find its maximum depth.

The maximum depth is the number of nodes along the longest path from the root node down to the farthest leaf node.

Nary-Tree input serialization is represented in their level order traversal, each group of children is separated by the null value (See examples).


Example 1:



Input: root = [1,null,3,2,4,null,5,6]

Output: 3

Example 2:



Input: root =
 [1,null,2,3,4,5,null,null,6,7,null,8,null,9,10,null,null,11,null,12,null,13,null,null,14]

Output: 5

Constraints:

- The total number of nodes is in the range $[0, 10^4]$.
- The depth of the n-ary tree is less than or equal to 1000.

560. Subarray Sum Equals K

Medium

15525463Add to ListShare

Given an array of integers `nums` and an integer `k`, return *the total number of subarrays whose sum equals to k*.

A subarray is a contiguous **non-empty** sequence of elements within an array.

Example 1:

Input: `nums = [1,1,1]`, `k = 2`

Output: 2

Example 2:

Input: `nums = [1,2,3]`, `k = 3`

Output: 2

Constraints:

- $1 \leq \text{nums.length} \leq 2 * 10^4$
- $-1000 \leq \text{nums}[i] \leq 1000$
- $-10^7 \leq k \leq 10^7$

561. Array Partition

Easy

1146174Add to ListShare

Given an integer array `nums` of $2n$ integers, group these integers into n pairs $(a_1, b_1), (a_2, b_2), \dots, (a_n, b_n)$ such that the sum of $\min(a_i, b_i)$ for all i is **maximized**. Return *the maximized sum*.

Example 1:

Input: `nums = [1,4,3,2]`

Output: 4

Explanation: All possible pairings (ignoring the ordering of elements) are:

1. $(1, 4), (2, 3) \rightarrow \min(1, 4) + \min(2, 3) = 1 + 2 = 3$
2. $(1, 3), (2, 4) \rightarrow \min(1, 3) + \min(2, 4) = 1 + 2 = 3$
3. $(1, 2), (3, 4) \rightarrow \min(1, 2) + \min(3, 4) = 1 + 3 = 4$

So the maximum possible sum is 4.

Example 2:**Input:** nums = [6,2,6,5,1,2]**Output:** 9**Explanation:** The optimal pairing is (2, 1), (2, 5), (6, 6). $\min(2, 1) + \min(2, 5) + \min(6, 6) = 1 + 2 + 6 = 9$.**Constraints:**


- $1 \leq n \leq 10^4$
- $\text{nums.length} == 2 * n$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

563. Binary Tree Tilt**Easy**

18171988Add to ListShare

Given the `root` of a binary tree, return *the sum of every tree node's **tilt***.


The **tilt** of a tree node is the **absolute difference** between the sum of all left subtree node **values** and all right subtree node **values**. If a node does not have a left child, then the sum of the left subtree node **values** is treated as **0**. The rule is similar if the node does not have a right child.

Example 1:**Input:** root = [1,2,3]**Output:** 1**Explanation:**Tilt of node 2 : $|0-0| = 0$ (no children)Tilt of node 3 : $|0-0| = 0$ (no children)

Tilt of node 1 : $|2-3| = 1$ (left subtree is just left child, so sum is 2; right subtree is just right child, so sum is 3)

Sum of every tilt : $0 + 0 + 1 = 1$

Example 2:



Input: root = [4,2,9,3,5,null,7]

Output: 15

Explanation:

Tilt of node 3 : $|0-0| = 0$ (no children)

Tilt of node 5 : $|0-0| = 0$ (no children)

Tilt of node 7 : $|0-0| = 0$ (no children)


Tilt of node 2 : $|3-5| = 2$ (left subtree is just left child, so sum is 3; right subtree is just right child, so sum is 5)

Tilt of node 9 : $|0-7| = 7$ (no left child, so sum is 0; right subtree is just right child, so sum is 7)

Tilt of node 4 : $|(3+5+2)-(9+7)| = |10-16| = 6$ (left subtree values are 3, 5, and 2, which sums to 10; right subtree values are 9 and 7, which sums to 16)

Sum of every tilt : $0 + 0 + 0 + 2 + 7 + 6 = 15$

Example 3:



Input: root = [21,7,14,1,1,2,2,3,3]

Output: 9

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $-1000 \leq \text{Node.val} \leq 1000$

564. Find the Closest Palindrome

Hard

5431239Add to ListShare

Given a string n representing an integer, return *the closest integer (not including itself), which is a palindrome*. If there is a tie, return **the smaller one**.

The closest is defined as the absolute difference minimized between two integers.

Example 1:

Input: n = "123"

Output: "121"

Example 2:

Input: n = "1"

Output: "0"

Explanation: 0 and 2 are the closest palindromes but we return the smallest which is 0.

Constraints:

- $1 \leq n.length \leq 18$
- n consists of only digits.
- n does not have leading zeros.
- n is representing an integer in the range $[1, 10^{18} - 1]$.

565. Array Nesting**Medium**

1965147 Add to List Share

You are given an integer array nums of length n where nums is a permutation of the numbers in the range $[0, n - 1]$.

You should build a set $s[k] = \{\text{nums}[k], \text{nums}[\text{nums}[k]], \text{nums}[\text{nums}[\text{nums}[k]]], \dots\}$ subjected to the following rule:

- The first element in $s[k]$ starts with the selection of the element $\text{nums}[k]$ of $\text{index} = k$.
- The next element in $s[k]$ should be $\text{nums}[\text{nums}[k]]$, and then $\text{nums}[\text{nums}[\text{nums}[k]]]$, and so on.
- We stop adding right before a duplicate element occurs in $s[k]$.

Return *the longest length of a set* $s[k]$.

Example 1:**Input:** $\text{nums} = [5, 4, 0, 3, 1, 6, 2]$ **Output:** 4**Explanation:**

$\text{nums}[0] = 5, \text{nums}[1] = 4, \text{nums}[2] = 0, \text{nums}[3] = 3, \text{nums}[4] = 1, \text{nums}[5] = 6, \text{nums}[6] = 2$.

One of the longest sets $s[k]$:

$s[0] = \{\text{nums}[0], \text{nums}[5], \text{nums}[6], \text{nums}[2]\} = \{5, 6, 2, 0\}$

Example 2:**Input:** $\text{nums} = [0, 1, 2]$ **Output:** 1

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $0 \leq \text{nums}[i] < \text{nums.length}$
- All the values of `nums` are **unique**.

566. Reshape the Matrix**Easy**


2737311Add to ListShare

In MATLAB, there is a handy function called `reshape` which can reshape an $m \times n$ matrix into a new one with a different size $r \times c$ keeping its original data.

You are given an $m \times n$ matrix `mat` and two integers `r` and `c` representing the number of rows and the number of columns of the wanted reshaped matrix.

The reshaped matrix should be filled with all the elements of the original matrix in the same row-traversing order as they were.


If the `reshape` operation with given parameters is possible and legal, output the new reshaped matrix; Otherwise, output the original matrix.

Example 1:

Input: `mat = [[1,2],[3,4]]`, `r = 1`, `c = 4`

Output: `[[1,2,3,4]]`

Example 2:



Input: mat = [[1,2],[3,4]], r = 2, c = 4

Output: [[1,2],[3,4]]

Constraints:

- m == mat.length
- n == mat[i].length
- 1 <= m, n <= 100
- -1000 <= mat[i][j] <= 1000
- 1 <= r, c <= 300

567. Permutation in String

Medium

7200237Add to ListShare

Given two strings s1 and s2, return `true` if s2 contains a permutation of s1, or `false` otherwise.

In other words, return `true` if one of s1's permutations is the substring of s2.

Example 1:

Input: s1 = "ab", s2 = "eidbaooo"

Output: true

Explanation: s2 contains one permutation of s1 ("ba").

Example 2:

Input: s1 = "ab", s2 = "eidboao"

Output: false

Constraints:

- $1 \leq s1.length, s2.length \leq 10^4$
- $s1$ and $s2$ consist of lowercase English letters.


572. Subtree of Another Tree

Easy

6263345Add to ListShare

Given the roots of two binary trees `root` and `subRoot`, return `true` if there is a subtree of `root` with the same structure and node values of `subRoot` and `false` otherwise.


A subtree of a binary tree `tree` is a tree that consists of a node in `tree` and all of this node's descendants. The tree `tree` could also be considered as a subtree of itself.

Example 1:

Input: `root` = [3,4,5,1,2], `subRoot` = [4,1,2]

Output: `true`

Example 2:



Input: root = [3,4,5,1,2,null,null,null,null,0], subRoot = [4,1,2]

Output: false

Constraints:

- The number of nodes in the `root` tree is in the range [1, 2000].
- The number of nodes in the `subRoot` tree is in the range [1, 1000].
- $-10^4 \leq \text{root.val} \leq 10^4$
- $-10^4 \leq \text{subRoot.val} \leq 10^4$

575. Distribute Candies

Easy

10841207Add to ListShare

Alice has `n` candies, where the `ith` candy is of type `candyType[i]`. Alice noticed that she started to gain weight, so she visited a doctor.

The doctor advised Alice to only eat $n / 2$ of the candies she has (n is always even). Alice likes her candies very much, and she wants to eat the maximum number of different types of candies while still following the doctor's advice.

Given the integer array `candyType` of length n , return *the maximum number of different types of candies she can eat if she only eats $n / 2$ of them*.

Example 1:

Input: `candyType = [1,1,2,2,3,3]`

Output: 3

Explanation: Alice can only eat $6 / 2 = 3$ candies. Since there are only 3 types, she can eat one of each type.

Example 2:

Input: `candyType = [1,1,2,3]`

Output: 2

Explanation: Alice can only eat $4 / 2 = 2$ candies. Whether she eats types [1,2], [1,3], or [2,3], she still can only eat 2 different types.

Example 3:

Input: `candyType = [6,6,6,6]`

Output: 1

Explanation: Alice can only eat $4 / 2 = 2$ candies. Even though she can eat 2 candies, she only has 1 type.

Constraints:

- $n == \text{candyType.length}$
- $2 \leq n \leq 10^4$
- n is even.
- $-10^5 \leq \text{candyType}[i] \leq 10^5$

576. Out of Boundary Paths

Medium


2828224Add to ListShare

There is an $m \times n$ grid with a ball. The ball is initially at the position `[startRow, startColumn]`. You are allowed to move the ball to one of the four adjacent cells in the grid (possibly out of the grid crossing the grid boundary). You can apply **at most** `maxMove` moves to the ball.


Given the five integers `m, n, maxMove, startRow, startColumn`, return the number of paths to move the ball out of the grid boundary. Since the answer can be very large, return it **modulo** $10^9 + 7$.

Example 1:

Move one time:







Move two times:



Input: `m = 2, n = 2, maxMove = 2, startRow = 0, startColumn = 0`

Output: 6

Example 2:

Move one time:**Move two times:****Move three times:**

Input: $m = 1$, $n = 3$, $\text{maxMove} = 3$, $\text{startRow} = 0$, $\text{startColumn} = 1$

Output: 12

Constraints:

- $1 \leq m, n \leq 50$
- $0 \leq \text{maxMove} \leq 50$
- $0 \leq \text{startRow} < m$
- $0 \leq \text{startColumn} < n$

581. Shortest Unsorted Continuous Subarray

Medium

6866241 Add to List Share

Given an integer array `nums`, you need to find one **continuous subarray** that if you only sort this subarray in ascending order, then the whole array will be sorted in ascending order.

Return *the shortest such subarray and output its length*.

Example 1:

Input: `nums = [2,6,4,8,10,9,15]`

Output: 5

Explanation: You need to sort [6, 4, 8, 10, 9] in ascending order to make the whole array sorted in ascending order.

Example 2:

Input: nums = [1,2,3,4]

Output: 0

Example 3:

Input: nums = [1]

Output: 0

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^5 \leq \text{nums}[i] \leq 10^5$

583. Delete Operation for Two Strings

Medium

448668Add to ListShare

Given two strings `word1` and `word2`, return the minimum number of **steps** required to make `word1` and `word2` the same.

In one **step**, you can delete exactly one character in either string.

Example 1:

Input: word1 = "sea", word2 = "eat"

Output: 2

Explanation: You need one step to make "sea" to "ea" and another step to make "eat" to "ea".

Example 2:

Input: word1 = "leetcode", word2 = "etco"

Output: 4

Constraints:

- $1 \leq \text{word1.length}, \text{word2.length} \leq 500$
- `word1` and `word2` consist of only lowercase English letters.

584. Find Customer Referee**Easy**

592228Add to ListShare

SQL Schema

Table: `Customer`

Column Name	Type
<code>id</code>	<code>int</code>
<code>name</code>	<code>varchar</code>
<code>referee_id</code>	<code>int</code>

`id` is the primary key column for this table.

Each row of this table indicates the `id` of a customer, their `name`, and the `id` of the customer who referred them.

Write an SQL query to report the names of the customer that are **not referred by** the customer with `id = 2`.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:**Input:**

Customer table:

```

+---+---+-----+
| id | name | referee_id |
+---+---+-----+
| 1  | Will | null      |
| 2  | Jane | null      |
| 3  | Alex | 2         |
| 4  | Bill | null      |
| 5  | Zack | 1         |
| 6  | Mark | 2         |
+---+---+-----+

```

Output:

```

+---+
| name |
+---+
| Will |
| Jane |
| Bill |
| Zack |
+---+

```

586. Customer Placing the Largest Number of Orders

Easy

45827Add to ListShare

SQL Schema

Table: `Orders`

```

+-----+-----+
| Column Name | Type   |
+-----+-----+
| order_number | int   |

```

```
| customer_number | int      |
+-----+-----+
```

order_number is the primary key for this table.

This table contains information about the order ID and the customer ID.

Write an SQL query to find the `customer_number` for the customer who has placed **the largest number of orders**.

The test cases are generated so that **exactly one customer** will have placed more orders than any other customer.

The query result format is in the following example.

Example 1:

Input:

Orders table:

```
+-----+-----+
| order_number | customer_number |
+-----+-----+
| 1           | 1           |
| 2           | 2           |
| 3           | 3           |
| 4           | 3           |
+-----+-----+
```

Output:

```
+-----+
| customer_number |
+-----+
| 3           |
+-----+
```

Explanation:

The customer with number 3 has two orders, which is greater than either customer 1 or 2 because each of them only has one order.

So the result is `customer_number` 3.

587. Erect the Fence

Hard


595370Add to ListShare

You are given an array `trees` where `trees[i] = [xi, yi]` represents the location of a tree in the garden.

You are asked to fence the entire garden using the minimum length of rope as it is expensive. The garden is well fenced only if **all the trees are enclosed**.

Return *the coordinates of trees that are exactly located on the fence perimeter*.


Example 1:



Input: points = [[1,1],[2,2],[2,0],[2,4],[3,3],[4,2]]

Output: [[1,1],[2,0],[3,3],[2,4],[4,2]]

Example 2:



Constraints:

- $1 \leq \text{points.length} \leq 3000$
- $\text{points}[i].length == 2$
- $0 \leq x_i, y_i \leq 100$
- All the given points are **unique**.

589. N-ary Tree Preorder Traversal


Easy

2327107 Add to List Share

Given the `root` of an n-ary tree, return *the preorder traversal of its nodes' values*.

Nary-Tree input serialization is represented in their level order traversal. Each group of children is separated by the null value (See examples)


Example 1:



Input: root = [1,null,3,2,4,null,5,6]

Output: [1,3,5,6,2,4]

Example 2:



Input: root =
 [1,null,2,3,4,5,null,null,6,7,null,8,null,9,10,null,null,11,null,12,null,13,null,null,14]

Output: [1,2,3,6,7,11,14,4,8,12,5,9,13,10]

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^4$
- The height of the n-ary tree is less than or equal to 1000 .

590. N-ary Tree Postorder Traversal


Easy

187287Add to ListShare

Given the `root` of an n-ary tree, return *the postorder traversal of its nodes' values*.

Nary-Tree input serialization is represented in their level order traversal. Each group of children is separated by the null value (See examples)


Example 1:



Input: `root = [1,null,3,2,4,null,5,6]`

Output: `[5,6,3,2,4,1]`

Example 2:



Input: root = [1,null,2,3,4,5,null,null,6,7,null,8,null,9,10,null,null,11,null,12,null,13,null,null,14]

Output: [2,6,14,11,7,3,12,8,4,13,9,10,5,1]

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^4$
- The height of the n-ary tree is less than or equal to 1000.

591. Tag Validator

Hard

144600Add to ListShare

Given a string representing a code snippet, implement a tag validator to parse the code and return whether it is valid.

A code snippet is valid if all the following rules hold:

1. The code must be wrapped in a **valid closed tag**. Otherwise, the code is invalid.
2. A **closed tag** (not necessarily valid) has exactly the following format : `<TAG_NAME>TAG_CONTENT</TAG_NAME>`. Among them, `<TAG_NAME>` is the start tag, and `</TAG_NAME>` is the end tag. The TAG_NAME in start and end tags should be the same. A closed tag is **valid** if and only if the TAG_NAME and TAG_CONTENT are valid.
3. A **valid TAG_NAME** only contain **upper-case letters**, and has length in range [1,9]. Otherwise, the TAG_NAME is **invalid**.
4. A **valid TAG_CONTENT** may contain other **valid closed tags**, **cdata** and any characters (see note1) **EXCEPT** unmatched `<`, unmatched start and end tag, and unmatched or closed tags with invalid TAG_NAME. Otherwise, the TAG_CONTENT is **invalid**.
5. A start tag is unmatched if no end tag exists with the same TAG_NAME, and vice versa. However, you also need to consider the issue of unbalanced when tags are nested.
6. A `<` is unmatched if you cannot find a subsequent `>`. And when you find a `<` or `</`, all the subsequent characters until the next `>` should be parsed as TAG_NAME (not necessarily valid).
7. The cdata has the following format: `<! [CDATA[CDATA_CONTENT]]>`. The range of `CDATA_CONTENT` is defined as the characters between `<! [CDATA[` and the **first subsequent]]**.
8. `CDATA_CONTENT` may contain **any characters**. The function of cdata is to forbid the validator to parse `CDATA_CONTENT`, so even it has some characters that can be parsed as tag (no matter valid or invalid), you should treat it as **regular characters**.

Example 1:

Input: code = "`<DIV>This is the first line <! [CDATA[<div>]]></DIV>`"

Output: true

Explanation:

The code is wrapped in a closed tag : `<DIV>` and `</DIV>`.

The TAG_NAME is valid, the TAG_CONTENT consists of some characters and cdata.

Although `CDATA_CONTENT` has an unmatched start tag with invalid TAG_NAME, it should be considered as plain text, not parsed as a tag.

So TAG_CONTENT is valid, and then the code is valid. Thus return true.

Example 2:

Input: code = "<DIV>>> ![CDATA[[]] <!CDATA[<div>]>]]>>>]</DIV>"

Output: true

Explanation:

We first separate the code into : start_tag|tag_content|end_tag.

start_tag -> "<DIV>"

end_tag -> "</DIV>"

tag_content could also be separated into : text1|cdata|text2.

text1 -> ">> ![CDATA[[]] "

cdata -> "<!CDATA[<div>]>]", where the CDATA_CONTENT is "<div>]"

text2 -> "]]>>]"

The reason why start_tag is NOT "<DIV>>>" is because of the rule 6.

The reason why cdata is NOT "<!CDATA[<div>]>]]>" is because of the rule 7.

Example 3:

Input: code = "<A> "

Output: false

Explanation: Unbalanced. If "<A>" is closed, then "" must be unmatched, and vice versa.

Constraints:

- `1 <= code.length <= 500`
- `code` consists of English letters, digits, '<', '>', '/', '!', '[', ']', '.', and ' '.

592. Fraction Addition and Subtraction

Medium

325466Add to ListShare

Given a string `expression` representing an expression of fraction addition and subtraction, return the calculation result in string format.

The final result should be an irreducible fraction. If your final result is an integer, change it to the format of a fraction that has a denominator `1`. So in this case, `2` should be converted to `2/1`.

Example 1:**Input:** expression = "-1/2+1/2"**Output:** "0/1"**Example 2:****Input:** expression = "-1/2+1/2+1/3"**Output:** "1/3"**Example 3:****Input:** expression = "1/3-1/2"**Output:** "-1/6"**Constraints:**

- The input string only contains '0' to '9', '/', '+' and '-'. So does the output.
- Each fraction (input and output) has the format $\pm \text{numerator}/\text{denominator}$. If the first input fraction or the output is positive, then '+' will be omitted.
- The input only contains valid **irreducible fractions**, where the **numerator** and **denominator** of each fraction will always be in the range $[1, 10]$. If the denominator is 1, it means this fraction is actually an integer in a fraction format defined above.
- The number of given fractions will be in the range $[1, 10]$.
- The numerator and denominator of the **final result** are guaranteed to be valid and in the range of **32-bit** int.

593. Valid Square**Medium**

791819Add to ListShare

Given the coordinates of four points in 2D space p_1, p_2, p_3 and p_4 , return `true` if the four points construct a square.

The coordinate of a point p_i is represented as $[x_i, y_i]$. The input is **not** given in any order.

A **valid square** has four equal sides with positive length and four equal angles (90-degree angles).

Example 1:

Input: p1 = [0,0], p2 = [1,1], p3 = [1,0], p4 = [0,1]

Output: true

Example 2:

Input: p1 = [0,0], p2 = [1,1], p3 = [1,0], p4 = [0,12]

Output: false

Example 3:

Input: p1 = [1,0], p2 = [-1,0], p3 = [0,1], p4 = [0,-1]

Output: true

Constraints:

- $p1.length == p2.length == p3.length == p4.length == 2$
- $-10^4 \leq x_i, y_i \leq 10^4$

594. Longest Harmonious Subsequence

Easy

1712163Add to ListShare

We define a harmonious array as an array where the difference between its maximum value and its minimum value is **exactly 1**.

Given an integer array `nums`, return *the length of its longest harmonious subsequence among all its possible subsequences*.

A **subsequence** of array is a sequence that can be derived from the array by deleting some or no elements without changing the order of the remaining elements.

Example 1:

Input: nums = [1,3,2,2,5,2,3,7]

Output: 5

Explanation: The longest harmonious subsequence is [3,2,2,2,3].

Example 2:

Input: nums = [1,2,3,4]

Output: 2

Example 3:

Input: `nums = [1,1,1,1]`

Output: `0`

Constraints:

- `1 <= nums.length <= 2 * 104`
- `-109 <= nums[i] <= 109`

595. Big Countries

Easy

12741017Add to ListShare

SQL Schema

Table: `World`

Column Name	Type
<code>name</code>	<code>varchar</code>
<code>continent</code>	<code>varchar</code>
<code>area</code>	<code>int</code>
<code>population</code>	<code>int</code>
<code>gdp</code>	<code>int</code>

`name` is the primary key column for this table.

Each row of this table gives information about the name of a country, the continent to which it belongs, its area, the population, and its GDP value.

A country is **big** if:

- it has an area of at least three million (i.e., `3000000 km2`), or
- it has a population of at least twenty-five million (i.e., `25000000`).

Write an SQL query to report the name, population, and area of the **big countries**.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

World table:

name	continent	area	population	gdp
Afghanistan	Asia	652230	25500100	20343000000
Albania	Europe	28748	2831741	12960000000
Algeria	Africa	2381741	37100000	188681000000
Andorra	Europe	468	78115	3712000000
Angola	Africa	1246700	20609294	100990000000

Output:

name	population	area
Afghanistan	25500100	652230
Algeria	37100000	2381741

596. Classes More Than 5 Students

Easy

563961Add to ListShare

SQL Schema

Table: Courses

Column Name	Type
student	varchar
class	varchar

(student, class) is the primary key column for this table.

Each row of this table indicates the name of a student and the class in which they are enrolled.

Write an SQL query to report all the classes that have **at least five students**.

Return the result table in **any order**.

The query result format is in the following example.

Example 1:

Input:

Courses table:

student	class
A	Math
B	English
C	Math
D	Biology
E	Math
F	Computer
G	Math

H	Math	
I	Math	
+-----+-----+		

Output:

+-----+	
class	
+-----+	
Math	
+-----+	

Explanation:

- Math has 6 students, so we include it.
- English has 1 student, so we do not include it.
- Biology has 1 student, so we do not include it.
- Computer has 1 student, so we do not include it.

598. Range Addition II


Easy

724842Add to ListShare

You are given an $m \times n$ matrix M initialized with all 0's and an array of operations ops , where $ops[i] = [a_i, b_i]$ means $M[x][y]$ should be incremented by one for all $0 \leq x < a_i$ and $0 \leq y < b_i$.

Count and return the number of maximum integers in the matrix after performing all the operations.

Example 1:



Input: $m = 3$, $n = 3$, $ops = [[2,2], [3,3]]$

Output: 4

Explanation: The maximum integer in M is 2, and there are four of it in M. So return 4.

Example 2:

Input: m = 3, n = 3, ops =
[[2,2],[3,3],[3,3],[3,3],[2,2],[3,3],[3,3],[3,3],[2,2],[3,3],[3,3],[3,3]]

Output: 4

Example 3:

Input: m = 3, n = 3, ops = []

Output: 9

Constraints:

- $1 \leq m, n \leq 4 * 10^4$
- $0 \leq \text{ops.length} \leq 10^4$
- $\text{ops}[i].length == 2$
- $1 \leq a_i \leq m$
- $1 \leq b_i \leq n$

599. Minimum Index Sum of Two Lists

Easy

1457349Add to ListShare

Given two arrays of strings `list1` and `list2`, find the **common strings with the least index sum**.

A **common string** is a string that appeared in both `list1` and `list2`.

A **common string with the least index sum** is a common string such that if it appeared at `list1[i]` and `list2[j]` then $i + j$ should be the minimum value among all the other **common strings**.

Return *all the common strings with the least index sum*. Return the answer in **any order**.

Example 1:

Input: list1 = ["Shogun", "Tapioca Express", "Burger King", "KFC"], list2 = ["Piatti", "The Grill at Torrey Pines", "Hungry Hunter Steakhouse", "Shogun"]

Output: ["Shogun"]

Explanation: The only common string is "Shogun".

Example 2:

Input: list1 = ["Shogun", "Tapioca Express", "Burger King", "KFC"], list2 = ["KFC", "Shogun", "Burger King"]

Output: ["Shogun"]

Explanation: The common string with the least index sum is "Shogun" with index sum = $(0 + 1) = 1$.

Example 3:

Input: list1 = ["happy", "sad", "good"], list2 = ["sad", "happy", "good"]

Output: ["sad", "happy"]

Explanation: There are three common strings:

"happy" with index sum = $(0 + 1) = 1$.

"sad" with index sum = $(1 + 0) = 1$.

"good" with index sum = $(2 + 2) = 4$.

The strings with the least index sum are "sad" and "happy".

Constraints:

- $1 \leq \text{list1.length}, \text{list2.length} \leq 1000$
- $1 \leq \text{list1[i].length}, \text{list2[i].length} \leq 30$
- `list1[i]` and `list2[i]` consist of spaces ' ' and English letters.
- All the strings of `list1` are **unique**.
- All the strings of `list2` are **unique**.

600. Non-negative Integers without Consecutive Ones

Hard

1191118Add to ListShare

Given a positive integer `n`, return the number of the integers in the range $[0, n]$ whose binary representations **do not** contain consecutive ones.

Example 1:

Input: `n = 5`

Output: 5

Explanation:

Here are the non-negative integers ≤ 5 with their corresponding binary representations:

0 : 0

1 : 1

2 : 10

3 : 11

4 : 100

5 : 101

Among them, only integer 3 disobeys the rule (two consecutive ones) and the other 5 satisfy the rule.

Example 2:

Input: n = 1

Output: 2

Example 3:

Input: n = 2

Output: 3

Constraints:

- $1 \leq n \leq 10^9$
- **601. Human Traffic of Stadium**
- **Hard**
- 424511Add to ListShare
- SQL Schema
- Table: `Stadium`
- | | |
|-------------|------|
| Column Name | Type |
|-------------|------|
- | | |
|----|-----|
| id | int |
|----|-----|
- | | |
|------------|------|
| visit_date | date |
|------------|------|
- | | |
|--------|-----|
| people | int |
|--------|-----|
- | | |
|--|--|
| | |
|--|--|
- `visit_date` is the primary key for this table.

- Each row of this table contains the visit date and visit id to the stadium with the number of people during the visit.
- No two rows will have the same visit_date, and as the id increases, the dates increase as well.
-
- Write an SQL query to display the records with three or more rows with consecutive id's, and the number of people is greater than or equal to 100 for each.
- Return the result table ordered by visit_date in ascending order.
- The query result format is in the following example.
-

• Example 1:

- **Input:**

- Stadium table:

id	visit_date	people
1	2017-01-01	10
2	2017-01-02	109
3	2017-01-03	150
4	2017-01-04	99
5	2017-01-05	145
6	2017-01-06	1455
7	2017-01-07	199
8	2017-01-09	188

- **Output:**

id	visit_date	people
5	2017-01-05	145
6	2017-01-06	1455
7	2017-01-07	199
8	2017-01-09	188

- **Explanation:**

- The four rows with ids 5, 6, 7, and 8 have consecutive ids and each of them has ≥ 100 people attended. Note that row 8 was included even though the visit_date was not the next day after row 7.
- The rows with ids 2 and 3 are not included because we need at least three consecutive ids.

605. Can Place Flowers

Easy

3182684 Add to List Share

You have a long flowerbed in which some of the plots are planted, and some are not. However, flowers cannot be planted in adjacent plots.

Given an integer array `flowerbed` containing 0's and 1's, where 0 means empty and 1 means not empty, and an integer `n`, return if `n` new flowers can be planted in the `flowerbed` without violating the no-adjacent-flowers rule.

Example 1:

Input: `flowerbed = [1,0,0,0,1]`, `n = 1`

Output: `true`

Example 2:

Input: `flowerbed = [1,0,0,0,1]`, `n = 2`

Output: `false`

Constraints:

- `1 <= flowerbed.length <= 2 * 104`
- `flowerbed[i]` is 0 or 1.
- There are no two adjacent flowers in `flowerbed`.
- `0 <= n <= flowerbed.length`

606. Construct String from Binary Tree


Easy

23402841Add to ListShare

Given the `root` of a binary tree, construct a string consisting of parenthesis and integers from a binary tree with the preorder traversal way, and return it.

Omit all the empty parenthesis pairs that do not affect the one-to-one mapping relationship between the string and the original binary tree.

Example 1:




Input: root = [1,2,3,4]

Output: "1(2(4))(3)"

Explanation: Originally, it needs to be "1(2(4)())(3())()", but you need to omit all the unnecessary empty parenthesis pairs. And it will be "1(2(4))(3)"

Example 2:



Input: root = [1,2,3,null,4]

Output: "1(2()(4))(3)"

Explanation: Almost the same as the first example, except we cannot omit the first parenthesis pair to break the one-to-one mapping relationship between the input and the output.

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-1000 \leq \text{Node.val} \leq 1000$

607. Sales Person• **Easy**

- 55264Add to ListShare

• SQL Schema

- Table: `SalesPerson`

Column Name	Type
<code>sales_id</code>	int
<code>name</code>	varchar
<code>salary</code>	int
<code>commission_rate</code>	int
<code>hire_date</code>	date

- `sales_id` is the primary key column for this table.
- Each row of this table indicates the name and the ID of a salesperson alongside their salary, commission rate, and hire date.

-

- Table: `Company`

Column Name	Type
<code>com_id</code>	int
<code>name</code>	varchar
<code>city</code>	varchar

- `com_id` is the primary key column for this table.
- Each row of this table indicates the name and the ID of a company and the city in which the company is located.

-

- Table: `Orders`

Column Name	Type
<code>order_id</code>	int
<code>order_date</code>	date
<code>com_id</code>	int
<code>sales_id</code>	int
<code>amount</code>	int

- `order_id` is the primary key column for this table.
- `com_id` is a foreign key to `com_id` from the `Company` table.
- `sales_id` is a foreign key to `sales_id` from the `SalesPerson` table.

- Each row of this table contains information about one order. This includes the ID of the company, the ID of the salesperson, the date of the order, and the amount paid.
- Write an SQL query to report the names of all the salespersons who did not have any orders related to the company with the name "RED".
- Return the result table in **any order**.
- The query result format is in the following example.
-

- **Example 1:**

- **Input:**

- SalesPerson table:

sales_id	name	salary	commission_rate	hire_date
1	John	100000	6	4/1/2006
2	Amy	12000	5	5/1/2010
3	Mark	65000	12	12/25/2008
4	Pam	25000	25	1/1/2005
5	Alex	5000	10	2/3/2007

- Company table:

com_id	name	city
1	RED	Boston
2	ORANGE	New York
3	YELLOW	Boston
4	GREEN	Austin

- Orders table:

order_id	order_date	com_id	sales_id	amount
1	1/1/2014	3	4	10000
2	2/1/2014	4	5	5000
3	3/1/2014	1	1	50000
4	4/1/2014	1	4	25000

- **Output:**

name
Amy
Mark
Alex

- **Explanation:**

- According to orders 3 and 4 in the Orders table, it is easy to tell that only salesperson John and Pam have sales to company RED, so we report all the other names in the table salesperson.

608. Tree Node

Medium

70744Add to ListShare

SQL Schema

Table: `Tree`

Column Name	Type
<code>id</code>	<code>int</code>
<code>p_id</code>	<code>int</code>

`id` is the primary key column for this table.

Each row of this table contains information about the `id` of a node and the `id` of its parent node in a tree.

The given structure is always a valid tree.

Each node in the tree can be one of three types:


- "**Leaf**": if the node is a leaf node.
- "**Root**": if the node is the root of the tree.
- "**Inner**": If the node is neither a leaf node nor a root node.

Write an SQL query to report the type of each node in the tree.

Return the result table **ordered** by `id` **in ascending order**.

The query result format is in the following example.

Example 1:



Input:

Tree table:

id	p_id
1	null
2	1
3	1
4	2
5	2

Output:

id	type
1	Root
2	Inner
3	Leaf
4	Leaf
5	Leaf

```
+---+-----+
```

Explanation:

Node 1 is the root node because its parent node is null and it has child nodes 2 and 3.

Node 2 is an inner node because it has parent node 1 and child node 4 and 5.

Nodes 3, 4, and 5 are leaf nodes because they have parent nodes and they do not have child nodes.

Example 2:



Input:

Tree table:

```
+---+-----+
| id | p_id |
+---+-----+
| 1  | null |
+---+-----+
```

Output:

```
+---+-----+
| id | type  |
+---+-----+
| 1  | Root  |
+---+-----+
```

Explanation: If there is only one node on the tree, you only need to output its root attributes.

609. Find Duplicate File in System

Medium

13991583Add to ListShare

Given a list `paths` of directory info, including the directory path, and all the files with contents in this directory, return *all the duplicate files in the file system in terms of their paths*. You may return the answer in **any order**.

A group of duplicate files consists of at least two files that have the same content.

A single directory info string in the input list has the following format:

- `"root/d1/d2/.../dm f1.txt(f1_content) f2.txt(f2_content) ... fn.txt(fn_content)"`

It means there are `n` files (`f1.txt, f2.txt ... fn.txt`) with content (`f1_content, f2_content ... fn_content`) respectively in the directory "`root/d1/d2/.../dm`". Note that `n >= 1` and `m >= 0`. If `m = 0`, it means the directory is just the root directory.

The output is a list of groups of duplicate file paths. For each group, it contains all the file paths of the files that have the same content. A file path is a string that has the following format:

- `"directory_path/file_name.txt"`

Example 1:

Input: `paths = ["root/a 1.txt(abcd) 2.txt(efgh)", "root/c 3.txt(abcd)", "root/c/d 4.txt(efgh)", "root 4.txt(efgh)"]`

Output:

`[["root/a/2.txt", "root/c/d/4.txt", "root/4.txt"], ["root/a/1.txt", "root/c/3.txt"]]`

Example 2:

Input: `paths = ["root/a 1.txt(abcd) 2.txt(efgh)", "root/c 3.txt(abcd)", "root/c/d 4.txt(efgh)"]`

Output: `[["root/a/2.txt", "root/c/d/4.txt"], ["root/a/1.txt", "root/c/3.txt"]]`

Constraints:

- `1 <= paths.length <= 2 * 104`
- `1 <= paths[i].length <= 3000`
- `1 <= sum(paths[i].length) <= 5 * 105`
- `paths[i]` consist of English letters, digits, `'/'`, `'.'`, `'('`, `')'`, and `' '`.
- You may assume no files or directories share the same name in the same directory.
- You may assume each given directory info represents a unique directory. A single blank space separates the directory path and file info.

611. Valid Triangle Number

Medium

2938164Add to ListShare

Given an integer array `nums`, return *the number of triplets chosen from the array that can make triangles if we take them as side lengths of a triangle*.

Example 1:

Input: `nums = [2,2,3,4]`

Output: 3

Explanation: Valid combinations are:

2,3,4 (using the first 2)

2,3,4 (using the second 2)

2,2,3

Example 2:

Input: `nums = [4,2,3,4]`

Output: 4

Constraints:

- `1 <= nums.length <= 1000`
- `0 <= nums[i] <= 1000`

617. Merge Two Binary Trees

Easy


7330259Add to ListShare

You are given two binary trees `root1` and `root2`.

Imagine that when you put one of them to cover the other, some nodes of the two trees are overlapped while the others are not. You need to merge the two trees into a new binary tree. The merge rule is that if two nodes overlap, then sum node values up as the new value of the merged node. Otherwise, the NOT null node will be used as the node of the new tree.

Return *the merged tree*.

Note: The merging process must start from the root nodes of both trees.

Example 1:

Input: root1 = [1,3,2,5], root2 = [2,1,3,null,4,null,7]

Output: [3,4,5,5,4,null,7]

Example 2:

Input: root1 = [1], root2 = [1,2]

Output: [2,2]

Constraints:

- The number of nodes in both trees is in the range [0, 2000].
- $-10^4 \leq \text{Node.val} \leq 10^4$

620. Not Boring Movies

Easy

564374Add to ListShare

SQL Schema

Table: Cinema

Column Name	Type
id	int
movie	varchar

```

| description | varchar |
| rating     | float   |
+-----+-----+
id is the primary key for this table.

Each row contains information about the name of a movie, its genre, and its rating.

rating is a 2 decimal places float in the range [0, 10]

```

Write an SQL query to report the movies with an odd-numbered ID and a description that is not "boring".

Return the result table ordered by `rating` in **descending order**.

The query result format is in the following example.

Example 1:

Input:

Cinema table:

```

+-----+-----+-----+-----+
| id | movie      | description | rating |
+-----+-----+-----+-----+
| 1  | War        | great 3D   | 8.9    |
| 2  | Science    | fiction    | 8.5    |
| 3  | irish      | boring     | 6.2    |
| 4  | Ice song   | Fantacy   | 8.6    |
| 5  | House card | Interesting | 9.1    |
+-----+-----+-----+-----+

```

Output:

```

+-----+-----+-----+-----+
| id | movie      | description | rating |
+-----+-----+-----+-----+

```

5	House card	Interesting	9.1
1	War	great 3D	8.9

Explanation:

We have three movies with odd-numbered IDs: 1, 3, and 5. The movie with ID = 3 is boring so we do not include it in the answer.

621. Task Scheduler**Medium**

73881451Add to ListShare

Given a characters array `tasks`, representing the tasks a CPU needs to do, where each letter represents a different task. Tasks could be done in any order. Each task is done in one unit of time. For each unit of time, the CPU could complete either one task or just be idle.

However, there is a non-negative integer `n` that represents the cooldown period between two **same tasks** (the same letter in the array), that is that there must be at least `n` units of time between any two same tasks.

Return *the least number of units of times that the CPU will take to finish all the given tasks*.

Example 1:

Input: `tasks = ["A", "A", "A", "B", "B", "B"]`, `n = 2`

Output: 8

Explanation:

`A -> B -> idle -> A -> B -> idle -> A -> B`

There is at least 2 units of time between any two same tasks.

Example 2:

Input: `tasks = ["A", "A", "A", "B", "B", "B"]`, `n = 0`

Output: 6

Explanation: On this case any permutation of size 6 would work since `n = 0`.

`["A", "A", "A", "B", "B", "B"]`

`["A", "B", "A", "B", "A", "B"]`

```
[ "B", "B", "B", "A", "A", "A" ]
```

...

And so on.

Example 3:

Input: tasks = ["A", "A", "A", "A", "A", "A", "B", "C", "D", "E", "F", "G"], n = 2

Output: 16

Explanation:

One possible solution is

A -> B -> C -> A -> D -> E -> A -> F -> G -> A -> idle -> idle -> A -> idle -> A

Constraints:

- `1 <= task.length <= 104`
- `tasks[i]` is upper-case English letter.
- The integer `n` is in the range `[0, 100]`.

622. Design Circular Queue

Medium

2772226Add to ListShare

Design your implementation of the circular queue. The circular queue is a linear data structure in which the operations are performed based on FIFO (First In First Out) principle and the last position is connected back to the first position to make a circle. It is also called "Ring Buffer".

One of the benefits of the circular queue is that we can make use of the spaces in front of the queue. In a normal queue, once the queue becomes full, we cannot insert the next element even if there is a space in front of the queue. But using the circular queue, we can use the space to store new values.

Implementation the `MyCircularQueue` class:

- `MyCircularQueue (k)` Initializes the object with the size of the queue to be `k`.
- `int Front ()` Gets the front item from the queue. If the queue is empty, return `-1`.
- `int Rear ()` Gets the last item from the queue. If the queue is empty, return `-1`.
- `boolean enqueue (int value)` Inserts an element into the circular queue. Return `true` if the operation is successful.
- `boolean dequeue ()` Deletes an element from the circular queue. Return `true` if the operation is successful.
- `boolean isEmpty ()` Checks whether the circular queue is empty or not.

- `boolean isFull()` Checks whether the circular queue is full or not.

You must solve the problem without using the built-in queue data structure in your programming language.

Example 1:

Input

```
["MyCircularQueue", "enQueue", "enQueue", "enQueue", "enQueue", "Rear", "isFull",
"deQueue", "enQueue", "Rear"]
[[3], [1], [2], [3], [4], [], [], [], [4], []]
```

Output

```
[null, true, true, true, false, 3, true, true, true, 4]
```

Explanation

```
MyCircularQueue myCircularQueue = new MyCircularQueue(3);

myCircularQueue.enQueue(1); // return True

myCircularQueue.enQueue(2); // return True

myCircularQueue.enQueue(3); // return True

myCircularQueue.enQueue(4); // return False

myCircularQueue.Rear(); // return 3

myCircularQueue.isFull(); // return True

myCircularQueue.deQueue(); // return True

myCircularQueue.enQueue(4); // return True

myCircularQueue.Rear(); // return 4
```

Constraints:

- $1 \leq k \leq 1000$
- $0 \leq \text{value} \leq 1000$
- At most 3000 calls will be made to `enQueue`, `deQueue`, `Front`, `Rear`, `isEmpty`, and `isFull`.

623. Add One Row to Tree

Medium

1440180Add to ListShare


Given the `root` of a binary tree and two integers `val` and `depth`, add a row of nodes with value `val` at the given depth `depth`.

Note that the `root` node is at depth `1`.

The adding rule is:

- Given the integer `depth`, for each not null tree node `cur` at the depth `depth - 1`, create two tree nodes with value `val` as `cur`'s left subtree root and right subtree root.
- `cur`'s original left subtree should be the left subtree of the new left subtree root.
- `cur`'s original right subtree should be the right subtree of the new right subtree root.
- If `depth == 1` that means there is no depth `depth - 1` at all, then create a tree node with value `val` as the new root of the whole original tree, and the original tree is the new root's left subtree.


Example 1:



Input: `root = [4,2,6,3,1,5]`, `val = 1`, `depth = 2`

Output: `[4,1,1,2,null,null,6,3,1,5]`

Example 2:



Input: root = [4,2,null,3,1], val = 1, depth = 3

Output: [4,2,null,1,1,3,null,null,1]

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- The depth of the tree is in the range $[1, 10^4]$.
- $-100 \leq \text{Node.val} \leq 100$
- $-10^5 \leq \text{val} \leq 10^5$
- $1 \leq \text{depth} \leq \text{the depth of tree} + 1$

626. Exchange Seats

Medium

803388Add to ListShare

SQL Schema

Table: `Seat`

Column Name	Type

```

| id          | int      |
| student     | varchar  |
+-----+-----+

```

id is the primary key column for this table.

Each row of this table indicates the name and the ID of a student.

id is a continuous increment.

Write an SQL query to swap the seat id of every two consecutive students. If the number of students is odd, the id of the last student is not swapped.

Return the result table ordered by **id in ascending order**.

The query result format is in the following example.

Example 1:

Input:

Seat table:

```

+-----+
| id | student |
+-----+
| 1  | Abbot   |
| 2  | Doris   |
| 3  | Emerson |
| 4  | Green   |
| 5  | Jeames  |
+-----+

```

Output:

```

+-----+
| id | student |
+-----+

```

1	Doris
2	Abbot
3	Green
4	Emerson
5	Jeames

Explanation:

Note that if the number of students is odd, there is no need to change the last one's seat.

627. Swap Salary

Easy

1201536Add to ListShare

SQL Schema

Table: `Salary`

Column Name	Type
<code>id</code>	<code>int</code>
<code>name</code>	<code>varchar</code>
<code>sex</code>	<code>ENUM</code>
<code>salary</code>	<code>int</code>

`id` is the primary key for this table.

The `sex` column is `ENUM` value of type ('m', 'f').

The table contains information about an employee.

Write an SQL query to swap all '`f`' and '`m`' values (i.e., change all '`f`' values to '`m`' and vice versa) with a **single update statement** and no intermediate temporary tables.

Note that you must write a single update statement, **do not** write any select statement for this problem.

The query result format is in the following example.

Example 1:

Input:

Salary table:

id	name	sex	salary
1	A	m	2500
2	B	f	1500
3	C	m	5500
4	D	f	500

Output:

id	name	sex	salary
1	A	f	2500
2	B	m	1500
3	C	f	5500
4	D	m	500

Explanation:

(1, A) and (3, C) were changed from 'm' to 'f'.

(2, B) and (4, D) were changed from 'f' to 'm'.

628. Maximum Product of Three Numbers

Easy

3180560Add to ListShare

Given an integer array `nums`, *find three numbers whose product is maximum and return the maximum product.*

Example 1:

Input: `nums = [1,2,3]`

Output: 6

Example 2:

Input: `nums = [1,2,3,4]`

Output: 24

Example 3:

Input: `nums = [-1,-2,-3]`

Output: -6

Constraints:

- $3 \leq \text{nums.length} \leq 10^4$
- $-1000 \leq \text{nums}[i] \leq 1000$

629. K Inverse Pairs Array

Hard

1838212Add to ListShare

For an integer array `nums`, an **inverse pair** is a pair of integers `[i, j]` where $0 \leq i < j < \text{nums.length}$ and $\text{nums}[i] > \text{nums}[j]$.

Given two integers n and k , return the number of different arrays consist of numbers from 1 to n such that there are exactly k **inverse pairs**. Since the answer can be huge, return it **modulo** $10^9 + 7$.

Example 1:

Input: `n = 3, k = 0`

Output: 1

Explanation: Only the array [1,2,3] which consists of numbers from 1 to 3 has exactly 0 inverse pairs.

Example 2:

Input: n = 3, k = 1

Output: 2

Explanation: The array [1,3,2] and [2,1,3] have exactly 1 inverse pair.

Constraints:

- $1 \leq n \leq 1000$
- $0 \leq k \leq 1000$

630. Course Schedule III

Hard

329786Add to ListShare

There are n different online courses numbered from 1 to n . You are given an array `courses` where `courses[i] = [durationi, lastDayi]` indicate that the i^{th} course should be taken **continuously** for `durationi` days and must be finished before or on `lastDayi`.

You will start on the 1st day and you cannot take two or more courses simultaneously.

Return *the maximum number of courses that you can take*.

Example 1:

Input: courses = [[100,200],[200,1300],[1000,1250],[2000,3200]]

Output: 3

Explanation:

There are totally 4 courses, but you can take 3 courses at most:

First, take the 1st course, it costs 100 days so you will finish it on the 100th day, and ready to take the next course on the 101st day.

Second, take the 3rd course, it costs 1000 days so you will finish it on the 1100th day, and ready to take the next course on the 1101st day.

Third, take the 2nd course, it costs 200 days so you will finish it on the 1300th day.

The 4th course cannot be taken now, since you will finish it on the 3300th day, which exceeds the closed date.

Example 2:

Input: courses = [[1,2]]

Output: 1

Example 3:

Input: courses = [[3,2],[4,3]]

Output: 0

Constraints:

- $1 \leq \text{courses.length} \leq 10^4$
- $1 \leq \text{duration}_i, \text{lastDay}_i \leq 10^4$

632. Smallest Range Covering Elements from K Lists

Hard

258442Add to ListShare

You have k lists of sorted integers in **non-decreasing order**. Find the **smallest** range that includes at least one number from each of the k lists.

We define the range $[a, b]$ is smaller than range $[c, d]$ if $b - a < d - c$ or $a < c$ if $b - a == d - c$.

Example 1:

Input: nums = [[4,10,15,24,26],[0,9,12,20],[5,18,22,30]]

Output: [20,24]

Explanation:

List 1: [4, 10, 15, 24, 26], 24 is in range [20,24].

List 2: [0, 9, 12, 20], 20 is in range [20,24].

List 3: [5, 18, 22, 30], 22 is in range [20,24].

Example 2:

Input: nums = [[1,2,3],[1,2,3],[1,2,3]]

Output: [1,1]

Constraints:

- `nums.length == k`
- `1 <= k <= 3500`
- `1 <= nums[i].length <= 50`
- `-105 <= nums[i][j] <= 105`
- `nums[i]` is sorted in **non-decreasing** order.

633. Sum of Square Numbers

Medium

1746490Add to ListShare

Given a non-negative integer `c`, decide whether there're two integers `a` and `b` such that $a^2 + b^2 = c$.

Example 1:

Input: `c = 5`

Output: `true`

Explanation: $1 * 1 + 2 * 2 = 5$

Example 2:

Input: `c = 3`

Output: `false`

Constraints:

- `0 <= c <= 231 - 1`

636. Exclusive Time of Functions

Medium

17122521Add to ListShare

On a **single-threaded** CPU, we execute a program containing `n` functions. Each function has a unique ID between `0` and `n-1`.


Function calls are **stored in a call stack**: when a function call starts, its ID is pushed onto the stack, and when a function call ends, its ID is popped off the stack. The function whose ID is at the top of the stack is **the current function being executed**. Each time a function starts or ends, we write a log with the ID, whether it started or ended, and the timestamp.

You are given a list `logs`, where `logs[i]` represents the i^{th} log message formatted as a string "`{function_id}:{start|end}:{timestamp}`". For example, "`0:start:3`" means a function call with function ID `0` **started at the beginning** of timestamp `3`, and "`1:end:2`" means a function call with function ID `1` **ended at the end** of timestamp `2`. Note that a function can be called **multiple times, possibly recursively**.

A function's **exclusive time** is the sum of execution times for all function calls in the program. For example, if a function is called twice, one call executing for `2` time units and another call executing for `1` time unit, the **exclusive time** is $2 + 1 = 3$.

Return the **exclusive time** of each function in an array, where the value at the i^{th} index represents the exclusive time for the function with ID `i`.

Example 1:



Input: `n = 2, logs = ["0:start:0", "1:start:2", "1:end:5", "0:end:6"]`

Output: `[3,4]`

Explanation:

Function `0` starts at the beginning of time `0`, then it executes for `2` units of time and reaches the end of time `1`.

Function `1` starts at the beginning of time `2`, executes for `4` units of time, and ends at the end of time `5`.

Function 0 resumes execution at the beginning of time 6 and executes for 1 unit of time.

So function 0 spends $2 + 1 = 3$ units of total time executing, and function 1 spends 4 units of total time executing.

Example 2:

Input: $n = 1$, logs =
`["0:start:0", "0:start:2", "0:end:5", "0:start:6", "0:end:6", "0:end:7"]`

Output: [8]

Explanation:

Function 0 starts at the beginning of time 0, executes for 2 units of time, and recursively calls itself.

Function 0 (recursive call) starts at the beginning of time 2 and executes for 4 units of time.

Function 0 (initial call) resumes execution then immediately calls itself again.

Function 0 (2nd recursive call) starts at the beginning of time 6 and executes for 1 unit of time.

Function 0 (initial call) resumes execution at the beginning of time 7 and executes for 1 unit of time.

So function 0 spends $2 + 4 + 1 + 1 = 8$ units of total time executing.

Example 3:

Input: $n = 2$, logs =
`["0:start:0", "0:start:2", "0:end:5", "1:start:6", "1:end:6", "0:end:7"]`

Output: [7,1]

Explanation:

Function 0 starts at the beginning of time 0, executes for 2 units of time, and recursively calls itself.

Function 0 (recursive call) starts at the beginning of time 2 and executes for 4 units of time.

Function 0 (initial call) resumes execution then immediately calls function 1.

Function 1 starts at the beginning of time 6, executes 1 unit of time, and ends at the end of time 6.

Function 0 resumes execution at the beginning of time 6 and executes for 2 units of time.

So function 0 spends $2 + 4 + 1 = 7$ units of total time executing, and function 1 spends 1 unit of total time executing.

Constraints:

- $1 \leq n \leq 100$
- $1 \leq \text{logs.length} \leq 500$
- $0 \leq \text{function_id} < n$
- $0 \leq \text{timestamp} \leq 10^9$
- No two start events will happen at the same timestamp.
- No two end events will happen at the same timestamp.
- Each function has an "end" log for each "start" log.


637. Average of Levels in Binary Tree

Easy

4296276Add to ListShare

Given the `root` of a binary tree, return *the average value of the nodes on each level in the form of an array*. Answers within 10^{-5} of the actual answer will be accepted.

Example 1:




Input: root = [3,9,20,null,null,15,7]

Output: [3.00000,14.50000,11.00000]

Explanation: The average value of nodes on level 0 is 3, on level 1 is 14.5, and on level 2 is 11.

Hence return [3, 14.5, 11].

Example 2:



Input: root = [3,9,20,15,7]

Output: [3.00000,14.50000,11.00000]

Constraints:

- The number of nodes in the tree is in the range [1, 10⁴].
- $-2^{31} \leq \text{Node.val} \leq 2^{31} - 1$

638. Shopping Offers

Medium

1159676Add to ListShare

In LeetCode Store, there are `n` items to sell. Each item has a price. However, there are some special offers, and a special offer consists of one or more different kinds of items with a sale price.

You are given an integer array `price` where `price[i]` is the price of the `ith` item, and an integer array `needs` where `needs[i]` is the number of pieces of the `ith` item you want to buy.

You are also given an array `special` where `special[i]` is of size `n + 1` where `special[i][j]` is the number of pieces of the `jth` item in the `ith` offer and `special[i][n]` (i.e., the last integer in the array) is the price of the `ith` offer.

Return *the lowest price you have to pay for exactly certain items as given, where you could make optimal use of the special offers*. You are not allowed to buy more items than you want, even if that would lower the overall price. You could use any of the special offers as many times as you want.

Example 1:

Input: price = [2,5], special = [[3,0,5],[1,2,10]], needs = [3,2]

Output: 14

Explanation: There are two kinds of items, A and B. Their prices are \$2 and \$5 respectively.

In special offer 1, you can pay \$5 for 3A and 0B

In special offer 2, you can pay \$10 for 1A and 2B.

You need to buy 3A and 2B, so you may pay \$10 for 1A and 2B (special offer #2), and \$4 for 2A.

Example 2:

Input: price = [2,3,4], special = [[1,1,0,4],[2,2,1,9]], needs = [1,2,1]

Output: 11

Explanation: The price of A is \$2, and \$3 for B, \$4 for C.

You may pay \$4 for 1A and 1B, and \$9 for 2A ,2B and 1C.

You need to buy 1A ,2B and 1C, so you may pay \$4 for 1A and 1B (special offer #1), and \$3 for 1B, \$4 for 1C.

You cannot add more items, though only \$9 for 2A ,2B and 1C.

Constraints:

- $n == \text{price.length} == \text{needs.length}$
- $1 \leq n \leq 6$
- $0 \leq \text{price}[i], \text{needs}[i] \leq 10$
- $1 \leq \text{special.length} \leq 100$
- $\text{special}[i].length == n + 1$
- $0 \leq \text{special}[i][j] \leq 50$

639. Decode Ways II

Hard

1230771Add to ListShare

A message containing letters from A-Z can be **encoded** into numbers using the following mapping:

```
'A' -> "1"
'B' -> "2"
...
'Z' -> "26"
```

To **decode** an encoded message, all the digits must be grouped then mapped back into letters using the reverse of the mapping above (there may be multiple ways). For example, "11106" can be mapped into:

- "AAJF" with the grouping (1 1 10 6)
- "KJF" with the grouping (11 10 6)

Note that the grouping (1 11 06) is invalid because "06" cannot be mapped into 'F' since "6" is different from "06".

In **addition** to the mapping above, an encoded message may contain the '*' character, which can represent any digit from '1' to '9' ('0' is excluded). For example, the encoded message "1*" may represent any of the encoded messages "11", "12", "13", "14", "15", "16", "17", "18", or "19". Decoding "1*" is equivalent to decoding **any** of the encoded messages it can represent.

Given a string s consisting of digits and '*' characters, return the **number of ways to decode** it.

Since the answer may be very large, return it **modulo** $10^9 + 7$.

Example 1:

Input: $s = "*"$

Output: 9

Explanation: The encoded message can represent any of the encoded messages "1", "2", "3", "4", "5", "6", "7", "8", or "9".

Each of these can be decoded to the strings "A", "B", "C", "D", "E", "F", "G", "H", and "I" respectively.

Hence, there are a total of 9 ways to decode "*".

Example 2:

Input: $s = "1*"$

Output: 18

Explanation: The encoded message can represent any of the encoded messages "11", "12", "13", "14", "15", "16", "17", "18", or "19".

Each of these encoded messages have 2 ways to be decoded (e.g. "11" can be decoded to "AA" or "K").

Hence, there are a total of $9 * 2 = 18$ ways to decode "1*".

Example 3:

Input: s = "2*"

Output: 15

Explanation: The encoded message can represent any of the encoded messages "21", "22", "23", "24", "25", "26", "27", "28", or "29".

"21", "22", "23", "24", "25", and "26" have 2 ways of being decoded, but "27", "28", and "29" only have 1 way.

Hence, there are a total of $(6 * 2) + (3 * 1) = 12 + 3 = 15$ ways to decode "2*".

Constraints:

- $1 \leq s.length \leq 10^5$
- $s[i]$ is a digit or '*'.

640. Solve the Equation

Medium

384742Add to ListShare

Solve a given equation and return the value of ' x ' in the form of a string " $x=#value$ ". The equation contains only '+', '-' operation, the variable ' x ' and its coefficient. You should return "No solution" if there is no solution for the equation, or "Infinite solutions" if there are infinite solutions for the equation.

If there is exactly one solution for the equation, we ensure that the value of ' x ' is an integer.

Example 1:

Input: equation = "x+5-3+x=6+x-2"

Output: "x=2"

Example 2:

Input: equation = "x=x"

Output: "Infinite solutions"

Example 3:

Input: equation = "2x=x"

Output: "x=0"

Constraints:

- `3 <= equation.length <= 1000`
- `equation` has exactly one '='.
- `equation` consists of integers with an absolute value in the range `[0, 100]` without any leading zeros, and the variable 'x'.

641. Design Circular Deque

Medium

85566Add to ListShare

Design your implementation of the circular double-ended queue (deque).

Implement the `MyCircularDeque` class:

- `MyCircularDeque(int k)` Initializes the deque with a maximum size of `k`.
- `boolean insertFront()` Adds an item at the front of Deque. Returns `true` if the operation is successful, or `false` otherwise.
- `boolean insertLast()` Adds an item at the rear of Deque. Returns `true` if the operation is successful, or `false` otherwise.
- `boolean deleteFront()` Deletes an item from the front of Deque. Returns `true` if the operation is successful, or `false` otherwise.
- `boolean deleteLast()` Deletes an item from the rear of Deque. Returns `true` if the operation is successful, or `false` otherwise.
- `int getFront()` Returns the front item from the Deque. Returns `-1` if the deque is empty.
- `int getRear()` Returns the last item from Deque. Returns `-1` if the deque is empty.
- `boolean isEmpty()` Returns `true` if the deque is empty, or `false` otherwise.
- `boolean isFull()` Returns `true` if the deque is full, or `false` otherwise.

Example 1:

Input

```
["MyCircularDeque", "insertLast", "insertLast", "insertFront", "insertFront",
 "getRear", "isFull", "deleteLast", "insertFront", "getFront"]
```

```
[[3], [1], [2], [3], [4], [], [], [], [4], []]
```

Output

```
[null, true, true, true, false, 2, true, true, true, 4]
```

Explanation

```
MyCircularDeque myCircularDeque = new MyCircularDeque(3);

myCircularDeque.insertLast(1); // return True

myCircularDeque.insertLast(2); // return True

myCircularDeque.insertFront(3); // return True

myCircularDeque.insertFront(4); // return False, the queue is full.

myCircularDeque.getRear(); // return 2

myCircularDeque.isFull(); // return True

myCircularDeque.deleteLast(); // return True

myCircularDeque.insertFront(4); // return True

myCircularDeque.getFront(); // return 4
```

Constraints:

- $1 \leq k \leq 1000$
- $0 \leq \text{value} \leq 1000$
- At most 2000 calls will be made to `insertFront`, `insertLast`, `deleteFront`, `deleteLast`, `getFront`, `getRear`, `isEmpty`, `isFull`.

643. Maximum Average Subarray I

Easy

1911171Add to ListShare

You are given an integer array `nums` consisting of `n` elements, and an integer `k`.

Find a contiguous subarray whose **length is equal to `k`** that has the maximum average value and return *this value*. Any answer with a calculation error less than 10^{-5} will be accepted.

Example 1:**Input:** nums = [1,12,-5,-6,50,3], k = 4**Output:** 12.75000**Explanation:** Maximum average is $(12 - 5 - 6 + 50) / 4 = 51 / 4 = 12.75$ **Example 2:****Input:** nums = [5], k = 1**Output:** 5.00000**Constraints:**

- $n == \text{nums.length}$
- $1 \leq k \leq n \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

645. Set Mismatch**Easy**

2284604Add to ListShare

You have a set of integers s , which originally contains all the numbers from 1 to n . Unfortunately, due to some error, one of the numbers in s got duplicated to another number in the set, which results in **repetition of one** number and **loss of another** number.

You are given an integer array `nums` representing the data status of this set after the error.

Find the number that occurs twice and the number that is missing and return *them in the form of an array*.

Example 1:**Input:** nums = [1,2,2,4]**Output:** [2,3]**Example 2:****Input:** nums = [1,1]**Output:** [1,2]

Constraints:

- $2 \leq \text{nums.length} \leq 10^4$
- $1 \leq \text{nums}[i] \leq 10^4$

646. Maximum Length of Pair Chain**Medium**

2619105 Add to List Share

You are given an array of n pairs `pairs` where `pairs[i] = [lefti, righti]` and `lefti < righti`.

A pair `p2 = [c, d]` **follows** a pair `p1 = [a, b]` if `b < c`. A **chain** of pairs can be formed in this fashion.

Return *the length longest chain which can be formed*.

You do not need to use up all the given intervals. You can select pairs in any order.

Example 1:

Input: `pairs = [[1,2],[2,3],[3,4]]`

Output: 2

Explanation: The longest chain is `[1,2] -> [3,4]`.

Example 2:

Input: `pairs = [[1,2],[7,8],[4,5]]`

Output: 3

Explanation: The longest chain is `[1,2] -> [4,5] -> [7,8]`.

Constraints:

- $n == \text{pairs.length}$
- $1 \leq n \leq 1000$
- $-1000 \leq \text{left}_i < \text{right}_i \leq 1000$

647. Palindromic Substrings**Medium**

8073176Add to ListShare

Given a string `s`, return *the number of palindromic substrings in it*.A string is a **palindrome** when it reads the same backward as forward.A **substring** is a contiguous sequence of characters within the string.**Example 1:****Input:** `s = "abc"`**Output:** 3**Explanation:** Three palindromic strings: "a", "b", "c".**Example 2:****Input:** `s = "aaa"`**Output:** 6**Explanation:** Six palindromic strings: "a", "a", "a", "aa", "aa", "aaa".**Constraints:**

- `1 <= s.length <= 1000`
- `s` consists of lowercase English letters.

648. Replace Words**Medium**

1746159Add to ListShare

In English, we have a concept called **root**, which can be followed by some other word to form another longer word - let's call this word **successor**. For example, when the **root** "an" is followed by the **successor** word "other", we can form a new word "another".Given a `dictionary` consisting of many **roots** and a `sentence` consisting of words separated by spaces, replace all the **successors** in the sentence with the **root** forming it. If a **successor** can be replaced by more than one **root**, replace it with the **root** that has **the shortest length**.Return *the sentence* after the replacement.**Example 1:**

Input: dictionary = ["cat", "bat", "rat"], sentence = "the cattle was rattled by the battery"

Output: "the cat was rat by the bat"

Example 2:

Input: dictionary = ["a", "b", "c"], sentence = "aadsfasf absbs bbab cadsfafs"

Output: "a a b c"

Constraints:

- `1 <= dictionary.length <= 1000`
- `1 <= dictionary[i].length <= 100`
- `dictionary[i]` consists of only lower-case letters.
- `1 <= sentence.length <= 106`
- `sentence` consists of only lower-case letters and spaces.
- The number of words in `sentence` is in the range `[1, 1000]`
- The length of each word in `sentence` is in the range `[1, 1000]`
- Every two consecutive words in `sentence` will be separated by exactly one space.
- `sentence` does not have leading or trailing spaces.

649. Dota2 Senate

Medium

473331Add to ListShare

In the world of Dota2, there are two parties: the Radiant and the Dire.

The Dota2 senate consists of senators coming from two parties. Now the Senate wants to decide on a change in the Dota2 game. The voting for this change is a round-based procedure. In each round, each senator can exercise **one** of the two rights:

- **Ban one senator's right:** A senator can make another senator lose all his rights in this and all the following rounds.
- **Announce the victory:** If this senator found the senators who still have rights to vote are all from the same party, he can announce the victory and decide on the change in the game.

Given a string `senate` representing each senator's party belonging. The character '`R`' and '`D`' represent the Radiant party and the Dire party. Then if there are `n` senators, the size of the given string will be `n`.

The round-based procedure starts from the first senator to the last senator in the given order. This procedure will last until the end of voting. All the senators who have lost their rights will be skipped during the procedure.

Suppose every senator is smart enough and will play the best strategy for his own party. Predict which party will finally announce the victory and change the Dota2 game. The output should be "Radiant" or "Dire".

Example 1:

Input: senate = "RD"

Output: "Radiant"

Explanation:

The first senator comes from Radiant and he can just ban the next senator's right in round 1.

And the second senator can't exercise any rights anymore since his right has been banned.

And in round 2, the first senator can just announce the victory since he is the only guy in the senate who can vote.

Example 2:

Input: senate = "RDD"

Output: "Dire"

Explanation:

The first senator comes from Radiant and he can just ban the next senator's right in round 1.

And the second senator can't exercise any rights anymore since his right has been banned.

And the third senator comes from Dire and he can ban the first senator's right in round 1.

And in round 2, the third senator can just announce the victory since he is the only guy in the senate who can vote.

Constraints:

- `n == senate.length`
- `1 <= n <= 104`
- `senate[i]` is either 'R' or 'D'.

650. 2 Keys Keyboard

Medium

2855172Add to ListShare

There is only one character '`'A'`' on the screen of a notepad. You can perform one of two operations on this notepad for each step:

- Copy All: You can copy all the characters present on the screen (a partial copy is not allowed).
- Paste: You can paste the characters which are copied last time.

Given an integer `n`, return *the minimum number of operations to get the character '`'A'`' exactly `n` times on the screen.*

Example 1:**Input:** `n = 3`**Output:** `3`

Explanation: Initially, we have one character '`'A'`'.

In step 1, we use Copy All operation.

In step 2, we use Paste operation to get '`'AA'`'.

In step 3, we use Paste operation to get '`'AAA'`'.

Example 2:**Input:** `n = 1`**Output:** `0`**Constraints:**

- `1 <= n <= 1000`

652. Find Duplicate Subtrees


Medium

3734323Add to ListShare

Given the `root` of a binary tree, return all **duplicate subtrees**.


For each kind of duplicate subtrees, you only need to return the root node of any **one** of them.

Two trees are **duplicate** if they have the **same structure** with the **same node values**.

Example 1:


Input: root = [1,2,3,4,null,2,4,null,null,4]

Output: [[2,4],[4]]

Example 2:

Input: root = [2,1,1]

Output: [[1]]

Example 3:

Input: root = [2,2,2,3,null,3,null]

Output: [[2,3],[3]]

Constraints:

- The number of the nodes in the tree will be in the range [1, 5000]
- $-200 \leq \text{Node.val} \leq 200$


653. Two Sum IV - Input is a BST

Easy

4450215Add to ListShare

Given the `root` of a Binary Search Tree and a target number `k`, return `true` if there exist two elements in the BST such that their sum is equal to the given target.


Example 1:



Input: root = [5,3,6,2,4,null,7], k = 9

Output: true

Example 2:



Input: root = [5,3,6,2,4,null,7], k = 28

Output: false

Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $-10^4 \leq \text{Node.val} \leq 10^4$
- `root` is guaranteed to be a **valid** binary search tree.
- $-10^5 \leq k \leq 10^5$

654. Maximum Binary Tree

Medium


4173306Add to ListShare

You are given an integer array `nums` with no duplicates. A **maximum binary tree** can be built recursively from `nums` using the following algorithm:

1. Create a root node whose value is the maximum value in `nums`.
2. Recursively build the left subtree on the **subarray prefix** to the **left** of the maximum value.
3. Recursively build the right subtree on the **subarray suffix** to the **right** of the maximum value.

Return *the maximum binary tree built from `nums`.*

Example 1:



Input: `nums = [3,2,1,6,0,5]`

Output: [6,3,5,null,2,0,null,null,1]

Explanation: The recursive calls are as follow:

- The largest value in [3,2,1,6,0,5] is 6. Left prefix is [3,2,1] and right suffix is [0,5].

- The largest value in [3,2,1] is 3. Left prefix is [] and right suffix is [2,1].

- Empty array, so no child.

- The largest value in [2,1] is 2. Left prefix is [] and right suffix is [1].

- Empty array, so no child.


- Only one element, so child is a node with value 1.

- The largest value in [0,5] is 5. Left prefix is [0] and right suffix is [].

- Only one element, so child is a node with value 0.

- Empty array, so no child.

Example 2:



Input: nums = [3,2,1]

Output: [3,null,2,null,1]

Constraints:

- `1 <= nums.length <= 1000`

- $0 \leq \text{nums}[i] \leq 1000$
- All integers in `nums` are **unique**.

655. Print Binary Tree

Medium


271303Add to ListShare

Given the `root` of a binary tree, construct a **0-indexed** $m \times n$ string matrix `res` that represents a **formatted layout** of the tree. The formatted layout matrix should be constructed using the following rules:

- The **height** of the tree is `height` and the number of rows `m` should be equal to `height + 1`.
- The number of columns `n` should be equal to $2^{\text{height}+1} - 1$.
- Place the **root node** in the **middle** of the **top row** (more formally, at location `res[0][((n-1)/2)]`).
- For each node that has been placed in the matrix at position `res[r][c]`, place its **left child** at `res[r+1][c-2^{\text{height}-r-1}]` and its **right child** at `res[r+1][c+2^{\text{height}-r-1}]`.
- Continue this process until all the nodes in the tree have been placed.
- Any empty cells should contain the empty string "".

Return *the constructed matrix* `res`.

Example 1:




Input: `root = [1,2]`

Output:

```
[[ "", "1", "" ],
 [ "2", "", "" ]]
```

Example 2:



Input: root = [1,2,3,null,4]

Output:

```
[[ "", "", "", "1", "", "", "" ],
 [ "", "2", "", "", "", "3", "" ],
 [ "", "", "4", "", "", "", "" ]]
```

Constraints:

- The number of nodes in the tree is in the range $[1, 2^{10}]$.
- $-99 \leq \text{Node.val} \leq 99$
- The depth of the tree will be in the range $[1, 10]$.

657. Robot Return to Origin

Easy

1866725Add to ListShare

There is a robot starting at the position $(0, 0)$, the origin, on a 2D plane. Given a sequence of its moves, judge if this robot ends up at $(0, 0)$ after it completes its moves.

You are given a string `moves` that represents the move sequence of the robot where `moves[i]` represents its i^{th} move. Valid moves are 'R' (right), 'L' (left), 'U' (up), and 'D' (down).

Return `true` if the robot returns to the origin after it finishes all of its moves, or `false` otherwise.

Note: The way that the robot is "facing" is irrelevant. '`R`' will always make the robot move to the right once, '`L`' will always make it move left, etc. Also, assume that the magnitude of the robot's movement is the same for each move.

Example 1:

Input: `moves` = "UD"

Output: true

Explanation: The robot moves up once, and then down once. All moves have the same magnitude, so it ended up at the origin where it started. Therefore, we return true.

Example 2:

Input: `moves` = "LL"

Output: false

Explanation: The robot moves left twice. It ends up two "moves" to the left of the origin. We return false because it is not at the origin at the end of its moves.

Constraints:

- $1 \leq \text{moves.length} \leq 2 * 10^4$
- `moves` only contains the characters '`U`', '`D`', '`L`' and '`R`'.

658. Find K Closest Elements

Medium

5103460Add to ListShare

Given a **sorted** integer array `arr`, two integers `k` and `x`, return the `k` closest integers to `x` in the array. The result should also be sorted in ascending order.

An integer `a` is closer to `x` than an integer `b` if:

- $|a - x| < |b - x|$, or
- $|a - x| == |b - x|$ and `a < b`

Example 1:

Input: `arr` = [1,2,3,4,5], `k` = 4, `x` = 3

Output: [1,2,3,4]

Example 2:**Input:** arr = [1,2,3,4,5], k = 4, x = -1**Output:** [1,2,3,4]**Constraints:**

- $1 \leq k \leq \text{arr.length}$
- $1 \leq \text{arr.length} \leq 10^4$
- arr is sorted in **ascending** order.
- $-10^4 \leq \text{arr}[i], x \leq 10^4$

659. Split Array into Consecutive Subsequences**Medium**

3917747Add to ListShare

You are given an integer array `nums` that is **sorted in non-decreasing order**.

Determine if it is possible to split `nums` into **one or more subsequences** such that **both** of the following conditions are true:

- Each subsequence is a **consecutive increasing sequence** (i.e. each integer is **exactly one** more than the previous integer).
- All subsequences have a length of **3 or more**.

Return `true` if you can split `nums` according to the above conditions, or `false` otherwise.

A **subsequence** of an array is a new array that is formed from the original array by deleting some (can be none) of the elements without disturbing the relative positions of the remaining elements. (i.e., `[1, 3, 5]` is a subsequence of `[1, 2, 3, 4, 5]` while `[1, 3, 2]` is not).

Example 1:**Input:** nums = [1,2,3,3,4,5]**Output:** true**Explanation:** `nums` can be split into the following subsequences:`[1,2,3,3,4,5] --> 1, 2, 3``[1,2,3,3,4,5] --> 3, 4, 5`**Example 2:**

Input: nums = [1,2,3,3,4,4,5,5]

Output: true

Explanation: nums can be split into the following subsequences:

[1,2,3,3,4,4,5,5] --> 1, 2, 3, 4, 5

[1,2,3,3,4,4,5,5] --> 3, 4, 5

Example 3:

Input: nums = [1,2,3,4,4,5]

Output: false

Explanation: It is impossible to split nums into consecutive increasing subsequences of length 3 or more.

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-1000 \leq \text{nums}[i] \leq 1000$
- `nums` is sorted in **non-decreasing** order.

661. Image Smoother

Easy

4141689Add to ListShare


An **image smoother** is a filter of the size 3×3 that can be applied to each cell of an image by rounding down the average of the cell and the eight surrounding cells (i.e., the average of the nine cells in the blue smoother). If one or more of the surrounding cells of a cell is not present, we do not consider it in the average (i.e., the average of the four cells in the red smoother).

1	2	3	4	5	
6	7	8	9	10	
11	12	13	14	15	
16	17	18	19	20	
21	22	23	24	25	

Given an $m \times n$ integer matrix `img` representing the grayscale of an image, return *the image after applying the smoother on each cell of it.*

Example 1:

1	1	1
1	0	1
1	1	1



0	0	0
0	0	0
0	0	0

Input: img = [[1,1,1],[1,0,1],[1,1,1]]

Output: [[0,0,0],[0,0,0],[0,0,0]]

Explanation:


For the points (0,0), (0,2), (2,0), (2,2): $\text{floor}(3/4) = \text{floor}(0.75) = 0$

For the points (0,1), (1,0), (1,2), (2,1): $\text{floor}(5/6) = \text{floor}(0.83333333) = 0$

For the point (1,1): $\text{floor}(8/9) = \text{floor}(0.88888889) = 0$

Example 2:

100	200	100
200	50	200
100	200	100



137	141	137
141	138	141
137	141	137

Input: img = [[100,200,100],[200,50,200],[100,200,100]]

Output: [[137,141,137],[141,138,141],[137,141,137]]

Explanation:

For the points (0,0), (0,2), (2,0), (2,2): $\text{floor}((100+200+200+50)/4) = \text{floor}(137.5) = 137$

For the points (0,1), (1,0), (1,2), (2,1): $\text{floor}((200+200+50+200+100+100)/6) = \text{floor}(141.666667) = 141$

For the point (1,1): $\text{floor}((50+200+200+200+200+100+100+100+100)/9) = \text{floor}(138.888889) = 138$

Constraints:

- $m == \text{img.length}$
- $n == \text{img}[i].length$
- $1 \leq m, n \leq 200$
- $0 \leq \text{img}[i][j] \leq 255$

662. Maximum Width of Binary Tree

Medium

5645808Add to ListShare


Given the `root` of a binary tree, return the **maximum width** of the given tree.

The **maximum width** of a tree is the maximum **width** among all levels.

The **width** of one level is defined as the length between the end-nodes (the leftmost and rightmost non-null nodes), where the null nodes between the end-nodes that would be present in a complete binary tree extending down to that level are also counted into the length calculation.

It is **guaranteed** that the answer will in the range of a **32-bit** signed integer.

Example 1:




Input: root = [1,3,2,5,3,null,9]

Output: 4

Explanation: The maximum width exists in the third level with length 4 (5,3,null,9).

Example 2:




Input: root = [1,3,2,5,null,null,9,6,null,7]

Output: 7

Explanation: The maximum width exists in the fourth level with length 7 (6,null,null,null,null,7).

Example 3:



Input: root = [1,3,2,5]

Output: 2

Explanation: The maximum width exists in the second level with length 2 (3,2).

Constraints:

- The number of nodes in the tree is in the range [1, 3000].
- $-100 \leq \text{Node.val} \leq 100$

664. Strange Printer

Hard

96189Add to ListShare

There is a strange printer with the following two special properties:

- The printer can only print a sequence of **the same character** each time.
- At each turn, the printer can print new characters starting from and ending at any place and will cover the original existing characters.

Given a string `s`, return the minimum number of turns the printer needed to print it.

Example 1:

Input: `s = "aaabbb"`

Output: 2

Explanation: Print "aaa" first and then print "bbb".

Example 2:

Input: `s = "aba"`

Output: 2

Explanation: Print "aaa" first and then print "b" from the second place of the string, which will cover the existing character 'a'.

Constraints:

- `1 <= s.length <= 100`
- `s` consists of lowercase English letters.

665. Non-decreasing Array

Medium

5053732Add to ListShare

Given an array `nums` with `n` integers, your task is to check if it could become non-decreasing by modifying **at most one element**.

We define an array is non-decreasing if `nums[i] <= nums[i + 1]` holds for every `i` (**0-based**) such that `(0 <= i <= n - 2)`.

Example 1:

Input: `nums = [4,2,3]`

Output: `true`

Explanation: You could modify the first 4 to 1 to get a non-decreasing array.

Example 2:

Input: `nums = [4,2,1]`

Output: `false`

Explanation: You cannot get a non-decreasing array by modifying at most one element.

Constraints:

- `n == nums.length`
- `1 <= n <= 104`
- `-105 <= nums[i] <= 105`

667. Beautiful Arrangement II

Medium

708992Add to ListShare

Given two integers `n` and `k`, construct a list `answer` that contains `n` different positive integers ranging from `1` to `n` and obeys the following requirement:

- Suppose this list is `answer = [a1, a2, a3, ..., an]`, then the list `[|a1 - a2|, |a2 - a3|, |a3 - a4|, ..., |an-1 - an|]` has exactly `k` distinct integers.

Return *the list* `answer`. If there multiple valid answers, return **any of them**.

Example 1:

Input: `n = 3, k = 1`

Output: `[1,2,3]`

Explanation: The `[1,2,3]` has three different positive integers ranging from `1` to `3`, and the `[1,1]` has exactly `1` distinct integer: `1`

Example 2:

Input: `n = 3, k = 2`

Output: `[1,3,2]`

Explanation: The `[1,3,2]` has three different positive integers ranging from `1` to `3`, and the `[2,1]` has exactly `2` distinct integers: `1` and `2`.

Constraints:

- $1 \leq k < n \leq 10^4$

668. Kth Smallest Number in Multiplication Table

Hard

177350Add to ListShare

Nearly everyone has used the Multiplication Table. The multiplication table of size $m \times n$ is an integer matrix `mat` where `mat[i][j] == i * j` (**1-indexed**).

Given three integers m , n , and k , return the k^{th} smallest element in the $m \times n$ multiplication table.

Example 1:

1	2	3
2	4	6
3	6	9

1	2	2	3	3	4	6	6	9
---	---	---	---	---	---	---	---	---

Input: $m = 3$, $n = 3$, $k = 5$

Output: 3

Explanation: The 5^{th} smallest number is 3.

Example 2:

1	2	3
2	4	6

1	2	2	3	4	6
---	---	---	---	---	---

Input: m = 2, n = 3, k = 6

Output: 6

Explanation: The 6th smallest number is 6.

Constraints:

- $1 \leq m, n \leq 3 \times 10^4$
- $1 \leq k \leq m \times n$

669. Trim a Binary Search Tree


Medium

5067244Add to ListShare


Given the `root` of a binary search tree and the lowest and highest boundaries as `low` and `high`, trim the tree so that all its elements lies in `[low, high]`. Trimming the tree should **not** change the relative structure of the elements that will remain in the tree (i.e., any node's descendant should remain a descendant). It can be proven that there is a **unique answer**.

Return *the root of the trimmed binary search tree*. Note that the root may change depending on the given bounds.

Example 1:



Example 2:



Constraints:

- The number of nodes in the tree is in the range $[1, 10^4]$.
- $0 \leq \text{Node.val} \leq 10^4$
- The value of each node in the tree is **unique**.

- `root` is guaranteed to be a valid binary search tree.
- $0 \leq \text{low} \leq \text{high} \leq 10^4$

670. Maximum Swap

Medium

2746159Add to ListShare

You are given an integer `num`. You can swap two digits at most once to get the maximum valued number.

Return *the maximum valued number you can get*.

Example 1:

Input: `num = 2736`

Output: `7236`

Explanation: Swap the number 2 and the number 7.

Example 2:

Input: `num = 9973`

Output: `9973`

Explanation: No swap.

Constraints:

- $0 \leq \text{num} \leq 10^8$

671. Second Minimum Node In a Binary Tree


Easy

14221649Add to ListShare

Given a non-empty special binary tree consisting of nodes with the non-negative value, where each node in this tree has exactly `two` or `zero` sub-node. If the node has two sub-nodes, then this node's value is the smaller value among its two sub-nodes. More formally, the property `root.val = min(root.left.val, root.right.val)` always holds.

Given such a binary tree, you need to output the **second minimum** value in the set made of all the nodes' value in the whole tree.


If no such second minimum value exists, output `-1` instead.

Example 1:

Input: root = [2,2,5,null,null,5,7]

Output: 5

Explanation: The smallest value is 2, the second smallest value is 5.

Example 2:

Input: root = [2,2,2]

Output: -1

Explanation: The smallest value is 2, but there isn't any second smallest value.

Constraints:

- The number of nodes in the tree is in the range `[1, 25]`.
- `1 <= Node.val <= 231 - 1`
- `root.val == min(root.left.val, root.right.val)` for each internal node of the tree.

672. Bulb Switcher II

Medium

60111Add to ListShare

There is a room with `n` bulbs labeled from `1` to `n` that all are turned on initially, and **four buttons** on the wall. Each of the four buttons has a different functionality where:

- **Button 1:** Flips the status of all the bulbs.
- **Button 2:** Flips the status of all the bulbs with even labels (i.e., `2, 4, ...`).
- **Button 3:** Flips the status of all the bulbs with odd labels (i.e., `1, 3, ...`).
- **Button 4:** Flips the status of all the bulbs with a label $j = 3k + 1$ where $k = 0, 1, 2, \dots$ (i.e., `1, 4, 7, 10, ...`).

You must make **exactly** `presses` button presses in total. For each press, you may pick **any** of the four buttons to press.

Given the two integers `n` and `presses`, return *the number of different possible statuses after performing all `presses` button presses*.

Example 1:

Input: `n = 1, presses = 1`

Output: `2`

Explanation: Status can be:

- `[off]` by pressing button 1
- `[on]` by pressing button 2

Example 2:

Input: `n = 2, presses = 1`

Output: `3`

Explanation: Status can be:

- `[off, off]` by pressing button 1

- [on, off] by pressing button 2
- [off, on] by pressing button 3

Example 3:

Input: $n = 3$, $\text{presses} = 1$

Output: 4

Explanation: Status can be:

- [off, off, off] by pressing button 1
- [off, on, off] by pressing button 2
- [on, off, on] by pressing button 3
- [off, on, on] by pressing button 4

Constraints:

- $1 \leq n \leq 1000$
- $0 \leq \text{presses} \leq 1000$

673. Number of Longest Increasing Subsequence

Medium

4223192Add to ListShare

Given an integer array `nums`, return *the number of longest increasing subsequences*.

Notice that the sequence has to be **strictly** increasing.

Example 1:

Input: `nums = [1,3,5,4,7]`

Output: 2

Explanation: The two longest increasing subsequences are `[1, 3, 4, 7]` and `[1, 3, 5, 7]`.

Example 2:

Input: `nums = [2,2,2,2,2]`

Output: 5

Explanation: The length of the longest increasing subsequence is 1, and there are 5 increasing subsequences of length 1, so output 5.

Constraints:

- $1 \leq \text{nums.length} \leq 2000$
- $-10^6 \leq \text{nums}[i] \leq 10^6$

674. Longest Continuous Increasing Subsequence

Easy

1885168Add to ListShare

Given an unsorted array of integers `nums`, return *the length of the longest **continuous increasing subsequence** (i.e. subarray)*. The subsequence must be **strictly** increasing.

A **continuous increasing subsequence** is defined by two indices `l` and `r` ($l < r$) such that it is $[\text{nums}[l], \text{nums}[l + 1], \dots, \text{nums}[r - 1], \text{nums}[r]]$ and for each $l \leq i < r$, $\text{nums}[i] < \text{nums}[i + 1]$.

Example 1:

Input: `nums = [1,3,5,4,7]`

Output: 3

Explanation: The longest continuous increasing subsequence is `[1,3,5]` with length 3.

Even though `[1,3,5,7]` is an increasing subsequence, it is not continuous as elements 5 and 7 are separated by element

4.

Example 2:

Input: `nums = [2,2,2,2,2]`

Output: 1

Explanation: The longest continuous increasing subsequence is `[2]` with length 1. Note that it must be strictly increasing.

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

675. Cut Off Trees for Golf Event

Hard

1005596Add to ListShare

You are asked to cut off all the trees in a forest for a golf event. The forest is represented as an $m \times n$ matrix. In this matrix:

- 0 means the cell cannot be walked through.
- 1 represents an empty cell that can be walked through.
- A number greater than 1 represents a tree in a cell that can be walked through, and this number is the tree's height.

In one step, you can walk in any of the four directions: north, east, south, and west. If you are standing in a cell with a tree, you can choose whether to cut it off.

You must cut off the trees in order from shortest to tallest. When you cut off a tree, the value at its cell becomes 1 (an empty cell).

Starting from the point $(0, 0)$, return the minimum steps you need to walk to cut off all the trees. If you cannot cut off all the trees, return -1 .

Note: The input is generated such that no two trees have the same height, and there is at least one tree needs to be cut off.

Example 1:

1	2	3
0	0	4
7	6	5

Input: forest = [[1,2,3],[0,0,4],[7,6,5]]

Output: 6

Explanation: Following the path above allows you to cut off the trees from shortest to tallest in 6 steps.

Example 2:

1	2	3
0	0	0
7	6	5

Input: forest = [[1,2,3],[0,0,0],[7,6,5]]

Output: -1

Explanation: The trees in the bottom row cannot be accessed as the middle row is blocked.

Example 3:

Input: forest = [[2,3,4],[0,0,5],[8,7,6]]

Output: 6

Explanation: You can follow the same path as Example 1 to cut off all the trees.

Note that you can cut off the first tree at (0, 0) before making any steps.

Constraints:

- $m == \text{forest.length}$
- $n == \text{forest}[i].length$
- $1 \leq m, n \leq 50$
- $0 \leq \text{forest}[i][j] \leq 10^9$
- Heights of all trees are **distinct**.

676. Implement Magic Dictionary

Medium

1141186Add to ListShare

Design a data structure that is initialized with a list of **different** words. Provided a string, you should determine if you can change exactly one character in this string to match any word in the data structure.

Implement the `MagicDictionary` class:

- `MagicDictionary()` Initializes the object.
- `void buildDict(String[] dictionary)` Sets the data structure with an array of distinct `strings` `dictionary`.
- `bool search(String searchWord)` Returns `true` if you can change **exactly one character** in `searchWord` to match any string in the data structure, otherwise returns `false`.

Example 1:

Input

```
["MagicDictionary", "buildDict", "search", "search", "search", "search"]
[[], [[{"hello", "leetcode"}]], [{"hello"}, {"hhllo"}, {"hell"}, {"leetcoded"}]]
```

Output

```
[null, null, false, true, false, false]
```

Explanation

```
MagicDictionary magicDictionary = new MagicDictionary();
magicDictionary.buildDict(["hello", "leetcode"]);
magicDictionary.search("hello"); // return False
magicDictionary.search("hhllo"); // We can change the second 'h' to 'e' to match
"hello" so we return True
magicDictionary.search("hell"); // return False
magicDictionary.search("leetcoded"); // return False
```

Constraints:

- `1 <= dictionary.length <= 100`
- `1 <= dictionary[i].length <= 100`
- `dictionary[i]` consists of only lower-case English letters.

- All the strings in `dictionary` are **distinct**.
- `1 <= searchWord.length <= 100`
- `searchWord` consists of only lower-case English letters.
- `buildDict` will be called only once before `search`.
- At most `100` calls will be made to `search`.

677. Map Sum Pairs

Medium

1355134Add to ListShare

Design a map that allows you to do the following:

- Maps a string key to a given value.
- Returns the sum of the values that have a key with a prefix equal to a given string.

Implement the `MapSum` class:

- `MapSum()` Initializes the `MapSum` object.
- `void insert(String key, int val)` Inserts the `key-val` pair into the map. If the `key` already existed, the original `key-value` pair will be overridden to the new one.
- `int sum(string prefix)` Returns the sum of all the pairs' value whose `key` starts with the `prefix`.

Example 1:

Input

```
["MapSum", "insert", "sum", "insert", "sum"]
[[], ["apple", 3], ["ap"], ["app", 2], ["ap"]]
```

Output

```
[null, null, 3, null, 5]
```

Explanation

```
MapSum mapSum = new MapSum();

mapSum.insert("apple", 3);

mapSum.sum("ap");           // return 3 (apple = 3)

mapSum.insert("app", 2);

mapSum.sum("ap");           // return 5 (apple + app = 3 + 2 = 5)
```

Constraints:

- $1 \leq \text{key.length, prefix.length} \leq 50$
- `key` and `prefix` consist of only lowercase English letters.
- $1 \leq \text{val} \leq 1000$
- At most 50 calls will be made to `insert` and `sum`.

678. Valid Parenthesis String**Medium**

385492Add to ListShare

Given a string `s` containing only three types of characters: '(', ')' and '*', return `true` if `s` is **valid**.

The following rules define a **valid** string:

- Any left parenthesis '(' must have a corresponding right parenthesis ')'.
- Any right parenthesis ')' must have a corresponding left parenthesis '('.
- Left parenthesis '(' must go before the corresponding right parenthesis ')'.
- '*' could be treated as a single right parenthesis ')' or a single left parenthesis '(' or an empty string "".

Example 1:**Input:** `s = "()"`**Output:** `true`**Example 2:****Input:** `s = "(*)"`**Output:** `true`**Example 3:****Input:** `s = "(*))"`**Output:** `true`**Constraints:**

- $1 \leq \text{s.length} \leq 100$

- `s[i]` is `'(`, `')` or `'*'`.

679. 24 Game

Hard

1285227Add to ListShare

You are given an integer array `cards` of length `4`. You have four cards, each containing a number in the range `[1, 9]`. You should arrange the numbers on these cards in a mathematical expression using the operators `['+', '-', '*', '/']` and the parentheses `'('` and `')'` to get the value `24`.

You are restricted with the following rules:

- The division operator `'/'` represents real division, not integer division.
 - For example, `4 / (1 - 2 / 3) = 4 / (1 / 3) = 12`.
- Every operation done is between two numbers. In particular, we cannot use `'-'` as a unary operator.
 - For example, if `cards = [1, 1, 1, 1]`, the expression `"-1 - 1 - 1 - 1"` is **not allowed**.
- You cannot concatenate numbers together
 - For example, if `cards = [1, 2, 1, 2]`, the expression `"12 + 12"` is not valid.

Return `true` if you can get such expression that evaluates to `24`, and `false` otherwise.

Example 1:

Input: `cards = [4,1,8,7]`

Output: `true`

Explanation: $(8-4) * (7-1) = 24$

Example 2:

Input: `cards = [1,2,1,2]`

Output: `false`

Constraints:

- `cards.length == 4`
- `1 <= cards[i] <= 9`

680. Valid Palindrome II

Easy

6319329Add to ListShare

Given a string `s`, return `true` if the `s` can be palindrome after deleting **at most one** character from it.**Example 1:****Input:** `s = "aba"`**Output:** `true`**Example 2:****Input:** `s = "abca"`**Output:** `true`**Explanation:** You could delete the character 'c'.**Example 3:****Input:** `s = "abc"`**Output:** `false`**Constraints:**

- $1 \leq s.length \leq 10^5$
- `s` consists of lowercase English letters.

682. Baseball Game**Easy**

18681704Add to ListShare

You are keeping the scores for a baseball game with strange rules. At the beginning of the game, you start with an empty record.

You are given a list of strings `operations`, where `operations[i]` is the i^{th} operation you must apply to the record and is one of the following:

- An integer `x`.
 - Record a new score of `x`.
- `'+'`.
 - Record a new score that is the sum of the previous two scores.
- `'D'`.
 - Record a new score that is the double of the previous score.
- `'C'`.
 - Record a new score that is the previous score minus the previous score.

- Invalidate the previous score, removing it from the record.

Return *the sum of all the scores on the record after applying all the operations*.

The test cases are generated such that the answer and all intermediate calculations fit in a **32-bit** integer and that all operations are valid.

Example 1:

Input: ops = ["5", "2", "C", "D", "+"]

Output: 30

Explanation:

"5" - Add 5 to the record, record is now [5].

"2" - Add 2 to the record, record is now [5, 2].

"C" - Invalidate and remove the previous score, record is now [5].

"D" - Add $2 * 5 = 10$ to the record, record is now [5, 10].

"+" - Add $5 + 10 = 15$ to the record, record is now [5, 10, 15].

The total sum is $5 + 10 + 15 = 30$.

Example 2:

Input: ops = ["5", "-2", "4", "C", "D", "9", "+", "+"]

Output: 27

Explanation:

"5" - Add 5 to the record, record is now [5].

"-2" - Add -2 to the record, record is now [5, -2].

"4" - Add 4 to the record, record is now [5, -2, 4].

"C" - Invalidate and remove the previous score, record is now [5, -2].

"D" - Add $2 * -2 = -4$ to the record, record is now [5, -2, -4].

"9" - Add 9 to the record, record is now [5, -2, -4, 9].

"+" - Add $-4 + 9 = 5$ to the record, record is now [5, -2, -4, 9, 5].

"+" - Add $9 + 5 = 14$ to the record, record is now [5, -2, -4, 9, 5, 14].

The total sum is $5 + -2 + -4 + 9 + 5 + 14 = 27$.

Example 3:

Input: ops = ["1", "C"]

Output: 0

Explanation:

"1" - Add 1 to the record, record is now [1].

"C" - Invalidate and remove the previous score, record is now [].

Since the record is empty, the total sum is 0.

Constraints:

- $1 \leq \text{operations.length} \leq 1000$
- $\text{operations}[i]$ is "C", "D", "+", or a string representing an integer in the range $[-3 * 10^4, 3 * 10^4]$.
- For operation "+", there will always be at least two previous scores on the record.
- For operations "C" and "D", there will always be at least one previous score on the record.

684. Redundant Connection

Medium


4504320Add to ListShare

In this problem, a tree is an **undirected graph** that is connected and has no cycles.

You are given a graph that started as a tree with n nodes labeled from 1 to n , with one additional edge added. The added edge has two **different** vertices chosen from 1 to n , and was not an edge that already existed. The graph is represented as an array `edges` of length n where `edges[i] = [ai, bi]` indicates that there is an edge between nodes a_i and b_i in the graph.

Return *an edge that can be removed so that the resulting graph is a tree of n nodes*. If there are multiple answers, return the answer that occurs last in the input.


Example 1:



Input: edges = [[1,2],[1,3],[2,3]]

Output: [2,3]

Example 2:



Input: edges = [[1,2],[2,3],[3,4],[1,4],[1,5]]

Output: [1,4]

Constraints:

- $n == \text{edges.length}$
- $3 \leq n \leq 1000$
- $\text{edges}[i].length == 2$
- $1 \leq a_i < b_i \leq \text{edges.length}$
- $a_i \neq b_i$
- There are no repeated edges.
- The given graph is connected.

685. Redundant Connection II

Hard


1843283Add to ListShare

In this problem, a rooted tree is a **directed** graph such that, there is exactly one node (the root) for which all other nodes are descendants of this node, plus every node has exactly one parent, except for the root node which has no parents.

The given input is a directed graph that started as a rooted tree with n nodes (with distinct values from 1 to n), with one additional directed edge added. The added edge has two different vertices chosen from 1 to n , and was not an edge that already existed.

The resulting graph is given as a 2D-array of `edges`. Each element of `edges` is a pair $[u_i, v_i]$ that represents a **directed** edge connecting nodes u_i and v_i , where u_i is a parent of child v_i .


Return *an edge that can be removed so that the resulting graph is a rooted tree of n nodes*. If there are multiple answers, return the answer that occurs last in the given 2D-array.

Example 1:

Input: `edges = [[1,2],[1,3],[2,3]]`

Output: `[2,3]`

Example 2:



Input: edges = [[1,2],[2,3],[3,4],[4,1],[1,5]]

Output: [4,1]

Constraints:

- $n == \text{edges.length}$
- $3 \leq n \leq 1000$
- $\text{edges}[i].length == 2$
- $1 \leq u_i, v_i \leq n$
- $u_i \neq v_i$

686. Repeated String Match

Medium

1756921 Add to List Share

Given two strings `a` and `b`, return the minimum number of times you should repeat string `a` so that string `b` is a substring of it. If it is impossible for `b` to be a substring of `a` after repeating it, return `-1`.

Notice: string "abc" repeated 0 times is "", repeated 1 time is "abc" and repeated 2 times is "abcabc".

Example 1:

Input: a = "abcd", b = "cdabcdab"

Output: 3

Explanation: We return 3 because by repeating a three times "abcdabcdabcd", b is a substring of it.

Example 2:

Input: a = "a", b = "aa"

Output: 2

Constraints:

- $1 \leq a.length, b.length \leq 10^4$
- a and b consist of lowercase English letters.

687. Longest Univalue Path


Medium

3483635Add to ListShare

Given the `root` of a binary tree, return *the length of the longest path, where each node in the path has the same value*. This path may or may not pass through the root.

The length of the path between two nodes is represented by the number of edges between them.

Example 1:




Input: root = [5,4,5,1,1,null,5]

Output: 2

Explanation: The shown image shows that the longest path of the same value (i.e. 5).

Example 2:



Input: root = [1,4,5,4,4,null,5]

Output: 2

Explanation: The shown image shows that the longest path of the same value (i.e. 4).

Constraints:

- The number of nodes in the tree is in the range $[0, 10^4]$.
- $-1000 \leq \text{Node.val} \leq 1000$
- The depth of the tree will not exceed 1000.


688. Knight Probability in Chessboard

Medium

2241312Add to ListShare

On an $n \times n$ chessboard, a knight starts at the cell $(\text{row}, \text{column})$ and attempts to make exactly k moves. The rows and columns are **0-indexed**, so the top-left cell is $(0, 0)$, and the bottom-right cell is $(n - 1, n - 1)$.

A chess knight has eight possible moves it can make, as illustrated below. Each move is two cells in a cardinal direction, then one cell in an orthogonal direction.



Each time the knight is to move, it chooses one of eight possible moves uniformly at random (even if the piece would go off the chessboard) and moves there.

The knight continues moving until it has made exactly k moves or has moved off the chessboard.

Return *the probability that the knight remains on the board after it has stopped moving*.

Example 1:

Input: n = 3, k = 2, row = 0, column = 0

Output: 0.06250

Explanation: There are two moves (to (1,2), (2,1)) that will keep the knight on the board.

From each of those positions, there are also two moves that will keep the knight on the board.

The total probability the knight stays on the board is 0.0625.

Example 2:

Input: n = 1, k = 0, row = 0, column = 0

Output: 1.00000

Constraints:

- $1 \leq n \leq 25$
- $0 \leq k \leq 100$
- $0 \leq \text{row}, \text{column} \leq n - 1$

689. Maximum Sum of 3 Non-Overlapping Subarrays

Hard

1718100Add to ListShare

Given an integer array `nums` and an integer `k`, find three non-overlapping subarrays of length `k` with maximum sum and return them.

Return the result as a list of indices representing the starting position of each interval (**0-indexed**). If there are multiple answers, return the lexicographically smallest one.

Example 1:

Input: nums = [1,2,1,2,6,7,5,1], k = 2

Output: [0,3,5]

Explanation: Subarrays [1, 2], [2, 6], [7, 5] correspond to the starting indices [0, 3, 5].

We could have also taken [2, 1], but an answer of [1, 3, 5] would be lexicographically larger.

Example 2:

Input: `nums = [1,2,1,2,1,2,1,2,1], k = 2`

Output: `[0,2,4]`

Constraints:

- `1 <= nums.length <= 2 * 104`
- `1 <= nums[i] < 216`
- `1 <= k <= floor(nums.length / 3)`

690. Employee Importance

Medium

17591275Add to ListShare


You have a data structure of employee information, including the employee's unique ID, importance value, and direct subordinates' IDs.

You are given an array of employees `employees` where:

- `employees[i].id` is the ID of the `ith` employee.
- `employees[i].importance` is the importance value of the `ith` employee.
- `employees[i].subordinates` is a list of the IDs of the direct subordinates of the `ith` employee.

Given an integer `id` that represents an employee's ID, return *the total importance value of this employee and all their direct and indirect subordinates*.

Example 1:



Input: employees = [[1,5,[2,3]],[2,3,[]],[3,3,[]]], id = 1


Output: 11

Explanation: Employee 1 has an importance value of 5 and has two direct subordinates: employee 2 and employee 3.

They both have an importance value of 3.

Thus, the total importance value of employee 1 is $5 + 3 + 3 = 11$.

Example 2:



Input: employees = [[1,2,[5]],[5,-3,[]]], id = 5

Output: -3

Explanation: Employee 5 has an importance value of -3 and has no direct subordinates.

Thus, the total importance value of employee 5 is -3.

Constraints:

- $1 \leq \text{employees.length} \leq 2000$
- $1 \leq \text{employees}[i].id \leq 2000$
- All `employees[i].id` are **unique**.
- $-100 \leq \text{employees}[i].importance \leq 100$
- One employee has at most one direct leader and may have several subordinates.
- The IDs in `employees[i].subordinates` are valid IDs.

691. Stickers to Spell Word

Hard

88073Add to ListShare

We are given `n` different types of `stickers`. Each sticker has a lowercase English word on it.

You would like to spell out the given string `target` by cutting individual letters from your collection of stickers and rearranging them. You can use each sticker more than once if you want, and you have infinite quantities of each sticker.

Return the minimum number of stickers that you need to spell out `target`. If the task is impossible, return `-1`.

Note: In all test cases, all words were chosen randomly from the 1000 most common US English words, and `target` was chosen as a concatenation of two random words.

Example 1:

Input: `stickers = ["with", "example", "science"]`, `target = "thehat"`

Output: 3

Explanation:

We can use 2 "with" stickers, and 1 "example" sticker.

After cutting and rearrange the letters of those stickers, we can form the target "thehat".

Also, this is the minimum number of stickers necessary to form the target string.

Example 2:

Input: `stickers = ["notice", "possible"]`, `target = "basicbasic"`

Output: -1

Explanation:

We cannot form the target "basicbasic" from cutting letters from the given stickers.

Constraints:

- `n == stickers.length`
- `1 <= n <= 50`
- `1 <= stickers[i].length <= 10`
- `1 <= target.length <= 15`
- `stickers[i]` and `target` consist of lowercase English letters.

692. Top K Frequent Words

Medium

5199271 Add to List Share

Given an array of strings `words` and an integer `k`, return the `k` most frequent strings.

Return the answer **sorted** by the **frequency** from highest to lowest. Sort the words with the same frequency by their **lexicographical order**.

Example 1:

Input: words = ["i", "love", "leetcode", "i", "love", "coding"], k = 2

Output: ["i", "love"]

Explanation: "i" and "love" are the two most frequent words.

Note that "i" comes before "love" due to a lower alphabetical order.

Example 2:

Input: words = ["the", "day", "is", "sunny", "the", "the", "the", "sunny", "is", "is"], k = 4

Output: ["the", "is", "sunny", "day"]

Explanation: "the", "is", "sunny" and "day" are the four most frequent words, with the number of occurrence being 4, 3, 2 and 1 respectively.

Constraints:

- `1 <= words.length <= 500`
- `1 <= words[i].length <= 10`
- `words[i]` consists of lowercase English letters.
- `k` is in the range `[1, The number of unique words[i]]`

693. Binary Number with Alternating Bits

Easy

1031104Add to ListShare

Given a positive integer, check whether it has alternating bits: namely, if two adjacent bits will always have different values.

Example 1:

Input: n = 5

Output: true

Explanation: The binary representation of 5 is: 101

Example 2:**Input:** n = 7**Output:** false**Explanation:** The binary representation of 7 is: 111.**Example 3:****Input:** n = 11**Output:** false**Explanation:** The binary representation of 11 is: 1011.**Constraints:**

- $1 \leq n \leq 2^{31} - 1$

695. Max Area of Island**Medium**

7958176Add to ListShare

You are given an $m \times n$ binary matrix `grid`. An island is a group of `1`'s (representing land) connected **4-directionally** (horizontal or vertical.) You may assume all four edges of the grid are surrounded by water.

The **area** of an island is the number of cells with a value `1` in the island.

Return *the maximum area of an island in `grid`*. If there is no island, return `0`.

Example 1:

0	0	1	0	0	0	0	1	0	0	0	0	0
0	0	0	0	0	0	0	1	1	1	0	0	0
0	1	1	0	1	0	0	0	0	0	0	0	0
0	1	0	0	1	1	0	0	1	0	1	0	0
0	1	0	0	1	1	0	0	1	1	1	0	0
0	0	0	0	0	0	0	0	0	0	1	0	0
0	0	0	0	0	0	0	1	1	1	0	0	0
0	0	0	0	0	0	0	1	1	0	0	0	0

Input: grid =

```
[[0,0,1,0,0,0,0,1,0,0,0,0,0,0],[0,0,0,0,0,0,0,1,1,1,0,0,0],[0,1,1,0,1,0,0,0,0,0,0,0,0],[0,1,0,0,1,1,0,0,1,0,0,0],[0,1,0,0,1,1,0,0,1,1,0,0],[0,0,0,0,0,0,0,0,0,0,1,0,0],[0,0,0,0,0,0,1,1,1,0,0,0,0]]
```

Output: 6

Explanation: The answer is not 11, because the island must be connected 4-directionally.

Example 2:

Input: grid = [[0,0,0,0,0,0,0,0]]

Output: 0

Constraints:

- $m == \text{grid.length}$
 - $n == \text{grid}[i].length$
 - $1 \leq m, n \leq 50$
 - $\text{grid}[i][j]$ is either 0 or 1.

696. Count Binary Substrings

Easy

3267711Add to ListShare

Given a binary string `s`, return the number of non-empty substrings that have the same number of `0`'s and `1`'s, and all the `0`'s and all the `1`'s in these substrings are grouped consecutively.

Substrings that occur multiple times are counted the number of times they occur.

Example 1:

Input: `s = "00110011"`

Output: 6

Explanation: There are 6 substrings that have equal number of consecutive 1's and 0's: `"0011"`, `"01"`, `"1100"`, `"10"`, `"0011"`, and `"01"`.

Notice that some of these substrings repeat and are counted the number of times they occur.

Also, `"00110011"` is not a valid substring because all the 0's (and 1's) are not grouped together.

Example 2:

Input: `s = "10101"`

Output: 4

Explanation: There are 4 substrings: `"10"`, `"01"`, `"10"`, `"01"` that have equal number of consecutive 1's and 0's.

Constraints:

- `1 <= s.length <= 105`
- `s[i]` is either `'0'` or `'1'`.

697. Degree of an Array

Easy

23311401Add to ListShare

Given a non-empty array of non-negative integers `nums`, the **degree** of this array is defined as the maximum frequency of any one of its elements.

Your task is to find the smallest possible length of a (contiguous) subarray of `nums`, that has the same degree as `nums`.

Example 1:**Input:** nums = [1,2,2,3,1]**Output:** 2**Explanation:**

The input array has a degree of 2 because both elements 1 and 2 appear twice.

Of the subarrays that have the same degree:

[1, 2, 2, 3, 1], [1, 2, 2, 3], [2, 2, 3, 1], [1, 2, 2], [2, 2, 3], [2, 2]

The shortest length is 2. So return 2.

Example 2:**Input:** nums = [1,2,2,3,1,4,2]**Output:** 6**Explanation:**

The degree is 3 because the element 2 is repeated 3 times.

So [2,2,3,1,4,2] is the shortest subarray, therefore returning 6.

Constraints:

- `nums.length` will be between 1 and 50,000.
- `nums[i]` will be an integer between 0 and 49,999.

698. Partition to K Equal Sum Subsets

Medium

5696389Add to ListShare

Given an integer array `nums` and an integer `k`, return `true` if it is possible to divide this array into `k` non-empty subsets whose sums are all equal.

Example 1:**Input:** nums = [4,3,2,3,5,2,1], k = 4**Output:** true

Explanation: It is possible to divide it into 4 subsets (5), (1, 4), (2,3), (2,3) with equal sums.

Example 2:

Input: nums = [1,2,3,4], k = 3

Output: false

Constraints:

- $1 \leq k \leq \text{nums.length} \leq 16$
- $1 \leq \text{nums}[i] \leq 10^4$
- The frequency of each element is in the range [1, 4].

699. Falling Squares

Hard

49972Add to ListShare

There are several squares being dropped onto the X-axis of a 2D plane.


You are given a 2D integer array `positions` where `positions[i] = [lefti, sideLengthi]` represents the *ith* square with a side length of `sideLengthi` that is dropped with its left edge aligned with X-coordinate `lefti`.

Each square is dropped one at a time from a height above any landed squares. It then falls downward (negative Y direction) until it either lands **on the top side of another square or on the X-axis**. A square brushing the left/right side of another square does not count as landing on it. Once it lands, it freezes in place and cannot be moved.

After each square is dropped, you must record the **height of the current tallest stack of squares**.

Return an integer array `ans` where `ans[i]` represents the height described above after dropping the *ith* square.

Example 1:



Input: positions = [[1,2],[2,3],[6,1]]

Output: [2,5,5]

Explanation:

After the first drop, the tallest stack is square 1 with a height of 2.

After the second drop, the tallest stack is squares 1 and 2 with a height of 5.

After the third drop, the tallest stack is still squares 1 and 2 with a height of 5.

Thus, we return an answer of [2, 5, 5].

Example 2:

Input: positions = [[100,100],[200,100]]

Output: [100,100]

Explanation:

After the first drop, the tallest stack is square 1 with a height of 100.

After the second drop, the tallest stack is either square 1 or square 2, both with heights of 100.

Thus, we return an answer of [100, 100].

Note that square 2 only brushes the right side of square 1, which does not count as landing on it.

Constraints:

- $1 \leq \text{positions.length} \leq 1000$
- $1 \leq \text{left}_i \leq 10^8$
- $1 \leq \text{sideLength}_i \leq 10^6$

700. Search in a Binary Search Tree


Easy

4025157Add to ListShare

You are given the `root` of a binary search tree (BST) and an integer `val`.

Find the node in the BST that the node's value equals `val` and return the subtree rooted with that node. If such a node does not exist, return `null`.


Example 1:



Input: root = [4,2,7,1,3], val = 2

Output: [2,1,3]

Example 2:



Input: root = [4,2,7,1,3], val = 5

Output: []

Constraints:

- The number of nodes in the tree is in the range [1, 5000].

- $1 \leq \text{Node.val} \leq 10^7$
- `root` is a binary search tree.
- $1 \leq \text{val} \leq 10^7$

701. Insert into a Binary Search Tree

Medium



4011152Add to ListShare

You are given the `root` node of a binary search tree (BST) and a `value` to insert into the tree.

Return *the root node of the BST after the insertion*. It is **guaranteed** that the new value does not exist in the original BST.

Notice that there may exist multiple valid ways for the insertion, as long as the tree remains a BST after insertion. You can return **any of them**.


Example 1:



Input: `root = [4,2,7,1,3]`, `val = 5`

Output: `[4,2,7,1,3,5]`

Explanation: Another accepted tree is:

**Example 2:**

Input: root = [40,20,60,10,30,50,70], val = 25

Output: [40,20,60,10,30,50,70,null,null,25]

Example 3:

Input: root = [4,2,7,1,3,null,null,null,null,null], val = 5

Output: [4,2,7,1,3,5]

Constraints:

- The number of nodes in the tree will be in the range [0, 10⁴].
- $-10^8 \leq \text{Node.val} \leq 10^8$
- All the values `Node.val` are **unique**.
- $-10^8 \leq \text{val} \leq 10^8$
- It's **guaranteed** that `val` does not exist in the original BST.

703. Kth Largest Element in a Stream

Easy

34692023Add to ListShare

Design a class to find the k^{th} largest element in a stream. Note that it is the k^{th} largest element in the sorted order, not the k^{th} distinct element.

Implement `KthLargest` class:

- `KthLargest(int k, int[] nums)` Initializes the object with the integer `k` and the stream of integers `nums`.
- `int add(int val)` Appends the integer `val` to the stream and returns the element representing the `kth` largest element in the stream.

Example 1:

Input

```
["KthLargest", "add", "add", "add", "add", "add", "add"]
[[3, [4, 5, 8, 2]], [3], [5], [10], [9], [4]]
```

Output

```
[null, 4, 5, 5, 8, 8]
```

Explanation

```
KthLargest kthLargest = new KthLargest(3, [4, 5, 8, 2]);
kthLargest.add(3);    // return 4
kthLargest.add(5);    // return 5
kthLargest.add(10);   // return 5
kthLargest.add(9);    // return 8
kthLargest.add(4);    // return 8
```

Constraints:

- $1 \leq k \leq 10^4$
- $0 \leq \text{nums.length} \leq 10^4$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- $-10^4 \leq \text{val} \leq 10^4$
- At most 10^4 calls will be made to `add`.
- It is guaranteed that there will be at least `k` elements in the array when you search for the `kth` element.

704. Binary Search

Easy

6632144Add to ListShare

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`. If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [-1,0,3,5,9,12]`, `target = 9`

Output: 4

Explanation: 9 exists in `nums` and its index is 4

Example 2:

Input: `nums = [-1,0,3,5,9,12]`, `target = 2`

Output: -1

Explanation: 2 does not exist in `nums` so return -1

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 < \text{nums}[i], \text{target} < 10^4$
- All the integers in `nums` are **unique**.
- `nums` is sorted in ascending order.

705. Design HashSet

Easy

2335221Add to ListShare

Design a HashSet without using any built-in hash table libraries.

Implement `MyHashSet` class:

- `void add(key)` Inserts the value `key` into the HashSet.
- `bool contains(key)` Returns whether the value `key` exists in the HashSet or not.
- `void remove(key)` Removes the value `key` in the HashSet. If `key` does not exist in the HashSet, do nothing.

Example 1:

Input

```
["MyHashSet", "add", "add", "contains", "contains", "add", "contains", "remove",
"contains"]
```

```
[], [1], [2], [1], [3], [2], [2], [2], [2]]
```

Output

```
[null, null, null, true, false, null, true, null, false]
```

Explanation

```
MyHashSet myHashSet = new MyHashSet();

myHashSet.add(1);      // set = [1]
myHashSet.add(2);      // set = [1, 2]
myHashSet.contains(1); // return True
myHashSet.contains(3); // return False, (not found)
myHashSet.add(2);      // set = [1, 2]
myHashSet.contains(2); // return True
myHashSet.remove(2);   // set = [1]
myHashSet.contains(2); // return False, (already removed)
```

Constraints:

- $0 \leq \text{key} \leq 10^6$
- At most 10^4 calls will be made to `add`, `remove`, and `contains`.

706. Design HashMap**Easy**

3583336Add to ListShare

Design a HashMap without using any built-in hash table libraries.

Implement the `MyHashMap` class:

- `MyHashMap()` initializes the object with an empty map.
- `void put(int key, int value)` inserts a `(key, value)` pair into the HashMap. If the `key` already exists in the map, update the corresponding `value`.

- `int get(int key)` returns the `value` to which the specified `key` is mapped, or `-1` if this map contains no mapping for the `key`.
- `void remove(key)` removes the `key` and its corresponding `value` if the map contains the mapping for the `key`.

Example 1:

Input

```
["MyHashMap", "put", "put", "get", "get", "put", "get", "remove", "get"]
[], [1, 1], [2, 2], [1], [3], [2, 1], [2], [2], [2]
```

Output

```
[null, null, null, 1, -1, null, 1, null, -1]
```

Explanation

```
MyHashMap myHashMap = new MyHashMap();

myHashMap.put(1, 1); // The map is now [[1,1]]

myHashMap.put(2, 2); // The map is now [[1,1], [2,2]]

myHashMap.get(1); // return 1, The map is now [[1,1], [2,2]]

myHashMap.get(3); // return -1 (i.e., not found), The map is now [[1,1], [2,2]]

myHashMap.put(2, 1); // The map is now [[1,1], [2,1]] (i.e., update the existing value)

myHashMap.get(2); // return 1, The map is now [[1,1], [2,1]]

myHashMap.remove(2); // remove the mapping for 2, The map is now [[1,1]]

myHashMap.get(2); // return -1 (i.e., not found), The map is now [[1,1]]
```

Constraints:

- $0 \leq \text{key}, \text{value} \leq 10^6$
- At most 10^4 calls will be made to `put`, `get`, and `remove`.

707. Design Linked List

Medium

17921303Add to ListShare

Design your implementation of the linked list. You can choose to use a singly or doubly linked list. A node in a singly linked list should have two attributes: `val` and `next`. `val` is the value of the current node, and `next` is a pointer/reference to the next node.

If you want to use the doubly linked list, you will need one more attribute `prev` to indicate the previous node in the linked list. Assume all nodes in the linked list are **0-indexed**.

Implement the `MyLinkedList` class:

- `MyLinkedList()` Initializes the `MyLinkedList` object.
- `int get(int index)` Get the value of the `indexth` node in the linked list. If the index is invalid, return `-1`.
- `void addAtHead(int val)` Add a node of value `val` before the first element of the linked list. After the insertion, the new node will be the first node of the linked list.
- `void addAtTail(int val)` Append a node of value `val` as the last element of the linked list.
- `void addAtIndex(int index, int val)` Add a node of value `val` before the `indexth` node in the linked list. If `index` equals the length of the linked list, the node will be appended to the end of the linked list. If `index` is greater than the length, the node **will not be inserted**.
- `void deleteAtIndex(int index)` Delete the `indexth` node in the linked list, if the index is valid.

Example 1:

Input

```
["MyLinkedList", "addAtHead", "addAtTail", "addAtIndex", "get", "deleteAtIndex",
"get"]
```

```
[], [1], [3], [1, 2], [1], [1], [1]
```

Output

```
[null, null, null, null, 2, null, 3]
```

Explanation

```
MyLinkedList myLinkedList = new MyLinkedList();
myLinkedList.addAtHead(1);
myLinkedList.addAtTail(3);
```

```

myLinkedList.addAtIndex(1, 2);      // linked list becomes 1->2->3
myLinkedList.get(1);                // return 2
myLinkedList.deleteAtIndex(1);      // now the linked list is 1->3
myLinkedList.get(1);                // return 3

```

Constraints:

- `0 <= index, val <= 1000`
- Please do not use the built-in `LinkedList` library.
- At most `2000` calls will be made to `get`, `addAtHead`, `addAtTail`, `addAtIndex` and `deleteAtIndex`.

709. To Lower Case

Easy

12762453Add to ListShare

Given a string `s`, return *the string after replacing every uppercase letter with the same lowercase letter*.

Example 1:

Input: `s = "Hello"`

Output: `"hello"`

Example 2:

Input: `s = "here"`

Output: `"here"`

Example 3:

Input: `s = "LOVELY"`

Output: `"lovely"`

Constraints:

- `1 <= s.length <= 100`
- `s` consists of printable ASCII characters.

710. Random Pick with Blacklist

Hard

70998Add to ListShare

You are given an integer `n` and an array of **unique** integers `blacklist`. Design an algorithm to pick a random integer in the range `[0, n - 1]` that is **not** in `blacklist`. Any integer that is in the mentioned range and not in `blacklist` should be **equally likely** to be returned.

Optimize your algorithm such that it minimizes the number of calls to the **built-in** random function of your language.

Implement the `Solution` class:

- `Solution(int n, int[] blacklist)` Initializes the object with the integer `n` and the blacklisted integers `blacklist`.
- `int pick()` Returns a random integer in the range `[0, n - 1]` and not in `blacklist`.

Example 1:

Input

```
["Solution", "pick", "pick", "pick", "pick", "pick", "pick", "pick"]
[[7, [2, 3, 5]], [], [], [], [], [], [], []]
```

Output

```
[null, 0, 4, 1, 6, 1, 0, 4]
```

Explanation

```
Solution solution = new Solution(7, [2, 3, 5]);

solution.pick(); // return 0, any integer from [0,1,4,6] should be ok. Note that for
every call of pick,
                                // 0, 1, 4, and 6 must be equally likely to be returned (i.e., with
probability 1/4).

solution.pick(); // return 4

solution.pick(); // return 1

solution.pick(); // return 6

solution.pick(); // return 1
```

```

solution.pick(); // return 0
solution.pick(); // return 4

```

Constraints:

- $1 \leq n \leq 10^9$
- $0 \leq \text{blacklist.length} \leq \min(10^5, n - 1)$
- $0 \leq \text{blacklist}[i] < n$
- All the values of `blacklist` are **unique**.
- At most $2 * 10^4$ calls will be made to `pick`.

712. Minimum ASCII Delete Sum for Two Strings

Medium

224066Add to ListShare

Given two strings `s1` and `s2`, return the lowest **ASCII** sum of deleted characters to make two strings equal.

Example 1:

Input: `s1 = "sea", s2 = "eat"`

Output: 231

Explanation: Deleting "s" from "sea" adds the ASCII value of "s" (115) to the sum.

Deleting "t" from "eat" adds 116 to the sum.

At the end, both strings are equal, and $115 + 116 = 231$ is the minimum sum possible to achieve this.

Example 2:

Input: `s1 = "delete", s2 = "leet"`

Output: 403

Explanation: Deleting "dee" from "delete" to turn the string into "let",

adds $100[d] + 101[e] + 101[e]$ to the sum.

Deleting "e" from "leet" adds $101[e]$ to the sum.

At the end, both strings are equal to "let", and the answer is $100+101+101+101 = 403$.

If instead we turned both strings into "lee" or "eet", we would get answers of 433 or 417, which are higher.

Constraints:

- `1 <= s1.length, s2.length <= 1000`
- `s1` and `s2` consist of lowercase English letters.

713. Subarray Product Less Than K

Medium

4609150Add to ListShare

Given an array of integers `nums` and an integer `k`, return the number of contiguous subarrays where the product of all the elements in the subarray is strictly less than `k`.

Example 1:

Input: `nums = [10,5,2,6]`, `k = 100`

Output: 8

Explanation: The 8 subarrays that have product less than 100 are:

`[10], [5], [2], [6], [10, 5], [5, 2], [2, 6], [5, 2, 6]`

Note that `[10, 5, 2]` is not included as the product of 100 is not strictly less than `k`.

Example 2:

Input: `nums = [1,2,3]`, `k = 0`

Output: 0

Constraints:

- `1 <= nums.length <= 3 * 104`
- `1 <= nums[i] <= 1000`
- `0 <= k <= 106`

714. Best Time to Buy and Sell Stock with Transaction Fee

Medium

4627113Add to ListShare

You are given an array `prices` where `prices[i]` is the price of a given stock on the i^{th} day, and an integer `fee` representing a transaction fee.

Find the maximum profit you can achieve. You may complete as many transactions as you like, but you need to pay the transaction fee for each transaction.

Note: You may not engage in multiple transactions simultaneously (i.e., you must sell the stock before you buy again).

Example 1:

Input: `prices = [1,3,2,8,4,9]`, `fee = 2`

Output: 8

Explanation: The maximum profit can be achieved by:

- Buying at `prices[0] = 1`
- Selling at `prices[3] = 8`
- Buying at `prices[4] = 4`
- Selling at `prices[5] = 9`

The total profit is $((8 - 1) - 2) + ((9 - 4) - 2) = 8$.

Example 2:

Input: `prices = [1,3,7,5,10,3]`, `fee = 3`

Output: 6

Constraints:

- $1 \leq \text{prices.length} \leq 5 * 10^4$
- $1 \leq \text{prices}[i] < 5 * 10^4$
- $0 \leq \text{fee} < 5 * 10^4$

715. Range Module

Hard

112292Add to ListShare

A Range Module is a module that tracks ranges of numbers. Design a data structure to track the ranges represented as **half-open intervals** and query about them.

A **half-open interval** `[left, right)` denotes all the real numbers x where $left \leq x < right$.

Implement the `RangeModule` class:

- `RangeModule()` Initializes the object of the data structure.
- `void addRange(int left, int right)` Adds the **half-open interval** `[left, right)`, tracking every real number in that interval. Adding an interval that partially overlaps with currently tracked numbers should add any numbers in the interval `[left, right)` that are not already tracked.
- `boolean queryRange(int left, int right)` Returns `true` if every real number in the interval `[left, right)` is currently being tracked, and `false` otherwise.
- `void removeRange(int left, int right)` Stops tracking every real number currently being tracked in the **half-open interval** `[left, right)`.

Example 1:

Input

```
["RangeModule", "addRange", "removeRange", "queryRange", "queryRange", "queryRange"]
[], [10, 20], [14, 16], [10, 14], [13, 15], [16, 17]]
```

Output

```
[null, null, null, true, false, true]
```

Explanation

```
RangeModule rangeModule = new RangeModule();
rangeModule.addRange(10, 20);
rangeModule.removeRange(14, 16);
rangeModule.queryRange(10, 14); // return True, (Every number in [10, 14) is being tracked)
rangeModule.queryRange(13, 15); // return False, (Numbers like 14, 14.03, 14.17 in [13, 15) are not being tracked)
rangeModule.queryRange(16, 17); // return True, (The number 16 in [16, 17) is still being tracked, despite the remove operation)
```

Constraints:

- $1 \leq \text{left} < \text{right} \leq 10^9$
- At most 10^4 calls will be made to `addRange`, `queryRange`, and `removeRange`.

717. 1-bit and 2-bit Characters

Easy

7101822Add to ListShare

We have two special characters:

- The first character can be represented by one bit `0`.
- The second character can be represented by two bits (`10` or `11`).

Given a binary array `bits` that ends with `0`, return `true` if the last character must be a one-bit character.

Example 1:

Input: `bits = [1,0,0]`

Output: `true`

Explanation: The only way to decode it is two-bit character and one-bit character.

So the last character is one-bit character.

Example 2:

Input: `bits = [1,1,1,0]`

Output: `false`

Explanation: The only way to decode it is two-bit character and two-bit character.

So the last character is not one-bit character.

Constraints:

- $1 \leq \text{bits.length} \leq 1000$
- `bits[i]` is either `0` or `1`.

718. Maximum Length of Repeated Subarray

Medium

5636142Add to ListShare

Given two integer arrays `nums1` and `nums2`, return *the maximum length of a subarray that appears in both arrays*.

Example 1:

Input: `nums1 = [1,2,3,2,1]`, `nums2 = [3,2,1,4,7]`

Output: 3

Explanation: The repeated subarray with maximum length is `[3,2,1]`.

Example 2:

Input: `nums1 = [0,0,0,0,0]`, `nums2 = [0,0,0,0,0]`

Output: 5

Explanation: The repeated subarray with maximum length is `[0,0,0,0,0]`.

Constraints:

- `1 <= nums1.length, nums2.length <= 1000`
- `0 <= nums1[i], nums2[i] <= 100`

719. Find K-th Smallest Pair Distance

Hard

230972Add to ListShare

The **distance of a pair** of integers `a` and `b` is defined as the absolute difference between `a` and `b`.

Given an integer array `nums` and an integer `k`, return *the k^{th} smallest **distance among all the pairs** `nums[i]` and `nums[j]` where $0 \leq i < j < \text{nums.length}$* .

Example 1:

Input: `nums = [1,3,1]`, `k = 1`

Output: 0

Explanation: Here are all the pairs:

`(1,3) -> 2`

`(1,1) -> 0`

```
(3,1) -> 2
```

Then the 1st smallest distance pair is (1,1), and its distance is 0.

Example 2:

Input: nums = [1,1,1], k = 2

Output: 0

Example 3:

Input: nums = [1,6,1], k = 3

Output: 5

Constraints:

- n == nums.length
- 2 <= n <= 10⁴
- 0 <= nums[i] <= 10⁶
- 1 <= k <= n * (n - 1) / 2

720. Longest Word in Dictionary

Medium

15521375Add to ListShare

Given an array of strings `words` representing an English Dictionary, return *the longest word in `words` that can be built one character at a time by other words in `words`*.

If there is more than one possible answer, return the longest word with the smallest lexicographical order. If there is no answer, return the empty string.

Note that the word should be built from left to right with each additional character being added to the end of a previous word.

Example 1:

Input: words = ["w", "wo", "wor", "worl", "world"]

Output: "world"

Explanation: The word "world" can be built one character at a time by "w", "wo", "wor", and "worl".

Example 2:

Input: words = ["a", "banana", "app", "appl", "ap", "apply", "apple"]

Output: "apple"

Explanation: Both "apply" and "apple" can be built from other words in the dictionary. However, "apple" is lexicographically smaller than "apply".

Constraints:

- `1 <= words.length <= 1000`
- `1 <= words[i].length <= 30`
- `words[i]` consists of lowercase English letters.

721. Accounts Merge

Medium

4808846 Add to List Share

Given a list of `accounts` where each element `accounts[i]` is a list of strings, where the first element `accounts[i][0]` is a name, and the rest of the elements are `emails` representing emails of the account.

Now, we would like to merge these accounts. Two accounts definitely belong to the same person if there is some common email to both accounts. Note that even if two accounts have the same name, they may belong to different people as people could have the same name. A person can have any number of accounts initially, but all of their accounts definitely have the same name.

After merging the accounts, return the accounts in the following format: the first element of each account is the name, and the rest of the elements are emails **in sorted order**. The accounts themselves can be returned in **any order**.

Example 1:

Input: accounts =
`[["John", "johnsmith@mail.com", "john_newyork@mail.com"], ["John", "johnsmith@mail.com", "john00@mail.com"], ["Mary", "mary@mail.com"], ["John", "johnnybravo@mail.com"]]`

Output:
`[["John", "john00@mail.com", "john_newyork@mail.com", "johnsmith@mail.com"], ["Mary", "mary@mail.com"], ["John", "johnnybravo@mail.com"]]`

Explanation:

The first and second John's are the same person as they have the common email "johnsmith@mail.com".

The third John and Mary are different people as none of their email addresses are used by other accounts.

We could return these lists in any order, for example the answer `[['Mary', 'mary@mail.com'], ['John', 'johnnybravo@mail.com'], ['John', 'john00@mail.com', 'john_newyork@mail.com', 'johnsmith@mail.com']]` would still be accepted.

Example 2:

Input: `accounts = [[["Gabe", "Gabe0@m.co", "Gabe3@m.co", "Gabe1@m.co"], ["Kevin", "Kevin3@m.co", "Kevin5@m.co", "Kevin0@m.co"], ["Ethan", "Ethan5@m.co", "Ethan4@m.co", "Ethan0@m.co"], ["Hanzo", "Hanzo3@m.co", "Hanzo1@m.co", "Hanzo0@m.co"], ["Fern", "Fern5@m.co", "Fern1@m.co", "Fern0@m.co"]]]`

Output:

`[[["Ethan", "Ethan0@m.co", "Ethan4@m.co", "Ethan5@m.co"], ["Gabe", "Gabe0@m.co", "Gabe1@m.co", "Gabe3@m.co"], ["Hanzo", "Hanzo0@m.co", "Hanzo1@m.co", "Hanzo3@m.co"], ["Kevin", "Kevin0@m.co", "Kevin3@m.co", "Kevin5@m.co"], ["Fern", "Fern0@m.co", "Fern1@m.co", "Fern5@m.co"]]]`

Constraints:

- `1 <= accounts.length <= 1000`
- `2 <= accounts[i].length <= 10`
- `1 <= accounts[i][j].length <= 30`
- `accounts[i][0]` consists of English letters.
- `accounts[i][j] (for j > 0)` is a valid email.

722. Remove Comments

Medium

6011594Add to ListShare

Given a C++ program, remove comments from it. The program source is an array of strings `source` where `source[i]` is the i^{th} line of the source code. This represents the result of splitting the original source code string by the newline character '`\n`'.

In C++, there are two types of comments, line comments, and block comments.

- The string `"/\/*"` denotes a line comment, which represents that it and the rest of the characters to the right of it in the same line should be ignored.
- The string `"/\/*/*"` denotes a block comment, which represents that all characters until the next (non-overlapping) occurrence of `/*/*` should be ignored. (Here, occurrences happen in reading order: line by line from left to right.) To be clear, the string `"/\/*/*"` does not yet end the block comment, as the ending would be overlapping the beginning.

The first effective comment takes precedence over others.

- For example, if the string `"/ /"` occurs in a block comment, it is ignored.
- Similarly, if the string `"/ /*"` occurs in a line or block comment, it is also ignored.

If a certain line of code is empty after removing comments, you must not output that line: each string in the answer list will be non-empty.

There will be no control characters, single quote, or double quote characters.

- For example, `source = "string s = /* Not a comment. */;"` will not be a test case.

Also, nothing else such as defines or macros will interfere with the comments.

It is guaranteed that every open block comment will eventually be closed, so `"/ /*"` outside of a line or block comment always starts a new comment.

Finally, implicit newline characters can be deleted by block comments. Please see the examples below for details.

After removing the comments from the source code, return *the source code in the same format*.

Example 1:

Input: `source = ["/*Test program */", "int main()", "{ ", " // variable declaration", "int a, b, c;", "/* This is a test", " multiline ", " comment for ", "testing */", "a = b + c;", "}"]`

Output: `["int main()", "{ ", " ", "int a, b, c;", "a = b + c;", "}"]`

Explanation: The line by line code is visualized as below:

```
/*Test program */

int main()

{
    // variable declaration

    int a, b, c;

    /* This is a test
        multiline
        comment for
        testing */
```

```
a = b + c;
}
```

The string /* denotes a block comment, including line 1 and lines 6-9. The string // denotes line 4 as comments.

The line by line output code is visualized as below:

```
int main()
{
```

```
int a, b, c;
a = b + c;
}
```

Example 2:

Input: source = ["a/*comment", "line", "more_comment*/b"]

Output: ["ab"]

Explanation: The original source string is "a/*comment\nline\nmore_comment*/b", where we have bolded the newline characters. After deletion, the implicit newline characters are deleted, leaving the string "ab", which when delimited by newline characters becomes ["ab"].

Constraints:

- $1 \leq \text{source.length} \leq 100$
- $0 \leq \text{source}[i].length \leq 80$
- `source[i]` consists of printable **ASCII** characters.
- Every open block comment is eventually closed.
- There are no single-quote or double-quote in the input.

724. Find Pivot Index

Easy

4824519Add to ListShare

Given an array of integers `nums`, calculate the **pivot index** of this array.

The **pivot index** is the index where the sum of all the numbers **strictly** to the left of the index is equal to the sum of all the numbers **strictly** to the index's right.

If the index is on the left edge of the array, then the left sum is 0 because there are no elements to the left. This also applies to the right edge of the array.

Return *the leftmost pivot index*. If no such index exists, return -1.

Example 1:

Input: nums = [1,7,3,6,5,6]

Output: 3

Explanation:

The pivot index is 3.

Left sum = $\text{nums}[0] + \text{nums}[1] + \text{nums}[2] = 1 + 7 + 3 = 11$

Right sum = $\text{nums}[4] + \text{nums}[5] = 5 + 6 = 11$

Example 2:

Input: nums = [1,2,3]

Output: -1

Explanation:

There is no index that satisfies the conditions in the problem statement.

Example 3:

Input: nums = [2,1,-1]

Output: 0

Explanation:

The pivot index is 0.

Left sum = 0 (no elements to the left of index 0)

Right sum = $\text{nums}[1] + \text{nums}[2] = 1 + -1 = 0$

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-1000 \leq \text{nums}[i] \leq 1000$

725. Split Linked List in Parts

Medium

2048207 Add to List Share


Given the `head` of a singly linked list and an integer `k`, split the linked list into `k` consecutive linked list parts.

The length of each part should be as equal as possible: no two parts should have a size differing by more than one. This may lead to some parts being null.

The parts should be in the order of occurrence in the input list, and parts occurring earlier should always have a size greater than or equal to parts occurring later.

Return *an array of the `k` parts*.

Example 1:



Input: head = [1,2,3], k = 5


Output: [[1],[2],[3],[],[]]

Explanation:

The first element `output[0]` has `output[0].val = 1`, `output[0].next = null`.

The last element `output[4]` is `null`, but its string representation as a `ListNode` is `[]`.

Example 2:



Input: head = [1,2,3,4,5,6,7,8,9,10], k = 3

Output: [[1,2,3,4],[5,6,7],[8,9,10]]

Explanation:

The input has been split into consecutive parts with size difference at most 1, and earlier parts are a larger size than the later parts.

Constraints:

- The number of nodes in the list is in the range `[0, 1000]`.
- `0 <= Node.val <= 1000`
- `1 <= k <= 50`

726. Number of Atoms**Hard**

1039263Add to ListShare

Given a string `formula` representing a chemical formula, return *the count of each atom*.

The atomic element always starts with an uppercase character, then zero or more lowercase letters, representing the name.

One or more digits representing that element's count may follow if the count is greater than `1`. If the count is `1`, no digits will follow.

- For example, `"H2O"` and `"H2O2"` are possible, but `"H1O2"` is impossible.

Two formulas are concatenated together to produce another formula.

- For example, `"H2O2He3Mg4"` is also a formula.

A formula placed in parentheses, and a count (optionally added) is also a formula.

- For example, `"(H2O2)"` and `"(H2O2) 3"` are formulas.

Return the count of all elements as a string in the following form: the first name (in sorted order), followed by its count (if that count is more than `1`), followed by the second name (in sorted order), followed by its count (if that count is more than `1`), and so on.

The test cases are generated so that all the values in the output fit in a **32-bit** integer.

Example 1:

Input: `formula = "H2O"`

Output: `"H2O"`

Explanation: The count of elements are {'H': 2, 'O': 1}.

Example 2:

Input: formula = "Mg(OH)2"

Output: "H2MgO2"

Explanation: The count of elements are {'H': 2, 'Mg': 1, 'O': 2}.

Example 3:

Input: formula = "K4(ON(SO3)2)2"

Output: "K4N2O14S4"

Explanation: The count of elements are {'K': 4, 'N': 2, 'O': 14, 'S': 4}.

Constraints:

- $1 \leq \text{formula.length} \leq 1000$
- `formula` consists of English letters, digits, '`(`', and '`)`'.
- `formula` is always valid.

728. Self Dividing Numbers

Easy

1283354Add to ListShare

A **self-dividing number** is a number that is divisible by every digit it contains.

- For example, 128 is a **self-dividing number** because $128 \% 1 == 0$, $128 \% 2 == 0$, and $128 \% 8 == 0$.

A **self-dividing number** is not allowed to contain the digit zero.

Given two integers `left` and `right`, return a list of all the **self-dividing numbers** in the range `[left, right]`.

Example 1:

Input: left = 1, right = 22

Output: [1,2,3,4,5,6,7,8,9,11,12,15,22]

Example 2:

Input: left = 47, right = 85

Output: [48,55,66,77]

Constraints:

- `1 <= left <= right <= 104`

729. My Calendar I

Medium

347690Add to ListShare

You are implementing a program to use as your calendar. We can add a new event if adding the event will not cause a **double booking**.

A **double booking** happens when two events have some non-empty intersection (i.e., some moment is common to both events.).

The event can be represented as a pair of integers `start` and `end` that represents a booking on the half-open interval `[start, end)`, the range of real numbers `x` such that `start <= x < end`.

Implement the `MyCalendar` class:

- `MyCalendar()` Initializes the calendar object.
- `boolean book(int start, int end)` Returns `true` if the event can be added to the calendar successfully without causing a **double booking**. Otherwise, return `false` and do not add the event to the calendar.

Example 1:

Input

```
["MyCalendar", "book", "book", "book"]
[], [10, 20], [15, 25], [20, 30]
```

Output

```
[null, true, false, true]
```

Explanation

```
MyCalendar myCalendar = new MyCalendar();
```

```
myCalendar.book(10, 20); // return True

myCalendar.book(15, 25); // return False, It can not be booked because time 15 is
already booked by another event.

myCalendar.book(20, 30); // return True, The event can be booked, as the first event
takes every time less than 20, but not including 20.
```

Constraints:

- $0 \leq \text{start} < \text{end} \leq 10^9$
- At most 1000 calls will be made to `book`.

730. Count Different Palindromic Subsequences

Hard

153180Add to ListShare

Given a string s , return the number of different non-empty palindromic subsequences in s . Since the answer may be very large, return it **modulo** $10^9 + 7$.

A subsequence of a string is obtained by deleting zero or more characters from the string.

A sequence is palindromic if it is equal to the sequence reversed.

Two sequences a_1, a_2, \dots and b_1, b_2, \dots are different if there is some i for which $a_i \neq b_i$.

Example 1:

Input: $s = "bccb"$

Output: 6

Explanation: The 6 different non-empty palindromic subsequences are 'b', 'c', 'bb', 'cc', 'bcb', 'bccb'.

Note that 'bcb' is counted only once, even though it occurs twice.

Example 2:

Input: $s = "abcdabcdaabcdabcdaabcdabcdaabcdabcda"$

Output: 104860361

Explanation: There are 3104860382 different non-empty palindromic subsequences, which is 104860361 modulo $10^9 + 7$.

Constraints:

- $1 \leq s.length \leq 1000$
- $s[i]$ is either 'a', 'b', 'c', or 'd'.

731. My Calendar II**Medium**

1324131Add to ListShare

You are implementing a program to use as your calendar. We can add a new event if adding the event will not cause a **triple booking**.

A **triple booking** happens when three events have some non-empty intersection (i.e., some moment is common to all the three events.).

The event can be represented as a pair of integers `start` and `end` that represents a booking on the half-open interval $[start, end]$, the range of real numbers x such that $start \leq x < end$.

Implement the `MyCalendarTwo` class:

- `MyCalendarTwo()` Initializes the calendar object.
- `boolean book(int start, int end)` Returns `true` if the event can be added to the calendar successfully without causing a **triple booking**. Otherwise, return `false` and do not add the event to the calendar.

Example 1:**Input**

```
["MyCalendarTwo", "book", "book", "book", "book", "book", "book", "book"]
[], [10, 20], [50, 60], [10, 40], [5, 15], [5, 10], [25, 55]
```

Output

```
[null, true, true, true, false, true, true]
```

Explanation

```
MyCalendarTwo myCalendarTwo = new MyCalendarTwo();
myCalendarTwo.book(10, 20); // return True, The event can be booked.
myCalendarTwo.book(50, 60); // return True, The event can be booked.
myCalendarTwo.book(10, 40); // return True, The event can be double booked.
```

```
myCalendarTwo.book(5, 15); // return False, The event cannot be booked, because it
would result in a triple booking.
```

```
myCalendarTwo.book(5, 10); // return True, The event can be booked, as it does not
use time 10 which is already double booked.
```

```
myCalendarTwo.book(25, 55); // return True, The event can be booked, as the time in
[25, 40) will be double booked with the third event, the time [40, 50) will be single
booked, and the time [50, 55) will be double booked with the second event.
```

Constraints:

- $0 \leq \text{start} < \text{end} \leq 10^9$
- At most 1000 calls will be made to `book`.

732. My Calendar III

Hard

850153Add to ListShare

A k -booking happens when k events have some non-empty intersection (i.e., there is some time that is common to all k events.)

You are given some events `[start, end]`, after each given event, return an integer k representing the maximum k -booking between all the previous events.

Implement the `MyCalendarThree` class:

- `MyCalendarThree()` Initializes the object.
- `int book(int start, int end)` Returns an integer k representing the largest integer such that there exists a k -booking in the calendar.

Example 1:

Input

```
["MyCalendarThree", "book", "book", "book", "book", "book", "book", "book"]
[], [10, 20], [50, 60], [10, 40], [5, 15], [5, 10], [25, 55]
```

Output

```
[null, 1, 1, 2, 3, 3, 3]
```

Explanation

```

MyCalendarThree myCalendarThree = new MyCalendarThree();

myCalendarThree.book(10, 20); // return 1, The first event can be booked and is
disjoint, so the maximum k-booking is a 1-booking.

myCalendarThree.book(50, 60); // return 1, The second event can be booked and is
disjoint, so the maximum k-booking is a 1-booking.

myCalendarThree.book(10, 40); // return 2, The third event [10, 40) intersects the
first event, and the maximum k-booking is a 2-booking.

myCalendarThree.book(5, 15); // return 3, The remaining events cause the maximum K-
booking to be only a 3-booking.

myCalendarThree.book(5, 10); // return 3

myCalendarThree.book(25, 55); // return 3

```

Constraints:

- $0 \leq \text{start} < \text{end} \leq 10^9$
- At most 400 calls will be made to `book`.

733. Flood Fill

Easy

5533536Add to ListShare


An image is represented by an $m \times n$ integer grid `image` where `image[i][j]` represents the pixel value of the image.

You are also given three integers `sr`, `sc`, and `color`. You should perform a **flood fill** on the image starting from the pixel `image[sr][sc]`.

To perform a **flood fill**, consider the starting pixel, plus any pixels connected **4-directionally** to the starting pixel of the same color as the starting pixel, plus any pixels connected **4-directionally** to those pixels (also with the same color), and so on. Replace the color of all of the aforementioned pixels with `color`.

Return *the modified image after performing the flood fill*.

Example 1:



Input: image = [[1,1,1],[1,1,0],[1,0,1]], sr = 1, sc = 1, color = 2

Output: [[2,2,2],[2,2,0],[2,0,1]]

Explanation: From the center of the image with position (sr, sc) = (1, 1) (i.e., the red pixel), all pixels connected by a path of the same color as the starting pixel (i.e., the blue pixels) are colored with the new color.

Note the bottom corner is not colored 2, because it is not 4-directionally connected to the starting pixel.

Example 2:

Input: image = [[0,0,0],[0,0,0]], sr = 0, sc = 0, color = 0

Output: [[0,0,0],[0,0,0]]

Explanation: The starting pixel is already colored 0, so no changes are made to the image.

Constraints:

- $m == \text{image.length}$
- $n == \text{image}[i].length$
- $1 \leq m, n \leq 50$
- $0 \leq \text{image}[i][j], \text{color} < 2^{16}$
- $0 \leq sr < m$
- $0 \leq sc < n$

735. Asteroid Collision

Medium

4099345 Add to List Share

We are given an array `asteroids` of integers representing asteroids in a row.

For each asteroid, the absolute value represents its size, and the sign represents its direction (positive meaning right, negative meaning left). Each asteroid moves at the same speed.

Find out the state of the asteroids after all collisions. If two asteroids meet, the smaller one will explode. If both are the same size, both will explode. Two asteroids moving in the same direction will never meet.

Example 1:

Input: asteroids = [5,10,-5]

Output: [5,10]

Explanation: The 10 and -5 collide resulting in 10. The 5 and 10 never collide.

Example 2:

Input: asteroids = [8,-8]

Output: []

Explanation: The 8 and -8 collide exploding each other.

Example 3:

Input: asteroids = [10,2,-5]

Output: [10]

Explanation: The 2 and -5 collide resulting in -5. The 10 and -5 collide resulting in 10.

Constraints:

- $2 \leq \text{asteroids.length} \leq 10^4$
- $-1000 \leq \text{asteroids}[i] \leq 1000$
- $\text{asteroids}[i] \neq 0$

736. Parse Lisp Expression

Hard

411319Add to ListShare

You are given a string expression representing a Lisp-like expression to return the integer value of.

The syntax for these expressions is given as follows.

- An expression is either an integer, let expression, add expression, mult expression, or an assigned variable. Expressions always evaluate to a single integer.
- (An integer could be positive or negative.)
- A let expression takes the form "`(let v1 e1 v2 e2 ... vn en expr)`", where let is always the string "`let`", then there are one or more pairs of alternating variables and expressions, meaning that the first variable `v1` is assigned the value of the expression `e1`, the second variable `v2` is assigned the value of the expression `e2`, and so on sequentially; and then the value of this let expression is the value of the expression `expr`.
- An add expression takes the form "`(add e1 e2)`" where add is always the string "`add`", there are always two expressions `e1, e2` and the result is the addition of the evaluation of `e1` and the evaluation of `e2`.
- A mult expression takes the form "`(mult e1 e2)`" where mult is always the string "`mult`", there are always two expressions `e1, e2` and the result is the multiplication of the evaluation of `e1` and the evaluation of `e2`.
- For this question, we will use a smaller subset of variable names. A variable starts with a lowercase letter, then zero or more lowercase letters or digits. Additionally, for your convenience, the names "`add`", "`let`", and "`mult`" are protected and will never be used as variable names.
- Finally, there is the concept of scope. When an expression of a variable name is evaluated, within the context of that evaluation, the innermost scope (in terms of parentheses) is checked first for the value of that variable, and then outer scopes are checked sequentially. It is guaranteed that every expression is legal. Please see the examples for more details on the scope.

Example 1:

Input: expression = "`(let x 2 (mult x (let x 3 y 4 (add x y))))`"

Output: 14

Explanation: In the expression `(add x y)`, when checking for the value of the variable `x`,

we check from the innermost scope to the outermost in the context of the variable we are trying to evaluate.

Since `x = 3` is found first, the value of `x` is 3.

Example 2:

Input: expression = "`(let x 3 x 2 x)`"

Output: 2

Explanation: Assignment in let statements is processed sequentially.

Example 3:

Input: expression = "(let x 1 y 2 x (add x y) (add x y))"

Output: 5

Explanation: The first (add x y) evaluates as 3, and is assigned to x.

The second (add x y) evaluates as $3+2 = 5$.

Constraints:

- $1 \leq \text{expression.length} \leq 2000$
- There are no leading or trailing spaces in expression.
- All tokens are separated by a single space in expression.
- The answer and all intermediate calculations of that answer are guaranteed to fit in a **32-bit** integer.
- The expression is guaranteed to be legal and evaluate to an integer.

738. Monotone Increasing Digits

Medium

104590Add to ListShare

An integer has **monotone increasing digits** if and only if each pair of adjacent digits x and y satisfy $x \leq y$.

Given an integer n , return *the largest number that is less than or equal to n with monotone increasing digits*.

Example 1:

Input: n = 10

Output: 9

Example 2:

Input: n = 1234

Output: 1234

Example 3:

Input: n = 332

Output: 299

Constraints:

- $0 \leq n \leq 10^9$

739. Daily Temperatures**Medium**

8197185Add to ListShare

Given an array of integers `temperatures` represents the daily temperatures, return an array `answer` such that `answer[i]` is the number of days you have to wait after the `ith` day to get a warmer temperature. If there is no future day for which this is possible, keep `answer[i] == 0` instead.

Example 1:

Input: `temperatures = [73,74,75,71,69,72,76,73]`

Output: `[1,1,4,2,1,1,0,0]`

Example 2:

Input: `temperatures = [30,40,50,60]`

Output: `[1,1,1,0]`

Example 3:

Input: `temperatures = [30,60,90]`

Output: `[1,1,0]`

Constraints:

- $1 \leq \text{temperatures.length} \leq 10^5$
- $30 \leq \text{temperatures}[i] \leq 100$

740. Delete and Earn**Medium**

5637301Add to ListShare

You are given an integer array `nums`. You want to maximize the number of points you get by performing the following operation any number of times:

- Pick any `nums[i]` and delete it to earn `nums[i]` points. Afterwards, you must delete **every** element equal to `nums[i] - 1` and **every** element equal to `nums[i] + 1`.

Return *the maximum number of points* you can earn by applying the above operation some number of times.

Example 1:

Input: nums = [3,4,2]

Output: 6

Explanation: You can perform the following operations:

- Delete 4 to earn 4 points. Consequently, 3 is also deleted. nums = [2].
- Delete 2 to earn 2 points. nums = [].

You earn a total of 6 points.

Example 2:

Input: nums = [2,2,3,3,3,4]

Output: 9

Explanation: You can perform the following operations:

- Delete a 3 to earn 3 points. All 2's and 4's are also deleted. nums = [3,3].
- Delete a 3 again to earn 3 points. nums = [3].
- Delete a 3 once more to earn 3 points. nums = [].

You earn a total of 9 points.

Constraints:

- $1 \leq \text{nums.length} \leq 2 * 10^4$
- $1 \leq \text{nums}[i] \leq 10^4$

741. Cherry Pickup

Hard

3201130Add to ListShare

You are given an $n \times n$ grid representing a field of cherries, each cell is one of three possible integers.


- 0 means the cell is empty, so you can pass through,
- 1 means the cell contains a cherry that you can pick up and pass through, or

- -1 means the cell contains a thorn that blocks your way.

Return the maximum number of cherries you can collect by following the rules below:

- Starting at the position $(0, 0)$ and reaching $(n - 1, n - 1)$ by moving right or down through valid path cells (cells with value 0 or 1).
- After reaching $(n - 1, n - 1)$, returning to $(0, 0)$ by moving left or up through valid path cells.
- When passing through a path cell containing a cherry, you pick it up, and the cell becomes an empty cell 0.
- If there is no valid path between $(0, 0)$ and $(n - 1, n - 1)$, then no cherries can be collected.

Example 1:



Input: grid = $[[0,1,-1],[1,0,-1],[1,1,1]]$

Output: 5

Explanation: The player started at $(0, 0)$ and went down, down, right right to reach $(2, 2)$.

4 cherries were picked up during this single trip, and the matrix becomes $[[0,1,-1],[0,0,-1],[0,0,0]]$.

Then, the player went left, up, up, left to return home, picking up one more cherry.

The total number of cherries picked up is 5, and this is the maximum possible.

Example 2:

Input: grid = $[[1,1,-1],[1,-1,1],[-1,1,1]]$

Output: 0

Constraints:


- $n == \text{grid.length}$
- $n == \text{grid}[i].length$
- $1 \leq n \leq 50$
- $\text{grid}[i][j]$ is $-1, 0$, or 1 .
- $\text{grid}[0][0] \neq -1$
- $\text{grid}[n - 1][n - 1] \neq -1$

743. Network Delay Time**Medium**

5590318Add to ListShare

You are given a network of n nodes, labeled from 1 to n . You are also given times , a list of travel times as directed edges $\text{times}[i] = (u_i, v_i, w_i)$, where u_i is the source node, v_i is the target node, and w_i is the time it takes for a signal to travel from source to target.

We will send a signal from a given node k . Return the **minimum** time it takes for all the n nodes to receive the signal. If it is impossible for all the n nodes to receive the signal, return -1 .

Example 1:

Input: $\text{times} = [[2,1,1],[2,3,1],[3,4,1]]$, $n = 4$, $k = 2$

Output: 2

Example 2:

Input: $\text{times} = [[1,2,1]]$, $n = 2$, $k = 1$

Output: 1

Example 3:

Input: times = [[1,2,1]], n = 2, k = 2

Output: -1

Constraints:

- $1 \leq k \leq n \leq 100$
- $1 \leq \text{times.length} \leq 6000$
- $\text{times}[i].length == 3$
- $1 \leq u_i, v_i \leq n$
- $u_i \neq v_i$
- $0 \leq w_i \leq 100$
- All the pairs (u_i, v_i) are **unique**. (i.e., no multiple edges.)

744. Find Smallest Letter Greater Than Target

Easy

22031871Add to ListShare

Given a characters array `letters` that is sorted in **non-decreasing** order and a character `target`, return *the smallest character in the array that is larger than target*.

Note that the letters wrap around.

- For example, if `target == 'z'` and `letters == ['a', 'b']`, the answer is `'a'`.

Example 1:

Input: letters = ["c", "f", "j"], target = "a"

Output: "c"

Example 2:

Input: letters = ["c", "f", "j"], target = "c"

Output: "f"

Example 3:

Input: letters = ["c", "f", "j"], target = "d"

Output: "f"

Constraints:

- `2 <= letters.length <= 104`
- `letters[i]` is a lowercase English letter.
- `letters` is sorted in **non-decreasing** order.
- `letters` contains at least two different characters.
- `target` is a lowercase English letter.

745. Prefix and Suffix Search**Hard**

2038461Add to ListShare

Design a special dictionary that searches the words in it by a prefix and a suffix.

Implement the `WordFilter` class:

- `WordFilter(string[] words)` Initializes the object with the `words` in the dictionary.
- `f(string pref, string suff)` Returns *the index of the word in the dictionary*, which has the prefix `pref` and the suffix `suff`. If there is more than one valid index, return **the largest** of them. If there is no such word in the dictionary, return `-1`.

Example 1:**Input**

```
[ "WordFilter", "f" ]
[[["apple"]], ["a", "e"]]
```

Output

```
[null, 0]
```

Explanation

```
WordFilter wordFilter = new WordFilter(["apple"]);
wordFilter.f("a", "e"); // return 0, because the word at index 0 has prefix = "a" and
suffix = "e".
```

Constraints:

- `1 <= words.length <= 104`
- `1 <= words[i].length <= 7`
- `1 <= pref.length, suff.length <= 7`

- `words[i]`, `pref` and `suff` consist of lowercase English letters only.
- At most 10^4 calls will be made to the function `f`.

746. Min Cost Climbing Stairs

Easy

79161263Add to ListShare

You are given an integer array `cost` where `cost[i]` is the cost of i^{th} step on a staircase. Once you pay the cost, you can either climb one or two steps.

You can either start from the step with index `0`, or the step with index `1`.

Return *the minimum cost to reach the top of the floor*.

Example 1:

Input: `cost = [10, 15, 20]`

Output: 15

Explanation: You will start at index 1.

- Pay 15 and climb two steps to reach the top.

The total cost is 15.

Example 2:

Input: `cost = [1, 100, 1, 1, 1, 100, 1, 1, 100, 1]`

Output: 6

Explanation: You will start at index 0.

- Pay 1 and climb two steps to reach index 2.

- Pay 1 and climb two steps to reach index 4.

- Pay 1 and climb two steps to reach index 6.

- Pay 1 and climb one step to reach index 7.

- Pay 1 and climb two steps to reach index 9.

- Pay 1 and climb one step to reach the top.

The total cost is 6.

Constraints:

- $2 \leq \text{cost.length} \leq 1000$
- $0 \leq \text{cost}[i] \leq 999$

747. Largest Number At Least Twice of Others**Easy**

816808Add to ListShare

You are given an integer array `nums` where the largest integer is **unique**.

Determine whether the largest element in the array is **at least twice** as much as every other number in the array. If it is, return *the index of the largest element*, or return `-1` otherwise.

Example 1:**Input:** `nums = [3,6,1,0]`**Output:** `1`**Explanation:** `6` is the largest integer.For every other number in the array x , `6` is at least twice as big as x .The index of value `6` is `1`, so we return `1`.**Example 2:****Input:** `nums = [1,2,3,4]`**Output:** `-1`**Explanation:** `4` is less than twice the value of `3`, so we return `-1`.**Constraints:**

- $2 \leq \text{nums.length} \leq 50$
- $0 \leq \text{nums}[i] \leq 100$
- The largest element in `nums` is unique.

748. Shortest Completing Word**Easy**

370919Add to ListShare

Given a string `licensePlate` and an array of strings `words`, find the **shortest completing** word in `words`.

A **completing** word is a word that **contains all the letters** in `licensePlate`. **Ignore numbers and spaces** in `licensePlate`, and treat letters as **case insensitive**. If a letter appears more than once in `licensePlate`, then it must appear in the word the same number of times or more.

For example, if `licensePlate = "aBc 12c"`, then it contains letters '`a`', '`b`' (ignoring case), and '`c`' twice. Possible **completing** words are "`abccdef`", "`caaacab`", and "`cbca`".

Return *the shortest **completing** word in `words`*. It is guaranteed an answer exists. If there are multiple shortest **completing** words, return the **first** one that occurs in `words`.

Example 1:

Input: `licensePlate = "1s3 PSt"`, `words = ["step", "steps", "stripe", "stepple"]`

Output: "`steps`"

Explanation: `licensePlate` contains letters '`s`', '`p`', '`s`' (ignoring case), and '`t`'.

"`step`" contains '`t`' and '`p`', but only contains 1 '`s`'.

"`steps`" contains '`t`', '`p`', and both '`s`' characters.

"`stripe`" is missing an '`s`'.

"`stepple`" is missing an '`s`'.

Since "`steps`" is the only word containing all the letters, that is the answer.

Example 2:

Input: `licensePlate = "1s3 456"`, `words = ["looks", "pest", "stew", "show"]`

Output: "`pest`"

Explanation: `licensePlate` only contains the letter '`s`'. All the words contain '`s`', but among these "`pest`", "`stew`", and "`show`" are shortest. The answer is "`pest`" because it is the word that appears earliest of the 3.

Constraints:

- `1 <= licensePlate.length <= 7`
- `licensePlate` contains digits, letters (uppercase or lowercase), or space ''.
- `1 <= words.length <= 1000`
- `1 <= words[i].length <= 15`
- `words[i]` consists of lower case English letters.

749. Contain Virus

Hard

285400Add to ListShare

A virus is spreading rapidly, and your task is to quarantine the infected area by installing walls.

The world is modeled as an $m \times n$ binary grid `isInfected`, where `isInfected[i][j] == 0` represents uninfected cells, and `isInfected[i][j] == 1` represents cells contaminated with the virus. A wall (and only one wall) can be installed between any two **4-directionally** adjacent cells, on the shared boundary.

Every night, the virus spreads to all neighboring cells in all four directions unless blocked by a wall. Resources are limited. Each day, you can install walls around only one region (i.e., the affected area (continuous block of infected cells) that threatens the most uninfected cells the following night). There **will never be a tie**.

Return *the number of walls used to quarantine all the infected regions*. If the world will become fully infected, return the number of walls used.

Example 1:


							
							
							

Input: `isInfected = [[0,1,0,0,0,0,0,1],[0,1,0,0,0,0,0,1],[0,0,0,0,0,0,0,1],[0,0,0,0,0,0,0,0]]`


Output: 10

Explanation: There are 2 contaminated regions.


On the first day, add 5 walls to quarantine the viral region on the left. The board after the virus spreads is:



On the second day, add 5 walls to quarantine the viral region on the right. The virus is fully contained.



Example 2:



Input: isInfected = [[1,1,1],[1,0,1],[1,1,1]]

Output: 4

Explanation: Even though there is only one cell saved, there are 4 walls built.

Notice that walls are only built on the shared boundary of two different cells.

Example 3:

Input: isInfected = [[1,1,1,0,0,0,0,0,0],[1,0,1,0,1,1,1,1,1],[1,1,1,0,0,0,0,0,0]]

Output: 13

Explanation: The region on the left only builds two new walls.

Constraints:

- $m == \text{isInfected.length}$
- $n == \text{isInfected}[i].length$
- $1 \leq m, n \leq 50$
- $\text{isInfected}[i][j]$ is either 0 or 1.
- There is always a contiguous viral region throughout the described process that will **infect strictly more uncontaminated squares** in the next round.

752. Open the Lock

Medium

3212115Add to ListShare

You have a lock in front of you with 4 circular wheels. Each wheel has 10 slots: '0', '1', '2', '3', '4', '5', '6', '7', '8', '9'. The wheels can rotate freely and wrap around: for example we can turn '9' to be '0', or '0' to be '9'. Each move consists of turning one wheel one slot.

The lock initially starts at `'0000'`, a string representing the state of the 4 wheels.

You are given a list of `deadends` dead ends, meaning if the lock displays any of these codes, the wheels of the lock will stop turning and you will be unable to open it.

Given a `target` representing the value of the wheels that will unlock the lock, return the minimum total number of turns required to open the lock, or `-1` if it is impossible.

Example 1:

Input: `deadends = ["0201", "0101", "0102", "1212", "2002"]`, `target = "0202"`

Output: `6`

Explanation:

A sequence of valid moves would be `"0000" -> "1000" -> "1100" -> "1200" -> "1201" -> "1202" -> "0202"`.

Note that a sequence like `"0000" -> "0001" -> "0002" -> "0102" -> "0202"` would be invalid,

because the wheels of the lock become stuck after the display becomes the dead end `"0102"`.

Example 2:

Input: `deadends = ["8888"]`, `target = "0009"`

Output: `1`

Explanation: We can turn the last wheel in reverse to move from `"0000" -> "0009"`.

Example 3:

Input: `deadends = ["8887", "8889", "8878", "8898", "8788", "8988", "7888", "9888"]`, `target = "8888"`

Output: `-1`

Explanation: We cannot reach the target without getting stuck.

Constraints:

- `1 <= deadends.length <= 500`
- `deadends[i].length == 4`
- `target.length == 4`

- target **will not be** in the list deadends.
- target and deadends[i] consist of digits only.

753. Cracking the Safe

Hard

32562Add to ListShare

There is a safe protected by a password. The password is a sequence of `n` digits where each digit can be in the range `[0, k - 1]`.

The safe has a peculiar way of checking the password. When you enter in a sequence, it checks the **most recent `n` digits** that were entered each time you type a digit.

- For example, the correct password is "345" and you enter in "012345":
 - After typing 0, the most recent 3 digits is "0", which is incorrect.
 - After typing 1, the most recent 3 digits is "01", which is incorrect.
 - After typing 2, the most recent 3 digits is "012", which is incorrect.
 - After typing 3, the most recent 3 digits is "123", which is incorrect.
 - After typing 4, the most recent 3 digits is "234", which is incorrect.
 - After typing 5, the most recent 3 digits is "345", which is correct and the safe unlocks.

Return *any string of **minimum length** that will unlock the safe **at some point** of entering it.*

Example 1:

Input: `n = 1, k = 2`

Output: "10"

Explanation: The password is a single digit, so enter each digit. "01" would also unlock the safe.

Example 2:

Input: `n = 2, k = 2`

Output: "01100"

Explanation: For each possible password:

- "00" is typed in starting from the 4th digit.
- "01" is typed in starting from the 1st digit.
- "10" is typed in starting from the 3rd digit.

- "11" is typed in starting from the 2nd digit.

Thus "01100" will unlock the safe. "01100", "10011", and "11001" would also unlock the safe.

Constraints:

- $1 \leq n \leq 4$
- $1 \leq k \leq 10$
- $1 \leq k^n \leq 4096$

754. Reach a Number

Medium

1341694Add to ListShare

You are standing at position `0` on an infinite number line. There is a destination at position `target`.

You can make some number of moves `numMoves` so that:

- On each move, you can either go left or right.
- During the i^{th} move (starting from $i = 1$ to $i = \text{numMoves}$), you take i steps in the chosen direction.

Given the integer `target`, return the **minimum** number of moves required (i.e., the minimum `numMoves`) to reach the destination.

Example 1:

Input: `target = 2`

Output: `3`

Explanation:

On the 1st move, we step from 0 to 1 (1 step).

On the 2nd move, we step from 1 to -1 (2 steps).

On the 3rd move, we step from -1 to 2 (3 steps).

Example 2:

Input: `target = 3`

Output: `2`

Explanation:

On the 1st move, we step from 0 to 1 (1 step).

On the 2nd move, we step from 1 to 3 (2 steps).

Constraints:

- $-10^9 \leq \text{target} \leq 10^9$
- $\text{target} \neq 0$

756. Pyramid Transition Matrix

Medium

474447Add to ListShare

You are stacking blocks to form a pyramid. Each block has a color, which is represented by a single letter. Each row of blocks contains **one less block** than the row beneath it and is centered on top.


To make the pyramid aesthetically pleasing, there are only specific **triangular patterns** that are allowed. A triangular pattern consists of a **single block** stacked on top of **two blocks**. The patterns are given as a list of three-letter strings `allowed`, where the first two characters of a pattern represent the left and right bottom blocks respectively, and the third character is the top block.

- For example, "ABC" represents a triangular pattern with a 'C' block stacked on top of an 'A' (left) and 'B' (right) block. Note that this is different from "BAC" where 'B' is on the left bottom and 'A' is on the right bottom.

You start with a bottom row of blocks `bottom`, given as a single string, that you **must** use as the base of the pyramid.

Given `bottom` and `allowed`, return `true` if you can build the pyramid all the way to the top such that **every triangular pattern** in the pyramid is in `allowed`, or `false` otherwise.

Example 1:



Input: bottom = "BCD", allowed = ["BCC", "CDE", "CEA", "FFF"]


Output: true

Explanation: The allowed triangular patterns are shown on the right.

Starting from the bottom (level 3), we can build "CE" on level 2 and then build "A" on level 1.

There are three triangular patterns in the pyramid, which are "BCC", "CDE", and "CEA". All are allowed.

Example 2:



Input: bottom = "AAAA", allowed = ["AAB", "AAC", "BCD", "BBE", "DEF"]

Output: false

Explanation: The allowed triangular patterns are shown on the right.

Starting from the bottom (level 4), there are multiple ways to build level 3, but trying all the possibilities, you will get always stuck before building level 1.

Constraints:

- $2 \leq \text{bottom.length} \leq 6$
- $0 \leq \text{allowed.length} \leq 216$
- $\text{allowed}[i].length == 3$
- The letters in all input strings are from the set `{'A', 'B', 'C', 'D', 'E', 'F'}`.
- All the values of `allowed` are **unique**.

757. Set Intersection Size At Least Two

Hard

52064Add to ListShare

You are given a 2D integer array `intervals` where `intervals[i] = [starti, endi]` represents all the integers from `starti` to `endi` inclusively.

A **containing set** is an array `nums` where each interval from `intervals` has **at least two** integers in `nums`.

- For example, if `intervals = [[1,3], [3,7], [8,9]]`, then `[1,2,4,7,8,9]` and `[2,3,4,8,9]` are **containing sets**.

Return *the minimum possible size of a containing set*.

Example 1:

Input: `intervals = [[1,3],[3,7],[8,9]]`

Output: 5

Explanation: let `nums = [2, 3, 4, 8, 9]`.

It can be shown that there cannot be any containing array of size 4.

Example 2:

Input: `intervals = [[1,3],[1,4],[2,5],[3,5]]`

Output: 3

Explanation: let `nums` = [2, 3, 4].

It can be shown that there cannot be any containing array of size 2.

Example 3:

Input: `intervals` = [[1,2],[2,3],[2,4],[4,5]]

Output: 5

Explanation: let `nums` = [1, 2, 3, 4, 5].

It can be shown that there cannot be any containing array of size 4.

Constraints:

- $1 \leq \text{intervals.length} \leq 3000$
- $\text{intervals}[i].length == 2$
- $0 \leq \text{start}_i < \text{end}_i \leq 10^8$

761. Special Binary String

Hard

588183Add to ListShare

Special binary strings are binary strings with the following two properties:

- The number of 0's is equal to the number of 1's.
- Every prefix of the binary string has at least as many 1's as 0's.

You are given a **special binary** string `s`.

A move consists of choosing two consecutive, non-empty, special substrings of `s`, and swapping them. Two strings are consecutive if the last character of the first string is exactly one index before the first character of the second string.

Return the lexicographically largest resulting string possible after applying the mentioned operations on the string.

Example 1:

Input: `s` = "11011000"

Output: "11100100"

Explanation: The strings "10" [occurring at `s[1]`] and "1100" [at `s[3]`] are swapped.

This is the lexicographically largest string possible after some number of swaps.

Example 2:

Input: `s = "10"`

Output: `"10"`

Constraints:

- `1 <= s.length <= 50`
- `s[i]` is either `'0'` or `'1'`.
- `s` is a special binary string.

762. Prime Number of Set Bits in Binary Representation

Easy

532480Add to ListShare

Given two integers `left` and `right`, return the **count** of numbers in the **inclusive** range `[left, right]` having a **prime number of set bits** in their binary representation.

Recall that the **number of set bits** an integer has is the number of `1`'s present when written in binary.

- For example, `21` written in binary is `10101`, which has `3` set bits.

Example 1:

Input: `left = 6, right = 10`

Output: `4`

Explanation:

```

6  -> 110 (2 set bits, 2 is prime)
7  -> 111 (3 set bits, 3 is prime)
8  -> 1000 (1 set bit, 1 is not prime)
9  -> 1001 (2 set bits, 2 is prime)
10 -> 1010 (2 set bits, 2 is prime)
4 numbers have a prime number of set bits.

```

Example 2:**Input:** left = 10, right = 15**Output:** 5**Explanation:**

10 -> 1010 (2 set bits, 2 is prime)

11 -> 1011 (3 set bits, 3 is prime)

12 -> 1100 (2 set bits, 2 is prime)

13 -> 1101 (3 set bits, 3 is prime)

14 -> 1110 (3 set bits, 3 is prime)

15 -> 1111 (4 set bits, 4 is not prime)

5 numbers have a prime number of set bits.

Constraints:

- $1 \leq \text{left} \leq \text{right} \leq 10^6$
- $0 \leq \text{right} - \text{left} \leq 10^4$

763. Partition Labels**Medium**

8563325Add to ListShare

You are given a string `s`. We want to partition the string into as many parts as possible so that each letter appears in at most one part.

Note that the partition is done so that after concatenating all the parts in order, the resultant string should be `s`.

Return a list of integers representing the size of these parts.

Example 1:**Input:** s = "ababcacadebegdehijklj"**Output:** [9,7,8]**Explanation:**

The partition is "ababcba", "defegde", "hijhklj".

This is a partition so that each letter appears in at most one part.

A partition like "ababcba" and "defegde", "hijhklj" is incorrect, because it splits s into less parts.

Example 2:

Input: s = "eccbbbdec"

Output: [10]

Constraints:

- $1 \leq s.length \leq 500$
- s consists of lowercase English letters.

764. Largest Plus Sign

Medium

1224201Add to ListShare

You are given an integer n. You have an $n \times n$ binary grid grid with all values initially 1's except for some indices given in the array mines. The i^{th} element of the array mines is defined as $\text{mines}[i] = [x_i, y_i]$ where $\text{grid}[x_i][y_i] == 0$.

Return the order of the largest **axis-aligned plus sign** of 1's contained in grid. If there is none, return 0.

An **axis-aligned plus sign** of 1's of order k has some center $\text{grid}[r][c] == 1$ along with four arms of length $k - 1$ going up, down, left, and right, and made of 1's. Note that there could be 0's or 1's beyond the arms of the plus sign, only the relevant area of the plus sign is checked for 1's.

Example 1:

1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	0	1	1

Input: n = 5, mines = [[4,2]]

Output: 2

Explanation: In the above grid, the largest plus sign can only be of order 2. One of them is shown.

Example 2:

0

Input: n = 1, mines = [[0,0]]

Output: 0

Explanation: There is no plus sign, so return 0.

Constraints:

- $1 \leq n \leq 500$
- $1 \leq \text{mines.length} \leq 5000$
- $0 \leq x_i, y_i < n$

- All the pairs (x_i, y_i) are **unique**.

765. Couples Holding Hands

Hard

186994Add to ListShare

There are n couples sitting in $2n$ seats arranged in a row and want to hold hands.

The people and seats are represented by an integer array `row` where `row[i]` is the ID of the person sitting in the i^{th} seat. The couples are numbered in order, the first couple being $(0, 1)$, the second couple being $(2, 3)$, and so on with the last couple being $(2n - 2, 2n - 1)$.

Return *the minimum number of swaps so that every couple is sitting side by side*. A swap consists of choosing any two people, then they stand up and switch seats.

Example 1:

Input: `row = [0,2,1,3]`

Output: `1`

Explanation: We only need to swap the second (`row[1]`) and third (`row[2]`) person.

Example 2:

Input: `row = [3,2,0,1]`

Output: `0`

Explanation: All couples are already seated side by side.

Constraints:

- $2n == \text{row.length}$
- $2 \leq n \leq 30$
- n is even.
- $0 \leq \text{row}[i] < 2n$
- All the elements of `row` are **unique**.

766. Toeplitz Matrix

Easy

2132127Add to ListShare

Given an $m \times n$ matrix, return `true` if the matrix is Toeplitz. Otherwise, return `false`.

A matrix is **Toeplitz** if every diagonal from top-left to bottom-right has the same elements.

Example 1:

1	2	3	4
5	1	2	3
9	5	1	2

Input: matrix = [[1,2,3,4],[5,1,2,3],[9,5,1,2]]

Output: true

Explanation:

In the above grid, the diagonals are:

"[9]", "[5, 5]", "[1, 1, 1]", "[2, 2, 2]", "[3, 3]", "[4]".

In each diagonal all elements are the same, so the answer is True.

Example 2:

1	2
2	2

Input: matrix = [[1,2],[2,2]]

Output: false

Explanation:

The diagonal "[1, 2]" has different elements.

Constraints:

- `m == matrix.length`
- `n == matrix[i].length`
- `1 <= m, n <= 20`
- `0 <= matrix[i][j] <= 99`

768. Max Chunks To Make Sorted II**Hard**

144441Add to ListShare

You are given an integer array `arr`.

We split `arr` into some number of **chunks** (i.e., partitions), and individually sort each chunk. After concatenating them, the result should equal the sorted array.

Return *the largest number of chunks we can make to sort the array*.

Example 1:**Input:** `arr = [5,4,3,2,1]`**Output:** 1**Explanation:**

Splitting into two or more chunks will not return the required result.

For example, splitting into `[5, 4], [3, 2, 1]` will result in `[4, 5, 1, 2, 3]`, which isn't sorted.

Example 2:**Input:** `arr = [2,1,3,4,4]`**Output:** 4**Explanation:**

We can split into two chunks, such as `[2, 1], [3, 4, 4]`.

However, splitting into `[2, 1], [3], [4], [4]` is the highest number of chunks possible.

Constraints:

- $1 \leq \text{arr.length} \leq 2000$
- $0 \leq \text{arr}[i] \leq 10^8$

769. Max Chunks To Make Sorted**Medium**

2218202Add to ListShare

You are given an integer array `arr` of length `n` that represents a permutation of the integers in the range `[0, n - 1]`.

We split `arr` into some number of **chunks** (i.e., partitions), and individually sort each chunk. After concatenating them, the result should equal the sorted array.

Return *the largest number of chunks we can make to sort the array*.

Example 1:

Input: arr = [4,3,2,1,0]

Output: 1

Explanation:

Splitting into two or more chunks will not return the required result.

For example, splitting into [4, 3], [2, 1, 0] will result in [3, 4, 0, 1, 2], which isn't sorted.

Example 2:

Input: arr = [1,0,2,3,4]

Output: 4

Explanation:

We can split into two chunks, such as [1, 0], [2, 3, 4].

However, splitting into [1, 0], [2], [3], [4] is the highest number of chunks possible.

Constraints:

- $n == \text{arr.length}$
- $1 \leq n \leq 10$

- $0 \leq arr[i] < n$
- All the elements of `arr` are **unique**.

770. Basic Calculator IV

Hard

1271268Add to ListShare

Given an expression such as `expression = "e + 8 - a + 5"` and an evaluation map such as `{"e": 1}` (given in terms of `evalvars = ["e"]` and `evalints = [1]`), return a list of tokens representing the simplified expression, such as `["-1*a", "14"]`

- An expression alternates chunks and symbols, with a space separating each chunk and symbol.
- A chunk is either an expression in parentheses, a variable, or a non-negative integer.
- A variable is a string of lowercase letters (not including digits.) Note that variables can be multiple letters, and note that variables never have a leading coefficient or unary operator like `"2x"` or `"-x"`.

Expressions are evaluated in the usual order: brackets first, then multiplication, then addition and subtraction.

- For example, `expression = "1 + 2 * 3"` has an answer of `["7"]`.

The format of the output is as follows:

- For each term of free variables with a non-zero coefficient, we write the free variables within a term in sorted order lexicographically.
 - For example, we would never write a term like `"b*a*c"`, only `"a*b*c"`.
- Terms have degrees equal to the number of free variables being multiplied, counting multiplicity. We write the largest degree terms of our answer first, breaking ties by lexicographic order ignoring the leading coefficient of the term.
 - For example, `"a*a*b*c"` has degree 4.
- The leading coefficient of the term is placed directly to the left with an asterisk separating it from the variables (if they exist.) A leading coefficient of 1 is still printed.
- An example of a well-formatted answer is `["-2*a*a*a", "3*a*a*b", "3*b*b", "4*a", "5*c", "-6"]`.
- Terms (including constant terms) with coefficient 0 are not included.
 - For example, an expression of `"0"` has an output of `[]`.

Note: You may assume that the given expression is always valid. All intermediate results will be in the range of `[-231, 231 - 1]`.

Example 1:

Input: expression = "e + 8 - a + 5", evalvars = ["e"], evalints = [1]

Output: ["-1*a", "14"]

Example 2:

Input: expression = "e - 8 + temperature - pressure", evalvars = ["e", "temperature"], evalints = [1, 12]

Output: ["-1*pressure", "5"]

Example 3:

Input: expression = "(e + 8) * (e - 8)", evalvars = [], evalints = []

Output: ["1*e*e", "-64"]

Constraints:

- $1 \leq \text{expression.length} \leq 250$
- `expression` consists of lowercase English letters, digits, '+', '-', '*', '(', ')', ' '.
- `expression` does not contain any leading or trailing spaces.
- All the tokens in `expression` are separated by a single space.
- $0 \leq \text{evalvars.length} \leq 100$
- $1 \leq \text{evalvars}[i].length \leq 20$
- `evalvars[i]` consists of lowercase English letters.
- `evalints.length == evalvars.length`
- $-100 \leq \text{evalints}[i] \leq 100$

771. Jewels and Stones

Easy

3948507Add to ListShare

You're given strings `jewels` representing the types of stones that are jewels, and `stones` representing the stones you have. Each character in `stones` is a type of stone you have. You want to know how many of the stones you have are also jewels.

Letters are case sensitive, so "a" is considered a different type of stone from "A".

Example 1:

Input: jewels = "aA", stones = "aAAbbbb"

Output: 3

Example 2:

Input: jewels = "z", stones = "ZZ"

Output: 0

Constraints:

- `1 <= jewels.length, stones.length <= 50`
- `jewels` and `stones` consist of only English letters.
- All the characters of `jewels` are **unique**.

773. Sliding Puzzle

Hard

168044Add to ListShare

On an 2×3 board, there are five tiles labeled from 1 to 5, and an empty square represented by 0. A **move** consists of choosing 0 and a 4-directionally adjacent number and swapping it.

The state of the board is solved if and only if the board is `[[1,2,3], [4,5,0]]`.

Given the puzzle board `board`, return *the least number of moves required so that the state of the board is solved*. If it is impossible for the state of the board to be solved, return `-1`.

Example 1:

1	2	3
4		5

Input: board = `[[1,2,3], [4,0,5]]`

Output: 1

Explanation: Swap the 0 and the 5 in one move.

Example 2:

1	2	3
5	4	

Input: board = [[1,2,3],[5,4,0]]

Output: -1

Explanation: No number of moves will make the board solved.

Example 3:

4	1	2
5		3

Input: board = [[4,1,2],[5,0,3]]

Output: 5

Explanation: 5 is the smallest number of moves that solves the board.

An example path:

After move 0: [[4,1,2],[5,0,3]]

After move 1: [[4,1,2],[0,5,3]]

After move 2: [[0,1,2],[4,5,3]]

After move 3: [[1,0,2],[4,5,3]]

After move 4: [[1,2,0],[4,5,3]]

After move 5: [[1,2,3],[4,5,0]]

Constraints:

- `board.length == 2`
- `board[i].length == 3`
- `0 <= board[i][j] <= 5`
- Each value `board[i][j]` is **unique**.

775. Global and Local Inversions

Medium

1418330Add to ListShare

You are given an integer array `nums` of length `n` which represents a permutation of all the integers in the range `[0, n - 1]`.

The number of **global inversions** is the number of the different pairs `(i, j)` where:

- `0 <= i < j < n`
- `nums[i] > nums[j]`

The number of **local inversions** is the number of indices `i` where:

- `0 <= i < n - 1`
- `nums[i] > nums[i + 1]`

Return `true` if the number of **global inversions** is equal to the number of **local inversions**.

Example 1:

Input: `nums = [1,0,2]`

Output: `true`

Explanation: There is 1 global inversion and 1 local inversion.

Example 2:

Input: `nums = [1,2,0]`

Output: `false`

Explanation: There are 2 global inversions and 1 local inversion.

Constraints:

- `n == nums.length`
- `1 <= n <= 10^5`
- `0 <= nums[i] < n`

- All the integers of `nums` are **unique**.
- `nums` is a permutation of all the numbers in the range `[0, n - 1]`.

777. Swap Adjacent in LR String

Medium

982801Add to ListShare

In a string composed of '`L`', '`R`', and '`X`' characters, like "`RXXLXRXL`", a move consists of either replacing one occurrence of "`XL`" with "`LX`", or replacing one occurrence of "`RX`" with "`XR`". Given the starting string `start` and the ending string `end`, return `True` if and only if there exists a sequence of moves to transform one string to the other.

Example 1:

Input: `start` = "`RXXLXRXL`", `end` = "`XRLXXRRLX`"

Output: `true`

Explanation: We can transform `start` to `end` following these steps:

`RXXLXRXL` ->

`XRXLXRXL` ->

`XRLXRXRL` ->

`XRLXXRXL` ->

`XRLXXRRLX`

Example 2:

Input: `start` = "`X`", `end` = "`L`"

Output: `false`

Constraints:

- $1 \leq \text{start.length} \leq 10^4$
- `start.length == end.length`
- Both `start` and `end` will only consist of characters in '`L`', '`R`', and '`X`'.

778. Swim in Rising Water

Hard

2518167Add to ListShare

You are given an $n \times n$ integer matrix `grid` where each value `grid[i][j]` represents the elevation at that point (i, j) .

The rain starts to fall. At time t , the depth of the water everywhere is t . You can swim from a square to another 4-directionally adjacent square if and only if the elevation of both squares individually are at most t . You can swim infinite distances in zero time. Of course, you must stay within the boundaries of the grid during your swim.

Return *the least time until you can reach the bottom right square $(n - 1, n - 1)$ if you start at the top left square $(0, 0)$* .

Example 1:

0	2
1	3

Input: `grid = [[0,2],[1,3]]`

Output: 3

Explanation:

At time 0, you are in grid location $(0, 0)$.

You cannot go anywhere else because 4-directionally adjacent neighbors have a higher elevation than $t = 0$.

You cannot reach point $(1, 1)$ until time 3.

When the depth of water is 3, we can swim anywhere inside the grid.

Example 2:

0	1	2	3	4
24	23	22	21	5
12	13	14	15	16
11	17	18	19	20
10	9	8	7	6

Input: grid =
`[[0,1,2,3,4],[24,23,22,21,5],[12,13,14,15,16],[11,17,18,19,20],[10,9,8,7,6]]`

Output: 16

Explanation: The final route is shown.

We need to wait until time 16 so that (0, 0) and (4, 4) are connected.

Constraints:

- `n == grid.length`
- `n == grid[i].length`
- `1 <= n <= 50`
- `0 <= grid[i][j] < n2`
- Each value `grid[i][j]` is **unique**.

779. K-th Symbol in Grammar

Medium

2131264Add to ListShare

We build a table of `n` rows (**1-indexed**). We start by writing `0` in the `1st` row. Now in every subsequent row, we look at the previous row and replace each occurrence of `0` with `01`, and each occurrence of `1` with `10`.

- For example, for $n = 3$, the 1st row is 0, the 2nd row is 01, and the 3rd row is 0110.

Given two integer n and k , return the k^{th} (1-indexed) symbol in the n^{th} row of a table of n rows.

Example 1:

Input: $n = 1, k = 1$

Output: 0

Explanation: row 1: 0

Example 2:

Input: $n = 2, k = 1$

Output: 0

Explanation:

row 1: 0

row 2: 01

Example 3:

Input: $n = 2, k = 2$

Output: 1

Explanation:

row 1: 0

row 2: 01

Constraints:

- $1 \leq n \leq 30$
- $1 \leq k \leq 2^{n-1}$

780. Reaching Points

Hard

1111187Add to ListShare

Given four integers s_x , s_y , t_x , and t_y , return `true` if it is possible to convert the point (s_x, s_y) to the point (t_x, t_y) through some operations, or `false` otherwise.

The allowed operation on some point (x, y) is to convert it to either $(x, x + y)$ or $(x + y, y)$.

Example 1:

Input: $s_x = 1, s_y = 1, t_x = 3, t_y = 5$

Output: true

Explanation:

One series of moves that transforms the starting point to the target is:

$(1, 1) \rightarrow (1, 2)$

$(1, 2) \rightarrow (3, 2)$

$(3, 2) \rightarrow (3, 5)$

Example 2:

Input: $s_x = 1, s_y = 1, t_x = 2, t_y = 2$

Output: false

Example 3:

Input: $s_x = 1, s_y = 1, t_x = 1, t_y = 1$

Output: true

Constraints:

- $1 \leq s_x, s_y, t_x, t_y \leq 10^9$

781. Rabbits in Forest

Medium

878516 Add to List Share

There is a forest with an unknown number of rabbits. We asked n rabbits "How many rabbits have the same color as you?" and collected the answers in an integer array `answers` where `answers[i]` is the answer of the i^{th} rabbit.

Given the array `answers`, return the minimum number of rabbits that could be in the forest.

Example 1:

Input: answers = [1,1,2]

Output: 5

Explanation:

The two rabbits that answered "1" could both be the same color, say red.

The rabbit that answered "2" can't be red or the answers would be inconsistent.

Say the rabbit that answered "2" was blue.

Then there should be 2 other blue rabbits in the forest that didn't answer into the array.

The smallest possible number of rabbits in the forest is therefore 5: 3 that answered plus 2 that didn't.

Example 2:

Input: answers = [10,10,10]

Output: 11

Constraints:

- `1 <= answers.length <= 1000`
- `0 <= answers[i] < 1000`

782. Transform to Chessboard

Hard

309286Add to ListShare

You are given an `n x n` binary grid `board`. In each move, you can swap any two rows with each other, or any two columns with each other.

Return the minimum number of moves to transform the board into a **chessboard board**. If the task is impossible, return `-1`.

A **chessboard board** is a board where no `0`'s and no `1`'s are 4-directionally adjacent.

Example 1:

0	1	1	0
0	1	1	0
1	0	0	1
1	0	0	1

1	0	1	0
1	0	1	0
0	1	0	1
0	1	0	1

1	0	1	0
0	1	0	1
1	0	1	0
0	1	0	1

Input: board = [[0,1,1,0],[0,1,1,0],[1,0,0,1],[1,0,0,1]]

Output: 2

Explanation: One potential sequence of moves is shown.

The first move swaps the first and second column.

The second move swaps the second and third row.

Example 2:

0	1
1	0

Input: board = [[0,1],[1,0]]

Output: 0

Explanation: Also note that the board with 0 in the top left corner, is also a valid chessboard.

Example 3:

1	0
1	0

Input: board = [[1,0],[1,0]]

Output: -1

Explanation: No matter what sequence of moves you make, you cannot end with a valid chessboard.

Constraints:

- `n == board.length`
- `n == board[i].length`
- $2 \leq n \leq 30$
- `board[i][j]` is either 0 or 1.


783. Minimum Distance Between BST Nodes

Easy

1866333 Add to List Share

Given the `root` of a Binary Search Tree (BST), return *the minimum difference between the values of any two different nodes in the tree*.


Example 1:



Input: `root = [4,2,6,1,3]`

Output: 1

Example 2:



Input: root = [1,0,48,null,null,12,49]

Output: 1

Constraints:

- The number of nodes in the tree is in the range [2, 100].
- $0 \leq \text{Node.val} \leq 10^5$

784. Letter Case Permutation

Medium

3793150Add to ListShare

Given a string s , you can transform every letter individually to be lowercase or uppercase to create another string.

Return a *list of all possible strings we could create*. Return the output in **any order**.

Example 1:

Input: s = "a1b2"

Output: ["a1b2", "a1B2", "A1b2", "A1B2"]

Example 2:

Input: s = "3z4"

Output: ["3z4", "3Z4"]

Constraints:

- $1 \leq s.length \leq 12$
- s consists of lowercase English letters, uppercase English letters, and digits.

785. Is Graph Bipartite?

Medium

5573291 Add to List Share


There is an **undirected** graph with n nodes, where each node is numbered between 0 and $n - 1$. You are given a 2D array graph , where $\text{graph}[u]$ is an array of nodes that node u is adjacent to. More formally, for each v in $\text{graph}[u]$, there is an undirected edge between node u and node v . The graph has the following properties:

- There are no self-edges ($\text{graph}[u]$ does not contain u).
- There are no parallel edges ($\text{graph}[u]$ does not contain duplicate values).
- If v is in $\text{graph}[u]$, then u is in $\text{graph}[v]$ (the graph is undirected).
- The graph may not be connected, meaning there may be two nodes u and v such that there is no path between them.

A graph is **bipartite** if the nodes can be partitioned into two independent sets A and B such that **every** edge in the graph connects a node in set A and a node in set B .

Return `true` if and only if it is **bipartite**.

Example 1:




Input: `graph = [[1,2,3],[0,2],[0,1,3],[0,2]]`

Output: false

Explanation: There is no way to partition the nodes into two independent sets such that every edge connects a node in one and a node in the other.

Example 2:



Input: graph = [[1,3],[0,2],[1,3],[0,2]]

Output: true

Explanation: We can partition the nodes into two sets: {0, 2} and {1, 3}.

Constraints:

- `graph.length == n`
- `1 <= n <= 100`
- `0 <= graph[u].length < n`
- `0 <= graph[u][i] <= n - 1`
- `graph[u]` does not contain `u`.
- All the values of `graph[u]` are **unique**.
- If `graph[u]` contains `v`, then `graph[v]` contains `u`.

786. K-th Smallest Prime Fraction

Medium

89843Add to ListShare

You are given a sorted integer array `arr` containing 1 and **prime** numbers, where all the integers of `arr` are unique. You are also given an integer `k`.

For every `i` and `j` where `0 <= i < j < arr.length`, we consider the fraction `arr[i] / arr[j]`.

Return the `kth` smallest fraction considered. Return your answer as an array of integers of size 2, where `answer[0] == arr[i]` and `answer[1] == arr[j]`.

Example 1:**Input:** arr = [1,2,3,5], k = 3**Output:** [2,5]**Explanation:** The fractions to be considered in sorted order are:

1/5, 1/3, 2/5, 1/2, 3/5, and 2/3.

The third fraction is 2/5.

Example 2:**Input:** arr = [1,7], k = 1**Output:** [1,7]**Constraints:**

- $2 \leq \text{arr.length} \leq 1000$
- $1 \leq \text{arr}[i] \leq 3 \times 10^4$
- $\text{arr}[0] == 1$
- $\text{arr}[i]$ is a **prime** number for $i > 0$.
- All the numbers of `arr` are **unique** and sorted in **strictly increasing** order.
- $1 \leq k \leq \text{arr.length} * (\text{arr.length} - 1) / 2$


787. Cheapest Flights Within K Stops**Medium**

5885269Add to ListShare

There are n cities connected by some number of flights. You are given an array `flights` where $\text{flights}[i] = [\text{from}_i, \text{to}_i, \text{price}_i]$ indicates that there is a flight from city from_i to city to_i with cost price_i .

You are also given three integers src , dst , and k , return **the cheapest price** from src to dst with at most k stops. If there is no such route, return -1 .

Example 1:



Input: $n = 4$, $\text{flights} = [[0,1,100],[1,2,100],[2,0,100],[1,3,600],[2,3,200]]$, $\text{src} = 0$, $\text{dst} = 3$, $k = 1$

Output: 700


Explanation:

The graph is shown above.

The optimal path with at most 1 stop from city 0 to 3 is marked in red and has cost $100 + 600 = 700$.

Note that the path through cities $[0,1,2,3]$ is cheaper but is invalid because it uses 2 stops.

Example 2:



Input: $n = 3$, $\text{flights} = [[0,1,100],[1,2,100],[0,2,500]]$, $\text{src} = 0$, $\text{dst} = 2$, $k = 1$


Output: 200

Explanation:

The graph is shown above.

The optimal path with at most 1 stop from city 0 to 2 is marked in red and has cost $100 + 100 = 200$.

Example 3:



Input: $n = 3$, $\text{flights} = [[0,1,100],[1,2,100],[0,2,500]]$, $\text{src} = 0$, $\text{dst} = 2$, $k = 0$

Output: 500

Explanation:

The graph is shown above.

The optimal path with no stops from city 0 to 2 is marked in red and has cost 500.

Constraints:

- $1 \leq n \leq 100$
- $0 \leq \text{flights.length} \leq (n * (n - 1) / 2)$
- $\text{flights}[i].length == 3$
- $0 \leq \text{from}_i, \text{to}_i < n$
- $\text{from}_i \neq \text{to}_i$
- $1 \leq \text{price}_i \leq 10^4$
- There will not be any multiple flights between two cities.
- $0 \leq \text{src}, \text{dst}, k < n$
- $\text{src} \neq \text{dst}$

788. Rotated Digits**Medium**

6191794Add to ListShare

An integer x is a **good** if after rotating each digit individually by 180 degrees, we get a valid number that is different from x . Each digit must be rotated - we cannot choose to leave it alone.

A number is valid if each digit remains a digit after rotation. For example:

- 0, 1, and 8 rotate to themselves,
- 2 and 5 rotate to each other (in this case they are rotated in a different direction, in other words, 2 or 5 gets mirrored),
- 6 and 9 rotate to each other, and
- the rest of the numbers do not rotate to any other number and become invalid.

Given an integer n , return *the number of good integers in the range [1, n]*.

Example 1:**Input:** $n = 10$ **Output:** 4

Explanation: There are four good numbers in the range $[1, 10] : 2, 5, 6, 9$.

Note that 1 and 10 are not good numbers, since they remain unchanged after rotating.

Example 2:**Input:** $n = 1$ **Output:** 0

Example 3:**Input:** n = 2**Output:** 1**Constraints:**

- $1 \leq n \leq 10^4$

789. Escape The Ghosts**Medium**

15619Add to ListShare

You are playing a simplified PAC-MAN game on an infinite 2-D grid. You start at the point `[0, 0]`, and you are given a destination point `target = [xtarget, ytarget]` that you are trying to get to. There are several ghosts on the map with their starting positions given as a 2D array `ghosts`, where `ghosts[i] = [xi, yi]` represents the starting position of the i^{th} ghost. All inputs are **integral coordinates**.

Each turn, you and all the ghosts may independently choose to either **move 1 unit** in any of the four cardinal directions: north, east, south, or west, or **stay still**. All actions happen **simultaneously**.

You escape if and only if you can reach the target **before** any ghost reaches you. If you reach any square (including the target) at the **same time** as a ghost, it **does not** count as an escape.

Return `true` if it is possible to escape regardless of how the ghosts move, otherwise return `false`.

Example 1:**Input:** ghosts = `[[1,0],[0,3]]`, target = `[0,1]`**Output:** `true`

Explanation: You can reach the destination `(0, 1)` after 1 turn, while the ghosts located at `(1, 0)` and `(0, 3)` cannot catch up with you.

Example 2:**Input:** ghosts = `[[1,0]]`, target = `[2,0]`**Output:** `false`

Explanation: You need to reach the destination `(2, 0)`, but the ghost at `(1, 0)` lies between you and the destination.

Example 3:

Input: ghosts = [[2,0]], target = [1,0]

Output: false

Explanation: The ghost can reach the target at the same time as you.

Constraints:


- $1 \leq \text{ghosts.length} \leq 100$
- $\text{ghosts}[i].length == 2$
- $-10^4 \leq x_i, y_i \leq 10^4$
- There can be **multiple ghosts** in the same location.
- $\text{target.length} == 2$
- $-10^4 \leq x_{\text{target}}, y_{\text{target}} \leq 10^4$

790. Domino and Tromino Tiling


Medium

1733625Add to ListShare

You have two types of tiles: a 2×1 domino shape and a tromino shape. You may rotate these shapes.



Domino tile




Tromino tile

Given an integer n , return *the number of ways to tile an $2 \times n$ board*. Since the answer may be very large, return it **modulo $10^9 + 7$** .

In a tiling, every square must be covered by a tile. Two tilings are different if and only if there are two 4-directionally adjacent cells on the board such that exactly one of the tilings has both squares occupied by a tile.

Example 1:



Input: $n = 3$

Output: 5

Explanation: The five different ways are show above.

Example 2:

Input: $n = 1$

Output: 1

Constraints:

- $1 \leq n \leq 1000$

791. Custom Sort String

Medium

2246300 Add to List Share

You are given two strings `order` and `s`. All the characters of `order` are **unique** and were sorted in some custom order previously.

Permute the characters of `s` so that they match the order that `order` was sorted. More specifically, if a character `x` occurs before a character `y` in `order`, then `x` should occur before `y` in the permuted string.

Return *any permutation of s that satisfies this property*.

Example 1:**Input:** order = "cba", s = "abcd"**Output:** "cbad"**Explanation:**

"a", "b", "c" appear in order, so the order of "a", "b", "c" should be "c", "b", and "a".

Since "d" does not appear in order, it can be at any position in the returned string. "dcba", "cdba", "cbda" are also valid outputs.

Example 2:**Input:** order = "cbafg", s = "abcd"**Output:** "cbad"**Constraints:**

- `1 <= order.length <= 26`
- `1 <= s.length <= 200`
- `order` and `s` consist of lowercase English letters.
- All the characters of `order` are **unique**.

792. Number of Matching Subsequences**Medium**

4706192Add to ListShare

Given a string `s` and an array of strings `words`, return *the number of* `words[i]` *that is a subsequence of* `s`.

A **subsequence** of a string is a new string generated from the original string with some characters (can be none) deleted without changing the relative order of the remaining characters.

- For example, "ace" is a subsequence of "abcde".

Example 1:**Input:** s = "abcde", words = ["a", "bb", "acd", "ace"]**Output:** 3

Explanation: There are three strings in words that are a subsequence of s: "a", "acd", "ace".

Example 2:

Input: s = "dsahjpjauf", words = ["ahjpjau", "ja", "ahbwzgqnu", "tnmlanowax"]

Output: 2

Constraints:

- $1 \leq s.length \leq 5 * 10^4$
- $1 \leq \text{words.length} \leq 5000$
- $1 \leq \text{words}[i].length \leq 50$
- s and words[i] consist of only lowercase English letters.

793. Preimage Size of Factorial Zeroes Function

Hard

34179Add to ListShare

Let $f(x)$ be the number of zeroes at the end of $x!$. Recall that $x! = 1 * 2 * 3 * \dots * x$ and by convention, $0! = 1$.

- For example, $f(3) = 0$ because $3! = 6$ has no zeroes at the end, while $f(11) = 2$ because $11! = 39916800$ has two zeroes at the end.

Given an integer k , return the number of non-negative integers x have the property that $f(x) = k$.

Example 1:

Input: k = 0

Output: 5

Explanation: $0!, 1!, 2!, 3!,$ and $4!$ end with $k = 0$ zeroes.

Example 2:

Input: k = 5

Output: 0

Explanation: There is no x such that $x!$ ends in $k = 5$ zeroes.

Example 3:

Input: k = 3

Output: 5

Constraints:

- $0 \leq k \leq 10^9$

794. Valid Tic-Tac-Toe State

Medium

4531046Add to ListShare


Given a Tic-Tac-Toe board as a string array `board`, return `true` if and only if it is possible to reach this board position during the course of a valid tic-tac-toe game.

The board is a 3×3 array that consists of characters ' ', 'X', and 'O'. The ' ' character represents an empty square.

Here are the rules of Tic-Tac-Toe:

- Players take turns placing characters into empty squares ' '.
- The first player always places 'X' characters, while the second player always places 'O' characters.
- 'X' and 'O' characters are always placed into empty squares, never filled ones.
- The game ends when there are three of the same (non-empty) character filling any row, column, or diagonal.
- The game also ends if all squares are non-empty.
- No more moves can be played if the game is over.

Example 1:




Input: board = ["O ", " ", " "]

Output: false

Explanation: The first player always plays "X".

Example 2:



Input: board = ["XOX", " X ", " "]

Output: false

Explanation: Players take turns making moves.

Example 3:

X	O	X
O		O
X	O	X

Input: board = ["XOX", "O O", "XOX"]

Output: true

Constraints:

- board.length == 3
- board[i].length == 3
- board[i][j] is either 'X', 'O', or ' '.

795. Number of Subarrays with Bounded Maximum

Medium

183198Add to ListShare

Given an integer array `nums` and two integers `left` and `right`, return *the number of contiguous non-empty subarrays* such that *the value of the maximum array element in that subarray is in the range* `[left, right]`.

The test cases are generated so that the answer will fit in a **32-bit** integer.

Example 1:

Input: nums = [2,1,4,3], left = 2, right = 3

Output: 3

Explanation: There are three subarrays that meet the requirements: [2], [2, 1], [3].

Example 2:

Input: nums = [2,9,2,5,6], left = 2, right = 8

Output: 7

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $0 \leq \text{nums[i]} \leq 10^9$
- $0 \leq \text{left} \leq \text{right} \leq 10^9$

796. Rotate String

Easy

219894Add to ListShare

Given two strings `s` and `goal`, return `true` if and only if `s` can become `goal` after some number of **shifts** on `s`.

A **shift** on `s` consists of moving the leftmost character of `s` to the rightmost position.

- For example, if `s = "abcde"`, then it will be `"bcdea"` after one shift.

Example 1:

Input: `s = "abcde"`, `goal = "cdeab"`

Output: `true`

Example 2:

Input: `s = "abcde"`, `goal = "abced"`

Output: `false`

Constraints:

- $1 \leq \text{s.length, goal.length} \leq 100$
- `s` and `goal` consist of lowercase English letters.

797. All Paths From Source to Target


Medium

5013120Add to ListShare

Given a directed acyclic graph (**DAG**) of `n` nodes labeled from `0` to `n - 1`, find all possible paths from node `0` to node `n - 1` and return them in **any order**.

The graph is given as follows: `graph[i]` is a list of all nodes you can visit from node `i` (i.e., there is a directed edge from node `i` to node `graph[i][j]`).

Example 1:




Input: `graph = [[1,2],[3],[3],[]]`

Output: `[[0,1,3],[0,2,3]]`

Explanation: There are two paths: $0 \rightarrow 1 \rightarrow 3$ and $0 \rightarrow 2 \rightarrow 3$.

Example 2:



Input: `graph = [[4,3,1],[3,2,4],[3],[4],[]]`

Output: `[[0,4],[0,3,4],[0,1,3,4],[0,1,2,3,4],[0,1,4]]`

Constraints:

- `n == graph.length`
- `2 <= n <= 15`
- `0 <= graph[i][j] < n`
- `graph[i][j] != i` (i.e., there will be no self-loops).
- All the elements of `graph[i]` are **unique**.
- The input graph is **guaranteed** to be a **DAG**.

798. Smallest Rotation with Highest Score**Hard**

42532Add to ListShare

You are given an array `nums`. You can rotate it by a non-negative integer `k` so that the array becomes `[nums[k], nums[k + 1], ... nums[nums.length - 1], nums[0], nums[1], ..., nums[k-1]]`. Afterward, any entries that are less than or equal to their index are worth one point.

- For example, if we have `nums = [2, 4, 1, 3, 0]`, and we rotate by `k = 2`, it becomes `[1, 3, 0, 2, 4]`. This is worth 3 points because `1 > 0` [no points], `3 > 1` [no points], `0 <= 2` [one point], `2 <= 3` [one point], `4 <= 4` [one point].

Return *the rotation index `k` that corresponds to the highest score we can achieve if we rotated `nums` by it*. If there are multiple answers, return the smallest such index `k`.

Example 1:

Input: `nums = [2,3,1,4,0]`

Output: `3`

Explanation: Scores for each `k` are listed below:

<code>k = 0, nums = [2,3,1,4,0], score 2</code>
<code>k = 1, nums = [3,1,4,0,2], score 3</code>
<code>k = 2, nums = [1,4,0,2,3], score 3</code>
<code>k = 3, nums = [4,0,2,3,1], score 4</code>
<code>k = 4, nums = [0,2,3,1,4], score 3</code>

So we should choose `k = 3`, which has the highest score.

Example 2:

Input: `nums = [1,3,0,2,4]`

Output: `0`

Explanation: `nums` will always have 3 points no matter how it shifts.

So we will choose the smallest `k`, which is `0`.

Constraints:

- `1 <= nums.length <= 105`
- `0 <= nums[i] < nums.length`

799. Champagne Tower


Medium

2484137Add to ListShare

We stack glasses in a pyramid, where the **first** row has `1` glass, the **second** row has `2` glasses, and so on until the `100th` row. Each glass holds one cup of champagne.

Then, some champagne is poured into the first glass at the top. When the topmost glass is full, any excess liquid poured will fall equally to the glass immediately to the left and right of it. When those glasses become full, any excess champagne will fall equally to the left and right of those glasses, and so on. (A glass at the bottom row has its excess champagne fall on the floor.)

For example, after one cup of champagne is poured, the top most glass is full. After two cups of champagne are poured, the two glasses on the second row are half full. After three cups of champagne are poured, those two cups become full - there are 3 full glasses total now. After four cups of champagne are poured, the third row has the middle glass half full, and the two outside glasses are a quarter full, as pictured below.



Now after pouring some non-negative integer cups of champagne, return how full the j^{th} glass in the i^{th} row is (both i and j are 0-indexed.)

Example 1:

Input: poured = 1, query_row = 1, query_glass = 1

Output: 0.0000

Explanation: We poured 1 cup of champagne to the top glass of the tower (which is indexed as $(0, 0)$). There will be no excess liquid so all the glasses under the top glass will remain empty.

Example 2:

Input: poured = 2, query_row = 1, query_glass = 1

Output: 0.5000

Explanation: We poured 2 cups of champagne to the top glass of the tower (which is indexed as $(0, 0)$). There is one cup of excess liquid. The glass indexed as $(1, 0)$ and the glass indexed as $(1, 1)$ will share the excess liquid equally, and each will get half cup of champagne.

Example 3:

Input: poured = 100000009, query_row = 33, query_glass = 17

Output: 1.00000

Constraints:

- $0 \leq \text{poured} \leq 10^9$
- $0 \leq \text{query_glass} \leq \text{query_row} < 100$