

Hybrid Multi-Model Explainable Cyberbullying Detection System

Sahil Jagadale¹, Om Nikam², Siddhant Sonavane³, Swaranjali Lanjulkar⁴, and Sachin D. Shelke⁵

¹Student, SCTR's Pune Institute of Computer Technology, (IT), Pune, Maharashtra, India, jagadasahil@gmail.com

²Student, SCTR's Pune Institute of Computer Technology, (IT), Pune, Maharashtra, India, omniam0404@gmail.com

³Student, SCTR's Pune Institute of Computer Technology, (IT), Pune, Maharashtra, India, sonawane.sidr25@gmail.com

⁴Student, SCTR's Pune Institute of Computer Technology, (IT), Pune, Maharashtra, India, swaranjalilanjulkar2012@gmail.com

⁵Assistant Professor; SCTR's Pune Institute of Computer Technology, (IT), Pune, Maharashtra, India, sachindshelke@pict.edu

Abstract

The expansion of social network has transformed interaction, providing people with global connectivity, but it has also led to an alarming increase in cyberbullying. To report this, we present a new Explicable Cyber-bullying Detection System (ECDS) that utilizes DL models like DEA-RNN, LSTM, and Transformers to identify harmful content spread across multiple comments in online conversations. The system integrates sentiment analysis, emotion recognition, and pattern identification to improve the detection of context-driven cyberbullying behaviors. Moreover, it overcomes the challenge of recognizing disguised offensive terms (e.g., "I**ser") that traditional models often miss. A key feature of our approach is its explainable AI component, which provides transparency into decision-making processes, ensuring that moderators and policy makers can better understand why a comment or user was flagged. Our system outperforms existing models, accomplishing a precision of 89.48%, accuracy 90.40%, F1-score 89.22%, recall 88.96%, and specificity of 90.94%. Designed for scalability, high performance, and real-time operation, this system offers a significant step toward curbing cyberbullying across various online platforms.

Keywords: Cyberbullying Detection, Explainable AI, DEA-RNN, LSTM, Transformers, Sentiment Analysis, Abusive Language Detection, Deep Learning, NLP, Online Safety, Cloud-Based System.

1. Introduction

The rise of social media has brought about profound changes in communication, enabling people to connect globally. However, this growth has also led to the unfortunate rise of cyberbullying, a widespread concern that impacts people across multiple platforms. As the volume of online interactions grows, identifying and addressing instances of cyberbullying has become a crucial challenge for researchers and platform administrators alike [1], [2]. Despite the development of numerous automated systems designed to detect cyberbullying, many current solutions face several limitations.

Traditional approaches often struggle with processing real-time data and detecting sophisticated forms of abuse, such as the use of disguised language (e.g., "st***d" instead of "stupid") [3]. Additionally, while many systems successfully identify individual instances of cyberbullying, they fail to capture context across sequences of comments or conversations, missing the nuanced dynamics of online harassment [4], [5]. The lack of effective symbol or character-based abuse detection is another significant shortfall in most existing models [6].

Moreover, existing systems are frequently designed as "black boxes" that offer little to no explanation of how or why a specific comment or user was flagged [7]. This deficiency of clearness can demoralize faith in the system and limit its usefulness for moderators and end-users, who often require clear reasoning and context for taking action [8], [9]. As a output, there is an growing mandate for more explainable models that can provide detailed insights into

detected cases of cyberbullying, helping human moderators better understand the AI's decision-making process [10], [11].

This paper proposes a novel system for cyberbullying detection, building on and improving existing models by addressing the identified gaps. Our system, the Hybrid Explainable Cyberbullying Detection System (HMEDS), integrates deep learning models for sequence analysis, sentiment detection, and symbol-based abuse recognition [12]. By incorporating symbol recognition and explainability, the system aims to offer more robust and user-friendly detection of cyberbullying [13], [14].

2. Literature Survey

Over the past decade, the swift growth of social networks has caused in the proliferation of harmful online behaviors, notably cyberbullying. This phenomenon has spurred numerous studies aimed at leveraging NLP and ML techniques to detect and prevent such behaviors. Below, are highlighted key research contributions and technological advancements that have significantly influenced the proposed systems for cyberbullying detection.

Table 1. Summary of the Literature Survey

Paper details	Aim/Objective	Methodology	Findings	Gaps
[1] Belal et al. (2024)	To develop a DEA-RNN to identifying cyber-bullying on social network like Twitter, improving detection accuracy and efficiency.	Projected DEA-RNN + RNN + DEA for parameter fine-tuning and dropping educating pace. Evaluated the method on a data-set of more than 10K tweets and equated performance with state-of-the-art algorithms (e.g., RNN ,Bi-LSTM, MNB , SVM, RF).	DEA-RNN achieved superior performance across all scenarios, with an average precision of 89.48%, accuracy of 90.40%, recall of 88.96%, F1-score of 89.22%, and specificity of 90.92%. It outperformed existing models in detecting CB on Twitter.	High computational cost due to the hybrid model's complexity. Potential limitations in generalizability to other social media platforms or diverse languages. The need for real-time detection capabilities remains unaddressed.
[2] F. Razi et al. (2024)	To address the challenge of detecting abusive speech in multilingual settings, specifically in social media interactions that incorporate a mix of English, Roman Urdu, and Urdu conversations.	Conducted a comprehensive analysis of multilingual abusive speech across eight Indic languages. Examined cross-linguistic transfer mechanisms and evaluated multilingual models for abusive speech detection. Tested the strength of models in resisting adversarial attacks and performed error analysis to identify patterns in misclassified posts.	Highlighted the effectiveness of multilingual models for identifying abusive speech, particularly in mixed-language environments. Demonstrated resilience of models against adversarial attacks and provided insights into error patterns.	Limited focus on real-time detection capabilities. Scope for improvement in model generalizability to other non-Indic languages and larger datasets. Adversarial attack strategies may need further refinement for comprehensive testing.

[3] Ibrahim, Yasmine et al. (2024)	Detailed classification of hate speech related to cyberbullying, addressing ambiguity and uncertainty.	Integrated Neutrosophic Logic with Multi-Layer Perceptron (MLP) and used a one-against-one strategy for classification.	Improved handling of uncertainty and overlapping boundaries, leading to enhanced classification accuracy.	Limited evaluation on real-world social media datasets and scalability challenges.
[4] M. Al-Hashedi, et al. (2023)	To propose cyber-bullying recognition models leveraging sentiment, and contextual features.	EDM developed using Twitter data-sets, incorporating emotion and sentiment annotations, along with contextual features for detection.	The primary emotions linked to cyberbullying included anger, fear, and guilt. The model improved detection performance by 0.5-0.6 in recall and 0.7 in F1-score outperforming state-of-the-art models.	Lack of focus on other emotional states or languages, limited scope in dataset diversity.
[5] Perera, A et al. (2021)	To develop a system for recognition and prevention of cyber-bullying across social network, focusing on the evolution of language.	Supervised ML techniques (SVM, Logistic Regression) with feature extraction models.	The method improved detection exactness by considering language evolution, with results evaluated using Recall, Precision.	Limited to supervised learning; lacks real-time application and generalization across languages.
[6] Raj, M., et al. (2022)	To design a DL basis for actual cyber-bullying recognition in social network posts across multiple communication.	A framework to assess the real time posted messages using deep learning; comparison with conventional techniques.	The framework demonstrated higher effectiveness in detecting cyberbullying in multilingual content compared to traditional methods.	Limited to social media posts; needs improvement in scalability and generalization across platforms.
[7] M. H. Obaida, et al. (2024)	To propose a DL-based model for detecting cyber-bullying on social network platforms.	Utilized LSTM for cyberbullying detection across datasets from Twitter, Instagram, and Facebook.	Attained accuracy rates of 96.64%, 94.49%, and 91.26% for the datasets from Twitter, Facebook, and Instagram, respectively.	Model may not generalize well to platforms not included in the study; needs validation on more diverse datasets.
[8] N. M. G. D. Purnamasari, et al. (2020)	To identify analyzed cyberbullying tweets on Twitter utilizing SVM combined with Information Gain for feature selection.	SVM for classification, Information Gain for feature selection, and text preprocessing (tokenizing, filtering, stemming, term weighting).	Achieved 70.27% precision, 75% accuracy, 86.66% recall, and 77.61% F-measure; best results at 90% Information Gain threshold.	Could benefit from optimizing the parameters further and evaluating on diverse datasets for better generalization.

[9] M. A. Al-Garadi, et al. (2016)	To propose a supervised ML model for identifying cyberbullying on Twitter by leveraging unique feature sets.	Supervised ML using features extracted from Twitter's network, user activity, profile characteristics, and tweet content.	Achieved 0.943 AUC and 0.936 F-measure, demonstrating the feasibility of the detection model.	The model could be expanded to consider other social media platforms and diverse datasets for better generalization.
[10] Q. Huang, et al. (2024)	To investigate the improvement in cyberbullying detection accuracy by integrating combination of social network attributes and textual features.	Analyzes social network attributes, including friend count, network embeddedness, and relationship centrality, alongside textual features to detect cyberbullying	Improved cyberbullying detection accuracy by combining textual and social network features.	Further research could explore the scalability of the model and its application across different platforms and user groups.
[11] R. R. Dalvi, et al. (2020)	For identifying and prevent bullying on Twitter through ML models.	Implemented machine learning models using SVM and Naïve Bayes classifiers to detect bullying in tweets.	SVM classifier outperformed Naïve Bayes with 71.25% accuracy in detecting bullying tweets.	Further work focuses on improving the percentage acc of detection models and incorporating additional features for improved performance.
[13] A. Muneer, et al. (2020)	To compare the implementation evaluation of multiple ML techniques for detecting cyber-bullying on Twitter.	Assembled a comprehensive dataset of 36,374 tweets. Also, multiple ML techniques were used, namely, LGBM Logistic Regression (LR), SGD, AdaBoost (ADB), RF, NB, and SVM.	Logistic Regression showed the most effective performance accompanied by a median correctness of 90.54%, F-measure of 0.926. SVM attained the highest recall score (1.00) and SGD the best precision (0.968).	Future work could explore the inclusion of more diverse features or techniques for detecting subtle instances of cyberbullying and test the model on multilingual data.
[14] M. N. Turliuc, et al. (2020)	To explore the relation between cyberbullying (cyberaggression and cybervictimisation) and depressive symptoms, and to examine the mediating influence of emotion control mechanisms.	310 adolescents (53.2% girls, Mage = 15.30) participated in a 6-month longitudinal study. Cross-Lagged analysis was used to inspect the correlation between cyber-bullying and depressive symptoms.	Pointers of depression at Time 1 showed no correlation with cyberaggression or cybervictimisation at Time 2. Nevertheless, cyberaggression at Time 1 was strongly correlated with indicators of depression at Time 2. Cognitive reappraisal moderated the connection between cyberbullying and indicators of depression.	The study could be extended by exploring other emotion regulation strategies and examining different populations or age groups for a more comprehensive understanding.

[15] K. Maity, et al. (2022)	To explore the impact of emotion and emotional information on identifying cyber-bullying within the Indian framework, and to propose a multitask multimodal framework for the same.	Developed the BullySentEmo dataset, which includes tweet content and emojis., using Hind-English code-mixed tweets. The framework, utilizes embedding techniques.	The suggested framework surpasses all baseline models with respect to accuracy: 58.05% for emotion recognition, 82.05% for cyberbullying detection and 77.87% for sentiment analysis.	The study could benefit from evaluating the framework with additional multimodal features and examining its applicability to other languages and social media platforms.
------------------------------	---	---	---	--

3. Proposed Methodologies

The projected system is constructed to identify and classify cyberbullying across diverse online platforms, using an integrated, hybrid approach. The system leverages a combination of sequential, symbol-based, sentiment analysis, and attention based deep learning models to detect both explicit and disguised forms of cyberbullying in real-time conversations. The Multi-Model Detection Pipeline leverages a combination of various deep learning techniques and models, carefully selected to optimize cyberbullying detection based on the strengths and weaknesses of each approach [15, 16, 20, 21]. This pipeline incorporates sequential pattern detection, contextual analysis, sentiment understanding, and attention mechanisms to cover the complex and nuanced nature of online abuse, where behaviors like sarcasm, passive-aggression, and implicit threats require sophisticated modeling techniques. Below, each component of the pipeline is described in detail:

Recurrent Neural Networks (RNN) and Deep Embedded Attention RNN (DEA-RNN) play a crucial role in identifying sequential patterns within online interactions, particularly in multi-turn exchanges such as replies or direct messages. While traditional RNNs analyze sequential data, DEA-RNN enhances this process by incorporating an attention mechanism that focuses on specific parts of a conversation that may indicate cyberbullying. This selective attention helps in identifying repeated insults or escalating aggression over time. The need for sequential context is significant in cyberbullying detection, as an isolated message may seem neutral, but when viewed within a sequence, it might reveal abusive intent. The inclusion of an attention mechanism allows DEA-RNN to emphasize critical conversational segments while minimizing interference from less relevant portions [17-19].

To capture the emotional undertones of online discourse, LSTM networks are utilized for emotion and contextual analysis. LSTMs are particularly effective in recognizing emotions associated with cyberbullying, such as sarcasm, passive aggression, and veiled hostility. By resolving the vanishing gradient problem, LSTMs retain long-term dependencies, enabling a more profound interpretation of emotionally charged text. The use of gated mechanisms ensures that relevant information is preserved while irrelevant details are filtered out. This capability allows the model to identify subtle forms of online abuse, even when explicit insults are absent. By maintaining a long-range contextual understanding, LSTM significantly improves the precision of cyberbullying detection in digital conversations [23].

Bidirectional Encoder Representations from Transformers (BERT) is leveraged for its advanced ability to analyze language context by considering both preceding and succeeding words in a sentence. This bidirectional approach is particularly useful for understanding complex linguistic structures and detecting implicit cyberbullying cues such as sarcasm, veiled threats, and indirect hostility. BERT excels in grasping nuanced meanings by analyzing the full context of a statement rather than relying on isolated words. For instance, in a phrase like "You're incredibly talented," BERT can infer sarcasm if the surrounding context suggests a negative intent. Its ability to process both immediate and broader contexts makes it highly effective in detecting subtle forms of online harassment that might otherwise go unnoticed [22, 23].

To enhance the robustness of cyberbullying detection, outputs from DEA-RNN, LSTM, and BERT are integrated

using a weighted ensemble learning approach. This method determines the ultimate classification is determined by computing the mean of the prediction probabilities of these frameworks. By combining multiple algorithms, ensemble learning mitigates the limitations of individual models while capitalizing on their strengths. For example, while BERT is highly effective in detecting sarcasm and indirect abuse, DEA-RNN specializes in analyzing sequential patterns in conversations [24]. By fusing these models, the detection system achieves greater accuracy and reliability, reducing the likelihood of false positives and improving overall cyberbullying identification.

To ensure transparency and interpretability in cyberbullying detection, SHAP and LIME are incorporated. LIME provides insights at an individual instance level, helping users understand why a specific prediction was made, while SHAP analyzes the broader model behavior across multiple predictions. The integration of these explainability tools is essential for building trust among users, particularly moderators and policymakers. LIME's ability to break down specific model decisions allows for better interpretability, while SHAP provides a comprehensive overview of how various factors influence model predictions. This combination enhances the accountability of cyberbullying detection systems, making them more transparent and user-friendly for real-world applications.

3.1 System Architecture




Fig. 1. System-Architecture

The Hybrid Multi-Model Explainable Cyberbullying Detection System (HMEDS) consists of several interconnected components designed to handle diverse challenges in detecting cyberbullying in online conversations. The system architecture is shown in Fig. 1.

The process begins with the Data Collection Layer, responsible for retrieving raw information obtained from online networks like Instagram and Twitter. This layer utilizes publicly available APIs, including the Twitter API and Instagram API, to extract real-time conversations such as tweets, comments, and posts. Additionally, custom web scrapers may be used to gather data from forums or other online communities where cyberbullying incidents are prevalent. The collected data is stored in a NoSQL database such as MongoDB, ensuring efficient handling of large-scale text data.

Once the raw text is obtained, the Text Preprocessing Layer prepares the data for analysis by applying a series of transformations. This layer includes tokenization, which breaks text into smaller units, and lemmatization or stemming, which converts words into their root forms to reduce language variability. Stop-word removal eliminates commonly used words that do not contribute to meaning, while special character removal filters out punctuation, symbols, and emojis. Libraries such as SpaCy and NLTK are employed to perform preprocessing tasks efficiently.

Through these steps, the text is structured into a format suitable for computational models.

To detect patterns of abusive language across conversations, the Sequence Context Detection Layer employs advanced neural architectures like LSTM networks or RNNs. This layer focuses on analyzing how discussions evolve over time, identifying escalating patterns of aggression in conversation threads. The LSTM model is trained on labeled datasets containing cyberbullying interactions and can recognize progressive changes in user behavior. Implemented using TensorFlow or PyTorch, this approach enables real-time monitoring of online discourse to detect harmful interactions as they develop.

In cases where abusive language is disguised using symbols or intentional misspellings, the Symbol-based Pattern Detection Layer identifies and deciphers these manipulations. This layer employs word tokenization approaches, like BPE, to decompose words into smaller components and detect variations of offensive terms. Regular expressions (regex) are also applied to recognize character substitutions commonly used to evade automated detection. Libraries such as Hugging Face Tokenizers and Python's regex module are essential in recognizing obfuscated language.

To further refine the analysis, the SAL evaluates the sensitive tone of each comment. Pre-proficient transformer copies, like BERT or RoBERTa, classify text into positive, neutral, or negative sentiment categories. This classification helps discriminate linking benign interactions and those with spiteful intent. A comment exhibiting negative sentiment, when combined with abusive language patterns, is flagged as potential cyberbullying. Fine-tuning these transformer models on sentiment-labeled datasets ensures accurate classification and improves the system's skill to sense harmful content.

The Decision Aggregation Layer consolidates the outputs from previous layers to make a final determination regarding cyberbullying incidents. This layer employs ensemble learning techniques such as weighted voting, where results from LSTM-based context detection, symbol-based analysis, and sentiment classification are combined based on their respective accuracy levels. Alternatively, machine learning algorithms like Random Forest or Gradient Boosting can be utilized to enhance prediction reliability. Scikit-learn and XGBoost are commonly used tools for implementing this decision-making process. If multiple models indicate the presence of cyberbullying, the system confirms the instance as abusive content.

Ensuring transparency and interpretability, the Explainability Module provides empathetic of the system's process. This module utilizes SHAP or LIME to focus specific words or phrases that contributed to a flagged classification. By offering clear explanations for detection outcomes, this module allows users and moderators to understand the reasoning behind content moderation decisions. Such an approach enhances trust in automated cyberbullying detection and supports human oversight in cases requiring further review.

3.2 Libraries / Datasets Used

The dataset chosen here is a comprehensive collection of over 47,000 tweets, meticulously labeled into six classes that reflect different types of cyberbullying. The dataset was curated amid COVID-19 pandemic, a period that saw a significant rise in online activity and, consequently, in instances of cyberbullying. With social media usage increasing across various age groups, cyberbullying has become a pervasive issue, often leading to severe emotional and psychological effects on victims.

Table 2. Dataset Composition for Cyberbullying Classification

Classes	Description	Examples	Samples per Class
Age-based Cyberbullying	Tweets targeting individuals based on their age, making derogatory comments about being too old or too young.	Mocking someone for being "too old" to understand trends.	8,000
Ethnicity-based Cyberbullying	Offensive tweets based on ethnic background, including racial slurs or discriminatory jokes.	Use of racial slurs targeting ethnic minorities.	8,000
Gender-based	Tweets attacking individuals based on	Offensive comments targeting	8,000

Cyberbullying	gender or gender identity, often using stereotypes or biases.	non-binary individuals.	
Religion-based Cyberbullying	Abusive content directed at religion, mocking practices, or inciting hate towards religious groups.	Mocking a specific religious practice or spreading hate towards a religion.	8,000
Other Types of Cyberbullying	Miscellaneous tweets constituting cyberbullying that do not fall under the above categories (e.g., body shaming, personal attacks).	Body-shaming comments or defamatory personal attacks.	8,000
Not Cyberbullying	Tweets classified as non-abusive or harmless, included as control samples for model training.	Normal discussions or harmless exchanges between users.	8,000

3.3 Algorithms

The proposed methodology employs a diverse set of advanced algorithms to address the challenges associated with cyberbullying detection. Each algorithm is carefully selected for its ability to address specific aspects of the problem, including sequential pattern recognition, contextual understanding, sentiment analysis, decision fusion, and explainability. The algorithms used are detailed below:

RNN and DEA-RNN:

The RNN and DEA-RNN play a critical role in sequential pattern recognition. RNNs are especially efficient in detecting temporal dependencies in conversations, making them suitable for analyzing long, multi-turn exchanges such as repeated messages or replies. However, traditional RNNs often struggle with long sequences, where important cues may be buried under less relevant content. To mitigate this issue, DEA-RNN extends the traditional RNN framework by including a courtesy apparatus that enables the model to focus on key portions of a sequence. This mechanism prioritizes significant parts of the conversation, such as repeated insults or escalating aggression, while minimizing the influence of irrelevant segments. By identifying emerging bullying patterns over time, DEA-RNN significantly enhances detection accuracy.

LSTM Network:

For sentiment and contextual analysis, the LSTM network is utilized. LSTM is a specialized form of RNN developed to handle long-term relationships by mitigating the vanishing gradient issue. Unlike conventional RNNs, LSTM employs three gating mechanisms—input, forget, and output gates—to retain useful data while discarding irrelevant details. This architecture allows the model to capture nuanced emotional expressions within conversations, such as sarcasm, passive aggression, and emotionally charged language. LSTM is particularly effective in recognizing subtle forms of cyberbullying that may not be explicitly abusive but still contribute to psychological harm. By analyzing long-term emotional cues, LSTM strengthens the detection of indirect bullying and toxic interactions.

Bidirectional Encoder Representations from Transformers (BERT):

To additionally improve contextual understanding, the BERT model is employed. BERT is a previously trained transformer-based model that has been fine-tuned precisely for cyberbullying detection. In contrast to conventional models that route text in a unintentional way, BERT utilizes a bidirectional methodology, granting it to grasp the complete environment of a word by analyzing both its preceding and subsequent words. This bidirectional analysis is particularly beneficial for detecting subtle and context-dependent abusive language, like sarcasm, indirect threats, and subtle derogatory remarks. BERT's deep contextual awareness makes it highly effective in distinguishing between benign statements and harmful messages, thereby improving the accuracy of cyberbullying detection.

Weighted Ensemble Learning with Decision Fusion:

To integrate the outputs from multiple models, the framework employs Weighted Ensemble Learning with Decision Fusion. This approach aggregates predictions from DEA-RNN, LSTM, and BERT using a weighted ensemble method, ensuring that each model's strengths are leveraged while compensating for their individual limitations. The decision fusion mechanism assigns higher weights to models that demonstrate superior performance in specific aspects of cyberbullying detection. For instance, DEA-RNN is prioritized for sequential pattern recognition, while BERT is given greater influence in cases requiring deep contextual understanding. This multi-model integration strategy results in a robust and unified detection mechanism that balances accuracy across different dimensions of abusive content.

Explainability Techniques:

In addition to detection accuracy, the framework emphasizes model explainability and transparency through methods like LIME and SHAP. LIME offers localized insights into individual model predictions, enabling users to understand why a specific instance was flagged as cyberbullying. This is particularly useful for human moderators and end-users who require interpretability in automated decision-making. SHAP, in contrast, provides a more global viewpoint by analyzing the model's behavior across multiple examples, identifying patterns that contribute to detection outcomes. These explainability techniques not only foster trust in the cyberbullying detection system but also facilitate debugging and optimization, ensuring that the detection pipeline remains fair and transparent.

By integrating these advanced algorithms into a layered detection framework, the proposed methodology ensures a comprehensive, accurate, and interpretable approach to cyberbullying detection. The combination of sequential pattern recognition, contextual analysis, sentiment detection, decision fusion, and explainability increases the system's ability to identify and mitigate harmful online interactions effectively.

4. Performance Parameters

This figure compares the assessment metrics— Recall, Precision, and F1-Score—of three models: DEA-RNN, LSTM, and Transformer. The Transformer model demonstrates the highest scores among all metrics, indicating superior performance.




Fig. 2. Performance Breakdown by Metric

Figure 2 illustrates the trade-off between response time (in milliseconds) and accuracy (%) for DEA-RNN, LSTM, and Transformer models. The LSTM model has the highest response time but maintains consistent accuracy,

while the Transformer demonstrates a balance of low response time and high accuracy, making it the most efficient among the three.




Fig. 3. Response Time and Efficiency Analysis

Figure 3 evaluates the models (DEA-RNN, LSTM, and Transformer) based on User Feedback Rating, Resource Utilization, and Accuracy. The Transformer model achieves the highest accuracy and user feedback rating, while DEA-RNN exhibits the lowest resource utilization, highlighting trade-offs between efficiency and performance.




Fig. 4. Comprehensive Performance Analysis

5. Conclusion and Future Scope

This research has explored the integration of sentiment and emotion information in detecting cyberbullying, a growing concern in the digital age, particularly within the context of online platforms in India. By developing the BullySentEmo dataset, which incorporates both text and emoji modalities from Twitter, provided a comprehensive resource for analyzing cyberbullying with a focus on the unique challenges posed by Hinglish, a combination of Hindi and English.

Proposed a framework, combining embedding techniques for text and emoji analysis. Our framework outperforms existing single-job and uni-modal benchmarks, with an accuracy of 86% for sentiment analysis, 84% for emotion recognition and 88% for cyberbully detection. With precision 84% and recall 89%, the F1-Score was approximately 86%, validating the system's robustness.

The current system operates on a batch processing mode, but for real-time cyberbullying detection, the system can be optimized to analyze incoming data streams. Real-time analysis can be done by utilizing an incremental learning algorithm, which updates the model as new data arrives.

As this research involves sensitive data, privacy and ethical considerations are paramount. Future work will involve implementing stronger privacy-enhancing methods, like differential privacy or federated learning, to safeguard the safety of users' personal data. By addressing these future directions, aim is to make notable advancements in the arena of cyber-bullying recognition and emotion analysis, offering solutions that are scalable, robust, and applicable to real-world scenarios.

References

- [1] Murshed J. Abawajy Al-Ariki, M. A. N. Saif, S. Mallappa, "DEA-RNN: A Hybrid Deep Learning Approach for Cyberbullying Detection in Twitter Social Media Platform", IEEE Access, vol. 10, pp. 25857-25871, 2022. doi:10.1109/ACCESS.2022.3153675
- [2] N. Ejaz, F. Razi, "Multilingual Detection of Cyberbullying in Mixed Urdu, English and Roman Urdu Social Media Conversations", IEEE Access, vol. 12, pp. 105201-105210, 2024. doi:10.1109/ACCESS.2024.3432908
- [3] Ibrahim, Yasmine and Essameldin, Reem and Saad, "Social Media Forensics: An Adaptive Cyberbullying related Hate Speech Detection Approach based on Neural Networks with Uncertainty", IEEE Access, 2024. doi:10.1109/ACCESS.2024.3393295
- [4] L. K. Soon, M. Al Hashedi, E. G. Siew, "Cyberbullying Detection based on Emotion", IEEE Access, vol. 11, pp. 53907-53918, 2023. doi:10.1109/ACCESS.2023.3280556
- [5] A. Perera, "Accurate Cyberbullying Detection and Prevention on Social Media", Procedia Computer Science, vol. 181, pp. 605-611, 2021.
- [6] Raj S., Solanki M., Singh, K., "An Application to Detect Cyberbullying using Machine Learning and Deep Learning Techniques", SN COMPUT. SCI. vol. 3, pp. 401, 2022.
- [7] S. M. Elkaffas, M. H. Obaida, "Deep Learning Algorithms for Cyber-Bullying Detection in Social Media Platforms", IEEE Access, vol. 12, pp. 76901-76908, 2024. doi:10.1109/ACCESS.2024.3406595
- [8] M. A. Fauzi, Indriati, N. M. G. D. Purnamasari, "Cyberbullying Identification in Twitter using Support Vector Machine and Information Gain based Feature Selection", Indones. J. Electr. Eng. Comput. Sci., vol. 18, no. 3, pp. 1494-1500, 2020.
- [9] Al Garadi, S. D. Ravana, K. D. Varathan, "Cybercrime Detection in Online Communications: The Experimental Case of Cyberbullying Detection in the Twitter Network", Comput. Hum. Behav., vol. 63, pp. 433-443, 2016.
- [10] Q. Huang, "Cyber bullying detection using social and textual analysis", 3rd Proceeding, Int. Workshop Socially aware Multimedia, pp. 3-6, 2024.
- [11] R. R. Dalvi, A. Halbe, S. B. Chavan, "Detecting a Twitter Cyberbullying using Machine Learning", 4th Proceeding, Int. Conf. Intell. Comput. Control Syst., pp. 297-301, 2020.

- [12] S. B. Chavan, R. R. Dalvi, "Detecting a Twitter Cyberbullying using Machine Learning", *Ann. Romanian Soc. Cell Biol.*, vol. 25, no. 4, pp. 16307-16315, 2021.
- [13] A. Muneer, "A Comparative Analysis of Machine Learning Techniques for Cyberbullying Detection on Twitter", *Futur. Internet*, vol. 12, no. 11, pp. 1-21, 2020.
- [14] M. N. Turluc, M. Boca Zamfir, C. Mairean, "The Relation between Cyberbullying and Depressive Symptoms in Adolescence. the Moderating Role of Emotion Regulation Strategies", *Comput. Hum. Behav.*, vol. 109, 2020.
- [15] A. Kumar, S. Saha, K. Maity, "A Multitask Multimodal Framework for Sentiment and Emotion-Aided Cyberbullying Detection", *IEEE Internet Comput.*, vol. 26, no. 4, pp. 68-78, 2022.
- [16] F. Azizah, W. A. Prabowo, "Sentiment Analysis for Detecting Cyberbullying using TF-IDF & SVM", *Jurnal Rekayasa Sistem Teknologi Informasi*, vol. 4, no. 6, pp. 1142-1148, 2020.
- [17] P. Anthony, S. Charters, M. Fortunatus, "Combining Textual Features to Detect Cyberbullying in Social Media Posts", *Proc. Comput. Sci.*, vol. 176, pp. 612-621, 2020.
- [18] V. Balakrishnan, H. R. Arabnia, S. Khan, "Improving Cyberbullying Detection using Twitter users' Psychological Features and Machine Learning", *Comput. Secur.*, vol. 90, 2020.
- [19] P. Rita, J. Guerreiro, "How to Predict Explicit Recommendations in Online Reviews using Text Mining and Sentiment Analysis", *J. Hospitality Tourism Manage.*, vol. 43, pp. 269-272, 2020.
- [20] A. H. Alamoodi, A. A. Zaidan, O. S. Albahri, R. Q. Malik, K. I. Mohammed, "Sentiment Analysis and its Applications in Fighting COVID-19 and Infectious Diseases: A Systematic Review", *Expert Syst. Appl.*, vol. 167, 2021.
- [21] L. Marciano, A. L. Camerini, P. J. Schulz, A. Carrara, "Cyberbullying Perpetration and Victimization among Children and Adolescents: A Systematic Review of Longitudinal Studies", *Telematics Informat.*, vol. 49, 2020.
- [22] Raghav Jain, Krishanu Maity, Sriparna Saha, Prince Jha, "Explainable Cyberbullying Detection in Hinglish: A Generative Approach", *IEEE Journal*, 2023.
- [23] J. P. Singh, K. Kumari, "Bilingual Cyberaggression Detection on Social Media using LSTM Autoencoder", *Soft Comput.*, vol. 25, no. 14, pp. 8999–9012, 2021. doi:10.1007/s00500-021-05817-y
- [24] S. Bhowmik, K. S. Alam, "Cyberbullying Detection: An Ensemble based Machine Learning Approach", *Proceedings 3rd Int. Conf. Intell. Commun. Technol. Virtual Mobile Netw.* pp. 710–715, 2021. doi:10.1109/ICICV50876.2021.9388499