

Wyświetlacze i panele dotykowe w systemach embedded

Kamil Kozłowski

Agenda

- **Riverdi, Unisystem, Lummico**
- **STN, TFT, OLED, VFD**
- **Wyzwanie wyświetlacza, dlaczego Apollo 11 nie miał TFT?**
- **Embedded Displays, interfejsy**
- **Jasność, kontrast, odbicia**
- **TP, TS, RTP, CTP, PCAP, CG, DITO, SITO, OGS, GG, GF, GFF, OCA, LOCA, SCA**
- **Q&A (P&O?)**
- **Kahoot**

Zapowiadało się nieźle




Unisystem, Riverdi, Lummico...

unisystem

Dystrybucja




Produkcja



lummico

Gotowe urządzenia



Ultra Low Power
Wi-Fi Connectivity

3 Years Always-Connected
Operation on a Single Charge


Different Sizes
for Different Applications

lummico



Our Mission

Our mission is to bring you high-quality, accessible, and customizable display solutions.




OLED, STN, VFD, TFT

Comparison



OLED




STN



VFD

LCD - TN

TN - Twisted Nematic – technology associated mainly with passive matrices, and the improvements introduced in it allow to improve the image quality (e.g. by giving it color). TN technology is also the basis for TFT matrices.



LCD, TFTs, LCD TFTs?

TFT

transistor
FET
(CMOS)

LCD



Transistor
with
TFT

Each
through
the



unlike
substrate

displays
made in




The display challenge, why Apollo 11 had no TFT?



The display challenge, why Apollo 11 had no TFT?

- $1920 \times 1080 \times 3 = 6\,220\,800\text{ B}$, $\times 2 = 12\,441\,600\text{ B}$
- $60\text{Hz} \times 6\,220\,800\text{ B} = 373\,248\,000\text{ B/s}$
- $1024 \times 600 \times 3 = 1\,843\,200$, $\times 2 = 3\,686\,400\text{ B}$
- $60\text{Hz} \times 1\,843\,200 = 110\,592\,000\text{ B/s}$
- Apollo 11 AGC (Apollo Guidance Computer)
 - 4094 B of RAM, 72KB of ROM
 - 43 kHz
- Central Air Data Computer
 - 375 kHz, six chips, 20-bit fixed-point
 - F-14 CADDC, 1970 -> 1998
- Intel 4004 – 1971 4bit

Embedded, czyli jaki



Internal interfaces

Universal

SPI

I2C

RS232

UART

Image transfer

LVDS

RGB

MIPI

Vx1

eDP

External interfaces

Universal

USB C

Image
transfer

HDMI

DVI

VGA

DP

CONTRAST RATIO

6. Electro-optical characteristics

STANDARD TN SERIES 7":

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT	REMARK	NOTE
Response Time	Tr+Tf	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25	-	20	35	ms	Figure 4	4
Contrast Ratio	Cr		400	500	-	---	Figure 5	1
Luminance Uniformity	δ WHITE		70	75	-	%	Figure 5	3
Surface Luminance	TFT		400	500	-	cd/m ²	Figure 5	2
	TFT+CTP	Lv	360	450	-			
	TFT+RTP		320	400	-			

STANDARD HB/IPS SERIES 4.3":

7 ELECTRO-OPTICAL CHARACTERISTICS

Optical characteristics are determined after the unit has been 'c minutes in a dark environment at 25 °C. The values specified are from the LCD surface at a viewing angle of Φ and θ equal to 0°.


ITEM	SYMBOL	CONDITION	MIN	TYP
Response Time	Tr+Tf	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25 °C	-	30
Contrast Ratio	Cr		640	800
Luminance Uniformity	δ WHITE		-	75
Surface Luminance	Lv		-	800

6 ELECTRO-OPTICAL CHARACTERISTICS STANDARD HB/IPS SERIES 10.1":

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT	REMARK	NOTE
Response Time	Tr+Tf	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25 °C	-	25	35	ms	FIG 1.	4
Contrast Ratio	Cr		800	1000	-	---	FIG 2.	1
Luminance Uniformity	δ WHITE		-	75	-	%	FIG 2.	3
Surface Luminance	Lv		-	800	-	cd/m ²	FIG 2.	2

CONTRAST (RATIO)

Difference whitest white
and blackest black



„the amount of light emitted by the brightest white pixels divided by the amount of light emitted by the darkest black pixels, with the measurement being made in a dark room”

CONTRAST (RATIO) - REAL WORLD



In the real world we have to take external light into consideration

CONTRAST (RATIO)- ECR

ECR = EFFECTIVE CONTRAST RATIO

- Rarely published
- Depends on many hard-to-control factors
- Usually only estimated

$$\text{ECR} = 1 + \left(\frac{\text{emitted light}}{\text{reflected light}} \right)$$

emitted light – manufacturer spec brightness
[cd/m²]

reflected light -amount of light reflected by the
surface of the display.

This is calculated by multiplying the ambient light in nits by the percentage reflectivity of the display.
Ambient light is normally measured in lux. Sunlight ranges from approximately 30,000 lux to 100,000 lux;

CONTRAST (RATIO)- ECR

WELL Building Standard™
Task Luminance Ratio (TLR) 3:1

1:1 – 20:1

Effective Contrast Ratio (ECR)	LCD Outdoor Readability
1-2	Unreadable in sunlight
3-4	Adequately readable in shade; barely readable in sunlight
5-9	Adequately readable in sunlight; looks OK
10	Very readable in sunlight; looks good
15	Outstanding readability; looks great
20	Totally awesome; excellent readability; can't be improved

CONTRAST (RATIO) - ECR

WELL Building Standard™ Task Luminance Ratio (TLR) 3:1

We are the International WELL Building Institute (IWBI) and we know that the spaces around us can make everyone, everywhere, healthier, happier and more productive.

SUNLIGHT

The intensity of the reflected light from the outside it must be summed up with the intensity individual pixel lights to be able to use them compare and evaluate the contrast observed in practice.


Low/standard brightness modules;

LCD TFT brightness: 400cd/m²,
exposed to the direct sunlight (about 30 000 lux ~10 000 cd/m²)
surface reflects about 4.5%

„additional” brightness ~ 10k cd x4.5% = 450 cd/m²

The real contrast is:

$$Cr \approx \frac{400 + 450}{450} \approx 2:1$$




$$Cr \cong \frac{1500cd/m^2 + 450cd/m^2}{450cd/m^2} \approx 4,3$$



REFLECTIONS


Assuming 5% reflection for the LCD TFT surface – is that all?



Kontrast+ – mini LED



Apple iPad Pro with blue mini LED

- Apple iPad Pro 12.9" in with blue mini LED. (The iPad Pro 11" does NOT use mini LED, but regular LEDs).
- 10,000 blue mini LEDs. 2500 local dimming zones. The result is a contrast ratio of 1 million: 1.



Picture source: Apple

HB Outdoor Display



Key Features

- Ultra high brightness and sunlight readable
- Dust-Water proof (IP66)
- Impact Resistant (IK10 rated)
- Blackening defect free by Hi-Tni LC
- Sunglasses viewable by circular polarizer
- Auto dimming control (Ambient Light Sensor)

Temperature Blackout



OPERATING AND STORAGE TEMPERATURES


**industrial
standard:**

	Min	Max	Unit
Operating temperature	-20	+70	°C
Storage temperature	-30	+80	

Hi-Tni:

A high TNI panel is designed to prevent blackening when the display operates under elevated temperature conditions:

Hi Tni LC – High Temperature nematic - isotropic



Hi Tni LC – example

1920x540 P370IVN03.0 1500 Adv. Hi-Tni LC (-40~110°C), C-POL, 70Khrs

1. General Description

This specification applies to the 37.0 inch Color TFT-LCD Module P370IVN03.0. This LCD module has a TFT active matrix type liquid crystal panel 1,920x540 pixels, and diagonal size of 37.0 inch. This module supports 1,920x540 resolution display. Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 10-bit gray scale signal for each dot.

The P370IVN03.0 has been designed to apply the 8/10-bit 2 channel LVDS interface method. The main feature of P370IVN03.0 would be high brightness, high contrast, wide viewing angle, wide temp. LC(-40°C~110°C), circular PF film, high color saturation, edge LED backlight and high color depth.

* General Information

Items	Specification	Unit	Note
Active Screen Size	37.0	Inch	
Display Area	904.32(H) x 254.34(V)	mm	
Outline Dimension	923.30(H) x 277.1(V) x 10.65(D)	mm	1

5. Absolute Maximum Ratings

The followings are maximum values which, if exceeded, may cause faulty operation or damage to the unit

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vcc	-0.3	14	[Volt]	Note 1
Input Voltage of Signal	Vin	-0.3	4	[Volt]	Note 1
Operating Temperature	TOP	0	+50	[°C]	Note 2
Operating Humidity	HOP	10	90	[%RH]	Note 2
Storage Temperature	TST	-20	+60	[°C]	Note 2
Storage Humidity	HST	10	90	[%RH]	Note 2
Panel Surface Temperature	PST		70	[°C]	Note 3

Panele dotykowe

TP, TS, RTP, CTP, PCAP


- **Touch Panel**
- **Touch Screen**
- **Resistive Touch Panel**
- **Capacitive Touch Panel**
- **Projected Capacitive**



Panele dotkowe

CG, DITO, SITO, OGS, GG, GF, GFF


- Cover Glass
- Double Indium Thin Oxide
- Single ITO
- One Glass Solution
- Glass Glass
- Glass Film
- Glass Film Film



Bonding optyczny

OCA, LOCA, SCA


- Optical Clear Adhesive
- Liquid OCA
- Silicon Clear Adhesive



Produceni kontrolerów paneli dotykowych

	FocalTech	HYCON	ILITEK	EETI	Penmount	Goodix	TouchNetix	SIS
Works with EVE	yes	yes	Yes!	No	No	Yes	No	No
Max CG thickness	1.8 mm	5mm	10 (15) mm	10 (15)mm	15mm	2mm		10mm
Unique value	cheap	Thick glass support	Direct contact and support, best value for money	Direct contact and support, military projects	Wide customization	cheap	Air touch, hover touch, haptic feedback	
Direct support	indirect	indirect	direct	direct	direct	indirect	direct	direct
Focus market	Mobile phones, tablets	Industrial and semi-industrial market	Industrial, Medical, Semi-Industrial	Industrial, Medical, Semi-Industrial	Industrial, Medical, Military	Mobile phone, tablets	Automotive	Industrial, Medical, Semi-Industrial

Brave new world




Arm® Cortex® -M7 up to 550 MHz

Most powerful Cortex core with double precision FPU, MPU, advanced DSP and L1 cache



Arm® Cortex® -M4 @240 MHz

Best in class core for **real-time** with single precision FPU, DSP, MPU and ART Accelerator™

Example use case how to benefit from dual-core STM32H7



STM32 Embedded Displays



10.1" IPS



Optical
Bonding



850 cd/m²



Industrial
Capacitive



uxTouch



All STM32H7
Interfaces




STM32H7



Low EMI

STM32 Embedded Displays



Q & A



kamil@riverdi.com



linkedin.com/in/kamil-kozlowski/



youtube.com/@Riverdi



kamilcozy





Display Solution Experts

Thank you