

UNIVERSITY OF TARTU
Faculty of Science and Technology
Institute of Computer Science
Computer Science Curriculum

Gediminas Milašius

Exploring integration complexity of
different multi-national eID
authentication solutions in the EU private
sector

Master's Thesis (24 ECTS)

Supervisor(s): Arnis Paršovs, MSc

Tartu 2022

Exploring integration complexity of different multi-national eID authentication solutions in the EU private sector

Abstract:

Many interpreting program languages are dynamically typed, such as Visual Basic or Python. As a result, it is easy to write programs that crash due to mismatches of provided and expected data types. One possible solution to this problem is automatic type derivation during compilation. In this work, we consider study how to detect type errors in the WHITESPACE language by using fourth order logic formulae as annotations. The main result of this thesis is a new triple-exponential type inference algorithm for the fourth order logic formulae. This is a significant advancement as the question whether there exists such an algorithm was an open question. All previous attempts to solve the problem lead to logical inconsistencies or required tedious user interaction in terms of interpretative dance. Although the resulting algorithm is slightly inefficient, it can be used to detect obscure programming bugs in the WHITESPACE language. The latter significantly improves productivity. Our practical experiments showed that productivity is comparable to average Java programmer. From a theoretical viewpoint, the result is only a small advancement in rigorous treatment of higher order logic formulae. The results obtained by us do not generalise to formulae with the fifth or higher order.

Keywords:

List of keywords

CERCS:

CERCS code and name: <https://www.etis.ee/Portal/Classifiers/Details/d3717f7b-bec8-4cd9-8ea4-c89cd56ca46e>

Tüübituletus neljandat järku loogikavalemitele

Lühikokkuvõte:

One or two sentences providing a basic introduction to the field, comprehensible to a scientist in any discipline.

Two to three sentences of more detailed background, comprehensible to scientists in related disciplines.

One sentence clearly stating the general problem being addressed by this particular study.

One sentence summarising the main result (with the words “here we show” or their equivalent).

Two or three sentences explaining what the main result reveals in direct comparison to what was thought to be the case previously, or how the main result adds to previous knowledge.

One or two sentences to put the results into a more general context.

Two or three sentences to provide a broader perspective, readily comprehensible to a scientist in any discipline, may be included in the first paragraph if the editor considers that the accessibility of the paper is significantly enhanced by their inclusion.

Võtmesõnad:

List of keywords

CERCS:

CERCS kood ja nimetus: <https://www.etis.ee/Portal/Classifiers/Details/d3717f7b-bec8-4cd9-8ea4-c89cd56ca46e>

Contents

1	Introduction	9
1.1	Motivation	9
1.2	Research Problem	10
1.3	Scope and goal	10
1.4	Contribution	11
1.5	Structure of work	11
2	Background	12
2.1	Electronic identity eID	12
2.2	eIDAS	12
2.3	eID providers in Estonia	13
2.3.1	Bank link	14
2.3.2	Smart card (ID card)	14
2.3.3	Mobile-ID	14
2.3.4	Smart-ID	15
2.3.5	TARA	15
2.3.6	eeID	16
2.3.7	HarID	16
2.3.8	Dokobit	16
2.4	Authentication and QSCD	17
2.5	Levels of assurance	18
2.6	GDPR	19
2.7	Threats	19
3	Related Work	22
3.1	National e-ID card schemes: A European overview	22
3.2	The Austrian eID ecosystem in the public cloud: How to obtain privacy while preserving practicality	23
3.3	Secure cross-cloud single sign-on (SSO) using eIDs	23
3.4	EID @ Cloud: integración de la identificación electrónica en plataformas europeas en la nube de acuerdo con el reglamento eIDAS.	24
3.5	LEPS - Leveraging eID in the private sector	24
3.6	Federated Identity Architecture of the European eID System	25
3.6.1	Authentication methods	25
3.6.2	Authentication Paradigms and Models	26
3.6.3	Authentication protocols and services	26

4	Architecture Definition	27
4.1	System architecture	27
4.1.1	System overview	27
4.1.2	Process overview	29
4.1.3	Linking eID to an internal user ID	29
4.1.4	Privacy Policy	32
4.2	Weaknesses in the architecture	32
4.2.1	SuperApp	33
4.2.2	AuthServer	34
4.2.3	Data stores	34
5	Case Study: eeID	36
5.1	About	36
5.2	Data Flow	36
5.3	Trust Anchor	38
5.4	Pricing	38
5.5	Security Requirements	38
5.5.1	Protocol's built-in security features	38
5.5.2	Validation requirements for the relying party	42
5.6	Integration	44
5.6.1	Discovered Weaknesses	48
5.7	Case Study: Dokobit	51
5.7.1	About	51
5.7.2	Dokobit Identification Service	51
5.7.3	Data Flow	52
5.7.4	Trust Anchor	54
5.7.5	Pricing	54
5.7.6	Security Analysis	55
5.7.7	Discovered weaknesses	57
5.8	Case Study: Web eID	61
5.8.1	About	61
5.8.2	Data Flow	61
5.8.3	Trust Anchor	61
5.8.4	Pricing	61
5.8.5	Security Analysis	62
6	Discussion	70
6.1	Do businesses even want eID?	70
6.2	Do businesses even want digital signatures?	72
6.3	Which eID provider to choose?	72
6.4	Dangers with having no control over identity	73

7 Conclusion	75
References	83
Appendix	84
I. Glossary	84
II. Licence	85
III. Questionnaire	86
IV. Privacy Policy	88

Unsolved issues

List of keywords	2
CERCS code and name: https://www.etis.ee/Portal/Classifiers/Details/d3717f7b-bec8-4cd9-8ea4-c89cd56ca46e	2
One or two sentences providing a basic introduction to the field, comprehensible to a scientist in any discipline.	2
Two to three sentences of more detailed background, comprehensible to scientists in related disciplines.	2
One sentence clearly stating the general problem being addressed by this particular study.	2
One sentence summarising the main result (with the words “here we show” or their equivalent).	2
Two or three sentences explaining what the main result reveals in direct comparison to what was thought to be the case previously, or how the main result adds to previous knowledge.	2
One or two sentences to put the results into a more general context.	3
Two or three sentences to provide a broader perspective, readily comprehensible to a scientist in any discipline, may be included in the first paragraph if the editor considers that the accessibility of the paper is significantly enhanced by their inclusion.	3
List of keywords	3
CERCS kood ja nimetus: https://www.etis.ee/Portal/Classifiers/Details/d3717f7b-bec8-4cd9-8ea4-c89cd56ca46e	3
ISO standard to pick trust level for if companies even need it	11
What are different options in eIDAS, e.g. what is a QESSD	11
What are the differences between primary services and middlemen, advantages disadvantages	11
What are the weakpoints in the company structure	11
What is the research model?	11
Findings about ID Card, Dokobit, and eeID	11
Non web-based SSO?	11
Ponder about the advantages of middleware pseudominization? Say instead of personal code you get some arbitrary ID that matters only in the system . . .	11
source: I did it myself 02-27, have video recorded, will have to blur	12
Redo the validation sections into 1) security requirements, 2) security requirement compliance by eID provider, 3) security requirement compliance by developers	27
Possible mess? Suggestions wanted.	29
Image proof?	39

I have no clue about the benefit of performing additional verification. The token was received within a secure backchannel, and the nonce matches, meaning the user created the request. If the server makes the user agent session in a way so that no one other than the server itself can tamper, why bother verifying the rest?	47
should I include	49
is this true?	61
Discuss how we can never trust developers without proper supervision	61
This library does favor EE cards a lot more, even having hardcoded some Mobile ID policies. Not sure if it is worth mentioning.	66
Discussion: suggest how the certificates are way too challenging to obtain for a casual company and may lead to additional vulnerabilities	68
Discussion: phishing attacks if the company establishes policy to add certificates if they cannot sign in with their card	68
citation missing	69
Related research about legal person documents?	69
Complete alternative, using your own issued certificates?	69
Talk about which of the 3 case studies would work best in a company in early 2022	72
Should notify how eeID and Web eID are really in their infancy and further research should repeat this study in a couple of years	72
Footnote on ID generation. Why not use the id and not store? Generally you would want to store who created a internal document, or who last edited a page. Using national ID for this purpose can open pandoras box when it comes to logging. Pseudonimization and linking the keys behind strong locks is next best thing.	72
Does this make sense?	74

1 Introduction

1.1 Motivation

With the emergence of COVID-19, work from home has rapidly grown in popularity. It has been especially noticeable in the IT industry. This phenomenon has led some businesses to transition to operate fully remote [1], allowing for potential customers, clients, and employees to operate with the companies' IT systems from all around the globe.

Identity verification is a significant roadblock when establishing a remote work policy. In some managerial businesses, such as logistics, it is essential to assure the authenticity of persons logging in to perform their duties. This security requirement is essential for those dealing with contracts, where one input can cost thousands. Traditionally, as work was always on-premises, it was easy to verify the identity with the help of an identity document. With the constraints imposed by fully remote operations, companies no longer have the luxury to perform such a check.

Establishing identity online for potential employees and clients is not the only use case for digital identity. Organizations such as the British Council employ privacy undermining practices. As part of the registration process for the IELTS exam, they require their customers to submit a photocopy of their identity document for verification purposes [2]. This process is a significant privacy concern since anyone could replicate the uploaded document. Having no agency over their documents is of great concern for the end-users, making them reluctant to use the company services. Replacing the document upload with a digital signature check is more secure and less privacy undermining way of performing business.

After the EU introduced the eIDAS regulation, an alternative method for identity verification became available [3]. All EU member states are mandated to implement an eID solution in their country and recognize other countries' eID solutions. Each eID solution guarantees some degree of authenticity, from substantial to high, allowing for verification of a persons' identity via trustworthy means.

Particular risks exist that businesses must be aware of before integrating an eID authentication service. There are no comprehensive resources outlining the obstacles and costs of implementing eID authentication in the private sector at this point in time. Unknown risks are an excellent deterrent to innovation, making companies reluctant to use new technologies. Proper research into this subject may lead companies to take risks associated with implementing new technology and kickstart the mainstream adoption of eIDs in the private sector.

1.2 Research Problem

The main goal of the thesis is to investigate what options companies have if they wish to integrate eID authentication into their day-to-day businesses and if the advantages provided by eIDs are sufficient to outweigh the risks associated with adopting new technology. From this goal, the extracted research question is as follows:

What is the best eID authentication option available for an Estonian EU targeting enterprise for use in their Web-based Single Sign-On (SSO)?

To help answer this question, we would need to refine it into additional sub-questions:

- What advantages do eIDs provide?
- How should an existing authentication scheme change to support eID?
- What privacy considerations must companies take when processing user data?
- What are the different eID authentication providers available to Estonia's private sector?
 - How complicated is the solution to integrate?
 - What risks does the eID provider add or take away from the consumer company?
 - What is the market reach (in countries) of a given solution?
 - Where are the weak points in the protocol used, and how should the relying company address them?
 - How expensive is the solution to operate?

With these questions answered, it would be possible for any company to understand the risks and benefits of any eID solution and have a framework to compare them.

1.3 Scope and goal

There will be some assumptions about the company wishing to implement eID authentication in the thesis.

Company already uses an HTTP-based SSO (in the cloud or on-premises) Non-HTTP-based SSOs or other esoteric authentication systems will not be considered.

Company is committed to getting some form of eID authentication system in place

This means market research was done, and the management found that it is favorable to invest in eID authentication, as the users would adopt this authentication mechanism.

This thesis is only interested in the technological aspect of eID integration. Any legal, political, social or any other obstacles, if covered, will only be tangential.

The eID provider must be accessible by an Estonian company Other countries are also capable of providing eID solutions. However, for the scope of the thesis, only solutions originating from or heavily invested in Estonia will be considered.

1.4 Contribution

The thesis aims to fill the research gap on the use of eID in the private sector and provide a framework for researchers or people in managerial positions to compare different eID authentication providers.

The thesis contains the following contributions:

1. enumeration of eID service providers in Estonia;
2. analysis of personal data storage under GDPR for use on authentication;
3. comparison of the different approaches eID service providers can take for integrating cross-border authentication;
4. assessment of various data transfer protocols in use for eID authentication;
5. display of example on how a company could integrate an eID service into an SSO;
6. security assessment and disclose a vulnerabilities in analyzed eID authentication providers;

1.5 Structure of work

The document will consist of the following main chapters:

ISO standard to pick trust level for if companies even need it

What are different options in eIDAS, e.g. what is a QESSD

What are the differences between primary services and middlemen, advantages disadvantages

What are the weakpoints in the company structure

What is the research model?

Findings about ID Card, Dokobit, and eeID

Non web-based SSO?

Ponder about the advantages of middleware pseudominization? Say instead of personal code you get some arbitrary ID that matters only in the system

2 Background

2.1 Electronic identity eID

In Estonia, digital identity has been around for over 20 years [4]. The Estonian government issues ID cards preloaded with certificates that enable cardholders to identify themselves digitally. Estonia's early adoption of eID, the political focus on digital government, has led to over 89% of internet users accessing the e-government, making it the leading country in the EU [5]. This adoption rate is in stark contrast to another EU country - Romania, where the first easy access to eIDs came in the form of new chip ID cards in August of 2021 [6]. In that country, only 16% of internet users access government services online. The adoption of eIDs in other countries lands somewhere between these two extremes.

If a company wishes to implement eID authentication in a given country, it must realize the differences between the adoption rates. For some countries' citizens, the button "log-in with eID" will instinctively make them draw their smart card or other eID capable device, whereas, for others, it would confuse and repulse them. The eID authentication method may attract or repel potential clients depending on the country, and early adopters should be aware of this adoption gap.

eID adoption in Estonia and Lithuania On the surface, Estonia and Lithuania have the exact eID solutions: Bank Link, ID card, Mobile-ID, and Smart-ID. However, even with the same infrastructure, we see many inconsistencies even in the case of just these two countries.

Consider Lithuania. It is possible to connect from a centralized website (<https://epaslaugos.lt>) to access the country's public services [7]. Here it is possible to authenticate via bank link, ID card, and Mobile-ID. Smart-ID is not an option. The omission of Smart-ID is strange, as most banks support authentication via the three major eID providers, which include Smart-ID.

Some banks listed on the public sector gateway portal, like PaySera, provide significant security concerns. With that bank, it is possible to access the e-government services with only email, password, and a 2FA code sent to the registered person's phone number. For similar security concerns, Estonia's Information System Authority has taken steps to deprecate bank link [8] from use in TARA, Estonia's gateway to e-government.

In Estonia, all three major authentication options, ID card, Mobile-ID, and Smart-ID, can be used to access the e-government.

2.2 eIDAS

The eIDAS regulation [3] provided the groundwork for recognizing the signatures issued by other EU countries by imposing strict liability and mutual-recognition requirements.

source:
I did it
myself
02-27,
have
video
recorded,
will have
to blur

The regulation introduced the concept of a Trust Service Provider (TSP), which allowed relying parties to have a trust anchor. Before, with digital signatures, it was possible to verify that the person signed documents with a certificate and it was valid. However, there was no good way of ascertaining if a trusted authority issued the signing certificate, meaning that the certificate could have been fabricated somewhere up the trust chain. Failure to validate certificate signatures could have severe consequences [9]. Establishing trust is the purpose of TSPs, a list of which is maintained by EU member states.

The eIDAS regulation requires member states to establish eID systems and integrate them into a federal plan if they haven't already. This legislation is the origin of the eIDAS node network [10]. These nodes connect across country borders, allowing users to authenticate with the eID of their home (issuer) country in the host (current residence) country. The eIDAS authentication protocol redirects the authentication requests to the appropriate country, federating the identification process. For the institutions trying to target the EU market, this provides a significant advantage since access to one node would mean access to all nodes in the EU.

The main issue private companies encounter when accessing the network is the highly exclusive access. The eIDAS network is only concerned about connecting countries. How and who can access an eIDAS node is up to the member states to decide.

eIDAS notifications in Estonia and Lithuania For countries to communicate through the eIDAS node network, the governments must first notify the European Commission about what eID authentication methods they will provide [3]. Other countries can then use these methods to authenticate foreign citizens into their public services.

In the case of Estonia, the country has notified the European Commission about its smart card and Mobile-ID authentication methods in 2018 [11]. Smart-ID is not a permitted method of authentication in the context of eIDAS.

In Lithuania's case, only the smart card solution is allowed - no mobile sign-in methods have been notified [11].

The governments of these two countries have revealed a gap between what they consider to be a secure and trusted source of eID domestically and what they are willing to be held liable for in the more global context within the eIDAS network.

2.3 eID providers in Estonia

Applied Cyber Security Group of the University of Tartu maintains a list of e-services [12] that use at least one eID authentication method in Estonia. The following authentication methods were listed: Bank Link, ID-card, Mobile-ID, Smart-ID, TARA, and HarID.

While the list does not count Dokobit and eeID as primary eID providers, they list them as consumers of at least one of the aforementioned schemes. These services act as intermediaries, where users could indirectly authenticate with eID schemes.

2.3.1 Bank link

Banks have initially created this authentication method to provide close integration with e-commerce providers to receive risk-free payments [13]. Over time it saw an additional use case - a secure and trustworthy authentication method for the public and private services [14].

Researchers found that the bank link protocol, while applicable, was "extremely insecure" [15]. From March of 2021, RIA has disabled the use of bank link to access public services [8], which accounted for only 1 percent of all authentications, revealing its overall popularity.

Due to the lack of security auditing required to satisfy eIDAS, poor market reach, and no support from the government, this authentication method will not be discussed in the scope of this thesis.

2.3.2 Smart card (ID card)

ID cards are the most popular way to access their eID in Estonia, primarily due to the legal requirement of having one. The Identity Documents Act [4] states that all EU, not only Estonian, citizens residing in Estonia must hold an ID card, with which they can access public services online. Interestingly, this requirement caused the government to issue more ID cards than people are living in Estonia [16, 17]. Smart card functionality touches not only ID cards but residence permits and other government-issued cards as well [11].

There are no variable costs to allow a person to log in to websites with their smart card. For this authentication method, no per-transaction fees exist, as the certificate validity service (OCSP) [18] can be queried for free.

An end user's computer can extract an authentication certificate from their smart card with the help of special software, commonly distributed by the government agency responsible for maintaining the cards [16]. This certificate, once on the computer, can be sent to the private company's authorization server with Client Certificate TLS option [19] or with the use of a specialized helper library, using standard REST calls [20].

Qualified trust service provider for Qualified Certificates for e-signatures installs the certificates in ID cards [21], which ensures a high degree of certainty about the identity of the person authenticating.

A significant advantage of using a decentralized eID infrastructure, such as ID card authentication, is that there is no intermediary service in the operational process, allowing companies to skip going into expensive contracts with an eID service provider.

2.3.3 Mobile-ID

Five years after SK ID Solutions started managing ID cards for use in Estonia, they have developed a mobile phone-friendly way to access the users' eID for use in Estonia, and

Lithuania [22]. SK achieved it by extending the functionality of phone SIM cards by adding new applications on the microchip.

The price of using Mobile-ID for the service provider varies based on usage, starting from 10 euros per month (10ct per request) to costing over 5 000 euros, where the effective cost is under 1ct for request [23]. For the end-user, mobile operators can charge an additional fee for the use of this service [24].

Accepting Mobile-ID would allow companies to access the markets of two countries: Estonia, and Lithuania, as the technical implementation is identical.

Qualified trust service provider for Qualified Certificates for e-signatures installs the certificates in a particular variety of SIM cards, capable of supporting Mobile-ID [21], which ensures a high degree of certainty about the identity of the person authenticating.

2.3.4 Smart-ID

Smart-ID is the latest and fastest-growing way of accessing citizens' eID, working in all 3 of the Baltic States [25]. The protocol utilizes mobile phones as authentication, similar to Mobile-ID. Unlike Mobile-ID, however, it does not require specialized external hardware [26]. The authentication process is handled by combining the eID server and the end user's smartphone. Despite that, it still passed the eIDAS compliance audit for the requirement of ensuring the signature private key is "with a high level of confidence under sole control" of its owner [27]. After passing the audit, Smart-ID was recognized as a QSCD, allowing it to create QES in 2018 [28].

The price of using Smart-ID for service providers, much like Mobile-ID, varies based on usage, starting from 50 euros per month (10ct per request) to over 20 000 euros, where the effective cost is under 1ct per request, based on the total amount of transactions performed within a month [29]. For users, unlike Mobile-ID [24], there are no telecommunication operators involved, and there are no additional costs.

Implementation of Smart-ID would allow users to access the markets of three countries: Estonia, Latvia, and Lithuania.

Qualified trust service provider for Qualified Certificates for e-signatures users their data centers to hold part of the private key and certificate used to authenticate users [21], which ensures a high degree of certainty about the identity of the person authenticating.

2.3.5 TARA

TARA is Estonia's primary gateway for authentication to public services [30]. TARA provides the ability for users to sign in with any of the three primary eID methods of Estonia and with the eID schemes of other EU member states. The ability to authenticate with the systems of other countries is of particular interest, as it also doubles up as the official eIDAS node of Estonia [30].

Unfortunately for private businesses, the Estonian Information System Authority intends to limit the use of TARA to public services only [31].

Technical implementation for the consumer, unlike Mobile-ID and Smart-ID, will be much easier to implement, as it uses the well-adopted protocol of OpenID Connect [32, 33].

It is worth mentioning that while the underlying authentication methods have received proper eIDAS auditing and are backed by a qualified trust service, this and all of the following authentication methods have not been audited in compliance with eIDAS or the auditing was not made public.

TARA only acts as an authentication service. It would not be able to provide means of signing documents [32]. If the business is considering expanding to allow for online digital signing, an infrastructure like TARA would unlikely be a great choice.

2.3.6 eeID

Estonian Internet Foundation created the eeID service for the exclusive purpose of bringing eID authentication to the private sector [34]. It is a clone of TARA without it being Estonia's gateway for the eIDAS node network. The similarities mean that all points outlined to TARA apply to this service.

The service is new, does not have pricing tiers, and currently asks for 9ct per successful authentication request [35].

The vision of the said service is to allow users to access the markets of all EU countries. Currently, there are only fourteen countries with notified eID authentication methods [11]: Estonia, Germany, Italy, Spain, Belgium, Luxembourg, Croatia, Portugal, Latvia, Lithuania, Netherlands, Czech Republic, Slovakia, and Denmark. Currently, the cross-border authentication feature is disabled.

2.3.7 HarID

Estonian Ministry of Education and Research created this service for the youth of Estonia to access different educational institutions across Estonia [36]. ID cards are only legally required to be held by citizens over the age of 15 [4], so everyone under would be unable to access their school system. HarID accepts TARA authentication methods with the addition of username & password.

This authentication method is held exclusively for the education sector and will be skipped in this thesis.

2.3.8 Dokobit

In the initial list of services using eID in Estonia [12], one service stands out - Dokobit [37]. They provide services comparable to eeID in that they aggregate different eID

methods in Estonia (ID-card, Mobile-ID, and Smart-ID) and other countries. The primary difference between the two authentication providers is how they want to achieve their multi-national implementation goals. Dokobit relies on integrating each country's system individually, whereas eeID depends on using the eIDAS node infrastructure [34].

Pricing for Dokobit varies drastically, and the provided prices for the Baltic States [38] start at 50 euros per month (7.1ct per request), going down to 4.2ct per request at 500 euros per month.

Dokobit supports 11 countries: Estonia, Italy, Spain, Belgium, Latvia, Lithuania, Finland, Norway, Iceland, Poland, and Portugal [37].

UAB Dokobit is a trust service provider for Qualified validation of qualified e-signature. It means the service itself does not provide Digital Signature certificates, but eIDAS considers the results of verification of signatures trustworthy [21].

2.4 Authentication and QSCD

The requirements for Estonian ID cards make a clear distinction between "ADF AWP" and "ADF QSCD" applications [39]. Both software applications are loaded onto the smart card; however, only the QSCD application, guarded by PIN2, can create QES. Implication here is that for authentication with an ID card, a QSCD is not used.

The fact that smart cards do not use a QSCD for authentication does not mean that the certificate used was not audited under eIDAS. In practice, the same QTSP CA can and likely will issue both the authentication and the QSCD certificates (see figure 1). "Since the authentication certificate is issued under the same CA and the same Terms and Conditions, the certificate policy documents and other CA statements are applicable to both certificates" [40]. While eIDAS does not outline any requirements for authentication modules in the QSCDs, we will assume that the QTSP took the exact organizational and technical measures to protect the authentication key on the same physical device.

For different eID authentication schemes, companies have to assess the scheme's security on a case-by-case basis. For all of the methods analyzed in the thesis (Lithuanian and Estonian ID cards, Mobile-ID, and Smart-ID), the same QTSP signed both certificates - for authentication and signing. There seems to be no discernable benefit to issuing an authentication certificate with a different CA, so if a device offers both authentication and qualified signature creation functionality, it is highly likely that the authentication certificate is as trustworthy as the eIDAS compliant QSCD.

Special case: third-party providers When using an intermediary such as TARA (eeID) or Dokobit, the new eID provider acts as a new trust anchor. All rigorous eIDAS and QTSP auditing become irrelevant when using intermediary services, as systems are as secure as their weakest links. Companies must first look at the security auditing and the certifications of the intermediary; only then consider the security of authentication




Figure 1. Comparison of authentication (left) and signing (right) certificate issuer field

options the intermediary service uses.

2.5 Levels of assurance

The eIDAS regulation uses three assurance levels: low, substantial, and high. These levels refer to the degree of confidence about the claimed or asserted identity of a person [3]. These assurance levels map to levels 2-4 of ISO 29115 [41].

Not all authentication methods are equal. In the simplest case, the username and password authentication method is significantly weaker than username and password with multi-factor authentication (MFA) enabled. The eIDAS framework takes this concept and builds on it in two unique ways to construct a level of assurance (LoA) [42].

The first part of determining the eIDAS assurance level is related to the registration process. The legislation distinguishes different enrollment options, such as registering on an online self-service or going to the police office to receive a physical item. The levels of assurance over the person's identity are significantly different and warrant different assurance ratings.

The second part of determining the schemes LoA is analyzing the authentication process. Username and password is less secure than username and password with MFA enabled, and both are less secure than a physical cryptographic authentication device.

The game's name here is to make the user harder to impersonate. LoA maps as one would expect - the higher the security level, the higher the level of assurance.

Companies should investigate the data they are protecting and then see what level of assurance they would need. In most use cases, the assurance level of substantial will be more than enough.

2.6 GDPR

When dealing with eID, sensitive personal data processing is unavoidable. Two years after the EU enacted the eIDAS legislation, the EU parliament issued new legislation to consolidate all previous privacy laws [43].

In GDPR, companies must be aware of key terminology. Interested parties can find a complete list of definitions in article 4 of the regulation. The thesis will go over only the most critical keywords and concepts.

Personal data The eID solutions in scope all provide the following personal information: full name, serial number (national id), and country of origin.

Processing The minimal amount required to process information is to store uniquely identifying information that would link an eID to an internal id code. At the very least, this action involves collecting, storing, and retrieving personal data.

Processor and Controller In the minimal case, no third parties are involved, and the controller, the processor, and the recipient are the same entity.

2.7 Threats

In the sequence diagram (see figure 2), we see a generalized high-level overview of any eID authentication solution. In the authentication protocol, the relying party (company implementing eID sign-in) entirely depends on the eID Provider, which acts as a trust anchor. A communication channel exists between the relying party and the interface, which can be categorized into two groups:

1. trusted, where the sender can reasonably guarantee that adversaries are unable to change the data in transit (Smart-ID, TARA, Dokobit);
2. untrusted, where there is a significant possibility for data to be tampered with in transit (Web eID).




Figure 2. High-level sequence diagram of a eID authentication flow

Trusted communications commonly operate using an encrypted backchannel, whereas untrusted ones require the client to send data from the QSCD interface. Because the untrusted client sends the data, this becomes an untrusted channel, and the relying party must perform additional verification.

Failure to encrypt and establish the authenticity of the eID provider in a trusted backchannel or not validating data in an untrusted channel allows adversaries to perform man-in-the-middle attacks.

3 Related Work

3.1 National e-ID card schemes: A European overview

In 2008, researcher Siddhartha Arora investigated different uses of eID in Europe [44].

The technical report was published when the eID technology was still in its infancy, and the concept of eID was tied to it being linked to a physical ID card.

Paper references that eID cards offer three forms of information security functionality, each with an increasing level of security provisions: identification, authentication, and signature (see table 1). In this table, A is prover and B is verifier.

Table 1. Forms of information security functionality provided by eID [44, 45]

Identification (I)	A can prove to B that he is A, but someone else can not prove to B that he is A.
Authentication (A)	A can prove to B that he is A, but B can not prove to someone else that he is A.
Signature (S)	A can prove to B that he is A, but B can not prove to himself that he is A.

The idea of splitting functionality into identification, authentication, and signature can be traced to today’s Estonian [39], and Lithuanian [46] ID cards. In these cards, there are two certificates — one for client authentication and the second for digital signature.

These authentication and identification certificates are not encrypted, and can anyone with the correct tools can read them from the ID card. Signed documents also have a copy of the certificate attached. These certificates identify a person, but due to ease of replication, the recipient should not trust the sender’s certificate because there are no guarantees that the certificate belongs to the sender.

The authentication and signing certificates require their respective keys to perform asymmetric cryptographic operations. In theory, it is possible to sign documents with the authentication certificate; however, the verification software will reject such signatures because the certificate’s purposes would not include a digital signature.

Another topic the paper touches on is the possibility of having multiple eID schemes. The author spotlights Austria as they want to have various sources of eID, not limit themselves only to one card. Having multiple authentication methods was a novel concept at the time. Many countries followed suit, and in Estonia, there are three primary sources of eID. In France, a source of eID doesn’t even come from an ID card [47].

The paper’s conclusion emphasizes the importance of the eID itself, not ID cards. The EU took this path when implementing the legislation for eIDAS, which allowed easier integration of infrastructure member states already had in place.

3.2 The Austrian eID ecosystem in the public cloud: How to obtain privacy while preserving practicality

This paper explores what information the Austrian government stores on the issued identity documents and what operations the documents can perform [48]. Researchers identified four types of functionality: identification and authentication of Austrian citizens, qualified electronic signature creation, encryption and decryption, data storage. This functionality seems widely adopted as it matches Estonia's ID card.

Paper presented an interesting legal issue - Austria does not allow a person identifying code (CRR number) to be "used directly in e-Government applications due to legal data protection restrictions." The solution required Austria to create SourcePIN, a framework to develop different personal identifying numbers for each service trying to access it while hiding the original code [48, 49].

Authors express a big concern that everything goes through one single source of trust, which does not scale well. If many people wanted to use the system, it would quickly become a bottleneck. Moving many essential components to the public cloud can alleviate the problem.

The paper's main contribution to this thesis is to remind us that even though technological barriers are crumbling, there might still be legal obstacles to overcome. Austria is currently not part of the eIDAS node network, and it would be an excellent further research topic to investigate how Austria's eIDAS node operates.

3.3 Secure cross-cloud single sign-on (SSO) using eIDs

Researchers explore the possibility of users using an SSO system to log in via their eID instead of the traditional username/password authentication method [50]. As means of doing so, they explore the capabilities of the STORK framework and other frameworks seen in previously mentioned related literature. The STORK framework is the predecessor to eIDAS [51].

The idea of the STORK framework is that any EU citizen should be able to use their eID issued by their home country to authenticate with services in other countries. An example of an activity would be opening a bank with an Italian ID card. The paper suggests extending the framework to support federation so private business identity providers can use the security options provided by eIDs and not store weak passwords.

The paper shows a proof of concept prototype usage for bringing STORK to support SSO. Emphasis was given on the backward compatibility, not to require any breaking changes to an existing STORK protocol.

Researchers found that one SAML protocol, however similar they may be, is not compatible with one another. The consumer company wishing to implement the proposed protocol must develop an adapter application to integrate different identity providers,

such as STORK, Facebook, and Google. Before a protocol sees widespread mainstream adoption, facades will be required.

3.4 EID @ Cloud: integración de la identificación electrónica en plataformas europeas en la nube de acuerdo con el reglamento eIDAS.

This paper talks about integrating a new eIDAS node with the private sector in mind [52]. The eID@Cloud research initiative has proven it possible to allow private citizens to integrate this system to authenticate persons. Researchers emphasize that it does not mean ready for use and outline some issues that need addressing.

Even though the eIDAS node infrastructure brings apparent benefits to the citizens, the public, private entities, and the service vendors, there are still caveats that slow the final integration of the EU digital identity platform. The project eID@cloud shines light upon these barriers:

1. There are still some differences between the national schemes and the integrations of said national schemes in a unique and interoperable net that must be the eIDAS in the context of the EU.
2. The deployment of each eIDAS node of each member state happens at different speeds, creating mistakes and a lack of availability to complete the eIDAS project.

The interoperability testing consisted of accessing each partner's cloud platforms to verify the identities that belonged to the citizens of the other partners' countries. Norway's eIDAS node did not work with other countries' eID - the protocol executes correctly, but the user incorrectly received an error message asking for Norway identification. It shows that some parts of the system were not stable at the research time, but the whole infrastructure continued to run.

The eID@Cloud was a great project testing the implementation and readiness for public and private sectors, which provided excellent feedback for the EU Commission. The most important finding is that it found a way for private entities to connect to the mesh.

3.5 LEPS - Leveraging eID in the private sector

This final research [53] was performed at a similar time to the eID@cloud [52], but in different countries. LEPS researchers have implemented an eIDAS node for private customers. However, they also provided market analysis.

The market analysis targeted four main categories of e-service providers, who would be interested in integrating eID authentication:

1. Organizations that need or want to migrate from the existing identity and access management (IAM) solution. This could apply to organizations that have scaled out their internal or tailor-made IAM solutions or organizations that already use partially external or third-party e-identification or authentication services but are looking for a higher level of assurance (LoA).
2. Organizations that use low assurance third-party eID providers such as a social login want to elevate the overall level of security and decrease identity theft and fraud by integrating eIDAS eID services.
3. Organizations that are already acting or could be acting as eID brokers.
4. Organizations that want to open new service delivery channels through mobile phone and are interested in mobile ID solutions that work across borders.

In the case of the thesis, the targeted e-service providers are of the first category - organizations wishing to improve IAM solutions to include a higher level of assurance.

The researchers recommend using an approach like LEPS to integrate eID authentication rather than creating an eIDAS node. The primary reason for avoiding node creation would be the cost-effectiveness of implementation. These adopters "are unlikely to have the know-how, resources, and capacity to implement eIDAS connectivity." "Many organizations do not have resources for eID service implementation and operation internally was already exploited by social networks." The targeted benefit is the "easy way to integrate highly scalable, yet low assurance, eID services."

LEPS is a service similar to Estonia's eeID.

3.6 Federated Identity Architecture of the European eID System

The authors of this paper describe the current situation in the identity management landscape [54]. The researchers provide all the necessary background information to understand the implementation details of any eID authentication system design.

3.6.1 Authentication methods

The first significant contribution relates to explaining different ways of authenticating persons.

Any authentication method is based on something the user knows (password, pin code, answer to security question), is (biometrics - eyes, fingerprints), or has (physical device - key card, USB device) [55]. Any other method would leave the person without agency over the authentication process.

An emphasis is put on the importance of mixing and matching these authentication schemes to increase the system's security.

3.6.2 Authentication Paradigms and Models

The second helpful point of the paper is the description of different identity management paradigms and models [56]. Paradigms refer to the implementation and deployment, whereas models refer to the data storage and roles.

The three main paradigms are network, service, or user-centric. The network-centric approach gathers all identities into one place, usually known as a "Domain Controller." The service-centric method would create a new identity for each service, leading to high duplication. The user-centric paradigm makes the user prove their own identity. Europe's eID solution does not favor any of the paradigms allowing identity providers to innovate [4, 34, 37].

There are also three authentication models: isolated, centralized, and federated. Unlike paradigms, where any of them is fair game, Europe's identity providers can use only the federated one. The isolated model requires all services to hold a copy of every identity in the EU. The centralized model is suitable for having a central place for looking up identity in a country, and it is an excellent solution for high-profile agencies. The federated system can scale well horizontally (adding more servers would increase the network capacity) and not require keeping an index of all citizens it would like to serve, which is a tremendous advantage when considering the GDPR requirements.

3.6.3 Authentication protocols and services

Researchers have allocated a good portion of the paper to provide an overview of potential protocols and implementations. The list is massive and in-depth; however, it becomes clear that SAML [57], OAuth2.0 [58], and OpenID Connect [33] protocols are by far the most popular protocols to choose for implementation. The engineers behind the eIDAS network implementation decided to settle on the SAML protocol.



Figure 3. Initial system architecture

4 Architecture Definition

Redo the validation sections into 1) security requirements, 2) security requirement compliance by eID provider, 3) security requirement compliance by developers

4.1 System architecture

This section will look at our company's systems' current and desired states before and after integrating an eID provider. We will also declare common terminology used in the case studies, referring to the same server with the same name everywhere.

For namesake's clarity, the company wishing to integrate eID authentication is a physical exercise data tracking enterprise, **WorkAuth**.

4.1.1 System overview

Initial state In figure 3 we see a high-level overview of a system where we are trying to integrate eID authentication. This system consists of the following components:

1. AuthServer. The company's SSO. Acts as a central authority for identity. This server issues OIDC id tokens containing user ID numbers, roles, and claims. It is the primary access control mechanism.
2. SuperApp. A resource server with access control enabled. It uses OIDC id tokens issued by AuthServer and verifies them using cryptography or other means. It contains the data the company is trying to protect with stricter access control.
3. User store. A data store containing user log-in information - usernames, password hashes, other Personally Identifiable Information (PII).




Figure 4. System architecture after the inclusion of an eID provider

4. Actor. A person accessing the resources in the system. Typically can be anyone, including computers; however, in our thesis's scope, we will limit ourselves to only natural persons holding an eID.

Desired state The company WorkAuth wishes to implement eID authentication. Since the authentication is not done locally but is delegated to some remote service or device, the protocol can be treated as an external federated log-in. Application development frameworks such as ASP.NET Identity have helpful tools to handle external identity providers.

With the inclusion of an external eID provider, we can compose the new system architecture to be akin to figure 4. In this figure we can see two significant additions:

1. eID provider. It is WorkAuth's gateway to obtain someone's eID. It can be any eID source such as Dokobit, TARA, Smart-ID, or an ID card.
2. Remote key store. Storage for unique identifiers provided by the eID provider.

The primary purpose of the remote key store is to link the user ID used in the internal system with the unique identifier given by the eID provider. Because the unique identifier can change or the same physical person can have multiple eIDs [59], companies should foresee cases where numerous eIDs could map to a single internal ID.

In the diagram (figure 4), the key store has a red lock next to its icon. Depending on the country, the data stored there may be subject to strict privacy regulations. Companies must consider implementing strict access control for this part of the infrastructure.



Figure 5. System architecture after the inclusion of all eID providers in scope

Final state The end goal for the scope of this thesis is to implement three eID providers into the architecture. For regular companies, it would make sense to implement multiple only if they would like to get more coverage. Additionally, they could register non eID providers, such as Google or Microsoft social log-ins; however, we will not cover this in the thesis. The final high-level overview of the system can be seen in figure 5.

4.1.2 Process overview

For validation of the architecture, we will consider two use cases.

The first one (see figure 6) is concerned about accessing a protected resource with a token issued by the AuthServer. This use case validates the base state of the system.

The second use case (see figure 7) is also concerned about accessing a protected resource, but only those, who authenticate with a higher level of assurance, like an eID solution, would be able to access it. This use case validates the successful implementation of eID authentication and access control.

4.1.3 Linking eID to an internal user ID

Possible mess? Suggestions wanted.

There will be a need to uniquely link an identity to an internal account in the company SSO server. The security requirement, in this case, is not to allow other users to access the same account. For this goal, companies must use one or more person-identifying properties.



Figure 6. System behavior when authenticated with a username + password scheme



Figure 7. System behavior when authenticated with an eID scheme

Using Estonia's passport as a reference, we see that it has the following identifiers: (issuer) country code, document number, surname, given name, personal code, citizenship, date of birth, document date of issue, expiry, and authority. In these cases, it is easy to use the personal code for identifying a person as it is unlikely to change - people change names, documents expire. Document authority information and date of birth do not narrow it down nearly enough. The use of a personal number seems like an obvious choice.

Unfortunately, not all countries have personal numbers. If we look at Ireland's passport, we would be unable to find such a code. The lack of an id number shows one of the many challenges eID authentication adopters will face. If the data on the passport is all we would have, the next best unique identifier for linking users would be to use the document number. It is cumbersome and would require users to update the account with a new number when the document eventually expires and is replaced. Still, no other option satisfies the security condition requiring an eID to link only to the correct user as effectively as this one.

Fortunately, there is hope to avoid ambiguity in the digital world. European Telecommunications Standards Institute has identified the issue of countries having different people accounting systems and proposed a prefix system to account for it [60]. In their system, each ID code consists of a three-character identity type reference, followed by a two-character country code, a dash (-), and then the code unique in the country. Identity references include passport numbers (PAS), personal numbers (PNO), tax references (TIN), or even custom ones (XX:). Example of Estonian identity number under this system - PNOEE-30303039914.

If we look at the eIDAS node network, its architecture does not have strong opinions on how an ID should look, as long as it has a country code and a unique code inside the country. How countries achieve uniqueness is not of concern.

The eIDAS node architecture solves another issue of what to do if a person's identifier changes. A unique identifier remains "unchanged for the lifetime of the account" [59]. If an identifier were to change when "the user's digital identity is replaced or repaired," relying parties should treat the newly obtained identifier as a completely new identity.

eIDAS Unique Identifier Structure In eIDAS SAML Attribute Profile, an identifier code is defined as:

1. The first part is the Nationality Code of the identifier. Value is an ISO 3166-1 alpha-2 code, followed by a slash ("/").
2. The second part is the Nationality Code of the destination country or international organization. Value is an ISO 3166-1 alpha-2 code, followed by a slash ("/").
3. The third part is a combination of readable characters. This sequence of characters uniquely identifies the identity asserted in the country of origin but does not nec-

essarily reveal any discernible correspondence with the subject's actual identifier (for example, username, fiscal number, etc.).

Example: ES/AT/02635542Y (Spanish eID Number for an Austrian SP).

Summary Using the eIDAS Unique Identifier structure as a base, we can see that it is enough to uniquely identify a digital identity in eIDAS with the country of origin, country of destination, and a set of characters to identify that person in the origin country. The destination country will always be the same in our company's case. To uniquely identify a person, we will only need its origin country and a unique identifier a member state must provide.

For this thesis, identifiers will be marked as "{ISO 3166-1 alpha-2}/{Code provided by country}". Unique identifier examples: EE/38001085718, LT/49003111045, SE/870314-2391.

4.1.4 Privacy Policy

A company wishing to implement eID authentication will have to deal with personal information as described by GDPR [43]. Before going live with an eID solution, they must conduct a legal audit for compliance.

A privacy policy is a legal document and is way outside of the scope of a technical implementation thesis. However, it is still important to understand the basics. For this goal, two privacy policies will be analyzed: Web eID [61] and Dokobit [62].

From the cursory analysis of the two policies, there are three fundamental aspects our company needs to address: what data is processed, with whom the company shares the data, and what is the retention policy. An actual privacy policy varies drastically from case to case.

Based on the privacy policies of Web eID and Dokobit, we constructed a rudimentary privacy policy for the use of the test application environment. The thesis appendix contains a copy of the text.

4.2 Weaknesses in the architecture

When analyzing the weaknesses of WorkAuth's internal systems, it is good to understand their cause. Some vulnerabilities can appear due to existing issues, faulty implementation, or deeply rooted issues in the architecture itself. In this chapter, we will address these categories.

eID provider dependant weaknesses These threats come from one common issue: trusting an eID service provider when a relying party should not have. There are four primary causes:

1. relying party trusts an input from an insecure channel;
2. relying party does not perform the necessary validation mandated by the protocol;
3. inherent weakness in the architecture of the used transport protocol;
4. eID provider itself gets compromised;

The thesis will address these points on a case-by-case basis for each eID provider in the study. We will address each of these points in the case studies' respective chapters.

Local weaknesses In figure 4, four system components are not linked to a particular eID: AuthServer, SuperApp, application store, user store, and remote key store. We can identify weaknesses in those parts in this section. We will analyze each weakness through the lens of CIA security analysis.

4.2.1 SuperApp

[CI] Users can see and or edit data normally forbidden to access This issue is created by one of the following:

1. access control measures are disabled on a specific resource;
2. OIDC token validation is disabled or misconfigured;

The first cause has a trivial fix - developers have likely forgotten to enable the data access guard on the endpoint. It is unlikely that all authorization rules break.

In the case of the second cause, some corners were likely to be cut in the ID token validation process. When validating a token, the process has to match the one described in the OIDC spec [33] exactly. This process consists of three major parts:

1. check if the token's crypto algorithm is as expected;
2. validate token signature;
3. validate claims - issuer, audience, timestamp, nonce;

Developers usually need not worry about the process, as most frameworks have adopted the OpenID Connect protocol or have well-maintained libraries.

[A] Service becomes unavailable This threat is caused by one of the following:

1. server is offline or overloaded;
2. OIDC token validation is misconfigured to have an incorrect authority;

The first case is a common availability issue, meaning the server is suffering a denial of service attack. We will not cover the mitigation of this form of availability threat in the scope of the thesis.

A likely cause for the second part of this issue is the manually configured OIDC properties on the relying party. If possible, developers should never configure the properties manually and use the well-known metadata endpoint instead. A metadata endpoint usually looks like this - `https://auth.mycompany.org/.well-known/openid-configuration`.

4.2.2 AuthServer

All of the points that apply to SuperApp also apply to AuthServer. However, there is a critical use case that is worth mentioning explicitly.

[CI] Users can see used eID schemes and add new ones with unsafe log-in As per usability requirements, users must be able to assign multiple identity providers to their accounts. When adding a new external scheme, the currently logged-in user must have the same privilege level as the scheme they are trying to add. This countermeasure is in place if an adversary gains access to their account; they wouldn't be able to elevate their privileges by adding their eID scheme and signing in with it.

With this requirement in place, registration with an email and password becomes less valuable, as those accounts could never add an eID afterward. Companies can enact an exception to this security requirement for the first eID scheme a user would add. However, a better solution would be to have a company policy to verify the user's first added eID manually.

4.2.3 Data stores

All three data stores have the exact issues between them. For the sake of brevity, we will group them under the umbrella of *data store*.

[CI] Users have a less secure way of accessing the data store The system is as secure as its weakest link. If users or developers have direct access to the database while bypassing the eID authentication check, the security and assurance guarantees are worthless.

If there are alternative ways of accessing the database, companies must implement proper access rules that would be as secure as the one's eIDs provide. How companies can achieve that depends on what data storage options they use. The best option would be to completely close down external or internal access to the data stores.

[CI] Man-in-the-middle attacks While uncommon, some data stores are vulnerable to MitM attacks [63]. Although the best course of action would be to move the data storage server away from the internet and make it accessible only on the local network or via a VPN. However, in cases where an attacker has access to the internal network, even that is not enough. For maximum security, companies must implement the recommended MitM prevention techniques [64].

[A] Data is destroyed or lost Ransomware attacks and accidental database corruptions can happen, so offline remote backups are a must.

An interesting issue arises when companies should treat backups to the same security standards as live databases. One approach to ensuring data integrity and confidentiality would be encryption; keys should only be available after authenticating with an eID scheme. One equally secure alternative would be to use something like the encryption and decryption functionality of Estonia's ID cards.

5 Case Study: eeID

5.1 About

The Estonian Information System Authority has created TARA - a gateway for public sector services to integrate eID authentication easier and cheaper [31]. It is heavily inspired by the OpenID Connect [32] protocol to communicate between the service and relying parties.

The Estonian Internet Foundation has then created the eeID service - a clone of TARA, but with the intent to open it up for private businesses at a premium [34].

These services' goal is to use domestic eID providers (ID cards, Mobile-ID, and Smart-ID) and act as a gateway to the eIDAS node network.

Cross-border authentication supported by these schemes extends (or will soon extend) to the notified countries [11]. Currently notified countries (in order of time notified) include Germany, Italy, Croatia, Estonia, Spain, Luxembourg, Belgium, Portugal, Czechia, Netherlands, Slovakia, Latvia, Denmark, Lithuania, Malta, France, and Sweden.

At the time of writing, TARA does not support the eID schemes of the last three - Malta, France, and Sweden, and cross-border authentication is only in the planned state for the eeID service and is currently not supported.

5.2 Data Flow

The underlying data transfer protocol used by eeID is almost identical to OpenID Connect code flow [32, 33]. One irregularity exists between the OIDC spec and TARA, which makes the whole flow non-compliant to the spec [65]. Otherwise, the flow is identical. A high-level overview of this flow can be seen in figure 8. It consists of seven main steps:

1. Initial log-in. Preparation for redirect to the eID provider.
2. Redirection to the eID provider.
3. Authentication. Users log in with the chosen authentication scheme (ID card, Mobile-ID, Smart-ID, eIDAS).
4. Redirection back to the Auth server.
5. Browsing session verification. Cryptographically check if the request came from the same browser. This step is required to protect against CSRF attacks.
6. Token acquisition. The Auth server exchanges the received code for an identity token containing the user's information.
7. Signature verification. Verify the authenticity and validity of the received token.




Figure 8. OIDC code flow used in TARA/eeID

5.3 Trust Anchor

One of the main advantages of using eeID is the simplicity of integrating multiple sources of eID (ID card, Mobile-ID, Smart-ID, and eIDAS) with a single API. To accommodate this, eeID acts as an intermediary service, reading and reprocessing data to create a normalized response. With this approach, there are two issues: confidentiality and integrity.

Confidentiality issues occur whenever users do not wish to share their personal information with more parties than absolutely required. For example, if a user wants to authenticate with Smart-ID, only two parties should be involved: the company user is trying to log in to (WorkAuth) and the Smart-ID service provider (SK ID Solutions). With the eeID service, another entity is added between them who has full read and write to the data.

Integrity issues are caused by having that full access to data. Should the eeID service get compromised, attackers could impersonate anyone in all services relying on eeID.

Companies should keep these risks in mind when integrating the eeID identity provider.

5.4 Pricing

The operational cost when using the eeID identity provider is nine cents per successful authentication [35]. It is the highest price among all identity providers and does not have tiers. A thousand successful authentications would cost WorkAuth 90 €.

5.5 Security Requirements

The TARA documentation has an in-depth integration guide and the validation requirements clients must implement [32]. Additionally, RIA claims that the protocol used is mostly OpenID Connect compliant. Because of this, we can have two resources to validate the resilience of the architecture - TARA docs themselves [32] and IETF's OAuth 2.0 Security Best Current Practice document [66].

Communication channel The eeID service uses a secure communication channel, encrypted end-to-end using HTTPS. When the system is integrated correctly, malicious clients (or user agents) have no possible way of influencing any of the authentication parameters without triggering alarms when validating the request.

5.5.1 Protocol's built-in security features

OpenID Connect specifies three different flows - code, implicit, and hybrid [33]. In code flow, all sensitive tokens are handled via backchannel - a secure communications channel

where the user client is not involved. The implicit flow is the opposite - a client receives an identity token and sends it to the company's authentication server, which validates the signature. A hybrid flow is a mixture of the two. Security experts consider the code flow to be the safest option of the three [66]. Coincidentally, it is the only supported flow by TARA and eeID [32].

Replay attacks

- eeID will reject the second POST /token request with the same code.

Image
proof?

The developer does not have to implement internal state management to verify that a given session token was used only once. When combined with other countermeasures available, a replay attack becomes impossible to execute by any practical means. Mitigation measures provided by the eID provider are sufficient.

Insufficient Redirect URI Validation

- Changes in the registered OIDC application undergo manual verification by eeID employees.

The manual verification process is sufficient to mitigate this attack; it is impossible to test if countermeasures exist on the client registration interface used by the eeID service employees. Mitigation measures provided by the eID provider are adequate.

Credential Leakage via Referrer Headers

- eeID does not include third-party resources (javascript, image, or other); therefore, it cannot leak any query parameters to third parties.
- The company is required not to have any third-party resources on the authentication and redirect pages.

The eeID service does not leak credentials to third parties anywhere on their log-in page (all resources used in their service are from their domain, see figure 10). No mitigation measures are required.

Credential Leakage via Browser History

- Replay attacks are mitigated against, the only form of attack possible with this.
- The form post response mode is not supported. Not required, but it would prevent this form of attack completely.

It is possible for attackers to obtain authorization code, nonce, and state from the browser history, however for them to be able to use them, the relying party must be susceptible to CSRF attacks. Mitigation measures are sufficient only when CSRF mitigation is in place.

Name	Status	Domain	Type	Initiator
ExternalLogin?returnUrl=%2F	302	auth.eid.gedas.dev	document ...	Other
authorize?client_id=oidc-b0669946-896...	302	test-auth.eeid.ee	document ...	auth.eid.gedas.dev/l...
login?service=https%3A%2F%2Ftest-aut...	200	test-auth.eeid.ee	document	test-auth.eeid.ee/oj...
main.css	200	test-auth.eeid.ee	stylesheet	login?service=https...
eis_logo_eng_rgb_horizontal.png	200	test-auth.eeid.ee	png	login?service=https...
main.js	200	test-auth.eeid.ee	script	login?service=https...
cef-logo-en.svg	200	test-auth.eeid.ee	svg+xml	login?service=https...
roboto-regular-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
roboto-medium-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
roboto-bold-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
login?service=https%3A%2F%2Ftest-aut...	200	test-auth.eeid.ee	document	Other
main.css	200	test-auth.eeid.ee	stylesheet	login?service=https...
eis_logo_eng_rgb_horizontal.png	200	test-auth.eeid.ee	png	login?service=https...
main.js	200	test-auth.eeid.ee	script	login?service=https...
form-check.js	200	test-auth.eeid.ee	script	login?service=https...
roboto-regular-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
roboto-medium-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
roboto-bold-webfont.woff2	200	test-auth.eeid.ee	font	test-auth.eeid.ee/stv...
cef-logo-en.svg	200	test-auth.eeid.ee	svg+xml	login?service=https...
login?service=https%3A%2F%2Ftest-aut...	302	test-auth.eeid.ee	document ...	Other
callbackAuthorize?client_id=oidc-b0669...	302	test-auth.eeid.ee	document ...	login?service=https...
authorize?client_id=oidc-b0669946-896...	302	test-auth.eeid.ee	document ...	test-auth.eeid.ee/oa...
signin-tara?code=OC-131-rZmyzx2qMU...	(failed)	auth.eid.gedas.dev	document	test-auth.eeid.ee/oj...

Figure 9. The eeID service does not use resources outside of their domain in the authentication flow




Figure 10. Authorization code is leaked inside the browser history when using eeID authentication




Figure 11. CSRF/Code injection mitigation in OIDC code flow

Authorization Code Injection and Cross-Site Request Forgery

- The use of state parameter prevents CSRF, but not code injection attacks. Because the state is not bound to an authorization code, an attacker can perform a high-tech attack (such as MitM) and inject their code into someone else's user agent or steal someone else's code.
- The eeID service optionally supports the OIDC nonce parameter, fixing the injection attack. When a company redirects the user to the authorize endpoint, a nonce parameter will be bound to the given code response. After the relying party receives the identity token, they can check if the nonce parameter matches the one sent initially. If they are not, an attacker likely has injected a session token.

Figure 11 illustrates this mitigation well. Because an attacker does not have access to both authentication requests (1 and 4), they would be unable to influence either nonce or state. If the relying party validates the integrity of both nonce and state, mitigation measures are sufficient to protect from both CSRF and code injection attacks.

Clickjacking

- The eeID service's auth page does not use Content-Security-Policy, however it does use header X-Frame-Option: DENY (see figure 12).
- Relying party should integrate this or a similar countermeasure.

▼ Response Headers View parsed

```
HTTP/1.1 200 200
Date: Sat, 02 Apr 2022 07:45:59 GMT
Server: Apache/2.4.38 (Debian)
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
Strict-Transport-Security: max-age=15768000 ; includeSubDomains
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-XSS-Protection: 1; mode=block
X-Application-Context: cas:standalone
Content-Language: en
Vary: Accept-Encoding
Content-Encoding: gzip
Keep-Alive: timeout=5, max=99
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: text/html; charset=UTF-8
```

Figure 12. Response headers browsers receive when opening the eeID service’s login page

Mitigation measures are sufficient on almost all browsers released in the last ten years [67].

5.5.2 Validation requirements for the relying party

In the previous section, we saw the security features of the protocol. The relying party should implement validation and reject requests for some of the features if those validations do not match. This section will contain all of the features the RP needs to address.

Misconfiguration Attacks

Incorrect OpenID Configuration The relying party should make sure to use the correct OpenID Connect discovery document. For test environment the URL is `https://test-auth.eeid.ee/oidc/.well-known/openid-configuration`, and for production - `https://auth.eeid.ee/oidc/.well-known/openid-configuration`. A connection with a malicious party could be established when using the incorrect URL.

Developers should make sure these values are not easily editable (such as placed in environment variables) by anyone. Best they should be hardcoded in the application.

Weak TLS configuration TLS is the primary defense mechanism against MitM attacks when connecting to the eeID servers. WorkAuth’s IT Ops team should ensure

that the server does not trust any malicious CA.

Authorization Code Injection and Cross-Site Request Forgery The primary validation user has to implement is protection against CSRF and code injection. Developers can accomplish this by using the state and nonce parameters of the protocol.

Attack description For reference to how the mitigation works, we will use the figure 11. We will provide three examples for the countermeasure: no state and nonce, strong state and nonce, and strong state and nonce. Because eeID and TARA both require sending the state parameter, for this example, we will use a weak constant state string, such as "x".

Our attack exists on the third step of the OIDC code flow - right after the user agent receives the redirect response but before they are redirected. An attacker can stop a request by changing the victim's firewall settings to block the WorkAuth servers and would be able to extract the authorization code from the browser history. This attack, however, is just a single example of countless similarly creative attacks.

Attack #1 - No state and no nonce After the user agent gets redirected, the attacker can extract both code and state. If no session binding is performed, they can use the URL themselves and authenticate with the victim's identity.

Attack #2 - Strong state without nonce This attack is similar to the first example but with the introduction of user agent session binding. The relying party, before they redirect the user agent (step 1 response in figure 11), would issue a cookie on who's value the state parameter depends. An example would be to have a session token, a regular 32-byte random string, and the state parameter would be an SHA-256 hash of that string. Attackers would not be able to reverse the hash to fabricate the cookie, and if the server, when validating the request, notices that the hash of the session cookie does not match the state, it would reject the HTTP request.

A way to circumvent this for attackers would be to use two sessions. Attackers would create a session with the relying party and wait for a victim. The victim creates a session, gets redirected, and authenticates. After the victim tries to return, the attacker stops them, takes only their authorization code, and puts it in their request. When the relying party validates the request, it would see that the attacker's cookie's hash matches the attacker's state parameter.

Attack #3 - Strong state with nonce To protect against authorization token injection, the relying party must bind the user agent session to the state parameter and the identity token (the result of consuming the authorization code). The relying party can achieve this by using the nonce parameter.




Figure 13. Adding OpenID Connect provider to Amazon Web Services

In step 6 of figure 11, we see that if we use the nonce parameter, additionally, we receive a nonce value in the identity token. This value exactly matches the one sent in the initial authorize request (step 2). If we store nonce and state inside of a user agent cookie, we can see that this prevents the previous attack, as it required victims to create a session themselves, and by doing so, they would generate a nonce that would be different than the attackers. Unlike the state parameter, they do not know what nonce was used and are unlikely to guess.

If the attackers manage to guess the nonce, they would also be required to update their user agent cookie. For relying parties to protect against this attack, they can encrypt this cookie to prevent external tampering.

5.6 Integration

The best way to integrate the eeID service would be to use existing OpenID Connect implementation options. Cloud hosting giants Amazon Web Services and Microsoft Azure offer an easy way to incorporate an OIDC provider (see figures 13, 14). Alternatively, there are many officially certified services and libraries developers can use [68].

This thesis will use Microsoft's official ASP.NET Core library [69].




Figure 14. Adding OpenID Connect provider to Microsoft Azure

Manual integration If, for any reason, the use of libraries is not available or acceptable, developers can integrate the OpenID Connect protocol themselves. They do not have to integrate the whole protocol, just the code flow. For reference, we will use the source code from the .NET library [69] and the TARA documentation [32]. The steps listed will be as seen in figure 8.

Login This step is all about user agent session binding and authorize URL generation. This is a multipart section so each part will be split into its own paragraph.

For the authorize endpoint URL generation is best to look at chapter 4.1 of TARA documentation [32]. There are, however, some notes to keep in mind when integrating the eeID service:

- <https://auth.eeid.ee/oidc/.well-known/openid-configuration> contains all of the necessary information to realize which endpoints to use and what values are currently accepted.
- <https://test-auth.eeid.ee/oidc/.well-known/openid-configuration> contains the configuration for the eeID test environment.
- `response_type`: the only flow supported by TARA/eeID is code flow, so this value can only be code.

- `nonce`: although not required, it protects against authorization code injection attacks and should be used whenever possible [66]. See previous chapter for more details.
- `ui_locales`, `acr_values`: these fields are non-standard, and most if not all libraries will not support them out of the box. For most use cases, these values can be left empty.
- `code_challenge`, `code_verifier`: Proof Key for Code Exchange (PKCE) is not supported, `nonce` should be used in its place.
- `response_mode`: not supported, therefore only response mode of query can be used.
- `nonce`, `state`: both `nonce` and `state` have the exact behavior (see Discovered Weaknesses section for more information).

With this information, we can extrapolate a working authorize request (see listing 1).

```
GET https://test_auth.eeid.ee/oidc/authorize?

client_id=oidc_b0669946_896b4cdf_a478_a60afd5c18a5_20&
redirect_uri=https%3A%2F%2Fauth.eid.gedas.dev%2Fsignin_tara&
response_type=code&
scope=openid&
nonce=CWWLeSzn5tyu3XCSUTIz_BQJgnFxu7US&
state=J5BpaPNynnbhZCWmDICZc5QWznVyIfebYGkZ3...
```

Listing 1. The eeID service authorize endpoint request

Before redirecting the user to the authorize endpoint, it is essential to bind the `nonce` and the `state` to the user agent session. We accomplish this by attaching an encrypted cookie to the response, which the user agent will save before it gets redirected.

Authorize and Second log-in When the user agent redirects the user to the eeID service authentication page, they can choose any authentication option. This process is not relevant to the thesis.

Callback: verify state After the user finishes authentication with the eeID service, they are redirected to the `redirect_url` defined in the request with particular query parameters (see listing 2). Note the inclusion of `nonce`, as this value should not be here [70] (see Discovered Weaknesses section), and we will ignore it for the rest of this section.

```
GET https://auth.eid.gedas.dev/signin_tara?

code=OC106_2hUkp91Z2acDYJF7PUFjDoTJKkHncVYl&
```

```
nonce=CWWLeSzn5tyu3XCSUTIz_BQJgnFxu7US&
state=J5BpaPNynnbhZCWmDlCZc5QWznVyIfeyYGkZ3 . . .
```

Listing 2. The eeID service authorize redirect response

The WorkAuth's server's first step is to verify if the state received in the callback matches the one stored in the user agent session. If it does not, it was a possible CSRF attack, and the process should end here.

Callback: acquire token Once the authorization server that the state matches the user agent session, it is safe to exchange the received code for an identity token. See listing 3 for a request example.

```
POST /oidc/token HTTP/1.1
Host: tara.ria.ee
Content-Type: application/x-www-form-urlencoded
Authorization: Basic b2lkYyliMDY2OTk0Ni04OTZiLTRjZGYtYTQ3OC1hNjBhZmQlYzE4YTUtMjA6aHR0cHM6Ly95b3V0dS5iZS9kUXc0dzlXZ1hjUQ==

grant_type=authorization_code&
code=OC1062hUkp91Z2acDYJF7PUFjDoTJKkHncVYl&
redirect_uri=https%3A%2F%2Fauth.eid.gedas.dev%2Fsignin-tara
```

Listing 3. The eeID service token request

The inclusion of `redirect_uri` here may be confusing. It is required as per the OAuth2 spec (section 4.1.3) [58] and prevents open redirection attacks when using wildcards. The eeID service does not appear to allow them, so the inclusion of this value is redundant; however, if it were excluded, the protocol would no longer be OpenID Connect compliant.

Callback: verify token In the unlikely event the token endpoint request failed, it could mean a sophisticated replay attack could have taken place. If an access token was already issued for that code, it must be immediately revoked. Another way for the request to fail would be if the client or user agent took too long to be redirected. If the token endpoint returns a faulty result, the authentication process should stop.

If the token endpoint returns the identity token successfully, the user should validate its authenticity. If the nonce parameter was used in the first request, the server should verify that nonce in the user agent session matches the one in the `id_token`. The rest of the verification should be done as described in the TARA documentation [32].

I have no clue about the benefit of performing additional verification. The token was received within a secure backchannel, and the nonce matches, meaning the user created the request. If the server makes the user agent session in a way so that no one other than the server itself can tamper, why bother verifying the rest?

Issue access token After the server verifies the identity token, issue a new access token with the necessary information from the identity token. The most common solution would be to create a new cookie and attach it to the response.

5.6.1 Discovered Weaknesses

Incorrect implementation of at_hash In the TARA Technical Specification [32], the identity token has at_hash value that is not according to the OIDC spec [33].

When looking at the id token response, it has a property at_hash with the value of X0MVjwrmMQs/IBzfU2osvw==. This value is supposed to be base64url encoded. Instead, it is a regular base64 string. The Demo REST Client example provided by the same authors [71] correctly converts the base64 value into the base64url encoded value, which leads us to believe that there is a mistake in the documentation and or implementation. If it was following the specifications of the TARA documentation and not OIDC spec, it should have no reason to do so.

The eeID service follows the TARA documentation, and because of that, the at_hash uses base64. An issue arises when the using OpenID Connect libraries (see listing 4).

```
IDX21348: Validating the 'at_hash' failed , see inner exception .
IDX21300: The hash claim: 'UtsKV8+hA/bB0EE/xR9cCQ==' in the
id_token did not validate with against: 'AT 95
VU6Y2LZjrNrVCdhIEaCxG6Gpzt0RsE Z', algorithm: 'RS256'.
```

Listing 4. Microsoft.IdentityModel.Protocols.OpenIdConnect fails to validate at_hash

If we compute the hash manually, we see precisely why the verification failure happens (see listing 5). The implementation expects a different string than was provided. The same transcoding behavior is seen on the TARA Demo Client [71].

```
user@localhost:~$ access_token="AT 95
VU6Y2LZjrNrVCdhIEaCxG6Gpzt0RsE Z"
user@localhost:~$ echo n $access_token | openssl dgst binary
sha256 | head -c 16 | base64
UtsKV8+hA/bB0EE/xR9cCQ==
user@localhost:~$ echo n $access_token | openssl dgst binary
sha256 | head -c 16 | base64 | tr '/+' '_' | tr -d '='
UtsKV8 hA_bB0EE_xR9cCQ
```

Listing 5. Verifying at_hash manually

The implication of this discovery means that all working clients who use eeID have incorrect OpenID connect implementation. This issue affects only those who use the correct OpenID Connect implementation libraries.

The reason for the incorrect implementation stems from backward compatibility [65].

Confusing state and nonce behavior Nowhere in the OpenID Connect specification mentions that state should be transferred over to the id_token. TARA confused the purposes of state and nonce properties, extended the behavior to cover each other, and, by extension, made one of the properties obsolete.

The state property is part of the underlying OAuth2.0 specification, where it is an "opaque value used by the client to maintain state between the request and callback" [58]. The primary security feature is to prevent CSRF attacks [58, 66].

The nonce property is part of the OpenID Connect specification, and its primary purpose is to prevent replay attacks when using implicit or hybrid flows [33]. Later, researchers discovered that it could also protect against authorization code injection attacks with the code flow. The disadvantage of using nonce as a state parameter is that it directly influences the size of the id_token, which should be kept as small as possible. The reason for keeping this token as small as possible is so that developers could later send them in request headers to their resource servers [72]. The only issue is that these tokens expire after 40 seconds and cannot be refreshed [32], making this approach impractical.

If we look at the data flow diagram (see figure 15), we see that both state and nonce have each other's properties. After the user agent returns to the callback URL, both nonce and state are returned when only state is required. After the company's authentication server establishes a backchannel and redeems the code for an id_token, this token again contains both nonce and state when only nonce is required.

In the security analysis performed last year, a researcher suggested removing the nonce parameter from the protocol [73]. We disagree with this approach and would suggest removing the state parameter from the id_token response. Removing the nonce parameter and having no support for PKCE would break OIDC compliant libraries' ability to mitigate authorization code injection attacks.

Wrong claims in the OpenID Connect discovery endpoint The discovery endpoint provides all information about possible requests and responses. The data listed there does not match the documentation. For example, in the discovery endpoint for eeID (<https://auth.eeid.ee/oidc/.well-known/openid-configuration>), claims like gender are present, even though this claim can never appear. On the flip side, the claim profile_attributes, as described in the documentation, is missing from the discovery document.

should I include token and .well-known response example here?




Figure 15. The incorrect OIDC code flow used in TARA/eeID

5.7 Case Study: Dokobit

5.7.1 About

Dokobit [37], trademark and subsidiary of Estina [74], offers two products: Document Signing Portal and API solutions.

The first product, the Document Signing Portal, was released in 2014 [75]. The primary purpose of this solution is to allow users to upload documents and digitally sign them online.

Estina has acquired the DigiDoc portal (<https://digidoc.ee>) from SK ID Solutions in 2016 [76] which had the exact purpose. This portal should not be confused with the similarly named DigiDoc4 client Estonians commonly use to sign documents [16].

The second product, API solutions, targets businesses in a variety of scopes: signature collection, signing, identification, sealing, and TSP monitoring [37]. In the thesis, we will only consider the Identification service.

Dokobit's Identification service allows Lithuanian, Latvian, Estonian, Finnish, Norwegian, Icelandic, Polish, Belgian, Portuguese, Spanish, and Italian [37] users to authenticate themselves with their countries' scheme.

The company has received ISO/IEC 27001:2013 certification [77] and in 2020 was included in the EU Trusted Service List [21, 75], thus it becoming a Qualified Trust Service Provider.

In 2021, the Norwegian electronic identity solutions provider company Signicat AS acquired UAB Dokobit.

5.7.2 Dokobit Identification Service

Identification service supports two distinct data flows: Gateway and API. The core difference between them is that the Gateway uses a prebuilt UI on their server. In contrast, the API requires the companies to develop their UI and have their server communicate with Dokobit servers instead. This difference only affects the user experience.

The main advantage of Identity Gateway over Identity API is the added brand trust. A study finds that users "associate higher security feelings with a higher level of brand trust" [78]. If an organization has not matured yet as a brand (such as a recent startup), it will make more sense for them to choose Identity Gateway over API. On the contrary, if they are a large, highly trusted organization, such as a bank, it would make more sense to use Identity API and have all user interactions happen on the same domain.

For this thesis, we will only analyze the Identity Gateway in depth.

Embed or Redirect Identity Gateway comes in two primary user flows: embedded and redirect-based.

In embedded flow, users could stay on the website, authenticate in a pop-up modal, and update the website view accordingly after finishing the authentication process.

Embedded flow has the advantage of not requiring the users to leave the website, which is helpful to preserve user data in complex forms.

In redirect-based flow, users are sent to an external website, perform authentication, and redirect to the company website, in a flow similar to OAuth2.

Ultimately, experts consider the embedded flow to be the weaker of the two methods [79] for two main reasons:

1. Cross-origin requests are inherently more dangerous, allowing for MitM and CSRF attacks;
2. The client application, even when embedded, receives full client credentials, which adds another point of compromise in the form of XSS;

When using federated sign-in for Native Apps, "best current practice requires that native apps **MUST NOT** use embedded user-agents to perform authorization requests" [80]. This practice means that companies who have a mobile app or would consider having one in the future mustn't use Embedded flow.

5.7.3 Data Flow

This section will analyze Dokobit Identity Gateway, redirect-based user flow, the general overview of which can be seen in figure 16. We can group the authentication process into three parts: establishing a session with Dokobit, user authentication with an eID provider, and user information retrieval.

Establishing a session with Dokobit When a user requests to authenticate, the company's back-end systems' first step is to establish a session with Dokobit Identity Gateway. To do this, a POST request must be made to the `/api/authenticate/create` endpoint. This response will contain the session identifier and the redirect URL. Users will have to go there to interface with their eID providers.

Sample HTTP request data can be seen in listing 6.

```
Request :
POST https://id sandbox.dokobit.com/api/authentication/create?
    access_token=YOUR_ACCESS_TOKEN
{
    'return_url': 'https://id sandbox.dokobit.com/example/success.
    php'
}

Response :
{
    "status": "ok",
```




Figure 16. Dokobit Identity Gateway - Redirect-based user flow [81]

```

"session_token": "02
f922c9917231ea8acbbbcf63796924af548c801d75772f2b1701b413462c61
",
"url": "https://id-sandbox.dokobit.com/auth/02
f922c9917231ea8acbbbcf63796924af548c801d75772f2b1701b413462c61
",
"expires_in": 3600
}

```

Listing 6. Handling Dokobit session creation

User authentication with an eID provider After the back-end successfully creates a session, they must redirect the user to the received endpoint. An easy way to accomplish that is to respond to the initial authentication request with HTTP status 302 - Found.

Most of the heavy lifting with authentication is delegated to this step and handled by Dokobit. The company's back-end systems should wait for the user to return after authenticating.

User information retrieval After the user returns after successful authentication, the back-end servers should make a GET request to /api/authentication/session_token/status endpoint. The company can securely receive the user information via a backchannel.

Sample HTTP request data can be seen in listing 7.

Request :

```
GET https://id_sandbox.dokobit.com/api/authentication/SESSION_TOKEN
/status?access_token=YOUR_ACCESS_TOKEN
```

Response :

```
{
  "status": "ok",
  "certificate": { ... },
  "code": "30303039914",
  "country_code": "lt",
  "name": "DEMO",
  "surname": "SMART ID",
  "authentication_method": "smartid",
  "date_authenticated": "2019 05 06T12:15:34+03:00"
}
```

Listing 7. Handling Dokobit session creation

5.7.4 Trust Anchor

Dokobit assumes the role of being the trust anchor. This means that it also acts as a single point of failure. Should Dokobit become compromised, all applications using Dokobit will become susceptible to impersonation. On the flip side, there is only one system company developers need to implement, meaning that it would be harder for adversaries to break into the system via external means.

Companies should consider the risks when using a provider capable of dictating who the person is, as no integrity checks are supported in the protocol.

5.7.5 Pricing

Dokobit is a commercial product, and therefore it has associated usage costs. In 2022, these costs are as seen in the table 2.

Table 2. Dokobit Identity Gateway pricing 2022

Plan	Number of transactions	Monthly fee	Price per extra transaction
1	700	50 €	0,071 €
2	1 600	100 €	0,063 €
3	5 000	250 €	0,050 €
4	12 000	500 €	0,042 €

Each pricing tier includes a specific number of transactions and adds a cost for each transaction exceeding it. For example, if the total amount of transactions is 200, the price will still be 50 €, as the number of transactions hasn't reached 700.

Assuming the company's users authenticate around 25 times per month, the monthly user price will be in the ballpark of 1-2 €.

5.7.6 Security Analysis

Actors The actors in the figure 2 assume the roles of the following: QSCD Interface - Dokobit Identity Gateway; QSCD - eID solutions registered on Dokobit.

In the case of Dokobit Identity Gateway, developers should not be concerned about the QSDC used, as the QSCD interface - Dokobit will provide the user's identity in a standardized form.

Communication channel The Dokobit identity gateway uses a secure communication channel, encrypted end-to-end using HTTPS.

Validation requirements Unlike eeID and Web eID, Dokobit does not provide validation requirements documentation, so the relying party and developers must be aware of protecting themselves from common authentication attacks.

Because the idea behind authentication is similar inflow to OAuth2, the thesis will use the current security best practices document [66] and assess which measures developers should be aware of and which ones have been addressed by Dokobit. A detailed explanation of each attack can be found on the IETF document.

Dokobit issues client secrets - API tokens for creating sessions and obtaining user information after the authentication.

Replay attacks

- Identity Gateway will reject the second GET request with the session token.

The developer does not have to implement state management to verify that a given session token was used only once. Mitigation measures are sufficient.

Insufficient Redirect URI Validation

- The adversary does not have any agency over redirect URI after authentication, as the authorize endpoint does not have any query parameters.
- The `redirect_url` parameter when sending the initial request outlined in step 3 of the sequence diagram cannot be longer than 255 ASCII characters.
- The redirect URL is never validated on the Dokobit servers, as it was never registered as a client. Each redirect URL is generated for one-time use.

Adversaries cannot influence the redirect URI. Mitigation measures are sufficient.

Credential Leakage via Referrer Headers

- Dokobit Identity Gateway does not include third-party resources (javascript, image, or other); therefore, it cannot leak the session token.
- The company is required not to have any third-party resources on the authentication and redirect pages.
- The client is using a secret API key, rendering it impossible to obtain private information without its use.

Dokobit does not leak credentials via Referrer Headers, and the developers should not embed third-party resources in the critical authentication pages. Mitigation measures are sufficient.

Credential Leakage via Browser History

- Session tokens are stored in browser history; however, they are single-use only and are immune to replay attacks.
- User personal information details are never exposed to the client.

The only thing adversaries could extract from the browser history is a used-up session token, which does not provide much value. Mitigation measures are sufficient.

Session Token Injection and Cross-Site Request Forgery Adversaries would perform the injection and CSRF attacks identically.

- The protocol does not protect against session token injection attacks.
- The protocol also adds more attack surfaces by issuing the session token before the user signs in, allowing the adversary to obtain or inject it before and after the user performs authentication.
- It is possible to mitigate adversaries stealing a victim's session.
- **It is impossible to mitigate adversaries injecting their session** (phishing).

Identity Gateway protocol does not have security measures built-in against session token injection or CSRF attacks. It is possible to prevent adversaries from being able to redeem the victim's session. However, there is **no possible way to prevent adversaries from injecting their Dokobit session**.

From the attacker's point of view, they can exploit this vulnerability by performing these steps [82]:

1. Establish session with identity server and Dokobit;
2. Trick the user into opening the link issued by Dokobit;
3. After the user authenticates, but before gets redirected, reload the page;
4. If an adversary managed to do it in time, they receive that person's access;

The only way to mitigate this attack for the user will be to make the authentication server invalidate the authenticated session if a request presents the same session_token. Thankfully, it is easy to detect if the server has consumed the session token already, as Dokobit would reject additional requests, as described in replay attack mitigation.

Mitigation measures are **weak**, and developers should be ready to implement authentication session revocation.

Client Impersonating Resource Owner

- Dokobit does not allow users to choose their id or secret.

Dokobit made it impossible to perform this attack. Mitigation measures are sufficient.

Clickjacking

- Dokobit auth page does not use Content-Security-Policy, however it does use header X-Frame-Option: SAMEORIGIN.
- Framebusting [83] techniques were not discovered.

Mitigation measures are sufficient on modern browsers.

5.7.7 Discovered weaknesses

When analyzing and implementing the protocol, two weaknesses were discovered that developers should be aware of and mitigate.

Session binding The Dokobit Identity Gateway protocol is simple and resilient to most forms of attacks out of the box. However, developers should make sure to enforce session binding. Adversaries can perform this attack by going through the following steps:

1. Adversary establishes an authentication session with the server, and by extension, Dokobit. They receive a Dokobit session_token.
2. Victim establishes an authentication session with authentication session.

3. Adversary tricks the user into using their session or injects their session token by other means.
4. Victim authenticates on Dokobit with adversary's session token.
5. Adversary finishes the session and successfully impersonates the victim.

Developers can mitigate this session token injection and CSRF attack by binding the Dokobit session to the browsing session. When the user returns from Dokobit Identity Gateway, the return URL will have the session token attached in the path. If the authentication server can verify that the same browser has sent the session token and created the session, it would be possible to eliminate this attack.

It is possible to eliminate this attack using encrypted cookies with the session_token attached (see listings 8, 9).

```
protected override async Task HandleChallengeAsync(
    AuthenticationProperties properties)
{
    if (string.IsNullOrEmpty(properties.RedirectUri))
        properties.RedirectUri = OriginalPathBase + OriginalPath +
            Request.QueryString;

    var body = JsonSerializer.Serialize(new { return_url =
        BuildRedirectUri(Options.CallbackPath) });
    var response = await ExecuteRequestAsync(HttpMethod.Post, "/api
/authentication/create", body);

    response.EnsureSuccessStatusCode();
    using var sessionResponse = await JsonDocument.ParseAsync(await
        response.Content.ReadAsStreamAsync(Context.RequestAborted))
        ;
    var root = sessionResponse.RootElement;

    properties.Items["session_token"] = root.GetString("
        session_token");

    Response.Cookies.Append(Options.StateCookie.Name!, Options.
        StateDataFormat.Protect(properties), Options.StateCookie.
        Build(Context, Clock.UtcNow));
    var redirectContext = new RedirectContext<DokobitOptions>(
        Context, Scheme, Options, properties, root.GetString("url")
        !);

    await Events.RedirectToAuthorizationEndpoint(redirectContext);
}
```

Listing 8. Handling Dokobit session creation

```

protected override async Task<HandleRequestResult>
    HandleRemoteAuthenticateAsync()
{
    var properties = Options.StateDataFormat.Unprotect(Request.
        Cookies[Options.StateCookie.Name!]);
    if (properties == null)
        return HandleRequestResult.Fail("Invalid state");

    var sessionToken = Request.Query["session_token"];
    if (StringValues.IsNullOrEmpty(sessionToken))
        return HandleRequestResult.Fail("Missing session_token",
            properties);

    if (properties.Items["session_token"] != sessionToken)
        return HandleRequestResult.Fail("Unexpected session_token
            received", properties);

    var response = await ExecuteRequestAsync(HttpMethod.Get, $"/api
        /authentication/{sessionToken}/status");
    response.EnsureSuccessStatusCode();

    Response.Cookies.Delete(Options.StateCookie.Name!);

    await using var stream = await response.Content.
        ReadAsStreamAsync(Context.RequestAborted);
    using var user = await JsonDocument.ParseAsync(stream);

    var ticket = await CreateTicketAsync(new ClaimsIdentity(
        ClaimsIssuer), properties, user.RootElement);
    return HandleRequestResult.Success(ticket);
}

```

Listing 9. Handling access token creation

The first code block (listing 8) has three main parts:

1. establish a session with Dokobit as described in listing 6;
2. append an **encrypted** session cookie which would bind the browser to that specific Dokobit session (this cookie stores the encrypted session_token);
3. redirect the user to the authorization endpoint;

After the user authenticates and returns, the next code block gets executed (listing 9). This code performs request validation in addition to retrieving the user data:

1. try to decrypt the cookie data - if decryption fails, it was likely tampered with, and the application cannot proceed with the authentication;

2. try to obtain the session token from query parameters - it should always exist if the request was not tampered with;
3. verify the session_token received from cookie and query parameters match - prevents victim's session from being stolen, as adversaries would be unable to redeem it;
4. redeem the session_token and receive user data as described in listing 7;
5. if redemption was unsuccessful, **invalidate the previous user session** [82];
6. clean up the used cookies;
7. issue an access token or a new session for use in the company;

5.8 Case Study: Web eID

5.8.1 About

Released in the Summer of 2021 [20] and having undergone significant changes in January of 2022, this eID framework allows users to authenticate and sign documents using their smart cards.

Functionally this framework is split into three parts: software the user needs to install on their computer, a javascript library that acts as a data intermediary, and the certificate validation library for the back-end.

The software users need to install is similar to the one various countries' governments issue. The significant difference is that this software supports more than one countries' eID solutions. Supported countries include Estonia, Latvia, Lithuania, and Finland [20].

This service is built by the Estonian Information System Authority, responsible for TARA, Estonia's public sector gateway. No publicly available audit certification is available at the time of writing .

is this
true?

5.8.2 Data Flow

Figure 17 displays the high-level overview of the complete flow of data within the Web eID framework. A detailed explanation of the steps can be found on the technical specification page [84]. Companies implementing the framework should only consider the browser and the server application (steps 1-3 and 13-17).

5.8.3 Trust Anchor

Unlike Dokobit and eeID, Web eID does not provide any guarantees about the trustworthiness of a certificate. It is, however, not out of malice and reminds developers by sending the certificate in a field called "unverifiedCertificate" [85].

The relying party must verify the certificate and challenge themselves by checking the origin, certificate expiry, trust chain, OCSP response, and the challenge. This validation structure makes the trust anchor technological and highly dependent on the implementation correctness by the developers.

Discuss
how we
can never
trust de-
velopers
without
proper
supervi-
sion

5.8.4 Pricing

The Web eID authentication service is free of charge, as the only external validation, OCSP [18] requests are free to use. When creating digital signatures, the timestamping service may require payment [85].




Figure 17. Web eID Authentication flow [84]

5.8.5 Security Analysis

Actors The actors in the figure 2 assume the roles of: QSCD Interface - web-eid.js [86], web-eid-app [87]; QSCD - Smart cards of Estonia, Latvia, Lithuania, and Finland [20].

Even though distributed by the same website, id.ee, this interface is separate from the official id.ee software Estonian citizens use to sign and verify documents. "In the future, the final version of Web eID will be added into the ID-software installation package, available for the users the website on www.id.ee" [20]. Owners of other countries' smart cards will still have to download the special software from id.ee.

Communication channel The Web eID framework uses an insecure channel for communications, so developers must take caution and verify received data when implementing the framework. This channel is susceptible to man-in-the-middle attacks done by the client.

Unlike in the cases of Dokobit and eeID, the risk of impersonation is not transferred to the eID service provider.

Validation requirements For each protocol implementation step, developers will have to fulfill certain guarantees before the system goes into production.

Steps 1-3 Building the challenge nonce. The goal of these steps is to create the challenge the user will have to sign with their private key. There are a couple of guarantees the application must provide:

1. Generated challenge nonce must be between 32 and 96 bytes (inclusive) in length [88];
2. "It must be guaranteed that the authentication token is received from the same browser to which the corresponding challenge nonce was issued" [85]. The framework creators suggest attaching it to the user session.
3. "Cache must be used for protection against replay attacks by guaranteeing that each authentication token can be used exactly once" [85].
4. "Cookie-based authentication must be protected against cross-site request forgery (CSRF) attacks and extra measures must be taken to secure the cookies by serving them only over HTTPS and setting the HttpOnly, Secure and SameSite attributes" [85].

In the implementation example, these measures were addressed by:

1. a 64 byte cryptographically secure randomly generated nonce is created (see listing 10);
2. challenge nonce is set in the user's session, which adversaries cannot tamper;
3. the generated nonce is stored into local memory cache for later use; nonce expires after 5 minutes;
4. an input field is rendered on the page with a unique CSRF validation token, which prevents cross-site request forgery attacks (see listing 11);

```
private TimeSpan ChallengeLifetime { get; } = TimeSpan.FromMinutes(5);

private readonly IMemoryCache _cache; // Injected

[HttpGet("challenge")]
public IActionResult GetChallenge()
{
    var nonce = RandomNumberGenerator.GetBytes(64);

    _cache.Set(Convert.ToBase64String(nonce), true, ChallengeLifetime);
    HttpContext.Session.Set("eid.challenge", nonce);
}
```

```

    return Ok(new { nonce });
}

```

Listing 10. Web eID Challenge Endpoint

```

@Inject Microsoft.AspNetCore.Antiforgery.IAntiforgery _csrf
@{ var csrfToken = _csrf.GetAndStoreTokens(HttpContext); }

<!-- Button used to sign in -->
<a role="button" class="btn btn secondary" id="webeid_auth_button">
    Web eID</a>

<input id="csrfToken" type="hidden" value="@csrfToken.RequestToken" />

<script>
    ...

    const authTokenResponse = await fetch("/signin_id/login", {
        method: "POST",
        headers: {
            "Content Type": "application/json",
            "RequestVerificationToken": document.getElementById("
                csrfToken").value
        },
        body: JSON.stringify(...)
    });

    ...
</script>

```

Listing 11. Web eID UI excerpt

Steps 13-17 After the user signs the nonce challenge and sends their certificate, the server must verify its authenticity. The application must perform all of the following before allowing the user to sign in:

1. verify the CSRF token from earlier steps [85];
2. verify the challenge nonce came from the original user and has not expired, was not consumed;
3. verify the certificate validity and check if nonce was signed by the associated private key (see below);
4. issue an authentication token with the fields from the certificate's subject;

In the implementation example, these measures were addressed by:

1. the back end endpoint for log-in is decorated with `ValidateAntiForgeryToken` Attribute. This attribute instructs the ASP.NET API to ignore requests not containing a CSRF token [89]. A JavaScript application can only access the protected endpoints by providing `RequestVerificationToken` header (see listing 11);
2. the application tries to extract the challenge nonce from the browsing session. The process would succeed if the session cookie were not modified. After the extraction, the application checks the nonce cache to verify if the challenge is still active. Cache hit means the nonce has not expired, and no previous authentication attempt was performed. Remove the challenge nonce from all stores.
3. The API calls a standalone validation service to verify the nonce and certificate (see below).
4. Application populates the ASP.NET identity management system with the fields from the certificate: serial number, given name, surname, country. An identity session cookie is sent to the client.

```
[HttpPost("login")]
[ValidateAntiForgeryToken]
public async Task<IActionResult> Login([FromBody]
    WebIdAuthTokenResponse token)
{
    // Obtain the challenge from session
    if (!HttpContext.Session.TryGetValue(ChallengeNonceKey, out var
        nonce) && nonce == null)
        return Unauthorized();

    // Check if token was not used before or expired
    var challenge = Convert.ToBase64String(nonce);
    if (!_cache.TryGetValue(challenge, out _))
        return Unauthorized();

    _cache.Remove(challenge);
    HttpContext.Session.Remove(ChallengeNonceKey);

    // Validate the certificate and signed challenge
    var validationResult = await _webEidValidationService.GetResult(
        new WebEidValidationRequest(token, nonce));
    if (!validationResult.Success)
        return Forbid();

    // Certificate is valid. Sign in the user

    await HttpContext.SignInAsync(BuildUser(new X509Certificate2(
        Convert.FromBase64String(token.UnverifiedCertificate)).Subject
    ));
```

```

        return Ok();
    }

```

Listing 12. Web eID Login Endpoint

Certificate and nonce verification This step is the most complicated in the entire validation process. To prevent any issues with incorrect implementation, the framework maintainers recommend using their library for validation [85]. Libraries can come with security vulnerabilities, and developers are reluctant to update their used version; however, it is still more favorable to creating vulnerabilities from misconfiguration [90].

The eu.webeid.security Java package performs most of the certificate validation: expiry, purpose, policy, OCSP [85]. Developers will only have to configure the CA and host validation. Configuration is handled by providing a set of trusted CA certificates for trust chain verification and the hostname for challenge nonces (see listing 13).

```

public class AuthTokenValidatorService {

    @Bean
    public AuthTokenValidator validator() {
        try {
            return new AuthTokenValidatorBuilder()
                .withSiteOrigin(URI.create(System.getenv("ORIGIN_URL")))
                .withTrustedCertificateAuthorities(
                    loadTrustedCACertificatesFromCerFiles())
                .build();
        } catch (JceException e) {
            throw new RuntimeException("Error building the Web eID auth
                token validator.", e);
        }
    }

    private X509Certificate[] loadTrustedCACertificatesFromCerFiles() {
        List<X509Certificate> caCertificates = new ArrayList<>();

        try {
            CertificateFactory certFactory = CertificateFactory.getInstance(
                "X.509");

            File[] files = new File("/certs").listFiles((f, n) -> n.
                endsWith(".cer"));
            if (files != null) {
                for (File file : files) {
                    try (InputStream stream = new FileInputStream(file)) {
                        X509Certificate caCertificate = (X509Certificate)
                            certFactory.generateCertificate(stream);
                        caCertificates.add(caCertificate);
                    }
                }
            }
        } catch (Exception e) {
            // ...
        }
    }
}

```

This library does favor EE cards a lot more, even having hard-coded some Mobile ID policies. Not sure if it is worth mentioning.




Figure 18. List of EU Trust service providers of Estonia and Lithuania capable of creating qualified certificates for e-signatures

```

    }
  }
}
} catch (CertificateException | IOException e) {
    throw new RuntimeException("Error initializing trusted CA
                             certificates.", e);
}

return caCertificates.toArray(new X509Certificate[0]);
}
}

```

Listing 13. Web eID Login Endpoint

The token validation service described in listing 13 requires the maintainers to set the origin URL in the form of an environment variable and to populate the folder /certs with trusted CA certificates.

Origin URL can be obtained by checking the window.origin JavaScript variable in the page containing the sign-in button.

For the CA certificate set, the company can get an up-to-date list of trusted certificates at the EU Trust Services Dashboard [21]. The issue with this list is that it contains all trust certificates for various scopes. In our case, we should limit the search to the extent of QCert for ESig. In the case of Estonia and Lithuania, only three entities are certified to issue certificates for QSCD (see figure 18). It is in stark contrast to Spain's 31 [21]. It is possible to further narrow down to only certificate generation services for qualified certificates (CA/QC).

In the case of Estonia's single TSP, we can see that only 3 CA are currently operational (see figure 19). Unfortunately, there is no standardized way of narrowing down which certificates could be used for authentication.

An alternative way to obtain certificates would be to go to the government authority of each country responsible for the distribution of certificates. This action requires prior




Figure 19. List of certificates issued to SK ID Solutions AS for the purposes of Qualified certificate for electronic signature

knowledge of who is responsible for issuing certificates and their purposes.

In Lithuania's case, it is the Ministry of the Interior [91] who issue two certificates (A and B) every couple of years. As of early 2022, four certificates are active, and all will be added to the trusted CA list.

In Estonia's case, SK ID Solutions manages the CA certificates [92]. Of the three certificates found on the EU Trust Services Dashboard, only two are relevant to us, the 2015 and 2018 ones, as the 2016 one has its purpose for use in Smart-ID, which the Web eID framework does not support.

The final list of certificates to support Lithuania and Estonia include four certificates from Lithuania's Ministry of the Interior and two certificates issued by SK ID Solutions for a total of six. It is essential to keep track of these certificates as each one of them can act as a point of compromise and must be monitored in the event they are revoked for security [93] or other issues.

Discussion: suggest how the certificates are way too challenging to obtain for a casual company and may lead to additional vulnerabilities

Discussion: phishing attacks if the company establishes policy to add certificates if they cannot sign in with their card

Exposing the service With the certificate validation service configured, it is now required to link it to the Web API. If the company orients around using microservices, this

service can be just that. All that the validation service requires is to expose an endpoint that accepts a nonce and a token from the javascript library and returns a validation result.

Companies must take proper measures to protect such service from adversaries as it acts as a fundamental trust anchor. Developers should take steps outlined in assume breach to mitigate the risk of misuse, with the use of TLS and other countermeasures.

citation
missing

Transport protocol Researcher Arnis Paršovs published a security analysis of the protocol v1 in October of 2021 [94]. Developers behind the Web eID framework acknowledged the weaknesses and addressed them in v2 [84], which will be used in the scope of the thesis. At the time of writing, independent researchers and auditors have not yet performed security analysis for this version.

The protocol is two asynchronous JavaScript calls to an API endpoint, which exists on the same website; the user does not need to leave the page. No redirects or third parties are involved; therefore, the analysis of a redirect-based protocol is not applicable in this scenario.

Related research about legal person documents?

Complete alternative, using your own issued certificates?

6 Discussion

6.1 Do businesses even want eID?

When conducting the initial investigation on what criteria we should use to compare different eID providers, we interviewed the CTO of a logistics company. The full interview can be found in the appendix. The responses about current practices were shocking but not surprising.

Authentication or Digital Signatures. What is more important to you? When asked if there was a choice between implementing eID authentication and qualified digital signature infrastructure, the company's focus would be on digital signature. Authentication only helps ensure the confidentiality and integrity of data and requires an additional heap of technological measures to prevent bypass. Qualified digital signatures offer an immediate benefit in the form of legally binding documents.

Trust. What trust requirements the eID provider should fulfill for you to adopt it? When asked if ISO/IEC 20001:2013 certification is sufficient, the answer was a resounding no. This certification should be the bare minimum for the company to consider using that solution. The CTO would "like to see that government portal, or banks are adopting this solution. This provides sufficient trust into the solution". This quote supports the assumption at the start that widespread adoption is low because there are no big-name adopters.

Source. Does the eID have to come from a TSP? The company CTO was not concerned much about the kind of eID provider is: primary or third-party. As long as other large entities the solution is trusted by other entities (governments or large companies), there is no significant difference between choosing services from an eIDAS QTSP and not. This logistics company sees no clear advantage in creating a contract with SK ID Solutions to implement Smart-ID authentication over an agreement with the Estonian Internet Foundation.

One can argue that a TSP is the trusted solution by large governmental institutions; however, it comes with a problem, especially in Estonia, of poor market reach, which is also highly important.

Market reach. How much impact does it have? While trust and security in solution are the main deciding factors, increasing security would not attract companies to use an eID solution after it reaches a certain widespread adoption level. What will have more impact is the market reach.

We have presented the interviewee four options: eeID (eIDAS), Dokobit (private company), Web eID (DIY), Smart-ID (narrow specialty TSP). With all their advantages and disadvantages, assuming all reach the trust requirement and price of operations are similar, the CTO's option was the one with the highest market reach. The reasoning behind it was saving money on implementing multiple providers, and the less company has to do, the lower the risk of something going wrong.

In short, a larger market size would positively impact the decision process of choosing a particular eID provider.

Pricing. How much is worth spending on eID solutions? Reducing costs is one of the cornerstones of running a business. When presented with the ballpark of how much the company would have to spend to operate an eID solution, the company's CTO suggested looking at the broader market for identity management solutions. They currently use Azure for their services. The company would still need to pay Microsoft for their accounts to access the cloud platform infrastructure. Azure AD B2C is used for all other use cases, which provides identity management options the company is used to, and the operational cost is close to nothing.

The issue with the eID solutions is that they are targeting a different kind of company. Still, it is not clear which industry would willingly, without regulatory requirements, choose to implement such a system. The CTO estimates that for 10 000 authentications per month, a company could reasonably support 300-400 active users. This price effectively means adding 1€ per system user to operational costs. Not many industries can afford such a luxury.

Technological hurdles The system is only as secure as its weakest link. The hardest part of implementing an eID solution is not integrating with an external provider but creating access controls for new or existing resources. These measures will have to be in place for all interaction methods - from user interfaces to database and backup solutions.

Summary Ultimately, the eID authentication solution suffers from a lack of benefits for companies. This solution deals with authentication and, by extension, access control. There is no visible advantage of using eID over a regular MFA solution from Microsoft. The company is just not dealing with data that personal.

The picture I have painted from the interview is that for the eID authentication to be helpful, there should be a legitimate interest to obtain the user's national ID code. There are cheaper alternatives available for those interested in only the additional security measures.

6.2 Do businesses even want digital signatures?

If there is one quote to take from the interview, it must be "today [business owners] open PDF and apply PNG of signature into the file free of charge." Part of the reason why eID authentication is not widespread is that digital signatures are not widespread.

The benefits of eID in the private sector, even after the research, remain unclear. The value provided by Qualified Electronic Signatures is obvious.

The only real business value eID authentication provides - is trustworthy audit logs in the case of legal disputes. Still, even then, there are no high-profile cases in court on that matter. Although, it would be harder for defendants to claim they didn't access the system when logs clearly showed. Unfortunately, even that argument collapses when you look at the trust chain - people in power can sabotage AuthServer, issue tokens in the victim's name, fabricate access records.

The only thing that is legally binding is Qualified Digital Signatures. Only special approved devices can create digital signatures, and when signing, the cryptographic operations are performed on the device. There is no higher authority like AuthServer that can doctor these signatures.

Unfortunately, even with the visible advantages of electronic signatures, business owners still do not use them. Having a picture of a written signature inside a PDF document remains a popular way of doing business.

Talk about which of the 3 case studies would work best in a company in early 2022

6.3 Which eID provider to choose?

The three case studies were not selected at random, they represent different approaches to accessing the electronic identity. Summary of pros and cons can be seen in table 3.

Which to choose? First, companies should decide if they need eID authentication in the first place. After that, it depends on priorities.

If the highest degree of trust factor is required, a company will have no other option other than to use a QTSP.

If high market reach and stability are required, adequately vetted and audited eIDAS node access is likely to be the best choice.

If the highest market reach is everything, third-party providers are a great choice. They are separated from the eIDAS category because they can use digital authentication schemes the origin countries do not wish to be liable for.

In short, there is no clear advantage of one option over the other, and companies should address the options available to them individually.

Should notify how eeID and Web eID are really in their infancy and further research should repeat this study in a couple of years

Table 3. Advantages and disadvantages of each eID solution

Scheme	Examples	Advantages	Disadvantages
eIDAS	TARA, (eeID)	large target audience; officially supported and used by governments; cheaper than implement- ing many individual QTSP services;	may not include some more popular schemes; does not offer means to sign documents;
Third-party aggregator	Dokobit, Signicat, (eeID), (Web eID)	large target audience; includes schemes ex- cluded from eIDAS; cheaper than implement- ing many individual QTSP services;	not officially supported by governments or legisla- tion; trust issues; risk of provider ceasing op- erations;
QTSP	ID-Card, Mobile-ID, Smart-ID, (Web eID)	highest degree of trust; security audits are regu- lated by law; support for digital signa- tures; some options (ID card) can be free to operate;	very narrow market reach in comparison; complicated to integrate; paid service operational stack up quickly;

Footnote on ID generation. Why not use the id and not store? Generally you would want to store who created a internal document, or who last edited a page. Using national ID for this purpose can open pandoras box when it comes to logging. Pseudonimization and linking the keys behind strong locks is next best thing.

6.4 Dangers with having no control over identity

As per the case with using external identity providers such as Auth0, Azure AD, or AWS Cognito, companies put a significant amount of trust when using their services. These services create access tokens, which almost always contain some form of user-id, roles, or claims.

From a technical standpoint, nothing stops these companies from creating fake access tokens skipping the whole authentication process. As far as the relying party would be concerned, these tokens would be indistinguishable from real ones. A corrupt or compromised company would have to only need to compromise the last step of authentication protocol - the one that sends (and optionally signs) personal information.

The same security concerns apply to state-issued electronic identity. We can identify three tiers of security, ordered from most to least secure:

1. Local device certificate authentication. Examples include ID cards and USB keys.
2. Local device certificate authentication. Examples include Mobile-ID and Smart-ID.
3. Third party authentication. Examples include eeID and Dokobit.

In the example of local device certificate authentication, a weakness lies in the fact that those certificates can be freely generated

Is it likely?

Ultimately, governments should have no interest in compromising their systems. The only benefit of doing so is simply too contrived - they would gain the ability to frame someone in a heavily audited space to have an edge in court. There are more straightforward legal or technical methods for all other activities.

More importantly, the issue with any system is that if an interaction method exists, it is bold to assume that only the intended users can access it. It is not unreasonable to think that backdoors can themselves have backdoors. Thus the only 100% safe countermeasure preventing anyone from accessing a system would be to make sure no one can.

In conclusion, it makes little sense for companies or governments to compromise their systems. The risks in doing so are astronomical in comparison to the benefits received.

Does this
make
sense?

7 Conclusion

In the thesis, we looked into the background, legality, and extensibility of eIDs, discussed the viability of using eID as a replacement for authentication, and analyzed three different eID providers the private sector could implement.

We have shown that it is possible to integrate an eID authentication scheme into a pre-existing SSO easily. The discovered challenges with integration are protecting the data from access by other means - no reason to force users to authenticate with eID if they can access the database with username and password.

We have created a privacy policy for the dummy test application considering the privacy requirements imposed by GDPR.

We have compared three different eID providers and discovered three different ways of performing cross-border authentication: integrating each provider individually, integrating a third-party provider aggregator, or tapping into a legally governed eIDAS framework.

We have interviewed with a logistics company representative to gauge the acceptance of eIDs in the general public, only to discover that it is unlikely that companies will adopt this technology without drastic changes in the market.

Summary The ability to integrate eID in the private sector exists; however, the public acceptance of them is limited. The technical and legal challenges associated with eID authentication make it impractical to implement. The only exception is if a company has a legitimate interest in processing personal data.

References

- [1] Adam Ozimek. The future of remote work. *Available at SSRN 3638597*, 2020.
- [2] British Council. IELTS - how to register. <https://www.ielts.org/for-test-takers/how-to-register>, 2022. Online; accessed 26-Feb-2022.
- [3] THE EUROPEAN PARLIAMENT and THE COUNCIL OF THE EUROPEAN UNION. Regulation (EU) No 910/2014 of the European Parliament and of the Council of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC. *Official Journal of the European Union*, L 257/73, 2014.
- [4] Riigikogu. Identity documents act. 2021.
- [5] European Comission. Digital economy and society index (desi) 2021. 2021.
- [6] Răzvan Dan. Cât plătesc oamenii pentru buletinul cu cip care a început să fie eliberat deja populației. <https://stirileprotv.ro/stiri/actualitate/buletinul-cu-cip-eliberat-deja-in-cluj-napoca-oamenii-platesc-70-de-lei-pentru->html, 2021. Online; accessed 27-Feb-2022.
- [7] Informacinės visuomenės plėtros komitetas. E-government gateway. <https://www.epaslaugos.lt/portal/nlogin>, 2022. Online; accessed 27-Feb-2022.
- [8] Estonian Information System Authority. As of 1 march, it will no longer be possible to access certain public e-services via a bank link. <https://www.ria.ee/en/news/1-march-it-will-no-longer-be-possible-access-certain-public-e-services-bank-link>html, 2021. Online; accessed 27-Feb-2022.
- [9] Arnis Parsovs. SEB Estonia Internet bank ID card authentication bypass. <https://youtu.be/rRB8jZnS5nY>, 2015. Online; accessed 30-Mar-2022.
- [10] Jesus Carretero, Guillermo Izquierdo-Moreno, Mario Vasile-Cabezas, and Javier Garcia-Blas. Federated identity architecture of the european eid system. *IEEE Access*, 6:75302–75326, 2018.
- [11] European Comission. Electronic identification schemes notified pursuant to Article 9(1) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market. *Official Journal of the European Union*, 2022/C 78 I/02, 2022.
- [12] Applied CyberSecurity Group. Estonian e-services using eid. https://acs.cs.ut.ee/services_using_eid, 2021. Online; accessed 21-Nov-2021.

- [13] Katri Kerem. *Internet banking in Estonia*, volume 7. PRAXIS, 2003.
- [14] AS SEB Pank. Bank link and authentication service. <https://www.seb.ee/en/bank-link>, 2021. Online; accessed 21-Nov-2021.
- [15] Arnis Parššovs. Security analysis of internet bank authentication protocols and their implementations. Master's thesis, Tallinn University of Technology, 2012.
- [16] Estonian Information System Authority. Home - id.ee. <https://www.id.ee/en/>, 2021. Online; accessed 20-Nov-2021.
- [17] Statistics Estonia. Population figure. <https://www.stat.ee/en/avasta-statistikat/valdkonnad/rahvastik/population-figure>, 2021. Online; accessed 20-Nov-2021.
- [18] Stefan Santesson, Michael Myers, Rich Ankney, Ambarish Malpani, Slava Galperin, and Dr. Carlisle Adams. X.509 Internet Public Key Infrastructure Online Certificate Status Protocol - OCSP. RFC 6960, June 2013.
- [19] Eric Rescorla. The Transport Layer Security (TLS) Protocol Version 1.3. RFC 8446, August 2018.
- [20] Estonian Information System Authority. Web eid. <https://www.id.ee/en/article/web-eid/>, 2022. Online; accessed 28-Feb-2022.
- [21] European Commission. Trust service providers. <https://esignature.ec.europa.eu/efda/tl-browser/>, 2022. Online; accessed 28-Feb-2022.
- [22] SK ID Solutions. History - 2007. <https://www.skidsolutions.eu/en/about/history/year-2007/>, 2007. Online; accessed 21-Nov-2021.
- [23] SK ID Solutions. Price list of Mobile-ID service. <https://www.skidsolutions.eu/en/services/pricelist/mobile-id-service>, 2021. Online; accessed 21-Nov-2021.
- [24] Telia. Mobiil-ID. <https://www.telia.ee/era/lisateenused/mobiil-id/>, 2022. Online; accessed 28-Feb-2022.
- [25] SK ID Solutions. History - 2017. <https://www.skidsolutions.eu/en/about/history/year-2017/>, 2017. Online; accessed 21-Nov-2021.
- [26] SK ID Solutions. Smart-ID documentation. <https://github.com/SK-EID/smart-id-documentation>, 2021. Online; accessed 10-Feb-2022.

- [27] Sylvie Lacroix, Olivier Delos, Evgenia Nikolouzou (ENISA), and Slawomir Gorniak (ENISA). Assessment of Standards related to eIDAS. Technical report, European Union Agency For Network and Information Security, 2018.
- [28] SK ID Solutions. Digital signatures with Smart-ID. <https://www.smart-id.com/e-service-providers/smart-id-as-a-qscd/>, 2018. Online; accessed 28-Feb-2022.
- [29] SK ID Solutions. Price list of Smart-ID service. <https://www.skidsolutions.eu/en/services/pricelist/smart-id/>, 2021. Online; accessed 21-Nov-2021.
- [30] Estonian Information System Authority. The information system authority’s authentication service TARA. <https://www.ria.ee/en/state-information-system/eid/partners.html>, 2022. Online; accessed 27-Feb-2022.
- [31] Estonian Information System Authority. TARA business description. <https://e-gov.github.io/TARA-Doku/Arikirjeldus>, 2021. Online; accessed 21-Nov-2021.
- [32] Estonian Information System Authority. TARA technical specification. <https://e-gov.github.io/TARA-Doku/TechnicalSpecification>, 2021. Online; accessed 21-Nov-2021.
- [33] Natsuhiko Sakimura, John Bradley, Mike Jones, Breno De Medeiros, and Chuck Mortimore. Openid connect core 1.0. *The OpenID Foundation*, 2014.
- [34] Estonian Internet Foundation. eeid service. <https://www.internet.ee/eeid-service>, 2021. Online; accessed 28-Feb-2022.
- [35] Estonian Internet Foundation. Subscription agreement and terms of use of the estonian internet foundation electronic identification service. https://meedia.internet.ee/files/Pricing_eeID.pdf, 2021. Online; accessed 28-Feb-2022.
- [36] Estonian Ministry of Education and Research. HarID. https://harid.ee/et/users/sign_in, 2022. Online; accessed 28-Feb-2022.
- [37] Dokobit. Electronic signature API solutions. <https://www.dokobit.com/solutions>, 2022. Online; accessed 28-Feb-2022.
- [38] Dokobit. Dokobit authentication solutions pricing. <https://www.dokobit.com/docs/pricing/Dokobit-authentication-solutions-pricing.pdf>, 2022. Online; accessed 28-Feb-2022.

- [39] Estonian Information System Authority. Id-card documentation. <https://www.id.ee/en/article/id-card-documentation/>, 2021. Online; accessed 01-Mar-2022.
- [40] Arnis Paršovs. *Estonian Electronic Identity Card and its Security Challenges*. PhD thesis, University of Tartu, 2021.
- [41] Information technology — Security techniques — Entity authentication assurance framework. Standard, International Organization for Standardization, Geneva, CH, 2013.
- [42] European Commission. COMMISSION IMPLEMENTING REGULATION (EU) 2015/1502 of 8 September 2015 on setting out minimum technical specifications and procedures for assurance levels for electronic identification means pursuant to Article 8(3) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market. *Official Journal of the European Union*, L 235/7, 2015.
- [43] THE EUROPEAN PARLIAMENT and THE COUNCIL OF THE EUROPEAN UNION. Regulation (EU) 2016/679 of the European Parliament and of the Council of 27 April 2016 on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC. *Official Journal of the European Union*, L 119/1, 2016.
- [44] Siddhartha Arora. National e-id card schemes: A european overview. *Information Security Technical Report*, 13(2):46–53, 2008.
- [45] Amos Fiat and Adi Shamir. How to prove yourself: Practical solutions to identification and signature problems. In *Conference on the theory and application of cryptographic techniques*, pages 186–194. Springer, 1986.
- [46] Lietuvos Respublikos vidaus reikalų ministerija. Sertifikatai įrašyti atk. <https://www.eid.lt/lt/apie-tapatybes-kortele/sertifikatai-ir-ju-valdymas>, 2020. Online; accessed 01-Mar-2022.
- [47] The eIDAS Cooperation Network. Opinion no. 3/2021 of the cooperation network on the french eid scheme (“franceconnect+/the digital identity la poste”). <https://ec.europa.eu/digital-building-blocks/wikis/pages/viewpage.action?pageId=439222578>, 2021. Online; accessed 01-Mar-2022.
- [48] Bernd Zwattendorfer and Daniel Slamanig. The austrian eid ecosystem in the public cloud: How to obtain privacy while preserving practicality. *Journal of Information Security and Applications*, 27-28:35–53, 2016. Special Issues on Security and Privacy in Cloud Computing.

- [49] Herbert Leitold. eid and egovernment in austria. Graz University of Technology https://online.tugraz.at/tug_online/voe_main2.getvolltext?pCurrPk=16600, 2006. Online; accessed 01-Mar-2022.
- [50] Bernd Zwattendorfer and Arne Tauber. Secure cross-cloud single sign-on (sso) using eids. In *2012 International Conference for Internet Technology and Secured Transactions*, pages 150–155, 2012.
- [51] Ribeiro C., Leitold H., Esposito S., and Mitzam D. Stork: a real, heterogeneous, large-scale eid management system. *International Journal of Information Security*, 17(5):569 – 585, 2018.
- [52] Vicente Guerola-Navarro, Raúl Francisco Oltra Badenes, Hermenegildo Gil Gómez, and Doina Stratu-Strelet. Eid@ cloud: integration of electronic identification in european platforms in the cloud in accordance with the eidas regulation. *3C Business, Research and critical thinking*, 8(3):64–87, 2019.
- [53] Martín J.C., Aranda N.I., Carreras R.C., Pasic A., Baún J.C.P., Ksysstra K., Triantafyllou N., Papadakis H., Torroglosa E., and Ortiz J. *LEPS - Leveraging eID in the private sector*. River Publishers, 2019.
- [54] Jesus Carretero, Guillermo Izquierdo-Moreno, Mario Vasile-Cabezas, and Javier Garcia-Blas. Federated identity architecture of the european eid system. *IEEE Access*, 6:75302–75326, 2018.
- [55] L. O’Gorman. Comparing passwords, tokens, and biometrics for user authentication. *Proceedings of the IEEE*, 91(12):2021–2040, 2003.
- [56] Yuan Cao and Lin Yang. A survey of identity management technology. In *2010 IEEE International Conference on Information Theory and Information Security*, pages 287–293, 2010.
- [57] Scott Cantor, Internet2 John Kemp, Nokia Rob Philpott, and E Maler. Assertions and protocols for the oasis security assertion markup language. *OASIS Standard (March 2005)*, pages 1–86, 2005.
- [58] Dick Hardt. The OAuth 2.0 Authorization Framework. RFC 6749, October 2012.
- [59] eIDAS eID Technical Subgroup. eidas saml attribute profile v1.2. Technical report, European Commission, 2019.
- [60] ESI. Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and common data structures. 319 412-1 V1.4.4. Technical report, ETSI, 2021.

- [61] Estonian Information System Authority. Data protection terms of the web eid website. <https://web-eid.eu/files/Web%20eID%20privacy%20policy.pdf>, 2021. Online; accessed 09-Mar-2022.
- [62] Dokobit. Privacy policy. <https://www.dokobit.com/compliance/privacy-policy>, 2022. Online; accessed 09-Mar-2022.
- [63] Adam Chester. Sql server authentication with metasploit and mitm. <https://blog.xpnsec.com/sql-server-auth-mitm/>, 2017. Online; accessed 09-Mar-2022.
- [64] Microsoft Docs contributors. Enable encrypted connections to the database engine. <https://docs.microsoft.com/en-us/sql/database-engine/configure-windows/enable-encrypted-connections-to-the-database-engine>, 2021. Online; accessed 09-Mar-2022.
- [65] Gediminas Milasius. at_hash is not OIDC compliant. <https://github.com/e-gov/TARA-Doku/pull/16>, 2022. Online; accessed 01-Apr-2022.
- [66] Torsten Lodderstedt, John Bradley, Andrey Labunets, and Daniel Fett. OAuth 2.0 Security Best Current Practice. Internet-Draft draft-ietf-oauth-security-topics-19, Internet Engineering Task Force, December 2021. Work in Progress.
- [67] Alexis Deveria. Can I use X-Frame-Options HTTP header. <https://caniuse.com/x-frame-options>, 2022. Online; accessed 02-Apr-2022.
- [68] OpenID Foundation. Certified OpenID Connect Implementations. <https://openid.net/developers/certified/>, 2022. Online; accessed 27-Mar-2022.
- [69] ASP.NET Core Contributors. Microsoft.AspNetCore.Authentication.OpenIdConnect source code. <https://github.com/dotnet/aspnetcore/tree/main/src/Security/Authentication/OpenIdConnect/src>, 2022. Online; accessed 27-Mar-2022.
- [70] OKTA Developer Documentation Contributors. OpenID Connect & OAuth 2.0 API. <https://developer.okta.com/docs/reference/api/oidc/>, 2022. Online; accessed 27-Mar-2022.
- [71] Estonian Information System Authority. TARA-Client. <https://github.com/e-gov/TARA-Client/blob/279cdce40aa470498b8db5b476ed99ec99147875/src/main/java/ee/ria/tara/mid/controller/DemoRestController.java#L177>, 2022. Online; accessed 26-Mar-2022.
- [72] Michael Jones, John Bradley, and Nat Sakimura. JSON Web Token (JWT). RFC 7519, May 2015.

- [73] Arnis Parsovs. Security Analysis of RIA's Authentication Service TARA. Technical report, University of Tartu, 2021.
- [74] European Union Intellectual Property Office. 017858226 - dokobit. <https://euipo.europa.eu/eSearch/#details/trademarks/017858226>, 2018. Online; accessed 20-Mar-2022.
- [75] Dokobit. Dokobit - about us. <https://www.dokobit.com/company/about-us>, 2022. Online; accessed 20-Mar-2022.
- [76] SK ID Solutions. The digidoc portal has a new manager. <https://www.skidsolutions.eu/en/News/the-digidoc-portal-has-a-new-manager>, 2016. Online; accessed 20-Mar-2022.
- [77] Bureau Veritas. Dokobit - iso/iec 27001:2013 certification. <https://www.dokobit.com/docs/compliance/Dokobit-iso27001-certificate.pdf>, 2019. Online; accessed 20-Mar-2022.
- [78] Hong-Youl Ha. Factors influencing consumer perceptions of brand trust online. *Journal of product & brand management*, 2004.
- [79] Microsoft Docs contributors. Centralized universal login vs. embedded login. <https://auth0.com/docs/authenticate/login/universal-vs-embedded-login>. Online; accessed 20-Mar-2022.
- [80] W. Denniss and J. Bradley. OAuth 2.0 for Native Apps. RFC RFC8252, October 2017.
- [81] Dokobit. Dokobit identity gateway api documentation. <https://id-sandbox.dokobit.com/api/doc>. Online; accessed 20-Mar-2022.
- [82] Gediminas Milasius. Vulnerability in dokobit identity gateway - low tech. <https://youtu.be/dG42UaHUoOE>, 2022. Online; accessed 21-Mar-2022.
- [83] Gustav Rydstedt, Elie Bursztein, Dan Boneh, and Collin Jackson. Busting frame busting a study of clickjacking vulnerabilities on popular sites. In *Web 2.0 Security and Privacy*. IEEE, 2010.
- [84] Estonian Information System Authority. Web eid: electronic identity cards on the web. <https://github.com/web-eid/web-eid-system-architecture-doc>, 2022. Online; accessed 05-Mar-2022.
- [85] Estonian Information System Authority. web-eid-app - authenticate.cpp. <https://github.com/web-eid/web-eid-authtoken-validation-java>, 2022. Online; accessed 05-Mar-2022.

- [86] Estonian Information System Authority. web-eid.js. <https://github.com/web-eid/web-eid.js>, 2021. Online; accessed 06-Mar-2022.
- [87] Estonian Information System Authority. web-eid-app. <https://github.com/web-eid/web-eid-app>, 2021. Online; accessed 05-Mar-2022.
- [88] Estonian Information System Authority. web-eid-app. <https://github.com/web-eid/web-eid-app/blob/8bedc0c57698c729012a0c16f590ce0907d27d20/src/controller/command-handlers/authenticate.cpp#L103>, 2021. Online; accessed 05-Mar-2022.
- [89] Fiyaz Hasan, Rick Anderson, and Steve Smith. Prevent cross-site request forgery (xsrp/csrf) attacks in asp.net core. <https://docs.microsoft.com/en-us/aspnet/core/security/anti-request-forgery>, 2022. Online; accessed 05-Mar-2022.
- [90] Ying Wang, Bihuan Chen, Kaifeng Huang, Bowen Shi, Congying Xu, Xin Peng, Yijian Wu, and Yang Liu. An empirical study of usages, updates and risks of third-party libraries in java projects. In *2020 IEEE International Conference on Software Maintenance and Evolution (ICSME)*, pages 35–45, 2020.
- [91] Asmens dokumentų išrašymo centras. Asmens tapatybės kortelė ir elektroninis parašas. <https://www.nsc.vrm.lt/downloads.htm>, 2021. Online; accessed 05-Mar-2022.
- [92] SK ID Solutions. Certificates. <https://www.skidsolutions.eu/en/repository/certs/>, 2022. Online; accessed 05-Mar-2022.
- [93] Estonian Information System Authority. Roca vulnerability and eid: Lessons learned. Technical report, Estonian Information System Authority, 2018.
- [94] Arnis Paršovs. On the format of the authentication proof used by ria’s web eid solution. Technical report, University of Tartu, 2021.

Appendix

I. Glossary

II. Licence

Non-exclusive licence to reproduce thesis and make thesis public

I, **Gediminas Milašius**,
(author's name)

1. herewith grant the University of Tartu a free permit (non-exclusive licence) to reproduce, for the purpose of preservation, including for adding to the DSpace digital archives until the expiry of the term of copyright,

Exploring integration complexity of different multi-national eID authentication solutions in the EU private sector,
(title of thesis)

supervised by Arnis Paršovs.
(supervisor's name)

2. I grant the University of Tartu a permit to make the work specified in p. 1 available to the public via the web environment of the University of Tartu, including via the DSpace digital archives, under the Creative Commons licence CC BY NC ND 3.0, which allows, by giving appropriate credit to the author, to reproduce, distribute the work and communicate it to the public, and prohibits the creation of derivative works and any commercial use of the work until the expiry of the term of copyright.
3. I am aware of the fact that the author retains the rights specified in p. 1 and 2.
4. I certify that granting the non-exclusive licence does not infringe other persons' intellectual property rights or rights arising from the personal data protection legislation.

Gediminas Milašius
11.06.2022

III. Questionnaire

The interview's goal is to understand better the reasons for the poor adoption of eIDs in the private sector. This interview was conducted with the CTO of a multinational logistics company.

1. With electronic key cards, users can authenticate themselves using a piece of hardware, say a card or a USB stick. This authentication method is often more secure than the usual username and password approach. Are you and the company in general aware of this?
2. I would describe an eID scheme as something like your id card, but digitally. There are three main schemes in Estonia: ID cards, Mobile-ID, and Smart-ID. Are you familiar with at least one of them?
3. With the eIDAS regulation, these three eID schemes can create digital signatures, with the legal value of a handwritten signature. Do you have a place in the company where you print a document, sign it, scan it and upload it? Would you switch to a solution that would avoid this process?
4. Without disclosing the worth of transactions floating around the company, would the security benefits of the eID schemes benefit company enough for you to switch to using them?
5. Authentication and signing usually come hand in hand, but if you were to have the ability to choose, assuming authentication and signing both costs equally as much to implement, would you rather spend the resources on authentication or digital signing? SEB Bank used to or still allows for transactions under 50€ to be done without signatures, only authentication. Would you at that point no longer consider the authentication method entirely?
6. Your company deals a lot with automation. Would you be comfortable automating the use of digital signatures in your company's name, or would you rather still have a person at the end manually reviewing and signing documents?
7. Say a human mistake occurs: a person mistakenly signs a document they shouldn't have, and the company faces losses. It would be easy to track who made a mistake with digital signatures. What would your company do in that case?
8. I have four different authentication options a company can take. Assume you would have to pick one of the four and explain the main reasons for your choice.
The first option uses the primary eIDAS network of Europe to authenticate themselves to any EU public sector service. For example, a Lithuanian citizen can use

their eID to sign into Estonia's banks. This network's security is held to the highest standards. Some discrepancies appear because of the criteria, such as Estonians being unable to sign in via Smart-ID to foreign websites. It is significant as a lot of people use Smart-ID. Do you think it is an acceptable solution for you?

The second option would use a company in the middle whose sole responsibility would be to federate the sign-in process. Like the first authentication method, you can also sign in from many more European countries, but this time without using the eIDAS network. A clear advantage over the first one is the more lax security requirements, allowing other authentication methods such as Smart-ID. Keep in mind that this authentication method is still highly trustworthy. Would you consider the ability to reach a broader audience at the cost of not using the official infrastructure a risk worth taking?

The third option puts a lot more risk on the company and allows for only a narrow market band. I am talking about smart cards and how a company could accept one, but the server should never trust the certificate a card sends. This approach is challenging to integrate and susceptible to many attacks; however, its advantage is that it is free to operate. If we ignore the personnel costs for maintaining the trust certificates, that is. Would no operational fees be convincing enough to pick this option?

The last option is similar to the third about the challenging implementations and the narrow market band. This time you will not have the advantage of free operational costs. However, you will still benefit from not having an intermediary company. This option would be if you integrated with Smart-ID directly. Is having an intermediary company of concern to you?

9. What is an acceptable price for a single successful authentication? The business model of options 1, 2, and 4 is to charge an amount per authentication. Let's aim for around 10 000 authentications per month; how much do you think is acceptable to spend on such a number? Would 500€ per month be acceptable?
10. Options 2-4 also create digital signatures; the first cannot. Does your opinion change at all about which solution you would pick?
11. An alternative to using government-issued eID solutions, you can also issue them yourself at a highly reduced price and trust factor. This solution is still more secure than the username+password approach. If you were to change how the company performs authentication, would you switch to the internal system, eID scheme, or not switch at all, and why?

IV. Privacy Policy

1. This document explains which personal data is processed on the AuthServer website (auth.eid.gedas.dev) for use as part of master's thesis research.
2. Information we process:
 - (a) User's eID authentication data, which can include: given name, surname, country of eID issue, unique identifier provided by eID, birth date;
3. Information we store:
 - (a) registration email address as part of the account creation process;
 - (b) user's country and unique identifier as provider by services used for external authentication;
4. Data retention policy:
 - (a) all data is wiped from the application at 00:00, Estonia time;
 - (b) users can manually remove their data by visiting <https://auth.eid.gedas.dev/Identity/Account/Manage/PersonalData>; effective immediately;
 - (c) users can download their personal data on the same page as (b);
5. Data shared with third-parties:
 - (a) information received from Dokobit service is subject to UAB Dokobit privacy policy;
 - (b) information received from Web eID service is subject to RIA's privacy policy;
 - (c) information received from eeID service is subject to internet.ee privacy policy;
 - (d) when checking the validity of certificates, the issuer defined in the certificate received will receive a certificate identifying information to validate the revocation status;