Nullable types

&

Nullable Types Under the Hood

`@Nullable, @NotNull` annotations

Nullability annotations



Nullability & Java

`Type` → `?`

behaves like
regular Java type

Platform type



type that came from Java

type of “unknown” nullability

A bit of history…

The safest approach would be…

`Type` → `Type?`

We tried, but it didn’t work well

If

then the code looks like



And it doesn’t really work with generics

Platform type

`Type` → `Type!`

type that came from Java

type of “unknown” nullability

Platform type in error message

```java
public class Session {
    public String getDescription()
}
```

```
val session = Session()
val description: Boolean = session.description
```

```
Compiler error: Type mismatch:
    inferred type is String!
    but Boolean was expected
```

What happens while running the code below?

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

```kotlin
val session = Session()
val description = session.description
println(description.length)
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

What happens while running the code below?

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

```kotlin
val session = Session()
val description = session.description
println(description.length)
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

Using Java from Kotlin

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

: String!

```
val session = Session()
val description = session.description
println(description.length)
```

NullPointerException!

Using Java from Kotlin

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

```
: String!
```

```kotlin
val session = Session()
val description = session.description
println(description?.length)
```

✓

How to still prevent NPEs?

- Annotate your Java types
- Specify types explicitly

How to still prevent NPEs?

- Annotate your Java types
- Specify types explicitly

Annotate your Java types



Different annotations are supported

`@Nullable`	`@NotNull`	JetBrains
`@Nullable`	`@NonNull`	Android
`@Nullable`	`@CheckForNull`	JSR-305
`@Nullable`	`@CheckForNull`	FindBugs
	`@NonNull`	Lombok

...

What happens while running the code below?

```java
public class Session {
    @Nullable
    String getDescription() {
        return null;
    }
}
```

```kotlin
val session = Session()
val description = session.description
println(description.length)
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

What happens while running the code below?

```java
public class Session {
    @Nullable
    String getDescription() {
        return null;
    }
}
```

```kotlin
val session = Session()
val description = session.description
println(description.length)
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

Using Java from Kotlin

```java
public class Session {
    @Nullable
    String getDescription() {
        return null;
    }
}
```

```
: String?
```

```
val session = Session()
val description = session.description
println(description.length)
```

compiler error

Using Java from Kotlin

```java
public class Session {
    @Nullable
    String getDescription() {
        return null;
    }
}
```

```
: String?
val session = Session()
val description = session.description
println(description?.length)
```

Annotate your Java types



- All of them???

- You can specify `@NotNull` as default, and annotate only `@Nullable` types

Non-null by default (JSR-305)

`@ParametersAreNonnullByDefault`

`@MyNonnullByDefault`

@MyNonnullApi

```
@javax.annotation.Nonnull
@TypeQualifierDefault(ElementType.PARAMETER, ...)
annotation class MyNonnullByDefault
```

package-info.java

```
@MyNonnullByDefault
package mypackage;
```

@NonNull by default

```java
@MyNonnullByDefault
public class Session {
    public void setDescription(String description) {
        this.description = description;
    }
}
```

```kotlin
val session = Session()
session.setDescription(null)
```

Warning: Expected type doesn’t accept nulls in Java, but the value may be null in Kotlin

Make it an error

build.gradle

```
compileKotlin {
    kotlinOptions {
        freeCompilerArgs += "-Xjsr305=strict"
    }
}
```

@NonNull by default

```
@MyNonnullByDefault
public class Session {
    public void setDescription(String description) {
        this.description = description;
    }
}
```

```
val session = Session()
session.setDescription(null)
```

Error: Null can not be a value of a non-null type String

How to still prevent NPEs?

- Annotate your Java types
- Specify types explicitly

What happens while running the code below?

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

```kotlin
val session = Session()
val description: String? = session.description
println(description?.length)
```

What happens while running the code below?

```java
public class Session {
   public String getDescription() {
      return null;
   }
}
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

```kotlin
val session = Session()
val description: String? = session.description
println(description?.length)
```

Specify types explicitly

```java
public class Session {
    public String getDescription() {
        return null;
    }
}
```

```
val session = Session()
val description: String? = session.description
println(description?.length)
```

✓

What happens while running the code below?

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

```kotlin
val session = Session()
val description: String = session.description
println(description.length)
```

What happens while running the code below?

```java
public class Session {
  public String getDescription() {
    return null;
  }
}
```

1. `NullPointerException` is thrown
2. `null` is printed
3. `compilation error`
4. `IllegalStateException` is thrown

```kotlin
val session = Session()
val description: String = session.description
println(description.length)
```

Specify types explicitly

```
public class Session {
  public String getDescription() {
    return null;
  }
}
```

```
val session = Session()
val description: String = session.description
                          IllegalStateException:
                          session.description must not be null
```

Intrinsic checks

```
val session = Session()
val description: String = session.description
println(description)
```

Intrinsic checks

```
val session = Session()
val description: String = session.description
```

```
Intrinsics.checkExpressionValueIsNotNull(
    description, "session.description");
```

```
println(description)
```

is generated by the compiler,
throws an exception if `session.description` is `null`

Intrinsic checks

```
public fun foo(s: String) {
    Intrinsics.checkParameterIsNotNull(s, "s");
}
```

How to still prevent NPEs?

- Annotate your Java types
- Specify types explicitly

Nullable platform types: summary

Good compromise between
safety and convenience