

Introduction to MATLAB Part I

Amit Amritkar

Center for Advanced Computation and Data Systems (CACDS)

<http://cacds.uh.edu>

<http://support.cacds.uh.edu>

University of Houston

Houston, TX

First Access Your Account

- Log into your accounts
 - Username or login = hpc_user**X**
 - Where **x** = sign in serial number 1 – 48 based on your token
 - Password = **cacds2014**
- Tutorials/Slides could be downloaded using a terminal as below

```
cp /share/apps/tutorials/spring2015/matlab/intro2matlab_part1.pdf ~
cp /share/apps/tutorials/spring2015/matlab/intro2matlab_part1.zip ~
```

Using Tutorial Materials

First login into the cluster:

TYPE AND EXECUTE COMMANDS IN RED!!!

```
cd
```


```
unzip intro2matlab_part1.zip
```

```
cd intro2matlab*
```

```
module load matlab
```

```
matlab
```

About CACDS



Mission Statement

To provide state-of-the-art Tier One High Performance Computing (HPC) resources, data solutions and expertise propelling research in the Houston-Galveston region to a competitive advantage in education and business. Through training, CACDS aims to develop a highly-talented diverse HPC workforce, as well as help promote interdisciplinary research excellence and provide competitive HPC, data analysis and scientific visualization resources.

CACDS Training courses: Register at

<http://www.cacds.uh.edu/education/courses/>



The screenshot shows a web browser window with the URL www.cacds.uh.edu/education/courses/. The page has a red header with the text "Training Courses". On the left, there is a sidebar with the heading "Education" and three red buttons: "Training Courses", "HPC Seminar Series", and "Workshops". The main content area is titled "Spring 2015 Course List". It contains a paragraph stating that CACDS has launched several HPC training courses for members of the UH research community, and that registration is required. It also provides an email address, LISTSERV@LISTSERV.UH.EDU, for those who want to receive email notifications. Below this, there is a table of courses for the Spring 2015 semester. The table has a header "CLASS NAME" and lists 15 courses. A red arrow icon is visible in the bottom right corner of the page.

Center for Advanced Computi... x +

www.cacds.uh.edu/education/courses/

Training Courses

Education

- Training Courses
- HPC Seminar Series
- Workshops

Spring 2015 Course List

CACDS has launched several HPC training courses for members of the UH research community. Registration is required to take the courses. Please click the date you would like to attend under each course to register.

If you would like to get email notifications of any CACDS events, please send an email from your UH email address to LISTSERV@LISTSERV.UH.EDU, leave the subject field blank, and in the body of the message type: SUBSCRIBE CACDS-WORKSHOPS.

SPRING 2015 SEMESTER
CLASS NAME
Introduction to Linux
Introduction to Shell Programming
Introduction to Cluster Computing and Maxwell Cluster
Introduction to C++ Programming Part I
Introduction to C++ Programming Part II
Introduction to Python Programming Part I
Introduction to Python Programming Part II
GPGPU Parallel Programming with OpenACC Part I
GPGPU Parallel Programming with OpenACC Part II
GPGPU Parallel Programming with CUDA Part I
GPGPU Parallel Programming with CUDA Part II
Introduction to Matlab Part I
Introduction to Matlab Part II
Introduction to Intel Xeon Phi Programming Part I
Introduction to Intel Xeon Phi Programming Part II
Visualization with VISIT Part I



- **VIZAPALOOZA 2015 -- CACDS Data Visualization Challenge** [Click here to see the Flyer.](#)
- CACDS provides modern and competitive training in High Performance Computing (HPC) tools and platforms for cross-domain research, and is calling you, all the Cougars, to participate in its 1st VIZAPALOOZA; an HPC visualization challenge aimed to promote research synergy @ UH.
- Join the UH research community at the CACDS visualization theater to share the coolest images and movies that talk about your important research. **All research images are welcome** (independently of the computer tools/equipment used to create them).
- **PARTICIPATE:**
- - Submit ONE image/movie, or a direct URL to it, from your research along with your name, position, Department, an abstract and a caption related to the image/movie to uh.data.viz@gmail.com by **April 29th**.
- - or -
- - Just join us for good discussions, but RSVP via email to uh.data.viz@gmail.com by April 29th.
- **WHEN?** Friday May the 1st.
- **WHERE?** CACDS' Visualization Theater at PGH 216.
- **PRIZES:**
- - An iPod touch,
- - Registration fees for [SC15 \(Austin TX, Nov 15-20, 2015\)](#),
- - A full color poster to be printed and displayed in CACDS' corridors (PGH 2nd floor) so you can show off your important research.


Overview

- Introduction to MATLAB
 - What is MATLAB
 - Variables, arrays, matrices, indexing, etc
 - Operators
 - Flow control
 - Using of M-files

What is MATLAB?

- MATLAB is a **high-level** programming language for scientific computing and data visualization built around an interactive programming environment.
- **MATLAB is NOT “Math” lab**
- The name stands for MATrix LABoratory since originally it was developed for matrix computation.
 - Think everything in matrix
 - Many specialized toolboxes for making things easier for us

How **high** ?



What Is MATLAB? (cont.)

- Full programming language.
- Strong on matrix manipulation and graphics.
- Optional toolboxes for statistics, image processing, signal processing, etc.
- Interfaces with C, Fortran, and Java.
- Can create stand-alone executable files.
 - HHsim, a Hodgkin-Huxley simulator developed by Dave Touretzky with help from Jon Johnson, is distributed as a stand-alone executable. (Source is also available.)


Why Should You Learn MATLAB?

- Data analysis:
 - Much more versatile than a spreadsheet.
 - Extensive statistics toolbox.
 - Third party domain applications e.g. SPM uses MATLAB.
 - Statistical Parametric Mapping (SPM)
- Graphics:
 - Many ways to visualize your data – even animations!
 - Produce great figures for your papers.
- Modeling and simulation:
 - Used for finite element method.

What Are We Interested In ?

Ours is a short introduction to MATLAB


The features we are going to require are



MATLAB Graphical User Interface (GUI)


- Features
 - Plots
 - Toolboxes – apps
 - Editor – debugging
 - Publish – web/latex format
 - View
- Can create your own GUI

MATLAB GUI



Variables and Arrays

- **Array:** A collection of data values organized into rows and columns, and known by a single name.



Arrays

- The fundamental unit of data in MATLAB
- Scalars are also treated as arrays by MATLAB (1 row and 1 column).
- Row and column indices of an array start from 1.
- Arrays can be classified as **vectors** and **matrices**.

Vector and Matrix

- **Vector:** Array with one dimension
- **Matrix:** Array with more than one dimension
- **Size** of an array is specified by the number of rows and the number of columns, with the number of rows mentioned first (For example: $n \times m$ array).

Total number of elements in an array is the product of the number of rows and the number of columns.

MATRIX BASICS

$$a = \begin{bmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{bmatrix}$$

3x2 matrix → 6 elements

$$b = [1 \quad 2 \quad 3 \quad 4]$$

1x4 array → 4 elements, **row vector**

$$c = \begin{bmatrix} 1 \\ 3 \\ 5 \end{bmatrix}$$

3x1 array → 3 elements, **column vector**

$$a(2,1)=3$$

Row # Column #

$$b(3)=3$$

$$c(2)=3$$

Variables

- A region of memory containing an array, which is known by a **user-specified name**.
- Contents can be used or modified at any time.
- **Variable names must begin with a letter**, followed by any combination of letters, numbers and the underscore (_) character. Only the first 31 characters are significant.
- The MATLAB language is Case Sensitive. NAME, name and Name are all different variables.

Give meaningful (descriptive and easy-to-remember) names for the variables. Never define a variable with the same name as a MATLAB function or command.

Common types of MATLAB Variables

- **double:** 64-bit double-precision floating-point numbers.
 - All variables are created with double precision unless specified
 - They can hold real, imaginary or complex numbers in the range from $\pm 10^{-308}$ to $\pm 10^{308}$ with 15 or 16 decimal digits.

```
>> var = 1 + i;
```
- **char:** 16-bit values, each representing a single character
 - The char arrays are used to hold character strings.

```
>> comment = 'This is a character string' ;
```
- The **type of data** assigned to a variable determines the type of variable that is created.

Initializing Variables in Assignment Statements

- Arrays are constructed using square brackets and semicolons
- All of the elements of an array are listed in row order
- The values in each row are listed from left to right and they are separated by blank spaces or commas
- The rows are separated by semicolons or new lines
- The number of elements in every row of an array must be the same.
- The expressions used to initialize arrays can include algebraic operations and all or portions of previously defined arrays

Initializing Variables in Assignment Statements

An assignment statement has the general form

var = expression

% Try these examples:

```
>> var = 40 * i;  
>> var2 = var / 5;  
>> array = [1 2 3 4];  
>> x = 1; y = 2;  
>> a = [3.4];  
>> b = [1.0 2.0 3.0 4.0];  
>> c = [1.0; 2.0; 3.0];  
>> d = [1, 2, 3; 4, 5, 6];  
>> e = [1, 2, 3  
        4, 5, 6];
```

```
>> a2 = [0 1+8];  
>> b2 = [a2(2) 7 a];  
>> c2(2,3) = 5;  
>> d2 = [1 2];  
>> d2(4) = 4;
```

‘;’ semicolon suppresses the automatic echoing of values.

Initializing with Shortcut Expressions

Syntax *first: increment: last*

- **Colon operator:** a shortcut notation used to initialize arrays with thousands of elements

```
>> x = 1 : 2 : 10;
```

```
>> angles = (0.01 : 0.1 : 1) * pi;
```

- **Transpose operator:** (') swaps the rows and columns of an array

```
>> f = [1:4]';
```

```
>> g = 1:4;
```

```
>> h = [ g' g' ];
```

$$h = \begin{bmatrix} 1 & 1 \\ 2 & 2 \\ 3 & 3 \\ 4 & 4 \end{bmatrix}$$

Concatenation of Arrays

- $\mathbf{x} = [1 \ 2], \mathbf{y} = [4 \ 5], \mathbf{z} = [0 \ 0]$

$$\mathbf{A} = [\mathbf{x} \ \mathbf{y}]$$

1 2 4 5

$$\mathbf{B} = [\mathbf{x} \ ; \ \mathbf{y}]$$

1 2

4 5

- $\mathbf{C} = [\mathbf{x} \ \mathbf{y} \ ; \ \mathbf{z}]$

Error:

??? Error using ==> vertcat CAT arguments dimensions are not consistent.

Initializing With Built-in Functions

- `zeros(n)`
- `zeros(n,m)`
- `zeros(size(arr))`
- `ones(n)`
- `ones(n,m)`
- `ones(size(arr))`
- `eye(n)`
- `eye(n,m)`
- `randn(n,m)`
- `rand(n)`
- `length(arr)`
- `size(arr)`

```
>> a = zeros(2);  
>> b = zeros(2, 3);  
>> c = [1, 2; 3, 4];  
>> d = zeros(size(c));
```

```
>> r = 1 + 3.*randn(1,100);  
    interval [1, 4]
```


Initializing with Keyboard Input

- The **input** function displays a prompt string in the Command Window and then waits for the user to respond.

```
my_val = input( 'Enter an input value: ' );
```

```
in1 = input( 'Enter data: ' );
```

- To enter a string

```
in2 = input( 'Enter data: ', 's' );
```

Multidimensional Arrays

- A two dimensional array with m rows and n columns will occupy mxn successive locations in the computer's memory. MATLAB always allocates array elements in **column major order**.

```
a = [1 2 3; 4 5 6; 7 8 9; 10 11 12];
```

```
a(5) = a(1,2) = 2
```

1	2	3
4	5	6
7	8	9
10	11	12

1
4
7
10
2
5
8
11

- A 2x3x2 array of three dimensions

```
c=zeros(2,3,2);
```

```
c(:, :, 1) = [1 2 3; 4 5 6];
```

```
c(:, :, 2) = [7 8 9; 10 11 12];
```

Size of a Matrix

```
pts=randn(5,4)
```

```
whos pts
```

```
size(pts)
```

```
length(pts)
```

```
- equivalent to max(size(pts))
```

Subarrays and Subscripting

$V = [10 \ 20 \ 30 \ 40 \ 50];$

$V(3)$

$M = [1 \ 2 \ 3; 4 \ 5 \ 6; 7 \ 8 \ 9]$

$M =$

1	2	3
4	5	6
7	8	9

$M(2,2)$

$M(2)$ ← access in column-major order

$M(6)$ ←

Subarrays and Subscripting

- It is also possible to select and use subsets of MATLAB arrays.

```
arr1 = [1.1 -2.2 3.3 -4.4 5.5];
```

```
arr1(3) is 3.3
```

```
arr1([1 4]) is the array [1.1 -4.4]
```

```
arr1(1 : 2 : 5) is the array [1.1 3.3 5.5]
```

- For two-dimensional arrays, a colon can be used in a subscript to select all of the values of that subscript.

```
arr2 = [1 2 3; -2 -3 -4; 3 4 5];
```

```
arr2(1, :)
```

```
arr2(:, 1:2:3)
```

Subarrays and Subscripting Matrix Slices

`V=[0:2:10]`

`V(2:4)`

`V(2:end)`

`M=rand(5);`

`M(1:2, 2:3)`

`M(:)`

`M(: , :)`

Subarrays and Subscripting

- The **end** function: When used in an array subscript, it returns the highest value taken on by that subscript.
arr3 = [1 2 3 4 5 6 7 8];
arr3(5:end) is the array [5 6 7 8]
arr4 = [1 2 3 4; 5 6 7 8; 9 10 11 12];
arr4(2:end, 2:end)
- Using subarrays on the left hand-side of an assignment statement:
arr4(1:2, [1 4]) = [20 21; 22 23];
(1,1) (1,4) (2,1) and (2,4) are updated.
arr4 = [20 21; 22 23]; all of the array is changed.

Subarrays and Subscripting

- Assigning a Scalar to a Subarray: A scalar value on the right-hand side of an assignment statement is copied into every element specified on the left-hand side.

```
>> arr4 = [1 2 3 4; 5 6 7 8; 9 10 11 12];
```

```
>> arr4(1:2, 1:2) = 1
```

```
arr4 =
```

```
1    1    3    4
```

```
1    1    7    8
```

```
9   10   11   12
```


Expanding a Matrix

`a = [1 2 3]`

`a = [a 4]`

`a(7) = 5`

`a(end+1) = 6`

`b = [a ; a.^2]`

Efficiency tip:

Use `ZEROS(rows,cols)` to preallocate large arrays instead of growing them dynamically.

Reshaping a Matrix

$M = \text{reshape}(1:12, 4, 3)$

M'

$M'{}' \text{ or } (M')'$

Exercise (1)

Create the following matrix using **only** the colon, reshape, and transpose operators.

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15

Deleting Rows or Columns

```
M=rand(5)
```

```
M(:, 3) = []
```

```
M(2, :) = []
```

```
size([ ])
```

Reduction Operators

`M = rand(5, 3)`

`sum(M)` **sum along first dimension**

`sum(M, 2)` **sum along second dimension**

`sum, prod, min, max, mean, var`

`min(min(M))`

`min(M(:))`

Expanding with REPMAT

REPMAT is often used to expand a vector to fit the shape of a matrix.

Example: adjusting a dataset to have zero mean.

```
M = rand(5,3);  
avgs = mean(M);  
Mavgs = repmat(avgs, 5, 1)  
Mzero = M - Mavgs;  
sum(Mzero)
```

Mavgs =

0.6220	0.7448	0.5099
0.6220	0.7448	0.5099
0.6220	0.7448	0.5099
0.6220	0.7448	0.5099
0.6220	0.7448	0.5099

ans =

1.0e-15 *

0.3331	0.3331	0.1110
--------	--------	--------

Exercise (2)

Suppose we want the rows of M to sum to zero, instead of the columns.

How would you do this, without using the transpose operator?

Special Values

- MATLAB includes a number of predefined special values. These values can be used at any time without initializing them.
- These predefined values are stored in ordinary variables. They can be overwritten or modified by a user.
- If a new value is assigned to one of these variables, then that new value will replace the default one in all later calculations.

```
>> circ1 = 2 * pi * 10;  
>> pi = 3;  
>> circ2 = 2 * pi * 10;
```

Never change the values of predefined variables.

Special Values

- **pi**: π value up to 15 significant digits
- **i, j**: $\sqrt{-1}$
- **Inf**: infinity (such as division by 0)
- **NaN**: Not-a-Number (division of zero by zero)
- **clock**: current date and time in the form of a 6-element row vector containing the year, month, day, hour, minute, and second
- **date**: current date as a string such as *16-Feb-2004*
- **eps**: epsilon is the smallest difference between two numbers
- **ans**: stores the result of an expression

Changing The Data Format

```
>> value = 12.345678901234567;
```

```
format short          → 12.3457
```

```
format long           → 12.34567890123457
```

```
format short e        → 1.2346e+001
```

```
format long e         → 1.234567890123457e+001
```

```
format short g        → 12.346
```

```
format long g         → 12.3456789012346
```

```
format rat            → 1000/81
```

Disp function

The **disp(*array*)** function

```
>> disp( 'Hello' )
```

```
Hello
```

```
>> disp(5)
```

```
5
```

```
>> disp( [ 'Bilkent ' 'University' ] )
```

```
Bilkent University
```

```
>> name = 'Alper';
```

```
>> disp( [ 'Hello ' name ] )
```

```
Hello Alper
```

Conversion Functions

The **num2str()** and **int2str()** functions

```
>> d = [ num2str(16) '-Feb-' num2str(2004) ];
```

```
>> disp(d)
```

```
16-Feb-2004
```

```
>> x = 23.11;
```

```
>> disp( [ 'answer = ' num2str(x) ] )
```

```
answer = 23.11
```

```
>> disp( [ 'answer = ' int2str(x) ] )
```

```
answer = 23
```

Changing The Data Format

The **`fprintf(format, data)`** function

- `%d` integer
- `%f` floating point format
- `%e` exponential format
- `%g` either floating point or exponential format, whichever is shorter
- `\n` new line character
- `\t` tab character

Changing The Data Format

```
>> fprintf( 'Result is %d', 3 )
```

```
Result is 3
```

```
>> fprintf( 'Area of a circle with radius %d is %f', 3, pi*3^2 )
```

```
Area of a circle with radius 3 is 28.274334
```

```
>> x = 5;
```

```
>> fprintf( 'x = %3d', x )
```

```
x =   5
```

```
>> x = pi;
```

```
>> fprintf( 'x = %0.2f', x )
```

```
x = 3.14
```

```
>> fprintf( 'x = %6.2f', x )
```

```
x =   3.14
```

```
>> fprintf( 'x = %d\ny = %d\n', 3, 13 )
```

```
x = 3
```

```
y = 13
```

MATLAB Files

Data files

- **save** *filename var1 var2 ...*

>> save myfile.mat x y → binary

>> save myfile.dat x -ascii → ascii

- **load** *filename*

>> load myfile.mat → binary

>> load myfile.dat -ascii → ascii

MATLAB Operations

- *variable_name = expression;*

– addition	$a + b$	→	$a + b$
– subtraction	$a - b$	→	$a - b$
– multiplication	$a \times b$	→	$a * b$
– division	a / b	→	a / b
– exponent	a^b	→	$a ^ b$

Hierarchy of operations

- $x = 3 * 2 + 6 / 2$
- Processing order of operations is important
 - parentheses (starting from the innermost)
 - exponentials (from left to right)
 - multiplications and divisions (from left to right)
 - additions and subtractions (from left to right)

>> $x = 3 * 2 + 6 / 2$

$x =$

9

Built-in MATLAB Functions

result = function_name(input);

- abs, sign
 - log, log10, log2
 - exp
 - sqrt
 - sin, cos, tan
 - asin, acos, atan
 - max, min
 - round, floor, ceil, fix
 - mod, rem
- help elfun → help for elementary math functions

Types Of Errors in MATLAB Programs

- Syntax errors
Fix: Check spelling and punctuation
- Run-time errors
Fix: Check input data
Can remove “;” or add “disp” statements
- Logical errors
Fix
 - Use shorter statements
 - Check typos
 - Check units
 - Ask your friends, assistants, instructor, ...

Linear Algebra

★ $A+B$

★ $A-B$

A' for the transpose of A

★ $\text{inv}(A)$ for the inverse of A

★ $\det(A)$ for determinant of A

★ $\text{diag}(A)$ for a vector equal to the diagonal elements of A

* must be used with appropriate sized matrices, e.g., square matrices to inv and \det and conformable matrices

Element Wise Operations

A= magic(3)

8	1	6
3	5	7
4	9	2

A.^2

64	1	36
9	25	49
16	81	4

Note A*A =		
91	67	67
67	91	67
67	67	91

Other element-wise operators: + - .* ./ .^

Logical Operations

Operators: == ~= < > <= >=

Can't use != as in Java or C

Logical values:

0 means “*false*”

1 (or any non-zero number) means “*true*”

a = (3 >= 1 : 5) What are the type and size of a?

a =

1 1 1 0 0

Conditional Statements And Looping

any & all

```
a=randn(2)
```

```
0.47785 -0.52364
```

```
-1.46193 1.29783
```

```
b=randn(2)
```

```
-0.68481 -1.20778
```

```
-0.10133 -0.85876
```

```
any (a<b)
```

```
1 0
```

```
all (a<b)
```

```
0 0
```

Conditional Statements And Looping

If & else

if expression

...

end

% Example 1:

X=2; if X>0, A=1/X; else A=0, end

if expression

...

else

...

end

%Example 2:

x = 5;

if (x > 10)

y = 10;

elseif (x < 0)

y = 0;

else

y = x;

end

Conditional Statements And Looping

While loop

Syntax

while expression

...statements

end

Example 1:

```
while ((a>3) & (b==5))  
    Some MATLAB Commands;  
end
```

Example 2:

How quickly can a random accumulator reach 5?

```
accum = 0; steps = 0;  
while accum < 5  
    steps = steps + 1;  
    accum = accum + rand(1);  
end  
steps, accum
```

Used when you don't know how many times the loop is to be executed

Conditional Statements And Looping

For loop

Syntax:

```
for index = values  
    statements  
end
```

% Example:

```
n=10; X=[1:n]; X(:)=0
```

```
for i=2:n
```

```
    X(i)=3*X(i-1)+1
```

```
end
```

Batch/Script file

Use of M files

- Batch or script file in MATLAB is simple. Simply put your code in a file with extension `.m`
- Every symbol will be visible in the current workspace
- Good for initial development

Functions

- Functions are exactly the same as batch files except they hide all variables excluding those you return

```
function out1=function_name(in1)
function out1=function_name(in1,in2,in3)
function [out1,out2]=function_name(in1,in2)
```

You should write this command at the beginning of the m-file and you should **save the m-file with a file name same as the function name**

Functions

file isprime1.m

```
function bool=isprime1(n)
bool=1;
for i=2:floor(sqrt(n))
    if mod(n,i)==0
        bool=0; break;
    end
end
```

in MATLAB terminal

```
>> type isprime1.m
function bool=isprime1(n)
bool=1;
for i=2:floor(sqrt(n))
    if mod(n,i)==0
        bool=0; break;
    end
end
>> bool=isprime1(5);
```

Function pointers
lambda functions:

```
>> add=@(x,y) x+y
add =
    @(x,y)x+y

>> add(1,2)
ans =
    3
```

```
>> addone=@(x)
add(1,x);
>> addone(3)
ans =
    4
```

Scripts vs. Functions

Scripts take no input arguments and produce no return values.

Scripts operate in the workspace of their caller.

If called from the command line, scripts operate in the **base workspace**.

If called from within a function, scripts operate in the function's **local workspace** and can see and modify its local variables.

Scripts vs. Functions

Functions can take zero or more arguments and return zero or more values.

Functions operate in their own **local workspace**.

Variables created inside a function are local to that function.

Local variables disappear when the function returns.

File I/O

- fopen
 - fread
 - fwrite
 - fprintf
 - save/load
- } More or less
same as C

```
>> save tmp a b c
>> load tmp
>> save tmp2 a -ascii
```


Profiling

- Using `tic/toc`

```
>> tic; parfor i=1:3; c(:,i)=eig(rand(1000)); end; toc  
Elapsed time is 0.862877 seconds.
```

```
>> tic; for i=1:3; c(:,i) = eig(rand(1000)); end; toc  
Elapsed time is 2.036540 seconds.
```

- MATLAB has its own profiling tools
 - `help profile`

Basic Plotting with MATLAB

```
N = 1000;  
f = zeros(N+1,1);  
t = zeros(N+1,1);  
for i = 1:N  
    t(i) = (i-1)/N;  
    f(i) = sin(2*pi*t(i));  
end  
plot(t,f);  
title('The Sine Function'); xlabel('t', 'FontSize',14);  
ylabel('sin(2 pi t)', 'FontSize',14);  
print -djpeg myfig.jpg  
print -depsc -r300 myfig.ps  
print -dtiff myfig.tiff
```

Basic Plotting + Vectorization

```
N = 1000;  
t = [1:N]/N;  
f = sin(2*pi*t);
```

```
plot(t,f);  
title('The Sine Function'); xlabel('t', 'FontSize',14);  
ylabel('sin(2 pi t)', 'FontSize',14);  
print -djpeg myfig2.jpg  
print -depsc -r300 myfig2.ps  
print -dtiff myfig2.tiff
```

Histograms

```
dat = randn(10000, 1);
```

```
hist(dat)
```

```
hist(dat, 50)
```

```
b = hist(dat, 6)
```

```
bar(b)
```

```
print -dtiff myhistogram.tiff
```

3D Plots

```
[X,Y] = meshgrid(-2:.2:2, -2:.2:2);  
Z = X .* exp(-X.^2 - Y.^2);  
surf(X,Y,Z)  
xlabel ('X','FontSize',18)  
ylabel ('Y','FontSize',18)  
zlabel ('Z','FontSize',18)  
title ('3D X,Y,Z Plot of Z = X .* exp(-X.^2 - Y.^2)','FontSize',18)  
print -dtiff myfig2.tiff
```

Exercise (3)

- Create a vector, t , that ranges from 0 to 1 with 1000 equally spaced points. Plot the functions $\cos(2\pi t)$. label the x and y axis

Ways To Learn MATLAB

- Tutorial videos at mathworks.com
- Built-in demos:
 - doc demo
- Browse the online documentation
- Dozens of books:
 - Amazon.com reports 4,600 search results!
- MATLAB Central: user community site
 - <http://www.mathworks.com/matlabcentral>
- Useful programs by John Burkardt –
 - http://people.sc.fsu.edu/~jburkardt/m_src/m_src.html
- Questions to support@mathworks.com

MATLAB Documentation


help cos
doc cos

clf, peaks

click on rotate3D icon

which peaks
edit peaks

lookfor rotate



Browsing Online Documentation

Help pulldown menu

- > Product Help

In the help browser:

- > MATLAB
 - > Statistics Toolbox
 - > User's Guide
 - > Probability Distributions
 - > Supported Distributions
 - > Beta

MATLAB BASICS

Summary

- *help command* → Online help
- *lookfor keyword* → Lists related commands
- *which* → Version and location info
- *clear* → Clears the workspace
- *clc* → Clears the command window
- *diary filename* → Sends output to file
- *diary on/off* → Turns diary on/off
- *who, whos* → Lists content of the workspace
- *more on/off* → Enables/disables paged output
- *Ctrl+c* → Aborts operation
- *...* → Continuation
- *%* → Comments

Introduction to MATLAB Part II

- parallel computing
 - compiling M code
 -
-
- will try to tailor it as per your requests

Questions?

- My office – PGH 223
- Email – aramritkar@uh.edu
- Please leave your feedback!