



Graph Traversals


Graph Representation

- ▶ $G=(V,E)$
 - ▶ V : set of vertices
 - ▶ E : set of edges
 - ▶ Directed edge: (u,v)
 - ▶ Undirected edge: $\{u,v\}$
- ▶ Graph representations affect the complexity of algorithms

Adjacency List: Undirected





Adjacency Matrix: Undirected




	1	2	3	4	5
1	0	1	1	1	0
2	1	0	0	1	0
3	1	0	0	1	1
4	1	1	1	0	1
5	0	0	1	1	0

Adjacency List: Directed



Adjacency Matrix: Directed



	1	2	3	4	5
1	0	1	0	1	0
2	0	0	0	1	0
3	1	0	0	1	1
4	0	0	0	0	0
5	0	0	0	1	0

Graph Representation: Comparison

- ▶ Adjacency list
 - ▶ Space: $\Theta(|V| + |E|)$
 - ▶ Random access an edge: $O(d)$ **d: degree**
 - ▶ Enumerate edges incident to a vertex: $O(d)$
- ▶ Adjacency matrix
 - ▶ Space: $\Theta(|V|^2)$
 - ▶ Random access an edge: $\Theta(1)$
 - ▶ Enumerate edges incident to a vertex: $O(|V|)$

Graph Traversal

- ▶ Visit reachable nodes from a certain node s in a graph $G=(V,E)$
 - ▶ Breadth-First-Search (BFS)
 - ▶ Depth-First-Search (DFS)
- ▶ Application
 - ▶ Finding the shortest paths in unweighted graphs or weighted DAGs
 - ▶ Cycle detection
 - ▶ Topological sort
 - ▶ Others

Breadth First Search

- ▶ Initialization:


- ▶ for each $v \in V$: $\text{enqueued}[v] = \text{visited}[v] = \text{false}$
- ▶ $\text{enqueued}[s] = \text{true}$, $Q.\text{enqueue}(s)$

- ▶ Main loop: $\text{while}(Q \neq \emptyset)$

- ▶ $u = Q.\text{dequeue}()$
for each v s.t. $(u, v) \in E$
if $\text{enqueued}[v] == \text{false}$
 $\text{enqueued}[v] = \text{true}$, $Q.\text{enqueue}(v)$
 $\text{visited}[u] = \text{true}$

Example: BFS

Starting at A




Queue



Example: BFS

Starting at A




Queue

E	F						
---	---	--	--	--	--	--	--

Example: BFS

Starting at A




Queue

F	G						
---	---	--	--	--	--	--	--

Example: BFS

Starting at A




Queue


G							
---	--	--	--	--	--	--	--

Example: BFS

Starting at A




Queue



Done!

Example 2: BFS

Starting at B




Queue

B							
---	--	--	--	--	--	--	--

Example 2: BFS

Starting at B




Queue

A	C	F					
---	---	---	--	--	--	--	--

Example 2: BFS

Starting at B




Queue

C	F	E					
---	---	---	--	--	--	--	--

Example 2: BFS

Starting at B




Queue

F	E	G					
---	---	---	--	--	--	--	--

Example 2: BFS

Starting at B




Queue

E	G						
---	---	--	--	--	--	--	--

Example 2: BFS

Starting at B




Queue



Example 2: BFS

Starting at B



Queue



Done!

Depth First Search

- ▶ Initialization:


- ▶ for each $v \in V$: $discovered[v] = visited[v] = false$

- ▶ DFS-visit(u)

- ▶ $discovered[u] = true$
for each v s.t. $(u, v) \in E$
if $discovered[v] == false$
DFS-visit(v)
 $visited[u] = true$

Example: DFS

Starting at A




Stack

A/o							
-----	--	--	--	--	--	--	--

Example: DFS

Starting at A




Stack

A/o	F/o						
-----	-----	--	--	--	--	--	--

Example: DFS

Starting at A




Stack

A/o	F/o	G/o					
-----	-----	-----	--	--	--	--	--

Example: DFS

Starting at A




Stack

A/o	F/1						
-----	-----	--	--	--	--	--	--

Example: DFS

Starting at A




Stack

A/1							
-----	--	--	--	--	--	--	--

Example: DFS

Starting at A




Stack

A/1	E/o						
-----	-----	--	--	--	--	--	--

Example: DFS

Starting at A




Stack



Example: DFS

Starting at A




Stack



Done!

Example 2: DFS

Starting at A




Stack

A/o							
-----	--	--	--	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/o	E/o						
-----	-----	--	--	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/o	E/o	F/o					
-----	-----	-----	--	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/o	E/o	F/o	G/o				
-----	-----	-----	-----	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/o	E/o	F/1					
-----	-----	-----	--	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/o	E/1						
-----	-----	--	--	--	--	--	--

Example 2: DFS

Starting at A




Stack

A/1							
-----	--	--	--	--	--	--	--

Example 2: DFS

Starting at A




Stack



Done!

Example 3: DFS

Starting at B




Stack

B/o							
-----	--	--	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o						
-----	-----	--	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o	E/o					
-----	-----	-----	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o	E/o	F/o				
-----	-----	-----	-----	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o	E/o	F/o	G/o			
-----	-----	-----	-----	-----	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o	E/o	F/1				
-----	-----	-----	-----	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/o	E/1					
-----	-----	-----	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/o	A/1						
-----	-----	--	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/1							
-----	--	--	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/1	C/o						
-----	-----	--	--	--	--	--	--

Example 3: DFS

Starting at B




Stack

B/2							
-----	--	--	--	--	--	--	--

Example 3: DFS

Starting at B



Stack



Done!