

(Theory of Computation)

Push Down Automata(PDA):



$$PDA = (\emptyset, \Sigma, \delta, \%, F) \cup (z_0, \Gamma)$$

H/p Alphabet

set of pushdown symbol

$$PDA = (Q, \Sigma, \delta, \Gamma, z_0, \Sigma, F)$$


finite non empty set of states

Transition function

Initial state

$q_0 \in Q$

$$\delta: Q \times (\Sigma \cup \{\}) \times \Gamma \rightarrow Q \times \Gamma^*$$



Initial push down symbol

Initial pushdown Symbol

$$DPA: Q \times \Sigma \rightarrow Q$$

$$NFA: Q \times \Sigma \rightarrow 2^Q$$

$$\Gamma^* = \{\epsilon, \Gamma, \Gamma\Gamma, \Gamma\Gamma\Gamma, \dots\}$$

(Theory of Computation)

26

Instantaneous Description (ID): - Instantaneous Description (ID) is an informal notation of how a PDA "computes" a input string and make a Decision that string is accepted or rejected.

A - ID is a triple (q, ω, a) , when

1. q is the current state
2. ω is the remaining input
3. a is the stack contents, top at the Left.

$$L = \{a^n b^n \mid n > 0\} = \{a^2, c^2 a^2, a^3 b^3, a^4 b^4, \dots\}$$

~~a²b²~~

a³b³



Turnstile Notation: \vdash Sign is Called a 'turnstile notation' and represents one move

\vdash^* Sign represents a sequence of Moves

i.e $(p, b, T) \vdash (q, \omega, a)$

\vdash

\vdash



This implies that while taking a transition from state p to state q , the input symbol b is consumed and the top of the STACK 'T' is replaced by a new string ' a '

(Theory of Computation)

Acceptance by PDA:

1. Acceptance by final: A PDA accepts a string when, after reading the entire string, The PDA is in a final state

$\boxed{\delta(q_0, \omega, z) \vdash^* (q_f, \epsilon, \alpha)}, q_f \in F, \alpha \in \Gamma^*$ 26

$\boxed{\text{PDA} = (Q, \Sigma, \delta, q_0, z_0, F)} \Rightarrow 7 \text{ tuples}$

Let $P = (Q, \Sigma, \delta, q_0, z_0, F)$ be a PDA the language accepted by the final state can be defined as

$$L(PDA) = \{ \omega \mid (q_0, \omega, z_0) \vdash^* (P, \epsilon, X), P \in F, X \in \Gamma^* \} \quad \boxed{\text{PDA} = (Q, \Sigma, \delta, q_0, z_0, \emptyset)}$$

2. Acceptance by Empty stack: Here a PDA accepts a string when, after reading the entire string, The PDA has emptied its stack.

$$N(PDA) = \{ \omega \mid (q_0, \omega, z_0) \vdash^* (P, \epsilon, \epsilon), P \in Q \}$$

$\boxed{\delta(q_0, \omega, z) \vdash^* (q', \epsilon, \epsilon)}$ STACK Empty

Initial $\Rightarrow q' \in Q$

NOTE: - if acceptance is defined by empty stack, then there is no meaning of final state and it is represented by \emptyset

(Theory of Computation)

Null Moves: The PDA can make a transition without taking input symbol such moves are called null moves

26

$$\delta(q_0, \epsilon, z) \rightarrow (q_1, az)$$

$$\delta(q_4, abb, z) \rightarrow (q_5, bz)$$

$$\delta: Q \times (\Sigma \cup \epsilon) \times \Gamma \rightarrow Q \times \Gamma^*$$

$$\begin{cases} \delta(q_1, \epsilon, z) \rightarrow (q_1, az) \\ \delta(q_1, \epsilon, z) \neq \emptyset \end{cases}$$

$$\begin{cases} \delta(q_4, ab, z) = \emptyset \\ \delta(q_4, ab, z) \neq \emptyset \end{cases}$$

Deterministic PDA(DPDA): A PDA is said to be deterministic if it satisfies the following 2 conditions

- 1. Every $\delta(q, a, z)$ is either empty or has a single move
- 2. If $\delta(q, \epsilon, z) \neq \emptyset$ then $\delta(q, a, z) = \emptyset$, for all $a \in \Sigma$

NULLmove

- 1. $\delta(q, \epsilon, z) \neq \emptyset$
- 2. $\delta(q, a, z) \neq \emptyset$

(Theory of Computation)

Non Deterministic PDA (NPDA):

$$\boxed{\delta: Q \times \Sigma \cup \epsilon \times \Gamma \rightarrow 2^{Q \times \Gamma^*}}$$



$$\delta(q_1, q_1, z) \xleftarrow{\text{HDDA}} (q_1, q_2), (q_2, z), (q_3, bz), (q, z)$$

~~DPDA~~

$$\text{DPDA}: Q \times (\Sigma \cup \epsilon) \times \Gamma \rightarrow Q \times \Gamma^*$$

$$\text{NPDA} : Q \times (\Sigma \cup \epsilon) \times \Gamma \rightarrow 2^{Q \times \Gamma^*}$$

CFG

CFL

NDCFL(CF)

~~NPDA~~

DGFL

$$\boxed{P(\text{DPDA}) < P(\text{NPDA})(\text{PDA})}$$

(Theory of Computation)

Difference b/w DPDA & NPDA:

Deterministic PDA (DPDA)	Non Deterministic PDA (NPDA)
✓ 1. Choice is not Allowed in DPDA	✓ 1. Choice Allowed in NPDA
✓ 2. Dead Configuration is Allowed in DPDA	✓ 2. Dead configuration is allowed in NPDA
3. Null moves Allowed Conditionally	3. Null Moves is allowed unconditionally.
4. $\delta: Q \times (\Sigma \cup \{\epsilon\}) \times \Gamma \rightarrow Q \times \Gamma^*$	4. $\delta: Q \times (\Sigma \cup \{\epsilon\}) \times \Gamma \rightarrow 2^{Q \times \Gamma^*}$
5. it is less powerful than NPDA	5. It is more powerful than DPDA
6. Language Accepted by DPDA is called DCFL	6. Language Accepted by NDPA is called NDCFL
7. It is Possible to Convert every DPDA to a corresponding NPDA	7. It is not possible to convert NDPA to a corresponding DPDA.

(Theory of Computation)


26

Representation of PDA:

1) Push:

$$\boxed{\delta(q_0, a, z_0) \vdash (q_1, az_0)}$$



(or)



$$\delta: Q \times (\Sigma \cup \epsilon) \times P \rightarrow Q \times P^*$$

2) Pop: $\delta(q_0, a, z_0) \vdash (q_1, \epsilon)$

or



$$\delta(q_0, a, z_0) \vdash (q_1, z_0)$$

or




(Theory of Computation)

26

PDA Designing:

Ex:- Design a PDA for the Language $L = \{a^n b^n | n > 0\}$

$L = \{ab, a^2b^2, a^3b^3, a^4b^4, \dots, \overline{ba}, \overline{aabb}, aabbbaab^b, \infty aabbbaab^b\}$



$S(\varrho_0, \epsilon, z_0) \vdash (\varrho_f, z)$: Acceptance by final state
or
 $S(\varrho_0, \epsilon, z_0) \vdash (\varrho_0, \epsilon, \epsilon)$] Empty stack (Acceptance)

(Theory of Computation)

26

$$L = \{ a^n b^n \mid n > 0 \}$$

$$\delta(q_0, a, z_0) \vdash (q_0, az_0)$$

$$\checkmark \quad \delta(q_0, a, a) \vdash (q_0, aa)$$

$$\delta(q_0, b, a) \vdash (q_1, \epsilon)$$

$$\delta(q_0, \epsilon, z_0) \vdash (q_0, \epsilon)$$

Analysis:

$$\cancel{a^2 b^3}, \cancel{a^3 b^2}$$


$$\delta(q_0, b, z) \vdash \delta(q_0, b | \boxed{\epsilon})$$

reject

Wrong Design b/c it Accept $a^n b^n \mid n > 0$
 not ~~per feal~~

and some Non Valid string $\epsilon, a^2 b^2 \text{ as},$

$$a^4 b^4 a^2 b^2 \xrightarrow{q_0} q_6 \xrightarrow{a^6} (q_i b^i)^*$$



$$\delta(q_0, a, z_0)$$


$$\delta(q_0, \epsilon, \underline{a})$$

Rejct.

(Theory of Computation)

26

$$\left\{ \begin{array}{l} \delta(q_0, a, z) \vdash (q_0, az) \\ \delta(q_0, a, a) \vdash (q_0, aa) \\ \delta(q_0, b, a) \vdash (q_1, \epsilon) \\ \delta(q_1, b, a) \vdash (q_1, \epsilon) \\ \boxed{\delta(q_1, \epsilon, z) \vdash (q_1, \epsilon)} \end{array} \right.$$



$\delta(q_1, a, z) = \emptyset$

$\delta(q_1, b, z) = \emptyset$

Acceptance by final state

DCFL

$$L_{DCFL} = \{a^n b^n | n > 0\}$$

Acceptance by Empty STACK


(Theory of Computation)

Ex:- Design DPDA for $L = \{a^n b^n \mid n \geq 0\}$ DCPL

$$L = \{ \text{as, as'5, as'3bs', as'4bs', ...} \}$$


DPDA

by empty
stack



$$\delta(a_0, \epsilon_{z_0}) \vdash (q_1, \epsilon)$$

$$\delta(q_0, a, z) = (q_0, q_0)$$




DPDA by fncl stc

(Theory of Computation)

26

$$L = \{a^n b^n \mid n \geq 0\}$$





(Theory of Computation)

26

Ex: $L = \{a^n b^{2n} \mid n \geq 0\}$ Construct DPDA

$$L = \{ \epsilon, a b^2, a 2b^4, a^3 b^6, a^4 b^8, \dots \}$$




(Theory of Computation)

Ex:- $L = \{ \omega \in (a,b)^*, N_b(\omega) = N_a(\omega) \}$ is DCFL





~~$L = \{ \epsilon, ab, ba, dab, bca, aab, aabb, \dots \}$~~




(Theory of Computation)

Ex:- ~~$L = \{ w \in \{a,b\}^* \mid w \in (a,b)^T \}$~~ = ~~odd length palindromes~~ \rightarrow DCFL

DPDA by empty stack



DPDA by final state






~~NDFA~~

~~$L = \{ w \in \{a+b\}^* \mid w \in (a+b)^T \}$~~

(Theory of Computation)

26

$$\text{Ex:- } L = \{ w \cdot w^T \mid w \in \{a, b\}^*\} = \{ \epsilon, aa, bb, abba, aaaa, bbbb, \dots \}$$




(Theory of Computation)

Ex:- $L = \{a^m b^n \mid m, n > 0\} \Rightarrow \underline{\text{PDA}} \Rightarrow \underline{\text{RL}} \Rightarrow \underline{\text{DFA}} \Rightarrow$

26

$$L = \{a^m b^n \mid m, n > 0\}$$



~~\$, z0/z0~~

~~b, z0/z0~~


DPDA

~~\$, z0/z0~~

~~b, z0/z0~~

~~DPDA by
Empty Stack~~

~~\$~~
~~#~~



$$\delta(q_2, \epsilon, z) = (q_2, z)$$


$$\delta(q_2, b, z) = (q_2, z)$$

(Theory of Computation)

26

Ex:-

Given PDA accept language?



HODA by EmplisTayy

\$



$$L = \{ a^n b^m \mid m, n > 0 \}$$



each \$
↑↑↑↑↑↑↑↑

(Theory of Computation)

26

Ex:- $L = \{a^m b^n \mid m > n > 0\}$ is DCFI = ?


~~DCFL~~
 $L = \{a^m b^n \mid m > n > 0\}$ - - - 3

~~m > n~~

~~a a a b b~~



DPDA




~~Non DFA~~

~~Non PDA~~

(Theory of Computation)

26



Ex:- $L = \{a^m b^n c^{m+n} \mid m, n > 0\}$ is DCFL ?



(Theory of Computation)

Ex:-

$$L = \{a^n b^n c^n \mid n > 0\} \Rightarrow \text{not CFL} \Rightarrow \text{CSL}$$



2 STACK PDA

CSTM


$$L = \{a^n b^n c^n \mid n \leq 10\}$$

Diagram illustrating the decomposition of the string aabbcc into a^n b^n c^n for $n \leq 10$. The stack diagram on the right shows the sequence of pushes and pops for the characters 'a' and 'c'.

TM

(Theory of Computation)

Ex:- $L = \{a^m b^n c^m d^n \mid m, n \geq 1\}$ {CSC}




$$a^3 b^2 c^3 d^2$$

$$a^m b^m c^m d^n$$


$L = \{a^m b^m c^n d^n \mid m, n \geq 1\}$

26

DONE




(Theory of Computation)



(Theory of Computation)

Ex^o: Design a PDA for the following language



(Theory of Computation)

26

Ex: Design PDA for the following Languages

(i) $L = \{a^m b^n c^k \mid m=n \text{ or } n=k, m, n, k \geq 1\} \Rightarrow \text{NDUPL}$

~~NDUPL~~ (or) $L = \text{DUPL}$ ~~2-DUPL~~

$$L = \{a^n b^n c^k \cup a^m b^k c^k \mid m, k \geq 1\}$$

~~DUPL~~ $a^n b^n c^k$ $a^m b^k c^k$

$\Rightarrow \text{CSL}$

(ii) $L = \{a^m b^n c^k \mid m=n \text{ AND } n=k, m, n, k \geq 1\} \Rightarrow \text{HotCPL}$

~~(or)~~ $L = \{a^m b^m c^m \mid m \geq 1\}$

$\Rightarrow \text{HotCPL}$