

Normalization and scaling

Lucie Pfeiferova

December 1.-3. 2025

Course on scRNA-seq Data Analysis

Motivation and Learning objectives

- Normalization reduces technical differences so that differences between cells are not technical but biological, allowing meaningful comparison of expression profiles between cells.
- Distinguish Normalization, Transformation, and Scaling
- Identify and apply Normalization techniques

Source of differences

- Biological
 - Cell subtype differences - size and transcriptional activity, variation in gene expression
- Technical: scRNA data is inherently noisy
 - Low mRNA content per cell
 - Cell-to-cell differences in mRNA capture efficiency
 - Variable sequencing depth
 - PCR amplification efficiency


Raw counts problematic

- 1. Library size bias → deeper sequenced cells dominate
- 2. Zero-inflation → most genes = 0
- 3. High dynamic range

Normalization, transformation, scaling


- **Normalization = correct for sequencing depth**
→ “Make cells comparable.”
- **Scaling = equalize gene variance**
→ “Make genes comparable.”
- **Transformation = stabilize distribution**
→ “Make the numbers behave statistically.”

Normalization process in scRNA-seq



Normalization process in scRNA-seq

- 1. Remove sequencing-depth (library-size) differences so that cells are comparable.
- Scale to common factor



Normalization process in scRNA-seq

- 1. Remove sequencing-depth (library-size) differences so that cells are comparable.
- 2. Scale to common factor
- 3. Transform values (with log)

Raw data				Log ₂ transform			
	Cell Type A	Cell Type B	Δ	Cell Type A	Cell Type B	Δ	
Gene 1	1	2	1	0	1	1	
Gene 2	100	200	100	6.64	7.64	1	

SCTransform

- **1. Model fitting:**
 - Fit a **negative binomial generalized linear model (NB-GLM)** for each gene.
 - Total UMI count per cell is used as a **covariate** (proxy for sequencing depth).
- **2. Parameter regularization:**
 - Intercept, slope, and dispersion parameters are **regularized** based on their relationship with gene mean.
 - Prevents **overfitting** and stabilizes parameter estimates, especially for lowly expressed genes.
- **3. Variance-stabilizing transformation:**
 - Use the regularized model to compute **Pearson residuals**.
 - These residuals represent normalized, variance-stabilized expression values.

SCTransform

- **1. Model fitting:**
 - Fit a **negative binomial** model to the data
 - Total UMI count per cell
- **2. Parameter regularization:**
 - Intercept, slope, and delta relationship with gene
 - Prevents **overfitting** on lowly expressed genes.
- **3. Variance-stabilizing transformation.**
 - Use the regularized model to compute **Pearson residuals**.
 - These residuals represent normalized, variance-stabilized expression values.

		Raw data		
		Cell Type A	Cell Type B	Δ
Gene 1		1	2	1
Gene 2		100	200	100

		Log ₂ transform		
		Cell Type A	Cell Type B	Δ
		0	1	1
		6.64	7.64	1

		Pearson residuals		
		Cell Type A (50%)	Cell Type B (50%)	Δ
Gene 1		0.816	1.63	0.814
Gene 2		8.16	16.3	8.14

Summary

Step	What it does	Why it's needed	Typical methods
Normalization	Adjusts library size / sequencing depth differences between cells	Cells have different total RNA counts; normalization puts them on the same scale	CPM/TPM, Size-factor methods (e.g., scran), SCTransform's model-based approach
Scaling	Adjusts per-gene variance across genes or cells	Prevents highly expressed genes from dominating analyses such as PCA	Z-score scaling, regression of covariates
Transformation	Changes the distribution of gene expression values	RNA counts are skewed; transformations stabilize variance and make data more normally distributed	log1p, variance stabilizing transformation (VST), SCTransform

Bonus – normalization by deconvolution


- **Why deconvolution?**
- Single cells have **low UMI counts**, making size factor estimation unstable.
- Many genes show **zero expression**, causing unreliable per-cell normalization.
- Deconvolution improves accuracy by **borrowing information across cells**

Bonus – normalization by deconvolution

- **1. Pooling:**
 - Group cells into pseudo-bulk pools to create higher-coverage “pseudo-samples.”
 - This reduces sparsity and increases signal for size factor estimation.
- **2. Compute pool-based size factors:**
 - Estimate size factors on pooled data, where zeros are less problematic.
- **3. Deconvolution:**
 - Mathematically solve for **individual cell size factors** from overlapping pools.
 - Ensures cell-specific normalization factors consistent across all pools.
- **4. Normalize counts:**
 - Divide each cell’s gene counts by its deconvolved size factor.

Bonus – normalization by deconvolution

- **1. Pooling:**
 - Group cells into pools
 - This reduces sparsity
- **2. Compute pool size factors**
 - Estimate size factor for each pool
- **3. Deconvolution**
 - Mathematically separate cell-specific signals
 - Ensures cell-specific normalization
- **4. Normalize counts**
 - Divide each cell's gene counts by its deconvolved size factor.



- <https://sib-swiss.github.io/single-cell-r-training/>
- Amezquita, R. A., Lun, A. T. L., Hicks, S. C., Marini, F., et al. (2020). Orchestrating single-cell analysis with Bioconductor. *Nature Methods*, 17(2), 137–145.
- <https://bioconductor.org/books/3.14/OSCA.basic/>
- <https://bioconductor.org/books/release/OSCA/>
- Hafemeister C, Satija R (2019). “Normalization and variance stabilization of single-cell RNA-seq data using regularized negative binomial regression.” *Genome Biology*, 20, 296. doi:10.1186/s13059-019-1874-1, <https://doi.org/10.1186/s13059-019-1874-1>.