

# Point-to-Point Network Switching

# Point-to-Point Network Switching

- Circuit Switching, Message Switching, Packet Switching, Cell Switching
- Connection-Oriented versus Connectionless
- Virtual Circuit versus Datagram Networks
- Internal/External Abstractions

# Point-to-Point Switching

- Circuit Switching
- Store-and -Forward Networks
  - Message Switching
  - Packet Switching
    - connection-oriented vs connectionless
    - virtual circuit vs datagram
  - Cell Switching

# Circuit Switching

- Seeking out and establishing a physical copper path from end-to-end  
.
- Circuit switching implies the need to first **set up** a , end-to-end path for the connection **before** the information transfer takes place.
- Once the connection is made the only delay is propagation time.

# Circuit Switching




Figure 2-38. (a) Circuit switching. (b) Packet switching.

# Store-and-Forward Networks

- Intermediate processors (IMPS, nodes, routers, gateways, switches) along the path store the incoming block of data.
- Each block is received in its entirety, inspected for errors, and retransmitted along the path to the destination. This implies buffering at the router and one transmission time per hop.

# Message Switching

- A store-and-forward network where the block of transfer is a complete .
- Since messages can be quite large, this can cause:
  - buffering problems
  - high mean delay times

# Packet Switching

- A store-and-forward network where the block of transfer is a complete . A packet is a variable length block of data with a tight upper bound.

⇒ Using packets improve mean message delay.



# Cell Switching



53 bytes


- A network where the unit of transfer is a small, fixed-size block of data (i.e., one cell).
- ATM (Asynchronous Transfer Mode) networks use 53-byte cells.

# Packet Switched Networks

## Connection-oriented Protocols

- A setup stage is used to determine the end-to-end path before a connection is established.

# Connection-Oriented Concatenation of Virtual Circuits




Internetworking using concatenated virtual circuits.

# Packet Switched Networks

## Connectionless Protocols

- No set up is needed.
- Each packet contains information which allows the packet to be individually routed hop-by-hop through the network.

# Connectionless Internetworking



A connectionless internet.

# Datagram vs Virtual Circuit

## Datagram


- Each datagram packet may be individually routed.

## Virtual Circuit


- Virtual circuit set up is required.
- All packets in a virtual circuit follow the same path.

# Event Timing


(a) Circuit switching





(b) Virtual circuit packet switching



(c) Datagram packet switching




# External Virtual Circuit And Datagram Operation






# Internal Virtual Circuit And Datagram Operation



(a) Internal virtual circuit. A route for packets between two stations is defined and labeled. All packets for that virtual circuit follow the same route and arrive in the same sequence.



(b) Internal datagram. Each packet is treated independently by the network. Packets are labeled with a destination address and may arrive at the destination node out of sequence.