



- PCV and SIMV+PS modes ensure flexibility in ventilation, suitable for both pediatric and adult operation
- Flowmeter with backlight, suitable for endoscopy surgery etc.
- Breathing system warmer for avoid condensation build-up during low-flow anesthesia
- Enhances usability with auxiliary oxygen, suction, auxiliary power source, monitor arm, infusion pump etc.
- Optional functions monitoring O₂, CO₂ and anesthetic gas
- With CE certificate, meets EU clinical requirement

Aeon8600A

Anaesthesia Machine

CE 0123

AEOMED
Reliable Quality Thoughtful Service

Technical Specification

Physical & Environment Specifications

- Dimensions(WxHxD): 704mm × 1403mm × 750mm
- Weight: 115kg (including trolley base and 2 vaporizers, without cylinder)
- Operation Temperature: +10~+40°C
- Operation Humidity: ≤80% (noncondensing)
- Storage Temperature: -20~+55°C
- Storage Humidity: ≤93% (noncondensing)

Electrical Specifications

- Mains: 100~240V AC, 50/60Hz
- Battery: 24V DC, minimum 120 min
- Outlets: 4 on back, 1.5A individual

Pneumatic Specifications

- Gas Supply: Air, O₂, N₂O; 280kPa ~ 600kPa
- Flowmeters: O₂ Range: 0~1L/min; 1~10L/min
N₂O Range: 0~1L/min; 1~10L/min
Air Range: 0~1L/min; 1~12L/min
Auxiliary O₂ Range: 0 ~15 L/min
- Gas System: Flowmeter backlight
Oxygen supply failure alarm
N₂O-cut-off system
O₂ flush: 25~75L/min
- ACGO: Optional auxiliary common gas outlet
- AGSS: Optional anesthetic gas scavenging system

Breathing System Specifications

- Operational Modes: Closed, Semi-closed, Semi-open
- CO₂ Canister: 2 Loose fill (3L) or 2 prepacks, optional single canister (1.8 L)
- APL Range: Spontaneous breathing (SP) - 70 cmH₂O
- Material: Autoclavable (except O₂ cell and mechanical pressure gauge)
- CO₂ bypass: Optional

Ventilator Specifications

- Driven Mode: Pneumatically driven and electronically controlled
- Patient Types: Adult, Pediatric
- Ventilation Modes: IPPV, PCV, SIMV+PS, PS and Manual
- Setting Modes: Touch key & navigator wheel knob
- Tidal Volume: 20~1500ml
- Ventilation Frequency: 4~100bpm
- I:E Ratio: 4:1~1:8
- Pressure (inspired) Range: 5~70cmH₂O
- Pressure (support) Range: 3~50cmH₂O
- PEEP: Off, 3~30 cmH₂O
- Tslope: 0~2s
- Inspiratory Plateau: Off, 5%~60%Ti
- Trigger Sensitivity: 1~15L/min
- Compensation: Compliance and leakage compensation, fresh gas compensation and altitude compensation

Ventilator Monitoring

- Display: 10.4" TFT color screen
- Pressure: P_{peak}, P_{plat}, P_{mean}, PEEP
- Volumes: MV, Vt, Freq
- Gas: O₂ Concentration, optional CO₂, Agent and MAC
- Graph Display: P-t, F-t, P-V, F-V loops(can be saved), optional CO₂-t
- Alarm: High Airway Pressure/Low Airway Pressure
Sustained airway pressure
High Minute Volume/Low Minute Volume
High FiO₂/Low FiO₂
High Breath Rate
O₂ Supply failure
Power failure
Apnea Alarm
Alarm Silence: 110 seconds

Vaporizer

- Support two vaporizers
- Agent: Halothane, Enflurane, Isoflurane, Sevoflurane
- Installation Mode: Selectatec® with interlock, optional standby vaporizer parking holder
- Filling Type: Pour Fill, Key Fill, Quik-Fil

Remark: Above configurations include standard and option. Please check price with your Aeonmed sales representative.



AEOMED
Reliable Quality Thoughtful Service

HQ: No.4 Hangfeng Road, Fengtai Science Park, Fengtai District, Beijing, China (100070)
Science Park: No. 10, Chaobai Street, Yanjiao Development Zone, Sanhe City, Hebei Province, China (065201)
TEL: +86-10-5841 1198 FAX: +86-10-6371 8989
Http: //www.aeonmed.com E-mail: marketing@aeonmed.com

Information contained in this leaflet is correct at the date of publication. The policy of Beijing Aeonmed Co., Ltd. is one of the continued improvement to its products. Because of this policy Beijing Aeonmed Co., Ltd. reserves the right to make any change, which may affect the information in this leaflet without giving prior notices.

AAM8600A-1703