CONTROLUNION	APPLE QUALITY & CONDITION ASSESSMENT - INSPECTION CHECKLIST	Doc number	CUC/FM/054
		Revision No.	00
		Date	08/08/26

Quality condition assessment checklist

Purpose: This checklist covers both quality defects (e.g. undersize, misshape and sunburn) and condition defects (e.g. decay, mould, bruising and chilling/freezing damage).

1. Consignment & Appointment Details

Client / Requesting Party	
Facility Name	
Facility Address	
Site Contact — Name	
Site Contact — Phone	
Inspection Date	
Inspection Start / End Time	
Lead Inspector	
Container Number(s)	
Reference / Job Number	

2. Consignment Identification

Variety / Varieties	
Grower(s) / Packer(s)	
Category / Class	
Packing Date(s)	
Total Pallets in Lot	
Total Boxes in Lot	
Prior Inspection Stamps Noted? (Y/N — details)	

3. Sample Selection (6 boxes / 6 pallets minimum)

Standard sample: 6 boxes from 6 different pallets, with 1 box selected per pallet. Additional samples may be taken where necessary to achieve representative coverage.

Boxes shall be taken from the 2nd row or below and not from the top row. Previously opened or inspected/stamped boxes shall not be re-inspected.

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi

Sample No.	Pallet No.	Box No. / Label Ref.	Row Taken From (2nd row or below)	Previously Opened / Stamped?
1				
2				
3				
4				
5				
6				
Additional — reason:				

4. Instrument Readings

Reference: SOP §6. Equipment for this assignment: weighing scale, calibration masses (500 g / 250 g), probe thermometers (2 pcs), cutting machine. Refractometer and penetrometer are not part of the standard kit — confirm availability below before the inspection.

4.1 Equipment Availability Check

Refractometer available for this assignment? (Y / N / Not Available)	
Penetrometer available for this assignment? (Y / N / Not Available)	
If either is unavailable, note under Section 8 (Limitations)	

4.2 Weighing Scale Verification (before use)

Calibration Mass Used	Known Mass	Scale Reading	Pass / Fail
	500 g		
	250 g		

4.3 Pulp Temperature & Weight

Sample No.	Pulp Temp (°C) [optimum 0–1°C]	Location/Time of Reading	Weight (g)	Within Size Table? (Y/N)
1				
2				
3				

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi

4				
5				
6				

4.4 Brix & Firmness

If no refractometer/penetrometer is available, write 'N/A – not available' in the relevant column. For firmness, still complete the tactile observation column by hand (see SOP §6.4) — this is not a substitute for an instrument reading.

Sample No.	Brix (°Bx)	Firmness (lb) — R1 [min. 14 lb]	Firmness (lb) — R2	Tactile Firmness Observation (if no penetrometer)
1				
2				
3				
4				
5				
6				

5. Quality Defects Log

Reference: SOP §7.1 and §7.4. Log one row per defect instance identified - undersize, under colour, skin defect, russet/scars (slight/moderate or severe), foreign material/dirty, mechanical damage, peduncle broken/absent, misshape, sunburn.

Sample/Box Ref.	Defect Type	Severity/Category	Fruits Examined	Fruits Affected	% Affected	Observations

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi

Total Quality Defects (%)					

6. Condition Defects Log

Reference: SOP §7.2, §7.3 and §7.4. Log one row per defect instance identified - decay, mould, softness, bruising, bitter pit, scald, dry fruit/shrivelling, water core damage, core flush, chilling/freezing damage, internal breakdown, open wounds, insect presence/damage. For suspected internal decay or internal breakdown, cut representative fruit using the cutting machine and note this under Observations, with a cross-reference to the corresponding photo.

Sample/Box Ref.	Defect Type	Severity/Category	Fruits Examined	Fruits Affected	% Affected	Observations

Total Condition Defects (%)					

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi

7. QC Score (per Apple Inspection Manual tolerance table)

	1 – Very Good	2 – Good	3 – Fair	4 – Poor	5 – Very Poor	Score Given
Total Quality Defects	> 0–5%	> 5–10%	> 10–20%	> 20–30%	> 30%	
Total Condition Defects	> 0–1%	> 1–10%	> 10–20%	> 20–30%	> 30%	

8. Condition & Handling Context at Time of Inspection

Reference: SOP §10. Record observed facts separately from third-party information and professional observations. Do not record conclusions on cause or responsibility unless supported by objective evidence and within the agreed scope.

Cargo moved / sorted / repacked before inspection? (Y/N — details)	
Cargo previously inspected? (Y/N — details, incl. stamps observed)	
Storage duration, if known	
Storage / temperature conditions observed	
Information provided by consignee/facility rep (attribute source)	
Limitations encountered during inspection	

9. Photographic Evidence

Photographic evidence will be compiled and included in the final survey report (see SOP §9), cross-referenced to the sample/box/pallet numbers recorded above.

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi

10. Inspector's Remarks

11. Sign-Off

Inspector Name	
Inspector Signature	
Date	
Site Representative Name	
Site Representative Signature	

Revision History

Version	Date	Description of Change	Prepared By	Approved By
1.0	08 August 2026	Initial issue	Isaac Sero	Albert Muriithi