

# Formulario F#

## 1 Funzioni

```
let nomeFunzione arg1 arg2 = <corpo funzione>
let rec nomeFunzioneRicorsiva arg1 arg2 = <corpo funzione>
fun arg1 arg2 -> <corpo funzione> // funzione anonima
```

## 2 Liste

1;2;3 → head::tail, head = 1, tail = [2;3]

- Usiamo @ per appendere una **lista** in coda ad un'altra, usiamo :: per concatenare un **elemento** in testa ad una lista

## 3 Pattern Matching

```
match x with
| 1 -> "Uno"
| 2 -> "Due"
| _ -> "Altro"
```

Si può usare il **when** per aggiungere condizioni

```
match x with
| x when x > 0 -> "Positivo"
| x when x < 0 -> "Negativo"
| _ -> "Zero"
```

## 4 Eccezioni

### 4.1 Per lanciarle

```
[altro codice] failwith "Messaggio di errore"
```

## 4.2 Per gestirle

```
try
  [codice che potrebbe lanciare eccezioni]
with
  | e -> printfn "Errore: %s" e.Message
```

## 5 Tipi

```
type nomeTipo = | Costruttore1 [of tipo1 * tipo2 * ...] | ...
```

## 6 Esempi di funzioni ricorsive e con accumulatore

### Accoppiamento elemento indice

```
// Senza accumulatore
let rec pairWithIndex list index =
  match list with
  | [] -> []
  | head :: tail -> (head, index) :: pairWithIndex tail (index+1)
// Con accumulatore
let pairWithIndexAcc list =
  let rec loop list acc =
    match list with
    | [] -> []
    | head :: tail -> (head, acc) :: loop tail (acc + 1)
  loop list 1
```

### Somma elemento per elemento

```
// Senza accumulatore
let rec sum_wise list1 list2 =
  match list1, list2 with
  | [], [] -> []
  | head1 :: tail1, head2 :: tail2 -> (head1 + head2) :: sum_wise tail1 tail2
  | _, _ -> failwith "Lists must have the same length"
// Con accumulatore
let sum_wise_acc list1 list2 =
  let rec loop list1 list2 acc =
    match list1, list2 with
    | [], [] -> List.rev acc
    | head1 :: tail1, head2 :: tail2 -> loop tail1 tail2 ((head1 + head2) :: acc)
    | _, _ -> failwith "Lists must have the same length"
  loop list1 list2 []
```

### Selezione elementi in base a condizione

```
// Senza accumulatore
let rec select comparer list1 list2 =
    match list1, list2 with
    | [], [] -> []
    | head1 :: tail1, head2 :: tail2 ->
        if comparer head1 head2 then
            head1 :: select comparer tail1 tail2
        else
            head2 :: select comparer tail1 tail2
    | _, _ -> failwith "Lists must have the same length"
// Con accumulatore
let select_acc comparer list1 list2 =
    let rec loop list1 list2 acc =
        match list1, list2 with
        | [], [] -> List.rev acc
        | head1 :: tail1, head2 :: tail2 ->
            if comparer head1 head2 then
                loop tail1 tail2 (head1 :: acc)
            else
                loop tail1 tail2 (head2 :: acc)
        | _, _ -> failwith "Lists must have the same length"
    loop list1 list2 []
```

## Unione di liste applicando funzione f

```
// Senza accumulatore
let rec combine f l1 l2 =
    match l1, l2 with
    | h1::t1, h2::t2 -> (f h1 h2)::(combine f t1 t2)
    | [], [] -> []
    | _ -> raise (System.ArgumentException("combine"))
// Con accumulatore
let accCombine f =
    let rec aux acc l1 l2 =
        match l1, l2 with
        | h1::t1, h2::t2 -> aux (f h1 h2 :: acc) t1 t2
        | [], [] -> List.rev acc
        | _ -> raise (System.ArgumentException("combine"))
    aux []
```

## Somma elementi lista (due elementi alla volta)

```
// Senza accumulatore
let rec agg = function
    | h1::h2::t -> h1+h2::agg t
    | l -> l
// Con accumulatore
let acc_agg =
    let rec aux acc = function
        | h1::h2::t -> aux (h1+h2::acc) t
        | [h] -> List.rev (h::acc)
```

```
    | _ -> List.rev acc  
in aux []
```

## Duplicazione elementi lista

```
// Senza accumulatore  
let rec dup = function  
| h::t -> h::h::dup t  
| _ -> []  
// Con accumulatore  
let accDup (l: 'a list) =  
    let rec aux (acc: 'a list) = function  
        | h::t -> aux (h::h::acc) t  
        | _ -> acc  
    List.rev (aux [] l)
```