

Optimization of Reverse Osmosis Performance

Angelica Persson
Pontus Lundberg



LUND
UNIVERSITY

Department of Automatic Control

MSc Thesis TFRT-9999
ISSN 0280-5316

Department of Automatic Control
Lund University
Box 118
SE-221 00 LUND
Sweden

© 2018 by Angelica Persson
Pontus Lundberg. All rights reserved.
Printed in Sweden by Media-Tryck.
Lund 2018

Abstract

A condensed description of my work.

Acknowledgements

These people helped me a lot with my work.

Contents

1. Introduction	9
2. Theory	12
2.1 Reverse osmosis membrane	13
2.2 System identification	13
2.3 Control theory	13
3. Equipment	14
3.1 Reverse osmosis membrane	15
4. Method	16
5. Results	18
6. Discussion	20
7. Conclusion	22

1

Introduction

Background

The Water Technologies department at Baxter develops water systems for use in mixing fluid for dialysis treatments. The water quality is important to not create any harm to the patients when using the final product. The water systems used for water purification are using the reverse osmosis (RO) method as the finest level of filtration. It remove impurities, as salt and inorganic molecules from the water[Dow].

In a RO-system the feed water is pressurized by a pump and forced through the RO-membrane to overcome the osmotic pressure. The RO-membrane is a semi-permeable membrane and let water passes freely true the membrane creating a purified product stream.

The pump in the current system has two purposes, creating a pressure to overcome the osmotic pressure and creating a flow on the reject side of the RO-membrane to prevent aggregation of impurities on the membrane surface.

Motivation

By using two pumps instead of one in the RO-system it will be possible to control the pressure on the module and the flow on the reject side independently and thus get better possibility to optimize the performance of the RO-system, focusing on reducing impurities and water consumption.

As the current model does not take temperature dependencies in concern, the model will be redesigned in order to handle temperature dependencies.

Goal

The purpose of this masters thesis is to evaluate the feasibility of replacing the main RO-pump with two pumps, one for controlling the flow through the membrane and one for controlling the pressure.

To achieve good performance it will be necessary to design a realistic model of the system, once the model has been designed and tested a control algorithm is to be developed. This algorithm, should be able to control the flow and pressure over the RO-membrane to maximize the efficiency of the filter while minimizing the amount of waste water that is produced.

The temperature dependencies will be taken in concern in the new model.

Method

In order to investigate the performance of the current system and to compare it with the new model following steps will be evaluated:

- Research on the RO-membrane that is implemented in the system
- Research on previous work on the field
- Modelling of the system to identify suitable component properties and design of the flow path
- Design of control algorithms
- Control simulations
- Implementation in a test rig to verify the performance of the system
- Run tests to determine the performance
- Improve if possible

2

Theory

2.1 Semi-permeable membrane

A membrane is defined as a barrier between two homogeneous phases. The process is a continuous steady-state operation consisting of three streams: feed, permeate and reject. Main concern in the process boundary is the semipermeable barrier that selectively allows the passage of some components but not others. [Singh]

2.2 Osmosis

The osmosis process occurs when two solutions of different chemical concentration are separated by a semi-permeable membrane. The two different solutions will try to reach equilibrium. The solution with less concentration will have a natural tendency to migrate through the membrane over to the side with higher concentration. Osmosis is a naturally occurring phenomenon and one of the most important processes in nature. The pressure that occurs is called the osmotic pressure. The phenomenon can be seen in PICTURE.

2.3 Reverse osmosis

The reverse osmosis(RO) process is the reverse process of the osmosis. When pressure is applied to a semipermeable membrane, the water molecules are forced through the semipermeable membrane and the contaminants are not allowed to pass. The amount of pressure required depends on the salt concentration of the water. In order to gain reverse osmosis the pressure applied must be greater than the osmosis pressure. The membra

2.4 Modeling

2.5 System identification

2.6 Control theory

3

Equipment

3.1 Reverse osmosis membrane

4

Method

method

5

Results

result

6

Discussion

discussion

7

Conclusion

conclusion???