

BASIC PROGRAMMING

VARIABLES OPERATORS EXPRESSIONS

Le Thi Ngoc Tho, PhD

Faculty of Information Technology, HUTECH

ltn.tho@hutech.edu.vn


1

CONTENTS

- Program Structure
- Variable Types:
 - Names
 - Data Types & Sizes
 - Constants
- Operators
- Expressions

2

PROGRAM STRUCTURE



Le T.N. Tho - Basic Programming - Expressions

3

3

C LANGUAGE

- C characters:
 - Letters: A...Z, a...z
 - Digits: 0...9
 - Arithmetic symbols: + - * / = > < ()
 - Special symbols: . , " ' _ @ # \$! ^ [] { } ...
 - Space
- C keywords: words predefined by Compiler

auto	double	int	struct	default	goto
break	else	long	switch	do	if
case	enum	register	typedef	sizeof	volatile
char	extern	return	union	static	while
const	float	short	unsigned	signed	void
continue	for				

Le T.N. Tho - Basic Programming - Expressions

4

4

VARIABLES

- Variables: Container to store the data,
- Variables are named for convenience.
- Characters Allowed :
 - Underscore(_)
 - Capital Letters (A – Z)
 - Small Letters (a – z)
 - Digits (0 – 9)
- Restrictions:
 - NO Blanks & Commas
 - NO Special Symbols
 - First character must be letter or underscore
 - Must NOT be keywords.
- Note: C is case sensitive

Le T.N. Tho - Basic Programming - Expressions

5

5

VARIABLES

- E.g.,
 - Correct: **a**, **A**, **x**, **x1**, **sum**, **_sum**
 - Incorrect: **1x**, **n!**, **al pha**
- Which of the following are correct variable names in C:

_a1	✓	_1a	
5linear	✗	1_a	
Delta		a_1	
x		f(x)	
sum_even		Del ta	
while		WHILE	


Le T.N. Tho - Basic Programming - Expressions

6

6

VARIABLES

- Declaration of variables: a statement



Le T.N. Tho - Basic Programming - Expressions

7

7

VARIABLES

- Data Types:
 - char: character
 - int: integer
 - float: single-precision floating point.
 - double: double-precision floating point.
- Qualifiers can be applied to basic types.
 unsigned and signed apply to integers:
 - signed int sh;
 - unsigned int counter;

Le T.N. Tho - Basic Programming - Expressions

8

8

VARIABLES

- Data Types: **char**
 - Use 1 byte to represent characters in ASCII table*.

Type	Domain
char	In ASCII table, character has value from -128 to 127
unsigned char	Character has value from 0 to 255
signed char	Character has value from -128 to 127

- E.g., In ASCII table, character 'A' as value 65 and character 'a' has value 97.

(*): <http://www.asciitable.com/>

Le T.N. Tho - Basic Programming - Expressions

9

9

VARIABLES

- Data Types: **int**
 - Use 2 bytes to represent integers.

Type	Domain
int	-32,768 to +32,767
signed int	-32,768 to +32,767
unsigned int	0 to 65,535
short int	-32,768 to +32,767

Le T.N. Tho - Basic Programming - Expressions

10

10

VARIABLES

- Data Types: **long**
 - Use 4 bytes to represent integers.

Type	Domain
long	-2,147,483,647 to +2,147,483,647
signed long	-2,147,483,647 to +2,147,483,647
long int	-2,147,483,647 to +2,147,483,647
unsigned long	0 to 4,294,967,295

Le T.N. Tho - Basic Programming - Expressions

11

11

VARIABLES

- Data Types: float number
 - Use 4-10 bytes to represent floating point numbers.

Type	Domain
float	4 bytes, 3.4E-38 to 3.4E+38
double	8 bytes, 1.7E-308 to 1.7E+308
long double	10 bytes, 3.4E-4932 to 1.1E+4932


Le T.N. Tho - Basic Programming - Expressions

12


12

VARIABLES

- Variables: values change during execution.



- Constants: the content whose value does not change at the time of execution of a program.




Le T.N. Tho - Basic Programming - Expressions

13

13

EXPRESSIONS

- The combinations of operators and operands in a specified order:



- Operators: + - * / %
- Operands: variables, constants

Le T.N. Tho - Basic Programming - Expressions

14

14

OPERATORS

- Arithmetic Operators: produce arithmetic output

Operators	Meaning	Syntax	Examples	Output
+	Addition	A+B	3+5	8
-	Subtract	A-B	9-6	3
*	Multiplication	A*B	4*7	28
/	Division	A/B	10/2	5
%	Modulo	A%B	10%2	0
-	Unary minus	-A	-3	-3
+	Unary plus	+A	+3	+3
++	Increment	A++, ++A		
--	Decrement	A--, --A		

Le T.N. Tho - Basic Programming - Expressions

15

15

OPERATORS

- Arithmetic Operators: produce arithmetic output

Operators	Meaning	Syntax	Examples	Output
++	Increment	A++, ++A		
--	Decrement	A--, --A		

- ++: add 1 to variable

```
int a, b;
a = 5;
b = a++;
```

b = 5

```
int a, b;
a = 5;
b = ++a;
```

b = 6

- : take away 1 from variable

```
int a, b;
a = 5;
b = a--;
```

b = 5

```
int a, b;
a = 5;
b = --a;
```

b = 4

Le T.N. Tho - Basic Programming - Expressions

16

16

OPERATORS

- Arithmetic Operators: Priority order
 - Parenthesizes ()
 - Unary minus –
 - Multiplication *, division / and modulo %
 - Addition + and subtraction –
- Operators with the same priority are processed from left to right.
- E.g.,
 - Sum of n first integers: $n * (n + 1) / 2$
 - Perimeter of a triangle: $p = a + b + c$

Le T.N. Tho - Basic Programming - Expressions

17

17

OPERATORS

- Arithmetic Operators: Exercises
- Which of the expressions are correct? And their corresponding values?

Expression	Value	Expression	Value
$37/(5*2)$	3	$37\%5\%2$	
$37/5/2$		$37-5-2$	
$37/(5/2)$		$(37-5)/2$	
$37\%(5\%2)$		$37/(5*2)$	

Le T.N. Tho - Basic Programming - Expressions

18

18

OPERATORS

- Relational Operators: produce TRUE/FALSE output

Operators	Meaning	Examples	Output
>	Greater	3 > 3	FALSE
≥	Greater or Equal	3 ≥ 3	TRUE
<	Less	3 < 3	FALSE
≤	Less or Equal	3 ≤ 3	TRUE
==	Is same	3 == 3	TRUE
!=	Is different	3 != 3	FALSE

Le T.N. Tho - Basic Programming - Expressions

19

19

OPERATORS

- Logic Operators: produce TRUE/FALSE output

- ! Negative
- && AND
- || OR

A	B	!A	A && B	A B
TRUE	TRUE	FALSE	TRUE	TRUE
TRUE	FALSE	FALSE	FALSE	TRUE
FALSE	TRUE	TRUE	FALSE	TRUE
FALSE	FALSE	TRUE	FALSE	FALSE

Le T.N. Tho - Basic Programming - Expressions

20

20

OPERATORS

• Relational and Logic Operators: Examples

Expression	Value
5 && 8	TRUE
!1	FALSE
(3>0) && (4>5)	FALSE
(3>0) (4>5)	TRUE
4 && !0	TRUE

Le T.N. Tho - Basic Programming - Expressions

21

21

OPERATORS

• Precedence and Associativity of Operators:

#	Operator	Description	Associativity
1	++ --	Suffix/postfix increment and decrement	Left-to-right
	()	Parenthesis	
2	++ --	Prefix increment and decrement	Right-to-left
	+ -	Unary plus and minus	
3	* / %	Multiplication, division, and remainder	Left-to-right
4	+ -	Addition and subtraction	
5	== !=	For relational = and ≠ respectively	
6	&&	Logical AND	
7		Logical OR	Right-to-Left
8	=	Simple assignment	
	+= -=	Assignment by sum and difference	

Le T.N. Tho - Basic Programming - Expressions


22

22

OPERATORS

- Type cast operator:

(<type> <expression>



Le T.N. Tho - Basic Programming - Expressions

23

23

OPERATORS

- Assignment:

<var> = <expression>;

Assignment operator

End of statement

```
int a, b, c;
a = 147;
```

```
int a, b, c;
a = b = 147;
```

```
int a, b, c;
c = (a = 2)+(b = 3);
```

Le T.N. Tho - Basic Programming - Expressions

24

24

Conditional Expression

- Precedence and Associativity of Operators:

<exp1> ? <exp2> : <exp3>


- If exp1 is correct, get exp2 as the result, otherwise, get exp3 as the result.
- Meaning:
 - exp1: condition
 - exp2: true value
 - exp3: false value
- E.g.,
 - Get the greater number: (a>b) ? (a) : (b);
 - Get the absolute value: (a>0) ? (a) : (-a);

Le T.N. Tho - Basic Programming - Expressions

25

25

C PROGRAM STRUCTURE



Le T.N. Tho - Basic Programming - Expressions

26

26

SIMPLE C PROGRAM

- Your first program: Hello World!

```
#include<stdio.h>
#include<conio.h>
int main()
{
    printf("Hello World!");

    return 0;
}
```

print formatted data



Le T.N. Tho - Basic Programming - Expressions

27


27

SIMPLE C PROGRAM

- Program: Sum of two integers

printf("format strings", <expressions>);

```
#include<stdio.h>
#include<conio.h>
int main()
{
    int a, b, sum;
    a = 5;
    a = 7;
    sum = a + b;
    printf("\nSum of two integers is %d\n", sum);
    printf("\nSum of two integers is %d\n", a + b);
    return 0;
}
```



28


SIMPLE C PROGRAM

- Print format text to screen: `printf`

```
printf("format string", <expressions>);
```

- E.g.,

```
printf("\n Sum of two integers is %d", a+b);
```



Le T.N. Tho - Basic Programming - Expressions

29

29

SIMPLE C PROGRAM

- Print format text to screen: `printf`

Control string	Meaning
<code>\n</code>	New line
<code>\t</code>	Horizontal tab

Format specifier	Meaning	Supported data types
<code>%c</code>	Character	char, unsigned char
<code>%d</code>	Signed Integer	int, long, short, unsigned short
<code>%f</code>	Floating point	float
<code>%s</code>	String	char *

Le T.N. Tho - Basic Programming - Expressions

30

30

SIMPLE C PROGRAM

- Say "Hello" to your friend: Hello, Alice!

```
#include<stdio.h>
#include<conio.h>
int main() {
    char name[40];
    printf("Your friend: ");
    scanf("%s", &name);
    printf("Hello, %s!", name);
    return 0;
}
```

Get in formatted data



Le T.N. Tho - Basic Programming - Expressions

31

31

SIMPLE C PROGRAM

- Program: Sum your input two integers

scanf("format specifiers", <addresses>);

```
#include<stdio.h>
#include<conio.h>
int main() {
    int a, b, sum;
    printf("a="); scanf("%d", &a);
    printf("b="); scanf("%d", &b);
    sum = a + b;
    printf("\nSum of two integers is %d\n", sum);
    return 0;
}
```

Le T.N. Tho - Basic Programming - Expressions

32

32

SIMPLE C PROGRAM

- Get format text from keyboard: scanf

```
scanf("format string", <addresses>);
```

- E.g.,

```
scanf("%d", &b);
```

%d &b
 ↙ ↘
 Format specifier Address

Le T.N. Tho - Basic Programming - Expressions

33

33

HOMEWORK

- Read the textbook: chapter 2
- Study how floating point numbers are represented.
<https://www.ntu.edu.sg/home/ehchua/programming/java/DataRepresentation.html>

Le T.N. Tho - Basic Programming - Expressions

34

34

Any Questions?



Le T.N. Tho - Basic Programming - Expressions

35