



REPORT NO. 12121		ULR NO. 45251	
ISSUED TO	: HII	DATE OF RECEIPT	: 18-11-2025
		DATE OF START OF ANALYSIS	: 18-11-2025
LETTER REF. NO. & DATE	: 45745475 & 2025-11-18	DATE OF COMPLETION OF ANALYSIS	: 17-11-2025
SAMPLE DESCRIPTION	: HIH LKFGF GLHMGFHL GFKLHMGHMG GFHLGFMHLKGF GFHKLG GKHM;LF	DATE OF ISSUE	: 18-11-2025
NAME OF WORK	: AVINASH KUMAR JHA DSDFGFD F GDFKJNGKLDF FJGNDFLG DFKGDFLG F,MD DFGDFKLNN		

S.No.	Tests	Test Methods	Requirements as per IS 269:2015 With Amendment No. 1	Results	Conformity
Discipline : Mechanical, Group : Buildings Materials					
Physical Requirements					
1.	Consistency, %	IS 4031(P-4):1988	-		
2.	Density, g/cc	IS 4031(P-11):1988	-		
3.	Fineness, m ² / kg	IS 4031(P-2):1999	225 Min.		
4.	Initial Setting Time, Minutes	IS 4031(P-5):1988	30 Min.		
5.	Final Setting Time, Minutes	IS 4031(P-5):1988	600 Max.		
6.	Soundness By Le-Chatelier Method, mm	IS 4031(P-3):1988	10 Max.		
7.	Soundness By Autoclave Test Method, %	IS 4031(P-3):1988	0.8 Max.		
8.	Compressive Strength at 3 Days (72±1 Hours), MPa	IS:4031(P-6):1988	23 Min.		
9.	Compressive Strength at 7 Days (168±2 Hours), MPa	IS 4031(P-6):1988	33 Min.		
10.	Compressive Strength at 28 Days (672±4 Hours), MPa	IS 4031(P-6):1988	43 - 58		
Discipline : Chemical, Group : Building Material					



REPORT NO. 12121		ULR NO. 45251	
ISSUED TO	: HII	DATE OF RECEIPT	: 18-11-2025
		DATE OF START OF ANALYSIS	: 18-11-2025
LETTER REF. NO. & DATE	: 45745475 & 2025-11-18	DATE OF COMPLETION OF ANALYSIS	: 17-11-2025
SAMPLE DESCRIPTION	: HIH LKFGF GLHMGFHL GFKLHMGHMG GFHLMGHLKGF GFHKLGF GKHM;LF	DATE OF ISSUE	: 18-11-2025
NAME OF WORK	: AVINASH KUMAR JHA DSDFGFD F GDFKJNGKLD FJGNDFLG DFKGDFLG F,MD DFGDFKLNN		

Chemical Requirements					
1.	Ratio of % of lime to % of SiO ₂ , Al ₂ O ₃ & Fe ₂ O ₃ as per formula $(\frac{CaO}{CaO} - \frac{0.7SO_3}{SO_3})$ 2.8SiO ₂ +1.2Al ₂ O ₃ +0.65Fe ₂ O ₃	IS 4032:1985	0.66 -1.02		
2.	Ratio of % of Alumina to that of Iron oxide	IS 4032:1985	0.66 Min.		
3.	Insoluble Residue, % by mass	IS 4032:1985	5.0 Max.		
4.	Magnesia as MgO, % by mass	IS 4032:1985	6.0 Max.		
5.	Total Sulphur Content Calculated as Sulphuric Anhydride (SO ₃), % by mass	IS 4032:1985	3.5 Max.		
6.	Loss on Ignition. % by mass	IS 4032:1985	5.0 Max.		
7.	Chloride Content, % by mass	IS 4032:1985	0.1 Max. 0.05 Max. (For Prestressed Structures)		
8.	Alkali Content expressed as Sodium Oxide (Na ₂ O+0.658 K ₂ O), % by mass	IS 4032:1985	0.6 Max.		



REPORT NO. 12121		ULR NO. 45251	
ISSUED TO	: HII	DATE OF RECEIPT	: 18-11-2025
		DATE OF START OF ANALYSIS	: 18-11-2025
LETTER REF. NO. & DATE	: 45745475 & 2025-11-18	DATE OF COMPLETION OF ANALYSIS	: 17-11-2025
SAMPLE DESCRIPTION	: HIH LKFGF GLHMGFHL GFKLHMGHMG GFHLGFMHLKGF GFHKLGF GKHM;LF	DATE OF ISSUE	: 18-11-2025
NAME OF WORK	: AVINASH KUMAR JHA DSDFGFD F GDFKJNGKLD FJGNDFLG DFKGDFLG F,MD DFGDFKLNN		

Analyst