

VRDots — Quick Reference for Collaborating Labs

G. Stoner · September 2026

One-time setup (do once, then skip to "Each session" below)

1. Create a Meta developer account at `developer.oculus.com` and enable **Developer Mode** on the Quest 3 (`Settings` → `System` → `Developer Options`).
2. Install **Unity Hub**, then install Unity **6000.2.7f2** with the **Android Build Support** module.
3. Install **Android Debug Bridge (ADB)** — download platform-tools from `developer.android.com/tools/releases/platform-tools` and add to your PATH.
4. Accept the GitHub repository invitation from Gene, then clone:

```
git clone -b wip/quest-pilot
https://github.com/GeneStoner/UnityQuestDotStimuli.git
```

5. Open the cloned folder in Unity Hub. Wait for asset import to finish (5–20 min first time).
 6. Verify: `Edit` → `Project Settings` → `Player` → `Other Settings` → `Active Input Handling` = `Both`
-

Each session — step by step

1. Load the experiment

1. Open Unity and load the project.
2. Open scene: `Assets/Scenes/UpToDateScene` (double-click in Project panel).
3. In the **Hierarchy**, search for `TrialBlockManager` and click it.
4. In the **Inspector**, find the **TrialBlockRunner** script component and its **Spec** slot.
5. From `Assets/ExperimentSpecs/`, drag the experiment asset into the **Spec** slot.
 - Gene will tell you which asset to use each session (e.g. `Exp_DensityCompare_HighDens`).
6. **Cmd+S / Ctrl+S** — save the scene. Required before every build.

2. Build and deploy

1. Connect the Quest 3 to the computer via USB-C (data cable, not charge-only).
2. **Put on the headset** — accept the *"Allow USB debugging?"* dialog that appears inside.
3. In Unity: `File` → `Build Settings` → `Build and Run` .
4. Wait for the build to complete (~2–5 min). The app installs and launches on the Quest automatically.
 - If it doesn't auto-launch, find it under **Unknown Sources** in the Quest App Library.

3. Run the session

- The observer puts on the headset. The app opens to a waiting screen.
- **Right trigger**: advance / confirm.
- **Right thumbstick**: report the perceived translation direction (push toward the motion).
- The observer should maintain fixation on the central dot throughout each trial.
- Sessions take **10–20 minutes** depending on the experiment.
- Data saves automatically at the end of each block.

4. Pull data and send to Gene

After the session, with the Quest still connected:

```
adb pull /sdcard/Android/data/com.genestoner.vrdptsrebuildX.test/files/ ~/VRDotsData/
```

Each session produces three files (`.tsv` , `.tsv.meta.json` , `.tsv.sidecar.json`). Send all three to Gene at `generstoner@gmail.com` .

Troubleshooting

Problem	Fix
"No Android device"	Put on headset and accept the USB debugging dialog
App not found after build	Check Unknown Sources in App Library
Controller input not working	Verify Active Input Handling = "Both" in Project Settings
Build fails	Ensure <code>Cmd+S</code> was pressed before building
Quest not charging/booting	Let it charge for 15 min before connecting for a session

Contact

Gene Stoner — `generstoner@gmail.com`

Repository: `https://github.com/GeneStoner/UnityQuestDotStimuli` · branch `wip/quest-pilot`