

Package ‘Isosceles’

August 1, 2023

Title Isoform Single-Cell and Long-read Expression Suite

Version 0.0.2

Description Transcript detection and quantification from long reads.

Depends R (>= 4.2.0),
SingleCellExperiment (>= 1.18.0)

Imports utils (>= 4.2.0),
methods (>= 4.2.0),
stats (>= 4.2.0),
rlang (>= 1.0.4),
assertthat (>= 0.2.1),
magrittr (>= 2.0.3),
tibble (>= 3.1.7),
tidyselect (>= 1.1.2),
dplyr (>= 1.0.9),
tidyr (>= 1.2.0),
glue (>= 1.6.2),
digest (>= 0.6.29),
Rcpp (>= 1.0.9),
Matrix (>= 1.4-1),
BiocParallel (>= 1.30.3),
BiocNeighbors (>= 1.14.0),
S4Vectors (>= 0.34.0),
BiocGenerics (>= 0.42.0),
Biostrings (>= 2.64.0),
BSgenome (>= 1.64.0),
GenomeInfoDb (>= 1.32.2),
IRanges (>= 2.30.0),
GenomicRanges (>= 1.48.0),
Rsamtools (>= 2.12.0),
GenomicAlignments (>= 1.32.1),
rtracklayer (>= 1.56.1),
GenomicFeatures (>= 1.48.3),
SummarizedExperiment (>= 1.26.1),
igraph (>= 1.3.4),
scuttle (>= 1.6.2),

fastmatch (\geq 1.1-3),
 pheatmap (\geq 1.0.12),
 ggbio (\geq 1.44.1),
 ggplot2 (\geq 3.3.6),
 biovizBase (\geq 1.44.0)

License GPL (\geq 3)

URL <https://github.com/timbitz/Isosceles>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Suggests testthat (\geq 3.0.0),
 tools (\geq 4.2.0),
 knitr (\geq 1.39),
 rmarkdown (\geq 2.14),
 BiocStyle (\geq 2.24.0),
 viridis (\geq 0.6.2),
 dittoSeq (\geq 1.8.1),
 scran (\geq 1.24.0),
 scater (\geq 1.24.0),
 bluster (\geq 1.6.0)

Config/testthat/edition 3

LinkingTo Rcpp (\geq 1.0.9),
 RcppArmadillo (\geq 0.11.2.0.0)

VignetteBuilder knitr

R topics documented:

Isosceles-package	3
export_gtf	3
extract_read_structures	4
merge_sc_neighbors	4
plot_psi_heatmap	5
plot_psi_regions	5
prepare_gene_se	6
prepare_pseudobulk_se	7
prepare_psi_se	7
prepare_tcc_se	8
prepare_transcripts	9
prepare_transcript_se	10

Index	12
--------------	-----------

Isosceles-package	<i>Isosceles: Isoform Single-Cell and Long-read Expression Suite</i>
-------------------	--

Description

Transcript detection and quantification from long reads

Author(s)

Tim Sterne-Weiler sternewt@gene.com

Michal Kabza michal.kabza@contractors.roche.com

export_gtf	<i>Data export to a GTF file</i>
------------	----------------------------------

Description

Export transcripts from a SummarizedExperiment to a GTF file

Usage

```
export_gtf(se, file)
```

Arguments

se	A transcript-level SummarizedExperiment object returned by the prepare_transcript_se function
file	A string specifying the output file path

Value

Nothing is returned

extract_read_structures

Read structure extraction from BAM files

Description

Extract non-redundant read structures from one or multiple BAM files

Usage

```
extract_read_structures(bam_files, chunk_size = 1e+06, ncpu = 1)
```

Arguments

bam_files	A character vector containing BAM file paths
chunk_size	An integer scalar specifying the chunk size for reading the BAM files
ncpu	An integer scalar specifying the number of cores to use for multicore parallelization

Value

A data frame containing non-redundant read structure data obtained from the BAM files

merge_sc_neighbors

Merging neighboring cell TCC values in scRNA-Seq data

Description

Prepares a TCC SummarizedExperiment object where count values from the nearest k neighbors are added to the count values of each cell

Usage

```
merge_sc_neighbors(se_tcc, pca_mat, k = 10, use_annoy = FALSE, ncpu = 1)
```

Arguments

se_tcc	A TCC SummarizedExperiment object returned by the prepare_tcc_se function
pca_mat	A matrix containing PCA coordinates of each cell
k	An integer scalar specifying the number of nearest neighbors to use
use_annoy	A logical scalar indicating whether to use the Annoy algorithm for approximate nearest neighbor identification (recommended for big datasets)
ncpu	An integer scalar specifying the number of cores to use for multicore parallelization

Value

A SummarizedExperiment object containing merged TCC data

plot_psi_heatmap	<i>Plot a PSI heatmap</i>
------------------	---------------------------

Description

Creates a heatmap of PSI (Percent Spliced In) values for the regions of a given gene across samples or cells

Usage

```
plot_psi_heatmap(
  se_psi,
  gene_id,
  heatmap_colors = viridis::cividis(100),
  region_colors = NULL,
  ...
)
```

Arguments

se_psi	A PSI SummarizedExperiment object returned by the prepare_psi_se function
gene_id	A string containing the identifier of the gene to plot
heatmap_colors	A character vector containing the color palette used in the heatmap
region_colors	A named character vector of colors for the region type annotations
...	Additional parameters for the plot, passed to the pheatmap function

Value

A plot object

plot_psi_regions	<i>Plot PSI regions</i>
------------------	-------------------------

Description

Creates a plot showing PSI regions and transcript structures for the given gene. Individual transcript structures are colored by their relative expression, calculated from the overall TPM values and expressed in percentages. For better visualization, introns can be shrunk using the `max_intron_length` argument

Usage

```
plot_psi_regions(
  se_psi,
  se_transcript,
  gene_id,
  max_transcripts = Inf,
  max_intron_length = NULL,
  region_colors = NULL
)
```

Arguments

se_psi	A PSI SummarizedExperiment object returned by the prepare_psi_se function
se_transcript	A transcript-level SummarizedExperiment object returned by the prepare_transcript_se function
gene_id	A string containing the identifier of the gene to plot
max_transcripts	An integer scalar specifying the maximum number of transcripts with the highest relative expression to plot
max_intron_length	An integer scalar specifying the maximum intron length after shrinking. If set to NULL, no shrinking is performed
region_colors	A named character vector of colors for the PSI region types

Value

A plot object

prepare_gene_se	<i>Prepare a gene-level SummarizedExperiment object</i>
-----------------	---

Description

Prepares a gene-level SummarizedExperiment from TCC data

Usage

```
prepare_gene_se(se_tcc)
```

Arguments

se_tcc	A TCC SummarizedExperiment object returned by a function from the Isosceles-package
--------	---

Value

A SummarizedExperiment object containing gene annotation and quantification data

```
prepare_pseudobulk_se
```

Prepare a pseudobulk TCC SummarizedExperiment object

Description

Prepares a pseudobulk TCC SummarizedExperiment from TCC data and given cell labels

Usage

```
prepare_pseudobulk_se(se_tcc, cell_labels)
```

Arguments

<code>se_tcc</code>	A TCC SummarizedExperiment object returned by the prepare_tcc_se function
<code>cell_labels</code>	A vector or a factor containing cell labels acting as a grouping variable

Value

A pseudobulk SummarizedExperiment object containing TCC annotation and quantification data

```
prepare_psi_se
```

Prepare a PSI SummarizedExperiment object

Description

Prepares a PSI (Percent Spliced In) SummarizedExperiment object for the given transcript-level SummarizedExperiment object. PSI values are calculated for the following types of regions:

- **TSS** - transcription start sites
- **TES** - transcription end sites
- **CE** - core exonic regions
- **RI** - retained intronic regions
- **A5** - 5' alternative exonic regions
- **A3** - 3' alternative exonic regions

TSS and TES positions are calculated based on transcripts' binned start and end coordinates extracted from their identifiers

Usage

```
prepare_psi_se(se, ncpu = 1)
```

Arguments

se	A transcript-level SummarizedExperiment object returned by the prepare_transcript_se function
ncpu	An integer scalar specifying the number of cores to use for multicore parallelization

Value

A SummarizedExperiment object containing PSI annotation and quantification data

prepare_tcc_se	<i>Prepare a TCC SummarizedExperiment object</i>
----------------	--

Description

Prepares a TCC (Transcript Compatibility Counts) SummarizedExperiment object for the given BAM files and transcript set

Usage

```
prepare_tcc_se(  
  bam_files,  
  transcript_data,  
  run_mode = "strict",  
  min_read_count = 1,  
  min_relative_expression = 0.1,  
  extend_spliced_transcripts = 100,  
  is_single_cell = FALSE,  
  barcode_tag = "BC",  
  chunk_size = 1e+06,  
  ncpu = 1  
)
```

Arguments

bam_files	A named character vector containing BAM file paths
transcript_data	A named list containing transcript data returned by the prepare_transcripts function
run_mode	A string specifying the mode for choosing the transcript set ('strict', 'de_novo_strict', 'de_novo_loose' or 'de_novo_full')
min_read_count	An integer scalar specifying the read count threshold for transcripts extracted from the BAM files
min_relative_expression	A numeric scalar specifying the relative expression threshold for transcripts extracted from the BAM files

extend_spliced_transcripts	An integer scalar specifying the number of base pairs by which transcript starts and ends are extended for spliced read compatibility search
is_single_cell	A logical scalar specifying if the BAM files contain single cell data
barcode_tag	A string specifying the name of the BAM file tag containing cell barcodes
chunk_size	An integer scalar specifying the chunk size for reading the BAM files
ncpu	An integer scalar specifying the number of cores to use for multicore parallelization

Value

A SummarizedExperiment object containing TCC annotation and quantification data

prepare_transcripts	<i>Transcript data preparation</i>
---------------------	------------------------------------

Description

Prepare transcript data (reference and extracted from the BAM files) for further analysis

Usage

```
prepare_transcripts(
  gtf_file,
  genome_fasta_file,
  bam_parsed,
  min_intron_length = 30,
  known_intron_motifs = c("GT-AG"),
  rescue_annotated_introns = FALSE,
  known_intron_granges = NULL,
  min_bam_splice_read_count = 2,
  min_bam_splice_fraction = 0.1,
  bin_size = 50
)
```

Arguments

gtf_file	A string containing a GTF file path
genome_fasta_file	A string containing a genome FASTA file path
bam_parsed	A data frame containing non-redundant read structure data returned by the extract_read_structures function. If NULL, only reference transcripts are used
min_intron_length	An integer scalar specifying the minimal length of introns to assign strand to
known_intron_motifs	A character vector specifying the known intron motifs

rescue_annotated_introns	A logical scalar specifying if introns found in genome annotations should be kept even if they don't have known intron motifs
known_intron_granges	A GRanges object storing known intron positions (e.g. from short read data) used for transcript classification. If set to NULL, only introns from reference annotations are used
min_bam_splice_read_count	An integer scalar specifying the read count threshold for splice sites confirmed by aligned reads
min_bam_splice_fraction	A numeric scalar specifying the minimum connectivity fraction to a known splice site for splice sites confirmed by aligned reads
bin_size	An integer scalar specifying the bin size for transcript start and end position binning

Value

A named list containing following elements:

tx_df a data frame storing extracted transcript data

tx_granges a GRanges object storing genomic positions of extracted transcript

tx_exon_granges_list a GRangesList object storing exon genomic positions of extracted transcript

tx_intron_granges_list a GRangesList object storing intron genomic positions of extracted transcript

prepare_transcript_se *Prepare a transcript-level SummarizedExperiment object*

Description

Prepares a transcript-level SummarizedExperiment from TCC data using the EM algorithm

Usage

```
prepare_transcript_se(
  se_tcc,
  em.maxiter = 250,
  em.conv = 0.01,
  use_length_normalization = TRUE,
  ncpu = 1
)
```

Arguments

<code>se_tcc</code>	A TCC SummarizedExperiment object returned by a function from the Isosceles-package
<code>em.maxiter</code>	An integer scalar specifying the maximum number of EM iterations
<code>em.conv</code>	A numeric scalar specifying the EM convergence threshold
<code>use_length_normalization</code>	A logical scalar specifying if normalization using effective transcript lengths should be used during EM
<code>ncpu</code>	An integer scalar specifying the number of cores to use for multicore parallelization

Value

A SummarizedExperiment object containing transcript annotation and quantification data

Index

export_gtf, [3](#)
extract_read_structures, [4](#), [9](#)

Isosceles-package, [3](#)

merge_sc_neighbors, [4](#)

pheatmap, [5](#)
plot_psi_heatmap, [5](#)
plot_psi_regions, [5](#)
prepare_gene_se, [6](#)
prepare_pseudobulk_se, [7](#)
prepare_psi_se, [5](#), [6](#), [7](#)
prepare_tcc_se, [4](#), [7](#), [8](#)
prepare_transcript_se, [3](#), [6](#), [8](#), [10](#)
prepare_transcripts, [8](#), [9](#)