

RoboArm 7200 Industrial

6-Axis Articulating Industrial Robot — High Payload Series

200 kg

MAX PAYLOAD

2,850 mm

MAX REACH

±0.02 mm

REPEATABILITY

MECHANICAL SPECIFICATIONS

Axes	6 (J1–J6)
Payload Capacity	200 kg (wrist) / 220 kg (with counterbalance)
Reach	2,850 mm
Repeatability	±0.02 mm (ISO 9283)
Weight	1,180 kg (base unit)
Mounting	Floor, inverted, wall, shelf (any angle)
J1 Rotation	±180° at 105°/s
J2 Arm	+155° / –90° at 101°/s
J3 Arm	+75° / –210° at 105°/s
J4 Wrist	±360° at 146°/s
J5 Wrist	±130° at 140°/s
J6 Wrist	±360° at 240°/s

CONTROLLER & SOFTWARE

Controller	HMR-CTL-900 (integrated)
Teach Pendant	10.1" color touchscreen
Programming	HMR Studio, RAPID-compatible
I/O	48 DI / 48 DO / 8 AI / 8 AO
Fieldbus	EtherNet/IP, PROFINET, EtherCAT
PLC Integration	Siemens S7, Allen-Bradley, Mitsubishi
Safety	SafeMove2 equivalent, Cat 3 / PL d
Vision Interface	GigE Vision, Cognex, Keyence

ENVIRONMENT & ELECTRICAL

Operating Temp	5°C to 45°C (41°F to 113°F)
Protection Rating	IP67 (wrist), IP54 (body) — IP67 full body optional
Power Supply	380–480V AC, 3-phase, 50/60 Hz
Power Consumption	8.5 kW (typical cycle)
Noise Level	<72 dB(A) at max speed

APPLICATIONS

Spot welding • Arc welding • Material handling • Palletizing • Machine tending • Assembly • Dispensing • Painting (with EX option)

COMPLIANCE & CERTIFICATIONS

ISO 10218-1:2011

CE Marked

UL Listed

ISO 9283

ANSI/RIA R15.06

PRICING & ORDERING

List Price (Base Unit)	\$87,500.00 USD
Calibration & Install	\$3,200.00/unit (SKU: HMR-RA-CAL)
12-Mo Service Agreement	\$6,800.00/unit (SKU: HMR-SVC-12M)
Lead Time	6–8 weeks ARO

Haley Martin Robotics • HMR-RA-7200 Specification Sheet • Rev 4.1 • Confidential

HALEY MARTIN ROBOTICS

Product Specification Sheet

CONFIDENTIAL — FOR CHASSIS SL1000 ONLY

Rev. 3.0 • March 2025

SortLine 1000

Automated High-Speed Parcel & Product Sorting System

800+

PARCELS / HOUR

4

SORTING LANES

99.7%

SORT ACCURACY

SYSTEM SPECIFICATIONS

Throughput	800–1,200 parcels/hour (size dependent)
Sort Accuracy	99.7% (verified per ASTM D6055)
Sorting Lanes	4 standard (expandable to 8)
Parcel Size Range	100×100×50 mm to 800×600×500 mm
Max Parcel Weight	35 kg
Conveyor Speed	0.5–2.5 m/s (variable)
Footprint	12m (L) × 4.2m (W) × 2.8m (H)
Weight	3,200 kg (installed)
Divert Mechanism	Pneumatic pusher + belt transfer

CONTROLS & INTEGRATION

Controller	HMR-CTL-500 embedded PLC
HMI	15.6" industrial touchscreen
Scanning	Integrated 6-side barcode reader
Vision	Top-mounted dimensioning camera
WMS Integration	Manhattan, Blue Yonder, SAP EWM
Communication	REST API, OPC UA, MQTT
I/O	24 DI / 24 DO / 4 AI
Network	Dual Gigabit Ethernet

ENVIRONMENT & ELECTRICAL

Operating Temp	0°C to 40°C (32°F to 104°F)
Protection Rating	IP54 (electronics), IP43 (conveyor)
Power Supply	208–480V AC, 3-phase, 50/60 Hz
Power Consumption	4.2 kW (typical), 6.8 kW (peak)

Air Supply	6 bar (87 psi), 120 L/min
Noise Level	<78 dB(A) at max throughput

COMPLIANCE & CERTIFICATIONS

ISO 13849-1 (PL c)	CE Marked	UL Listed	ASTM D6055	NFPA 79
--------------------	-----------	-----------	------------	---------

PRICING & ORDERING

List Price (per unit)	\$54,000.00 USD
Conveyor Integration Kit	\$4,500.00/unit (SKU: HMR-SL-CONV)
12-Mo Service Agreement	\$4,200.00/unit (SKU: HMR-SVC-12M)
Volume Discount	5% on 10+ units
Lead Time	4–6 weeks ARO

Haley Martin Robotics • HMR-SL-1000 Specification Sheet • Rev 3.0 • Confidential

HALEY MARTIN ROBOTICS

Product Specification Sheet

CONFIDENTIAL — FOR CHURN ONLY

Rev. 2.2 • February 2025

PrecisionCraft 5500

Ultra-Precision Micro-Assembly Robot — Semiconductor & Electronics Grade

±2 µm PLACEMENT ACCURACY	5 kg MAX PAYLOAD	ISO 5 CLEANROOM COMPATIBLE
-----------------------------	---------------------	-------------------------------

MECHANICAL SPECIFICATIONS

Axes	4+1 (X, Y, Z, θ + optional W)
Payload	5 kg (end effector + component)
Work Envelope	500 × 400 × 200 mm
Placement Accuracy	±2 µm (X/Y), ±5 µm (Z)
Repeatability	±0.5 µm (X/Y)
Max Speed	800 mm/s (X/Y), 200 mm/s (Z)
Resolution	0.1 µm (linear), 0.001° (rotary)
Drive System	Linear motors (X/Y), ball screw (Z)
Base Material	Natural granite, vibration-isolated

CONTROLS & VISION

Controller	HMR-CTL-UHP (Ultra High Precision)
Software	HMR MicroPlace 3.0
Vision System	Dual-camera (top + bottom)
Camera Resolution	20 MP monochrome, GigE Vision
Lighting	Coaxial + ring LED, programmable
Compatible Vision	Cognex In-Sight, Keyence CV-X
Fiducial Recognition	Sub-pixel alignment
Communication	EtherNet/IP, SECS/GEM, GEM300

Weight	680 kg (including granite base)	Data Logging	Full traceability per component
--------	---------------------------------	--------------	---------------------------------

ENVIRONMENT & ELECTRICAL

Operating Temp	20°C ±1°C (climate-controlled required)
Cleanroom Rating	ISO Class 5 compatible (Class 3 w/ enclosure)
Vibration Isolation	Active pneumatic, <0.5 µm amplitude
Power Supply	200–240V AC, single phase, 50/60 Hz
Power Consumption	2.8 kW (typical)
ESD Protection	Integrated grounding, <1V surface charge
Noise Level	<55 dB(A)

APPLICATIONS

BGA placement • Flip-chip assembly • Chiplet packaging • MEMS assembly • Optical alignment • Micro-dispensing • Wire bonding assist • Die attach

COMPLIANCE & CERTIFICATIONS

ISO 14644-1 (Class 5)

CE Marked

SEMI S2/S8

IEC 61340 (ESD)

SECS/GEM (SEMI E30)

PRICING & ORDERING

List Price (Base Unit)	\$215,000.00 USD
ISO 5 Cleanroom Enclosure	\$28,000.00/unit (SKU: HMR-PC-CLR)
24-Mo Premium Service	\$18,500.00/unit (SKU: HMR-SVC-24M)
Lead Time	10–12 weeks ARO

Haley Martin Robotics • HMR-PC-5500 Specification Sheet • Rev 2.2 • Confidential

HALEY MARTIN ROBOTICS

Product Specification Sheet

CONFIDENTIAL — FOR CHAIN OF SUPPLY ONLY

HMR-WS-3100

Rev. 3.5 • January 2025

WeldStation 3100

Integrated Robotic Welding Cell — MIG/MAG, TIG & Spot Welding

3-in-1

WELD PROCESSES

1,650 mm

MAX WORKPIECE

98.5%

FIRST-PASS YIELD

SYSTEM SPECIFICATIONS

POWER SOURCE & CONTROLS

Welding Processes	MIG/MAG, TIG, Resistance Spot	Weld Power Source	HMR-WP-500 Digital Inverter
Robot (Included)	HMR-RA-5100 (6-axis, 25 kg payload)	Output Range	10–500A, 10–44V
Reach	1,850 mm	Duty Cycle	100% at 350A, 60% at 500A
Positioner	2-axis servo, 500 kg capacity	Controller	HMR-CTL-700 with weld sequencer
Max Workpiece	1,650 mm diameter × 1,200 mm height	Software	HMR WeldPro 4.0
Torch	Water-cooled, quick-change	Weld Monitoring	Real-time current/voltage/speed
Wire Feeder	Dual-drive, 0.8–1.6 mm wire	Quality Logging	Per-weld data with traceability
Seam Tracking	Laser + tactile (through-arc optional)	Safety	Light curtain, area scanner, E-stop
Cell Footprint	4.5m × 3.8m × 3.0m (H)		
Weight	4,800 kg (complete cell)		

ENVIRONMENT & ELECTRICAL

Operating Temp	5°C to 40°C (41°F to 104°F)
Fume Extraction	Integrated overhead hood, 3,000 m³/h
Power Supply	380–480V AC, 3-phase, 50/60 Hz
Power Consumption	28 kW (peak welding), 8 kW (idle)
Shielding Gas	Ar/CO₂ mix, flow 12–22 L/min
Compressed Air	6 bar, 80 L/min

COMPLIANCE & CERTIFICATIONS

ISO 10218-1:2011

CE Marked

UL Listed

AWS D1.1

ANSI Z49.1

PRICING & ORDERING

List Price (Complete Cell)	\$124,000.00 USD
12-Mo Service Agreement	\$8,400.00/unit (SKU: HMR-SVC-12M)
Lead Time	8–10 weeks ARO

Haley Martin Robotics • HMR-WS-3100 Specification Sheet • Rev 3.5 • Confidential

120 PARTS / MINUTE	99.95% DETECTION RATE	<0.1% FALSE POSITIVE RATE
--	---	--

INSPECTION SPECIFICATIONS

Inspection Speed	Up to 120 parts/min
Detection Rate	99.95% (trained model)
False Positive Rate	<0.1%
Defect Resolution	10 µm minimum detectable
Field of View	50×50 mm to 500×500 mm (lens dependent)
Inspection Types	Surface, dimensional, assembly, OCR/OCV
AI Engine	HMR DeepInspect™ CNN (edge-deployed)
Training	50–200 sample images typical
Camera	20 MP GigE, global shutter

HARDWARE & INTEGRATION

Processor	NVIDIA Jetson AGX Orin (embedded)
Lighting	Multi-angle LED array, programmable
Enclosure	IP54 aluminum housing
Dimensions	450 × 380 × 600 mm
Weight	42 kg
Communication	EtherNet/IP, PROFINET, REST API
PLC Integration	Siemens, Allen-Bradley, Mitsubishi
Reject Mechanism	Pneumatic diverter (optional)
Dashboard	Web-based real-time analytics

ENVIRONMENT & ELECTRICAL

Operating Temp	5°C to 45°C (41°F to 113°F)
Protection Rating	IP54
Power Supply	100–240V AC, single phase, 50/60 Hz
Power Consumption	380W (typical)
Vibration Tolerance	IEC 60068-2-6 (10–150 Hz, 2g)

COMPLIANCE & CERTIFICATIONS

ISO 13849-1	CE Marked	UL Listed	GigE Vision 2.0	IEC 62443 (Cybersecurity)
-------------	-----------	-----------	-----------------	---------------------------

PRICING & ORDERING

List Price (per unit)	\$38,500.00 USD
12-Mo Service Agreement	\$3,600.00/unit (SKU: HMR-SVC-12M)
AI Model Training Package	\$5,200.00 (SKU: HMR-VS-TRN)
Lead Time	3–4 weeks ARO