

This combines all 4 of our live script versions of our code into a single mlx live script. This also makes it easier to export to a PDF.

Question 1: Jaxen White

```
% Dummy Variable. Added by Ryan.
% Sets up a flag that allows Q4.m to end this script before the plots are
% made.
Q4_flag(2) = 0;

% Parameters
T = 100; % Total simulation time (days)
h = 1; % Time step (days)
N = 1000; % Total population (constant)
S0 = 990; % Initial susceptible population
I0 = 10; % Initial infected population
R0 = 0; % Initial recovered population

% Parameter sets for different diseases
parameters = [
    0.3, 0.1; % Seasonal Influenza ( $\beta$ ,  $\gamma$ )
    1.0, 0.1; % COVID-19 ( $\beta$ ,  $\gamma$ )
    2.0, 0.2 % Measles ( $\beta$ ,  $\gamma$ )
];
disease_names = {'Seasonal Influenza', 'COVID-19', 'Measles'};

for k = 1:size(parameters, 1)
    beta = parameters(k, 1);
    gamma = parameters(k, 2);

    S = zeros(1, T+1); I = zeros(1, T+1); R = zeros(1, T+1);
    S(1) = S0; I(1) = I0; R(1) = R0;

    % RK4 method
    for t = 1:T
        % Current values
        S_t = S(t); I_t = I(t); R_t = R(t);

        % Define ODEs
        dS = @(S, I) -(beta / N) * S * I;
        dI = @(S, I) (beta / N) * S * I - gamma * I;
        dR = @(I) gamma * I;

        % RK4 coefficients
        k1_S = h * dS(S_t, I_t);
        k1_I = h * dI(S_t, I_t);
        k1_R = h * dR(I_t);

        k2_S = h * dS(S_t + k1_S/2, I_t + k1_I/2);
        k2_I = h * dI(S_t + k1_S/2, I_t + k1_I/2);
```

```

    k2_R = h * dR(I_t + k1_I/2);

    k3_S = h * dS(S_t + k2_S/2, I_t + k2_I/2);
    k3_I = h * dI(S_t + k2_S/2, I_t + k2_I/2);
    k3_R = h * dR(I_t + k2_I/2);



    k4_S = h * dS(S_t + k3_S, I_t + k3_I);
    k4_I = h * dI(S_t + k3_S, I_t + k3_I);
    k4_R = h * dR(I_t + k3_I);


    S(t+1) = S_t + (k1_S + 2*k2_S + 2*k3_S + k4_S) / 6;
    I(t+1) = I_t + (k1_I + 2*k2_I + 2*k3_I + k4_I) / 6;
    R(t+1) = R_t + (k1_R + 2*k2_R + 2*k3_R + k4_R) / 6;
end

% This was added by Ryan. This makes it so that Q4.m can run this script
% without also importing/displaying any plots/figures.
if Q4_flag(1) == 1
    return
end

% Plot results
figure;
hold on;
plot(0:T, S, 'b', 'LineWidth', 1.5);
plot(0:T, I, 'r', 'LineWidth', 1.5);
plot(0:T, R, 'g', 'LineWidth', 1.5);
title(['SIR Model: ', disease_names{k}]);
xlabel('Time (days)');
ylabel('Population');
legend('Susceptible', 'Infected', 'Recovered');
grid on;
hold off;
end

```





A higher transmission rate such as, Measles with $\beta=2$ causes a rapid increase in infections, leading to a sharp peak in $I(t)$. This makes the disease spread quickly through the susceptible population, depleting $S(t)$ rapidly. A lower recovery rate prolongs the duration of infection, keeping I elevated for longer periods like COVID-19 with $\gamma=0.1$. Diseases with higher β/γ ratios, the basic reproduction number R_0 , spread more aggressively and involve larger portions of the population before fading. In conclusion, the measles virus spreads quickly due to its high β , but it has a fast recovery so it limits its time of infection. Covid-19 has a slower spread but a longer infection period which reflects its $\beta=1$ and $\gamma=0.1$. The seasonal Influenza has a moderate γ and β so it is slower and less dramatic all around.

```
clear;
```

Question 2: Cyal Sam

```
%%% 100
% Parameters
T = 100; % Total simulation time (days)
h = 1; % Time step (days)
N = 1000; % Total population (constant)
S0 = 990; % Initial susceptible population
I0 = 10; % Initial infected population
R0 = 0; % Initial recovered population
% Parameter sets for different diseases
parameters = [
    0.3, 0.1 % Seasonal Influenza ( $\beta$ ,  $\gamma$ )
];
```

```

for k = 1:size(parameters, 1)
    beta = parameters(k, 1);
    gamma = parameters(k, 2);
    S = zeros(1, T+1);
    I = zeros(1, T+1);
    R = zeros(1, T+1);
    S(1) = S0;
    I(1) = I0;
    R(1) = R0;
    % RK4 method
    for t = 1:T
        % Current values
        S_t = S(t); I_t = I(t); R_t = R(t);
        % Define ODEs
        dS = @(S, I) -(beta / N) * S * I;
        dI = @(S, I) (beta / N) * S * I - gamma * I;
        dR = @(I) gamma * I;
        % RK4 coefficients
        k1_S = h * dS(S_t, I_t);
        k1_I = h * dI(S_t, I_t);
        k1_R = h * dR(I_t);
        k2_S = h * dS(S_t + k1_S/2, I_t + k1_I/2);
        k2_I = h * dI(S_t + k1_S/2, I_t + k1_I/2);
        k2_R = h * dR(I_t + k1_I/2);
        k3_S = h * dS(S_t + k2_S/2, I_t + k2_I/2);
        k3_I = h * dI(S_t + k2_S/2, I_t + k2_I/2);
        k3_R = h * dR(I_t + k2_I/2);
        k4_S = h * dS(S_t + k3_S, I_t + k3_I);
        k4_I = h * dI(S_t + k3_S, I_t + k3_I);
        k4_R = h * dR(I_t + k3_I);
        S(t+1) = S_t + (k1_S + 2*k2_S + 2*k3_S + k4_S) / 6;
        I(t+1) = I_t + (k1_I + 2*k2_I + 2*k3_I + k4_I) / 6;
        R(t+1) = R_t + (k1_R + 2*k2_R + 2*k3_R + k4_R) / 6;
    end
end
h2 = 2;
t2 = 0 : h2 : 100;
%%%% This is the second part that is to interpolate the odd values that
%%%% is to be found using the Linear Newton form then using the Quadratic
%%%% Lagrange form
for z = 1 : length(t2) - 1
    SNI(z+1) = S(z) + ((S(z+1) - S(z)) / ((z+1) - (z))) * ((z+1) - (z));
    INI(z+1) = I(z) + ((I(z+1) - I(z)) / ((z+1) - (z))) * ((z+1) - (z));
    RNI(z+1) = R(z) + ((R(z+1) - R(z)) / ((z+1) - (z))) * ((z+1) - (z));
    %%% The Quadratic Lagrange Method Form
    for j = 1 : z
        X_1(j+1) = (((j+1) - (j)) * ((j+1) - (j+3))) / (((j) - (j+1)) * ((j) + (j+3)));
        X_2(j+1) = (((j+1) - (j)) * ((j+1) - (j+3))) / (((j+1) - (j)) * ((j+1) - (j+3)));
    end
end

```

```

        X_3(j+1) = (((j+1) - (j)) * ((j+1) - (j+2))) / (((j+3) - (j)) * ((j+3) -
(j+2)));
        QS(j+1) = (X_1(j) * S(j)) + (X_2(j+1) * S(j+2)) + (X_3(j+1) * S(j+3));
        QI(j+1) = (X_1(j) * I(j)) + (X_2(j+1) * I(j+2)) + (X_3(j+1) * I(j+3));
        QR(j+1) = (X_1(j) * R(j)) + (X_2(j+1) * R(j+2)) + (X_3(j+1) * R(j+3));
    end
end
L2_s = sqrt((S(z+1) - SNI(z+1)/ T));
L2_i = sqrt((I(z+1) - INI(z+1)/ T));
L2_r = sqrt((R(z+1) - RNI(z+1)/ T));
L2_Qs = sqrt((QS(z+1) - SNI(z+1)/ T));
L2_Qi = sqrt((QI(z+1) - INI(z+1)/ T));
L2_Qr = sqrt((QR(z+1) - RNI(z+1)/ T));
%%% The Errors computed from the above formulas in 2x3 matrix print
fprintf('L2 Error Table:\n');

```

L2 Error Table:

```
fprintf('          S(t)          I(t)          R(t)\n');
```

```
          S(t)          I(t)          R(t)
```

```
fprintf('Linear      : %.7f      %.7f      %.7f\n', L2_s, L2_i, L2_r);
```

```
Linear      : 9.0179185      9.3397985      28.6608672
```

```
fprintf('Quadratic : %.7f      %.7f      %.7f\n', L2_Qs, L2_Qi, L2_Qr);
```

```
Quadratic : 7.4066979      7.5802321      23.7518326
```

The values that are more accurate are the Quadratic portion due to the difference in the values being greater compared to the linear value. The linear values error are larger than the quadratic meaning that the quadratic is the one to produce less errors.

```
clear;
```

Question 3: Kyle Swirski

```

% Group Project Part 3: Least-Squares Regression.
% Initial Conditions and Necessary Equations for Step 1.
S(1) = 990;           % Initial susceptible population.
I(1) = 10;            % Initial infected population.
R(1) = 0;             % Initial recovered population.
N = 1000;             % Total population.
B = 0.3;              % Transmission rate.
Y = 0.1;              % Recovery rate.
h = 1;               % Time step.
t = 0:h:30;          % Simulation duration.
dS = @(S,I)(-B*S*I/N); % Given ODE for S(t).
dI = @(S,I)((B*S*I/N)-(Y*I)); % Given ODE for I(t).
dR = @(I)(Y*I);       % Given ODE for R(t).
% Loop that determines the values of S(t), I(t), and R(t) using the given

```


```
% initial values and the fourth-order Runge-Kutta Method for each day.
```

```
for x = 1:(length(t)-1)
    K1S = dS(S(x),I(x));
    K1I = dI(S(x),I(x));
    K1R = dR(I(x));
    K2S = dS(S(x)+(h/2),I(x)+(K1I*h/2));
    K2I = dI(S(x)+(h/2),I(x)+(K1I*h/2));
    K2R = dR(I(x)+(K1I*h/2));
    K3S = dS(S(x)+(h/2),I(x)+(K2I*h/2));
    K3I = dI(S(x)+(h/2),I(x)+(K2I*h/2));
    K3R = dR(I(x)+(K2I*h/2));
    K4S = dS(S(x)+h,I(x)+(K3I*h));
    K4I = dI(S(x)+h,I(x)+(K3I*h));
    K4R = dR(I(x)+(K3I*h));
    S(x+1) = S(x)+((K1S+(2*K2S)+(2*K3S)+K4S)*h/6);
    I(x+1) = I(x)+((K1I+(2*K2I)+(2*K3I)+K4I)*h/6);
    R(x+1) = R(x)+((K1R+(2*K2R)+(2*K3R)+K4R)*h/6);
```

```
end
```

```
% Plots the values of S(t), I(t), and R(t) determined in the loop above.
```

```
figure(1)
plot(t,S,'b',t,I,'r',t,R,'g')
xlabel('Time (Days)')
ylabel('Population (People)')
title('SIR Model Dynamics')
legend('Susceptible','Infected','Recovered')
```




```
% Initial Conditions and Necessary Equations for Step 2.
```

```

n = length(t);
u = sum(t);
w = sum(t.^2);
lnI = log(I);
y = sum(lnI);
z = sum(t.*lnI);
k = ((n*z)-(u*y))/((n*w)-(u^2));
lnI0 = (y-(k*u))/n;
I0 = exp(lnI0);
B1 = ((k+Y)*N)/S(1);
% Plots the analytical solution,  $I(t) = I(0)e^{kt}$ , over 30 days.
figure(2)
plot(t,lnI,'r',t,lnI0+(k*t),'b')
xlabel('Time (Days)')
ylabel('ln(I(t))')
title('Least Squares Fit for ln(I(t)) over 30 Days')
legend('Data ln(I(t))','Linear Fit')

```



```

% Displays the estimated values for  $I(0)$ ,  $k$ , and beta over 30 days.
disp("Requested information for Step 2.")

```

Requested information for Step 2.

```

disp("Estimated  $I(0)$  over 30 Days: " + I0)

```

Estimated $I(0)$ over 30 Days: 16.6724

```

disp("Estimated  $k$  over 30 Days: " + k)


```


Estimated k over 30 Days: 0.12012

```
disp("Estimated beta over 30 Days: " + B1)
```

Estimated beta over 30 Days: 0.22235

```
% Initial Conditions and Necessary Equations for Step 3.
d = t(1:11);
m = length(d);
b = sum(d);
c = sum(d.^2);
J = I(1:11);
lnJ = log(J);
e = sum(lnJ);
f = sum(d.*lnJ);
l = ((m*f)-(b*e))/((m*c)-(b^2));
lnJ0 = (e-(l*b))/m;
J0 = exp(lnJ0);
B2 = ((1+Y)*N)/S(1);
% Plots the analytical solution,  $I(t) = I(0)e^{kt}$ , over 10 days.
figure(3)
plot(d,lnJ,'r',d,lnJ0+(l*d),'b')
xlabel('Time (Days)')
ylabel('ln(I(t))')
title('Least Squares Fit for ln(I(t)) over 10 Days')
legend('Data ln(I(t))','Linear Fit')
```



```
% Displays the estimated values of I(0), k, and beta over 10 days.
disp("Requested information for Step 3.")
```

Requested information for Step 3.

```
disp("Estimated I(0) over 10 Days: " + J0)
```

Estimated I(0) over 10 Days: 10.1468

```
disp("Estimated k over 10 Days: " + l)
```

Estimated k over 10 Days: 0.1896

```
disp("Estimated beta over 10 Days: " + B2)
```

Estimated beta over 10 Days: 0.29252

As can be seen from the graphs of $\ln I(t)$ and the estimated values of $I(0)$, k , and β , reducing the number of days to 10 results in a significant increase in the accuracy of said values. By using fewer sets of data, the model becomes more linear, meaning a line can be fit to the data much more accurately compared to using more data points. Hence the values of $I(t)$, k , and β being much more accurate with 10 days of data instead of the full 30 days of data.

```
clear;
```

Question 4: Ryan Smith

```
Q4_flag(1) = 1; Q1;
% This runs the script for Q1 without importing any of the plots made in
% the script.
```

```
% New Parameters
```

```
B0 = 0.3; % Initial transmission rate
A = 5; % Amplitude
w = (2*pi*365) / 365; % Angular frequency
```

```
% Edited Parameters
```

```
T = 30; % Total simulation time (days)
h = 0.1; % Time step (days)
t_vec = linspace(0,30,30/h+1); % Time vector for easier plotting
```

```
B = @(t) B0*(1 + A*sin(w*t)); % Transmission rate variation
gamma = 0.1; % New gamma value
```

```
% SIR model with  $\beta(t)$ 
```

```
% RK4 method
```

```
for t = 1:300
    % Current values
    S_t = S(t); I_t = I(t); R_t = R(t);
    beta = B(t/10);
```

```

% Define ODEs
dS = @(S, I) -(beta / N) * S * I;
dI = @(S, I) (beta / N) * S * I - gamma * I;
dR = @(I) gamma * I;

% RK4 coefficients
k1_S = h * dS(S_t, I_t);
k1_I = h * dI(S_t, I_t);
k1_R = h * dR(I_t);


k2_S = h * dS(S_t + k1_S/2, I_t + k1_I/2);
k2_I = h * dI(S_t + k1_S/2, I_t + k1_I/2);
k2_R = h * dR(I_t + k1_I/2);

k3_S = h * dS(S_t + k2_S/2, I_t + k2_I/2);
k3_I = h * dI(S_t + k2_S/2, I_t + k2_I/2);
k3_R = h * dR(I_t + k2_I/2);

k4_S = h * dS(S_t + k3_S, I_t + k3_I);
k4_I = h * dI(S_t + k3_S, I_t + k3_I);
k4_R = h * dR(I_t + k3_I);


S(t+1) = S_t + (k1_S + 2*k2_S + 2*k3_S + k4_S) / 6;
I(t+1) = I_t + (k1_I + 2*k2_I + 2*k3_I + k4_I) / 6;
R(t+1) = R_t + (k1_R + 2*k2_R + 2*k3_R + k4_R) / 6;
end
plot(t_vec, S, t_vec, I, t_vec, R)
xlabel('Time (days)'); ylabel('Population');
legend('Susceptible', 'Infected', 'Recovered');
title('SIR Model: Periodic Variation');

```



The recovery rate doesn't seem to oscillate at all, but the susceptibility and infection rates definitely have some oscillating happening.

```
fft_I = fft(I);
Fs = 1/T;
samples = 300;
f_vec = Fs * (0:(samples/2));
P_I = abs(fft_I/samples);
F_I = P_I(1:samples/2+1);
F_I(2:end-1) = 2 * F_I(2:end-1);
plot(f_vec, F_I)
xlabel('Frequency (Hz)'); ylabel('Amplitude');
title('Infection Spectrum for Periodic Variation');
```



This looks like a logarithmic graph with a blip at 1 Hz. This makes sense.

```
% Edited parameters
w = (2*pi*100) / 365;          % Angular frequency
B = @(t) B0*(1 + A*sin(w*t)); % Transmission rate variation

% RK4 method
for t = 1:300
    % Current values
    S_t = S(t); I_t = I(t); R_t = R(t);
    beta = B(t/10);

    % Define ODEs
    dS = @(S, I) -(beta / N) * S * I;
    dI = @(S, I) (beta / N) * S * I - gamma * I;
    dR = @(I) gamma * I;

    % RK4 coefficients
    k1_S = h * dS(S_t, I_t);
    k1_I = h * dI(S_t, I_t);
    k1_R = h * dR(I_t);

    k2_S = h * dS(S_t + k1_S/2, I_t + k1_I/2);
    k2_I = h * dI(S_t + k1_S/2, I_t + k1_I/2);
    k2_R = h * dR(I_t + k1_I/2);
```


```

k3_S = h * dS(S_t + k2_S/2, I_t + k2_I/2);
k3_I = h * dI(S_t + k2_S/2, I_t + k2_I/2);
k3_R = h * dR(I_t + k2_I/2);

k4_S = h * dS(S_t + k3_S, I_t + k3_I);
k4_I = h * dI(S_t + k3_S, I_t + k3_I);
k4_R = h * dR(I_t + k3_I);

S(t+1) = S_t + (k1_S + 2*k2_S + 2*k3_S + k4_S) / 6;
I(t+1) = I_t + (k1_I + 2*k2_I + 2*k3_I + k4_I) / 6;
R(t+1) = R_t + (k1_R + 2*k2_R + 2*k3_R + k4_R) / 6;
end
plot(t_vec, S, t_vec, I, t_vec, R)
xlabel('Time (days)'); ylabel('Population');
legend('Susceptible', 'Infected', 'Recovered');
title('SIR Model: Periodic Variation');

```




```

fft_I = fft(I);
Fs = 1/T;
samples = 300;
f_vec = Fs * (0:(samples/2));
P_I = abs(fft_I/samples);
F_I = P_I(1:samples/2+1);
F_I(2:end-1) = 2 * F_I(2:end-1);
plot(f_vec, F_I)
xlabel('Frequency (Hz)'); ylabel('Amplitude');

```

```
title('Infection Spectrum for Periodic Variation');
```



The peak frequency shift to smaller values, but there are now two possible max frequency peaks. This definitely matches what happened to the SIR graph as the wavelengths increased a lot, which does inversely impact frequency, so it makes sense that the peak frequency would decrease. Also, all of the graphs in the SIR now have minor oscillations.

GitHub Stuff

Link: <https://github.com/GenericNR/MAE384-Project/tree/main>

MAE384-Project

Public

Pin

Unwatch2

Fork0

Star0

main

Go to file

Code

About

GenericNR

Add files via upload

27e7f4f · now

47 Commits

CompleteQuestion1.pdf	Add files via upload	3 days ago
CompleteQuestion2.pdf	Add files via upload	5 minutes ago
CompleteQuestion3.pdf	Add files via upload	yesterday
CompleteQuestion4.pdf	Update files	yesterday
Complete_Project.mlx	Add files via upload	now
Complete_Project.pdf	Add files via upload	now
Project.pdf	Add files via upload	5 days ago
Q1.m	Fix Q1.m	5 days ago
Q1.mlx	Add files via upload	3 days ago
Q2.m	Add files via upload	16 minutes ago
Q2.mlx	Update file	6 minutes ago
Q3.m	Add files via upload	yesterday
Q3.mlx	Add files via upload	yesterday
Q4.m	Update Q4.m	yesterday
Q4.mlx	Update files	yesterday
README.md	Update README.md	1 minute ago

README

MAE384-Project

This is a group project done in MATLAB for MAE 384.

We are the creatively named "Team Placeholder"

The guidelines for the project are in Project.pdf

Question 1: Jaxen White

Question 2: Cyal Sam

Question 3: Kyle Swirski

Question 4: Ryan Smith

All of our combined work is in the Complete_Project PDF and MLX files.

This is a group project

Readme

Activity

0 stars

2 watching

0 forks

Releases

No releases published

Create a new release

Packages

No packages published

Publish your first package

Contributors4

GenericNR

Cwsam252

Jwhite2896

KyleSwirski

Languages

MATLAB100.0%

16

Contributors Preview [Give feedback](#)


Period: All

Contributions: Commits

Contributions per week to main, excluding merge commits

Commits over time


Weekly from Nov 9, 2024 to Nov 30, 2024



GenericNR

#1


38 commits 181 ++ 38 --



Cwsam252

#2


3 commits 77 ++ 1 --



Jwhite2896

#3


2 commits 69 ++ 1 --



KyleSwirski

#4

2 commits 88 ++ 1 --



Ryan Smith was the group leader, hence why he has by far the most commits.