



#### Processor

Quad-core ARM® Cortex® A53 processor with a maximum frequency of 1.2GHz per core supporting 32 and 64bit computing

#### Excellent graphics processing power

HD video 720p@60fps  
HD video 1080p@30fps

#### Wide range of application scenarios

Applications in the communications, smart home, smart healthcare, Internet of Things (IoT) applications

#### Support system diversification

Android, Linux, Windows 10 IoT core

#### Graphics

Adreno™ 306 400MHz 3D graphics accelerator, PC-level graphics processing power

#### Camera

Support 13MP camera, support wavelet denoising, JPEG decoding and other hardware-level post-processing techniques.

#### Compatibility

Compatible with Mezzanine Board interface standard.  
Multiple Mezzanine boards (optional)

#### eMMC Storage

Reliable Write and Data Reliability parameter settings ensure existing data are not corrupted when a sudden power loss event occurs.



## Product Specification

CPU	Snapdragon 410C, Quad core
GPU	Qualcomm® Adreno™ 306
CPU Frequency	1.2GHz
Internal Memory	1GB/2GB LPDDR3 533MHz
Internal Storage	8GB/16GB eMMC 5.0
OS	Android 6.0, Linux based on Debian, Windows 10 IoT core
Bluetooth	4.1
Built-in WiFi	WLAN 802.11 b/g/n/ac 2.4GHz/5.0GHz
WiFi Frequency Range	2.400~2.497GHz, 5.725 ~ 5.825 GHz
Ethernet port	RJ45 10/1000Mbps
GPS	Yes
USB Interface	2x USB 2.0 type A (host mode only), 1x USB 2.0 micro B (device mode only, support OTG)
Micro SD Card Slot	1
Display	HDMI 1.3 – HDMI full-size type A connector (1080p HD @ 30 fps), 1x MIPI-DSI 4-lane, up to 720p 30fps or 1080p 30fps for optional display/touch
Expansion connector	1x Mezzanine boards 40 pin Low-Speed connector • UART, SPI, I2S, I2C x2, GPIO x12, DC power 1x Mezzanine boards 60 pin -Speed connector High • 4L-MIPI DSI, USB, I2C x2, 2L+4L-MIPI CSI Footprint for one optional 16-pin Analog expansion connector • Headset, Speaker, FM antenna
Size (mm)	85 * 60*12mm
Operating Temp	-25°C to +85°C
Power	DC:+6.5V to +18V