



Star 23,446

Dash Python > **Dash Enterprise Auth**

Plotly Studio: Transform any dataset into an interactive data application in minutes with AI. [Sign up for early access now.](#)

Dash Enterprise Auth

This documentation is for **Dash Enterprise**. Dash Enterprise is the fastest way to write & deploy Dash apps and Jupyter notebooks. 10% of the Fortune 500 uses Dash Enterprise to productionize AI and data science apps. [Find out if your company is using Dash Enterprise](#)

Dash Enterprise automatically implements user authentication if your **Dash app's viewer access level** is set to *Restricted* or *Authenticated*, but not if it is set to *Unauthenticated*. You can access the authentication data within your app using the `dash-enterprise-auth` package.

Using dash-enterprise-auth in an Existing Dash App

Dash Enterprise >=5.2

Dash Enterprise <5.2

If you have previously deployed your Dash app to Dash Enterprise, add `dash-enterprise-libraries` to your `requirements.txt` file to get started.

Note: `dash-enterprise-auth` is available from [PyPI.org](#), unlike the other dependencies of `dash-enterprise-libraries` which are installed from the Dash Enterprise host. In order for your `dash-enterprise-auth`-enabled app to successfully build, Dash Enterprise needs network access to PyPI.org or a private Python package index containing `dash-enterprise-auth`. [Learn more about using a private Python index.](#)

Known issue: If using `dash-enterprise-auth` with a Dash Enterprise instance <=5.4.0 that uses a certificate whose root CA is internal to your organization, you may see an error similar to `certificate verify failed: self-signed certificate in certificate chain`. To resolve this error, [set an app environment variable](#) with name `REQUESTS_CA_BUNDLE` and value `/etc/ssl/certs/ca-certificates.crt`. This issue is fixed in Dash Enterprise 5.5.0.

Dash Enterprise 5 requires `dash-enterprise-auth` 0.0.6 or later.

With `dash-enterprise-auth`, you can use the `get_username` and `get_user_data` methods to get information about the app viewer. These methods must be called from within callbacks.

`dash-enterprise-auth` also includes the `create_logout_button` method, which allows you to add a logout button to your app's layout. This button uses a special URL to log the user out. To use `create_logout_button` when developing locally, you need to set an environment variable called `DASH_LOGOUT_URL`. You can do this by running your code with `DASH_LOGOUT_URL=https://auth-<your-dash-enterprise-server>/auth/realms/dash/protocol/openid-connect/logout?client_id=dash-backend python app.py`. If you're developing in Workspaces, `DASH_LOGOUT_URL` is supplied automatically.

The example below demonstrates how to use `get_username`, `get_user_data`, and `create_logout_button`.

```
from dash import Dash, dcc, html, Input, Output, callback
import dash_enterprise_auth as auth
```



```
external_stylesheets = ['https://codepen.io/chriddyp/pen/bWLwgP.css']

app = Dash(__name__, external_stylesheets=external_stylesheets)

server = app.server # Expose the server variable for deployments

# Standard Dash app code below
app.layout = html.Div(className='container', children=[

    html.Div([
        html.H2('Sample App', id='header-title', className='ten columns'),
        html.Div(auth.create_logout_button(), className='two columns', style={'marginTop': 30})
    ]),
    html.Div(id='dummy-input', style={'display': 'none'}),

    html.Div([
        html.Div(
            className='four columns',
            children=[
                dcc.Dropdown(['LA', 'NYC', 'MTL'], 'LA', id='dropdown')
            ]),
        html.Div(
            className='eight columns',
            children=[
                dcc.Graph(id='graph')
            ]
        )
    ])
])

@callback(Output('header-title', 'children'),
          Input('dummy-input', 'children'))
def update_title(_):

    # print user data to the logs
    print(auth.get_user_data())

    # update header with username
    return 'Hello {}'.format(auth.get_username())

@callback(Output('graph', 'figure'),
          Input('dropdown', 'value'))
def update_graph(value):
    return {
        'data': [{
            'city': 'LA', 'count': 1},
            {'city': 'NYC', 'count': 2},
            {'city': 'MTL', 'count': 3},
            {'city': 'LA', 'count': 4},
            {'city': 'NYC', 'count': 5},
            {'city': 'MTL', 'count': 6}]
    }
```

Dash Python > Dash Enterprise Auth

Products

Dash
Consulting and Training

Pricing

Enterprise Pricing

About Us

Careers
Resources
Blog

Support

Community Support
Graphing Documentation

Join our mailing

list
Sign up to stay in the loop with all things Plotly — from Dash Club to product updates, webinars, and more!

SUBSCRIBE