






Dash Python > Dash Player

Plotly Studio: Transform any dataset into an interactive data application in minutes with Al. **Sign up for early access now.**



Dash Player is a Dash component for playing audio and video content. It can use files in your app as well as URLs from YouTube, Facebook, Twitch, SoundCloud, Streamable, Vimeo, Wistia, Mixcloud, and DailyMotion. Dash Player is wrapped around the **react-player component**.

Dash Player exposes the various controls and properties of React Player as Dash component properties, which you can modify via callback functions. This not only allows you to add video playback capabilities to your Dash app, but also enable interactivity with the video player using other Dash components.

Quickstart

```
pip install dash-player
```

Import Dash Player with:

```
import dash_player as dp
```

Example

Note:

- The checklist component interacts with the playing and muted properties, allowing you to toggle them on and off.
- Entering a number in the dcc.Input component and pressing the "seekTo" button allows you to interact with the seekTo property seek to a given point in the video, specified in seconds.
- The currentTime, secondsLoaded, and duration properties are displayed in their respective divs via callback.
- The dcc.Slider components to the right control the volume, playbackRate, intervalCurrentTime, intervalSecondsLoaded, and intervalDuration properties of the dash-player.



```
height="250px",
                           html.Div(
                                        style={"width": "105px"},
       Plotly's Dash: Putting AI & ML in the h...
Playing Loop 🗸 Controls
                                Muted
                                                      Update Interval for Current Time:
Current Time: 0
                                                      Update Interval for Seconds Loaded:
Second Loaded: 0
                                                      Update Interval for Duration:
```

Changes to Dash Player were sponsored by Volkswagen's Center of Excellence for Battery Systems.





DashPlayer Properties

Access this documentation in your Python terminal with:

>>> help(dash_player.DashPlayer)

Our recommended IDE for writing Dash apps is Dash Enterprise's **Data Science Workspaces**, which has typeahead support for Dash Component Properties. **Find out if your company is using Dash Enterprise**.

id (string; optional): The ID used to identify this component in Dash callbacks.

className (string; optional): Used to identify the CSS class of the Dash Player component.

url (string; optional): The url of the media to be played.

playing (boolean; default [False]): Whether or not the media is currently playing. Can be set to True or False to play and pause the media, respectively.

loop (boolean; default False): Whether or not the media will loop once the player reaches the end. Can be set to True or False to set looping on or off, respectively.

controls (boolean; default False): Set to True or False to display native player controls Vimeo, Twitch and Wistia player will always display controls.

volume (*number*; optional): A number between 0 and 1 representing the volume of the player. If set to None, Dash Player ises default volume on all players.

muted (boolean; default False): Set to True or False to mute or unmute player volume, respectively. Only works if volume is set.

playbackRate (*number*; default 1): Set the playback rate of the player Only supported by YouTube, Wistia, and file paths.

width (string; default '640px'): A number or string representing the pixel width of the player.

height (string; default '360px'): A number or string representing the pixel height of the player.

style (*dict*; optional): Optional additional CSS styles. If width or height are supplied within style, then this will override the component-level width or height.

playsinline (boolean; default False): Applies the html5 playsinline attribute where supported, which allows videos to be played inline and will not automatically enter fullscreen mode when playback begins (for iOS).

currentTime (*number*; optional): Returns the number of seconds that have been played.

secondsLoaded (number; optional): Returns the number of seconds that have been loaded.

duration (number; optional): Returns the duration (in seconds) of the currently playing media.

intervalCurrentTime (number; default 100): Interval in milliseconds at which currentTime prop is updated.

intervalSecondsLoaded (number; default 500): Interval in milliseconds at which secondsLoaded prop is updated

intervalDuration (number; default 500): Interval in milliseconds at which duration prop is updated.

seekTo (number; optional): Seek to the given number of seconds, or fraction if amount is between 0 and 1.

Dash Python > Dash Player

| Products | Pricing | About Us | Support | Join our mailing | |
|-------------------------------|--------------------|----------------------|---|------------------|------------------|
| Dash Consulting and Training | Enterprise Pricing | Careers Resources | Community Support Graphing Documentation | list | (*) |
| | | Blog | | | |

Sign up to stay in the loop with all things Plotly — from Dash Club to product updates, webinars, and more!

SUBSCRIBE

Copyright © 2025 Plotly. All rights reserved.

Terms of Service Privacy Policy